

RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
**Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada**
800 Burrard Street, 12th floor
800,rue Burrard, 12e étage
Vancouver
British Columbia
V6Z 2V8
Bid Fax: (604) 775-9381

SOLICITATION AMENDMENT
MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
**Raison sociale et adresse du
fournisseur/de l'entrepreneur**

Issuing Office - Bureau de distribution
Public Works and Government Services Canada -
Pacific Region
800 Burrard Street, 12th floor
800, rue Burrard, 12e étage
Vancouver
British C
V6Z 2V8

Title - Sujet Refit X-Ray Equipment Room	
Solicitation No. - N° de l'invitation EZ899-122746/A	Amendment No. - N° modif. 001
Client Reference No. - N° de référence du client	Date 2012-03-26
GETS Reference No. - N° de référence de SEAG PW-\$PWY-004-6642	
File No. - N° de dossier PWY-1-34475 (004)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2012-03-29	Time Zone Fuseau horaire Pacific Daylight Saving Time PDT
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Mestry, Ruth (PWY)	Buyer Id - Id de l'acheteur pwy004
Telephone No. - N° de téléphone (604) 775-9385 ()	FAX No. - N° de FAX (604) 775-6633
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: CSC - Healthcare Building, Kent Institution, Agassiz, B.C.	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Solicitation No. - N° de l'invitation

EZ899-122746/A

Client Ref. No. - N° de réf. du client

Amd. No. - N° de la modif.

001

File No. - N° du dossier

PWY-1-34475

Buyer ID - Id de l'acheteur

pw004

CCC No./N° CCC - FMS No/ N° VME

Attached is Addendum No. 1.

The following changes in the tender documents are effective immediately. This addendum will form part of the contract documents.

SPECIFICATIONS

.1 09 65 16 RESILIENT SHEET FLOORING

Paragraph 2.1.1:

(1) **Change:** paragraph 2.1.1 and Subparagraphs .1 to .9 to read as follows:

- .1 Resilient Flooring: 2 mm thickness homogeneous single layered vinyl floor covering to meet performance standards of ASTM F1913-04(2010) Standard Specification for Vinyl Sheet Floor Covering Without Backing and the following:
 - .1 Class 1 Reaction to Fire to ASTM E648-10e1 Standard Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source.
 - .2 Smoke density of less than 450 when tested to ASTM E662- 09 Standard Test Method for Specific Optical Density of Smoke Generated by Solid Materials.
 - .3 Static coefficient of friction minimum 0.6 rating to ASTM D2047- 11 Standard Test Method for Static Coefficient of Friction of Polish-Coated Flooring Surfaces as Measured by the James Machine.
 - .4 Static load limit of minimum 750 psi to ASTM F970- 07(2011) Standard Test Method for Static Load Limit, and residual indentation of approximately 0.03 mm to EN 433.
 - .5 Polyurethane surface treatment.
 - .6 Marbleized or terrazzo appearance.
 - .7 Adhesives to manufacturer's recommendation for substrate and use intended.
 - .8 Heat weld seams with matching vinyl rod.
 - .9 Apply flooring in strict accordance with manufacturer's instructions.

DRAWINGS N/A

END OF ADDENDUM No 1
