

- ◆ RELOCATE TO DRAWING E10 FOR DISCONNECTION AND RELOCATION OF EXISTING GENSET AND ENCLOSURE AT 875 HERON ROAD.
- ◆ CONNECT FEEDER FROM EXISTING PANEL BP-2 INSTALLED IN STAGE 5 TO RELOCATED EQUIPMENT FROM 875 HERON ROAD: 60A DISCONNECT, 45KVA TRANSFORMER AND 45KVA GENSET. FEED FROM PANEL BP-2 INSIDE THE BUILDING AS INDICATED. CONNECT PANEL P-1 FROM EXISTING PANEL PPI.
- ◆ MOUNT AND SECURE GENERATOR G2 ON CONCRETE PAD PROVIDE ALL NECESSARY WIRING TO CONNECT THE GENERATOR TO EXISTING SYSTEMS:
 - EMERGENCY GENERATOR POWER
 - GENERATOR CONTROL
 - GENERATOR BATTERY CHARGER
 - BLACK HEATER
 - FIRE ALARM SYSTEM
 - LIGHTING AND RECEPTACLES
- ◆ UPON COMPLETION OF G2 INSTALLATION, DISCONNECT AND REMOVE TEMPORARY MOBILE GENERATOR

F14 of 15