

PART 1 - GENERAL

- 1.1 REFERENCES .1 Canadian General Standards Board (CGSB)
.1 CGSB 1.59-97, Alkyd Exterior Gloss Enamel.
.2 CAN/CGSB 1.189-00, Exterior Alkyd Primer for Wood.
- .2 Canadian Standards Association (CSA International)
.1 CSA-O121-M1978(R2003), Douglas Fir Plywood.
- .3 Public Works Government Services Canada (PWGSC) Standard Acquisition Clauses and Conditions (SACC)-ID: R0202D, Title: General Conditions 'C', In Effect as Of: May 14, 2004.
- 1.2 INSTALLATION AND REMOVAL .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.
- 1.3 GUARD RAILS AND BARRICADES .1 Provide secure, rigid guard rails and barricades around deep excavations, open shafts, open stair wells, open edges of floors and roofs.
- .2 Provide as required by governing authorities as indicated.
- 1.4 WEATHER ENCLOSURES .1 Provide weather tight closures to unfinished door and window openings, tops of shafts and other openings in floors and roofs.
- .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work for temporary heat.
- .3 Design enclosures to withstand wind pressure and snow loading.
- 1.5 DUST TIGHT SCREENS .1 Provide dust tight screens or insulated partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.

- | | | |
|--|----|---|
| <u>1.5 DUST TIGHT
SCREENS
(Cont'd)</u> | .2 | Maintain and relocate protection until such work is complete. |
|
 | | |
| <u>1.6 ACCESS TO SITE</u> | .1 | Provide and maintain access roads, sidewalk crossings, ramps and construction runways as may be required for access to Work. |
|
 | | |
| <u>1.7 PUBLIC TRAFFIC
FLOW</u> | .1 | Provide and maintain competent signal flag operators, traffic signals, barricades and flares, lights, or lanterns as required to perform Work and protect public. |
|
 | | |
| <u>1.8 FIRE ROUTES</u> | .1 | Maintain access to property including overhead clearances for use by emergency response vehicles. |
|
 | | |
| <u>1.9 PROTECTION FOR
OFF-SITE AND PUBLIC
PROPERTY</u> | .1 | Protect surrounding private and public property from damage during performance of Work. |
| | .2 | Be responsible for damage incurred. |
|
 | | |
| <u>1.10 PROTECTION OF
BUILDING FINISHES</u> | .1 | Provide protection for finished and partially finished building finishes and equipment during performance of Work. |
| | .2 | Provide necessary screens, covers, and hoardings. |
| | .3 | Confirm with Departmental Representative locations and installation schedule 3 days prior to installation. |
| | .4 | Be responsible for damage incurred due to lack of or improper protection. |
-

PART 2 - PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED .1 Not Used.