

PART 1 - GENERAL

- 1.1 SUBMITTALS
- .1 Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
  - .2 Submit written request in advance of cutting or alteration which affects:
    - .1 Structural integrity of elements of project.
    - .2 Integrity of weather-exposed or moisture-resistant elements.
    - .3 Efficiency, maintenance, or safety of operational elements.
    - .4 Visual qualities of sight-exposed elements.
    - .5 Work of Departmental Representative or separate contractor.
  - .3 Include in request:
    - .1 Identification of project.
    - .2 Location and description of affected Work.
    - .3 Statement on necessity for cutting or alteration.
    - .4 Description of proposed Work, and products to be used.
    - .5 Alternatives to cutting and patching.
    - .6 Effect on Work of Departmental Representative or separate contractor.
    - .7 Written permission of affected separate contractor.
    - .8 Date and time work will be executed.
- 1.2 MATERIALS
- .1 Required for original installation.
  - .2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.
- 1.3 PREPARATION
- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
  - .2 After uncovering, inspect conditions affecting performance of Work.
  - .3 Beginning of cutting or patching means acceptance of existing conditions.
  - .4 Provide supports to assure structural integrity of surroundings; provide devices and

1.3 PREPARATION  
(Cont'd)

- .4 (Cont'd)  
methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.

1.4 EXECUTION

- .1 Execute cutting, fitting, and patching to complete Work.
- .2 Fit several parts together, to integrate with other Work.
- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .9 Restore work with new products in accordance with requirements of Contract Documents.
- .10 Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .11 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with firestopping material full thickness of the construction element.
- .12 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.

1.4 EXECUTION  
(Cont'd)

- .13 Conceal pipes, ducts and wiring in floor,  
wall and ceiling construction of finished  
areas except where indicated otherwise.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.