



FLOOR PLAN LEVEL 1

SCALE: 1:100

0m 1m 2m 3m 4m 5m 6m 7m 8m 9m 10m

LIGHTING LEGEND	
	CEILING MOUNTED POT LIGHT OR WALL MOUNTED LIGHT FIXTURE. SEE FIXTURE SCHEDULE.
	CEILING MOUNTED FLUORESCENT LIGHT FIXTURE. SEE FIXTURE SCHEDULE.
	COVE LIGHTING. SEE FIXTURE SCHEDULE.
	LIGHT FIXTURES AS ABOVE. TO BE ON NIGHT CIRCUIT.
	CEILING OR WALL MOUNTED EXIT SIGN.
	EMERGENCY LIGHTING BATTERY UNIT WITH TWO HEADS.
	SINGLE POLE TOGGLE SWITCH WITH ONE, TWO, OR THREE GANG COVER PLATE.
	WALL OR CEILING MOUNTED EMERGENCY LIGHTING REMOTE FIXTURES. NUMBER OF HEADS AS INDICATED ON DRAWINGS.
	"M" DENOTES MOTION SENSOR. LUTRON LOS-WOT.
	"D" DENOTES DIMMING CAPABILITIES.
	"C" DENOTES LIGHTING SCENE CONTROLLERS. ZONE AS INDICATED WITHIN ROOM.
	SWITCHES AS ABOVE. SUBSCRIPT DENOTES 2 POLES, 2-WAY, 3-WAY, OR 4-WAY.
	CEILING MOUNTED MOTION ACTIVATED LIGHT SWITCH.
	"O" DENOTES OCCUPANCY SENSOR. LUTRON LOS-COT-2000. PROVIDE ALL POWER PACKS AS REQUIRED.
	"O" DENOTES OCCUPANCY SENSOR LUTRON LOS-COT-500. ARROW DENOTES CENTER FIELD OF VIEW.
	CIRCUIT #1 IN PANEL 'A'. 'R' DENOTES FIXTURE TO BE CONTROLLED BY LUTRON RELAY PANEL.

FIXTURE SCHEDULE					
FIXTURE	MANUFACTURER	MANUFACTURER	MANUFACTURER	DESCRIPTION	LAMP
A	CORELITE PWP-215-10-120V-AC48	LEDALITE 7705-H02-L-1-1	METALUMEN C75-BAU-AAW6A	4" ARCHITECTURAL SEMI-INDIRECT SUSPENDED FLUORESCENT LUMINAIRE. SUSPEND AT 450mm BELOW CEILING USING AIRCRAFT CABLE. 120V RAPID START ELECTRONIC DIMMING BALLAST, LESS THAN 10% THD.	2x54 T5HO
B	CORELITE PWP-115-10-120V-AC48	LEDALITE 7705-H01-L-1-1	METALUMEN C75-AAU-AAW6A	4" ARCHITECTURAL SEMI-INDIRECT SUSPENDED FLUORESCENT LUMINAIRE. SUSPEND AT 450mm BELOW CEILING USING AIRCRAFT CABLE. 120V RAPID START ELECTRONIC BALLAST, LESS THAN 10% THD.	1x54 T5HO
C	METALUX G2B-232A19-120V-ERB1-U	CFI SPS1GFSK232-H1-120	LITHONIA SPB232-A19 MVOLT-GE810PS	1 1/4" RECESSED FLUORESCENT TROFFER SUITABLE FOR T-BAR OR DRYWALL MOUNTING WHERE INDICATED ON DRAWINGS. 120V RAPID START ELECTRONIC BALLAST, LESS THAN 10% THD. C/W K19 PRISMATIC LENS.	2x54 T8
D	LUMENCOVE LCSR120V-XX-40K-CL-XX-WH-DM	PHILIPS COLOR KINETICS 4W COVE MX POWERCORE 523-000050-13	GVA LIGHTING HL-COVE 4000K ND-XXX	LED COVE LIGHTING	46.1W/m LED
E	PORTFOLIO LD150-ERM640-6LM	LIGHTTOWER CBL1500L40K-CCL-W/ CBL15N1-120-0/1000DM	GOTHAM EVO-41/14 6AR-MVOLT	CEILING RECESSED 150mm LED POT LIGHT C/W ELECTRONIC DIMMING BALLAST. 120V OPERATION WITH 1500 LUMENS AT 4000K	28W LED
F	METALUX SSF-232	CFI SBR248-H1-120	LITHONIA C-2-32-MVOLT-GE810PS	COMMERCIAL FLUORESCENT STRIP SURFACE MOUNTED LUMINAIRE. UL/CUL LISTED. SUITABLE FOR DAMP LOCATIONS. 120V RAPID START ELECTRONIC BALLAST, LESS THAN 10% THD.	2x54 T8
G	PORTFOLIO LD130-ERM4 840-4LM111U	LIGHTTOWER C4110W-40K-CCL-W/ C4110N1-12-0/1000DM	GOTHAM EVO-41/14 4AR-MVOLT	CEILING RECESSED 100mm LED WALL WASH POT LIGHT C/W ELECTRONIC DIMMING BALLAST. 120V OPERATION WITH 1300 LUMENS AT 4000K	24.4W LED
H	PORTFOLIO LD4130-ERM4 840-4LM111U	LIGHTTOWER C4110L-40K-CCL-W/ C4110N1-12-0/1000DM	GOTHAM EVO-41/14 4AR-MVOLT	CEILING RECESSED 100mm LED POT LIGHT C/W ELECTRONIC DIMMING BALLAST. 120V OPERATION WITH 1300 LUMENS AT 4000K	24.4W LED
K	MP LIGHTING LS2-2-W41	CALCULITE C2L04-DL30K47R	LITON LHBL0212C35/LR2LH71C	44.5mm WALL WASH POT LIGHT. 120V OPERATION WITH 400 LUMENS AT 3000K	11W LED
L	METALUX VIZ-232	CFI VIZ248	DMW-232	HIGH IMPACT 4" VAPOR TIGHT FLUORESCENT. SURFACE MOUNTED C/W RAPID START ELECTRONIC BALLAST	2x54 T8
M	METALUX PB2L-C2C-AB-W30		BRUCK LIGHTING 222-850-MC-MP	12" TALL, 4" WIDE CABLE SUSPENDED PENDANT LUMINAIRE. 120V OPERATION.	6W LED
				EXIT LIGHT TO MATCH TYPE INSTALLED ON 2ND FLOOR RENOVATION PROJECT	LED
	AMITE EBST-247202M02Q0ATD			WALL OR CEILING MOUNTED EMERGENCY BATTERY UNIT. SINGLE OR DUAL HEAD AS INDICATED. MOUNTING AS REQUIRED.	2x20W MR16
	AMITE RMAB-24020			REMOTE FIXTURE FOR USE WITH LITHIUM BATTERY UNIT. SINGLE OR DUAL HEAD AS INDICATED. MOUNTING AS REQUIRED.	20W MR16

Public Works and Government Services Canada

Troux Publics et Services gouvernementaux Canada

Architects

architecture inc.

PROJECT NO. 3134

Phone: (506) 856-8882 Fax: (506) 383-7385
email: aec@aecinc.ca web: aecinc.ca

Key plan

Plan de localisation

Seal

Note

Note

00	ISSUED FOR TENDER	07-17 2013
revisions		date
project		project

**BUILDING MODERNIZATION
PHASE II
10 Weldon Street
Shediac, NB**

drawing	designed
	FLOOR PLAN LEVEL 1 ELECTRICAL LIGHTING

designed	KMR	congru
date	JULY 2013	
drawn	MML	designé
date	JULY 2013	
approved	MAL	approuvé
date	JULY 2013	
client	PMSC Project Manager	Administrateur de projets PMSC
project number	R.039554.001	no. du projet
drawing no.	E-101	no. du dessin

E-004/000-E 384039 Version 1