



Technical drawing of a staircase showing a plan view and a section view. The plan view shows a staircase with a total width of 6300 and a total depth of 7800. The section view shows a staircase with a total width of 6300 and a total depth of 5300. The drawing includes dimensions and labels A through M.

ZONE	DECK SIZE (DEPTH x THICK)	200 PLYING WELD S.P/C	BUTTON PLANCH SPACING	REMARK
	76mm x 0.9mm (200a)	300 O/C	300 O/C	
	76mm x 0.9mm (200a)	300 O/C	450 O/C	

DECK GAUGES ARE NOT REQUIRED FOR IN PLANE DESIGN DUE TO LATERAL LOAD ONLY.
 DECK SUPPORTS SHALL BE INDICATED FOR DECK DESIGN FOR VERT. LOAD DUE TO WIND UPLIFT & GRAVITY LOADS INDICATED IN GEN. NOTES INCREASE DECK THK.
 AND UPLIFT & GRAVITY LOAD REQUIREMENT.

ROOF DIAPHRAGM

- NOTES:
1. DESIGNED, SUPPLIED & INSTALLED BY STEEL FABRICATOR. WHEN STEEL STUD IS USED, REFER TO S102 FOR BEAM BOTTOM PLATE BRACCS
2. STEEL DECK OPENINGS GREATER THAN 150, REFER TO SPECIFICATION FOR FRAMING DETAIL
3. SNOW GUARD - SUPPLIED, DESIGNED & INSTALLED BY SUPPLIER. REFER TO SUPPLIER FOR LOADS. SEE ARCH. FOR LOCATIONS.
4. MINIMUM SEAT HEIGHT FOR OWSL = 125mm

#

✖ ○

✖ ○

BY SUPPLIER,
FOR LOCATION, SEE ARCH.
(COORDINATE WITH OWS, SUPPLIER
FOR LOADS & BRACING DETAILS)

DENOTES OUTRIGGERS FROM COLUMN
FOR SIZES & LOCATIONS

DENOTES DUCT OPENINGS, SEE MECH.

6			
5	100% COMPLETE	2012/03/26	
4	ISSUE FOR COORDINATION	2012/02-17	
3	99% Submission NOT FOR CONSTRUCTION	2011-03-31	
2	DESIGN DEVELOPMENT SUBMISSION	2010/12/17	
1	CONCEPT DESIGN	2010/09/01	
	Development Complete		
Characteristics	Revision	Date/Time	

**POLICE BUILDING
100 MILE HOUSE BC**

ROOF FRAMING PLAN