

RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Bid Receiving - PWGSC / Réception des soumissions -
TPSGC
11 Laurier St. / 11, rue Laurier
Place du Portage, Phase III
Core 0A1 / Noyau 0A1
Gatineau, Québec K1A 0S5
Bid Fax: (819) 997-9776

SOLICITATION AMENDMENT
MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Vehicles & Industrial Products Division
11 Laurier St./11, rue Laurier
7A2, Place du Portage, Phase III
Gatineau, Québec K1A 0S5

Title - Sujet Medium Truck	
Solicitation No. - N° de l'invitation 46533-146110/A	Amendment No. - N° modif. 001
Client Reference No. - N° de référence du client 46533-146110	Date 2013-10-15
GETS Reference No. - N° de référence de SEAG PW-\$\$HP-371-63565	
File No. - N° de dossier hp371.46533-146110	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2013-11-06	Time Zone Fuseau horaire Eastern Standard Time EST
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Modérie, Christine	Buyer Id - Id de l'acheteur hp371
Telephone No. - N° de téléphone (819) 956-3970 ()	FAX No. - N° de FAX (819) 953-2953
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Amendment No. 001 to the solicitation is hereby raised to provide Questions (Q) and Answers (A) received from the Industry and to revise Annex "A" as follows:

Question (Q) and Answer (A) received from the Industry

Q1) On page 1 of the specs you ask for GVWR 21000 LBS, on page two you ask for 21000 lb Payload. Please let me know which one is correct?

A.1 GVWR 21,000 LBS would be correct.

Q.2) Unit states Tandem Rear Axle and then it states Power Brakes. Tandem axles will require Air Brake?

A.2 We do not need a tandem axle. We are ordering a truck in similar size to an F-550 which would require power brakes.

Q.3) There is no specification for front or rear axle weights.

A. 3 This question will be answered by answering questions 1 and 2.

Q.4) There is no specification for the type of suspension

A.4 This question should take care of itself also. Keep in mind we want power brakes with ABS brake system.

Q.5) There is no specification for the exhaust required (ie: vertical stack).

A.5 We do not require vertical stack. Conventional, under the truck, exhaust is fine.

All other terms and conditions remain unchanged.

ANNEX “A” – SPECIFICATIONS

PROPOSALS WILL BE EVALUATED IN ACCORDANCE WITH THE MANDATORY EVALUATION CRITERIA DETAILED BELOW.

2013 or Newer Medium Truck with Box and Lift Gate.

MANDATORY REQUIREMENTS FOR THE TRUCK

BIDDERS ARE TO SPECIFY
THEIR CONFORMANCE
TO THE SPECIFICATIONS.
DESCRIBE THE DEVIATIONS:

YES

NO

Mandatory Specifications

- | | | |
|--|-------|-------|
| 1. Medium Truck | _____ | _____ |
| 2. Conventional Cab and Chassis, 16' Box and Lift Gate Provided and Installed | _____ | _____ |
| 3. GVWR of 21,000 lbs. minimum | _____ | _____ |
| 4. Cab to axle dimension to accommodate an aluminum box of 16'. Should provide optimum axle loading. | _____ | _____ |
| 5. Cab-to-End of Frame dimension – to accommodate length of body | _____ | _____ |
| 6. 362 HP - minimum | _____ | _____ |
| 7. Automatic Transmission | _____ | _____ |
| 8. Air conditioning | _____ | _____ |
| 9. Power Brakes | _____ | _____ |
| 10. Two West Coast Type Heated Mirrors of approximately 150 x 400 mm (6 x 16 in) mounted on 5 arms - minimum | _____ | _____ |
| 11. Front Seating must have seating for 3 people | _____ | _____ |
| 12. Intermittent Wipers | _____ | _____ |

MANDATORY REQUIREMENTS FOR THE TRUCK CONTINUE

	<u>YES</u>	<u>NO</u>
13. Step Rails (or equivalent) on Cab	_____	_____
14. Color: White	_____	_____
15. Type of Terrain: Flat and Hilly	_____	_____
16. Full Size Spare Tire on Rim	_____	_____
17. Alternator and Battery – Heavy duty, maximum capacity available for options required on model specified	_____	_____
18. Block Heater – Standard single element, 115 V, 400 W minimum	_____	_____
19. Cooling System operating range from -37°C to +37°C	_____	_____
20. Power Windows and Door Locks	_____	_____
21. Gauges for voltmeter, temperature and oil pressure	_____	_____
22. Performance. The power Train must provide a geared top speed of at least 105 Km/h. (Performance is to be in accordance with SAE J688 procedures. The driveline must provide a minimum grade ability of 0.50% at 90 km/h and a minimum grade ability of 30% at peak torque in first gear using full GVWR at sea level.)	_____	_____
23. Basic Manufacturer AM/FM Radio	_____	_____
24. Safety Features must meet the provisions of the Canada Motor Vehicle Safety Act and the Regulations made There under which are in effect on the date of manufacture.	_____	_____
26. Standard Exhaust		

MANDATORY REQUIREMENTS FOR THE BOX**YES****NO**

- | | | |
|--|-------|-------|
| 1. Heavy Duty Aluminum box as per following dimensions:
Length: 16' (ft)
Width: 95 1/2" (in)
Height: 95" (in) | _____ | _____ |
| 2. Box floor must be compatible to height of dock at 53" | _____ | _____ |
| 3. Rear roll up door c/w side - seals with
86" (in) high x 86.5" (in) opening – minimum | _____ | _____ |
| 4. Heavy Gauge Satin coated steel rear door frame | _____ | _____ |
| 5. One piece roof with 2" top hat roof bows | _____ | _____ |
| 6. Deep aluminum extrusion bottom rail with built in rub rail | _____ | _____ |
| 7. 13/8" Ship Lap Hardwood Floor on 12" centre | _____ | _____ |
| 8. Recessed 3/16" steel checker plate threshold plate at
rear 48" deep | _____ | _____ |
| 9. 3" structural channel cross members with 5" structural
channel longsills | _____ | _____ |
| 10. 1/2" Plywood Lining on Walls, 3/4" on front wall | _____ | _____ |
| 11. 18" galvanized extruded scuffplate on walls & front | _____ | _____ |
| 12. Two rows on each wall 1806 cargo control 2' and 4' heights | _____ | _____ |
| 13. 3" X 5" x 1/4" front crash angle | _____ | _____ |
| 14. 2 Interior Dome lights with pilot light in cab | _____ | _____ |
| 15. One pair rubber grab handles on door pillars | _____ | _____ |
| 16. All Canada Motor Vehicle Safety Standards (CMVSS)
Body clearance lights and reflectors | _____ | _____ |
| 17. 1 pair splash shields | _____ | _____ |
| 18. Pre-painted white panels .040 ga aluminum | _____ | _____ |
| 19. Underbody "Tectyl" (or equivalent) undercoated | _____ | _____ |

<u>MANDATORY REQUIREMENTS FOR THE LIFT GATE</u>	<u>YES</u>	<u>NO</u>
1. Fold and Stow style – Level Ride	_____	_____
2. Capacity 3000 lbs minimum	_____	_____
3. Aluminum platform: 60” W x 95.5” L minimum * Maximum width must be less than 7 feet Wide since call site pillars are 7 feet apart.	_____	_____
4. Cart stop	_____	_____
5. Steel pump and motor enclosure	_____	_____
6. Heavy-duty dock bumpers	_____	_____
7. Side steps	_____	_____
8. Pump and motor enclosure	_____	_____
9. Dual hydraulics	_____	_____
10. Cab cut off switch	_____	_____
11. Underride	_____	_____