

RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Bid Receiving - PWGSC / Réception des soumissions -
TPSGC
11 Laurier St. / 11, rue Laurier
Place du Portage, Phase III
Core 0A1 / Noyau 0A1
Gatineau, Québec K1A 0S5
Bid Fax: (819) 997-9776

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Vehicles & Industrial Products Division
11 Laurier St./11, rue Laurier
7A2, Place du Portage, Phase III
Gatineau, Québec K1A 0S5

Title - Sujet Trailer, Beavertail		
Solicitation No. - N° de l'invitation W8476-144670/A		Amendment No. - N° modif. 002
Client Reference No. - N° de référence du client W8476-144670		Date 2013-10-30
GETS Reference No. - N° de référence de SEAG PW-\$\$HP-539-63608		
File No. - N° de dossier hp539.W8476-144670	CCC No./N° CCC - FMS No./N° VME	
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2013-11-13		Time Zone Fuseau horaire Eastern Standard Time EST
F.O.B. - F.A.B. Specified Herein - Précisé dans les présentes Plant-Usine: <input type="checkbox"/> Destination: <input type="checkbox"/> Other-Autre: <input checked="" type="checkbox"/>		
Address Enquiries to: - Adresser toutes questions à: Cafferty, Kathy		Buyer Id - Id de l'acheteur hp539
Telephone No. - N° de téléphone (819) 956-5917 ()		FAX No. - N° de FAX () -
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:		

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

1. This Solicitation Amendment 002 is raised to answer questions on this procurement.
2. The following questions have been asked by potential bidders:
 - Q3: In the Purchase description, Page 5 Section 3.5.1 Section C Trailer deck part (iv) - What do you mean by this statement. Is there something specific that you are looking for other than the d rings in the same section(iii)
 - A3: 3.5.1 (c) (iii) refers to deck mounted D-rings, 3.5.1 (c) (iv) are frame mounted tie down points.
 - Q4: Section 3.5.1. Trailer deck, Rear Stabilizer Jack. Need more clarification as to what you are looking for as well as location as when you have a tilting trailer, you don't really have a location to put a rear stabilizer jack.
 - A4: The rear stabilizer jack is to support the trailer during loading of equipment when the tilt is not being used.
 - Q5: Section 3.5.1. Section c - (e) Landing Gear - Ground Clearance. There is no way to accommodate these measurements when you do not want it to go above the bulkhead. Is the 18 inches a mandatory number based on your table on page 2. Our ground clearance is approx 10.5 inches.
 - A5: The 450mm is the required minimum for the trailer ground clearance.

Paragraph 3. REQUIREMENTS, Sub-paragraph 3.5.1(e) of the Purchase Description dated 22 May 2013 is amended as follows:

Delete: **Landing Gear** - Landing gear with a positively locked travel position and a stored ground clearance of at least that given as **“GROUND CLEARANCE”** in the Configuration Capability Table with the capability of lifting a fully loaded trailer at least 200 mm (7.8 in). The top of the landing gear *shall* not be the higher than the top of the forward bulkhead of the trailer deck. Landing gear *shall* be furnished with a spreader plate to allow deployment on soft ground for each pad. The spreader plate *shall* be at least 500 mm (20 inches) square and *shall* be at least 50 mm (2 inches) thick. The load spreader plate *shall*_(E) be made of pressure treated wood and have rope handle. Each spreader plate *shall*_(E) have an individual storage location on the trailer;

Insert: **Landing Gear** - Landing gear with a positively locked travel position and a stored ground clearance of at least that given as **“GROUND**

CLEARANCE” in the Configuration Capability Table with the capability of lifting a fully loaded trailer at least 200 mm (7.8 in). Landing gear *shall* be furnished with a spreader plate to allow deployment on soft ground for each pad. The spreader plate *shall* be at least 500 mm (20 inches) square and *shall* be at least 50 mm (2 inches) thick. The load spreader plate *shall*_(E) be made of pressure treated wood and have rope handle. Each spreader plate *shall*_(E) have an individual storage location on the trailer;

ALL OTHER TERMS AND CONDITIONS OF THIS SOLICITATION REMAIN UNCHANGED.