

1.1 DESCRIPTION OF WORK .1

In general, work under this contract consists of but not limited to:
.1 the removal and replacement of cell doors in Bldg 5, 6 and 7 and all related hardware.

.2 Site of Work is at: Springhill Institution
Mcgee street, Springhill, Nova Scotia.

1.2 FAMILIARIZATION WITH SITE .1

Before submitting a bid, it is recommended that bidders visit the site to review and verify the form, nature and extent of the work, materials needed, the means of access and the temporary facilities required to perform the Work.

.2 Obtain prior permission from the Departmental Representative before carrying out such site inspection. Security clearance required prior to entry to site.

1.3 CODES AND STANDARDS .1

Perform work in accordance with the 2010 National Building Code of Canada and any other code of provincial or local application, including all amendments up to bid closing date, provided that in any case of conflict or discrepancy, the more stringent requirement shall apply.

.2 Materials and workmanship must meet or exceed requirements of specified standards, codes and referenced documents.

1.4 INTERPRETATION OF DOCUMENTS .1

Supplementary to the Order of Precedence article of the General Conditions of the Contract, the Division 01 sections take precedence over the technical specification sections in other Divisions of the Specification Manual.

1.5 TERM ENGINEER .1

Unless specifically stated otherwise, the term Engineer where used in the Specifications and on the Drawings shall mean the Departmental Representative as defined in the General Conditions of the Contract.

- 1.6 SETTING OUT WORK
- .1 Assume full responsibility for and execute complete layout of work to locations, lines and elevations indicated.
 - .2 Provide devices needed to lay out and construct work.
 - .3 Supply such devices as straight edges and templates required to facilitate Departmental Representative's inspection of work.
- 1.7 COST BREAKDOWN
- .1 Before submitting first progress claim submit breakdown of Contract price in detail as directed by Departmental Representative and aggregating contract price. Required forms will be provided for application of progress payment.
 - .2 List items of work numerically following the same division/section number system of the specification manual and thereafter sub-divide into major work components and building systems as directed by Departmental Representative.
 - .3 Upon approval, cost breakdown will be used as basis for progress payment.
- 1.8 DOCUMENTS REQUIRED
- .1 Maintain at job site, one copy each of the following:
 - .1 Contract Drawings
 - .2 Specifications
 - .3 Addenda
 - .4 Reviewed Shop Drawings
 - .5 List of outstanding shop drawings
 - .6 Change Orders
 - .7 Other modifications to Contract
 - .8 Field Test Reports
 - .9 Copy of Approved Work Schedule
 - .10 Health and Safety Plan and other safety related documents
 - .11 Other documents as stipulated elsewhere in the Contract Documents.
-

1.9 PERMITS

- .1 In accordance with the the General Conditions, obtain and pay for building permit, certificates, licenses and other permits as required by municipal, provincial and federal authorities.
- .2 Provide appropriate notifications of project to municipal and provincial inspection authorities.
- .3 Obtain compliance certificates as prescribed by legislative and regulatory provisions of municipal, provincial and federal authorities as applicable to the performance of work.
- .4 Submit to Departmental Representative, copy of application forms and approval documents received from above referenced authorities.

1.10 ALTERATIONS,
ADDITIONS OR
REPAIRS TO EXISTING
BUILDING

- .1 Execute work with least possible interference or disturbance to building operations occupants, and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.
- .2 Where security has been reduced by work of Contract, provide temporary means to maintain security.
- .3 Provide temporary dust screens, barriers, warning signs in locations where renovation and alteration work is adjacent to areas which will be operative during such work.

1.11 ROUGHING-IN

- .1 Be responsible for obtaining manufacturer's literature and for correct roughing-in and hook-up of equipment, fixtures and appliances.

1.12 CUTTING,
FITTING AND
PATCHING

- .1 Ensure that cutting and patching required by all trades is included in total bid price submitted for the work.
- .2 Execute cutting including excavation, fitting and patching required to make work fit properly.

1.14 BILINGUAL
NOTATIONS

- .1 Any items supplied and installed under this contract which have operating instructions on them and which can be expected to be used by the building tenants, must have such operating instructions in bilingual format - English and French.
- .2 Factory embossed or recessed symbols illustrating equipment operation is an acceptable alternate to lettering.
- .3 Items supplied with factory - embossed or recessed lettering in one official language with an applied sticker or decal representing the second official language is not acceptable unless the Departmental Representative gives prior approval before any such items are ordered.
- .4 Internationally recognized colour coding such as red and blue center pieces for plumbing brass is acceptable.
- .5 No extra costs will be paid for re-stocking or re-ordering of materials and equipment due to Contractor's failure to fully meet bilingual signage requirements specified herein.
- .6 Ensure that all trades are made aware of above requirements.

1.15 BUILDING
SMOKING
ENVIRONMENT

- .1 Comply with smoking restrictions. No smoking.

1.1 SUBMITTALS

- .1 Upon acceptance of bid and prior to commencement of work, submit to Departmental Representative the following work management documents:
 - .1 Work Schedule as specified herein.
 - .2 Shop Drawing Submittal Schedule specified in Section 01 33 00.
 - .3 Hot Work Procedures specified in Section 01 35 24.
 - .4 Lockout Procedures specified in Section 01 35 25.
 - .5 Health and Safety Plan specified in Section 01 35 29.
 - .6 Environmental Plan specified in Section 01 35 43.
 - .7 List of workers requiring security clearance and those to be placed on Site Security Control list as specified in Section 01 35 59.
 - .8 Dust Control Plan specified in Section 01 50 00.
 - .9 Waste Management Plan specified in Section 01 74 22.
 - .10 Common Product Requirements specified in Section 01 61 00.

1.2 WORK SCHEDULE

- .1 Upon acceptance of bid submit:
 - .1 Preliminary work schedule within 7 calendar days of contract award.
 - .2 Detailed work schedule within 14 calendar days of contract award.
- .2 Schedule to indicate all calendar dates from commencement to completion of all work within the time stated in the accepted bid.
- .3 Provide sufficient details to clearly illustrate entire implementation plan, depicting efficient coordination of tasks and resources, to achieve completion of work on time and permit effective monitoring of work progress in relation to established milestones.
- .4 Work schedule content to include as a minimum the following:
 - .1 Bar (GANTT) Charts, indicating all work activities, tasks and other project elements, their anticipated durations, planned dates for achieving key activities and major project milestones supported with;

-
- 1.2 WORK SCHEDULE .4 (Cont'd)
(Cont'd)
- .2 Written narrative on key elements of work illustrated in bar chart, providing sufficient details to demonstrate a reasonable implementation plan for completion of project within designated time.
 - .3 Generally Bar Charts derived from commercially available computerized project management system are preferred but not mandatory.
 - .5 Work schedule must take into consideration and reflect the work phasing, required sequence of work, special conditions and operational restrictions as specified below and indicated on drawings.
 - .6 Schedule work in cooperation with the Departmental Representative. Incorporate within Detailed Work Schedule, items identified by Departmental Representative during review of preliminary schedule.
 - .7 Completed schedule shall be approved by Departmental Representative. When approved, take necessary measures to complete work within scheduled time. Do not change schedule without Departmental Representative's approval.
 - .8 Ensure that all subtrades and subcontractors are made aware of the work restraints and operational restrictions specified.
 - .9 Schedule Updates:
 - .1 Submit on a bi-weekly basis when requested by Departmental Representative.
 - .2 Provide information and pertinent details explaining reasons for necessary changes to implementation plan.
 - .3 Identify problem areas, anticipated delays, impact on schedule and proposed corrective measures to be taken.
 - .10 Departmental Representative will make interim reviews and evaluate progress of work based on approved schedule. Frequency of such reviews will be as decided by Departmental Representative. Address and take corrective measures on items identified by reviews and as directed by Departmental Representative. Update schedule accordingly.
-

1.2 WORK SCHEDULE
(Cont'd)

- .11 In every instance, change or deviation from the Work Schedule, no matter how minimal the risk or impact on safety or inconvenience to tenant or public might appear, will be subject to prior review and approval by the Departmental Representative.

1.3 OPERATIONAL
RESTRICTIONS

- .1 The Contractor must recognize that building occupants will be affected by implementation of this contract. The Contractor must perform the work with utmost regard to the safety and convenience of building occupants and users. All work activities must be planned and scheduled with this in mind. The Contractor will not be permitted to disturb any portion of the building without providing temporary facilities as necessary to ensure safe and direct passage through disturbed or otherwise affected areas.
- .2 Contractor to meet with the Departmental Representative on a weekly basis to identify intended work areas, activities and scheduling for the coming week.
- .3 See Section 01 35 59 in regards to:
.1 Special security requirements which must be observed in the course of work.
.2 Provision of security personnel by Contractor as part of the Work.
- .4 Limit Manoeuvring Space on Site: To area indicated on drawings. Staging area for placement of construction trailer, goods storage and portable toilet will be on the Institution's site, outside the security wall, in the location designated by the Institution.
- .5 Facility circulation maintained:
.1 Ensure that entrances, corridors, stairwells, fire exits and other circulation routes are maintained free and clear providing safe and uninterrupted passage for Facility users at all times during the entire work.
.2 Maintain those areas clean and free of construction materials and equipment. Provide temporary dust barriers and other suitable enclosures to ensure users are not exposed to construction activities and are protected from exposure to dust, noise and hazardous conditions.

1.3 OPERATIONAL
RESTRICTIONS
(Cont'd)

- .5 Facility circulation maintained:(Cont'd)
 - .3 Maintain fire escape routes accessible and fire fighting access open all times for the duration of the project.
 - .4 Do not under any circumstances block fire exit doors. Do not leave construction materials or debris in corridors, stairwells building entrances and exits.

- .6 Safety Signage:
 - .1 Provide on site, and erect as required during progress of work, proper bilingual signage. Mount where directed and as required on self-supporting stands, or on fixed walls warning the building occupants of construction activities in progress and alerting need to exercise caution in proceeding through disturbed areas of the facility, and directing building occupants through any detours which may be required.
 - .2 Signage to be professionally printed and mounted on wooden backing, coloured and to express messages as directed by the Departmental Representative.
 - .3 Generally maximum size of sign should be in the order of 1.0 square meters. Number of signs required will be decided in conjunction with Institution and as directed by departmental representative.
 - .4 Include costs for the supply and installation as well as removal of these signs and the related patching and making good of associated walls in the bid price.

- .7 Dust and Dirt Control:
 - .1 See Sections 01 50 00 and 01 74 11 for dust control and cleaning requirements.
 - .2 Effectively plan and implement dust control measures and cleaning activities as an integral part of all construction activities. Review all measures with the Departmental Representative before undertaking work, especially for major dust generating activities.
 - .3 Do not allow demolition debris and construction waste to accumulate on site and contribute to the propagation of dust.
 - .4 As work progresses, maintain construction areas in a tidy condition at all times. Remove gross dust accumulations by cleaning and vacuuming immediately following the completion of any major dust generating activity.

1.3 OPERATIONAL
RESTRICTIONS
(Cont'd)

- .7 Dust and Dirt Control:(Cont'd)
- .5 Immediately remove all debris and dust from within occupied areas as generated by work therein during a given workshift.
 - .6 Disconnect and seal-off ductwork of HVAC servicing the construction area to stop spread of dust into other areas of Facility.
 - .7 Avoid situations and practises which results in dust and dirt being brought from the construction areas or from the exterior and tracked inside the building into occupied areas used by tenants and the public.
 - .8 Stop workers with soiled footwear from entering building.
 - .9 Inform workers and make them sensitive to the need for dust and dirt control. Stringently enforce rules and regulations, immediately address non-compliance.
 - .10 Keep access doors to work areas closed at all times. Use only designated doors for entry or egress.
- .8 Cleaning of occupied areas used by Contractor:
- .1 Clean lobbies, circulation routes used by workers to gain access to work by conducting cleaning, vacuuming and washing of floors, walls and other soiled surfaces.
 - .2 Cleaning staff shall remain on site beyond the end of each off-hour workshifts to address any Tenant complaints or concerns and carryout additional cleaning functions as directed by Departmental Representative or by a pre-designated person(s) representing the tenant(s).
 - .3 Meager attempts at controlling dust and ineffective unprofessional cleaning procedures will not be tolerated.
 - .4 Failure to provide effective dust control, allowing construction dust and dirt to escape beyond construction areas and contaminate occupied areas and building circulation areas will result in Contractor being ordered to immediately provide professional cleaning services without delay to remedy the situation and conduct all cleaning to the extent as determined by Departmental Representative. Alternatively, Departmental Representative may, at certain times and at own discretion, obtain the services of an independent building cleaning agency when cleaning being provided by Contractor is ineffective or tardy in

1.3 OPERATIONAL
RESTRICTIONS
(Cont'd)

- .8 (Cont'd)
- .4 (Cont'd)
response. Costs of such services will be charged against Contractor in the form of financial penalties or holdback assessments against the Contract.
- .9 Ensure that all sub-trades are made aware of and abide by the contents of this section and in particular the work restrictions specified herein due to tenant operational requirements.

1.4 PROJECT MEETINGS

- .1 Schedule and administer project meetings, held on a minimum bi-weekly basis, for entire duration of work and more often when directed by Departmental Representative as deemed necessary due to progress of work or particular situation.
- .2 Prepare agenda for meetings.
- .3 Notify participants in writing 4 days in advance of meeting date.
 - .1 Ensure attendance of all subcontractors.
 - .2 Departmental Representative will provide list of other attendees to be notified.
- .4 Hold meetings at project site or where approved by Departmental Representative.
- .5 Preside at meetings and record minutes.
 - .1 Indicate significant proceedings and decisions. Identify action items by parties.
 - .2 Distribute to participants by mail or by facimile within 3 calendar days after each meeting.
 - .3 Make revisions as directed by Departmental Representative.
 - .4 Departmental Representative will advise whether submission of minutes by Email is acceptable. Decision will be based on compatibility of software among participants.

1.5 WORK
COORDINATION

- .1 The General Contractor is responsible for coordinating the work of the various trades and predetermining where the work of such trades interfaces with each other.

1.5 WORK
COORDINATION
(Cont'd)

- .1 (Cont'd)
 - .1 Designate one person from own employ having overall responsibility to review contract documents and shop drawings, plan and manage such coordination.
 - .2 The General Contractor shall convene meetings between trades whose work interfaces and ensure that they are fully aware of the areas and the extent of where interfacing is required.
 - .3 Submission of shop drawings and ordering of prefabricated equipment or prebuilt components shall only occur once coordination meeting for such items has taken place between trades and all conditions affecting the work of the interfacing trades has been made known and accounted for.
 - .4 Work Cooperation:
 - .1 Ensure cooperation between trades in order to facilitate the general progress of the work and avoid situations of spatial interference.
 - .2 Ensure that each trade provides all other trades reasonable opportunity for the completion of the work and in such a way as to prevent unnecessary delays, cutting, patching and the need to remove and replace completed work.
 - .5 No extra costs to the Contract will be considered by the Departmental Representative as a result of Contractor's failure to effectively coordinate all portions of the Work. Disputes between the various trades as a result of their not being informed of the areas and extent of interface work shall be the sole responsibility of the General Contractor to be resolved at own cost.

1.1 RELATED
SECTIONS

- .1 Section 01 14 10 - SCHEDULING and MANAGEMENT OF THE WORK.
- .2 Section 01 35 24 - SPECIAL PROCEDURES ON FIRE SAFETY PROCEDURES.
- .3 Section 01 35 25 - SPECIAL PROCEDURES ON LOCKOUT REQUIREMENTS.
- .4 Section 01 35 29 - HEALTH AND SAFETY REQUIREMENTS.
- .5 Section 01 78 00 - CLOSEOUT SUBMITTALS.
- .6 Section 08 34 60 - DETENTION DOOR HARDWARE.
- .7 Section 08 34 63 - DETENTION SECURITY METAL DOORS
- .8 Section 08 80 50 - GLAZING
- .9 Section 09 91 23 - INTERIOR PAINTING.

1.2 SUBMITTAL
GENERAL REQUIREMENTS

- .1 Submit to Departmental Representative for review requested submittals specified in various sections of the specifications including shop drawings, samples, permits, compliance certificates, test reports, work management plans and other data required as part of the work.
 - .2 Submit with reasonable promptness and in orderly sequence so as to allow for Departmental Representative's review and not cause delay in Work. Failure to submit in ample time will not be considered sufficient reason for an extension of Contract time and no claim for extension by reason of such default will be allowed.
 - .3 Do not proceed with work until relevant submissions have been reviewed.
 - .4 Present shop drawings, product data, samples and mock-ups in SI Metric units.
 - .5 Where items or information is not produced in SI Metric units, provide soft converted values.
-

1.2 SUBMITTAL
GENERAL REQUIREMENTS
(Cont'd)

- .6 Review submittals prior to submission. Ensure that necessary requirements have been determined and verified and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents.
- .1 Submittals not stamped, signed, dated and identified as to specific project will be returned unexamined by Departmental Representative and considered rejected.
- .7 Verify field measurements and affected adjacent Work are coordinated.
- .8 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .9 Contractor's responsibility for errors, omissions or deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative's review.
- .10 Submittal format: paper originals, or alternatively clear and fully legible photocopies of originals. Facsimiles are not acceptable, except in special circumstances pre-approved by Departmental Representative. Poorly printed non-legible photocopies or facsimiles will not be accepted and be returned for resubmission.
- .11 Make changes or revision to submissions which Departmental Representative may require, consistent with Contract Documents and resubmit as directed by Departmental Representative. When resubmitting, identify in writing of any revisions other than those requested.
- .12 Keep one reviewed copy of each submittal document on site for duration of Work.

1.3 SHOP DRAWINGS
AND PRODUCT DATA

- .1 The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, technical product data, brochures and other data to be provided by Contractor to illustrate details of a portion of Work.

1.3 SHOP DRAWINGS .2
AND PRODUCT DATA
(Cont'd)

Shop Drawing Submittal Schedule:

- .1 Submit within 15 working days of acceptance of bid a schedule listing all shop drawings to be submitted for project.
- .2 Schedule shall be in format acceptable to Departmental Representative and indicate proposed submission date for each item, status of review and anticipated product delivery date to site. Track all submissions for entire project.
- .3 Revise schedule as work progresses. Identify items which have been reviewed and finalized and indicating those outstanding.
- .4 Update schedule at stipulated dates or project time intervals predetermined and agreed upon with Departmental Representative at commencement of Work.

.3 Shop Drawing Quantities: submit sufficient copies required by the General Contractor and sub-contractors plus 3 copies which will be retained by Departmental Representative.

- .1 Ensure sufficient copies are submitted to enable one complete set to be included in each of the maintenance manuals specified in 01 78 00.

.4 Shop Drawings Format:

- .1 Opaque white prints or photocopies of original drawings or standard drawings modified to clearly illustrate work specific to project requirements. Maximum sheet size to be 1000 x 707 mm.
- .2 Product Data from manufacturer's standard catalogue sheets, brochures, literature, performance charts and diagrams, used to illustrate standard manufactured products, to be original full colour brochures, clearly marked indicating applicable data and deleting information not applicable to project.
- .3 Non or poorly legible drawings, photocopies or facsimiles will not be accepted and returned not reviewed.

.5 Shop Drawings Content:

- .1 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where items or equipment attach or connect to other items or equipment, confirm that all interrelated work have been

-
- 1.3 SHOP DRAWINGS .5 Shop Drawings Content:(Cont'd)
AND PRODUCT DATA .1 (Cont'd)
(Cont'd)
-
- .2 coordinated, regardless of section or trade from which the adjacent work is being supplied and installed.
- .2 Supplement manufacturer's standard drawings and literature with additional information to provide details applicable to project.
- .3 Delete information not applicable to project on all submittals.
- .4 Equipment installation/start-up data: include manufacturer's recommended installation instructions, pre-start and start-up checklists for those pieces of equipment and systems designated to be commissioned as specified in section.
- .6 Allow 7 calendar days for Departmental Representative's review of each submission.
- .7 Adjustments or corrections made on shop drawings by Departmental Representative are not intended to change Contract Price. If adjustments affect value of Work, advise Departmental Representative in writing prior to proceeding with Work.
- .8 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections and comments are made, fabrication and installation may proceed upon receipt of shop drawings. If shop drawings are rejected and noted to be Resubmitted, do not proceed with that portion of work until resubmission and review of corrected shop drawings, through same submission procedures indicated above.
- .9 Be advised that costs and expenses incurred by Departmental Representative to conduct more than one review of incorrectly prepared shop drawing submittal for a particular material, equipment or component of work may be assessed against the Contractor in the form of a financial holdback to the Contract.
- .10 Accompany each submissions with transmittal letter, in duplicate, containing:
- .1 Date.
 - .2 Project title and project number.
 - .3 Contractor's name and address.
-

-
- 1.3 SHOP DRAWINGS .10 (Cont'd)
AND PRODUCT DATA
(Cont'd)
-
- .4 Identification and quantity of each shop drawing, product data and sample.
.5 Other pertinent data.
- .11 Submissions shall include:
- .1 Date and revision dates.
.2 Project title and project number.
.3 Name and address of:
.1 Subcontractor.
.2 Supplier.
.3 Manufacturer.
.4 Contractor's stamp, signed by Contractor's authorized Representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
.5 Cross references to particular details of contract drawings and specifications section number for which shop drawing submission addresses.
.6 Details of appropriate portions of Work as applicable:
.1 Fabrication.
.2 Layout, showing dimensions, including identified field dimensions, and clearances.
.3 Setting or erection details.
.4 Capacities.
.5 Performance characteristics.
.6 Standards.
.7 Operating weight.
.8 Wiring diagrams.
.9 Single line and schematic diagrams.
.10 Relationship to adjacent work.
- .12 After Departmental Representative's review, distribute copies.
- .13 The review of shop drawings by the Departmental Representative or by an authorized Consultant or designate is for sole purpose of ascertaining conformance with general concept. This review shall not mean that Canada approves the detail design inherent in the shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting all requirements of the construction and Contract Documents. Without restricting generality of foregoing,
-

- 1.3 SHOP DRAWINGS .13 (Cont'd)
AND PRODUCT DATA
(Cont'd)
- Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of all sub-trades.
- 1.4 SAMPLES .1
- .2 Submit for review samples as specified in respective specification Sections. Label samples with origin and intended use.
 - .2 Deliver samples to Departmental Representative's office or to other address as directed. Do not drop off samples at construction site except for pre-approved circumstances previously approved by Departmental Representative.
 - .3 Notify Departmental Representative in writing, at time of submission of deviations in samples from requirements of Contract Documents.
 - .4 Where colour, pattern or texture is criterion, submit full range of samples.
 - .5 Adjustments made on samples by Departmental Representative are not intended to change Contract Price. If adjustments will result in a cost increase to the Contract notify Departmental Representative in writing prior to proceeding with Work.
 - .6 Make changes in samples which Departmental Representative may require, consistent with Contract Documents.
 - .7 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

1.1 SECTION
INCLUDES

- .1 Fire Safety Requirements
- .2 Hot Work Permit
- .3 Existing Fire Protection and Alarm Systems

1.2 RELATED WORK

- .1 Section 01 35 29 HEALTH and SAFETY REQUIREMENTS.
- .2 Section 01 14 10 SCHEDULING and MANAGEMENT of WORK.

1.3 REFERENCES

- .1 Fire Protection Standards issued by Fire Protection Services, Labour Program Division of Service Canada:
 - .1 FCC No. 301-June 1982 Standard for Construction Operations.
 - .2 FCC No. 302-June 1982 Standard for Welding and Cutting.
- .2 FCC standards may be viewed at:
 - .1 Fire Protection Services - Atlantic Region office, Halifax, N.S, Tel. (902) 426-6053 -Eileen Beck Manager fire commissioner.

1.4 DEFINITIONS

- .1 Hot Work defined as:
 - .1 Welding work
 - .2 Cutting of materials by use of torch or other open flame devices
 - .3 Grinding with equipment which produces sparks.
 - .4 Use of open flame torches such as for roofing work.

1.5 SUBMITTALS

- .1 Submit copy of Hot Work Procedures and sample of Hot Work permit to Departmental Representative for review, within 14 calendar days of acceptance of bid.
 - .2 Submit in accordance with section 01 33 00.
-

1.6 FIRE SAFETY
REQUIREMENTS

- .1 Implement and follow fire safety measures during Work. Comply with following:
 - .1 National Fire Code.
 - .2 Fire Protection Standards FCC 301 and FCC 302.
 - .3 Federal and Provincial Occupational Health and Safety Acts and Regulations.
- .2 In event of conflict between any provisions of above authorities the most stringent provision will apply. Should a dispute arise in determining the most stringent requirement, Departmental Representative will advise on the course of action to be followed.

1.7 HOT WORK
AUTHORIZATION

- .1 Obtain Departmental Representative's written "Authorization to Proceed" before conducting any form of Hot Work on site.
- .2 To obtain authorization submit to Departmental Representative:
 - .1 Contractor's typewritten Hot Work Procedures to be followed on site as specified below.
 - .2 Description of the type and frequency of Hot Work required.
 - .3 Sample Hot Work Permit to be used.
- .3 Upon review and confirmation that effective fire safety measures will be implemented and followed during performance of hot work, Departmental Representative will give authorization to proceed as follows:
 - .1 Issue one written "Authorization to Proceed" covering the entire project for duration of work or;
 - .2 Subdivide the work into pre-determined, individual activities, each activity requiring a separately written authorization to proceed.
- .4 Requirement for individual authorization will be based on:
 - .1 Nature or phasing of work;
 - .2 Risk to Facility operations;
 - .3 Quantity of various trades needing to perform hot work on project or;
 - .4 Other situation deemed necessary by Departmental Representative to ensure fire safety on premises.

1.7 HOT WORK
AUTHORIZATION
(Cont'd)

- .5 Do not perform any Hot Work until receipt of Departmental Representative's written "Authorization to Proceed" for that portion of work.
- .6 In coordinate performance of Hot Work with Facility Manager through the Departmental Representative. When directed, perform Hot Work only during non-operative hours of the Facility. Follow Departmental Representative's directives in this regard.

1.8 HOT WORK
PROCEDURES

- .1 Develop and implement safety procedures and work practises to be followed during the performance of Hot Work.
- .2 Hot Work Procedures to include:
 - .1 Requirement to perform hazard assessment of site and immediate work area beforehand for each hot work event in accordance with Safety Plan specified in section 01 35 29.
 - .2 Use of a Hot Work Permit system with individually written permit issued by Contractor's Superintendent to specific worker or subcontractor granting permission to proceed with Hot Work.
 - .3 Permit required for each Hot Work event.
 - .4 Designation of a person on site as a Fire Safety Watcher responsible to conduct a fire safety watch for a minimum duration of 30 minutes immediately following the completion of the Hot Work.
 - .5 Compliance with fire safety codes, standards and occupational health and safety regulations specified.
 - .6 Site specific rules and procedures in force at the site as provided by the Facility Manager.
- .3 Generic procedures, if used, must be edited and supplemented with pertinent information tailored to reflect specific project conditions. Label document as being the Hot Work Procedures for this contract.
- .4 Procedures shall clearly establish responsibilities of:
 - .1 Worker performing hot work,
 - .2 Person issuing the Hot Work Permit,
 - .3 Fire Safety Watcher,
 - .4 Subcontractor(s) and Contractor.

-
- 1.8 HOT WORK PROCEDURES (Cont'd)
- .5 Brief all workers and subcontractors on Hot Work Procedures and of Permit system. Stringently enforce compliance.
 - .6 Failure to comply with fire safety procedures may result in the issue of a Non-Compliance notification as specified in Section 01 35 29.
- 1.9 HOT WORK PERMIT
- .1 Hot Work Permit to include the following:
 - .1 Project name and project number;
 - .2 Building name and specific room or area where hot work will be performed;
 - .3 Date of issue;
 - .4 Description of hot work type needed;
 - .5 Special precautions to be followed, including type of fire extinguisher needed;
 - .6 Name and signature of permit issuer.
 - .7 Name of worker to which the permit is issued.
 - .8 Permit validity period not to exceed 8 hours. Indicate start time/date and termination time/date.
 - .9 Worker's signature with time/date of hot work completion.
 - .10 Stipulated time period of safety watch.
 - .11 Fire Safety Wather's signature with time/date.
 - .2 Permit to be typewritten form. Industry Standard forms shall only be used if all data specified above is included on form.
 - .3 Each Hot Work Permit to be completed in full, signed and returned to Contractor's Superintendent for safe keeping on site.
- 1.10 FIRE PROTECTION AND ALARM SYSTEMS
- .1 Fire protection and alarm systems shall not be:
 - .1 Obstructed.
 - .2 Shut-off, unless approved by Departmental Representative.
 - .3 Left inactive at the end of a working day or shift.
 - .2 Do not use fire hydrants, standpipes and hose systems for purposes other than fire fighting.
 - .3 Costs incurred, from the fire department, Facility owner and tenants, resulting from
-

1.10 FIRE PROTECTION.3
AND ALARM SYSTEMS
(Cont'd)

(Cont'd)
negligently setting off false alarms will be
charged to the Contractor in the form of
financial progress payment reductions and
holdback assessments against the Contract.

1.11 DOCUMENTS
ON SITE

- .1 Keep Hot Work Permits and Hazard assessment
documentation on site for duration of Work.
- .2 Upon request, make available to Departmental
Representative or to authorized safety
Representative for inspection.

- 1.1 SECTION INCLUDES .1 Procedures to isolate and lockout electrical facility and other equipment from energy sources.
- 1.2 RELATED WORK .1 Section 01 35 29: HEALTH and SAFETY
- .2 Section 01 14 10 SCHEDULING and MANAGEMENT of the WORK
- .3 Section 01 50 00: TEMPORARY FACILITIES.
- 1.3 REFERENCES .1 CSA C22.1-06 - Canadian Electrical Code, Part 1, Safety Standard for Electrical Installations.
- .2 CAN/CSA C22.3 No.1-06 - Overhead Systems.
- .3 CSA C22.3 No.7-06 - Underground Systems.
- .4 COSH: Canada Occupational Health and Safety Regulations made under Part II of the Canada Labour Code.
- 1.4 DEFINITIONS .1 Electrical Facility: means any system, equipment, device, apparatus, wiring, conductor, assembly or part thereof that is used for the generation, transformation, transmission, distribution, storage, control, measurement or utilization of electrical energy, and that has an amperage and voltage that is dangerous to persons.
- .2 Guarantee of Isolation: means a guarantee by a competent person in control or in charge that a particular facility or equipment has been isolated.
- .3 De-energize: in the electrical sense, that a piece of equipment is isolated and grounded, e.g. if the equipment is not grounded, it cannot be considered de-energized (DEAD).
- .4 Guarded: means that an equipment or facility is covered, shielded, fenced, enclosed, inaccessible by location, or otherwise protected in a manner that, to the extent that is reasonably practicable, will prevent or
-

1.4 DEFINITIONS
(Cont'd)

- .4 Guarded: (Cont'd)
reduce danger to any person who might touch or go near such item.
- .5 Isolate: means that an electrical facility, mechanical equipment or machinery is separated or disconnected from every source of electrical, mechanical, hydraulic, pneumatic or other kind of energy that is capable of making it dangerous.
- .6 Live/alive: means that an electrical facility produces, contains, stores or is electrically connected to a source of alternating or direct current of an amperage and voltage that is dangerous or contains any hydraulic, pneumatic or other kind of energy that is capable of making the facility dangerous to persons.

1.5 COMPLIANCE
REQUIREMENTS

- .1 Comply with the following in regards to isolation and lockout of electrical facilities and equipment:
 - .1 Canadian Electrical Code
 - .2 Federal and Provincial Occupational Health and Safety Acts and Regulations.
 - .3 Regulations and code of practise as applicable to mechanical equipment or other machinery being de-energized.
 - .4 Procedures specified herein.
- .2 In event of conflict between any provisions of above authorities the most stringent provision will apply. Should a dispute arise in determining the most stringent requirement, Departmental Representative will advise on the course of action to be followed.

1.6 SUBMITTALS

- .1 Submit copy of proposed lockout procedures and sample of lockout permit to Departmental Representative for review, within 14 calendar days of acceptance of bid.
- .2 Submit in accordance with section 01 33 00.

1.7 ISOLATION OF
EXISTING SERVICES

- .1 Obtain Departmental Representative's written authorization prior to working on existing live or active electrical facilities and equipment and before proceeding with isolation of such item.
- .2 To obtain authorization, submit to Departmental Representative the following documentation:
 - .1 Written request to isolate the particular service or facility and;
 - .2 Copy of Contractor's Lockout Procedures.
- .3 Make a Request for Isolation for each event, unless directed otherwise by Departmental Representative, as follows:
 - .1 Fill-out standard form in current use at the Facility as provided by Departmental Representative or;
 - .2 Where no form exist, make written request indicating:
 - .1 The equipment, system or service to be isolated and it's location;
 - .2 Duration of isolation period (ie: start time & date and completion time & date).
 - .3 Voltage of service feed to system or equipment being isolated.
 - .4 Name of person making the request.
- .4 Do not proceed with isolation until receipt of written notification from Departmental Representative granting the Isolation Request and authorizing to proceed with the work.
 - .1 Note that Departmental Representative may designate another person at the Facility being authorized to grant the Isolation Request.
- .5 Conduct safe, orderly shut down of equipment or facility. De-energize, isolate and lockout power and other sources of energy feeding the equipment or facility.
- .6 Determine in advance, as much as possible, in cooperation with the Departmental Representative, the type and frequency of situations which will require isolation of existing services.
- .7 Plan and schedule shut down of existing services in consultation with the Departmental Representative and the Facility Manager.

1.7 ISOLATION OF
EXISTING SERVICES
(Cont'd)

- .7 (Cont'd)
Minimize impact and downtime of Facility operations. Follow Departmental Representative's directives in this regard.
- .8 Conduct hazard assessment as part of the process in accordance with health and safety requirements specified Section 01 35 29.

1.8 LOCKOUTS

- .1 De-energize, isolate and lockout electrical facility, mechanical equipment and machinery from all potential sources of energy prior to working on such items.
- .2 Develop and implement clear and specific lockout procedures to be followed as part of the Work.
- .3 Prepare typed written Lockout Procedures describing safe work practices, procedures, worker responsibilities and sequence of activities to be followed on site by workforce to safely isolate an active piece of equipment or electrical facility and effectively lockout and tagout it's sources of energy.
- .4 Include as part of the Lockout Procedures a system of lockout permits managed by Contractor's Superintendent or other qualified person designated by him/her as being "in-charge" at the site.
 - .1 A lockout permit shall be issued to specific worker providing a Guarantee of Isolation before each event when work must be performed on a live equipment or electrical facility.
 - .2 Duties of person managing the permit system to include:
 - .1 Issuance of permits and lockout tags to workers.
 - .2 Determining permit duration.
 - .3 Maintaining record of permits and tags issued.
 - .4 Making a Request for Isolation to Departmental Representative when required as specified above.
 - .5 Designating a Safety Watcher, when one is required based on type of work.
 - .6 Ensuring equipment or facility has been properly isolated.

1.8 LOCKOUTS
(Cont'd)

- .4 (Cont'd)
 - .2 (Cont'd)
 - .7 Collecting and safekeeping lockout tags returned by workers as a record of the event.
 - .5 Clearly establish, describe and allocate responsibilities of:
 - .1 Workers.
 - .2 Person managing the lockout permit system.
 - .3 Safety Watcher.
 - .4 Subcontractor(s) and General Contractor.
 - .6 Generic procedures, if used, must be edited and supplemented with pertinent information to reflect specific project requirements.
 - .1 Incorporate site specific rules and procedures in force at site as provided by Facility Manager through the Departmental Representative.
 - .2 Clearly label the document as being the Lockout procedures applicable to work of this contract.
 - .7 Use energy isolation lockout devices specifically designed and appropriate for type of facility or equipment being locked out.
 - .8 Use industry standard lockout tags.
 - .9 Provide appropriate safety grounding and guards as required.

1.9 CONFORMANCE

- .1 Brief all workers and subcontractors on requirements of this section. Stringently enforce use and compliance.
- .2 Failure to follow lockouts procedures specified herein may result in the issuance of a Non-Compliance notification as specified in Section 01 35 29.

1.10 DOCUMENTS
ON SITE

- .1 Post Lockout Procedures on site in common location for viewing by workers.
- .2 Keep copies of Request for Isolation forms and lockout permits and tags issued to workers on site for full duration of Work.

1.10 DOCUMENTS .3 Upon request, make available to Departmental
ON SITE Representative or to authorized safety
(Cont'd) Representative for inspection.

1.1 RELATED WORK

- .1 Section 01 35 24: Special Procedures on Fire Safety Requirements.
- .2 Section 01 35 25: Special Procedures on Lockout Requirements.

1.2 DEFINITIONS

- .1 COSH: Canada Occupational Health and Safety Regulations made under Part II of the Canada Labour Code.
- .2 Competent Person: means a person who is:
 - .1 Qualified by virtue of personal knowledge, training and experience to perform assigned work in a manner that will ensure the health and safety of persons in the workplace, and;
 - .2 Knowledgeable about the provisions of occupational health and safety statutes and regulations that apply to the Work and;
 - .3 Knowledgeable about potential or actual danger to health or safety associated with the Work.
- .3 Medical Aid Injury: any minor injury for which medical treatment was provided and the cost of which is covered by Workers' Compensation Board of the province in which the injury was incurred.
- .4 PPE: personal protective equipment
- .5 Work Site: where used in this section shall mean areas, located at the premises where Work is undertaken, used by Contractor to perform all of the activities associated with the performance of the Work.

1.3 SUBMITTALS

- .1 Make submittals in accordance with Section 01 33 00.
 - .2 Submit site-specific Health and Safety Plan prior to commencement of Work.
 - .1 Submit within 10 work days of notification of Bid Acceptance. Provide 3 copies.
 - .2 Departmental Representative will review Health and Safety Plan and provide comments.
-

1.3 SUBMITTALS
(Cont'd)

- .2 (Cont'd)
 - .3 Revise the Plan as appropriate and resubmit within 5 work days after receipt of comments.
 - .4 Departmental Representative's review and comments made of the Plan shall not be construed as an endorsement, approval or implied warranty of any kind by Canada and does not reduce Contractor's overall responsibility for Occupational Health and Safety of the Work.
 - .5 Submit revisions and updates made to the Plan during the course of Work.
- .3 Submit name of designated Health & Safety Site Representative and support documentation specified in the Safety Plan.
- .4 Submit building permit, compliance certificates and other permits obtained.
- .5 Submit copy of Letter in Good Standing from Provincial Workers Compensation or other department of labour organization.
 - .1 Submit update of Letter of Good Standing whenever expiration date occurs during the period of Work.
- .6 Submit copies of reports or directions issued by Federal, Provincial and Territorial health and safety inspectors.
- .7 Submit copies of incident reports.
- .8 Submit WHMIS MSDS - Material Safety Data Sheets.

1.4 COMPLIANCE
REQUIREMENTS

- .1 Comply with the Occupational Health and Safety Act for the Province of Nova Scotia and the Occupational Health and Safety Regulations
- .2 Comply with Canada Labour Code - Part II (entitled Occupational Health and Safety) and the Canada Occupational Health and Safety Regulations (COSHA) as well as any other regulations made pursuant to the Act.
 - .1 The Canada Labour Code can be viewed at:
[www.http://laws.justice.gc.ca/en/L-2/](http://laws.justice.gc.ca/en/L-2/)

REQUIREMENTS
(Cont'd)

- .2 (Cont'd)
 - .2 COSH can be viewed at:
[www.http://laws.justice.gc.ca/eng/SOR-86-304/n e .html](http://laws.justice.gc.ca/eng/SOR-86-304/n e .html)
 - .3 A copy may be obtained at: Canadian Government Publishing Public Works & Government Services Canada Ottawa, Ontario, K1A 0S9 Tel: (819) 956-4800 (1-800-635-7943) Publication No. L31-85/2000 E or F)
- .3 Observe and enforce construction safety measures required by:
 - .1 National Building Code of Canada;
 - .2 Provincial Worker's Compensation Board;
 - .3 Municipal statutes and ordinances
- .4 In event of conflict between any provisions of above authorities the most stringent provision will apply. Should a dispute arise in determining the most stringent requirement, Departmental Representative will advise on the course of action to be followed.
- .5 Maintain Workers Compensation Coverage in good standing for duration of Contract. Provide proof of clearance through submission of Letter in Good Standing.
- .6 Medical Surveillance: Where prescribed by legislation or regulation, obtain and maintain worker medical surveillance documentation.

1.5 RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons and environment adjacent to the site to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by all workers, sub-contractors and other persons granted access to Work Site with safety requirements of Contract Documents, applicable federal, provincial, and local by-laws, regulations, and ordinances, and with site-specific Health and Safety Plan.

1.6 SITE CONTROL
AND ACCESS

- .1 Control work site and entry points to construction areas.
 - .1 Delineate and isolate construction areas from other areas of site Facility by use of appropriate means.
 - .2 Post notices and signage at entry points and at other strategic locations identifying entrance onto site to be restricted to authorized persons only.
 - .3 Signage must be professionally made, bilingual in both official languages or display internationally understood graphic symbols.
- .2 Approve and grant access to site only to workers and authorized persons.
 - .1 Immediately stop non-authorized persons from circulating in construction areas and remove from site.
 - .2 Provide site safety orientation to all persons before granting access. Advise of site conditions, hazards and mandatory safety rules to be observed on site.
- .3 Secure site at night time to extent required to protect against unauthorized entry. Engage and pay for services of Institutionally approved Commissionaire to provide security where protection cannot be achieved by other means.
- .4 Ensure persons granted access to site wear appropriate personal protective equipment (PPE) suitable to work and site conditions.
 - .1 Provide such PPE to authorized persons who require access to perform inspections or other approved purposes.

1.7 PROTECTION

- .1 Carry out work placing emphasis on health and safety of the Facility personnel, Inmates and construction workers and protection of the environment.
- .2 Erect safety barricades, signage on site to effectively delineate work areas, protect

- 1.7 PROTECTION
(Cont'd)
- .2 (Cont'd)
pedestrian around and adjacent to work and to create a safe working environment.
- .1 Erect fences, hoarding protective barriers as required. See Section 01 50 00 for minimum acceptable barricades.
- .3 Should unforeseen or peculiar safety related hazard or condition become evident during performance of work, immediately take measures to rectify the situation and prevent damage or harm. Advise Departmental Representative verbally and in writing.
- 1.8 FILING OF NOTICE
- .1 File Notice of Project with pertinent provincial health and safety authorities prior to beginning of Work.
- .1 Departmental Representative will assist in locating address if needed.
- 1.9 PERMITS
- .1 Post permits, licenses and compliance certificates, specified in section 01 10 10, at Work Site.
- .2 Where a particular permit or compliance certificate cannot be obtained, notify Departmental Representative in writing and obtain approval to proceed before carrying out applicable portion of work.
- 1.10 HAZARD ASSESSMENTS
- .1 Perform site specific health and safety hazard assessment of the Work and its site.
- .2 Carryout initial assessment prior to commencement of work with further assessments as needed during progress of work, including when new trades and subcontractors arrive on site.
- .3 Record results and address in Health and Safety Plan.
-

1.10 HAZARD
ASSESSMENTS
(Cont'd)

- .4 Keep documentation on site for entire duration of the work.

1.11 PROJECT/SITE
CONDITIONS

- .1 Following are potential health, environmental and safety hazards at the site for which Work may involve contact with:
- .1 Known latent site and environmental conditions:
 - .1 Contact with inmates. Ensure that employees follow CSC security requirements as indicated in tender specifications.
 - .2 Lifting hazard:
 - .1 Unloading and manipulation of heavy material.
 - .2 Above items shall not be construed as being complete and inclusive of potential health and safety hazards encountered during Work.
 - .3 Include above items in the hazard assessment of the Work.
 - .4 MSDS Data sheets of pertinent hazardous and controlled products stored on site can be obtain from Departmental Representative.

1.12 MEETINGS

- .1 Attend pre-construction health and safety meeting, convened and chaired by Departmental Representative, prior to commencement of Work, at time, date and location determined by Departmental Representative. Ensure attendance of:
- .1 Superintendent of work
 - .2 Designated Health & Safety Site Representative
 - .3 Subcontractors
- .2 Conduct regularly scheduled tool box and safety meetings during the Work in conformance with Occupational Health and Safety regulations.
- .3 Keep documents on site.
-

1.13 HEALTH AND
SAFETY PLAN

- .1 Prior to commencement of Work, developd written Health and Safety Plan specific to the Work. Implement, maintain, and enforce Plan for entire duration of Work and until final demobilization from site.
- .2 Health and Safety Plan shall include the following components:
 - .1 List of health risks and safety hazards identified by hazard assessment.
 - .2 Control measures used to mitigate risks and hazards identified.
 - .3 On-site Contingency and Emergency Response Plan as specified below.
 - .4 On-site Communication Plan as specified below.
 - .5 Name of Contractor's designated Health & Safety Site Representative and information showing proof of his/her competence and reporting relationship in Contractor's company.
 - .6 Names, competence and reporting relationship of other supervisory personnel used in the Work for occupational health and safety purposes.
- .3 On-site Contingency and Emergency Response Plan shall include:
 - .1 Operational procedures, evacuation measures and communication process to be implemented in the event of an emergency.
 - .2 Evacuation Plan: site and floor plan layouts showing escape routes, marshalling areas. Details on alarm notification methods, fire drills, location of fire fighting equipment and other related data.
 - .3 Name, duties and responsibilities of persons designated as Emergency Warden(s) and deputies.
 - .4 Emergency Contacts: name and telephone number of officials from:
 - .1 General Contractor and subcontractors.
 - .2 Pertinent Federal and Provincial Departments and Authorities having jurisdiction.
 - .3 Local emergency resource organizations.
 - .5 Harmonize Plan with Facility's Emergency Response and Evacuation Plan. Departmental Representative will provide pertinent data

-
- (Cont'd)
- .3 (Cont'd)
 - .5 (Cont'd)
including name of PWGSC and Facility
Management contacts.
 - .4 On-site Communication Plan:
 - .1 Procedures for sharing of work related
safety information to workers and
subcontractors, including emergency and
evacuation measures.
 - .2 List of critical work activities to be
communicated with Facility Manager which have
a risk of endangering health and safety of
Facility users.
 - .5 Address all activities of the Work including
those of subcontractors.
 - .6 Review Health and Safety Plan regularly
during the Work. Update as conditions warrant
to address emerging risks and hazards, such as
whenever new trade or subcontractor arrive at
Work site.
 - .7 Departmental Representative will respond in
writing, where deficiencies or concerns are
noted and may request re-submission of the
Plan with correction of deficiencies or
concerns.
 - .8 Post copy of the Plan, and updates,
prominently on Work site.
-
- 1.14 SAFETY SUPERVISION
- .1 Employ Health & Safety Site Representative
responsible for daily supervision of health
and safety of the Work.
 - .2 Health & Safety Site Representative may be
the Superintendent of the Work or other person
designated by Contractor and shall be assigned
the responsibility and authority to:
 - .1 Implement, monitor and enforce daily
compliance with health and safety requirements
of the Work
 - .2 Monitor and enforce Contractor's
site-specific Health and Safety Plan.
 - .3 Conduct site safety orientation session
to persons granted access to Work Site.
-

1.14 SAFETY
SUPERVISION
(Cont'd)

- .2 (Cont'd)
- .4 Ensure that persons allowed site access are knowledgeable and trained in health and safety pertinent to their activities at the site or are escorted by a competent person while on the Work Site.
- .5 Stop the Work as deemed necessary for reasons of health and safety.
- .3 Health & Safety Site Representative must:
- .1 Be qualified and competent person in occupational health and safety.
- .2 Have site-related working experience specific to activities of the Work.
- .3 Be on Work Site at all times during execution of the Work.
- .4 All supervisory personnel assigned to the Work shall also be competent persons.
- .5 Inspections:
- .1 Conduct regularly scheduled safety inspections of the Work on a minimum bi-weekly basis. Record deficiencies and remedial action taken.
- .6 Cooperate with Facility's Occupational Health and Safety representative should one be designated by Departmental Representative.
- .7 Keep inspection reports and supervision related documentation on site.

1.15 TRAINING

- .1 Use only skilled workers on Work Site who are effectively trained in occupational health and safety procedures and practices pertinent to their assigned task.
- .2 Maintain employee records and evidence of training received. Make data available to Departmental Representative upon request.
- .3 When unforeseen or peculiar safety-related hazard, or condition occur during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction and advise Departmental Representative verbally and in writing.

1.16 MINIMUM
SITE SAFETY RULES

- .1 Notwithstanding requirement to abide by federal and provincial health and safety regulations; ensure the following minimum safety rules are obeyed by persons granted access to Work Site:
 - .1 Wear appropriate PPE pertinent to the Work or assigned task; minimum being hard hat, safety footwear, safety glasses and hearing protection.
 - .2 Immediately report unsafe condition at site, near-miss accident, injury and damage.
 - .3 Maintain site and storage areas in a tidy condition free of hazards causing injury.
 - .4 Obey warning signs and safety tags.
- .2 Brief persons of disciplinary protocols to be taken for non compliance.

1.17 CORRECTION OF
NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative will stop Work if non-compliance of health and safety regulations is not corrected in a timely manner.

1.18 INCIDENT
REPORTING

- .1 Investigate and report the following incidents to Departmental Representative:
 - .1 Incidents requiring notification to Provincial Department of Occupational Safety and Health, Workers Compensation Board or to other regulatory Agency.
 - .2 Medical aid injuries.
 - .3 Property damage in excess of \$10,000.00,
 - .4 Interruptions to Facility operations resulting in an operational lost to a Federal department in excess of \$5000.00.
- .2 Submit report in writing.

-
- 1.19 HAZARDOUS PRODUCTS .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS).
- .2 Keep MSDS data sheets for all products delivered to site.
- .1 Post on site.
- .2 Submit copy to Departmental Representative.
- .3 For interior work in an occupied Facility, post additional copy in one or more publically accessible locations.
- 1.20 BLASTING .1 Blasting or other use of explosives is not permitted on site without prior receipt of written permission and instructions from Departmental Representative.
- 1.21 POWDER ACTUATED DEVICES .1 Use powder actuated fastening devices only after receipt of written permission from Departmental Representative.
- 1.22 CONFINED SPACES .1 Abide by occupational health and safety regulations regarding work in confined spaces.
- 1.23 SITE RECORDS .1 Maintain on Work Site copy of safety related documentation and reports stipulated to be produced in compliance with Acts and Regulations of authorities having jurisdiction and of those documents specified herein.
- .2 Upon request, make available to Departmental Representative or authorized Safety Officer for inspection.
- 1.24 POSTING OF DOCUMENTS .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on Work Site in accordance with Acts and Regulations of Province having jurisdiction.
-

- 1.24 POSTING OF DOCUMENTS
(Cont'd)
- .2 Post other documents as specified herein,
including:
- .1 Site specific Health and Safety Plan
 - .2 WHMIS data sheets

1.1 RELATED WORK

- .1 Section 01 74 22: CONSTRUCTION DEMOLITION WASTE MANAGEMENT and DISPOSAL.
- .2 Section 01 14 10 SCHEDULING and MANAGEMENT of the WORK

1.2 DEFINITIONS

- .1 Hazardous Material: Product, substance, or organism that is used for its original purpose; and that is either dangerous goods or a material that may cause adverse impact to the environment or adversely affect health of persons, animals, or plant life when released into the environment.

1.3 FIRES

- .1 Fires and burning of rubbish on site not permitted.

1.4 HAZARDOUS MATERIAL HANDLING

- .1 Store and handle hazardous materials in accordance with applicable federal and provincial laws, regulations, codes and guidelines. Store in location that will prevent spillage into the environment
 - .2 Label containers to WHMIS requirements and keep MSDS data sheets on site for all hazardous materials.
 - .3 Maintain inventory of hazardous materials and hazardous waste stored on site. List items by product name, quantity and date when storage began.
 - .4 Store and handle flammable and combustible materials in accordance with National Fire Code.
 - .5 Transport hazardous materials in accordance with federal Transportation of Dangerous Goods Regulations and applicable Provincial regulations.
-

1.5 DISPOSAL OF
WASTES

- .1 Do not bury rubbish and waste materials on site.
- .2 Do not dispose of hazardous waste or volatile materials, such as mineral spirits, paints, thinners, oil or fuel into waterways, storm or sanitary sewers or waste landfill sites.
- .3 Dispose of hazardous waste in accordance with applicable federal and provincial laws, regulations, codes and guidelines.

1.6 POLLUTION
CONTROL

- .1 Maintain temporary erosion and pollution control features installed under this contract.
- .2 Control emissions from equipment and plant to local authorities emission requirements.
- .3 Prevent sandblasting and other extraneous materials from contaminating air beyond application area, by providing temporary enclosures.
- .4 Report, spills of petroleum and other hazardous materials as well as accidents having potential of polluting the environment to Federal and Provincial Department of the Environment.
 - .1 Notify Departmental Representative and submit a written spill report to Departmental Representative within hours of occurrence.

1.1 GENERAL

- .1 Work of this Contract must not disrupt the daily operations of the Institution and shall be carried out in such a way to ensure that security at the Institution is maintained at all times.
- .2 Abide by all rules and procedures specified herein and with all directives given by the Director.

1.2 DEFINITIONS

- .1 Where used, the following terms shall be deemed to have the meaning stated herein.
- .2 Institution: means the Penitentiary or Correctional Facility where the Work will be carried out.
- .3 Director: means the person in charge of the Correctional Institution or Penitentiary where the Work will be carried out and includes any authorized person at the Facility, as designated by the Director, to provide directions on his/her behalf.
- .4 Contraband: means any of the following:
 - .1 An intoxicant, including alcoholic beverages, drugs and narcotics;
 - .2 A weapon or a component thereof, ammunition for a weapon, and any other object that is designed to kill, injure or disable a person or that is altered so as to be capable of killing, injuring or disabling a person, when possessed without prior authorization;
 - .3 An explosive or a bomb or a component thereof;
 - .4 Currency over the prescribed limit of 50.00 dollars and;
 - .5 Any other item, as deemed by the Director, to pose a risk to the security of a Penitentiary or to the safety of persons, when that item is possessed without prior authorization from the Director.
- .5 Smoking not permitted on Institutional property. Unauthorized smoking items: means all smoking items including, but not limited to, cigarettes, cigars, tobacco, chewing or snuffing tobacco, cigarette making machines, matches and lighters.

1.2 DEFINITIONS
(Cont'd)

- .6 Commercial vehicle: means any motor vehicle used to transport materials, equipment and tools to the site as required for construction purposes.
- .7 CSC: means the Department of Correctional Service Canada.
- .8 Construction employee: means any person working for the General Contractor or subcontractor(s), commercial vehicle or equipment operator, material supplier and personnel from testing, inspection or regulatory agencies who needs to circulate on the Institution's property as part of the Work.
- .9 Departmental Representative: means the person as defined in the General Conditions of the Contract for projects managed by Public Works and Government Services Canada (PWGSC) or the Project Manager for projects managed by Correctional Service Canada (CSC).
- .10 Perimeter: means the fenced or walled area of the Institution that restrains the movement of the inmates.
- .11 Construction zone: means the area as shown on the contract drawings and as described below where the Contractor will be allowed to work. This area may or may not be isolated from the security area of the Institution.
 - .1 In general, Contractor's work activities and movement is limited to the yard beside the building B6 and the masonry security wall around the Institution, and the area designated by the Institution during the startup meeting.

1.3 PRELIMINARY
PROCEEDINGS

- .1 Prior to commencement of work, the Contractor shall meet with the Director to:
 - .1 Discuss the nature and extent of all activities involved in the work of this contract.
 - .2 Obtain security rules, regulations and procedures in force at the Institution and directives to be followed by Contractor and all construction employees during the entire course of the work.

1.3 PRELIMINARY
PROCEEDINGS
(Cont'd)

- .2 The Departmental Representative will coordinate a pre-construction meeting between Contractor, the Director and Facility security personnel who will provide details on site security requirements.
- .3 The Contractor shall:
 - .1 Ensure that all construction employees are aware of the CSC security requirements.
 - .2 Ensure that a copy of the CSC security requirements is prominently displayed at the work site at all times.
 - .3 Co-operate with Institutional staff in ensuring that security requirements and procedures are stringently followed by all construction employees.
- .4 Any infraction of site security requirements by the Contractor or by a construction employee could result in the immediate removal of the offending party or person from the site.

1.4 WORKER
SECURITY CLEARANCE

- .1 Security clearance must be obtained from Correctional Service Canada (CSC) for all construction employees who needs to circulate on the Institution's property during the course of the Work.
 - .1 Applicable security application forms will be provided by the Departmental Representative.
 - .2 Have forms filled out by each worker.
- .2 Submit to the Director:
 - .1 A list of the names with date of birth of all construction employees;
 - .2 Completed security clearance form for each person
- .3 No person will be admitted inside the Institution without a valid CSC Security Clearance in place and a recent picture identification, such as a provincial driver's permit, to show proof of his identity.
 - .1 Security clearances obtained from other CSC Institutions are not valid at the Institution where the work of this contract will take place.
- .4 Allow two (2) weeks for processing of security clearances.

1.4 WORKER
SECURITY CLEARANCE
(Cont'd)

- .5 Be aware that facial photographs of security cleared construction employees may be taken as deemed required by the Director.
 - .1 These photographs may be posted for display at appropriate locations in the Institution or placed into an electronic database for identification purposes.
 - .2 Photo ID cards may also be issued to each construction employee to be donned while on site. ID cards will be left at the designated security entrance to be picked up by each person upon arrival at the Institution and must be prominently displayed on the person's clothing at all times.

- .6 CSC Security Clearance will be denied and entry into the Institution will be refused to any person which the Director has reason to believe may be a security risk to the Facility's operations.
 - .1 Also, a person will be subject to the immediate removal from the Institution if he/she:
 - .1 Appears to be under the influence of alcohol, drugs or narcotics.
 - .2 Behaves in an unusual disorderly manner.
 - .3 Is found in possession of contraband.

- .7 Facilitate security clearance application process:
 - .1 Provide copy of security clearance form to all workers including those of sub-contractors.
 - .2 Provide a list of names and birth dates for all persons who require security clearance to the Departmental Representative.
 - .3 Coordinate and expedite submissions from the various subcontractors.
 - .4 Brief and assist applicants in preparing and submitting the required application form and related documentation.
 - .5 Review application form of each applicant for completeness before submission.
 - .6 Have each worker keep a copy of their completed application form in case the initial submission gets lost.
 - .7 Submit documentation in an organized manner with transmittal letter clearly identifying the project for which worker security clearance is being requested.

1.4 WORKER .7
SECURITY CLEARANCE
(Cont'd)

(Cont'd)
.8 Send submission(s) to the approved
mailing address provided by the Departmental
Representative.

1.5 VEHICLES .1

- .1 All unattended vehicles on the Institution's
property shall have their windows, doors and
trunks closed and locked at all times. Keys
must be removed and kept securely in the
possession of the vehicle's owner or with an
employee of the Contractor or subcontractor
who owns the vehicle.
- .2 The Director may limit at any time the number
and type of vehicles allowed within the
Institution.
- .3 Drivers of vehicles simply delivering
materials to the site do not require security
clearance but shall remain inside their
vehicle for the entire duration that the
vehicle is on the Institution's property. This
is of particular importance for vehicles
entering the Institution's secure perimeter
area in which case the vehicle must be
escorted by Institutional staff or
Commissionaires while in that area.
- .4 If the Director permits office and/or storage
trailers to be left inside the secure
perimeter area of the Institution, their
exterior doors shall be kept locked at all
times and windows securely locked when trailer
is unoccupied. Additionally, windows shall be
covered with expanded metal mesh secured in
place. All storage trailers, whether inside
and outside of the secure perimeter area must
be kept locked when not in use.

1.6 PARKING OF .1
VEHICLES

- .1 Director will designate a location on site,
outside the secure perimeter area, where
construction employee vehicles may be parked
during workshifts.
- .2 All other areas are prohibited and vehicles
are subject to being removed by the
Institution with towing costs borne by their
owner.

1.7 SHIPMENTS

- .1 All shipments of materials, equipment and tools shall be clearly marked, addressed to the attention of the project title and Contractor's name to avoid confusion with the Institution's own shipments.
- .2 Contractor shall have designated employee(s) on site to receive and take possession of all deliveries and shipments.
- .3 **Under no circumstances** will personnel of the Institution accept delivery of materials, equipment and tools designated for use by the Contractor in the Work.

1.8 TELEPHONES

- .1 Telephone landlines, facsimile machines and computers with internet connections are not permitted within the secure perimeter of the Institution unless prior approval is obtained from the Director.
- .2 If approved, locate telephones, facsimile machines and computers with internet connections only where designated by the Director and in such location where they are not accessible to Inmates.
 - .1 Equip all computers with approved password protection features which will block internet connection to unauthorized computer users.
- .3 Wireless cellular and digital telephones, including but not limited to devices for telephone messaging, pagers, BlackBerries, telephone used as 2-way radios, are not permitted within the secure perimeter of the Institution unless prior approval is obtained from the Director.
 - .1 Should wireless cellular telephones be permitted, the owner/user of such device shall not permit it's use by any Inmate.
- .4 The Director may approve but limit the use of two way radios.

1.9 WORK HOURS

- .1 Be aware that for security reasons the days and hours which Contractor will be permitted to perform work at the site are limited to:
-

-
- 1.9 WORK HOURS
(Cont'd)
- .1 (Cont'd)
 - .1 Weekdays only from Monday to Friday and between the hours of 08:00 and 16:00.
 - .2 Work will **not** be permitted during evenings, nighttime, weekends and on statutory holidays without the permission of the Director. A minimum of two days (48 hours) advance notice will be required to obtain the necessary permission.
- 1.10 OVERTIME WORK
- .1 No overtime work will be allowed at the end of a workshift.
 - .2 Where overtime work is deemed necessary at the end of a workshift to complete a critical component of the work, it shall be planned and requested a minimum of 48 hours beforehand for approval by the Director.
 - .3 Should unplanned overtime work occur due to an emergency situation, such as to complete a concrete pour or to make the work site safe and secure, the Contractor shall immediately advise the Director of this pending situation and stringently follow all directions given by the Director.
 - .4 Extra Costs: Note that when overtime work or off-hour work on weekends and statutory holidays is approved by the Director, be aware that extra CSC security staff or commissionaires may need to be posted at the Institution to maintain security surveillance. The costs for such service will be charged to the Contractor in the form of a financial assessment to the Contract.
- 1.11 TOOLS AND EQUIPMENT
- .1 Make a complete list of all tools and equipment brought on site for use in the work. Provide copy of the list to the Director and to Departmental Representative.
 - .2 Maintain and update list during the entire course of the Work.
 - .3 Keep all tools and equipment under constant supervision. This is of particular importance for power-driven and cartridge-driven tools,
-

-
- 1.11 TOOLS AND EQUIPMENT
(Cont'd)
- .3 (Cont'd)
cartridges, files, saw blades, rod saws, wire, rope, ladders as well as all types of jacking devices.
 - .4 Store all tools and equipment in lockable tool boxes and place in approved and secure locations.
 - .5 Lock tool boxes when not in use. Keys shall remain in the possession of employees designated by Contractor.
 - .6 Scaffolding: Store and securely lock scaffolding components when not erected. When erected, secure against unauthorized disassembly in manner approved by the Director.
 - .7 Immediately report to the Director any missing tools and equipment.
 - .8 Tool Check: Be aware that CSC security personnel will conduct tool/equipment checks during the course of the Work against the list provided by Contractor. Frequency of checks to be as follows:
 - .1 At commencement and completion of the project.
 - .2 Weekly basis when the construction period is greater than 1 week.
 - .9 Controlled items: entry and use of certain tools and equipment, such as cartridges and hacksaw blades, are highly controlled at the Institution. The Director will determine and advise which items are to be controlled.
 - .1 Controlled items will be given to the Contractor at the beginning of each workday in quantities as required for 1 day's work.
 - .2 All controlled items must be returned to CSC security personnel at the end of each day including used blades, cartridges etc...
 - .10 When propane or natural gas is used as fuel for construction heaters, the Contractor shall provide an employee to supervise that work site during non-working hours.
-

1.12 KEYS

- .1 Security Hardware Keys:
 - .1 Arrange and ensure that keys for security door hardware are delivered directly by the hardware Supplier/Installer to the Institution's designated Security Maintenance Officer (SMO).
 - .2 The SMO will provide written receipt to Contractor for security keys received.
 - .3 Provide a copy of such receipt to the Departmental Representative.

- .2 Construction Keys:
 - .1 Supply and install construction cylinders on all new doors and keep such doors locked during the entire construction period.
 - .2 Instruct construction employees on the care and safekeeping of keys assigned to them to ensure safe custody of construction keys.
 - .3 Construction cylinders shall only be removed and be replaced with operational cylinders at such time as deemed appropriate by the Director. The SMO will, in conjunction with the lockset manufacturer:
 - .1 Prepare an operational keying schedule.
 - .2 Accept the operational keys and cylinders directly from the lockset manufacturer.
 - .3 Arrange for removal and return of the construction cylinders and install the operational cylinders in all locks.
 - .4 Upon putting operational security keys into use, an approved security escort designated by the Director will thereafter obtain specific keys from the SMO and open those doors as required by Contractor to access work areas.
 - .5 Contractor shall issue instructions to all construction employees advising them that all security keys must always remain with the security escort.

1.13 SECURITY
HARDWARE

- .1 Turn over to Director all security hardware removed as part of the work. This includes all items intended for disposal as well as those for temporary safekeeping until ready for reinstallation as part of the work.

1.14 PRESCRIPTION DRUGS .1

Construction employees who are required to take prescription drugs during the workday shall obtain approval from the Director beforehand and shall only bring on site a one days supply each day.

1.15 SMOKING RESTRICTIONS .1

Contractor and construction employees are not permitted to:

.1 Smoke inside the Institution or outdoors within the secure perimeter of the Facility and;

.2 Must not possess unauthorized smoking items within the secure perimeter of the Institution.

.2 All persons found in violation of this directive shall immediately cease smoking and dispose of any unauthorized smoking items. If violation persist, such persons will be removed from the Institution's property.

.3 Smoking on the Institution's property is only permitted outdoors, outside of the secure perimeter of the Institution and in a location designated by the Director.

1.16 CONTRABAND .1

Weapons, ammunition, explosives, alcoholic beverages, drugs and narcotics are considered contraband by the Institution and are strictly prohibited on the Institution's property.

.2 The discovery of contraband on the construction site and the identification of the person(s) responsible for the contraband shall be reported immediately to the Director.

.3 Contractor shall be vigilant with all construction employees and suppliers in ensuring that no contraband items are brought on site. Advise all persons that the discovery of contraband will result in the cancellation of their security clearance and their immediate removal from the site. Serious infractions may result in the removal of the Contractor or subcontractor from the Institution's property for the duration of the Contract.

-
- 1.16 CONTRABAND (Cont'd) .4 Presence of arms and ammunition found in vehicles owned by Contractor, subcontractors, suppliers and construction employees will result in the immediate cancellation of security clearance for the driver of that vehicle.
- 1.17 SEARCHES .1 All vehicles and persons entering Institutional property may be subject to search.
- .2 When the Director suspects, on reasonable grounds, that a construction employee is in possession of contraband, he/she may order that person to be searched.
- .3 Be aware that persons entering the Institution may be subject to screening of personal effects for traces of contraband drug residue.
- 1.18 OFF-HOURS SITE ACCESS .1 Construction personnel and commercial vehicles will not be permitted access to the Institution outside of the stipulated work hours specified, unless approved by the Director.
- 1.19 MOVEMENT OF VEHICLES .1 Be aware that commercial vehicles will only be allowed to enter or leave the secure perimeter of the Institution (ie: pass through the designated vehicle security gate) between the following hours of each day:
.1 From 07:45 AM to 11:00 AM and;
.2 From 13:00 PM to 15:30 AM.
- .2 Vehicles shall not be allowed to leave the Institution until an inmate count has been completed.
- .3 Vehicles must be escorted by approved CSC Staff or Commissionaire while inside the secure perimeter of the Institution.
- .4 Contractor shall provide 24 hours advance notice to the Director of the arrival of heavy equipment such as excavator, cranes, concrete trucks etc...to the site.
-

1.19 MOVEMENT
OF VEHICLES
(Cont'd)

- .5 Vehicles being loaded with soil or other debris at site, or any vehicle considered impossible to search, must be under continuous supervision by Institutional staff or Commissionaires working under the authority of the Director.
- .6 Commercial vehicles will only be allowed access onto the Institution's property when their contents are certified by the Contractor, or his representative, as being strictly necessary to the execution of the work.
- .7 Vehicles shall be refused access to Institutional property if, in the opinion of the Director, they contain any article which jeopardizes the security of the Institution.
- .8 Private vehicles of construction employees will NOT be allowed inside the secure perimeter area of a medium or maximum security Institution, except for a special situation as may be authorized by the Director.
- .9 Subject to approval from the Director, a vehicle may be used in the morning and evening of each day to transport construction employees to and from work areas inside the secure perimeter of the Institution. However the vehicle shall not be allowed to remain parked inside that area during the remainder of the workday.
- .10 Subject to prior approval from the Director, certain construction equipment may be permitted to remain in the work areas during nighttime or weekend provided such equipment is securely locked and has its battery removed. The Director may also require that the equipment be tied by chain and padlocked to a solid unmovable object.

1.20 MOVEMENT OF
PERSONS AT
THE INSTITUTION

- .1 Subject to the requirements of good security, the Director will permit the Contractor and construction employees as much freedom of action and movement in the work areas of the site as is possible.

1.23 CONTACT WITH
INMATES

- .1 Unless specifically authorized, it is forbidden to come into contact with inmates, to talk with them, to receive objects from them or to give them objects. Any construction employee doing any of the above will be removed from the site and his security clearance revoked.
- .2 Note that cameras are not allowed on CSC property.
- .3 Notwithstanding the above clause, if the Director approves the use of cameras, it is strictly forbidden to take pictures of inmates, CSC staff members or of any part of the Institution other than those areas under renovations as part of the Work.

1.24 COMPLETION
OF THE WORK

- .1 Upon completion of the work and/or prior to takeover and occupancy of the Facility, remove all materials, waste, tools and equipment that are not specified to remain at the Institution as part of the Work.

-
- 1.1 INSPECTION .1 Facilitate Departmental Representative's access to Work.
- .2 Give timely notice requesting inspection of Work designated for special tests, inspections or approvals by Departmental Representative or by inspection authorities having jurisdiction.
- .3 If Contractor covers or permits to be covered Work designated for special tests, inspections or approvals before such is made, uncover Work until particular inspections or tests have been fully and satisfactorily completed and until such time as Departmental Representative gives permission to proceed. Pay costs to uncover and make good such Work.
- .4 In accordance with the General Conditions, Departmental Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents.
- 1.2 INDEPENDENT INSPECTION AGENCIES .1 Departmental Representative may engage and pay for service of Independent Inspection and Testing Agencies for purpose of inspecting and testing portions of Work except for the following which remain part of Contractor's responsibilities:
- .1 Inspection and testing required by laws, ordinances, rules, regulations or orders of public authorities.
- .2 Inspection and testing performed exclusively for Contractor's convenience.
- .3 Testing, adjustment and balancing of laboratory equipment, mechanical and electrical equipment and systems.
- .4 Mill tests and certificates of compliance.
- .5 Tests as specified within various sections designated to be carried out by Contractor under the supervision of Departmental Representative.
- .6 Additional tests specified in Clause 1.2.2 below.
- .2 Where tests or inspections by designated Testing Agency reveal work not in accordance with contract requirements, Contractor shall pay costs for additional tests or inspections as Departmental Representative may require to verify acceptability of corrected work.
-

-
- 1.2 INDEPENDENT INSPECTION AGENCIES (Cont'd) .3 Employment of inspection and testing agencies by Departmental Representative does not relax responsibility to perform Work in accordance with Contract Documents.
- 1.3 ACCESS TO WORK .1 Furnish labour and facility to provide access to the work being inspected and tested.
- .2 Co-operate to facilitate such inspections and tests.
- .3 Make good work disturbed by inspections and tests.
- 1.4 PROCEDURES .1 Notify Departmental Representative sufficiently in advance of when work is ready for tests, in order for Departmental Representative to make attendance arrangements with Testing Agency. When directed by Departmental Representative, notify such Agency directly.
- .2 Submit representative samples of materials specified to be tested. Deliver in required quantities to Testing Agency. Submit with reasonable promptness and in an orderly sequence so as not to cause delay in Work.
- 1.5 REJECTED WORK .1 Remove and replace defective Work, whether result of poor workmanship, use of defective or damaged products and whether incorporated in Work or not, which has been identified by Departmental Representative as failing to conform to Contract Documents.
- .2 Make good damages to existing or new work resulting from removal or replacement of defective work.
- 1.6 TESTING BY CONTRACTOR .1 Provide all necessary instruments, equipment and qualified personnel to perform tests designated as Contractor's responsibilities herein or elsewhere in the Contract Documents.
-

1.6 TESTING BY
CONTRACTOR
(Cont'd)

- .2 At completion of tests, turn over 2 copies of fully documented test reports to Departmental Representative. Additionally, obtain other copies in sufficient quantities to enable one complete set of test reports to be placed in each of the maintenance manuals specified in Section 01 78 00.
- .3 Submit mill test certificates and other certificates as specified in various sections.
- .4 Submit adjustment and balancing reports for mechanical, electrical and other equipment systems specified in various trade sections.
- .5 Furnish test results.

- 1.1 SITE ACCESS AND PARKING .1 The Departmental Representative will designate Contractor's access to project site as well as parking facilities for equipment and workers.
- .2 The Contractor is advised that while parking facilities for his workers and subcontractors will be on property, such parking facilities may be remote from the actual site of the work. In any case, follow all instructions from the Departmental Representative in regards to parking facilities.
- 1.2 BUILDING ACCESS .1 Use only access doors, and circulation routes within building as designated by Departmental Representative to access interior work.
- 1.3 CONTRACTOR'S SITE OFFICE .1 Be responsible for and provide own site office, if required, including electricity, heat, lights and telephone. Locate site office as directed by Departmental Representative.
- 1.4 MATERIAL STORAGE .1 Locate site storage trailers where directed by Departmental Representative. Place in location of least interference with existing Facility operations.
- .2 Material storage space on site does not exist. Coordinate delivery to minimize storage period on site before being needed for incorporation into work.
- 1.5 SITE ENCLOSURES .1 Provide temporary fence where designated on by departmental and as agreed to by Site representative to enclose various construction areas of work site.
- .2 Make all gates lockable and provide keyed padlocks.
- .3 Obtain Departmental Representative's approval beforehand of location and layout of all temporary fence enclosures.
-

- 1.5 SITE ENCLOSURES .4 Provide warning signs affixed to all fenced areas, identifying those enclosed areas as "Construction Zones" with access restricted to only those persons so authorized by General Contractor.
(Cont'd)
- .5 Do not construe fencing as an acceptable replacement for pedestrian walkway and hoarding requirements specified below.
- 1.6 PEDESTRIAN WALKWAYS AND HOARDING
- .1 Ensure maximum safety and security to facility users during the course of work.
- .2 Be responsible for and provide temporary 2.4 metre high plywood construction hoarding when work is adjacent to circulation routes used by facility employees and inmates.
- .3 Maintain access and egress to building entrances and fire exits designated by Departmental Representative to remain in use.
- .4 Adequately frame and brace hoarding and walkways to resist site conditions.
- .5 Erect such protective devices during Facility's non-operational off hour periods.
- .6 Obtain Departmental Representative's concurrence prior to removal of hoarding and walkways.
- 1.7 INTERIOR HOARDING.1 Erect hoarding inside building to isolate construction areas and protect occupants for duration of work.
- .2 Construct hoarding as follows:
- .1 Height: to underside of ceiling above.
 - .2 Framing type: 38x89 wood studs spaced at 400 o/c.
 - .3 Covering: 19 mm thick plywood sheathing.
 - .4 Sealed to abutting surfaces.
 - .5 Access Doors: 1 quantity wood pedestrian door dust tight, lockable.
-

-
- 1.8 INTERIOR DUST CONTROL AND DUST BARRIERS
- .1 Control creation and spread of dust and dirt to building interior and in particular to areas within premises still under use by occupants.
 - .2 Develop and implement a dust control plan, addressing effective measures to carry out work with least amount of dust being created and propagated.
 - .1 Carefully evaluate the type of work to be undertaken and the physical layout of each work area on site.
 - .2 Provide specifically tailored strategy for each work area.
 - .3 Pre-determine location and placement of dust barriers to confine resulting dust to immediate work area.
 - .4 Inform Departmental Representative of the proposed dust control measures to be followed at each work area and for each major dust generating activities. Obtain Departmental Representative's approval before proceeding with work.
 - .3 Dust control plan to incorporate as a minimum the following dust protection and cleaning requirements:
 - .1 Erect dustproof partitions completely around work area to fully isolate construction from other parts of the building.
 - .2 Construct hoarding/dust partitions as follows:
 - .1 Use 10 mm polyethylene installed and sealed tightly to abutting walls, ceilings and floor with continuous duct tape along all edges and seams. Support in position with 38 x 89 wood framing at 400 mm o.c. Locate seams only at framing members and overlap sheathing by minimum of 150 mm.
 - .2 Use 19 mm thick plywood installed to wood stud framing spaced at 400 o.c.
 - .1 Erect from floor to underside of ceiling above, sheathing applied to occupied side of partition. Install polyethylene beneath plywood sheathing.
 - .2 Scribe, cut and fit sheathing tight to shape of structural steel, deck profile and to other obstructions in ceiling space and abutting walls.
-

-
- 1.8 INTERIOR DUST .3 (Cont'd)
CONTROL AND .2 (Cont'd)
DUST BARRIERS .2 (Cont'd)
(Cont'd) .3 Use compressable neoprene
gaskets around perimeter of
partition and at all protrusions to
achieve airtight construction.
- .3 Provide a "dust tight" and lockable
access door(s) within dust partition or
between rooms for worker entry into work area.
This is of particular importance for
situations where excessive dust will be
generated.
- .4 Provide additional dust barriers, placed
tightly to underside of the floor/roof deck
above, in locations where existing walls are
used as part of the dust barrier system but
simply terminate at the finished ceiling level
resulting in an open space above, or other
similar condition, permitting dust to migrate
beyond the construction areas.
- .5 Make all dust barriers airtight,
effectively blocking and stopping all dust
migration.
- .6 Inspect dust barriers at various
intervals during each work shift. Immediately
fix tears, unsealed edges and maintain
barriers effectively sealed for the entire
work duration.
- .7 Immediately clean areas in use by
occupants contaminated by work.
- .1 Vacuum, wash floors and walls.
Remove accumulated dust from all
surfaces. Clean and remove smears, scuffs
and marks.
- .4 Meager attempts at controlling dust will not
be tolerated. Failure to provide effective
dust control during work and to perform
satisfactory cleaning thereafter will result
in Departmental Representative to proceed and
obtain a separate cleaning service agency to
perform cleaning to tenant's satisfaction with
cost for such services being charged against
this Contract in the form of financial
holdbacks.
- .5 Construction of dust barriers, enclosures and
placement of temporary protective devices to
be performed during Facility non-operational
off-hour periods.
-

1.9 SANITARY
FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances. Facility to be located outside Institution's perimeter wall.
- .2 Post notices and take such precautions as required by local health authorities. Keep area and premises in sanitary condition.

1.10 POWER

- .1 Power supply is available and will be provided for construction usage at no cost.
 - .1 Make arrangements for the use of such services through the Departmental Representative.
 - .2 Departmental Representative will designate and approve each location of existing power source to which connections can be made to obtain temporary power service.
 - .3 Connect to existing power supply in accordance with Canadian Electrical Code.
- .2 Provide and pay all costs to supply and install temporary cabling, panelboards, switching devices and other equipment as required to connect into power source, provide adequate ground fault protection and extend power supply from existing source to work areas. Perform work and make all connections in accordance with the Canadian Electrical Code, in compliance with the federal and provincial Occupational Health and Safety Regulations as specified in section 01 35 29 and to lockout requirements specified in section 01 35 25.
- .3 Provide and maintain temporary lighting to conduct work. Ensure illumination level is not less than 162 lux in all locations.
- .4 Electrical power and lighting systems installed under this Contract can be used for construction requirements provided that guarantees are not affected thereby. Make good damage.

1.11 WATER SUPPLY

- .1 Water supply is available in existing building and will be provided for construction usage at no cost. Make arrangements for the use and transportation of such services to

-
- 1.11 WATER SUPPLY .1 (Cont'd)
(Cont'd) work area through the Departmental
Representative.
- .2 Permanent water supply system installed under
this Contract can be used for construction
requirements provided that guarantees are not
affected thereby. Make good damage.
- 1.12 VENTILATING .1 Provide temporary ventilation in enclosed
areas as required to:
.1 Facilitate progress of work.
.2 Provide adequate ventilation to meet
health regulations for safe working
environment.
- .2 Maintain strict supervision of operation of
temporary ventilating equipment to:
.1 Conform with applicable codes and
standards.
.2 Enforce safe practices.
.3 Prevent abuse of services.
.4 Prevent damage to finishes.
- .3 Upon acceptance of bid, Departmental
Representative may permit use of permanent
system providing agreement can be reached on:
.1 Conditions of use, special
equipment, protection and maintenance.
.2 Saving on Contract price.
.3 Provisions relating to warranties
on equipment.
- 1.13 CONSTRUCTION .1 Contractor or subcontractor advertisement
SIGN AND NOTICES signboards are not permitted on site.
- .2 Safety and Instruction Signs and Notices:
.1 Signs and notices for safety and
instruction shall be in both official
languages or commonly understood graphic
symbols conforming to CAN3-Z321-96(R2006).
- .3 Maintenance and Disposal of Site Signs:
.1 Maintain approved signs and notices in
good condition for duration of project and
dispose of off site on completion of project
or earlier if directed by Departmental
Representative.
-

1.14 REMOVAL OF TEMPORARY FACILITIES .1 Remove temporary facilities from site when directed by Departmental Representative.

1.1 GENERAL

- .1 Use new material and equipment unless otherwise specified.
- .2 Within 7 days of written request by Departmental Representative, submit following information for any materials and products proposed for supply:
 - .1 Name and address of manufacturer.
 - .2 Trade name, model and catalogue number.
 - .3 Performance, descriptive and test data.
 - .4 Compliance to specified standards.
 - .5 Manufacturer's installation or application instructions.
 - .6 Evidence of arrangements to procure.
 - .7 Evidence of manufacturer delivery problems or unforeseen delays.
- .3 Provide material and equipment of specified design and quality, performing to published ratings and for which replacement parts are readily available.
- .4 Use products of one manufacturer for equipment or material of same type or classification unless otherwise specified.
- .5 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.2 PRODUCT QUALITY

- .1 Contractor shall be solely responsible for submitting relevant technical data and independent test reports to confirm whether a product or system proposed for use meets contract requirements and specified standards.
 - .2 Final decision as to whether a product or system meets contract requirements rest solely with the Departmental Representative in accordance with the General Conditions of the Contract.
-

1.3 ACCEPTABLE
MATERIALS AND
ALTERNATIVES

- .1 Acceptable Materials: When materials specified include trade names or trade marks or manufacturer's or supplier's name as part of the material description, select and only use one of the names listed for incorporation into the Work.
- .2 Alternative Materials: Submission of alternative materials to trade names or manufacturer's names specified must be done during the bidding period following procedures indicated in the Instructions to Bidders.
- .3 Substitutions: After contract award, substitution of a specified material will be dealt with as a change to the Work in accordance with the General Conditions of the Contract.

1.4 MANUFACTURERS
INSTRUCTIONS

- .1 Unless otherwise specified, comply with manufacturer's latest printed instructions for materials and installation methods to be used. Do not rely on labels or enclosure provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Departmental Representative in writing of any conflict between these specifications and manufacturers instructions, so that Departmental Representative will designate which document is to be followed.

1.5 AVAILABILITY

- .1 Immediately notify Departmental Representative in writing of unforeseen or unanticipated material delivery problems by manufacturer. Provide support documentation as per clause 1.1.2 above.

1.6 WORKMANSHIP

- .1 Ensure quality of work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed.
 - .2 Remove unsuitable or incompetent workers from site as stipulated in the General Conditions of the Contract.
-

1.6 WORKMANSHIP
(Cont'd)

- .3 Ensure cooperation of workers in laying out work. Maintain efficient and continuous supervision on site at all times.
- .4 Coordinate work between trades and subcontractors. See section 01 14 10 in this regard.
- .5 Coordinate placement of openings, sleeves and accessories.

1.7 FASTENINGS -
GENERAL

- .1 Provide metal fastenings and accessories in same texture, colour and finish as base metal in which they occur. Prevent electrolytic action between dissimilar metals. Use non-corrosive fasteners, anchors and spacers for securing exterior work and in humid areas.
- .2 Space anchors within limits of load bearing or shear capacity and ensure that they provide positive permanent anchorage. Wood or organic material plugs not acceptable.
- .3 Keep exposed fastenings to minimum, space evenly and lay out neatly.
- .4 Fastenings which cause spalling or cracking of material to which anchorage is made, are not acceptable.
- .5 Do not use explosive actuated fastening devices unless approved by Departmental Representative. See section on Health and Safety Requirements in this regard.

1.8 FASTENINGS -
EQUIPMENT

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified.
- .3 Bolts may not project more than one diameter beyond nuts.
- .4 Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur and, use resilient washers with stainless steel.

1.9 STORAGE,
HANDLING AND
PROTECTION

- .1 Deliver, handle and store materials in manner to prevent deterioration and soiling and in accordance with manufacturer's instructions when applicable. Provide same degree of protection to materials supplied by Departmental Representative.
- .2 Store packaged or bundled materials in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work. Provide additional cover where manufacturer's packaging is insufficient to provide adequate protection.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Store cementitious products clear of earth or concrete floors, and away from walls.
- .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
- .6 Store sheet materials and lumber on flat, solid supports and keep clear of ground. Slope to shed moisture.
- .7 Store and mix paints in heated and ventilated room. Remove oily rags and other combustible debris from site daily. Take every precaution necessary to prevent spontaneous combustion.
- .8 Immediately remove damaged or rejected materials from site.
- .9 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

1.10 CONSTRUCTION
EQUIPMENT AND PLANT

- .1 On request, prove to the satisfaction of Departmental Representative that the construction equipment and plant are adequate to manufacture, transport, place and finish work to quality and production rates specified. If inadequate, replace or provide additional equipment or plant as directed.

1.10 CONSTRUCTION .2 Maintain construction equipment and plant in
EQUIPMENT AND PLANT good operating order.

(Cont'd)

- 1.1 GENERAL
- .1 Conduct cleaning and disposal operations to comply with local ordinances and anti-pollution laws.
 - .2 Store volatile waste in covered metal containers, and remove from premises at end of each working day.
 - .3 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.
- 1.2 MATERIALS
- .1 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.
- 1.3 CLEANING DURING CONSTRUCTION
- .1 Maintain work areas in a tidy condition, free from accumulations of waste material and debris. Clean areas on a daily basis.
 - .2 Keep building entrances, and occupied areas of building in a clean dust free condition at all times. Conduct thorough cleaning of these areas at end of each workshift when used by workers or affected by the Work.
 - .3 Provide on-site lockable metal containers for collection of waste materials and debris. Locate where approved and directed by Departmental Representative.
 - .4 Use separate collection bins, clearly marked as to purpose, for source separation and recycling of waste and debris in accordance with waste management requirements specified.
 - .5 Remove waste materials, and debris from site on a daily basis.
 - .6 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.
 - .7 Provide dust barriers, dividers, seals on doors and employ other dust control measures as required to ensure that dust and dirt, generated by work, are not transmitted to
-

1.3 CLEANING DURING .7
CONSTRUCTION
(Cont'd)

(Cont'd)
other existing areas of building. Should dust migrate into adjacent areas of building, employ such means as may be necessary to immediately clean all contaminated surfaces to the satisfaction of the Departmental Representative.

.1 See Section 01 50 00 for requirements on dust control and for erection of dust partitions.

1.4 FINAL CLEANING .1

In preparation for acceptance of the completed work perform final cleaning.

.2 Remove grease, dust, dirt, stains, labels, fingerprints, marks and other foreign materials, from interior and exterior finished surfaces. Clean and polish surfaces including glass, mirrors, hardware, stainless steel, chrome, baked enamel, mechanical and electrical fixtures.

.3 Replace items with broken pieces, scratches or disfigured.

.4 Clean lighting reflectors, lenses, and other lighting surfaces.

.5 Vacuum clean and dust building interiors.

.6 Wax, seal, shampoo or prepare floor finishes as recommended by manufacturer.

.7 Inspect finishes, fitments and equipment. Ensure specified workmanship and operation.

.8 Remove debris and surplus materials from crawl areas, and other accessible concealed spaces.

.9 Clean equipment, washroom fixtures to a sanitary condition.

1 DEFINITIONS

- .1 Hazardous Material: Product, substance, or organism that is used for its original purpose, and that is either dangerous goods or a material that may cause adverse impact to the environment or adversely affect health of persons, animals, or plant life when released into the environment.

2 WASTE MANAGEMENT

- .1 Incorporate environmental and sustainable practises in managing waste resulting from work.
- .2 Divert as much waste as possible from landfill.
- .3 Coordinate work of subtrades and subcontractors to ensure all possible waste reduction and recycling opportunities are taken. Follow waste management requirements specified in trade sections of the Specifications.
- .4 Reduce waste during installation of new materials. Undertake practices which will optimize full use of materials and minimize waste.
- .5 Develop innovative procedures to reduce quantity of waste generated by construction such as by delivering materials to site with minimal packaging etc...
- .6 Provide on-site facilities to collect, handle and store anticipated quantities of reusable, salvageable and recyclable materials.
- .7 During demolition and removal work separate materials and equipment at source, carefully dismantling, labelling and stockpiling alike items for the following purposes:
 - .1 Reinstallation into the work where indicated.
 - .2 Salvaging reusable items not needed in project which Contractor may sell to other parties.
 - .3 Sending as many items as possible to locally available recycling facility.
 - .4 Segregating remaining waste and debris into various individual waste categories for disposal in a "non-mixed state" as recommended by waste processing/landfill sites.

2 WASTE MANAGEMENT .8
(Cont'd)

- .8 Isolate product packaging and delivery containers from general waste stream. Send to recycling facility or return to supplier/manufacturer.
- .9 Send leftover material resulting from installation work for recycling whenever possible.
- .10 Establish methods whereby hazardous and toxic materials, and their containers used on site are properly handled, stored and disposed in accordance with applicable federal, provincial and municipal laws and regulations.

3 DISPOSAL
REQUIREMENTS

- .1 Burying or burning of rubbish and waste materials is prohibited.
- .2 Disposal of volatile materials, mineral spirits, oil, paint, and other hazardous materials into waterways, storm, or sanitary sewers is prohibited.
- .3 Dispose of waste only at approved waste processing facility or landfill sites approved by authority having jurisdiction.
- .4 Contact the authority having jurisdiction prior to commencement of work, to determine what, if any, demolition and construction waste materials have been banned from disposal in landfills and at transfer stations. Take appropriate action to isolate such banned materials at site of work and dispose in strict accordance with provincial and municipal regulations.
- .5 Transport and dispose of waste intended for waste processing plant or landfill facility in separated condition and to Operator's rules and recommendations in support of their effort to recycle, reduce and divert certain waste stream from general landfill.
- .6 Collect, bundle and transport salvaged materials to be recycled in separated categories and condition as directed by recycling facility. Ship materials only to approved recycling facilities.

3 DISPOSAL REQUIREMENTS .7 Sale of salvaged items by Contractor to other parties not permitted on site.

(Cont'd)

- 1.1 SECTION INCLUDES .1 Administrative procedures preceding inspection and acceptance of Work by Departmental Representative.
- 1.2 RELATED SECTIONS .1 Section 01 78 00 - Closeout Submittals.
- 1.3 INSPECTION AND DECLARATION .1 Contractor's Inspection: Coordinate and perform, in concert with subcontractors, an inspection and check of all Work. Identify and correct deficiencies, defects, repairs and perform outstanding items as required to complete work in conformance with Contract Documents.
- .1 Notify Departmental Representative in writing when deficiencies from Contractor's inspection have been rectified and that Work is deemed to be complete and ready for Departmental Representative's inspection of the completed work.
- .2 Departmental Representative's Inspection: Accompany Departmental Representative during all substantial and final inspections of the Work.
- .1 Address defects, faults and outstanding items of work identified by such inspections.
- .2 Advise Departmental Representative when all deficiencies identified have been rectified.
- .3 Note that Departmental Representative will not issue a Certificate of Substantial Performance of the work until such time that Contractor performs following work and turns over the specified documents:
- .1 Project record as-built documents;
- .2 Final Operations and Maintenance manuals;
- .3 Maintenance materials, parts and tools;
- .4 Compliance certificates from applicable authorities;
- .5 Reports resulting from designated tests;
- .6 Demonstration and training complete with user manuals;
- .7 Manufacturer's Guarantee certificates.
- .8 Testing, adjusting and balancing of equipment and systems complete with submission of test reports.
-

Observation cell door
replacement, Bldg 5, 6 & 7
Springhill Institution,
Springhill NS
p.n. R.061826.001

CLOSEOUT PROCEDURES

Section 01 77 00
Page 2

October 2013

1.3 INSPECTION AND .3
DECLARATION
(Cont'd)

(Cont'd)

.9 Commissioning of equipment and systems
specified.

.4 Correct all discrepancies before Departmental
Representative will issue the Certificate of
Completion.

- 1.1 RELATED SECTIONS
- .1 Section 01 14 10 SCHEDULING and MANAGEMENT of WORK.
 - .2 Section 01 33 00 - SUBMITTAL PROCEDURES.
 - .3 Section 01 77 00 - CLOSEOUT PROCEDURES.
 - .4 Section 08 34 60 - DETENTION DOOR HARDWARE
 - .5 Section 08 34 63 - DETENTION SECURITY METAL DOORS
 - .6 Section 09 91 23 - INTERIOR PAINTING.
- 1.2 SECTION INCLUDES
- .1 Project Record Documents.
 - .2 Operations and Maintenance data.
- 1.3 PROJECT RECORD DOCUMENTS
- .1 Departmental Representative will provide 2 white print sets of contract drawings and 2 copies of Specifications Manual specifically for 'AS-BUILT' purposes.
 - .2 Maintain at site one set of the contract drawings and specifications to record actual 'AS-BUILT' site conditions.
 - .3 Maintain up-to-date, real time as-built drawings and specifications in good condition and make available for inspection by the Departmental Representative upon request.
 - .4 'AS-BUILT': Drawings:
 - .1 Record changes in red ink on the prints. Mark only on one set of prints and at completion of work, neatly transfer notations to second set (also by use of red ink).
 - .2 Submit both sets to Departmental Representative prior to application for Certificate of Substantial Performance.
 - .3 Stamp all drawings with "As-Built Drawings". Label and place Contractor's signature and date.
 - .4 Show all modifications, substitutions and deviations from what is shown on the contract drawings or in specifications.
-

1.3 PROJECT RECORD .5
DOCUMENTS
(Cont'd)

Record following information:

- .1 Location of internal utilities and appurtenances concealed in construction, referenced to visible and accessible features of structure;
- .2 Field changes of dimension and detail;
- .3 Location of all capped or terminated services and utilities.
- .4 Chases for mechanical, electrical and other services;
- .5 All design details dimensioned and marked-up to consistently report finished installation conditions;
- .6 Any details produced in the course of the contract by the Departmental Representative to supplement or to change existing design drawings;
- .7 All change orders issued over the course of the contract must be documented on the finished 'AS-BUILT' documents, accurately and consistently depicting the changed condition as it applies to all affected drawing details.

.6 'AS-BUILT' Specifications: legibly mark in red each item to record actual construction, including:

.7 Maintain 'AS-BUILT' documents current as the contract progresses. Departmental Representative will conduct reviews and inspections of the documents on a regular basis. Failure to maintain as-builts current and complete to satisfaction of the Departmental Representative shall be subject to financial penalties in the form of progress payment reductions and holdback assessments.

1.4 REVIEWED
SHOP DRAWINGS

.1 Provide a complete set of all shop drawings reviewed for project to incorporate into each copy of the Operations & Maintenance manuals.

.2 Submit full sets at same time and as part of the contents of the Operation and Maintenance manuals specified.

1.5 OPERATIONS &
MAINTENANCE MANUAL

- .1 Operations & Maintenance Manual - Definition:
an organized compilation of operating and
maintenance data including detailed technical
information, documents and records describing
operation and maintenance of individual
products or systems as specified in individual
sections of the specifications.
- .2 Manual Language: final manuals to be in
English language.
- .3 Number of copies required:
 - .1 Submit 2 interim paper copies of the
manual for review and inspection by
Departmental Representative. Make revisions
and additions as directed and resubmit.
 - .2 Upon review and acceptance by
Departmental Representative, submit 4 final
paper copies and one electronic copy on
compact disc (pdf format). Interim copies are
not to be considered as part of the final
copies unless they have been fully revised and
are identical to the final approved version.
- .4 Submission Date: submit complete operation
and maintenance manual to Departmental
Representative 3 weeks prior to application
for Certificate of Substantial Performance of
the work.
- .5 Binding:
 - .1 Assemble, coordinate, bind and index
required data into Operation and Maintenance
Manual.
 - .2 Use vinyl, hard covered, 3 "D" ring
binders, loose leaf, sized for 215 x 280 mm
paper, with spine pocket.
 - .3 Where multiple binders are needed,
correlate data into related consistent
groupings.
 - .4 Identify contents of each binder on
spine.
 - .5 Organize and divide data following same
numerical system as the section numbers of the
Specification Manual.
 - .6 Dividers: separate each section by use
of cardboard dividers and labels. Provide
tabbed fly leaf for each individual product
and system and give description of product or
component.
 - .7 Type lists and notes. Do not hand write.
 - .8 Drawings, diagrams and manufacturers'
literature must be legible. Provide with

-
- 1.5 OPERATIONS & MAINTENANCE MANUAL (Cont'd)
- .5 Binding: (Cont'd)
- .8 (Cont'd)
reinforced, punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- .6 Manual Contents:
- .1 Cover sheet containing:
- .1 Date submitted.
- .2 Project title, location and project number.
- .3 Names and addresses of Contractor, and all Sub-contractors.
- .2 Table of Contents: provide full table of contents in each binder(s), clearly indicate which contents are in each binder.
- .3 List of maintenance materials.
- .4 List of spare parts.
- .5 List of special tools.
- .6 Original or certified copy of warranties and product guarantees.
- .7 Copy of approval documents and certificates issued by Inspection Authorities.
- .8 Copy of reports and test results performed by Contractor as specified.
- .9 Product Information (PI Data) on materials, equipment and systems as specified in various sections of the specifications.
Data to include:
- .1 List of equipment including manufacturer's name, supplier, local source of supplies and service depot(s). Provide full addresses and telephone numbers.
- .2 Nameplate information including equipment number, make, size, capacity, model number and serial number.
- .3 Parts list.
- .4 Installation details.
- .5 Operating instructions.
- .6 Maintenance instructions for equipment.
- .7 Maintenance instructions for finishes.
- .7 Shop drawings:
- .1 Include complete set of reviewed shop drawings into each copy of the operations and maintenance manual.
- .2 Fold and bind material professionally in a manner that corresponds with the specification section numbering system.
-

-
- 1.5 OPERATIONS & MAINTENANCE MANUAL
(Cont'd)
- .7 Shop drawings:(Cont'd)
.3 When large quantity of data is submitted, place into separate binders of same size as Operations & Maintenance binders.
- .8 Equipment and Systems Data: the following list indicates the type of data and extent of information required to be included for each item of equipment and for each system:
.1 Description of unit or system, and component parts. Give function, normal operation characteristics, and limiting conditions. Include complete nomenclature and commercial number of replaceable parts.
.2 Panel board circuit directories: provide electrical service characteristics, controls, and communications.
.3 Include installed colour coded wiring diagrams.
.4 Maintenance Requirements: include routine procedures and guide for trouble-shooting; disassembly, repair, and reassembly instructions; and alignment, adjusting, balancing, and checking instructions.
.5 Manufacturer's printed operation and maintenance instructions.
.6 Provide original manufacturer's parts list, illustrations, assembly drawings, and diagrams required for maintenance.
.7 Provide list of original manufacturer's spare parts, current prices, and recommended quantities to be maintained in storage.
.8 Include test and balancing reports.
.9 Additional requirements as specified in individual specification sections.
- .9 Materials and Finishes Maintenance Data:
.1 Building Products, Applied Materials, and Finishes: include product data, with catalogue number, size, composition, and colour and texture designations. Provide information for re-ordering custom manufactured products.
.2 Instructions for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
.3 Moisture-protection and Weather-exposed Products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental
-

1.5 OPERATIONS & .9
MAINTENANCE MANUAL (Cont'd)

- (Cont'd)
- .3 (Cont'd)
- agents and methods, and recommended schedule for cleaning and maintenance.
- .4 Additional Requirements: as specified in individual specifications sections.

1.6 SPARE PARTS, .1
TOOLS AND MAINTENANCE
MATERIALS

- .1 Provide spare parts, special tools and extra materials for maintenance purposes in quantities specified in individual specification sections.
- .2 Tag all items with associated function or equipment.
- .3 Provide items of same manufacture and quality as items in Work.
- .4 Deliver to site in well packaged condition. Store in location as directed by Departmental Representative.
- .5 Clearly mark as to contents indicating:
 - .1 Part number.
 - .2 Identification of equipment or system for which parts are applicable.
 - .3 Installation instructions or intended use as applicable.
 - .4 Name, address and telephone number of nearest supplier.
- .6 Prepare and submit complete inventory list of items supplied. Include list within Maintenance Manual.