

STANDARD MECHANICAL LEGEND AND SYMBOLS

HVAC		GENERAL	
SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION
	DUCT - SINGLE LINE		ELECTRIC UNIT HEATER
	RECTANGULAR DUCT - DOUBLE LINE FIRST DIM VISIBLE SIDE (mm)		WALL MOUNTED PROPELLER FAN
	ROUND DUCT		SQUARE INLINE CENTRIFUGAL FAN
	FLEXIBLE DUCT		ELECTRIC REHEAT COIL
	RETURN & EXHAUST DUCT RISER		DUCT MOUNTED HEATING COIL
	RETURN & EXHAUST DUCT AWAY		ROOF MOUNTED CENTRIFUGAL FAN - PLAN
	SUPPLY DUCT RISER		ROOF MOUNTED CENTRIFUGAL FAN - SECTION
	SUPPLY DUCT AWAY		COOLING COIL
	AIR IN DIRECTION		HEATING COIL
	AIR OUT DIRECTION		DOOR GRILLE
	SUPPLY DIFFUSERS		DOOR UNDERCUT
	RETURN AIR GRILLE		CENTRIFUGAL FAN
	CEILING MOUNTED AIR UNIT		THERMAL WELL
	CEILING ACCESS DOOR		PLATE & FRAME HEAT EXCHANGER
	DUCT INSPECTION DOOR		EXHAUST AIR PENTHOUSE
	BALANCING DAMPER		PIPE BREAK
	FIRE DAMPER		AIR CONDITIONING INDOOR UNIT
	SMOKE DAMPER		AIR HANDLING UNIT
	MOTORIZED DAMPER		CONDENSING UNIT
	BACKDRAFT DAMPER		MAKE-UP AIR UNIT (OUT DOOR AIR UNIT)
	FLOOR MOUNTED FIRE DAMPER		EXPANSION TANK
	INCLINED RISE (R) OR DROP (D) ARROW IN DIRECTION OF FLOW		AIR SEPARATOR
	MITERED ELBOW WITH TURNING VANES		WALL FIN HEATER
	ECCENTRIC TRANSITION		ELECTRICAL BASEBOARD HEATER
	CENTRIC TRANSITION		RETURN AIR
	PREHEAT COIL		EXHAUST AIR
	REHEAT COIL		DIRECT EXPANSION
	ELECTRIC DUCT HEATER		CONNECT TO EXISTING
	ENERGY RECOVERY VENTILATOR		
	HEAT RECOVERY VENTILATOR		

ANNOTATION	
SYMBOLS	DESCRIPTION
	EQUIPMENT TAG TYPE NUMBER
	DIFFUSER TAG TYPE SIZE [MM] AIRFLOW [L/S]
	VAV TAG VAV NUMBER VAV SIZE
	PHOTO NO. IDENTIFIER
	NOTE TAG

key plan



revision	description	date
04	ISSUED FOR TENDER	2013/10/29
03	ISSUED FOR 100% OWNER REVIEW	2013/07/25
02	SUBMITTED FOR 99% DESIGN	2011/07/18
01	ISSUED FOR REVIEW	2011/02/15

Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.



This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as approved by AECOM and its clients, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
**MECHANICAL LEGENDS
AND SYMBOLS
(SHEET 1 OF 2)**

drawn by
dessiné par L. TAURO

designed by
conçu par A. KABBANI

approved by
approuvé par D. DOVAS

bid offer
offre de projet O. TABAREZ project manager
administrateur de projets

project date
date du projet 2013-10-29

project no.
no. du projet R.033225.001

drawing no.
dessiné no. WDR-G-01

STANDARD PIPING AND PIPING LABEL SYMBOLS AND LEGEND

STANDARD PLUMBING AND DRAINAGE, VALVE SYMBOLS AND LEGEND

PIPING			
SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION
	STRAINER		METAL RESTRAINT JOINT - DOUBLE LINE
	REDUCER		HUB-SPIGOT JOINT - DOUBLE LINE
	FLANGE COUPLING ADAPTER		REDUCER - DOUBLE LINE
	FLANGED END JOINT		FLANGE COUPLING ADAPTER - DOUBLE LINE
	GROOVED END ADAPTOR FLANGE		FLANGED END JOINT - DOUBLE LINE
	GROOVED END JOINT		GROOVED END ADAPTOR FLANGE - DOUBLE LINE
	ECCENTRIC REDUCER		GROOVED END JOINT - DOUBLE LINE
	ELASTOMER BELLOWS EXPANSION JOINT		ECCENTRIC REDUCER - DOUBLE LINE
	METAL BELLOWS EXPANSION JOINT		ELASTOMER BELLOWS EXPANSION JOINT - DOUBLE LINE
	PIPE TO DRAIN		METAL BELLOWS EXPANSION JOINT - DOUBLE LINE
	TEE CONNECTION SIDE		BUSHING
	TEE CONNECTION DOWN		TEE CONNECTION SIDE - DOUBLE LINE
	TEE CONNECTION UP		TEE CONNECTION DOWN - DOUBLE LINE
	BRANCH CONNECTION - BOTTOM		TEE CONNECTION UP - DOUBLE LINE
	UNION		BRANCH CONNECTION - TOP
	RISER UP - STRAIGHT		UNION - DOUBLE LINE
	RISER UP - SIDE		RISER UP - STRAIGHT - DOUBLE LINE
	LATERAL DOWN		PIPE END
	LATERAL SIDE		LATERAL DOWN - DOUBLE LINE
	CROSS		LATERAL SIDE - DOUBLE LINE
	45 DEGREE ELBOW		CROSS - DOUBLE LINE
	90 DEGREE ELBOW		45 DEGREE ELBOW - DOUBLE LINE
	ELBOW DOWN		90 DEGREE ELBOW - DOUBLE LINE
	ELBOW UP		ELBOW DOWN - DOUBLE LINE
	PIPE CAP		ELBOW UP - DOUBLE LINE
	AIR-VACUUM RELEASE		PIPE CAP - DOUBLE LINE
	PRESSURE AND TEMPERATURE TEST PLUG		WEATHER PROOF COMBO
	GAUGE		PIPE ALIGNMENT GUIDE
	TURBINE METER		PIPE ANCHOR
	FLANGE CONNECTION		FLEXIBLE PIPE CONNECTION
	SUCTION GUIDE C/W STRAINER		WATER METER
	MULTI-FUNCTION VALVE (CHECK, ISOLATION AND BALANCING)		PUMP KIT WITH ACCESSORY
	MANUAL AIR VENT		PUMP
	AUTOMATIC AIR VENT		

PIPING LABEL	
SYMBOLS	DESCRIPTION
	DRAIN
	DOMESTIC COLD WATER
	HIGH TEMPERATURE HEATING WATER SUPPLY
	HIGH TEMPERATURE HEATING WATER RETURN
	REFRIGERANT DISCHARGE
	REFRIGERANT SUCTION
	REFRIGERANT LIQUID
	VENT

VALVES			
SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION
	GATE VALVE		BALL VALVE - DOUBLE LINE
	GLOBE VALVE		GLOBE VALVE - DOUBLE LINE
	BUTTERFLY VALVE		BUTTERFLY VALVE - DOUBLE LINE
	PLUG VALVE		PRESSURE GAUGE ISOLATING BALL VALVE - 1
	ECCENTRIC PLUG VALVE		PRESSURE RELIEF VALVE
	PINCH VALVE		BACKPRESSURE REGULATOR - SELF CONTAINED
	DIAPHRAGM VALVE		PRESSURE REDUCING INDICATOR VALVE
	CONE VALVE		RELIEF VALVE - PRESSURE AND TEMPERATURE
	BALL VALVE		BACKFLOW PREVENTER SET
	HOSE VALVE		BACKFLOW PREVENTER SET PRESSURE REDUCING PRINCIPLE
	CIRCUIT BALANCING VALVE		TRAP PRIMING DEVICE
	BALL CHECK	PLUMBING AND DRAINAGE	
	LOCKSHIELD GATE VALVE	SYMBOLS	DESCRIPTION
	LOCKSHIELD GLOBE VALVE		DIRECTION OF SLOPE DOWN
	CHECK VALVE		CLEAN OUT - ABOVE GRADE
	DOUBLE CHECK VALVE		P-TRAP
	2-WAY MOTORIZED VALVE		TRAP WITH CLEANOUT
	3-WAY MOTORIZED VALVE		FLOOR DRAIN
	ELECTRIC MOTORIZED VALVE		FUNNEL FLOOR DRAIN
	3-WAY VALVE		ROOF DRAIN
	DRAIN VALVE - HOSE END CONNECTION		HOSE BIBB
	MULTI-PORT VALVE - 1		BACKFLOW PREVENTER SET
	MULTI-PORT VALVE - 2		TRAP PRIMER DEVICE

key plan



04	ISSUED FOR TENDER	2013/10/29
03	ISSUED FOR 100% OWNER REVIEW	2013/07/25
02	SUBMITTED FOR 99% DESIGN	2011/07/18
01	ISSUED FOR REVIEW	2011/02/15
revision		date

Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.



This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as agreed by AECOM and its client, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
MECHANICAL LEGENDS AND SYMBOLS (SHEET 2 OF 2)

drawn by
dessiné par **L. TAURO**

designed by
conçu par **A. KABBANI**

approved by
approuvé par **D. DOVAS**

bid offer
offre **O. TABAREZ** project manager
administrateur de projets

project date
date du projet **2013-10-29**

project no.
no. du projet **R.033225.001**

drawing no.
dessiné no. **WDR-G-02**

MOTORIZED DAMPER SCHEDULE – WW03				
UNIT No.	LISTED SIZE (L x H)	TYPE	ASSOCIATED SYSTEM	REMARKS
MD-1	500x225	ON/OFF TWO POSITION	ENERGY RECOVERY VENTILATOR	1, 2, 3.
MD-2	600x600	ON/OFF TWO POSITION	ENERGY RECOVERY VENTILATOR	1, 2, 3.

NOTES:

- C/W AUXILIARY SWITCH
- FAIL SAFE ACTUATOR.
- 120V POWER SUPPLY TO DAMPER ACTUATOR BY DIVISION 26.

EXPANSION TANK SCHEDULE – WW03									
UNIT No.	SYSTEM SERVED	LOCATION	MANUFACTURER & MODEL NO.	DIMENSIONS		VOLUME (L)	WORKING PRESSURE (KPA)	WORKING TEMP. (°C)	REMARKS
				HEIGHT (mm)	DIAM. (mm)				
ET-1	WATER HEATING BOILER LOOP	MECHANICAL ROOM 130	-	635	305	35	862	115	1, 2.
ET-2	GLYCOL HEATING LOOP	MECHANICAL ROOM 130	-	305	254	30	1034	115	1, 2.

NOTES:

- C/W RING BASE, LIFTING RINGS AND AIR CHARGING VALVE.
- DESIGNED AND BUILT IN ACCORDANCE WITH ASME PRESSURE VESSEL CODE.

HEAT EXCHANGER SCHEDULE – WW03													
TAG No.	LOCATION	SERVICES	HOT SIDE (WATER)				COLD SIDE (45% PROPYLENE GLYCOL)				CAPACITY (kW)	LMTD (°C)	REMARKS
			INLET TEMP. (°C)	OUTLET TEMP. (°C)	FLOW (L/S)	PRESSURE DROP (kPa)	INLET TEMP. (°C)	OUTLET TEMP. (°C)	FLOW (L/S)	PRESSURE DROP (kPa)			
HEX-1	MECHANICAL ROOM 130	PRC-1 RC-1	93.33	82.22	0.352	34.47	71.11	82.22	0.378	34.47	15.86	11.11	1 - 10.

NOTES:

- BRAZED PLATE HEAT EXCHANGER, PLATE MATERIAL 316L SS
- 30 TOTAL PLATES, BRAZING MATERIAL, COPPER
- ESTIMATED WEIGHT (EMPTY/OPERATING) 2.72 KG/3.63 KG
- DESIGN TEMP. (MIN/MAX), HOT AND COLD SIDE, -190 °C/232 °C
- ALL INLET AND OUTLET CONNECTIONS, 19 MM MALE THREAD FRONT
- OVERALL DIMENSION (HXWD) 214X80X94 MM
- PRESSURE, DESIGN/TEST, HOT AND COLD SIDE, 3000 KPa/3613 KPa
- HOT SIDE NUMBER OF PASSES X CHANNELS 1X14
- COLD SIDE NUMBER OF PASSES X CHANNELS 1X15
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT

PUMP SCHEDULE – WW03												
UNIT No.	SYSTEM SERVED	LOCATION	TYPE	FLUID TYPE	FLOW (L/s)	HEAD (kPa)	MOTOR			RATED TEMP. (°C)	RATED PRESS. (kPa)	REMARKS
							kW	(RPM)	V/Ph/Hz			
P-1	HOT WATER HEATING SYSTEM	MECHANICAL ROOM 130	-	WATER	1.335	45	0.3	3600	208/1/60	110	1034	1, 2, 5
P-2	HOT WATER HEATING SYSTEM	MECHANICAL ROOM 130	-	WATER	1.335	45	0.3	3600	208/1/60	110	1034	1, 2, 5
P-3	GLYCOL HEATING SYSTEM	MECHANICAL ROOM 130	SYSTEM LUBRICATED IRON BODY CIRCULATOR	GLYCOL	0.378	89.67	0.27	3300	120/1/60	107	1034	1, 2, 4, 5
P-4	GLYCOL HEATING SYSTEM	MECHANICAL ROOM 130	SYSTEM LUBRICATED IRON BODY CIRCULATOR	GLYCOL	0.378	89.67	0.27	3300	120/1/60	107	1034	1, 2, 4, 5

NOTES:

- DUPLEX DUTY/STANDBY CONFIGURATION, WITH RUN TIME TOTALIZER & AUTO CHANGEOVER.
- MAGNETIC STARTER WITH HAND/OFF/AUTO SELECTOR SWITCH WITH AUXILIARY CONTACTS BY DIV.26.
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT.
- PROVIDE FLANGE IN-LINE, CAST IRON BODY, NORYL IMPELLER, CERAMIC SHAFT AND CARBON BEARINGS, MOTOR TO BE NON-OVERLOADING WITH ROTOR SHEATHED IN STAINLESS STEEL.
- PUMP MANUFACTURER SHALL BE ISO-9001 CERTIFIED.

COIL SCHEDULE – WW03													
TAG No.	LOCATION	CONSTRUCTION	NUMBER OF ROWS	CAPACITY (kW)	AIR				WATER				REMARKS
					FLOW (L/S)	TEMP. IN (°C)	TEMP. OUT (°C)	PRESS. DROP (Pa)	FLOW (L/S)	TEMP. IN (°C)	TEMP. OUT (°C)	PRESS. DROP (kPa)	
PRC-1	MECHANICAL ROOM 130 PRE-HEAT	TUBE: COPPER FIN: ALUMINUM CASING: GALVANIZED STEEL	1	6.7	405.5	-23	-9.4	20	0.14	93	81.5	2.1	1.
RC-1	MECHANICAL ROOM 130 RE-HEAT	TUBE: COPPER FIN: ALUMINUM CASING: GALVANIZED STEEL	1	8.14	235	4.15	20.5	25	0.17	93	81.5	3	1.

NOTES:

- COORDINATE INSTALLATION BASED ON COIL DIMENSIONS, REQUIRED FLANGES AND SERVICES LAYOUTS.

ENERGY RECOVERY VENTILATOR SCHEDULE – WW03																	
UNIT No.	UNIT LOCATION	MANUFACTURER & MODEL NO.	SYSTEM	FAN				FILTER	TEMPERATURE (°C)				ENERGY RECOVERED (kW)				REMARKS
				FLOW (L/S)	ESP (Pa)	MOTOR			WINTER		SUMMER		WINTER		SUMMER		
						(kW)	(V/Ph/Hz)		(TE)	(TL)	(TE)	(TL)	SENSIBLE	TOTAL	SENSIBLE	TOTAL	
ERV-1	MECHANICAL ROOM 130	-	SUPPLY AIR	405.5	200	0.4	208/1/60	WASHABLE FIBRE	9.4	4.15/3.11	30/23	27.3/21.3	6.6	9.6	1.32	3	1, 2, 3, 4, 5.
			EXHAUST AIR	235	125	0.4	208/1/60	WASHABLE FIBRE	21.1/12.4	-2/-2.7	24/17	29.8/18.6	6.6	9.6	1.32	3	1, 2, 3, 4, 5.

NOTES:

- UNITS WITH WASHABLE FIBRE FILTER.
- SHOP DRAWING SUBMITTAL TO INCLUDE SELECTION OF PREHEAT AND REHEAT COILS.
- COORDINATE INSTALLATION WITH SERVICES LAYOUT IN MECHANICAL ROOM 130.
- ERV SHALL BE SUPPLIED BY MANUFACTURER OF SPLIT SYSTEM. REFER TO NOTE No.3 IN CONDENSING UNIT (HEAT PUMP) SCHEDULE – WW03.
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT.

DIFFUSER, GRILLE AND REGISTER SCHEDULE							
TYPE	DESCRIPTION	BLADE SPACING (mm)	TYPE	SIZE	VOLUME CONTROL	DEFLECTION	REMARKS
A	SUPPLY AIR	19	LOUVERED STEEL REGISTER	REFER TO DRAWING	STEEL DAMPER	0°	1, 2, 6.
B	RETURN AIR	19	LOUVRED STEEL GRILLE	REFER TO DRAWING	NO	0°	1, 2, 6.
C	EXHAUST AIR	19	LOUVRED STEEL REGISTER	REFER TO DRAWING	STEEL DAMPER	45°	1, 2, 6.
D	SUPPLY AIR	-	LATTICE FACE SECURITY DIFFUSER	REFER TO DRAWING	STEEL DAMPER	-	2, 3, 4, 6.
E	SUPPLY AIR	19	LOUVRED STEEL REGISTER	REFER TO DRAWING	STEEL DAMPER	SINGLE DEFLECTION	2, 6.
F	EXHAUST AIR	19	LOUVRED STEEL REGISTER	REFER TO DRAWING	STEEL DAMPER	45° FIXED	2, 6.
G	SUPPLY AIR	-	STEEL SQUARE CONE	REFER TO DRAWING	STEEL DAMPER	ADJUSTABLE VANES	2, 5, 6.

NOTES:

- HEAVY DUTY, ABUSE RESISTANT.
- COLOR BY DEPARTMENTAL REPRESENTING.
- LOUVRED FOUR WAY DIFFUSER WITH LATTICE FACE PLATE.
- NECK SIZE 150x150.
- FACE SIZE 300X300, NECK TO BE SIZED IN ACCORDANCE WITH DUCT SIZE, MANUFACTURER'S STANDARD AND AIR FLOW.
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT.

CONDENSING UNIT (HEAT PUMP) SCHEDULE – WW02							
UNIT No.	LOCATION	MANUFACTURER & MODEL No.	COOLING CAPACITY (kW)	HEATING CAPACITY (kW)	POWER SUPPLY		REMARKS
					MAX. OVER CURRENT PROTECTION (A)	V/φ/Hz	
ACU-1	ROOF OF SECURITY POST 113	-	8.78	9.95	40	208/1/60	1, 2, 3, 4.

NOTES:

- COMPRESSOR WITH VARIABLE SPEED.
- UNIT WITH R-410A REFRIGERANT WITH INDICATED CAPACITIES AT:
 - A) COOLING: - OUTDOOR TEMP. OF 35°C
 - B) HEATING: - OUTDOOR TEMP. OF 8.3°C DB/6.1° CW.B - INDOOR TEMP. OF 26.7°C DB/19.4° CW.B - INDOOR TEMP. OF 21.1°C.
- CONTROL WITH FIXED REMOTE CONTROLLER AS DESCRIBED IN AIR CONDITIONING UNIT SCHEDULE.
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT.

AIR CONDITIONING UNIT (HEAT PUMP) INDOOR UNIT SCHEDULE – WW02											
UNIT No.	LOCATION	TYPE	MANUFACTURER & MODEL No.	EVAPORATOR			COOLING CAPACITY (kW)	HEATING CAPACITY (kW)	FILTER TYPE	POWER SUPPLY	REMARKS
				FLOW (L/S)	ESP (Pa)	MOTOR (kW)					
AC-1	SECURITY POST 113	CEILING SUSPENDED	-	450	0	0.16	8.78	9.95	WASHABLE PP HONEY AMP	208/1/60	1, 2, 3, 4, 5.

NOTES:

- MULTI-SPEED UNITS FLOW INDICATED AT MEDIUM SPEED.
- UNIT WITH R-410A REFRIGERANT WITH INDICATED CAPACITIES AT:
 - A) COOLING: - OUTDOOR TEMP. OF 35°C
 - B) HEATING: - OUTDOOR TEMP. OF 8.3°C DB/6.1° CW.B - INDOOR TEMP. OF 26.7°C DB/19.4° CW.B - INDOOR TEMP. OF 21.1°C.
- EXTERNAL DRAIN PUMP PROVIDED BY MANUFACTURER.
- C/W FIXED REMOTE CONTROLLER WITH READ OUT TO BMS.
- SUBMIT SHOP SUBMITTAL TO ENGINEER FOR REVIEW PRIOR TO PROCUREMENT.

AIR SEPARATOR SCHEDULE – WW03									
UNIT No.	MANUFACTURER & MODEL NO.	SYSTEM	MAX FLOW (L/s)	CONNECTION SIZE (DIA. mm)	CONSTRUCTION		OPERATING CONDITIONS		REMARKS
					SHELL	GASKET	MAX. TEMP. (°C)	MAX. PRESS. (kPa)	
AS-1	-	BOILER LOOP	53	50	CAST IRON	NON ASBESTOS	176	1105	1, 2.

NOTES:

- C/W BLOWDOWN CONNECTION AND SHUTOFF VALVE.
- DESIGN BUILT IN ACCORDANCE WITH ASME PRESSURE VESSEL CODE.

GLYCOL PACKAGE UNIT – WW03							
TAG No.	MANUFACTURER & MODEL NO.	LOCATION	TANK CAPACITY (L)	PUMP FLOW (L/MIN)	PUMP PRESSURE (kPa)	POWER SUPPLY	REMARKS
						V/φ/Hz	
GF-1	-	MECHANICAL ROOM 130	200	7.3	480	120/1/60	

SCHEDULE OF OUTDOOR AIR UNIT – WW02					
UNIT No.	FLOW (L/S)	POWER SUPPLY		COLLAR SIZE (mm)	REMARKS
		(kW)	V/φ/Hz		
MAU-1	28	2	208/1/60	150	1.

NOTES:

- C/W ROOM CONTROLLER BUILT IN DAMPER AND FACTORY INSTALLED DISCHARGE GRILL. CONTROLLER TO HAVE FAN STATUS AND FAULT STATUS READ OUT TO BMS.

FIRE DAMPER SCHEDULE – WW03				
TAG No.	DRAWING No.	LOCATION	TYPE	SIZE
FD-1	WDR-WW03-H-04	NORTHEAST WALL IN MECHANICAL ROOM 130	DYNAMIC	350X300
FD-2	WDR-WW03-H-04	SOUTHWEST WALL IN MECHANICAL ROOM 130	DYNAMIC	350X320

key plan



04	ISSUED FOR TENDER	2013/10/29
03	ISSUED FOR 100% OWNER REVIEW	2013/07/25
02	SUBMITTED FOR 99% DESIGN	2011/07/18
01	ISSUED FOR REVIEW	2011/02/15
revision		date

Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.



This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as agreed by AECOM and its client, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
MECHANICAL – SCHEDULES (SHEET 1 OF 2)

drawn by
dessiné par
L. TAURO

designed by
conc par
A. KABBANI

approved by
approuvé par
D. DOVAS

bid
offre
O. TABAREZ

project manager
administrateur de projets
project date
date du projet
2013-10-29

project no.
no. du projet
R.033225.001

drawing no.
dessiné no.
WDR-G-04

WALL FIN HEATER SCHEDULE--WW03

S.I. NO.	UNIT NO.	LOCATION	CAPACITY (kW)	WATER			ELEMENT		ROW(S)	ENCLOSURE		NOTES
				FLOW (L/S)	TEMP. IN (°C)	TEMP. OUT (°C)	DIA. (mm)	LENGTH (mm)		HEIGHT (mm)	LENGTH (mm)	
1	WFH-102	INMATE WAITING ROOM 102	1.2	0.025	93	81.5	32	820	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3, 4.
2	WFH-106	OFFICE 106	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
3	WFH-107	OFFICE 107	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
4	WFH-108-1	OFFICE 108	1.55	0.032	93	81.5	32	1050	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
5	WFH-108-2	OFFICE 108	1.55	0.032	93	81.5	32	1050	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
6	WFH-110	OFFICE 110	0.95	0.02	93	81.5	32	650	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
7	WFH-111	BOARDROOM 111	2.15	0.045	93	81.5	32	1465	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
8	WFH-112	OFFICE 112	1.9	0.04	93	81.5	32	1300	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
9	WFH-113	OFFICE 113	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
10	WFH-114-1	OFFICE 114	2.1	0.043	93	81.5	32	1430	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
11	WFH-114-2	OFFICE 114	1.0	0.021	93	81.5	32	680	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
12	WFH-115	OFFICE 115	1.425	0.03	93	81.5	32	975	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
13	WFH-116	OFFICE 116	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
14	WFH-117	OFFICE 117	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
15	WFH-118	OFFICE 118	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
16	WFH-119	OFFICE 119	2.15	0.045	93	81.5	32	1465	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
17	WFH-121-1	GENERAL OFFICE 121	1.2	0.025	93	81.5	32	820	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
18	WFH-121-2	GENERAL OFFICE 121	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
19	WFH-122-1	BOARD ROOM 122	2.15	0.045	93	81.5	32	1465	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
20	WFH-122-2	BOARD ROOM 122	2.15	0.045	93	81.5	32	1465	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
21	WFH-123	OFFICE 123	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
21	WFH-124	FOYER 124	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
22	WFH-125-1	OFFICE 125	1.8	0.0375	93	81.5	32	1225	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
23	WFH-125-2	OFFICE 125	1.8	0.0375	93	81.5	32	1225	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.
24	WFH-136	OFFICE 136	2.4	0.05	93	81.5	32	1635	1	450	REFER TO ARCH. DRAWINGS	1, 2, 3.

- NOTES:
- COORDINATE WITH ARCHITECTURAL DETAILS AND EXISTING MILLWORK DETAILS.
 - REFER TO NOTE No.3 IN CONDENSING UNIT (HEAT PUMP) SCHEDULE - WW03.
 - C/W BRACKETS, ELEMENT HANGERS, END CAPS, CORNERS AND ACCESS DOORS/REMOVABLE PANELS.
 - UNIT TO BE RATED FOR MEDIUM SECURITY APPLICATION.

AIR CONDITIONING UNIT (HEAT PUMP) INDOOR UNIT SCHEDULE - WW03

UNIT NO.	LOCATION	TYPE	MANUFACTURER & MODEL NO.	EVAPORATOR			COOLING CAPACITY	HEATING CAPACITY (kW)	FILTER TYPE	POWER SUPPLY V/ø/Hz	NOTES
				AIR FLOW	ESP	MOTOR					
AC-102	INMATE WAITING ROOM 102	CEILING CASSETTE 4 WAY	-	120 L/s	0	0.05 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 6.
AC-106	OFFICE 106	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-107	OFFICE 107	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-108	OFFICE 108	WALL MOUNTED	-	167 L/s	0	0.008 kW	3.6	4.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-110	OFFICE 110	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-110A	ELECTRICAL CLOSET 110A	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 6.
AC-111	BOARD ROOM 111	WALL MOUNTED	-	167 L/s	0	0.03 kW	3.6	4.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-112	OFFICE 112	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-113	OFFICE 113	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-114	OFFICE 114	WALL MOUNTED	-	145 L/s	0	0.028 kW	4.4	5.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-115	OFFICE 115	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-116	OFFICE 116	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-117	OFFICE 117	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-118	OFFICE 118	WALL MOUNTED	-	167 L/s	0	0.03 kW	3.6	4.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-119	OFFICE 119	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-121	GENERAL OFFICE 121	WALL MOUNTED	-	175 L/s	0	0.03 kW	5.3	5.9	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-122-1	BOARD ROOM 122	CEILING CASSETTE 4 WAY	-	150 L/s	0	0.015 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 7.
AC-122-2	BOARD ROOM 122	CEILING CASSETTE 4 WAY	-	150 L/s	0	0.015 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 7.
AC-124	FOYER	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-125	OFFICE 125	WALL MOUNTED	-	145 L/s	0	0.028 kW	4.4	5.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-127	LOUNGE 127	CEILING CASSETTE 4 WAY	-	217 L/s	0	0.05 kW	4.4	5.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 6.
AC-131-1	LOUNGE CORRIDOR	CEILING CASSETTE 4 WAY	-	150 L/s	0	0.015 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 6.
AC-131-2	LOUNGE CORRIDOR	CEILING CASSETTE 4 WAY	-	150 L/s	0	0.015 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 3, 6.
AC-128	OFFICE 128	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 3, 4.
AC-129	OFFICE 129	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-135	BOARD ROOM 135	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-136	OFFICE 136	WALL MOUNTED	-	87 L/s	0	0.008 kW	2.3	2.6	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-137	OFFICE 137	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.
AC-138	OFFICE 138	WALL MOUNTED	-	87 L/s	0	0.008 kW	1.8	2.0	WASHABLE PP HONEYCOMB	208/1/60	1, 2, 4, 5.

- NOTES:
- MULTI SPEED UNIT. FLOW INDICATED AT MEDIUM SPEED.
 - UNIT WITH R-410A REFRIGERANT WITH INDICATED CAPACITIES AT:
 - COOLING:
 - OUTDOOR TEMP. OF 35°C
 - INDOOR TEMP. OF 26.7°C DB/19.4° CW.B
 - HEATING:
 - OUTDOOR TEMP. OF 8.3°C DB/6.1° CW.B
 - INDOOR TEMP. OF 21.1°C.
 - C/W BUILT IN DRAIN PUMP & DECORATION PANEL.
 - WITH REMOTE FIXED CONTROLLER.
 - EXTERNAL DRAIN PUMP PROVIDED BY MANUFACTURER.
 - TEMPERATURE SETTING BY DIGITAL GROUP CONTROLLER IN MECHANICAL ROOM.
 - TWO UNITS CONNECTED TO SINGLE FIXED REMOTE CONTROLLER.

WALL FIN HEATER SCHEDULE - WW02

REF. No.	LOCATION	CAPACITY (kW)	WATER			ELEMENT		ENCLOSURE		REMARKS
			FLOW (L/S)	TEMP. IN (°C)	TEMP. OUT (°C)	DIA. (mm)	LENGTH (mm)	HEIGHT (mm)	LENGTH (mm)	
WFH-113-01	SECURITY POST 113	1.79	0.038	93	81.5	32	1220	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-02	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-03	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-04	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-05	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-06	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.
WFH-113-07	SECURITY POST 113	1.02	0.022	93	81.5	32	700	450	REFER TO ARCH. DRAWINGS	1, 2.

- NOTES:
- COORDINATE WITH ARCHITECTURAL DETAILS AND EXISTING MILLWORK DETAILS.
 - C/W BRACKETS, ELEMENT HANGERS, END CAP CORNERS AND ACCESS DOORS/REMOVABLE PANELS

CONDENSING UNIT (HEAT PUMP) SCHEDULE - WW03

UNIT NO.	UNIT LOCATION	MANUFACTURER & MODEL No.	CONDENSER FAN			COOLING CAPACITY (kW)	HEATING CAPACITY (kW)	POWER SUPPLY		REMARKS
			FLOW (L/S)	ESP (Pa)	MOTOR (kW)			MAX. OVER CURRENT PROTECTION (A)	V/ø/Hz	
ACU-1	ROOF	-	5000	0	0.92/0.92	35.15	39.55	77	208/3/60	1, 2, 3.
ACU-2	ROOF	-	5000	0	0.92/0.92	35.15	39.55	77	208/3/60	1, 2, 3.

- NOTES:
- UNIT IS PART OF A MODULAR OUTDOOR UNIT (WITH 2 MODULES) CONNECTED TO MULTIPLE INDOOR UNITS AS INDICATED ON DRAWINGS. TO BE C/W OUTDOOR CONNECTION PIPE, TUNING KIT, JOINT AND HEADER CONNECTING BOTH MODULES.
 - UNIT WITH R-410A REFRIGERANT WITH INDICATED CAPACITIES AT:
 - COOLING:
 - OUTDOOR TEMP. OF 35°C
 - INDOOR TEMP. OF 26.7°C DB/19.4° CW.B
 - HEATING:
 - OUTDOOR TEMP. OF 8.3°C DB/6.1° CW.B
 - INDOOR TEMP. OF 21.1°C.
 - CONTROL OF OUTDOOR UNITS, INDOOR UNITS, ENERGY RECOVERY VENTILATOR (INCLUDING SCHEDULING) AND VALVES OF HYDRONIC WALL FIN HEATERS IS THROUGH THE DIGITAL GROUP CONTROLLER PROVIDED BY THE SPLIT UNIT SYSTEM MANUFACTURER AND LOCATED IN THE MECHANICAL ROOM.

key plan



04	ISSUED FOR TENDER	2013/10/29
03	ISSUED FOR 100% OWNER REVIEW	2013/07/25
02	SUBMITTED FOR 99% DESIGN	2011/07/18
01	ISSUED FOR REVIEW	2011/02/15

revision _____ date _____
Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.



This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as agreed by AECOM and its client, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
MECHANICAL - SCHEDULES
(SHEET 2 OF 2)

drawn by
dessiné par L. TAURO

designed by
conçue par A. KABBANI


approved by
approuvé par D. DOVAS

bid offre O. TABAREZ project manager
administrateur de projets


project date
date du projet 2013-10-29

project no.
no. du projet R.033225.001


drawing no.
dessiné no. WDR-G-05



1 TYPICAL PIPE HANGER DETAIL
G-06 N.T.S.




2 HEAT RECOVERY VENTILATOR DETAIL
G-06 N.T.S.




- 1 600x 600x 25 THICK RIGID INSULATION.
- 2 600x 600x 20 THICK CREOSOTED EXTERIOR GRADE PLYWOOD.
- 3 50x 200x 450 LONG CREOSOTED PLANK.
- 4 150x 150x 450 LONG CREOSOTED BLOCK.
- 5 SCHEDULE 40 STEEL GAS PIPE OR COPPER REFRIGERANT PIPE.
- 6 WROUGHT IRON STRAPS - GRINNEL FIG. 262, 2 SIZES LARGER TO ALLOW FOR PIPE MOVEMENT. PAINT STRAPS WITH ANTI-CORROSIVE PAINT.
- 7 CADMIUM PLATED 50 LONG WOOD SCREWS.
- 8 PIPING SUPPORTS TO BE 3000 APART. PROVIDE A SUPPORT WITHIN 600 OF EVERY BEND AND TAKE-OFF.
- 9 SHIM WOOD BLOCKS AS REQUIRED TO COMPENSATE FOR ROOF SLOPE.
- 10 INSULATION WITH VAPOUR BARRIER AND JACKETING AS SPECIFIED.
- 11 FINISHED ROOF.


3 SUPPORTS FOR REFRIGERANT OR GAS PIPING ON ROOF
G-06 N.T.S.




4 TYPICAL DUCT SUPPORT DETAIL
G-06 N.T.S.




5 HOT WATER COIL PIPING DIAGRAM
G-06 N.T.S.




6 MOTORIZED DAMPER DETAIL
G-06 N.T.S.




7 DUCT SUPPORT DETAIL - WOODSHOP-LOW LEVEL
G-06 N.T.S.




8 CASSETTE UNIT DRAIN DETAIL
G-06 N.T.S.




9 O/A DUCT DETAIL-1
G-06 N.T.S.




10 O/A DUCT DETAIL-2
G-06 N.T.S.



11 FIRE DAMPER - THROUGH WALL (SMALL DUCT)
G-06 N.T.S.



12 WALL MOUNTED A/C UNIT- DRAIN & REF. PIPE DETAIL
G-06 N.T.S.



13 WALL MOUNTED A/C UNIT - DRN & REF. PIPE DETAIL (2)
G-06 N.T.S.

key plan



04	ISSUED FOR TENDER	2013/10/29
03	ISSUED FOR 100% OWNER REVIEW	2013/07/25
02	SUBMITTED FOR 99% DESIGN	2011/07/18
01	ISSUED FOR REVIEW	2011/02/15
revision		date

Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.

AECOM

This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as agreed by AECOM and its client, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
MECHANICAL DETAILS
(SHEET 1 OF 2)

drawn by
dessiné par L. TAURO

designed by
conçue par A. KABBANI


approved by
approuvé par D. DOVAS

bid
offre O. TABAREZ project manager
administrateur de projets


project date
date du projet 2013-10-29

project no.
no. du projet R.033225.001


drawing no.
dessiné no. WDR-G-06



15 WALL FIN HEATER DETAIL #1
G-07 N.T.S.



16 WALL FIN HEATER DETAIL #2
G-07 N.T.S.



14 WALL MOUNTED UNIT - DRAIN & REF. PIPE DETAIL #3
G-07 N.T.S.

key plan



revision	date
04	ISSUED FOR TENDER 2013/10/29
03	ISSUED FOR 100% OWNER REVIEW 2013/07/25
02	SUBMITTED FOR 99% DESIGN 2011/07/18
01	ISSUED FOR REVIEW 2011/02/15

Do not scale drawings. Verify all dimensions and conditions on site and immediately notify the Departmental Representative of all discrepancies.

AECOM

This drawing has been prepared for the use of AECOM's client and may not be used, reproduced or relied upon by third parties, except as agreed by AECOM and its client, as required by law or for use by governmental reviewing agencies. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that modifies this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from stated dimensions.

project title
titre du projet
WARKWORTH Ontario
MEDIUM SECURITY INSTITUTION
UNDERGROUND DUCT REPLACEMENT

drawing title
titre du dessin
MECHANICAL DETAILS
(SHEET 2 OF 2)

drawn by
dessiné par
L. TAURO

designed by
conçu par
A. KABBANI

approved by
approuvé par
D. DOVAS

bid
offre
O. TABAREZ project manager
administrateur
de projets

project date
date du projet
2013-10-29

project no.
no. du projet
R.033225.001

drawing no.
dessiné no.
WDR-G-07