

RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Public Works and Government Services / Travaux
publics et services gouvernementaux
Kingston Procurement
Des Acquisitions Kingston
86 Clarence Street, 2nd floor
Kingston
Ontario
K7L 1X3
Bid Fax: (613) 545-8067

SOLICITATION AMENDMENT MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Public Works and Government Services / Travaux
publics et services gouvernementaux
Kingston Procurement
Des Acquisitions Kingston
86 Clarence Street, 2nd floor
Kingston
Ontario
K7L 1X3

Title - Sujet Commercial Kitchen Equipment	
Solicitation No. - N° de l'invitation W0114-145070/A	Amendment No. - N° modif. 001
Client Reference No. - N° de référence du client W0114-14-5070	Date 2013-12-10
GETS Reference No. - N° de référence de SEAG PW-\$KIN-650-6238	
File No. - N° de dossier KIN-3-40131 (650)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2014-01-20	Time Zone Fuseau horaire Eastern Standard Time EST
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Rombough, Lori	Buyer Id - Id de l'acheteur kin650
Telephone No. - N° de téléphone (613) 545-8061 ()	FAX No. - N° de FAX (613) 545-8067
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction:	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Solicitation No. - N° de l'invitation

W0114-145070/A

Client Ref. No. - N° de réf. du client

W0114-14-5070

Amd. No. - N° de la modif.

001

File No. - N° du dossier

KIN-3-40131

Buyer ID - Id de l'acheteur

kin650

CCC No./N° CCC - FMS No/ N° VME

AMENDMENT #001

The intent of this amendment is to revise Annex "A" – Requirement.

DELETION & INSERTION

#1. Under: Annex "A"

Within: 5.1.8 Electric Jacketed Kettle – delete in its entirety & insert:

General

Self-contained steam 2/3 jacketed kettles have a closed steam system, the jacket is filled with distilled water and steam is supplied by electric boiler contained in a housing on the kettle's stand. This unit must be able to cook large quantities of food to meet the food service's needs.

Configuration

- Free standing kettle must be available as close to the following size: 60 gal (225L).

Material and Construction

- Stainless steel type 304 construction.
- A 2/3 double wall kettle or jacket covering the bottom to provide space for steam to circulate, then heating the cooking surface
- Rear mounted easy access pressure gauge and pressure relief valve to prevent tampering
- Re-enforced rolled rim design prevents damage to kettle rim
- Large pouring lip
- Faucet mounting bracket,
- 2" tangent draw-off valve
- Assisted, 45° hinged to rear rotatable stainless steel cover
- Electric tilting mechanism
- Built-in steam generator electric
- Pressure range from 35 psi to 50 psi

Temperature

Operating temperature range should fall within this range from 70°C - 127°C (150°F to 260°F).

Control Panel

Control panel to include:

- LED indicator for heat cycle
- LED indicator for low water
- Power ON/OFF switch
- Adjustable temperature control dial
- All controls to be water resistant, splash-proof construction