


GENERAL LABORATORY CASEWORK NOTES:

1. EXTENT OF LAB CASEWORK INDICATED ON LAB CASEWORK PLAN DRAWINGS
2. SHELVING TO BE ADJUSTABLE, UNLESS OTHERWISE NOTED
3. PROVIDE 100mm BACKSPLASH TO MATCH COUNTERTOP MATERIAL AT LOCATIONS WHERE COUNTERTOPS MEET ADJACENT WALLS, SERVICE CHASES, AND CABINETS THAT EXTEND ABOVE COUNTERTOPS UNLESS OTHERWISE NOTED
4. ALLOW KNEE SPACES TO ABSORB ANY FIELD DIMENSION DISCREPANCIES FOR CASEWORK LOCATED BETWEEN TWO WALLS
5. WORK TABLES TO BE OUTFITTED WITH PHENOLIC RESIN COUNTERS PER SPECIFICATION
6. PHENOLIC COUNTERTOPS, TYPICAL. REFER TO SPEC SECTION 12 35 53 FOR STAINLESS STEEL COMPONENTS
7. LAB SINK LOCATIONS TO BE OUTFITTED WITH GLASSARE DRYING RACKS. REFER TO INTERIOR ELEVATIONS FOR UNIQUE MOUNTING LOCATIONS
8. TASK LIGHTS (NOTED TSK), SEE DIVISION 26
9. PROVIDE SHEET METAL BACKING FOR UPPER SHELF ATTACHMENT IN MICROSCOPE ROOMS; REFER TO ROOM FINISH SCHEDULE.

 **DRAWING KEYNOTES**

1. STAINLESS STEEL INTEGRAL COUNTERTOP AND BACKSPLASH
2. NOT USED

