
Flooring materials

MT-1 - Olympia GI series 1x3 TH.GI.TPE.0103 Matt
PT-1 - GI series 4x12 TH.GI.IVO.0412.PL.OC
PT-2 - GI series 4x12 TH.GI.IVO.0412.L.OC
RF-1 - Johnsonite Triumph Hammered rubber interlocking color #742
VF-1 - Johnsonite iQ Optima color #874 Hardwired
VF-2 - Johnsonite iQ Optima color #897 Slate
RF-2 - Johnsonite VIHTR hammered color #48 Grey
RF-3 - Johnsonite HRT hammered color #48 Grey
RB-1 - Johnsonite #48 Grey 4"
RB-2 - Johnsonite #48 Grey 4" tightlock
CP-1 - Shaw Trace color #83761 Clay
CP-2 - Shaw Align color #83761 Clay

The installation of the floorcovering is guaranteed to be satisfactory within industry standards for a period of one year against any defects in workmanship from invoice date. In event of a claim against this guarantee, After Eight Floorings reserves the right to inspect the area.

Johnsonite®

iQ Natural, iQ Optima and iQ Granit

Maintenance Instructions for sheet and tile flooring

Initial Cleaning

Job site conditions usually cause grit and dirt to accumulate. Initial cleaning should not be performed until 5 days after installation. However the floor should be swept and protected until maintenance begins.

1. Thoroughly sweep or vacuum the flooring to remove all loose dirt and grit.
2. Prepare a cleaning solution of 2 to 4 oz of Taski "Profi" or Johnson Wax Professional "Stride" oil and grease emulsifying neutral detergents (pH of 7-8); per gallon of warm water. The dilution selected depends on light to heavy soil conditions.
3. Apply the cleaning solution with a nylon or rayon mop, and let stand for 5-15 minutes.
4. **IMPORTANT** – do not let the solution dry.
5. Scrub the flooring: Use a 22 gauge nylon bristle brush or low abrasive pad (tan or red) on a single disk rotary/scrubbing machine at low speed (150- 200 RPM).
6. Wet vacuum or mop-up the cleaning solution.
7. Rinse with clean cold water, and then remove all water by vacuum or mop. Replace rinse water often.
8. Allow the flooring to dry thoroughly (Approximately one hour, depending on temperature and humidity).
9. If trades continue to work on or over the floor, properly protect the floor from damage.

Preventative Care:

1. An effective barrier matting system should be installed at all entrances to reduce cleaning costs and extend the life of the floor.
2. Protect the flooring from damage by using good quality protective feet for chairs, tables, and other furniture. Chair mats may be required under chairs with casters/wheels.

Regular/Daily Cleaning:

It is very important to clean flooring at a frequency consistent with the amount and type of traffic. Daily cleaning is recommended.

1. Sweep, vacuum, or dry mop the floor daily when area is in use.
2. Damp mop the floor with a neutral cleaner/detergent (pH of 7-8) such as Taski's "Profi" or Johnson Wax Professional's "Stride Neutral".
 - Mix solution with water per manufacturer's directions.
 - The floor should not be flooded with water. The floor must be virtually dry after 15-20 seconds. Combine machine may be used in large areas. White or red pads should be used.
3. Remove minor stains and scuffs in conjunction with the cleaning. Use a white or red nylon pad with the neutral cleaner then wipe with clean water.

Dry buffing will produce a matte gloss patina finish.

- Initially buff daily for 30 days if possible, the floor will take on a matte gloss patina appearance that has

very good resistance to scuff and will require only minimum upkeep. The patina like appearance will become apparent after five or six buffing operations.

- After the desired gloss appearance has been achieved, buffing frequency can be reduced to fit the traffic pattern required.

Interim Cleaning:

Frequency of interim cleaning depends on the amount and type of traffic.

1. Follow the daily maintenance routine.
2. Additional cleaning requires the use of a rotary\scrubbing machine.
 - Mix neutral cleaner and water per manufacture's directions for spray application.
 - Spray the solution on the floor as the floor is cleaned with a low speed rotary\scrubbing machine (150-200 RPM) with a red fiber pad.
 - Rinse floor with clean water.

Combine machine may be used instead of a rotary\scrubbing machine. White or red pads should be used.

Periodic Cleaning:

Frequency of periodic cleaning depends on the amount and type of traffic

1. Repeat steps for Interim Cleaning.
2. For reduced Maintenance System: Finish process by dry buffing the floor with a red pad (Suitable speed – 1,500 RPM).

Flooring may be maintained in the conventional floor polish/finish maintenance system if desired. Conventional floor polish\finish maintenance system requires periodic stripping of the floor finish.

Special Maintenance Cautions:

1. Do not use steel wool, strong solvents (Lestoil, Top Job, etc. and similar products), gasoline, turpentine, and acetone.
2. Sweeping compounds or mop treated with petroleum solvents, silicone compounds or loose abrasives will damage the flooring.
3. Coatings such as shellac, lacquer, varnish, and paste wax or those containing aromatic solvents are not recommended.
4. Some disinfectant and insecticide sprays contain oil or solvents which may settle on the floor in sufficient quantity to discolor, cause slipperiness, and harm the floor covering.

Johnsonite®

Technical Services Department
16910 Munn Road, Chagrin Falls, Ohio 44023
(800) 899-8916 ext 297 Fax (440) 543-8920
www.johnsonite.com
E-mail: info@johnsonite.com
© 2012 Johnsonite, Inc. A Tarkett Company

Johnsonite®

Rubber & Vinyl Stair Treads

Maintenance Instructions

To support our customers' maintenance program, Johnsonite recommends the use of Taski or Johnson Wax Professional cleaning products. For a distributor near you please contact Taski at 1-800-827-5487 (USA and Canada calls) or Johnson Wax Professional at 1-800-558-2332.

Post Installation Initial Cleaning

Do not perform any maintenance on the products for 72 hours after installation is completed.

1. Thoroughly sweep or vacuum the entire surface area to remove all loose dirt and grit.
2. Prepare a cleaning solution by mixing 5 to 10 oz. of Taski's "Profil" or Johnson Wax Professional's "Stride Neutral" neutral detergent per gallon of warm water. The dilution depends on light to heavy soil conditions.
3. Apply the solution with a clean nylon or rayon mop, and let stand for 5-15 minutes.
Important: Do not let the solution dry.
4. Agitate the solution with a mop or a soft nylon deck brush then wet vacuum or mop up the cleaning solution.
5. Rinse stair treads with clean cold water then remove all water by vacuum or mop.
6. Allow the product to thoroughly dry.

Regular Maintenance


1. Thoroughly sweep or vacuum the entire surface area to remove all loose dirt and grit.
2. Prepare a cleaning solution by mixing 2 to 4 oz. of Taski's "Profil" or Johnson Wax Professional's "Stride Neutral" neutral detergent per gallon of warm water. The dilution depends on light to heavy soil conditions.
3. Apply the solution with a clean nylon or rayon mop, and let stand for 5-10 minutes.
Important: Do not let the solution dry.
4. Agitate the solution with the mop or a soft nylon deck brush, then wet vacuum or mop up the cleaning solution.
5. Rinse stair treads with clean cold water then remove all water with a mop.
6. Allow the product to thoroughly dry.

If you have any questions or need further assistance please contact Johnsonite 1-800-899-8916.

Johnsonite®

Technical Services Department
16910 Munn Road, Chagrin Falls, Ohio 44023
(800) 899-8916 ext 297 Fax (440) 543-8920

www.Johnsonite.com
E-mail: info@Johnsonite.com
© 2006 Johnsonite, Inc. A Tarkett Company.



**UNDERLOCK™ & SLIDELock™
RUBBER TILE**

Maintenance Instructions

Johnsonite®
A Tarkett Company

Triumph and Inertia™

Post Installation / Initial Cleaning:

The initial cleaning of rubber products is especially important. Job site conditions usually cause grit and dirt to accumulate. **NOTE: A minimal amount of water should be used when cleaning UnderLock Tiles. The tiles should never be flooded or saturated with water.**

1. Thoroughly sweep or vacuum the flooring to remove all loose dirt and grit.
2. Prepare a cleaning solution using one of the recommended pH neutral cleaners

(maintenance product reference chart below). The dilution ratio depends on light to heavy soil conditions.

3. Damp mop the cleaning solution on to the floor with a nylon or rayon mop, or pour the solution into a spray bottle and apply. Do not flood or saturate the flooring.
4. Allow the solution to dwell for 5 to 15 minutes. **IMPORTANT – do not let the solution dry.**

5. Scrub the rubber flooring:

- ◆ **Small area installations:** use a deck brush that attaches onto a handle system.
 - ◆ **Large area installations:** use a 22 to 28 gauge nylon bristle brush on an auto scrubbing machine (175-350 RPM). **Set the water volume to the lowest level and engage the vacuum when operating the scrubber.**
6. Allow the flooring to dry completely.

Preventive Care:

1. An effective barrier matting system should be installed at all entrances to reduce cleaning costs and extend the life of the floor.

2. Protect the flooring from damage by using good quality protective feet and casters for chairs, tables, and other furniture. Use

products designed for resilient floors. Caster or wheel damage can be avoided with the use of chair pads.

Routine / Daily Cleaning:

It is very important to clean the flooring at a frequency consistent with the amount and type of traffic and soil conditions. Daily cleaning is recommended.

1. Thoroughly sweep or vacuum the flooring to remove all loose dirt and grit.
2. Prepare a cleaning solution using a recommended pH neutral cleaner. The dilution ratio depends on light to heavy soil conditions.

3. Damp mop the cleaning solution onto the floor.
4. Be sure to wring the mop between each application. Do not flood or saturate the flooring.
5. Allow the flooring to dry completely.

Periodic / Deep Cleaning:

When routine / daily cleaning no longer provides adequate results, a more aggressive deep cleaning is required to thoroughly clean the floor.

NOTE: A minimal amount of water should be used when cleaning UnderLock Tiles. The tiles should never be flooded or saturated with water.

1. Thoroughly sweep or vacuum the flooring to remove all loose dirt and grit.

2. Prepare a cleaning solution using one of the recommended pH neutral cleaners (maintenance product reference chart below). The dilution ratio depends on light to heavy soil conditions.
3. Damp mop the cleaning solution on to the floor with a nylon or rayon mop, or pour the solution into a spray bottle and apply. Do not flood or saturate the flooring.
4. Allow the solution to dwell for 5 to 15 minutes. **IMPORTANT – do not let the solution dry.**

5. Scrub the rubber flooring:
 - ◆ **Small area installations:** use a deck brush that attaches onto a handle system.
 - ◆ **Large area installations:** use a 22 to 28 gauge nylon bristle brush on an auto scrubbing machine (175-350 RPM). **Set the water volume to the lowest level and engage the vacuum when operating the scrubber.**
6. Allow the flooring to dry completely.

Maintenance Product Reference Chart

NOTE: Always follow the manufacturer's label instructions for proper mixing ratios and use.

| | Initial Cleaning / Deep Cleaning | Routine / Daily Cleaning |
|---|---|-------------------------------------|
| Diversey www.diversey.com 1-800-558-2332 Certified Green Products | Profil | Profil |
| | | Prominence |
| | | Stride |
| Spartan Chemical www.spartanchemical.com 1-800-537-8990 Certified Green Products | Tribase Green Solutions Industrial Cleaner | Tribase |
| | | Damp Mop |
| | | Green Solutions All Purpose Cleaner |
| XL North www.xlnorth.com 1-888-530-2259 | XL Rubber Floor Cleaner | XL Rubber Floor Cleaner |

Tarkett STRONGER TOGETHER
 Technical Services Department
 18910 Munn Road, Chagrin Falls, Ohio 44023
 (800) 899-8918 ext 8297 Fax (440) 832-5843
 www.johnsonite.com
 email: info@johnsonite.com
 © 2012 Johnsonite Inc.