

PART 1 - GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 08 80 50 - Glazing.

1.2 REFERENCES

- .1 American National Standards Institute (ANSI)
  - .1 ANSI A208.2-09, Medium Density Fibreboard (MDF) for Interior Applications.
  - .2 ANSI/HPVA HP-1-2004, American National Standard for Hardwood and Decorative Plywood.
- .2 Architectural Woodwork Manufacturers Association of Canada (AWMAC) and Architectural Woodwork Institute (AWI)
  - .1 Architectural Woodwork Quality Standards, 1st edition, 2009.
- .3 CSA International
  - .1 CSA B111-74(R2003), Wire Nails, Spikes and Staples.
  - .2 CAN/CSA G164-M92(R2003), Hot Dip Galvanizing of Irregularly Shaped Articles.
  - .3 CSA O121-08, Douglas Fir Plywood.
  - .4 CSA O141-05, Softwood Lumber.
- .4 Forest Stewardship Council (FSC)
  - .1 FSC-STD-01-001-2004, FSC Principle and Criteria for Forest Stewardship.
  - .2 FSC-STD-20-002-2004, Structure and Content of Forest Stewardship Standards V2-1.
  - .3 FSC Accredited Certified Bodies.
- .5 National Lumber Grades Authority (NLGA)
  - .1 NLGA Standard Grading Rules for Canadian Lumber 2008.
- .6 South Coast Air Quality Management District (SCAQMD), California State, Regulation XI. Source Specific Standards
  - .1 SCAQMD Rule 1168-A2005, Adhesives and Sealants Applications.
- .7 European Committee for Standardization
  - .1 EN 438:2005 Decorative high-pressure laminates (HPL) sheets based on thermosetting resins.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
  - .1 Submit manufacturer's instructions, printed product literature and data sheets for MDF and include product characteristics, performance criteria, physical size, finish and limitations.
  - .2 Submit two copies of WHMIS MSDS in accordance with Section 01 35 29.06 - Health and Safety Requirements.

- .3 Shop Drawings:
  - .1 Indicate details of construction, profiles, jointing, fastening and other related details.
  - .2 Indicate materials, thicknesses, finishes and hardware.
- .4 Certifications: submit certificates signed by manufacturer certifying materials comply with specified performance characteristics and physical properties.
  - .1 Low-Emitting Materials:
    - .1 Submit listing of adhesives and sealants used in building, showing compliance with VOC and chemical component limits or restrictions requirements.
    - .2 Submit listing of composite wood products used in building, stating that they contain no added urea-formaldehyde resins, and laminate adhesives used in building, stating that they contain no urea-formaldehyde.

#### 1.4 QUALITY ASSURANCE

- .1 Lumber by grade stamp of agency certified by Canadian Lumber Standards Accreditation Board (CLSAB).
- .2 Plywood, particleboard, OSB and wood based composite panels to CSA and ANSI standards.

#### 1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
  - .1 Store materials off ground indoors in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
  - .2 Store and protect wood products from nicks, scratches, and blemishes.
  - .3 Replace defective or damaged materials with new.
- .4 Develop Waste Reduction Workplan related to Work of this Section and in accordance with Section 01 35 21 - LEED Requirements.
- .5 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding, and packaging materials as specified in Construction Waste Management Plan Waste Reduction Workplan in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal and Section 01 35 21 - LEED Requirements.

## PART 2 - PRODUCTS

### 2.1 MATERIALS

- .1 Softwood lumber: S4S, moisture content 19% or less in accordance with following standards:
  - .1 CSA O141.
  - .2 NLGA Standard Grading Rules for Canadian Lumber.
  - .3 AWMAC premium grade, moisture content as specified.
  - .4 Machine stress-rated lumber is acceptable.
  - .5 Hardwood lumber: moisture content 19% or less in accordance:
    - .1 National Hardwood Lumber Association (NHLA).
    - .2 AWMAC premium grade, moisture content as specified.
- .2 Panel Material: Urea-formaldehyde free
  - .1 Recycled content: 10% (Post-Consumer + ½ Post-Industrial).
  - .2 FSC certified.
  - .3 Medium density fibreboard (MDF): to ANSI A208.2, density 640-800 kg/m<sup>3</sup>.
- .3 High Pressure Laminate(HPL): solid core with homogenous colour through entire thickness of sheet, complying with EN 438:2005. 0.7 mm nominal thickness, colour to be selected from standard range by Departmental Representative.

### 2.2 ACCESSORIES

- .1 Nails and staples: to CSA B111; galvanized to CAN/CSA-G164 for exterior work, interior humid areas and for treated lumber; plain copper stainless steel finish elsewhere.
- .2 Wood screws: stainless steel, type and size to suit application.
- .3 Adhesive: in accordance with Section 08 08 50 - Glazing.
  - .1 VOC limit 30g/L maximum to SCAQMD Rule 1168.
- .4 Adhesive: in accordance with HPL manufacturer's recommendations.
  - .1 VOC limit 30g/L maximum to SCAQMD Rule 1168.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for wood products installation in accordance with manufacturer's written instructions.
  - .1 Visually inspect substrate in presence of Departmental Representative.
  - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
  - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to

proceed from Departmental Representative.

### 3.2 INSTALLATION

- .1 Do finish carpentry to Premium Quality Standards of AWMAC.

### 3.3 CONSTRUCTION

- .1 Fastening:
  - .1 Position items of finished carpentry work accurately, level, plumb, true and fasten or anchor securely.
  - .2 Design and select fasteners to suit size and nature of components being joined. Use proprietary devices as recommended by manufacturer.
  - .3 Set finishing nails to receive filler. Where screws are used to secure members, countersink screw in round smooth cut hole and plug with wood plug to match material being secured.
  - .4 Replace items of finish carpentry with damage to wood surfaces including hammer and other bruises.
  - .5 Install HPL with no visible joints on exposed edges of wall mirror mounting panels, using adhesives complying with 2.2 above.
  - .6 Install mirror with adhesive complying with 2.2 above. Mirror is to be installed without a frame as indicated. Make edge of glass perfectly flush with edge of mounting panels, as indicated.

### 3.4 SCHEDULE

- .1 Washroom mirror panels. Provide one in each washroom.

### 3.5 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
  - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
  - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

### 3.6 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by finish carpentry installation.

END OF SECTION