

RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Bid Receiving Public Works and Government
Services Canada/Réception des soumissions Travaux
publics et Services gouvernementaux Canada
800 Burrard Street, Room 219
800, rue Burrard, pièce 219
Vancouver
British Columbia
V6Z 0B9
Bid Fax: (604) 775-9381

SOLICITATION AMENDMENT
MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise
indicated, all other terms and conditions of the Solicitation
remain the same.

Ce document est par la présente révisé; sauf indication contraire,
les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Public Works and Government Services Canada -
Pacific Region
800 Burrard Street, Room 219
800, rue Burrard, pièce 219
Vancouver
British C
V6Z 0B9

Title - Sujet Principal Entrance Renovations	
Solicitation No. - N° de l'invitation EZ899-150573/A	Amendment No. - N° modif. 002
Client Reference No. - N° de référence du client	Date 2014-08-07
GETS Reference No. - N° de référence de SEAG PW-\$PWY-026-7283	
File No. - N° de dossier PWY-4-37064 (026)	CCC No./N° CCC - FMS No./N° VME
Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2014-08-14	Time Zone Fuseau horaire Pacific Daylight Saving Time PDT
F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/>	
Address Enquiries to: - Adresser toutes questions à: Liu (PWY), Patty	Buyer Id - Id de l'acheteur pwy026
Telephone No. - N° de téléphone (604) 775-6227 ()	FAX No. - N° de FAX (604) 775-6633
Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: CSC - William Head Institution - Metchosin, BC	

Instructions: See Herein

Instructions: Voir aux présentes

Delivery Required - Livraison exigée	Delivery Offered - Livraison proposée
Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur	
Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur	
Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie)	
Signature	Date

Solicitation No. - N° de l'invitation

EZ899-150573/A

Client Ref. No. - N° de réf. du client

Amd. No. - N° de la modif.

002

File No. - N° du dossier

PWY-4-37064

Buyer ID - Id de l'acheteur

pw026

CCC No./N° CCC - FMS No/ N° VME

Les documents français seront disponibles sur demande.

Amendment 002 has been raised to incorporate Addendum 002.

All other terms and conditions remain unchanged.

The following changes in the tender documents are effective immediately. This addendum will form part of the contract documents.

SPECIFICATIONS

.1 Section 09 65 16 – RESILIENT FLOORING

Clause 1.2

- (1) **Revise** paragraph 1.1 to read:

.4 ASTM F1913 - 04(2010) Standard Specification for Vinyl Sheet Floor Covering Without Backing.

Clause 2.1

- (2) **Revise** paragraph 2.1.1 and subparagraphs .1 to .8 to read:

.1 Sheet vinyl flooring: nonlayered and nonbacked homogeneous 1.83 to 2 m wide, having a nominal total thickness of 2.0 mm consisting of through-grain vinyl marbelized pattern and color uniformly distributed throughout entire thickness with a formulated polyurethane reinforcement. The pattern to merge subtle color accents with a detailed marbleized visual providing a monolithic appearance. Vinyl sheet flooring to meet wear-layer gauge and composition, flexibility, indentation, and solvent resistance requirements of ASTM F1309 Type 2, Class 1, Grade A. Flooring to consist of pvc resins, plasticisers, stabilizers, and fillers formulated to resist wear, chemical attack and scuffing; conforming to the following additional requirements:

- .1 Full load limit: 151 kg.
- .2 Static load limit to ASTM F970/modified: 125/800 lbs/sq in.
- .3 Gloss: 60 specular, 16.
- .4 Wear resistance: 58,000 cycles By Taber Abrader with H18 and 1,000 gram weight Or Frick Taber test to EN 660-2 and be in abrasion group M, as defined in EN 649.
- .5 Fire test data: ASTM E648-0.45 watts/cm² or more, Class 1; ASTM E662 smoke test, 450 or less;
- .6 Slip resistance: to ASTM D2047 - Coefficient of slip resistance minimum 0.5.
- .7 Acceptable Product: (other products are acceptable provide they meet the above specification)
 - .1 PolyFlor 2000 PUR.
 - .2 Johnsonite Tarlett Optima or Granit

END OF ADDENDUM No. 2
