

PART 1 - GENERAL

- 1.1 SECTION INCLUDES .1 Requirements and limitations for cutting and patching the Work.
- 1.2 RELATED SECTIONS .1 Section 01 11 00 - Summary of Work.  
.2 Section 01 33 00 - Submittal Procedures.  
.3 Individual product Sections: cutting and patching incidental to work of section. Advance notification to other sections required.
- 1.3 SUBMITTALS .1 Submit written request in advance of cutting or alteration which affects:  
.1 Structural integrity of any element of Project.  
.2 Integrity of weather-exposed or moisture-resistant elements.  
.3 Efficiency, maintenance, or safety of any operational element.  
.4 Visual qualities of sight-exposed elements.  
.5 Work of Departmental Representative or separate contractor.  
.2 Include in request:  
.1 Identification of Project.  
.2 Location and description of affected Work.  
.3 Statement on necessity for cutting or alteration.  
.4 Description of proposed Work, and products to be used.  
.5 Alternatives to cutting and patching.  
.6 Effect on Work of Departmental Representative or separate contractor.  
.7 Written permission of affected separate contractor.  
.8 Date and time work will be executed.
- 1.4 MATERIALS .1 Required for original installation.  
.2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.
- 1.5 PREPARATION .1 Inspect existing conditions, including elements subject to damage or movement during cutting and

patching.

- .2 After uncovering, inspect conditions affecting performance of Work.
- .3 Beginning of cutting or patching means acceptance of existing conditions.
- .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which may be exposed by uncovering work; maintain excavations free of water.

1.6 EXECUTION

- .1 Execute cutting, fitting, and patching including excavation and fill, to complete Work.
- .2 Fit several parts together, to integrate with other Work.
- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .8 Restore work with new products in accordance with requirements of Contract Documents.
- .9 Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .10 Refinish surfaces to match adjacent finishes: For continuous surfaces refinish to nearest intersection; for an assembly, refinish entire unit.

New Computer Based Training Room  
Data Taxation Building  
St. John's, NL  
Project No: R.061300.004

Execution  
Requirements

Section 01 73 03  
Page 3 of 3

---

PART 2 - PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED .1 Not Used.