

PART 1 - GENERAL

- 1.1 REFERENCES .1 Canadian General Standards Board (CGSB)
.1 CGSB 1.59, Alkyd Exterior Gloss Enamel.
.2 CAN/CGSB 1.189, Exterior Alkyd Primer for Wood.
- .2 Canadian Standards Association (CSA International)
.1 CSA-O121-M1978 (R2003), Douglas Fir Plywood.
- 1.2 INSTALLATION AND REMOVAL .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.
- 1.4 GUARD RAILS AND BARRICADES .1 Provide secure, rigid guard rails and barricades around deep excavations, and open edges of floors and roofs.
- 1.5 WEATHER ENCLOSURES .1 Provide weather tight closures to unfinished door and window openings, and other openings in floors and roofs.
- .2 Design enclosures to withstand wind pressure and snow loading.
- 1.6 DUST TIGHT SCREENS .1 Provide dust tight screens or partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.
- .2 Maintain and relocate protection until such work is complete.
- 1.7 ACCESS TO SITE .1 Provide and maintain access roads and sidewalk crossings, as may be required for access to Work.
- 1.8 FIRE ROUTES .1 Maintain access to property including overhead clearances for use by emergency response vehicles.
- 1.9 PROTECTION FOR OFF-SITE AND PUBLIC PROPERTY .1 Protect surrounding private and public property from damage during performance of Work.

.2 Be responsible for damage incurred.

1.10 PROTECTION OF
BUILDING FINISHES

.1 Provide protection for finished and partially
finished building finishes and equipment during
performance of Work.

.2 Provide necessary screens, covers, and hoardings.

PART 2 - PRODUCTS

2.1 NOT USED

.1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

.1 Not Used.