

PART 1 - GENERAL

- 1.1 REFERENCES .1 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
.1 Material Safety Data Sheets (MSDS).
- .2 National Fire Protection Association (NFPA)
.1 NFPA 13-2002, Standard for the Installation of Sprinkler Systems.
- .3 National Building Code of Canada (NBC) - 1995
- 1.2 ACTION AND INFORMATIONAL SUBMITTALS .1 Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
.1 Submit manufacturer's printed product literature, specifications and datasheet in accordance with Section 01 33 00 - Submittal Procedures. Include product characteristics, performance criteria, and limitations.
.1 Submit two copies of Workplace Hazardous Materials Information System (WHMIS) Material Safety Data Sheets (MSDS) in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Quality assurance submittals: submit following in accordance with Section 01 33 00 - Submittal Procedures.
.1 Instructions: submit manufacturer's installation instructions.
.1 Departmental Representative will make available 1 copy of systems supplier's installation instructions.
- 1.3 QUALITY ASSURANCE .1 Health and Safety:
.1 Do construction occupational health and safety in accordance with Section 01 35 29.06 - Health and Safety Requirements.
-

- 1.4 DELIVERY,
STORAGE, AND
HANDLING
- .1 Packing, shipping, handling and unloading:
 - .1 Deliver, store and handle in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Deliver, store and handle materials in accordance with manufacturer's written instructions.
 - .2 Waste Management and Disposal:
 - .1 Construction/Demolition Waste Management and Disposal: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

PART 2 - PRODUCTS

- 2.1 GENERAL
- .1 Size and shape of bases type and performance of vibration isolation as indicated.
- 2.2 ELASTOMERIC
PADS
- .1 Type EP1 - neoprene waffle or ribbed; 9 mm minimum thick; 50 durometer; maximum loading 350 kPa.
 - .2 Type EP2 - rubber waffle or ribbed; 9 mm minimum thick; 30 durometer natural rubber; maximum loading 415 kPa.
 - .3 Type EP3 - neoprene-steel-neoprene; 9 mm minimum thick neoprene bonded to 1.71 mm steel plate; 50 durometer neoprene, waffle or ribbed; holes sleeved with isolation washers; maximum loading 350 kPa.
 - .4 Type EP4 - rubber-steel-rubber; 9 mm minimum thick rubber bonded to 1.71 mm steel plate; 30 durometer natural rubber, waffle or ribbed; holes sleeved with isolation washers; maximum loading 415 kPa.
- 2.3 ELASTOMERIC
MOUNTS
- .1 Type M1 - colour coded; neoprene in shear; maximum durometer of 60; threaded insert and two bolt-down holes; ribbed top and bottom surfaces.
-

2.4 SPRINGS

- .1 Design stable springs: ratio of lateral to axial stiffness is equal to or greater than 1.2 times ratio of static deflection to working height. Select for 50% travel beyond rated load. Units complete with levelling devices.
- .2 Ratio of height when loaded to diameter of spring between 0.8 to 1.0.
- .3 Cadmium plate for outdoor 100% relative humidity installations.
- .4 Colour code springs.

2.5 SPRING MOUNT

- .1 Zinc or cadmium plated hardware; housings coated with rust resistant paint.
- .2 Type M2 - stable open spring: support on bonded 6 mm minimum thick ribbed neoprene or rubber friction and acoustic pad.
- .3 Type M3 - stable open spring: 6 mm minimum thick ribbed neoprene or rubber friction and acoustic pad, bonded under isolator and on isolator top plate; levelling bolt for rigidly mounting to equipment.
- .4 Type M4 - restrained stable open spring: supported on bonded 6 mm minimum thick ribbed neoprene or rubber friction and acoustic pad; built-in resilient limit stops, removable spacer plates.
- .5 Type M5 - enclosed spring mounts with snubbers for isolation up to 950 kg maximum.
- .6 Performance: as indicated.

2.6 HANGERS

- .1 Colour coded springs, rust resistant, painted box type hangers. Arrange to permit hanger box or rod to move through a 30 degrees arc without metal to metal contact.
 - .2 Type H1 - neoprene - in-shear, moulded with rod isolation bushing which passes through hanger box.
-

- 2.6 HANGERS
(Cont'd)
- .3 Type H2 - stable spring, elastomeric washer, cup with moulded isolation bushing which passes through hanger box.
 - .4 Type H3 - stable spring, elastomeric element, cup with moulded isolation bushing which passes through hanger box.
 - .5 Type H4 - stable spring, elastomeric element with precompression washer and nut with deflection indicator.

- 2.7 ACOUSTIC BARRIERS FOR ANCHORS AND GUIDES
- .1 Acoustic barriers: between pipe and support, consisting of 25 mm minimum thick heavy duty duck and neoprene isolation material.

- 2.8 HORIZONTAL THRUST RESTRAINT
- .1 Spring and elastomeric element housed in box frame; assembly complete with rods and angle brackets for equipment and ductwork attachment; provision for adjustment to limit maximum start and stop movement to 9 mm.
 - .2 Arrange restraints symmetrically on either side of unit and attach at centerline of thrust.

PART 3 - EXECUTION

- 3.1 MANUFACTURER'S INSTRUCTIONS
- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheet.

- 3.2 INSTALLATION
- .1 Install vibration isolation equipment in accordance with manufacturers instructions and adjust mountings to level equipment.
 - .2 Ensure piping, ducting and electrical connections to isolated equipment do not reduce system flexibility and that piping, conduit and ducting passage through walls and floors do not transmit vibrations.
-

- 3.2 INSTALLATION .3 Unless indicated otherwise, support piping
(Cont'd) connected to isolated equipment with spring
mounts or spring hangers with 25 mm minimum
static deflection as follows:
- .1 Up to NPS4: first 3 points of support.
NPS5 to NPS8: first 4 points of support. NPS10
and Over: first 6 points of support.
 - .2 First point of support: static
deflection of twice deflection of isolated
equipment, but not more than 50 mm.
 - .4 Where isolation is bolted to floor use
vibration isolation rubber washers.
 - .5 Block and shim level bases so that ductwork
and piping connections can be made to rigid
system at operating level, before isolator
adjustment is made. Ensure that there is no
physical contact between isolated equipment
and building structure.

- 3.3 CLEANING .1 Proceed in accordance with Section 01 74 11 -
Cleaning.
- .2 Upon completion and verification of
performance of installation, remove surplus
materials, excess materials, rubbish, tools
and equipment.