

PART 1 - GENERAL

- 1.1 REFERENCES
- .1 ASTM International Inc.
 - .1 ASTM D 2235, Standard Specification for Solvent Cement for Acrylonitrile-Butadiene-Styrene (ABS) Plastic Pipe and Fittings.
 - .2 ASTM D 2564-04e1, Standard Specification for Solvent Cements for Poly(Vinyl-Chloride) (PVC) Plastic Piping Systems.
 - .2 Canadian Standards Association (CSA International)
 - .1 CAN/CSA-Series B1800, Thermoplastic Nonpressure Pipe Compendium - B1800 Series.
 - .3 Green Seal Environmental Standards (GSES)
 - .1 Standard GS-36, Commercial Adhesives.
 - .4 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
 - .5 South Coast Air Quality Management District (SCAQMD), California State
 - .1 SCAQMD Rule 1168, Adhesive and Sealant Applications.
- 1.2 ACTION AND INFORMATIONAL SUBMITTALS
- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Product Data:
 - .1 Provide manufacturer's printed product literature and datasheets for piping and adhesives, and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Provide two copies WHMIS MSDS - Material Safety Data Sheets in accordance with Section 01 35 29.06 - Health and Safety Requirements 01 35 43 - Environmental Procedures.
- 1.3 DELIVERY, STORAGE AND HANDLING
- .1 Deliver, store and handle in accordance with Section 01 61 00 - Common Product Requirements.
-

- 1.3 DELIVERY,
STORAGE AND
HANDLING
(Cont'd)
- .2 Deliver materials to site in original factory packaging, labelled with manufacturer's name, address.
 - .3 Store at temperatures and conditions recommended by manufacturer.
 - .4 Packaging Waste Management: remove for reuse and return of packaging materials in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

PART 2 - PRODUCTS

- 2.1 MATERIAL
- .1 Adhesives and Sealants: in accordance with Section 07 92 00 - Joint Sealants.
- 2.2 PIPING AND
FITTINGS
- .1 For DWV piping to:
 - .1 CAN/CSA B1800.
- 2.3 JOINTS
- .1 Solvent weld for PVC: to ASTM D 2564.
 - .2 Solvent weld for ABS: to ASTM D 2235.

PART 3 - EXECUTION

- 3.1 APPLICATION
- .1 Manufacturer's Instructions: comply with manufacturer's written recommendations, including product technical bulletins, handling, storage and installation instructions, and datasheets.
- 3.2 INSTALLATION
- .1 Install in accordance with National Plumbing Code and local authority having jurisdiction.
-

- 3.3 TESTING .1 Pressure test buried systems before backfilling.
- .2 Hydraulically test to verify grades and freedom from obstructions.
- 3.4 PERFORMANCE VERIFICATION .1 Cleanouts:
- .1 Ensure accessible and that access doors are correctly located.
- .2 Open, cover with linseed oil and re-seal.
- .3 Verify cleanout rods can probe as far as the next cleanout, at least.
- .2 Test to ensure traps are fully and permanently primed.
- .3 Ensure fixtures are properly anchored, connected to system and effectively vented.
- .4 Affix applicable label (storm, sanitary, vent, pump discharge) c/w directional arrows every floor or 4.5 m (whichever is less).
- 3.5 CLEANING .1 Clean in accordance with Section 01 74 11 - Cleaning.
- .1 Remove surplus materials, excess materials, rubbish, tools and equipment.
- .2 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.