

**Part 1            General**

**1.1               RELATED SECTIONS**

- .1       Section 01 33 00 – Submittal procedures.

**1.2               REFERENCES**

- .1       Conform to reference standards, in whole or in part, as specifically requested in specifications.
- .2       If there is question as to whether products or systems are in conformance with applicable standards, Departmental Representative reserves right to have such products or systems tested to prove or disprove conformance.
- .3       If products or systems comply with contract documents, the costs involved for these tests will be paid for by Departmental Representative; otherwise, they will be paid for by the Contractor.
- .4       If no standard date or specific edition is mentioned, comply with the most recent edition in force at the time of the bid presentation.

**1.3               QUALITY**

- .1       Products, materials, equipment and articles (called products in the specifications) incorporated in Work shall be new, in good operating condition, and of best quality (in accordance with the specifications) for intended purpose. If requested, furnish evidence as to type, source and quality of products provided.
- .2       Defective products, whenever identified prior to completion of Work, will be rejected, regardless of previous inspections. Inspection does not relieve responsibility, but is precaution against oversight or error. Remove and replace defective products at contractor expense and be responsible for delays and expenses caused by rejection.
- .3       Should disputes arise as to quality or fitness of products, decision rests strictly with Departmental Representative based upon requirements of Contract Documents.
- .4       Unless otherwise indicated in specifications, maintain uniformity of manufacture for any particular or like item throughout building.
- .5       Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

**1.4               AVAILABILITY**

- .1       Immediately upon reception of Acceptance of Offer, review product delivery requirements and anticipate foreseeable supply delays for items. If delays in supply of products are foreseeable, notify Departmental Representative of such, in order that substitutions or other remedial action may be authorized in ample time to prevent delay in performance of Work.

- .2 In event of failure to notify Departmental Representative at commencement of Work and should it subsequently appear that Work may be delayed for such reason, Departmental Representative reserves right to substitute more readily available products of similar character, at no increase in Contract Price or Contract Time.

## **1.5 STORAGE, HANDLING AND PROTECTION**

- .1 Handle and store products in manner to prevent damage, alteration, deterioration and soiling and in accordance with manufacturer's instructions when applicable.
- .2 Store packaged or bundled products in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.
- .5 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

## **1.6 TRANSPORTATION**

- .1 Pay costs of transportation of products required in performance of Work.

## **1.7 QUALITY OF WORK**

- .1 Ensure Quality of Work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed. Immediately notify Departmental Representative if required Work is such as to make it impractical to produce required results.
- .2 Do not employ anyone unskilled in their required duties. Departmental Representative reserves right to require dismissal from site, workers deemed incompetent or careless.

## **1.8 CO-ORDINATION**

- .1 Ensure co-operation of workers in laying out Work. Maintain efficient and continuous supervision.
- .2 The contractor is responsible for coordination and placement of openings, sleeves and accessories.

## **1.9 CONCEALMENT**

- .1 Before installation inform Departmental Representative if there is interference. Install as directed by Departmental Representative.

**1.10 REMEDIAL WORK**

- .1 Perform remedial work required to repair or replace parts or portions of Work identified as defective or unacceptable. Co-ordinate adjacent affected Work as required or according to Departmental Representative's instructions.
- .2 Perform remedial work by specialists familiar with materials affected. Perform in a manner to neither damage nor put at risk any portion of Work.

**1.11 FASTENINGS**

- .1 Provide metal fastenings and accessories in same texture, colour and finish as adjacent materials, unless indicated otherwise.
- .2 Prevent electrolytic action between dissimilar metals and materials.
- .3 Use non-corrosive hot dip galvanized steel fasteners and anchors for securing exterior work, unless stainless steel or other material is specifically requested in affected specification Section.
- .4 Space anchors within individual load limit or shear capacity and ensure they provide positive permanent anchorage.

**1.12 FASTENINGS - EQUIPMENT**

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified.
- .3 Bolts may not project more than one diameter beyond nuts.

**1.13 PROTECTION OF WORK IN PROGRESS**

- .1 Prevent overloading of parts of building. Do not cut, drill or sleeve load bearing structural member, unless specifically indicated without written approval of Departmental Representative.

**Part 2 Products**

**2.1 NOT USED**

- .1 Not Used.

**Part 3 Execution**

**3.1 NOT USED**

- .1 Not Used.

**END OF SECTION**