

PART 1 - GENERAL

- | | | |
|--|----|---|
| <u>1.1 FIRE DEPARTMENT BRIEFING</u> | .1 | Departmental Representative will co-ordinate arrangements for contractor for briefing on Fire Safety at pre-work conference by Fire Chief before work is commenced. |
| <u>1.2 REPORTING FIRES</u> | .1 | Know location of nearest fire alarm box and telephone, including emergency phone number. |
| | .2 | Report immediately fire incidents to Fire Department as follows:
.1 Activate nearest fire alarm box; or
.2 Telephone. |
| | .3 | When reporting fire by telephone, give location of fire, name or number of building and be prepared to verify location. |
| <u>1.3 INTERIOR AND EXTERIOR FIRE PROTECTION AND ALARM SYSTEMS</u> | .1 | Fire protection and alarm system will not be:
.1 Obstructed;
.2 Shut-off; and
.3 Left inactive at end of working day or shift without authorization from Fire Chief. |
| | .2 | Fire hydrants, standpipes and hose systems will not be used for other than fire-fighting purposes unless authorized by Fire Chief. |
| <u>1.4 FIRE EXTINGUISHERS</u> | .1 | Supply fire extinguishers, as scaled by Fire Chief, necessary to protect work in progress and contractor's physical plant on site. |
| <u>1.5 INSTALLATION AND/OR REPAIR OF</u> | .1 | Notify Fire Chief of location of asphalt kettles and dates that kettles will be in use. Ensure |

ROOF TO INCLUDE

CONTRACTORS

PHYSICAL PLANT AT
SITE

personnel use and take precautions as follows:

- .1 Use kettles equipped with thermometers or gauges in good working order.
- .2 Locate kettles in safe place outside of building or, if approved by Fire Chief, on non-combustible roof. Locate to avoid danger of igniting combustible material below.
- .3 Maintain continuous supervision while kettles are in operation and provide metal covers for kettles to smother flames in case of fire. Provide fire extinguishers as required in 1.4.
- .4 Prior to start of work, demonstrate container capacities to Fire Chief.
- .5 Use only glass fibre roofing mops.
- .6 Do not leave used roofing mops unattended on roof. Store mops away from building and combustible materials.
- .7 Store roofing materials no closer than 3 m to structures.

1.6 BLOCKAGE OF
ROADWAYS

- .1 Advise Fire Chief of work that would impede fire apparatus response. This includes violation of minimum overhead clearance, as prescribed by Fire Chief, erecting of barricades and digging of trenches.

1.7 SMOKING
PRECAUTIONS

- .1 Observe smoking regulations.

1.8 RUBBISH AND
WASTE MATERIALS

- .1 Keep rubbish and waste materials at minimum quantities.
- .2 Burning of rubbish is prohibited.
- .3 Removal:
 - .1 Remove rubbish from work site at end of work day or shift or as directed.
- .4 Storage:
 - .1 Store oily waste in approved receptacles to ensure maximum cleanliness and safety.
 - .2 Deposit greasy or oily rags and materials subject to spontaneous combustion in approved receptacles and remove specified.

1.9 FLAMMABLE AND
COMBUSTIBLE LIQUIDS

- .1 Handling, storage and use of flammable and combustible liquids governed by current National Fire Code of Canada.
- .2 Keep flammable and combustible liquids such as gasoline, kerosene and naphtha for ready use in quantities not exceeding 45 litres provided they are stored in approved safety cans bearing Underwriters' Laboratory of Canada or Factory Mutual seal of approval. Storage of quantities of flammable and combustible liquids exceeding 45 litres for work purposes requires permission of Fire Chief.
- .3 Transfer of flammable and combustible liquids is prohibited within buildings or jetties.
- .4 Transfer of flammable and combustible liquids will not be carried out in vicinity of open flames or any type of heat-producing devices.
- .5 Do not use flammable liquids having flash point below 38 degrees C such as naphtha or gasoline as solvents or cleaning agents.
- .6 Store flammable and combustible waste liquids, for disposal, in approved containers located in safe ventilated area. Keep quantities minimum and Fire Department is to be notified when disposal is required.

1.10 HAZARDOUS
SUBSTANCES

- .1 Work entailing use of toxic or hazardous materials, chemicals and/or explosives, or otherwise creating hazard to life, safety or health, in accordance with National Fire Code of Canada.
- .2 Obtain from Fire Chief a "Hot Work" permit for work involving welding, burning or use of blowtorches and salamanders, in buildings or facilities.
- .3 When Work is carried out in dangerous or hazardous areas involving use of heat, provide fire watchers equipped with sufficient fire extinguishers. Determination of dangerous or hazardous areas along with level of protection necessary for Fire Watch is at discretion of Fire Chief. Contractors are responsible for providing fire watch service for work on scale established and in conjunction with

Fire Chief at pre-work conference.

- .4 Provide ventilation where flammable liquids, such as lacquers or urethanes are used, eliminate sources of ignition. Inform Fire Chief prior to and at cessation of such work.

1.11 QUESTIONS
AND/OR
CLARIFICATION

- .1 Direct questions or clarification on Fire Safety in addition to above requirements to Fire Chief.

1.12 FIRE
INSPECTION

- .1 Co-ordinate site inspections by Fire Chief through Departmental Representative.
- .2 Allow Fire Chief unrestricted access to work site.
- .3 Co-operate with Fire Chief during routine fire safety inspection of work site.
- .4 Immediately remedy unsafe fire situations observed by Fire Chief.

PART 2 - PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 - EXECUTION

3.1 NOT USED

- .1 Not Used.