

**Part 1            General**

**1.1            ACTION AND INFORMATIONAL SUBMITTALS**

- .1      Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
- .2      Submit written request in advance of cutting or alteration which affects:
  - .1          Structural integrity of elements of project.
  - .2          Integrity of weather-exposed or moisture-resistant elements.
  - .3          Efficiency, maintenance, or safety of operational elements.
  - .4          Visual qualities of sight-exposed elements.
  - .5          Work of Owner or separate contractor.
- .3      Include in request:
  - .1          Identification of project.
  - .2          Location and description of affected Work.
  - .3          Statement on necessity for cutting or alteration.
  - .4          Description of proposed Work, and products to be used.
  - .5          Alternatives to cutting and patching.
  - .6          Effect on Work of Owner or separate contractor.
  - .7          Written permission of affected separate contractor.
  - .8          Date and time work will be executed.

**1.2           MATERIALS**

- .1      Required for original installation.
- .2      Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.

**1.3           PREPARATION**

- .1      Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
- .2      After uncovering, inspect conditions affecting performance of Work.
- .3      Beginning of cutting or patching means acceptance of existing conditions.
- .4      Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5      Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.

**1.4           EXECUTION**

- .1      Execute cutting, fitting, and patching including excavation and fill, to complete Work.
- .2      Fit several parts together, to integrate with other Work.

- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .9 Restore work with new products in accordance with requirements of Contract Documents.
- .10 Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .11 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with fire stopping material in accordance with Section 07 84 00 - Fire stopping, full thickness of the construction element.
- .12 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.
- .13 Conceal pipes, ducts and wiring in floor, wall and ceiling construction of finished areas except where indicated otherwise.

**1.5 WASTE MANAGEMENT AND DISPOSAL**

- .1 Separate waste materials for recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management And Disposal.

**Part 2 Products**

**2.1 NOT USED**

- .1 Not Used.

**Part 3 Execution**

**3.1 NOT USED**

- .1 Not Used.

**END OF SECTION**