

**Part 1        General**

**1.1            SUBMITTALS**

- .1        Submittals: in accordance with Section 01 33 00 - Submittal Procedures.
- .2        Submit written request in advance of cutting or alteration which affects
  - .1        Structural integrity of elements of project.
  - .2        Integrity of weather-exposed or moisture-resistant elements.
  - .3        Efficiency, maintenance, or safety of operational elements.
  - .4        Visual qualities of sight-exposed elements.
  - .5        Work of Owner or separate contractor.
- .3        Include in request:
  - .1        Identification of project.
  - .2        Location and description of affected Work.
  - .3        Statement on necessity for cutting or alteration.
  - .4        Description of proposed Work, and products to be used.
  - .5        Alternatives to cutting and patching.
  - .6        Effect on Work of Owner or separate contractor.
  - .7        Written permission of affected separate
  - .8

**1.2            MATERIALS**

- .1        Required for original installation.
- .2        Change in Materials: Submit request for substitution in accordance with Section 01 33 00 - Submittal Procedures.

**1.3            EXECUTION**

- .1        Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .2        Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .3        Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .4        Restore work with new products in accordance with requirements of Contract Documents.
- .5        Fit Work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.

- .6 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with firestopping material.
- .7 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.
- .8 Conceal pipes, ducts and wiring in floor, wall and ceiling construction of finished areas except where indicated otherwise.

**Part 2 Products**

**2.1 NOT USED**

- .1 Not Used.

**Part 3 Execution**

**3.1 NOT USED**

- .1 Not Used.

**END OF  
SECTION**