

## **PART 1 - GENERAL**

### **1.1 RELATED SECTIONS**

- .1 Section 07 21 13 - Board Insulation.

### **1.2 REFERENCES**

- .1 American Society for Testing and Materials International (ASTM)
  - .1 ASTM C 665-12, Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing.
- .2 Underwriters Laboratories of Canada (ULC)
  - .1 CAN/ULC-S604-M1991, Type A Chimneys.

### **1.3 SUBMITTALS**

- .1 Product Data:
  - .1 Submit manufacturer's printed product literature, specifications and data sheet in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Manufacturer's Instructions:
  - .1 Submit manufacturer's installation instructions.

### **1.4 WASTE MANAGEMENT AND DISPOSAL**

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.
- .3 Collect and separate for disposal paper, plastic, polystyrene, corrugated cardboard and packaging material in appropriate on-site for recycling in accordance with Waste Management Plan.

## **PART 2 - PRODUCTS**

### **2.1 INSULATION**

- .1 Batt and blanket mineral fibre: to ASTM C.
    - .1 Type: 1.
    - .2 Thickness: as indicated on drawings.
-

### **PART 3 - EXECUTION**

#### **3.1 MANUFACTURER'S INSTRUCTIONS**

- .1 Compliance: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.

#### **3.2 INSULATION INSTALLATION**

- .1 Install insulation to maintain continuity of thermal protection to building elements and spaces.
- .2 Fit insulation closely around electrical boxes, pipes, ducts, frames and other objects in or passing through insulation.
- .3 Do not compress insulation to fit into spaces.
- .4 Keep insulation minimum 75 mm from heat emitting devices such as recessed light fixtures, and minimum 50 mm from sidewalls of CAN/ULC-S604 Type A chimneys and CAN/CGA-B149.1 and CAN/CGA-B149.2 Type B and L vents.
- .5 Do not enclose insulation until it has been inspected and approved by Departmental Representative.

#### **3.3 CLEANING**

- .1 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.