
PLEASANT CAMP, BRITISH COLUMBIA, PORT OF ENTRY TENDER A - SITE SERVICES & SITE SERVICES BUILDING



DRAWING LIST

COVER SHEET

ARCHITECTURAL			
A-101	OVERALL SITE PLAN		
A-201	FLOOR PLAN		
A-301	BUILDING SECTIONS		
A-401	EXTERIOR ELEVATIONS		
A-402	EXTERIOR ELEVATIONS		
A-501	WALL SECTIONS		
A-601	DETAILS & DOOR SCHEDULE		
A-602	DETAILS & WELL ENCLOSURE		
<u>STRUCTURAL</u>			
S-001	GENERAL NOTES & SPECIFICATION		
S-002	SPECIFICATION		
S-101	FOUNDATION AND MAIN FLOOR PLAN		
S-102	ROOF PLAN		
S-301	SECTIONS		
S-501	DETAILS		
S-502	DETAILS		
S-503	DETAILS		
S-504	DETAILS		
S-601	BRACING DIAGRAM		

CODE SUMMARY & ASSEMBLIES

EXISTING SITE BUILDINGS & U/G SERVICES PLAN

F-004 F-005 F-006 F-007 F-008	SITE SERVICES BUILDING PLAN & DETAILS MECHANICAL / CIVIL DETAILS MECHANICAL / CIVIL DETAILS ELECTRICAL SCHEMATICS & DETAILS ELECTRICAL SCHEMATICS & DETAILS
<u>MECHANICA</u>	<u>.L</u>
M001	MECHANICAL SITE PLAN & LEGENDS
M002	MECHANICAL DETAILED DEMO & NEW SITE
PLAN	
M101	SITE SERVICES BUILDING
M102	WELL PLANS & DETAILS
M501	DETAILS
M701	SCHEDULES & CONTROLS SCHEMATICS
ELECTRICAL	
E101	SITE PLAN - EXISTING SHALLOW UTILITIES PLAN 8
LIUI	MINOR MODIFICATIONS
E102	SITE PLAN - UTILITIES PLAN
E103	SITE PLAN - HEAT TRACE
E201	SITE SERVICES BUILDING PLAN
E202	SITE SERVICES BUILDING DETAILS
E202	MOTOR/EQUIPMENT LISTS
E301	SINGLE LINE DIAGRAM
E302	ELECTRICAL DETAILS
E303	TRENCHING DETAILS

Government Se Canada

REAL PRO

Travaux publics et
Services gouvernementaux

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique



Stantec Architecture Ltd.

authorized by Stantec is forbidden.

www.stantec.com

Copyright Reserved

SOIL REMEDIATION AREAS

APPROXIMATE LIMIT OF REMEDIAL EXCAVATION AND PROPOSED FUTURE PORT FACILITY LAYOUT

SOILS QUALITY

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Date
Client/cli	ent	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY

TENDER A

SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Or

Designed by/Concept p

Drawn by/Dessine par

Regional Manager, Architectural and Engineering Services Gestionnaire régionale. Services d'architectural et de génie. TPS

Drawing title/Titre du dessin

COVER SHEET

Project No./No. du projet

R.071363.001

Sheet/Feuille

G001

1 La Révision no.

ISSUED FOR TENDER, REVISION 0 FEBRUARY 2, 2015

PWGSC Project Number: R.071363.001 Stantec Project Number: 144901928

BUILDING CODE SUMMARY ANALYSIS

BUILDING CLASSIFICATION

SERVICES BUILDING, PLEASANT CAMP Part 9 - Group F, Division 3 (Low-Hazard Industrial) Table 9.10.2.1 Major Occupancy

Building Height One Storey Sprinklered 110.2 sm Building Area Streets Facing Combustible

Construction

FLOOR AREAS SERVICES BUILDING, PLEASANT CAMP

Room Area (sm) 42.4 Water Treatment 26.5 Electrical 25.8 Generator 15.5 Mechanical 110.2 Total Gross Area

OCCUPANCY LOAD CALCULATION (3.1.17)

Pleasant Camp, Site Services Building

Floor Area (sm) Area /person (sm) Occupant Load (persons) Floor/Type Use

Service rooms 110.2 Grand Total Occupant Load: (NBCC - Table 3.1.17.1)

* Note: This is considered an unoccupied Services building.

3.4.2.1 HEALTH REQUIREMENTS

 Water Closets: No water closets are required as this is strictly a services building and considered unoccupied. Washrooms are available elsewhere on the site

3.4.2.2 FIRE SEPARATIONS

• This building has multiple services so FRR separations between rooms apply (Section

3.3).

• Emergency Power requires a two-hour FRR separation from other occupancies.

(Sentence 3.2.7.9) This has been provided for the Generator room.

A one-hour FRR separation is required at service rooms with fuel-fired appliances.

(Sentence 9.10.10.4) This has been provided in the Mechanical Room.

• A one-hour FRR separation is required at electrical service room. (Sentence 3.6.2.1)

This has been provided in the Electrical Room. • FRR Separation wall to be a continuous, smoke-tight barrier that abuts a ceiling or

roof. (Sentence 9.10.9.2)

• Penetrations of Fire Separations to be sealed and tightly fitted to maintain the

integrity of the separation. (Section 9.10.9.6)

3.4.2.3 FLAME SPREAD LIMITS

All interior walls and ceilings to have a surface flame-spread rating of not more than

150. (Sentence 9.10.17.1) Doors to have a flame-spread rating of not more than

3.4.2.4 SOUND CONTROL

Sound control not required for this occupancy. (Section 9.11)

3.4.2.5 EXITS FROM FLOOR AREAS

• Number of Exits: Individual doors provided at each room, which exit to the exterior

• Exit Signs: Exit signs are not required. [Sentence 9.9.11.3 (1)]

3.4.2.6 BARRIER-FREE DESIGN

• Barrier-Free design not required because this is a non-occupied services building.

3.4.2.7 ROOF SPACES, VENTING

• Roof venting required, unless shown to be unnecessary. (Section 9.19)

3.4.2.8 CANOPY STRUCTURE

Canopy over fuel tank to be noncombustible construction (steel structure and

columns) c/w exposed structure. Steel structure to be separate from adjacent combustible construction Services building.

area is less than 300m2 (NBCC 9.36.1.3 (2b)

3.4.2.9 ENERGY EFFICIENCY

• Compliance to 9.36. does NOT apply to this building because the combined floor

CONTRUCTION ASSEMBLIES

INTERIOR WALL ASSEMBLIES

1. ALL FIRE AND SOUND RATED PARTITIONS ARE TO EXTEND TO THE UNDERSIDE OF STRUCTURE. INSTALL FIRE STOPPING AT

2. ALL STEEL STUD PARTITIONS TO HAVE MID-HEIGHT CONTINUOUS BRIDGING CHANNEL C/W BRIDGING ANGLE CLIP

3. LOCATE CONTROL JOINTS AT 9.144M O.C. ON 1524 MODULE OR ABOVE DOOR FRAME CORNER WHEREVER POSSIBLE 4. IN SOUND CONTROL ASSEMBLIES, ACOUSTICALLY SEAL PERIPHERY OF WALL AND ALL PENETRATIONS AIRTIGHT

GW1 - GENERATOR ROOM - WATER TREATMENT ROOM SOUND CONTROL - STC 58

2.0HR FRR - NBC ASSEMBLY W6b - TABLE 9.10.3.1

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED 1 LAYER 16mm TYPE X GWB 38x140 WOOD STUDS @ 400 O.C. 89mm THICK ABSORPTIVE MATERIAL

RESILIENT METAL CHANNELS @ 600 O.C. 1 LAYER 16mm TYPE X GWB

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED

5. IN FIRE RATED ASSEMBLIES, PROVIDE APPROVED FIRE STOPS AT ALL PENETRATIONS.

GW2 - GENERATOR ROOM - ELECTRICAL ROOM

SOUND CONTROL - STC 58 2.0HR FRR - NBC ASSEMBLY W6b - TABLE 9.10.3.1

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED

1 LAYER 16mm TYPE X GWB RESILIENT METAL CHANNELS @ 600 O.C. 38x140 WOOD STUDS @ 400 O.C. 89mm THICK ABSORPTIVE MATERIAL

1 LAYER 16mm TYPE X GWB 19mm PLYWOOD - PRIMED AND PAINTED

1 LAYER 16mm TYPE X GWB

GW3 - MECHANICAL ROOM - ELECTRICAL ROOM 1.0 FRR - NBC ASSEMBLY W1d - TABLE 9.10.3.1

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED

38x140 STUDS @ 400 O.C. 1 LAYER 16mm ABUSE RESISTANT TYPE X GWB

1 LAYER 19mm PLYWOOD - PRIMED AND PAINTED (ELECTRICAL ROOM SIDE)

GW4 - WATER TREATMENT ROOM - CHLORINE ROOM

PEEL AND STICK AIR VAPOUR BARRIER (WATER ROOM SIDE) 1 LAYER 12.7mm PLYWOOD

38x89 STUDS @ 400 O.C.

1 LAYER 12.7mm G1S PLYWOOD - PRIMED AND PAINTED

GW5 - NOT USED

GW6 - MECHANICAL ROOM - WATER TREATMENT ROOM - ELECTRICAL ROOM 1.0 FRR - NBC ASSEMBLY W1d - TABLE 9.10.3.1

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED

38x140 STUDS @ 400 O.C. 1 LAYER 16mm ABUSE RESISTANT TYPE X GWB

PEEL AND STICK AIR VAPOUR BARRIER (WATER TREATMENT ROOM SIDE)

GW7 - MECHANICAL ROOM - FURRING WALL

1 LAYER 16mm ABUSE RESISTANT TYPE X GWB - PRIMED AND PAINTED

EXTERIOR WALL ASSEMBLY

HORIZONTAL CEMENTITIOUS PLANK SIDING (EXISTING MAINTENANCE BUILDING FINISH TO MATCH) 19x89 STRAPPING

WEATHER BARRIER

206mm S.I.P. c/w S.I.P. TAPE TO SEAL JOINTS

19x89 STRAPPING INTERIOR MATERIAL AND FINISH TO MATCH ADJACENT INTERIOR WALL ASSEMBLIES IN EACH ROOM

* NOTE: 19x89 STRAPPING TO BE REPLACED WITH RESILIENT CHANNEL ON INTERIOR OF GENERATOR ROOM * NOTE: PEEL AND STICK MEMBRANE TO BE APPLIED FROM 150mm ABOVE BASE OF S.I.P. OVER TOP OF FOOTING. REFER TO

EW2

HORIZONTAL CEMENTITIOUS PLANK SIDING (TO MATCH NEW SITE SERVICE BUILDING) WEATHER BARRIER 13mm PWF PLYWOOD

38x89 PWF STUDS @ 400 O.C.

13mm PWF PLYWOOD

SECTIONS AND DETAILS.

ROOF ASSEMBLY

GALVALUME METAL ROOFING ICE AND WATER SHIELD

19mm PLYWOOD SHEATHING

PRE-MANUFACTURED WOOD ROOF TRUSSES (SLOPE TO MATCH EXISTING)

206mm S.I.P. TO U/S OF TRUSSES - REFER TO STRUCTURAL FOR FASTENING REQUIREMENTS PRIME AND PAINT AREAS OF EXPOSED S.I.P

GALVALUME METAL ROOFING GALVANIZED METAL DECKING STRUCTURAL STEEL FRAMING

FLOOR ASSEMBLY

150mm CONCRETE SLAB ON GRADE - FINISH PER SPECIFICATIONS 6 mil POLY VAPOUR BARRIER 100mm HI DENSITY RIGID INSULATION COMPACTED GRANULAR FILL

150mm CONCRETE SLAB ON GRADE - FINISH PER SPECIFICATIONS

COMPACTED GRANULAR FILL - REFER TO STRUCTURAL

- REFER TO STRUCTURAL

GENERAL NOTES:

- 1. ARCHITECTURAL DRAWINGS TO BE READ IN CONJUNCTION WITH STRUCTURAL, MECHANICAL AND ELECTRICAL DRAWINGS.
- 2. ALL CONSTRUCTION MUST MEET OR EXCEED THE REQUIREMENTS OF THE NATIONAL BUILDING CODE 2010.
- 3. ALL WORK TO BE PERFORMED IN ACCORDANCE WITH GOOD BUILDING PRACTICES. CONTRACTOR TO
- CAREFULLY INSPECT THE SITE OF WORK AND BE FULLY INFORMED OF CONDITIONS AND LIMITATIONS.
- 4. CONTRACTOR TO CONFIRM ALL DIMENSIONS ON SITE AND IMMEDIATELY REPORT ANY DISCREPANCIES TO THE DESIGN TEAM PRIOR TO PROCEEDING.
- 5. CONFIRM ALL ELEVATIONS (INCLUDING SLABS, LANDSCAPING, ETC.) ON SITE. REPORT ANY VARIANCES TO CONSULTANT.
- 6. PROVIDE MINIMUM 2% SLOPE AWAY FROM THE BUILDING FOR ALL EXTERIOR GRADING U.N.O. OR DICTATED BY EXIST. SITE CONDITIONS. CONFIRM WITH CONSULTANT.
- 7. WALLS NOT LOCATED BY DIMENSIONS ARE ASSUMED TO BE CENTERED ON GRID LINES. ALL DIMENSIONS ARE FROM CENTRELINE OF STUD U.N.O.

8. DOOR AND WINDOW SIZES ARE NOMINAL. CONTRACTOR TO CONSULT SUPPLIER FOR EXACT SIZES AND

- ROUGH OPENINGS.
- 9. INSTALL ALL DOORS AND FRAMES WITH A CLEAR DIMENSION OF 100MM IN STUD WALLS BETWEEN THE FRAME AND THE NEAREST ADJACENT WALL UNLESS NOTED OTHERWISE.
- 10. USE TYPE 'X' GWB ON ALL FIRE-RATED GWB PARTITIONS. REFER TO CODE INFORMATION. 11. WHERE MECHANICAL DUCTS AND ELECTRICAL CONDUIT PENETRATE FIRE SEPARATIONS OR WALLS WHICH ARE CONSTRUCTED TO U/S OF STRUCTURE, PROVIDE FIRESTOPPING AND SMOKE SEALS AT
- 12. PROVIDE ALL FRAMING / BLOCKING AS REQUIRED TO ENSURE PROPER SECUREMENT OF ALL MATERIALS, EQUIPMENT, ACCESSORIES, ETC. PROVIDE BACKING FOR ITEMS NOTED AS - IN CONTRACT (I.C.), NOT IN CONTRACT (N.I.C.), AND OWNER SUPPLIED CONTRACTOR INSTALLED (O.S.), PROVIDE BLOCKING IN STUD PARTITIONS BEHIND ALL WALL-MOUNTED ITEMS. ALSO REFER TO M AND E SERIES DRAWINGS.
- 13. PROVIDE FLASHING OVER ALL EXTERIOR DOORS AND WINDOWS.

PENETRATIONS TO MAINTAIN FRR NOTED ON PARTITION TYPES SCHEDULE.

- 14. MAINTAIN INTEGRITY OF THE VAPOUR / AIR BARRIER MEMBRANE IN THE EXTERIOR WALLS & ROOF STRUCTURE. ALL MEMBRANES ARE TO BE CONTINUOUS & HAVE A MINIMUM OVERLAP OF 200MM AT ALL FLASHINGS, JOINTS, CHANGES IN DIRECTION, DOORS, ETC.
- 15. PROVIDE CONTINUOUS ROD AND SEALANT AT ALL JUNCTIONS OF DISSIMILAR MATERIALS, CONTROL JOINTS AND OTHER LOCATIONS WHERE INDICATED.

19. PAINT ALL EXPOSED STRUCTURE AND MECHANICAL DUCTS. REFER TO FINISH SCHEDULE


- 16. ALL MATERIALS TO BE PRIMED AND PAINTED U.N.O.
- 17. FOR DOOR SCHEDULE, REFER TO DRAWINGS AND SPECIFICATIONS
- 18. FOR FINISH SCHEDULE, REFER TO DRAWINGS AND SPECIFICATIONS


SYMBOLS LEGEND:

*(*107.800\

T/O MECHANICAL FLOOR

RECEPTION





ELEVATION / LEVEL

REFERENCE

SPOT ELEVATION

111	ROOM NAME, NUMBER AND AREA REFERENCE
IW8	CONSTRUCTION ASSEMBLY REFERENCE
111.1	DOOR TYPE REFERENCE
₩5>	WINDOW TYPE REFERENCE
1	KEYNOTES

Public Works and Government Services

Travaux publics et Services gouvernementaux

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay. The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



ISSUED FOR TENDER Description/Description

> **CANADA BORDER SERVICES AGENCY**

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A**

SITE SERVICES & SITE SERVICES BUILDING

nsultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

Regional Manager, Architectural and Engineering Services Sestionnaire régionale, Services d'architectural et de génie, TPSGC Drawing title/Titre du dessin


CODE SUMMARY & ASSEMBLIES


R.071363.001


G002

DM5XXXXXX


PWGSC - A1 - 841X594







NOTE: BUILDING WIDTH AND HEIGHT TO MATCH EXISTING MAINTENANCE BUILDING. CONTRACTOR TO COORDINATE AND FIELD VERIFY DIMENSIONS.



FLOOR PLAN

LEGEND

1 HR FIRE RATED ASSEMBLY 2 HR FIRE RATED ASSEMBLY Public Works and Government Services Services gouvernementaux Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.







0	ISSUED FOR TENDER	15/02/0
Revision/ Revision	Description/Description	Date/Da
Client/client		

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Designed by/Concept par

Drawn by/Dessine par

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin


SITE SERVICES BUILDING FLOOR PLAN

R.071363.001

A201

DM5XXXXXX

0 10 20 30 40 50 60 70 80 90 100mm



Public Works and Government Services Services gouvernementaux Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/clie	nt	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Designed by/Concept par

Drawn by/Dessine par


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC


Drawing title/Titre du dessin SITE SERVICES BUILDING


BUILDING SECTIONS

R.071363.001

Revision no La Révision A301







Public Works and
Government Services
Canada

Travaux publics et
Services gouvernementaux
Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay. The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/client		

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Designed by/Concept par


Drawn by/Dessine par


Drawing title/Titre du dessin

SITE SERVICES BUILDING **EXTERIOR ELEVATIONS**

Revision no La Révision A401

R.071363.001





Public Works and Government Services Canada

Travaux publics et
Services gouvernementaux
Canada

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/client		

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY

TENDER A

SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSG

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSI


Drawing title/Titre du dessin
SITE SERVICES BUILDING


EXTERIOR ELEVATIONS


Project No./No. du Sheet/Fe projet R.071363.001

Revision no La Révision no.

OF







DESIGN NOTES

<u>GENERAL</u>

- 1. ALL CODES REFERENCED ARE TO BE THE LATEST VERSION AT THE DATE OF
- 2. DESIGN IS BASED ON THE NATIONAL BUILDING CODE 2010.
- 3. READ THESE DESIGN NOTES IN CONJUNCTION WITH THE CONTRACT SPECIFICATIONS AND ALL OTHER CONTRACT DOCUMENTS.
- 4. OBTAIN ENGINEER'S APPROVAL BEFORE CUTTING, BORING, OR SLEEVING
- LOAD—BEARING MEMBERS UNLESS NOTED OTHERWISE.

 5. THE STRUCTURAL DRAWINGS ARE FOR THE COMPLETED PROJECT. STABILITY OF THE EXISTING AND NEW STRUCTURE DURING CONSTRUCTION REMAINS THE
- RESPONSIBILITY OF THE CONTRACTOR.

 6. REFER TO ARCHITECTURAL, MECHANICAL, AND ELECTRICAL DRAWINGS FOR SMALL OPENINGS, SLEEVES, RECESSES, DEPRESSIONS, SUMPS, TRENCHES, CURBS, HOUSEKEEPING PADS, EQUIPMENT BASES, AND SLOPES NOT INDICATED ON THE
- STRUCTURAL DRAWINGS.

 7. OPENINGS AND SLEEVES INDICATED ON THE STRUCTURAL DRAWINGS ARE FOR REFERENCE ONLY. COORDINATE ALL OPENING LOCATIONS AND DIMENSIONS WITH THE APPROPRIATE CONSULTANT AND THE SUB-CONTRACTOR PRIOR TO
- 8. REVIEW ALL DRAWINGS AND CHECK DIMENSIONS PRIOR TO IMPLEMENTING THE WORK. REPORT ANY DISCREPANCIES TO THE CONSULTANT FOR CLARIFICATION
- 9. COORDINATE PLACEMENT AND LOCATION OF ITEMS BY SUBSEQUENT TRADES. RELEVANT TRADES SHALL REVIEW PRIOR TO ERECTION AND/OR INSTALLATION.
- 10. NOTIFY THE ENGINEER A MINIMUM OF 72 HOURS PRIOR TO ANY REQUIRED SITE REVIEWS.

EXISTING STRUCTURES

- 1. THE STRUCTURAL DESIGN IS BASED ON INFORMATION GATHERED FROM THE RECORD DRAWINGS AND FROM LIMITED VISUAL OBSERVATIONS ON SITE.
- 2. VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS ON SITE PRIOR TO IMPLEMENTING AFFECTED WORK.
- 3. NOTIFY THE CONSULTANT OF ANY SITE CONDITIONS THAT DIFFER FROM THE CONTRACT DOCUMENTS OR THE RECORD DRAWINGS.
- 4. SHORE AND UNDERPIN EXCAVATIONS AS REQUIRED TO PREVENT DISTURBANCE TO ADJACENT STRUCTURES, STREETS, SIDEWALKS AND UTILITIES.

DESIGN LOAD

- 1. UNLESS NOTED OTHERWISE, THE LOADS NOTED IN TABLES AND ON DRAWINGS ARE UNFACTORED.
- 2. CLIMATIC INFORMATION REFE
 - REFER TO CLIMATIC INFORMATION TABLE
- 3. SITE INFORMATION
- REFER TO SITE INFORMATION TABLE
 REFER TO DESIGN LOADS TABLE
- 4. DESIGN LOADS
 - ATERAL LOADS
 - 5.1 LATERAL LOADS FROM WIND AND SEISMIC LOADS ARE RESISTED BY THE FOLLOWING ELEMENTS: STEEL
- BRACING, AND WOOD PANEL SHEAR WALLS.
- 6. CONSTRUCTION LOADS SHALL NOT EXCEED THE LOADS NOTED ON THE DRAWINGS.

7. <u>DELEGATED DESIGN</u>

- 1. PORTIONS OF THE DETAILED DESIGN ARE DELEGATED TO THE CONTRACTOR][TRADE CONTRACTOR. RETAIN A PROFESSIONAL ENGINEER REGISTERED IN THE PROVINCE OF BRITISH COLUMBIA TO COMPLETE THE DESIGN.
- 2. SUBMIT SHOP DRAWINGS FOR COMPONENTS REQUIRING DELEGATED DESIGN UNDER THE SEAL AND SIGNATURE OF THE ENGINEER RESPONSIBLE FOR THE
- 3. THE FOLLOWING COMPONENTS REQUIRE DELEGATED DESIGN:
- 3.2. STRUCTURAL STEEL CONNECTIONS
- 3.3. SLIP CRITICAL CONNECTIONS FOR STEEL BRACING
- 3.4. SIP PANELS INCLUDING CONNECTIONS
- 3.5. PRE—FABRICATED WOOD TRUSSES
- 4. THE ENGINEER RESPONSIBLE FOR THE DESIGN IS ALSO RESPONSIBLE FOR REVIEW OF FABRICATION AND INSTALLATION OF THE COMPONENTS. UPON COMPLETION OF THE WORK, CERTIFY IN WRITING TO THE CONSULTANT THAT SUCH REVIEW HAS BEEN COMPLETED
- 4. REFER TO SPECIFICATIONS FOR FURTHER REQUIREMENTS.

FOUNDATION AND GEOTECHNICAL NOTES

- 1. FOUNDATION DESIGN IS BASED ON THE FOUNDATION INVESTIGATION SOILS REPORT NUMBER W14103501-01 PREPARED BY TETRA TECH EBA, AND DATED DECEMBER 9,2014. ENSURE THAT THE REQUIREMENTS OUTLINED IN THE REPORT ARE READ AND UNDERSTOOD PRIOR TO COMMENCING WITH FOUNDATION WORK.
- 2. BEAR ALL FOOTINGS ON UNDISTURBED SOIL NOTWITHSTANDING THE ELEVATIONS INDICATED ON THE DRAWINGS.
- 3. BRING OVER—EXCAVATION AND CAVITIES IN THE FOOTING BASE UP TO THE REQUIRED LEVELS WITH 10 MPa CONCRETE.
- 4. REMOVE ALL ORGANIC MATERIAL FROM THE BUILDING AREA AS OUTLINED IN THE GEOTECHNICAL REPORT.
- 5. REMOVE ALL LOOSE OR SATURATED MATERIAL AND GROUNDWATER FROM THE BASE OF FOOTING EXCAVATIONS BY APPROVED METHODS PRIOR TO PLACING FOUNDATIONS.
- 6. PROTECT EXCAVATIONS FOR FOOTINGS FROM RAIN, SNOW, FREEZING TEMPERATURES, STANDING WATER, LOSS OF MOISTURE AND DEGRADATION BY APPROVED METHODS.
- 7. BEARING SURFACES TO BE INSPECTED IN THE FIELD BY A PROFESSIONAL GEOTECHNICAL ENGINEER REGISTERED IN THE PROVINCE OF BRITISH COLUMBIA PRIOR TO PLACING CONCRETE.
- 8. GEOTECHNICAL TESTING AGENCY TO BE APPROVED BY AND RESPONSIBLE TO THE ENGINEER.
- 9. UNLESS OTHERWISE SHOWN ON PLAN, FOUNDATION ELEMENTS ARE TO BE

CENTERED UNDER WALLS, AND COLUMNS.

10. FOR BACKFILL MATERIAL SEE GEOTECHNICAL REPORT.

CAST-IN-PLACE REINFORCED CONCRETE

- 1. CONCRETE MATERIALS, QUALITY, MIXING, PLACING, FORMWORK AND OTHER CONSTRUCTION PRACTICES TO CONFORM TO THE LATEST EDITION OF CSA A23.1, A23.2, AND A23.3.
- 2. SUPPLY CONTROLLED CONCRETE IN ACCORDANCE WITH CSA-A23.1 WITH PROPERTIES NOTED IN CONTROLLED CONCRETE TABLE.
- 3. NOTIFY CONSULTANT 72 HOURS PRIOR TO CONCRETE POURS TO ALLOW FOR REVIEW OF REINFORCEMENT.
- 4. DO NOT USE ADMIXTURES CONTAINING CALCIUM CHLORIDE.
- 5. FOR FLOOR SLABS, DESIGN THE CONCRETE MIX WITH AGGREGATE GRADING AND WATER TO CEMENTING MATERIALS RATIO TO MINIMIZE SHRINKAGE.
- 6. FIELD AND LABORATORY TESTING OF CONCRETE TO BE COMPLETED BY A THIRD PARTY TESTING AND INSPECTION AGENCY APPROVED BY AND RESPONSIBLE TO THE ENGINEER. TESTING AGENCY SHALL BE CERTIFIED TO CSA—A283 AND TESTING TO BE COMPLETED IN ACCORDANCE WITH CSA—A23.2.
- 7. DO NOT PLACE LOAD ON NEW CONCRETE OR POUR NEW CONCRETE ON NEW CONCRETE UNTIL AT LEAST 75% OF ITS 28 DAY STRENGTH IS ATTAINED. CONCRETE QUALITY CONTROL TESTING SHALL BE COMPLETED BY QUALIFIED PERSONNEL AND REPORTS ARE TO BE SUBMITTED TO THE ENGINEER.
- 8. BUILDING IS NOT TO BE PUT INTO SERVICE UNTIL ALL CONCRETE COMPONENTS HAVE CURED FOR 28 DAYS OR PROOF THAT THE 28 DAY STRENGTH HAS BEEN ATTAINED THROUGH QUALITY CONTROL TESTING.
- FILL ALL HOLES IN CONCRETE MEMBERS CAUSED BY CONSTRUCTION PRACTICE WITH NON-SHRINK GROUT WITH A COMPRESSIVE STRENGTH EQUAL TO THAT OF THE CONCRETE.
- 10. UNLESS OTHERWISE SPECIFIED, ALL CONCRETE ANCHOR BOLTS SHALL BE GRADE A307.
- 11. PROVIDE 6mil POLYETHYLENE GROUND SHEETS UNDER ALL SLAB-ON-GRADES.
 LAP SEAMS AM MINIMUM OF 150mm AND TAPE THE ENTIRE LENGTH OF ALL
- 12. CONCRETE SHALL NOT BE POURED IN AN UNCONFINED MANNER FROM A HEIGHT OF MORE THAN 1220mm.
- 13. ALL BENDS IN PRIMARY REINFORCEMENT TO HAVE A RADIUS OF NOT LESS THAN 3 TIMES THE BAR DIAMETER.
- 14. QUALITY CONTROL TESTING OF THE CONCRETE AND GROUTS MUST BE COMPLETED BY QUALIFIED PERSONNEL AND REPORTS ARE TO BE SUBMITTED TO THE ENGINEER OF RECORD.
- 15. ALL CONTROL JOINTS SHALL BE SAW—CUT TO A DEPTH OF 1/4 OF THE SLAB THICKNESS OR 25mm, WHICHEVER IS GREATER. FILL ALL JOINTS WITH ELASTOMERIC JOINT SEALANT.
- 16. ALL GROUT UNDER BEARING PLATES AND BASE PLATES SHALL BE NON-METALLIC, NON-SHRINK TYPE WITH MINIMUM 72 HOUR/28 DAY COMPRESSIVE STRENGTH OF 20/50 MPa, INSTALLED IN ACCORDANCE WITH THE SPECIFICATION AND MANUFACTURER'S RECOMMENDATIONS. PROVIDE GROUT WEEP HOLES IN COLUMN BASE PLATES WHERE SHOWN

CONCRETE REINFORCEMENT

- 1. REINFORCEMENT STEEL TO CONFORM TO CSA-G30.18 GRADE 400W.
- 2. DO NOT WELD REINFORCEMENT UNLESS APPROVED IN WRITING BY THE ENGINEER. REINFORCEMENT TO BE WELDED TO CONFORM TO CSA G30.18 GRADE 400W.
- 3. NOTIFY THE ENGINEER PRIOR TO CONCRETE PLACEMENT TO ALLOW FOR REVIEW OF REINFORCEMENT.
- 4. CLEAR CONCRETE COVER TO REINFORCEMENT REFER TO CLEAR CONCRETE COVER TO REINFORCEMENT TABLE.
- 5. STANDARD END HOOK LENGTHS FOR REINFORCEMENT REFER TO STANDARD END HOOKS TABLE.
- 6. REINFORCEMENT SPLICES REFER TO REINFORCEMENT SPLICES TABLE.6.14. WHERE SPLICES ARE INDICATED ON THE DRAWINGS, SUCH DIMENSIONS
- SHALL APPLY.

 6.15 WHERE THE DRAWINGS INDICATE TENSION OR COMPRESSION SPLICES IT.
- 6.15. WHERE THE DRAWINGS INDICATE TENSION OR COMPRESSION SPLICES, IT SHALL BE AS INDICATED IN REINFORCEMENT SPLICES TABLE.
- 6.16. WHERE NO SPLICE OR SPLICE TYPE IS INDICATED ON THESE DRAWINGS, IT SHALL BE A TENSION SPLICE EXCEPT FOR COLUMNS WHICH SHALL BE A COMPRESSION SPLICE.
- 7. EMBEDMENT OF DOWELS REFER TO REINFORCEMENT SPLICES TABLE.
 - 7.1. WHERE EMBEDMENT IS DIMENSIONED ON THE DRAWINGS, SUCH DIMENSIONS SHALL APPLY.
 - 7.2. WHERE THE DRAWINGS INDICATE TENSION OR COMPRESSION EMBEDMENT, IT SHALL BE AS NOTED IN THE REINFORCEMENT SPLICES TABLE.
 - 7.3. WHERE NO EMBEDMENT OR EMBEDMENT TYPE IS INDICATED ON THESE DRAWINGS, IT SHALL BE A TENSION EMBEDMENT EXCEPT FOR COLUMNS WHICH SHALL BE A COMPRESSION EMBEDMENT.
- 8. OPENINGS IN WALLS AND SLABS UNLESS NOTED OTHERWISE PROVIDE TWO 15M BARS EACH SIDE, ONE EACH FACE, EXTENDING 600 mm PAST THE OPENINGS, PLUS TWO 15M DIAGONAL BARS 1.5 TIMES THE LENGTH OF SHORTEST SIDE OF OPENING OR MINIMUM 500 mm AND MAXIMUM 1500 mm IN LENGTH AT EACH CORNER.
- 9. DO NOT CUT REINFORCEMENT AT OPENINGS WHERE IT CAN BE SPREAD CONTINUOUS AROUND OPENING.
- 10. ALL REINFORCEMENT TO BE SUPPORTED AT 900 mm MAXIMUM SPACING.

CONCRETE FORMWORK

- 1. DESIGN, FABRICATION, ERECTION, AND OTHER CONSTRUCTION PRACTICES TO CONFORM TO CAN/CSA-S269.3.
- 2. REFER TO SPECIFICATIONS AND ARCHITECTURAL DRAWINGS FOR CHAMFERS ON CORNERS .

STRUCTURAL STEEL

DESIGN, FABRICATION, ERECTION, AND OTHER CONSTRUCTION PRACTICES TO CONFORM TO CSA—S16 AND THE CISC CODE OF STANDARD PRACTICE FOR STRUCTURAL STEEL.

- 2. STEEL TO BE FABRICATED AND ERECTED BY A SHOP CERTIFIED BY THE CANADIAN WELDING BUREAU TO THE REQUIREMENTS OF CSA-W47.1, DIVISION 1 OR 2.1
- 3. SUBMIT SHOP DRAWINGS SHOWING ALL STRUCTURAL STEEL MEMBERS FOR REVIEW PRIOR TO FABRICATION. WELDING TO CONFORM TO CSA—W59.
- 4. WELDING TO REINFORCEMENT STEEL ONLY BY A SHOP CERTIFIED TO CSA-W186 WITH REINFORCEMENT CONFORMING TO CSA-G30.18, GRADE 400W.
- 5. SHOP GALVANIZING TO CONFORM TO CAN/CSA-G164.
- ALL EXPOSED WELDS TO BE CONTINUOUS. GRIND ALL EXPOSED WELDS SMOOTH, INCLUDING PAINTED STEEL.
- 7. SUPPLY STEEL WITH PROPERTIES NOTED IN STEEL GRADES TABLE.
- 8. CONNECTIONS NOT DETAILED ON THE STRUCTURAL DRAWINGS SHALL BE DESIGNED AND DETAILED BY A PROFESSIONAL STRUCTURAL ENGINEER REGISTERED IN THE PROVINCE OF BRITISH COLUMBIA AT THE STEEL FABRICATOR'S EXPENSE.
- 9. UNLESS NOTED OTHERWISE, DESIGN CONNECTIONS FOR NON-COMPOSITE BEAMS FOR A FACTORED SHEAR FORCE EQUAL TO 80% OF THE TOTAL BEAM LOAD TABULATED IN THE CISC HANDBOOK OF STEEL CONSTRUCTION.
- 10. UNLESS NOTED OTHERWISE, DESIGN MOMENT CONNECTIONS FOR NON-COMPOSITE BEAMS FOR A FACTORED MOMENT EQUAL TO THE FULL MOMENT CAPACITY OF THE SMALLER MEMBER JOINED.
- 11. DESIGN BRACE CONNECTIONS FOR THE LOADS SHOWN ON THE DRAWINGS.
- 12. PROVIDED A MINIMUM OF 2 BOLTS IN BOLTED CONNECTIONS.
- 13. PROVIDE 12 mm PLATE STIFFENERS EACH SIDE OF BEAM WHERE AT ALL BEARING CONNECTIONS UNLESS OTHERWISE NOTED ON THE DRAWINGS.
- 14. DO NOT SPLICE MATERIAL WITHOUT THE WRITTEN APPROVAL OF THE ENGINEER. WHERE GRANTED, A COMPLETE NON-DESTRUCTIVE EXAMINATION WILL BE MANDATORY
- 15. PROVIDE 10 mm WEEP HOLES AT TOP AND BOTTOM OF ALL HSS COLUMNS.
- 16. ALL GROUT UNDER BEARING PLATES AND BASE PLATES SHALL BE NON-METALLIC, NON-SHRINK TYPE WITH MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 50 MPa, INSTALLED IN ACCORDANCE WITH THE SPECIFICATION AND MANUFACTURER'S RECOMMENDATIONS. PROVIDE GROUT WEEP HOLES IN COLUMN BASE PLATES WHERE SHOWN
- 17. SQUARE CUT OR FULL STRENGTH WELD ALL COLUMNS AT BASE PLATES AND AT TOP WHERE BEARING UNDER CONTINUOUS BEAMS.
- 18. ALL BOLTS AND WOOD FASTENERS PERMANENTLY EXPOSED TO THE ATMOSPHERE SHALL BE GALVANIZED OR ZINC PLATED.
- 19. ALL WELDS SHALL HAVE AN ULTIMATE STRENGTH OF NOT LESS THAN 490 MPa (E49XX ELECTRODES).
- 20. CLEAN, PREPARE AND PRIME ALL STRUCTURAL STEEL COLUMNS AND ANCHOR PLATES. DO NOT PRIME ANCHOR BOLTS, SURFACES IN CONTACT WITH CONCRETE OR ELEMENTS FORMING PART OF A SLIP—CRITICAL CONNECTION. DO NOT PRIME BEAMS OR STEEL JOIST PRODUCTS TO ALLOW FOR EASE OF APPLICATION OF
- 21. TOUCH-UP FIELD WELDS, CONNECTIONS AND ABRASIONS TO MATCH THE SHOP

STEEL DEC

- 1. DESIGN, FABRICATION, ERECTION, AND OTHER CONSTRUCTION PRACTICES TO CONFORM TO CAN/CSA-S136.
- 2. WELDING TO CONFORM TO CSA-W59. PLATE WASHERS MAY BE ELIMINATED ONLY IF WELDERS OR WELDING OPERATORS HAVE BEEN CERTIFIED BY THE CANADIAN WELDING BUREAU WITH QUALIFIED PROCEDURES FOR WELDING METAL DECK.
- 3. SHEET STEEL TO CONFORM TO ASTM A653/A653M, GRADE A STRUCTURAL QUALITY GRADE 230.
- 4. STEEL ROOF DECK UNLESS NOTED OTHERWISE ON DRAWINGS, 38mm DEEP PREFORMED ZINC-COATED STEEL IN ACCORDANCE WITH CSSBI 10M. FLUTES SPACED AT 150mm MAXIMUM ON CENTER.
- 5. UNLESS NOTED OTHERWISE, LIMIT ALLOWABLE DEFLECTION FOR STEEL ROOF DECK TO THE FOLLOWING:
 - a) LIVE LOAD SPAN/360
- b) TOTAL LOAD SPAN/240
- 6. DECK UNITS TO BE CONTINUOUS OVER AT LEAST THREE SUPPORTS WHERE STRUCTURAL FRAMING PERMITS.
- 7. PROVIDE L76x76x6.4 ANGLE TO SUPPORT DECK EDGES AT ALL OPENINGS UP TO 300mm IN SIZE, FOR LARGER OPENINGS, REFER TO TYPICAL DETAILS.

<u>TIMBER</u>

- ALL WOODEN MEMBERS SHALL BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH THE LATEST EDITION OF CSA 086.
- 2. UNLESS NOTED OTHERWISE, ROOF SHEATHING SHALL BE 18.5mm T&G CANADIAN SOFTWOOD PLYWOOD, SHEATHING/STANDARD GRADE (SHG). BLOCK AND NAIL WITH 3" NAILS @ 100mm O/C AT PANEL EDGES. NAILS INTERIOR OF PANELS WITH 3" NAILS @ 200mm O/C.
- 3. ENSURE ALL 75mm LONG NAILS HAVE A MINIMUM DIAMETER OF 3.66mm AND ALL 64mm LONG NAILS HAVE A MINIMUM DIAMETER OF 3.25mm. ALL SHEAR
- 4. UNLESS NOTED OTHERWISE, ALL DIMENSIONAL LUMBER SHALL BE SPECIES SPRUCE—PINE—FIR, GRADE No.1 / No.2.
 5. SIP WALL ANCHORAGE TO MAIN FLOOR SLAB AND FOUNDATION SHALL BE AS
- SHOWN ON THE DRAWING.

 6. INSTALL ROOF AND WALL ANCHORAGE AS PER DETAILS AND SCHEDULES.
- 7. ALL BOLTS CONNECTING WOOD TO WOOD OR WOOD TO CONCRETE SHALL BE GRADE ASTM A307. BOLTS SHALL BE GALVANIZED EXCEPT THOSE EMBEDDED INTO CONCRETE
- 8. ALL DIMENSIONAL LUMBER TO BE EXPOSED TO THE ATMOSPHERE SHALL BE PRESSURE TREATED OR FINISHED WITH A WEATHER RESISTANT COATING. ALL ENGINEERED LUMBER (LVL, PSL & GLULAM MEMBERS) TO BE EXPOSED TO THE ATMOSPHERE SHALL BE TREATED WITH A WEATHER RESISTANT COATING APPLIED AT THE MANUFACTURER'S FACILITY PRIOR TO SHIPMENT TO SITE.
- 9. RETREAT ALL CUT ENDS OF PRESSURE TREATED LUMBER WHICH REQUIRE ON—SITE CUTTING
- 10. ALL BOLTS AND WOOD FASTENERS PERMANENTLY EXPOSED TO THE ATMOSPHERE

SHALL BE GALVANIZED OR ZINC PLATED.

- 11. DESIGN CONNECTIONS IN ACCORDANCE WITH CSA-086 AND CSA-S16 FOR THE LOADS INDICATED ON THE DRAWINGS.
- 12. PROVIDED A MINIMUM OF 2 BOLTS IN BOLTED CONNECTIONS.
- 13. INSTALL SILL GASKET UNDER THE ALL SILL PLATES IN CONTACT WITH CONCRETE.

PREFABRICATED WOOD TRUSSES

- 1. MANUFACTURER SHALL BE RESPONSIBLE FOR USING LUMBER OF SUFFICIENT STRENGTH TO SAFELY CARRY ALL LOADS INDICATED ON THE DRAWINGS. PROVIDE ALL NECESSARY BLOCKING, BRACING, STIFFENERS AND CONNECTIONS IN ACCORDANCE WITH CSA-086.
- 2. ALL STRUCTURAL COMPOSITE LUMBER SHALL BE DESIGNED IN ACCORDANCE WITH CSA-086.
- 3. CONTRACTOR TO ENSURE TRUSS LOCATIONS ARE COORDINATED WITH ROOF PENETRATIONS, SEE ARCH. AND MECH. DRAWINGS
- 4. SUBMIT CHECKED SHOP DRAWINGS SIGNED AND SEALED BY PROFESSIONAL ENGINEER IN THE YUKON TERRITORY FOR REVIEW PRIOR TO FABRICATION.
- 5. CERTIFY AT THE COMPLETION OF WORK, ALL FABRICATED TRUSSES, SIP PANELS, STRUCTURAL COMPOSITE LUMBER AND ASSOCIATED COMPONENTS ARE FABRICATED AND ERECTED UNDER THE SEAL AND SIGNATURE OF THE CONTRACTORS' PROFESSIONAL STRUCTURAL ENGINEER RESPONSIBLE FOR THIS WORK.
- 6. CERTIFY THAT ALL FABRICATED TRUSSES, JOISTS, STRUCTURAL COMPOSITE LUMBER AND ASSOCIATED COMPONENTS ARE CAPABLE OF SUPPORTING ALL THE LOADS AND FORCES SPECIFIED IN THE CONTRACT SPECIFICATIONS AND ON THE DRAWINGS.
- 7. CERTIFY THAT ALL COMPONENTS ARE FABRICATED AND ERECTED IN ACCORDANCE WITH THE REVIEWED SHOP DRAWINGS.

STRUCTURAL INSULATED PANELS

- 1. MANUFACTURER SHALL BE RESPONSIBLE FOR USING LUMBER OF SUFFICIENT STRENGTH TO SAFELY CARRY ALL LOADS INDICATED ON THE DRAWINGS. PROVIDE ALL NECESSARY BLOCKING, BRACING, STIFFENERS AND CONNECTIONS IN ACCORDANCE WITH CSA—086.
- 2. UNLESS NOTED OTHERWISE, LIMIT ALLOWABLE DEFLECTION FOR WALL SIP PANELS TO THE FOLLOWING:

- LIVE LOAD - SPAN/240

THE REVIEWED SHOP DRAWINGS.

- 3. ALL STRUCTURAL COMPOSITE LUMBER SHALL BE DESIGNED IN ACCORDANCE WITH
- 4. CONTRACTOR TO ENSURE WALL & CEILING OPENINGS ARE COORDINATED WITH ARCH. AND MECH. DRAWINGS
- SUBMIT CHECKED SHOP DRAWINGS SIGNED AND SEALED BY PROFESSIONAL ENGINEER IN THE YUKON TERRITORY FOR REVIEW PRIOR TO FABRICATION.
 CERTIFY AT THE COMPLETION OF WORK SIP PANELS AND ASSOCIATED COMPONENTS ARE FABRICATED AND ERECTED UNDER THE SEAL AND SIGNATURE OF THE CONTRACTORS'
- PROFESSIONAL STRUCTURAL ENGINEER RESPONSIBLE FOR THIS WORK.

 7. CERTIFY THAT ALL FABRICATED SIP PANELS ASSOCIATED COMPONENTS ARE CAPABLE OF SUPPORTING ALL THE LOADS AND FORCES SPECIFIED IN THE CONTRACT SPECIFICATIONS

8. CERTIFY THAT ALL COMPONENTS ARE FABRICATED AND ERECTED IN ACCORDANCE WITH

Public Wo Governme

Works and Travaux publics et Services gouvernementaux

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DC

NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0 ISSUED FOR TENDER 15/02/02

Revision/ Description/Description Date/Dat

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY

TENDER A

SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

GENERAL NOTES & SPECIFICATION

Project No./No. du projet

R.071363.001

S-001 1 OF 10

10

PWGSC - A1 - 841X594

0 10 20 30 40 50 60 70 80 90 100mm

CLIMATIC INFORMATION		
TO BE READ IN CONJUNCTION WITH DESIGN LOADS DESIGN NOTES		
SNOW LOAD (1/50), Ss	8.5 kPa	
SNOW LOAD (1/50), Sr	0.3 kPa	
HOURLY WIND PRESSURE (1/50)	0.45 kPa	
SEISMIC RESPONSE, S₀(0.2)	0.896	
SEISMIC RESPONSE, S₀(0.5)	0.590	
SEISMIC RESPONSE, S₀(1.0)	0.322	
SEISMIC RESPONSE, S₀(2.0)	0.174	
SEISMIC RESPONSE, PGA	0.393	

SITE INFORMATION			
TO BE READ IN CONJUNCTION WITH DESIGN	LOADS DESIGN NOTES		
IMPORTANCE CATEGORY	POST-DISASTER		
WIND EXPOSURE TYPE	OPEN TERRAIN		
INTERNAL PRESSURE CATEGORY	2		
FOUNDATION SITE CLASS	F		
Fa	1.1		
Fv	1.2		
SPREAD FOOTING FACTORED BEARING CAPACITY (ULS/SLS)	213kPa/330kPa		

DESIGN LOADS		
TO BE READ IN CONJUNCTION WITH DESIGN LOADS DESIGN NOTES		
MAIN FLOOR		
SUPERIMPOSED DEAD LOAD	1.5 kPa	
LIVE LOAD	4.8 kPa	
ROOFS		
SUPERIMPOSED DEAD LOAD 1.0 kPa		
BASIC SNOW LOAD	8.90 kPa	
ACCUMULATED SNOW LOAD	REFER TO [PLANS]	
NET FACTORED WIND UPLIFT LOAD	REFER TO [PLANS]	
<u>CEILING</u>		
SUPERIMPOSED DEAD LOAD	2.0 kPa	
SIP WALL WIND LOAD		
BASIC WIND LOAD	1.2kPa/-1.3kPa	

STEEL GRADES			
TO BE READ IN CONJUNCTION WITH STRUCTURAL STEEL DESIGN NOTES			
MEMBER TYPE	GRADE		
ROLLED W-SHAPES, TEES	CSA G40.21 350W OR ASTM A992 GRADE 50		
WELDED WIDE FLANGE SECTIONS	CSA G40.21 350W		

		CONT	ROLLED (ONCRE	TE		
ТО	BE READ IN	CONJUNCTION WIT	TH CAST-IN-PLAC	E REINFORCE	D CONCRETE	E DESIGN	NOTES
CONCRETE ELEMENT	CLASS OF EXPOSURE	MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS (MPa)	MINIMUM COMPRESSIVE STRENGTH AT 56 DAYS (MPa)	MAXIMUM AGGREGATE SIZE (mm)	AIR CONTENT %	MAX. W/C RATIO	CEMENT TYPE
		•	EXTERIOR CONC	RETE			
SPREAD FOOTING	F-2	30	N/A	20	4-7	0.55	GU
STRIP FOOTING	F-2	30	N/A	20	4-7	0.55	
FOUNDATION WALL	F-2	30	N/A	20	4-7	0.55	GU
PIER	F-2	30	N/A	20	4-7	0.55	GU
SLAB ON GRADE-BUILDING	F-2	30	N/A	20	4-7	0.55	GU
SLAB ON GRADE-STEEL CANOPY	C-2	32	N/A	20	5-8	0.45	
APRON	C-2	32	N/A	20	5-8	0.45	GU
INTERIOR CONCRETE							
HOUSEKEEPING PADS	N	20	_	20	_	_	GU
* CORROSION INHIBITI	CORROSION INHIBITING ADMIXTURE REQUIRED						

	STANDARD END HOOKS							
TO BE READ	TO BE READ IN CONJUNCTION WITH CONCRETE REINFORCEMENT DESIGN NOTES							
BAR SIZE	10M	15M	20M	25M	30M	35M	45M	55M
90 HOOK LENGTH								
	180	260	310	400	510	640	790	1020
180 HOOK LENGTH								
	140	180	210	280	390	550	670	860

FORCE MODIFICATION FACTORS						
TO BE READ IN CONJUNCTION WITH DESIGN LOADS DESIGN NOTES						
LATERAL LOAD	MODIFICATION FACTOR					
RESISTANCE SYSTEM	DUCTILITY RELATED, RD	OVERSTRENGTH RELATED, RO				
LIMITED DUCTILITY CONCENTRICALLY BRACED FRAME	2.0	1.3				

	REINFORCEMENT SPLICES					
TO BE	TO BE READ IN CONJUNCTION WITH CONCRETE REINFORCEMENT DESIGN NOTES					
			TENSION SF	PLICE (mm)		
BAR	COMPRESSION	VERTICAL (HORIZON	OR BOTTOM TAL BARS	TOP HORIZO	ONTAL BARS	
SIZE	SPLICE (mm)	UNCOATED BARS	EPOXY COATED BARS	UNCOATED BARS	EPOXY COATED BARS	
10M	300	400	600	500	650	
15M	450	550	850	750	950	
20M	600	700	1000	900	1150	
25M	750	1100	1650	1400	1850	
30M	900	1300	1950	1700	2200	
35M	1025	1550	2300	2000	2600	
NOTE 1:	NOTE 1: THIS TABLE IS BASED ON NORMAL WEIGHT CONCRETE I'C - 35 MPg					

NOTE 1: THIS TABLE IS BASED ON NORMAL WEIGHT CONCRETE f'c = 35 MPa AND ON REINFORCING STEEL fy = 400 MPa.

NOTE 2: TOP HORIZONTAL BARS ARE DEFINED AS HORIZONTAL REINFORCEMENT PLACED SUCH THAT MORE THAN 300 mm OF CONCRETE IS CAST IN THE MEMBER BELOW THE REINFORCEMENT.

NOTE 3: FOR STANDARD EMBEDMENT DEPTH INTO CONCRETE, DIVIDE BASIC TENSION LAP SPLICE NUMBERS BY 1.3.

CLEAR CONCRETE CO'	VER 7	TO REINF	ORCEMENT		
TO BE READ IN CONJUNCTION WITH CONCRETE REINFORCEMENT DESIGN NOTES					
		EXPOSURE	CLASS		
EXPOSURE CONDITION	N		C-XL, C-1, C-2, C-3, A-1, A-2, A-3		
CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH	-	75 mm	75 mm		
BEAMS, GIRDERS, COLUMNS, AND PILES TO TIES/STIRRUPS (EXCEPT AS NOTED BELOW)	30 mm	40 mm	60 mm		
SLABS, WALLS, JOISTS, SHELLS, AND FOLDED PLATES (EXCEPT AS NOTED BELOW)	20 mm	40 mm	60 mm		
RATIO OF COVER TO NOMINAL BAR DIAMETER	1.0	1.5	2.0		
RATIO OF COVER TO NOMINAL MAXIMUM AGGREGATE SIZE	1.0	1.5	2.0		
NOTE					
THE LARGEST COVER REQUIRED FOR ANY ONE	ELEMENT	SHALL GOVERN.			



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



	_	
·		
·		
0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Date
Client/cli	ent	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY
TENDER A
SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Designed by/Concept par **MJW**

Drawn by/Dessine par **PP**

PWGSC Project Manager/Administrateur de Projets TPSG

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSG

Drawing title/Titre du dessin

SPECIFICATION

Project No./No. du projet

R.071363.001

Sheet/Feuille **S-002**2 OF 10


567 — −2.72 kPa −3.17 kPa (ROOF OVERHANG) -2.72 kPa --3.17 kPa (ROOF OVERHANG) -1.25 kPa -0.95 kPa (ROOF OVERHANG) −1.25 kPa −0.95 kPa (ROOF OVERHANG) -1.70 kPa --2.80 kPa (ROOF OVERHANG) B
-2.72 kPa
-3.17 kPa (ROOF OVERHANG)
-2.72 kPa -1.25 kPa [|] -0.95 kPa (ROOF OV<mark>ERHANG</mark>) −1.25 kPa −0.95 kPa (ROOF OVERHANG) -1.70 kPa --2.80 kPa (ROOF OVERHANG) - 1.70 kPa-2.80 kPa (ROOF OVERHANG) (C1)— -2.72 kPa -3.17 kPa (ROOF OVERHANG) -3.17 kPa (ROOF OVERHANG)



CASE I

ROOF NET FACTORED WIND UP-LIFT DIAGRAM SCALE: NTS


Revision no La Révision



1. GRIDS A,C,1,6 TO OUTSIDE FACE OF SIP/CONCRETE CURB 2. SLAB ON GRADE ACT AS DIAPHRAGM

FOUNDATION AND MAIN FLOOR PLAN SCALE: 1:50

FOOTING SCHEDULE				
LABEL	SIZE (mm)	SIZE (mm) REINFORCEMENT		
LABEL	SIZE (IIIII)	воттом	TOP	
F1		5-20M EQUALLY SPACED SHORT DIRECTION	5-15M EQUALLY SPACED SHORT DIRECTION	
ГІ	900x1200x300	4-20M EQUALLY SPACED LONG DIRECTION	4-15M EQUALLY SPACED LONG DIRECTION	
F2	1200x1200x300	5-20M EQUALLY SPACED, EACH DIRECTION	5-15M EQUALLY SPACED, EACH DIRECTION	
F3	1200x1200x300	5-20M EQUALLY SPACED, EACH DIRECTION	-	
F4	1200×2000×400	11-20M EQUALLY SPACED SHORT DIRECTION	11-15M EQUALLY SPACED SHORT DIRECTION	
Γ4		7-20M EQUALLY SPACED LONG DIRECTION	7-15M EQUALLY SPACED LONG DIRECTION	
F5	1500x1500x300	7-20M EQUALLY SPACED, EACH DIRECTION	_	
F6	1500x1500x300	7-20M EQUALLY SPACED, EACH DIRECTION	7-15M EQUALLY SPACED, EACH DIRECTION	
F7	1500x3000x400	16-20M EQUALLY SPACED SHORT DIRECTION	16-15M EQUALLY SPACED SHORT DIRECTION	
Γ/	1300330003400	9-20M EQUALLY SPACED LONG DIRECTION	9-15M EQUALLY SPACED LONG DIRECTION	



Public Works and Government Services Services gouvernementaux Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Date
Client/client		

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FOUNDATION AND MAIN FLOOR PLAN


R.071363.001

S-101

3 OF 10

0 10 20 30 40 50 60 70 80 90 100mm

Revision no La Révision



ROOF / CEILING /SHEAR WALL SCHEDULE					
ROOF / WALL LOCATION	STRUCTURE AND SPACING	SHEATHING	NAILS/SCREWS		
ROOF-STEEL CANOPY	W310x24, FOR SPACING SEE PLAN VIEW	38x1.52 STEEL ROOF DECK	POWDER DRIVEN FASTENERS @ 300mm O/C		
ROOF-BUILDING	PRE-ENGINEERED ROOF TRUSSES @ 406 mm O/C	19mm PLYWOOD	3"@ 50mm 0/C		
CEILING	184mm (CORE) SIP PANELS	12.5mm PLYWOOD (BOTH SIDES)	SIP SCREW @ 100mm o/c		

BEAM SCHEDULE				
LABEL	SIZE			
B1	W460x52			
B2	W530x74			
В3	W410x39			
B4	W250x33			
B5	HSS 127x127x4.8			

C	COLUMN SCHEDULE					
LABEL	SIZE					
C1	HSS152x152x4.8					
C2	HSS152x152x9.5					
C3	HSS 127x127x4.8					
C4	HSS 152x152x13					

1. SCREWS @ 50mm o/c AROUND MECH. OPENING, PROVIDE PROPER BLOCKING. 2. NAILING/SCREWING PATTERNS NOTED IN THE SCHEDULE ABOVE PERTAIN ONLY TO SHEATHING PANEL EDGES. THE INTERIOR OF THE SHEATHING PANELS MAY BE NAILED AT 300MM O/C. NAIL SIZE TO MATCH EDGE NAILS.

UPLIFT TIE SCHEDULE				
STRUCTURE	HURRICANE TIE			
TRUSS TO PLATE	HURRICANE TIE PER ROOF TRUSS (DOUBLE PLATE) MAX. FACTORED UPLIFT 4.56kN			

SILL PLATE ANCHOR BOLT SCHEDULE									
GRID LINE	ANCHOR BOLT SPECIFICATION								
EXTERIOR SIP PANELS	16mm CAST IN PLACE ANCHOR BOLT @ 610mm O/C, EMBEDM,ENT LENGTH 102mm								

1. ALTERNATIVE ANCHOR BOLTS SHALL MEET MIN. STRUCTURAL CAPACITY AS DESIGNED ANCHOR BOLTS



Services gouvernementaux

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay. The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision		Date/Dat
Client/cli	ent	

CANADA BORDER **SERVICES AGENCY**

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin


ROOF PLAN


R.071363.001


S-102


4 OF 10


0 10 20 30 40 50 60 70 80 90 100mm
























BRACING CONNECTIONS SHALL BE WELDED WITH MIN. 6mm FILLET WELD AND DESIGNED BY STEEL FABRICATOR











1. ALL CONNECTIONS SHALL BE DESIGNED BY STEEL FABRICATOR

2. ALL BRACING CONNECTIONS SHALL BE WITH SLIP-CRITICAL BOLTED UNLESS NOTED OTHERWISE-SEE GL-B

3. ALL FORCES SHOWN ARE TOTAL FACTORED LOADS







Public Works and Government Services Services gouvernementaux Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



	-	
0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/client		

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Drawn by/Dessine par

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC


Drawing title/Titre du dessin

BRACING DIAGRAMS

R.071363.001

S-601

10 OF 10



REAL PROPERTY SERVICES Pacific Region **SERVICES IMMOBILIERS** Région de Pacifique



Morrow Engineering Ltd.

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
В	ISSUED F□R 90% CLIENT REVIEW	15/01/14
Α	ISSUED FOR 50% CLIENT REVIEW	14/12/12
Revision/ Revision	Description/Description	Date/Dat

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par


PWGSC Project Manager/Administrateur de Projets TPSGC


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FUEL SYSTEMS SITE PLAN

Project No./No. du projet F-001 R.071363.001





REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Morrow Engineering Ltd

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



		•
Revision/ Revision	Description/Description	Date/Date
Α	ISSUED FOR 50% CLIENT REVIEW	14/12/12
В	ISSUED FOR 90% CLIENT REVIEW	15/01/14
0	ISSUED FOR TENDER	15/02/02

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY TENDER A SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FUEL SYSTEMS FUEL STORAGE PLAN & SECTIONS

Sheet/Feuille Project No./No. du R.071363.001

Revision no., La Révision F-003



REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Morrow Engineering Ltd

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/0
В	ISSUED FOR 90% CLIENT REVIEW	15/01/14
A	ISSUED FOR 50% CLIENT REVIEW	14/12/1
Revision/ Revision	Description/Description	Date/Da
Client/cli	ient	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY TENDER A SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FUEL SYSTEMS SITE SERVICES BUILDING **PLAN AND DETAILS**

R.071363.001

Revision no., La Révision F-004





The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to



0	ISSUED FOR TENDER	15/02/02
В	ISSUED FOR 90% CLIENT REVIEW	15/01/14
Α	ISSUED FOR 50% CLIENT REVIEW	14/12/12
Revision/ Revision	Description/Description	Date/Date
011		


SITE SERVICES & SITE SERVICES BUILDING





TEMPORARY CABLE TRAY & PIPING TO TANK AT CANADA CUSTOMS BUILDING





INTERMEDIATE INLINE SUMP





REAL PROPERTY SERVICES Pacific Region **SERVICES IMMOBILIERS**

Région de Pacifique



Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



Revision/ Revision	Description/Description	Date/Date
Α	ISSUED FOR 50% CLIENT REVIEW	14/12/12
В	ISSUED FOR 90% CLIENT REVIEW	15/01/14
0	ISSUED FOR TENDER	15/02/02

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

Client/client

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FUEL SYSTEMS MECHANICAL/CIVIL DETAILS (SHEET 2)

Project No./No. du projet R.071363.001

F-006




0 10 20 30 40 50 60 70 80 00 100mm

PWGSC - A1 - 841X594

15/01/14


14/12/12


Date/Date



LEAK DETECTION ALARM CONSOLE SCHEMATIC

(LOCATED IN SITE SERVICES BUILDING)






CONDUIT/CABLE TRENCH CROSS SECTION

N.T.S.


BUILDING FUEL TANK CONTROL PANEL SCHEMATIC

(HOUSE #9/MECHANICAL ROOM, CUSTOMS OFFICE & MAINTANANCE BUILDING ONLY)

SCALE: 1:10



SCALE: 1:50



IMPORTANT NOTES:

- FUEL SUPPLY RELAY (OR ENGINE RUN) MUST OPERATE IMMEDIATELY WHEN ENGINE IS CRANKED FOR STARTING <u>OR</u> IF FUEL PUMP IS RUN TO PRIME THE SYSTEM.
- 2. OFF-DELAY TIMER SET FOR TWO MINUTES TO HOLD SOLENOID OPEN AFTER ENGINE
- 3. CONTRACTOR TO CONFIRM GENERATOR DC CONTROL VOLTAGE PRIOR TO PURCHASE OF SOLENOID VALVE & TIMING RELAY.

GENERATOR SUPPLY SOLENOID VALVE CONTROL SCHEMATIC

FUEL SUPPLY SOLENOID

SOLENOID ACTIVATION

(PB)

(G)

GENERATOR FUEL SUPPLY SOLENOID ACTIVATION PANEL/TIMER ENCLOSURE

N.T.S.

0 ISSUED FOR TENDER 15/02/02

B ISSUED FOR 90% CLIENT REVIEW 15/01/14

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS

Région de Pacifique

The Contractor shall verify and be responsible for all dimensions. DO

NOT scale the drawing - any errors or omissions shall be reported to

Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.

Copyright Reserved

Morrow Engineering Ltd.

CONSULTING ENGINEERS NORTH VANCOUVER, B.C.

A ISSUED FOR 50% CLIENT REVIEW 14/12/12

Revision | Description | Date | Date |
Client | Client |

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY
TENDER A
SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par **B.deM**

Drawn by/Dessine par

PWGSC Project Manager/Administrateur de Projets TPSGC

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

FUEL SYSTEMS
ELECTRICAL SCHEMATICS & DETAILS
(SHEET 2)

Project No./No. du projet


R.071363.001

Sheet/Feuille
F-008


Revision no./La Révision no.
0


0 10 20 30 40 50 60 70 80 90 100mm


PWGSC - A1 - 841X594












	FURNACE SCHEDULE												
TAG No.	LOCATION	MANUFAC-	AC- MODEL ELEL 114 01 0011 01		COO	LING	FAN M	OTOR	MOTOR POWER	V/PH	REMARKS		
IAG NO.	LOCATION	TURER	MODEL	FOEL	(kW)	(kW)	CAPACITY (kW)	REFRIGERANT	FLOW (L/s)	E.S.P (Pa)			KLIMAKKS
FRN-1	ROOM 105	_	ı	No. 2 OIL	20.5	17.3	N/A	N/A	305	_	1/2	120/1	ECM VARIABLE SPEED BLOWER MOTOR
FRN-2	ROOM 105	_	-	No. 2 OIL	20.5	17.3	N/A	N/A	305	_	1/2	120/1	ECM VARIABLE SPEED BLOWER MOTOR


_													
	FAN SCHEDULE												
	FAN No.	SERVICE	LOCATION	MANUFACTURER	MODEL No.	AIR FLOW (L/s)	EXTERNAL STATIC PRESS. (Pa)		FAN RPM	ELECTRICAL (V/Ph/Hz)	MOUNTING ARR'GT	TYPE	REMARKS
	CF-1	COOLING	ROOM 102 GRLN A:2	_	_	100	110	1/9	1000	120/1/60	CEILING	CENTRIFUGAL	INTERLOCKED WITH CD-5
	EF-1	EXHAUST	ROOM 101 GRLN C1:2	_	_	25	75	1/6	1428	120/1/60	INLINE	CENTRIFUGAL	INTERLOCKED WITH CD-6


	MOTORIZED DAMPER SCHEDULE											
	THE TOTAL DE LA CONTEDUCE											
TAG No.	DUTY	POSITION	TYPE	SIZE	REMARKS							
CD-1	GENERATOR COMB/A	NC	2 POSITION	1800×150	PARALLEL BLADE THERMALLY INSULATED, THERMALLY BROKEN							
CD-2	GENERATOR O/A	NC	MODULATING	1800×1500	OPPOSED BLADE THERMALLY INSULATED, THERMALLY BROKEN							
CD-3	GENERATOR E/A	NC	MODULATING	1800×1500	OPPOSED BLADE THERMALLY INSULATED, THERMALLY BROKEN							
CD-4	GENERATOR R/A	NO	MODULATING	900×750	OPPOSED BLADE							
CD-5	ELECTRICAL ROOM O/A	NC	2 POSITION	200×150	PARALLEL BLADE THERMALLY INSULATED, THERMALLY BROKEN							
CD-6	CHLORINE ROOM T/A	NC	2 POSITION	200×150	PARALLEL BLADE							

	GRILLE, DIFFUSER, AND LOUVER SCHEDULE											
TAG No. MANUFACTURER MODEL No. SIZE SERVICE				SERVICE	DESCRIPTION	FINISH	REMARKS					
S-1	_	-	SEE DWG	SUPPLY	DOUBLE DEFLECTION SUPPLY GRILLE	WHITE	19mm BLADE SPACING, C/W BALANCING DAMPER					
R-1	-	ı	SEE DWG	RETURN	EGG CRATE RETURN GRILLE	WHITE						
T-1	-	ı	SEE DWG	TRANSFER	EGG CRATE RETURN GRILLE	WHITE						
LOUVER	-	ı	SEE DWG	-	STATIONARY, DRAINABLE LOUVER	-						



2 CHLORINE ROOM EXHAUST CONTROL SCHEMATIC N701 SCALE: NTS






TO BE INSTALLED IN THE WATER TREATMENT ROOM AS INDICATED ON DRAWING M101.

3. WATER TREATMENT PLANT ALARM IS FOR ALL ALARMS GENERATED BY THE WATER TREATMENT PLANT EQUIPMENT.

5 BUILDING ALARM SCHEMATIC
N701 SCALE: NTS




	ELECTRIC DOMESTIC HOT WATER HEATER SCHEDULE												
TAG No.	LOCATION	MANUFACTURER	MODEL	CAPACITY (L)	ELEMENTS (W)	V/PH	REMARKS						
DHWH-1.1	ROOM 100 GRIN B-C:2-3	_	_	303	1 @ 3000	208/3	610mm DIAMETER						

	PLUMBING FIXTURES SCHEDULE											
TAG No.	MANUFACTURER	MODEL No.	DESCRIPTION	DCW (ømm)	DHW (ømm)		VENT(ø mm)	REMARKS				
ES-1	-	-	EMERGENCY DRENCH SHOWER AND EYEWASH STATION	32	32	N/A		EMERGENCY SHOWER C/W EYEWASH STATION AND LEAD FREE THERMOSTATIC MIXING VALVE.				
FD-1	-	-	FLOOR DRAIN	N/A	N/A	75	N/A					
HB-1	_	-	INTERIOR HOSE BIBB	19	N/A	N/A	N/A	COMMERCIAL GRADE, STAINLESS STEEL, LEAD FREE, W/ VACUUM BREAKER				
SK-1	-	-	SAMPLE SINK	13	13	38	32	410x478x254 (LxWxD) STAINLESS STEEL DROP-IN SINK C/W 102mm CENTERSET 114mm RADIUS GOOSNECK FAUCET W/ 150mm WRIST BLADE HANDLES				

	FIRE EXTINGUISHER SCHEDULE											
TAG No.	MANUFACTURER	MODEL No.	DESCRIPTION	UL RATING	BRACKET	REMARKS						
DCE-1	-	-	PRESSURIZED DRY CHEMICAL, 9.07 kg	10A-120B:C	STANDARD HANGER WITH QUICK RELEASE MECHANICAL RETENSION STRAP							
DCE-2	-	_	PRESSURIZED DRY CHEMICAL, 4.54 kg		STANDARD HANGER WITH QUICK RELEASE MECHANICAL RETENSION STRAP	SUITABLE FOR OUTDOOR MOUNTING C/W HIGH VISIBILITY, HEAVY DUTY COVER						

	TANK SCHEDULE												
TAG No.	SERVICE	LOCATION	MANUFACTURER	MODEL No.	USAGE	TANK VOLUME (L)	TANK ACCEPTANCE VOLUME (L)	DIMENSIONS (Ø X L) (W x L x H) (mm)	REMARKS				
N/A	PRESSURE TANK	-	FLEXCON INDUSTRIES	PC366R	-	450	180	660x1518	EXISTING TANK LOCATED IN OLD WELLHOUSE TO BE TURNED OVER TO OWNER				
TK-1.1	EXPANSION TANK	ROOM 100 GRLN B	ELBI	FLEXTROL AF-300	FILTERED RAW WATER	-	300	660x1290	EXISTING TANK LOCATED IN GENERATOR BUILDING TO BE RELOCATED				
TK-1.2	EXPANSION TANK	ROOM 100 GRLN B	ELBI	FLEXTROL AF-300	FILTERED RAW WATER	-	300	660x1290	EXISTING TANK LOCATED IN GENERATOR BUILDING TO BE RELOCATED				
TK-1.3	EXPANSION TANK	ROOM 100 GRLN B	ELBI	FLEXTROL AF-300	FILTERED RAW WATER	-	300	660x1290	EXISTING TANK LOCATED IN GENERATOR BUILDING TO BE RELOCATED				
TK-1.4	EXPANSION TANK	ROOM 100 GRLN B	-	-	FILTERED RAW WATER	-	300	660x1290	NEW TANK TO MATCH TK-1.1, TK-1.2, AND TK-1.3				
TK-1.5	TREATMENT	ROOM 100 GRLN B	WELLMATE	WM-UT-450	CHLORINE CONTACT	454	_	610x1860	EXISTING TANK LOCATED IN GENERATOR BUILDING TO BE RELOCATED				
TK-1.6	TREATMENT	ROOM 100 GRLN B	WELLMATE	WM-UT-450	CHLORINE CONTACT	454	_	610×1860	EXISTING TANK LOCATED IN GENERATOR BUILDING TO BE RELOCATED				
TK-1.7	CHLORINE HOLDING	ROOM 101 GRLN C1:2	-	_	CHLORINE HOLDING	75	_	356x813	NEW TANK TO BE USED FOR CHLORINE SOLUTION HOLDING/MIXING FOR DOSING PUMPS				

	PUMP SCHEDULE													
TAG No.	SERVICE	LOCATION	MANUFACTURER	MODEL No.	CAPACITY (L/s)	HEAD (M)	FLUID	MOTOR (Hp)	RPM	ELECTRICAL (V/Ph/Hz)	REMARKS			
P-1.1	RAW WATER	WELL	-	_	1.26	78.7	WATER	3	3450	208/3/60	PUMP TO BE SUITABLE FOR 150mm CASING/BOREHOLE			
P-1.2	RAW WATER BOOSTER	ROOM 100 GRLN C:1	-	_	1.92	26.5	WATER	1.5	_	UNKNOWN	EXISTING PUMP LOCATED IN OLD WELLHOUSE TO BE TURNED OVER TO OWNER			
P-1.3	RAW WATER BOOSTER	ROOM 100 GRLN C:1	-	-	1.92	26.5	WATER	1.5	_	UNKNOWN	EXISTING PUMP LOCATED IN OLD WELLHOUSE TO BE TURNED OVER TO OWNER			
CL-1	CHLORINE INJECTION	ROOM 101 GRLN 2	_	_	-	_	CL SOL'N	20W	_	120/1/60				
CL-2	CHLORINE INJECTION	ROOM 101 GRLN 2	-	-	_	1	CL SOL'N	20W	-	120/1/60				





REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Convints to all designs and drawings are the property of

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



	194901928	
0	ISSUED FOR TENDER	15.02.02
Revision/ Revision	Description/Description	Date/Date
Client/cli	ent	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY
TENDER A
SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

B.Zrum / S.Birrell

Drawn by/Dessine par

B.Zrum

WOSC Project Multiger/Administrateur de Projets 17500

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Orawing title/Titre du dessin

SCHEDULES AND
CONTROLS SCHEMATICS


Project No./No. du projet

R.071363.001


Feuille Revision no.


N701


O











NOTES:


1. PROVIDE TELECOMMUNICATIONS GROUND BUS ON INSULATED STANDOFFS. SEE SPECIFICATIONS SECTION 26 05 28.

1 E202


ELECTRICAL ROOM 102 — WEST ELEVATION
1:25

	LEGEND
	FLUORESCENT STRIP LUMINAIRE
Ä	WALL MOUNTED EXTERIOR LUMINAIRE
\$	WALL MOUNTED LINE VOLTAGE SWITCH
3 \$	3 WAY WALL MOUNTED 3 WAY LINE VOLTAGE SWITCH
₩	DUPLEX RECEPTACLE
 	FOURPLEX RECEPTACLE
₩GF	GROUND FAULT INTERRUPTER (GFI) DUPLEX RECEPTACLE
₩	5-20R DUPLEX RECEPTACLE
t∯ GF	5-20R GROUND FAULT INTERRUPTER (GFI) DUPLEX RECEPTACLE
9	SPECIAL RECEPTACLE (TYPE AS INDICATED)
⊲ #	STRUCTURED WIRING OUTLET (# DENOTES NUMBER OF CABLES)
Ø	ELECTRIC MOTOR
다	DISCONNECT SWITCH
$ \leftarrow $	WALL MOUNTED EMERGENCY LIGHTS WITH 2 HOUR BATTERY PACK
₩	CEILING MOUNTED EMERGENCY LIGHTS WITH 2 HOUR BATTERY PACK
•	PUSHBUTTON
•	FIRE ALARM FIXED TEMPERATURE HEAT DETECTOR
F	FIRE ALARM MANUAL PULL STATION
	FIRE ALARM HORN/STROBE
ISO	FIRE ALARM ISOLATION MODULE
	PANEL BOARD
HTXX	HEAT TRACE CIRCUIT IDENTIFIER
©X)	HEAT TRACE CONTROLLER IDENTIFIER





3 LUMINAIRE SCHEDULE E202 N.T.S.





	TYPE	DESCRIPTION
	1	1450W, 120VAC, INTEGRAL THERMOSTAT, ELECTRIC BASEBOARD HEATER SUITABLE FOR CORROSIVE ENVIRONMENT, AND WITH TEMPERATURE RANGE THAT INCLUDES 10°C TO 25°C.
	2	800W, 120VAC, STRIP HEATER WITH INTEGRAL THERMOSTAT WITH TEMPERATURE RANGE THAT INCLUDES 5°C TO 25°C.

5 E202

ELECTRIC BASEBOARD HEATER SCHEDULE

Public Works and Government Services Canada

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique

Services gouvernementaux



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/cli	ent	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY

TENDER A

SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par CFM

Drawn by/Dessine par **EH**

PWGSC Project Manager/Administrateur de Projets TPSGC

Gestionnaire régionale, Services d'architectural et de génie, TF

Drawing title/Titre du dessin

SITE SERVICES BUILDING DETAILS

Project No./No. du projet

R.071363.001

E2

E202

Revision na La Révision

FOUTDMENT	LOCATION	LID	VOLTS	DUASE			I DDE AKED	CONTROL
EQUIPMENT	LOCATION	HP	VOLTS	PHASE	FLA	FEEDER	BREAKER	CONTROL
FRN-1	MECHANICAL ROOM	.5	120∨	1	12	2 #12 CU R90 + BOND	1P15	LRD
						IN 16mm GALV. STEEL		
FRN-2	MECHANICAL ROOM	.5	120∨	1	12	CONDUIT 2 #12 CU R90 + BOND	1P15	LRD
F KN-C	MECHANICAL ROOM	.5	1200	1	15	IN 16mm GALV. STEEL	1715	
						CONDUIT		
EF-1	CHLORINE ROOM	.1667	120V	1	3.4	2 #12 CU R90 + BOND	1P15	MMP/R/HOA
				-		IN 16mm GALV, STEEL		
						CONDUIT		
CF-1	ELECTRICAL ROOM	.1113	120V	1	.77	2 #12 CU R90 + BOND	1P15	MMP/R/HOA
						IN 16mm GALV. STEEL		
						CONDUIT		
P-1.1	WELL	3	208∨	3	11.9	2 #12 CU R90 + BOND	3P15	CMS
						IN 16mm GALV, STEEL		
70117711114	VATED TOTATMENT		200\/	1	145	CONDUIT	2020	DDEAKED
DHWH-1	WATER TREATMENT	_	208∨	1	14.5	2 #10 CU R90 + BOND IN 21mm GALV, STEEL	2P30	BREAKER ONLY
	KUUM					CONDUIT		
FUEL PUMP CONTROL	ELECTRICAL ROOM	_	120V	1	2	2 #12 CU R90 + #12	1P15	BREAKER
PANEL				-	_	GND. IN 21mm GALV.		DNLY
1						STEEL CONDUIT		
FUEL PUMP CONTROL	ELECTRICAL ROOM	.333	208∨	1	4	2 #12 CU R90 + #12	2P15	BREAKER
PANEL: STP-1 & -2						GND. IN 21mm GAL∨.		DNLY
MOTOR STARTERS						STEEL CONDUIT		
DIL WATER	EXTERIOR	_	208∨	1	15	2 #19 CU R90 + #12	2P30	BREAKER
SEPARATOR -						GND. IN 21mm GALV.		DNLY
HEAT TRACE	ELECTRICAL DEEM		100\/	1		STEEL CONDUIT	1015	DDE ALCED
OIL WATER	ELECTRICAL ROOM	_	120∨	1	_	2 #12 CU R90 + #12	1P15	BREAKER
SEPARATOR DIL						GND. IN 21mm GALV.		DNLY
LEVEL MONITOR LEAK DETECTION	ELECTRICAL ROOM	_	120∨	1	2	STEEL CONDUIT 2 #12 CU R90 + #12	1P15	BREAKER
PANEL	LELCTRICHE KOOM		120	•	_	GND. IN 21mm GALV.	"15	DNLY
						STEEL CONDUIT		
HEATING DIL TANK	MECHANICAL ROOM	_	120∨	1	2	2 #12 CU R90 + #12	1P15	BREAKER
FILL CONTROL						GND. IN 21mm GALV.		DNLY
PANEL						STEEL CONDUIT		

1. EQUIPMENT SCHEDULE IS FOR ESTIMATING PURPOSES ONLY. CONFIRM ALL MOTOR FULL LOAD CURRENTS WITH NAMEPLATES AND SIZE MOTOR DISCONNECTS, BREAKERS, FUSES, FEEDERS AND OVERLOADS

2. COORDINATE ALL INFORMATION WITH RELEVANT DISCIPLINES INCLUDING MECHANICAL AND FUEL OIL.

MOTOR/EQUIPMENT LIST

CONTROL DEVICE LEGEND:

LRD - LOAD RATED DISCONNECT

MAG — MAGNETIC STARTER

CMS - COMBINATION MAGNETIC STARTER WITH DISCONNECT

/R - WITH LOAD RATED RELAY /HOA - WITH H-O-A SWITCH

/K – KEYED

/SS — SOFT START
VFD — VARIABLE FREQUENCY DRIVE
MMP — MANUAL MOTOR PROTECTION

FDOM	TO	LOCATION	DECODIDION
FROM PUMP CONTROL	TO SUBMERGED	LOCATION	DESCRIPTION (140, OND, IN, OAL)
PANEL - STP	TURBINE PUMPS	TOP OF MAIN STORAGE TANK	2 X 2 #12 R90 COPPER+ #12 GND IN 21MM GALV. STEEL CONDUITS
STARTERS M1 & M2	AND SOLENOID	STORAGE TARK	GALV. STEEL CONDOITS
	VALVES		
PUMP CONTROL	GENERATOR DAY		6 #14 R90 COPPER IN 21MM GALV. STEEL
PANEL	TANK LEVEL ALARM		CONDUIT
	SWITCH	GENERATOR ROOM	
PUMP CONTROL	GENERATOR DAY		4 #14 R90 COPPER IN 21MM GALV. STEEL
PANEL	TANK PUMP	TANK IN	CONDUIT
	START/STOP LEVEL		
	SWITCH	ROOM	
PUMP CONTROL	GENERATOR DAY		2 #14 R90 COPPER IN 16MM GALV. STEEL
PANEL	TANK FILL SOLENOID VALVE	PIPING AT EAST END OF MAIN	CONDUIT
	SOLLINOID VALVE	STORAGE TANK	
PUMP CONTROL	E-STOP PUSH	ON FENCE	2 #14 R90 COPPER IN 16MM GALV. STEEL
PANEL		SOUTH OF MAIN	
		STORAGE TANK	
PUMP CONTROL	TANK FILL	ON FUEL	3X 2 #14 R90 COPPER IN 16MM GALV. STEEL
PANEL - TANK FILL	SOLENOID VALVES	PIPING AT EAST	" CONDUIT
SELECTOR SWITCH		END OF MAIN	
DI IMP CONTROL	MAIN STORAGE	STORAGE TANK	2 #14 BOO CODDED IN 10114 CALL CTEE
PUMP CONTROL PANEL	MAIN STORAGE TANK HIGH LEVEL	TOP OF MAIN STORAGE TANK	2 #14 R90 COPPER IN 16MM GALV. STEEL CONDUIT
IANEL	SWITCH	STORAGE TANK	CONDOIT
PUMP CONTROL	GENERATOR	ENGINE	2 #14 R90 COPPER IN 16MM GALV. STEEL
PANEL	CONTROL PANEL	SHUTDOWN	" CONDUIT
		RELAY (DAY	
		TANK LOW	
		LEVEL	
DUMP CONTROL	DEMOTE ALADM	SHUTDOWN) SOUTH WEST	0 //44 DOO CODDED IN CANNA CALV. CTEEL
PUMP CONTROL PANEL	REMOTE ALARM HORN, STROBE	CORNER OF	6 #14 R90 COPPER IN 21MM GALV. STEEL CONDUIT
IANEE	LIGHT AND ALARM	MAIN STORAGE	CONDOIT
	SILENCE	TANK AREA	
OIL WATER SEPARATOR			2 PAIR #16 DIRECT BURIED ARMOURED
OIL LEVEL MONITOR		SEPERATOR	INSTRUMENTATION CABLE
OIL WATER SEPARATOR	PUMP CONTROL	IN ELECTRICAL	RELAY OUTPUT. 2 #14 R90 COPPER IN 21MM
OIL LEVEL MONITOR	PANEL	ROOM	GALV. STEEL CONDUIT
RELAY			
U/G PIPING LEAK	EXISTING PIPING	IN DUPLEX	4 X #18 1 PAIR SHIELDED INSTRUMENTATION
DÉTECTION PANEL	LEAK DETECTION	RESIDENCE	CABLES IN 27MM GALV. STEEL CONDUIT
	PANEL FOR SUMPS	(LOCATION	
	#1-4	UNKNOWN)	
11/0 5151110 15111	DIDING CUMP 1 FAIX	INI NICIA/	4 × #40 4 DAID OUT DED BUTTOUT
U/G PIPING LEAK	PIPING SUMP LEAK SENSOR	IN NEW INTERMEDIATE	1 X #18 1 PAIR SHIELDED INSTRUMENTATION
DETECTION PANEL	SENSOR	UNDERGROUND	CABLE IN 21MM GALV. STEEL CONDUIT
		PIPING SUMP	
U/G PIPING LEAK	PIPING SUMP LEAK		1 X #18 1 PAIR SHIELDED INSTRUMENTATION
DETECTION PANEL	SENSOR	UNDERGROUND	CABLE IN 21MM GALV. STEEL CONDUIT
		PIPING SUMP	
		AT MAIN	
11/2		STORAGE TANK	DUN CDADE CANAL CALL CTEEL CONTROL
U/G PIPING LEAK	FUTURE PIPING	FUTURE	RUN SPARE 21MM GALV. STEEL CONDUIT TO
DETECTION PANEL	SUMP LEAK SENSOR	CUSTOMS BUILDING	INTERMEDIATE PIPING SUMP
	JE1430IX	PIPING SUMP	
LEAK DETECTION	PUMP CONTROL	IN ELECTRICAL	RELAY OUTPUTS. 4 #14 R90 COPPER IN 21MM
PANEL RELAYS	PANEL	ROOM	GALV. STEEL CONDUIT
GENERATOR CONTROL	GENERATOR FUEL	IN GENERATOR	12 VDC POWER TO SOLENOID VALVE CONTROL
PANEL	SUPPLY LINE	ROOM	PANEL. 2
	SOLENOID VALVE		#12 R90 COPPER IN 16MM GALV. STEEL CONDUIT
	CONTROL PANEL		
GENERATOR FUEL	GENERATOR FUEL	ON FUEL	12 VDC POWER TO SOLENOID VALVE. 2 #12 R90
SUPPLY LINE	SUPPLY LINE	SUPPLY LINE	COPPER IN 16MM GALV. STEEL CONDUIT
SOLENOID VALVE CONTROL PANEL	SOLENOID VALVE	AT TOP OF GENERATOR DAY	
CONTROL PANEL		TANK	
		171317	

1. PROVIDE CONDUIT, CABLE, WIRING AND TERMINATIONS BETWEEN DEVICES AND EQUIPMENT AS IDENTIFIED ABOVE. 2. COORDINATE WITH FUEL OIL DRAWINGS AND SPECIFICATIONS.



FUEL OIL SYSTEM EQUIPMENT LIST

Public Works and Government Services Canada

Public Works and Services Government Services Canada

Travaux publics et Services gouvernementaux Canada

REAL PROPERTY SERVICES Pacific Region SERVICES IMMOBILIERS Région de Pacifique



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay. The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



0	ISSUED FOR TENDER	15/02/02
Revision/ Revision	Description/Description	Date/Dat
Client/client	_	

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY **TENDER A** SITE SERVICES & SITE SERVICES BUILDING

Designed by/Concept par Drawn by/Dessine par


Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin MOTOR/EQUIPMENT LISTS

E203 R.071363.001

PWGSC - A1 - 841X594

Revision no. La Révision



Load Estimate Demand (kW) Existing Peak Demand Site Services Building Mechanical Water Treatment (est) Future PoE Building Mechanical Area New Well Mechanical Heat Trace Fuel & Misc Future Site Lighting Total 107 80% Service Factor 298 Amps (@ 208V, 3Φ)



					P	ANEL A					
		WATTS					WATTS				1
CIRC.	BRKR	Α	В	С	DESCRIPTION	DESCRIPTION	А	В	С	BRKR	CIRC
1	1P15	375			FRN-1	CF-1	100			1P15	2
3	1P15	15	375		FRN-2	OIL WATER SEPARATOR HEAT		1500		2P30	4
5	3P15			750	0 P-1.1				1500		6
7		750				MECHANICAL PANELS	400			1P15	8
9			750			MECH. ROOM PLUGS		300		1P15	10
11	1P15			150	FUEL ENCLOSURE PLUG	ELEC. ROOM PLUGS			750	1P15	12
13	2P15	125			OIL PUMP MOTOR STARTERS	GEN. ROOM PLUGS	450			1P15	14
15			125			EXTERIOR & FUEL ENCL. LIGHTS		700		1P15	16
17	1P15				SPARE	MECH/GEN/ELEC ROOM LIGHTS			750	1P15	18
19	2P60	2700			HEAT TRACE - C1 (GFI)	HEAT TRACE - C2 (GFI)	75			2P15	20
21			2700		HEAT TRACE - CI (GFI)			75		ZP 13	22
23	-2P15			200	HEAT TRACE - C4&C5 (GFI) HEAT TI	HEAT TRACE - C6 (GFI)			800	2P30	24
25		200			HEAT TRACE - C4&C3 (GFI)	HEAT TRACE - CO (GFI)	800				26
27	1P15				SPARE	SPARE				1P15	28
29	1P15				SPARE	SPARE				1P15	30
31					SPACE	SPACE					32
33					SPACE	SPACE					34
35					SPACE	SPACE					36
37					SPACE	SPACE					38
39					SPACE	SPACE					40
41					SPACE	SPACE					42
TOTAL		4150	3950	1100			1825	2575	3800		TOTAL
PHASE A T	OTAL =		5975								
PHASE B T	OTAL =		6525								
PHASE C T	OTAL =		4900								
PANEL TO	TAL =		17400		@ 120/208 VOLTS 3 PHASE	48.3	AMPS				

4 PANEL A SCHEDULE N.T.S.

						PANEL B					
		WATTS					WATTS				
IRC.	BRKR	Α	В	С	DESCRIPTION	DESCRIPTION	А	В	С	BRKR	CIRC
1	1 3 2P30	1500			DHWH-1	EF-1	125			1P15	2
3			1500			BASEBOARD HEATER		1450		1P20	4
5	2P15			560	 	P-1.3 (FUTURE)			560	2P15	6
7		560			F-1.2 (FOTORE)		560			25 13	8
9	1P15		300		MECHANICAL CONTROL	CHLORINE PUMPS		35		1P15	10
11	1P15			900	WATER TREATMENT PLUGS	CHLORINE ROOM PLUGS			150	1P15	12
13	1P15	375			WATER TREATMENT LIGHTS	CHLORINE ROOM LIGHTS	75			1P15	14
15	1P15				SPARE	SPARE				1P15	16
17	1P15				SPARE	SPARE				1P15	18
19					SPACE	SPACE					20
21					SPACE	SPACE					22
23					SPACE	SPACE					24
25					SPACE	SPACE					26
27					SPACE	SPACE					28
29					SPACE	SPACE					30
31					SPACE	SPACE					32
33					SPACE	SPACE					34
35					SPACE	SPACE					36
37					SPACE	SPACE					38
39					SPACE	SPACE					40
41					SPACE	SPACE					42
OTAL		2435	1800	1460			760	1485	710		TOTAL
HASE A T	OTAL=		3195								
PHASE B T	OTAL =		3285								
PHASE C T	OTAL=		2170								

24.0 AMPS

5 PANEL B SCHEDULE N.T.S.

8650

@ 120/208 VOLTS 3 PHASE

Public Works and Government Services Canada

REAL PROPERTY SERVICES
Pacific Region
SERVICES IMMOBILIERS
Région de Pacifique

Services gouvernementaux



Stantec Architecture Ltd.

www.stantec.com

Copyright Reserved

The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to Stantec without delay.

The Copyrights to all designs and drawings are the property of Stantec. Reproduction or use for any purpose other than that authorized by Stantec is forbidden.



	10						
0	ISSUED FOR TENDER	15/02/02					
Revision/ Revision	Description/Description	Date/Date					
Client/client							

CANADA BORDER SERVICES AGENCY

Project title/Titre du projet

PLEASANT CAMP PORT OF ENTRY

TENDER A

SITE SERVICES & SITE SERVICES BUILDING

Consultant Signature Only

Designed by/Concept par

CFM

Drawn by/Dessine par

EH

PWGSC Project Manager/Administrateur de Projets TPSGC

Regional Manager, Architectural and Engineering Services Gestionnaire régionale, Services d'architectural et de génie, TPSGC

Drawing title/Titre du dessin

SINGLE LINE DIAGRAM

R.071363.001

E301

OF

Revision no.
La Révision no.
0

∖E301

