

REPAIR EXTERIOR AND INTERIOR OF PERIMETER WALLS AS FOLLOWS:

1. CONTRACTOR IS TO REPAIR ALL LOCATIONS WHERE HOLES EXIST IN THE EXTERIOR SIDING OF THE BUILDING, EITHER AS A RESULT OF THE WORK OF THIS CONTRACT, OR PRE-EXISTING CONDITION. FOR SMALL HOLES (LESS THAN 1"), USE EXTERIOR PAINTABLE CAULKING. FOR HOLES LARGER THAN 1", REPLACE THE SIDING IN THE AREA OF THE HOLE. DO NOT 'PATCH' SIDING USING SMALL PIECES. WHERE SIDING IS TO BE REPLACED, IT SHALL BE DONE IN PIECES THAT SPAN FROM GROUND TO ROOF, OR OTHER SENSIBLE JOINT. USE SIDING THAT MATCHES THE PROFILE OF THE EXISTING. WHERE WALLS REQUIRE INFILLING, SUCH AS AT A PREVIOUS DUCT OPENING, DO SO WITH CONSTRUCTION TO MATCH EXISTING, UNLESS NOTED OTHERWISE. AT AREAS OF INFILL, REPAIR AIR AND VAPOUR BARRIERS AND SEAL TO EXISTING.
2. THE BUILDING SHALL BE PAINTED AFTER THE EXTERIOR REPAIRS ARE COMPLETE.
3. CONTRACTOR IS TO REMOVE EXISTING POLY VAPOUR BARRIER FROM INTERIOR OF PERIMETER WALLS WHERE EXPOSED. PROVIDE MISSING AND CORRECT SHIFTED FIBERGLASS BATT INSULATION FROM OUTER LAYER OF STEEL STUDS TO CREATE A CONTINUOUS LAYER OF INSULATION. REPLACE ANY DAMAGED STUDS ON THE OUTER AND INNER LAYERS OF THE PERIMETER WALL. ADD A NEW LAYER OF BATT INSULATION BETWEEN THE INNERMOST LAYER OF STUDS. REPLACE THE VAPOUR BARRIER WITH A NEW 6MIL POLY VAPOUR BARRIER OVER THE INNERMOST LAYER OF STEEL STUDS. SEAL THE NEW VAPOUR BARRIER TO THE EXISTING JUNCTIONS WITH WINDOWS AND ROOF.

GENERAL NOTES:

1. ALL EXISTING EXTERIOR WALLS HAVE TWO LAYERS OF SIDING.
2. EXISTING ROOF SYSTEM HAS TWO LAYERS OF ROOFING.
3. ALL INTERIOR WALL PARTITIONS TO GO TO U/S OF ROOF DECK UNLESS OTHERWISE NOTED. SEE SECTION DETAILS A/A9.
4. SEE SHEET A13 FOR DOOR AND WINDOW LEGEND. SEE SPECIFICATIONS FOR DOOR AND WINDOW SCHEDULES.
5. EXPOSED DUCT TO BE PAINTED.
6. EXISTING HOLES IN SLAB TO BE FILLED WITH CONCRETE. ENSURE SLAB IS ADEQUATELY PREPARED PRIOR TO APPLYING NEW FLOORING, CONTRACTOR TO PREPARE FLOOR TO WITHIN FLOORING MANUFACTURER'S TOLERANCES. REFER TO SPECIFICATION SECTION 09 65 19 PART 3 EXECUTION 3.2 INSPECTION FOR EXPECTED LEVEL OF FINISH.

SPECIALTIES

T1	TOILET TISSUE DISPENSER
T2	SANITARY NAPKIN DISPOSAL
T3	610mm GRAB BAR
T4	915mm GRAB BAR
T5	WALL MOUNTED SOAP DISPENSER
T6	WALL MOUNTED PAPER TOWEL DISPENSER
T7	FRAMED MIRROR
T8	WASTE RECEPTACLE
T9	TOILET BACKREST

LEGEND

- FD / FD — FLOOR DRAIN
- (##) — DOOR NUMBER (SEE SPEC FOR DOOR SCHEDULE)
- (SF) — SCREEN NUMBER (SEE SHEET A12 FOR WINDOWS, FRAMES DOORS AND JAMBS)
- NOT IN CONTRACT ITEMS.
- EXISTING ITEMS.

FIRE SEPARATIONS

◆ ◆ ◆ ◆ SEPARATION WITH A 1 HR FIRE RESISTANCE RATING

WALL TYPE LEGEND

P1	184	16mm GYPSUM WALL BOARD 92mm STEEL STUD @ 610 o/c WITH 89mm ACOUSTIC BATT INSULATION 16mm GYPSUM WALL BOARD
P2	235	16mm GYPSUM WALL BOARD 92mm STEEL STUD @ 610 o/c WITH ACOUSTIC BATT INSULATION
P3	254	16mm WATER RESISTANT GYPSUM WALL BOARD 152mm STEEL STUD @ 610 o/c WITH ACOUSTIC BATT INSULATION 16mm WATER RESISTANT GYPSUM WALL BOARD

FLOOR PLAN – NEW
SCALE: 1:50
0m 1m 2m 3m 4m 5m
1 A2

TRUE / PROJECT

PWGSC B1 (2004)

0 10 20mm 40 60 80 100 120 140 160 180 200mm

Public Works and Government Services Canada / Travaux Publics et Services gouvernementaux Canada

FOWLER BAULD & MITCHELL
architecture
Fowler Bauld & Mitchell Ltd.
PO Box 314, Suite 102
1660 Hollis Street
Halifax, Nova Scotia B3J 2R7
Tel: 902 429 4100
Fax: 902 423 3063
architects@fbm.ns.ca
www.fbm.ns.ca

CBCL LIMITED
Consulting Engineers
ISO 9001 CERTIFIED

LICENSED ARCHITECT
GEORGE A COTARAS
NOVA SCOTIA ASSOCIATION OF ARCHITECTS

revisions		date
1	ISSUED FOR TENDER	JUN. 4 2015

project / projet

ARGO BUILDING
BEDFORD INSTITUTE OF OCEANOGRAPHY

Dartmouth, NS

drawing / dessin

FLOOR PLAN – NEW

designed	SM / conçu
date	FEBRUARY 2015
drawn	CFH / dessiné
date	FEBRUARY 2015
approved	/ approuvé
date	
Tender	/ Soumission
NS	
PWGSC Project Manager	Administrateur de projets TPSGC

project number / no. du projet: R.069793.001

drawing no. / no. du dessin: A2

E-DRM/GDD-E: 508077