

PART 1 - GENERAL

1.1 REFERENCES

- .1 Unless otherwise indicated, all the works must be done in accordance with the in force edition of the "Code de construction du Québec".
- .2 Furthermore, the works will be done in accordance with any other code or standard having jurisdiction, as per the latest edition, notably including, but not limited to:
 - .1 Sheet Metal and Air Conditioning National Association (SMACNA).
 - .1 SMACNA HVAC Duct Construction Standards, Metal and Flexible -1985.
 - .2 Health Canada/Workplace Hazardous Materials Information System (WHMIS).
 - .1 Material Safety Data Sheets (MSDS).

1.2 SUBMITTALS

- .1 Submit submittal data in accordance with regulations.

PART 2 - PRODUCTS

2.1 GENERAL

- .1 Dampers to be manufactured according to SMACNA Standards.

2.2 SPLITTER DAMPERS

- .1 Fabricate from same material as duct but one sheet metal thickness heavier, with appropriate stiffening.
 - .2 Double thickness construction.
 - .3 Control rod with locking device and position indicator.
 - .4 Rod configuration to prevent end from entering duct.
 - .5 Pivot: Piano hinge.
 - .6 Folded leading edge.
-

2.3 SINGLE BLADE DAMPERS

- .1 Fabricate from same material as duct, but one sheet metal thickness heavier. V-groove stiffened.
- .2 Size and configuration to recommendations of SMACNA, except maximum height 250 mm (10 in).
- .3 Locking quadrant with shaft extension to accommodate insulation thickness.
- .4 Inside and outside nylon end bearings.
- .5 Channel frame of same material as adjacent duct, complete with angle stop.

2.4 MULTI-BLADED DAMPERS

- .1 Factory manufactured of material compatible with duct.
- .2 Opposed Blade: Configuration, metal thickness and construction to recommendations of SMACNA.
- .3 Maximum Blade Height: 100 mm.
- .4 Bearings: Pin in bronze bushings, self-lubricating.
- .5 Linkage: Shaft extension with locking quadrant.
- .6 Channel frame of same material as adjacent duct, complete with angle stop.

PART 3 - EXECUTION

3.1 INSTALLATION

- .1 Install in accordance with recommendations of SMACNA and in accordance with manufacturer's instructions.

END OF SECTION
