

PROJECT TITLE BATH, ONTARIO
BARRIER FREE ACCESS TO HOSPITAL AND A YARD PAVING
MILLHAVEN INSTITUTION

PROJECT NUMBER R.072798.001

PROJECT DATE 2015-06-25



Architect



Structural



Civil Engineer

END OF SECTION

Division 1 - General Requirements

Section 01 11 00 - SUMMARY OF WORK	2
Section 01 14 00 - WORK RESTRICTIONS	3
Section 01 31 19 - PROJECT MEETINGS	2
Section 01 32 16 - CONSTRUCTION PROGRESS SCHEDULE	3
Section 01 33 00 - SUBMITTAL PROCEDURES	5
Section 01 35 13 - SPECIAL PROJECT PROCEDURES FOR CORRECTIONAL SERVICE CANADA SECURITY REQUIREMENTS	5
Section 01 35 29 - HEALTH AND SAFETY REQUIREMENTS	5
Section 01 35 36 - FIRE SAFETY REQUIREMENTS	4
Section 01 41 00 - REGULATORY REQUIREMENTS	2
Section 01 42 13 - ABBREVIATIONS AND ACRONYMS	13
Section 01 45 00 - QUALITY CONTROL	3
Section 01 51 00 - TEMPORARY UTILITIES	2
Section 01 52 00 - CONSTRUCTION FACILITIES	3
Section 01 56 00 - TEMPORARY BARRIERS	2
Section 01 61 00 - COMMON PRODUCT REQUIREMENTS	5
Section 01 71 00 - EXAMINATION AND PREPARATION	2
Section 01 73 00 - EXECUTION	2
Section 01 74 11 - CLEANING	2
Section 01 77 00 - CLOSEOUT PROCEDURES	1
Section 01 78 00 - CLOSEOUT SUBMITTALS	6
Section 01 79 00 - DEMONSTRATION AND TRAINING	2

Division 2 - Existing Conditions

Section 02 41 99 - DEMOLITION	3
-------------------------------------	---

Division 3 - Concrete

Section 03 10 00 - CONCRETE FORMING AND ACCESSORIES	3
Section 03 20 00 - CONCRETE REINFORCING	4
Section 03 30 00 - CAST-IN-PLACE CONCRETE	5
Section 03 35 00 - CONCRETE FINISHING	4

Division 5 - Metals

Section 05 50 00 - METAL FABRICATIONS	4
---	---

Division 7 - Thermal and Moisture Protection

Section 07 92 00 - JOINT SEALANTS	4
---	---

Division 8 - Openings

Section 08 80 50 - GLAZING	5
----------------------------------	---

Division 11 - Equipment

Section 11 19 12 - DETENTION HARDWARE.....	5
Section 11 19 13 - DETENTION DOORS AND FRAMES.....	4

Division 26 - Electrical

Section 26 50 00 - LIGHTING	3
-----------------------------------	---

Division 31 - Earthwork

Section 31 14 13 - SOIL STRIPPING AND STOCKPILING	3
Section 31 22 13 - ROUGH GRADING.....	4
Section 31 23 33.01 - EXCAVATING, TRENCHING AND BACKFILLING	12

Division 32 - Exterior Improvements

Section 32 11 16.01 - GRANULAR SUB-BASE.....	5
Section 32 11 23 - AGGREGATE BASE COURSES.....	4
Section 32 12 16 - ASPHALT PAVING	5
Section 32 31 13 - CHAIN LINK FENCES AND GATES.....	7
Section 32 91 19.13 - TOPSOIL PLACEMENT AND GRADING.....	6
Section 32 92 23 - SODDING	5

Division 33 - Utilities

Section 33 05 14 - MAINTENANCE HOLES AND CATCH.....	6
Section 33 41 00 - STORM UTILITY DRAINAGE PIPING.....	5
Section 33 46 17 - SUBGRADE DRAINAGE NETWORK.....	4

END OF TABLE OF CONTENTS

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Title and description of Work.
- .2 Contract Method.
- .3 Contractor use of premises.
- .4 Departmental Representative occupancy.
- .5 Alterations to existing building and site.

1.2 PRECEDENCE

- .1 For Federal Government projects, Division 01 Sections take precedence over technical specification sections in other Divisions of this Project Manual.

1.3 WORK COVERED BY CONTRACT DOCUMENTS

- .1 Work of this Contract comprises the renovations at the Hospital 'S' Building of CSC Millhaven Institution, located at Highway 33, PO Box 280, Bath, Ontario K0H 1G0; and further identified as PWGSC Project Number: R.072798.001
 - .2 Work includes the construction of new security fencing, gates and asphalt paving in the area adjacent to Hospital 'S' Building to accommodate vehicular and pedestrian access to the building. Work will include the construction of a new accessible concrete ramp, railings, exterior light and modifications to the existing exterior door to the building to meet National Building Code (NBC), and barrier free standard CSA B651-12 Accessible Design for the Built Environment. Work will include excavation of existing materials, new storm drains and asphalt paving in the existing 'A' Yard and adjacent to the fire route.
 - .3 All vehicular access, facility security and existing services are to remain operational at all times. All Contractor equipment is to be removed from the site each night or disabled in accordance with CSC's security requirements.
 - .4 Replacement of the existing exterior security door to Hospital 'S' Building will require hoarding and dust protection to the hospital environment. Contractor will be responsible for maintaining emergency egress from this door at all times and shall provide a temporary security door if the replacement cannot be completed during working hours. Any work within the 'S' Building upgrades is to be carried out in accordance with CSA Z317.13-12 'Infection control during construction, renovation, and maintenance of health care facilities' in order to minimize risks to staff and patients during the renovation.
-

1.02 CONTRACT METHOD

1.4 COST BREAKDOWN

- .1 Within 48 hours of notification of acceptance of bid furnish a cost breakdown by Section aggregating contract price.
- .2 Within 48 hours of acceptance of bid submit a list of subcontractors.

1.5 CONTRACTOR USE OF PREMISES

- .1 Contractor shall limit use of premises for Work to allow;
 - .1 Departmental Representative occupancy.
- .2 Coordinate use of premises under direction of Departmental Representative.
- .3 Obtain and pay for use of additional storage or work areas needed for operations under this Contract.

1.6 OWNER OCCUPANCY

- .1 Owner will occupy premises during entire construction period for execution of normal operations.
- .2 Cooperate with Departmental Representative in scheduling operations to minimize conflict and to facilitate Owner usage.

1.7 ALTERATIONS TO EXISTING BUILDING

- .1 Block in openings where items removed with material and finish to match existing adjoining construction.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not used.

END OF SECTION

Part 1 GENERAL

1.1 ACCESS AND EGRESS

- .1 Design, construct and maintain temporary "access to" and "egress from" work areas, including stairs, runways, ramps or ladders independent of finished surfaces and in accordance with relevant municipal, provincial and other regulations.

1.2 USE OF SITE AND FACILITIES

- .1 Execute work with least possible interference or disturbance to normal use of premises. Make arrangements with Departmental Representative to facilitate work as stated.
- .2 Maintain existing services to building and provide for personnel and vehicle access.
- .3 Where security is reduced by work provide temporary means to maintain security.
- .4 Provide portable washroom facilities for use by Contractor's personnel. Keep facilities clean.
- .5 Closures: protect work temporarily until permanent enclosures are completed.

1.3 ALTERATIONS, ADDITIONS OR REPAIRS TO EXISTING BUILDING

- .1 Execute work with least possible interference or disturbance to building operations, occupants, and normal use of premises. Arrange with Departmental Representative to facilitate execution of work.

1.4 EXISTING SERVICES

- .1 Notify, Departmental Representative utility companies of intended interruption of services and obtain required permission.
- .2 Where Work involves breaking into or connecting to existing services, give Departmental Representative one (1) week of notice for necessary interruption of mechanical or electrical service throughout course of work. Keep duration of interruptions minimum. Carry out interruptions after normal working hours of occupants; weekend work will not be permitted.
- .3 Provide access for personnel and limited vehicular traffic.
- .4 Construct barriers in accordance with Section 01 56 00.

1.5 SPECIAL REQUIREMENTS

- .1 Submit schedule in accordance with Section 01 32 16.
 - .2 Ensure Contractor's personnel employed on site become familiar with and obey regulations including safety, fire, traffic and security regulations.
 - .3 Keep within limits of work and avenues of ingress and egress.
 - .4 Ingress and egress of Contractor vehicles at site is limited to 07:30 to 11:45 and 12:30 to 15:30. Notify Departmental Representative forty eight (48) hours in advance of necessary deliveries.
-

- .5 Coordinate delivery hours with Departmental Representative.
- .6 Prior to cutting or drilling horizontal or vertical surfaces including concrete, concrete block or other structural substrate, determine location of reinforcing, service lines, pipes, conduits or other items by x-ray, ground penetrating radar or other appropriate method. Submit findings to Departmental Representative prior to cutting or drilling.
- .7 Prior to excavation or other earthworks operations, determine location of reinforcing, service lines, pipes, conduits or other items by x-ray, ground penetrating radar or other appropriate method. Submit findings to Departmental Representative prior to digging.

1.6 SECURITY

- .1 Where security has been reduced by Work of Contract, provide temporary means to maintain security.
- .2 Security clearances:
 - .1 Personnel employed on this project will be subject to security check. Obtain clearance, as instructed, for each individual who will require to enter premises.
 - .2 Obtain requisite clearance, as instructed, for each individual required to enter premises.
 - .3 Personnel will be checked daily at start of work shift and provided with pass which must be worn at all times. Pass must be returned at end of work shift and personnel checked out.
 - .4 Contractor's personnel will require satisfactory CPIC initiated security screening in order to complete Work in premises and on site. Allow for 2 working weeks for CPIC approval.
- .3 Security escort:
 - .1 Personnel employed on this project must be escorted when executing work in non-public areas during normal working hours. Personnel must be escorted in all areas after normal working hours.
 - .2 Submit an escort request to Departmental Representative at least 14 days before service is needed. For requests submitted within time noted above, costs of security escort will be paid for by Departmental Representative. Cost incurred by late request will be Contractor's responsibility.
 - .3 Any escort request may be cancelled free of charge if notification of cancellation is given at least 48 hours before scheduled time of escort. Cost incurred by late request will be Contractor's responsibility.

- .4 Calculation of costs:
 - .1 Late Service Request Cost: Average hourly rate of security officer for minimum of 8 hours per day.
 - .2 Late Cancellations Cost: Average hourly rate of security officer for 4 hours.

1.7 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions. Smoking is not permitted.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 ADMINISTRATIVE

- .1 Schedule and administer project meetings throughout the progress of the work at the call of Departmental Representative.
- .2 Prepare agenda for meetings.
- .3 Distribute written notice of each meeting 4 days in advance of meeting date to Departmental Representative.
- .4 Provide physical space and make arrangements for meetings.
- .5 Preside at meetings.
- .6 Record the meeting minutes. Include significant proceedings and decisions. Identify actions by parties.
- .7 Reproduce and distribute copies of minutes within three days after meetings and transmit to Departmental Representative, meeting participants and affected parties not in attendance.
- .8 Representative of Contractor, Subcontractor and suppliers attending meetings will be qualified and authorized to act on behalf of party each represents.

1.2 PRECONSTRUCTION MEETING

- .1 Within 15 days after award of Contract, request a meeting of parties in contract to discuss and resolve administrative procedures and responsibilities.
- .2 Departmental Representative, Contractor, major Subcontractors, field inspectors and supervisors will be in attendance.
- .3 Establish time and location of meeting and notify parties concerned minimum 5 days before meeting.
- .4 Incorporate mutually agreed variations to Contract Documents into Agreement, prior to signing.
- .5 Agenda to include:
 - .1 Appointment of official representative of participants in the Work.
 - .2 Schedule of Work: in accordance with Section 01 32 16.
 - .3 Schedule of submission of shop drawings, samples. Submit submittals in accordance with Section 01 33 00.
 - .4 Security requirements in accordance with Section 01 35 13.
 - .5 Requirements for temporary facilities, site sign, offices, storage sheds, utilities, fences in accordance with Section 01 52 00.
 - .6 Site security in accordance with Section 01 56 00.
 - .7 Health and safety in accordance with Section 01 35 29.
 - .8 Proposed changes, change orders, procedures, approvals required, mark-up percentages permitted, time extensions, overtime, administrative requirements.

- .9 Record drawings and specifications in accordance with Sections 01 33 00 and 01 78 00.
- .10 Maintenance manuals in accordance with Section 01 78 00.
- .11 Take-over procedures, acceptance, warranties in accordance with Section 01 78 00.
- .12 Monthly progress claims, administrative procedures, photographs, hold backs.
- .13 Appointment of inspection and testing agencies or firms.
- .14 Insurances, transcript of policies.

1.3 PROGRESS MEETINGS

- .1 During course of Work schedule progress meetings bi-weekly.
- .2 Contractor, major Subcontractors involved in Work and Departmental Representative are to be in attendance.
- .3 Record minutes of meetings and circulate to attending parties and affected parties not in attendance within 3 days after meeting.
- .4 Agenda to include the following:
 - .1 Review, approval of minutes of previous meeting.
 - .2 Review of Work progress since previous meeting.
 - .3 Field observations, problems, conflicts.
 - .4 Problems which impede construction schedule.
 - .5 Review of off-site fabrication delivery schedules.
 - .6 Corrective measures and procedures to regain projected schedule.
 - .7 Revision to construction schedule.
 - .8 Progress schedule, during succeeding work period.
 - .9 Review submittal schedules: expedite as required.
 - .10 Maintenance of quality standards.
 - .11 Review proposed changes for affect on construction schedule and on completion date.
 - .12 Other business.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 DEFINITIONS

- .1 Activity: element of Work performed during course of Project. Activity normally has expected duration, and expected cost and expected resource requirements. Activities can be subdivided into tasks.
- .2 Bar Chart (GANTT Chart): graphic display of schedule-related information. In typical bar chart, activities or other Project elements are listed down left side of chart, dates are shown across top, and activity durations are shown as date-placed horizontal bars. Generally Bar Chart should be derived from commercially available computerized project management system.
- .3 Baseline: original approved plan (for project, work package, or activity), plus or minus approved scope changes.
- .4 Construction Work Week: Monday to Friday, inclusive, will provide five day work week and define schedule calendar working days as part of Bar (GANTT) Chart submission.
- .5 Duration: number of work periods (not including holidays or other nonworking periods) required to complete activity or other project element. Usually expressed as workdays or workweeks.
- .6 Master Plan: summary-level schedule that identifies major activities and key milestones.
- .7 Milestone: significant event in project, usually completion of major deliverable.
- .8 Project Schedule: planned dates for performing activities and the planned dates for meeting milestones. Dynamic, detailed record of tasks or activities that must be accomplished to satisfy Project objectives. Monitoring and control process involves using Project Schedule in executing and controlling activities and is used as basis for decision making throughout project life cycle.
- .9 Project Planning, Monitoring and Control System: overall system operated by Departmental Representative to enable monitoring of project work in relation to established milestones.

1.2 REQUIREMENTS

- .1 Ensure Master Plan and Detail Schedules are practical and remain within specified Contract duration.
- .2 Plan to complete Work in accordance with prescribed milestones and time frame.
- .3 Limit activity durations to maximum of approximately 10 working days, to allow for progress reporting.
- .4 Ensure that it is understood that Award of Contract or time of beginning, rate of progress, Certificate of Substantial Performance and Certificate of Completion as defined times of completion are of essence of this contract.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

- .2 Submit to Departmental Representative within 2 working days of Award of Contract Bar (GANTT) Chart as Master Plan for planning, monitoring and reporting of project progress.

1.4 PROJECT SCHEDULE

- .1 Develop detailed Project Schedule derived from Master Plan.
- .2 Ensure detailed Project Schedule includes as minimum milestone and activity types as follows:
 - .1 Award.
 - .2 Shop Drawings, Samples.
 - .3 Permits.
 - .4 Mobilization.
 - .5 Excavation.
 - .6 Backfill.
 - .7 Footings.
 - .8 Slab on grade.
 - .9 Fence installation
 - .10 Door installation.
 - .11 Paving.
 - .12 Sodding.

1.5 PROJECT SCHEDULE REPORTING

- .1 Update Project Schedule on weekly basis reflecting activity changes and completions, as well as activities in progress.
 - .2 Include as part of Project Schedule, narrative report identifying Work status to date, comparing current progress to baseline, presenting current forecasts, defining problem areas, anticipated delays and impact with possible mitigation.
-

1.6 PROJECT MEETINGS

- .1 Discuss Project Schedule at regular site meetings specified in Section 01 31 19, identify activities that are behind schedule and provide measures to regain slippage. Activities considered behind schedule are those with projected start or completion dates later than current approved dates shown on baseline schedule.
- .2 Weather related delays with their remedial measures will be discussed and negotiated.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not used.

END OF SECTION

Part 1 GENERAL

1.1 ADMINISTRATIVE

- .1 Submit to Departmental Representative submittals listed for review. Submit promptly and in orderly sequence to not cause delay in Work. Failure to submit in ample time is not considered sufficient reason for extension of Contract Time and no claim for extension by reason of such default will be allowed.
- .2 Do not proceed with Work affected by submittal until review is complete.
- .3 Present shop drawings, product data, samples and mock-ups in SI Metric units.
- .4 Where items or information is not produced in SI Metric units converted values are acceptable.
- .5 Review submittals prior to submission to Departmental Representative. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents. Submittals not stamped, signed, dated and identified as to specific project will be returned without being examined and considered rejected.
- .6 Notify Departmental Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .7 Verify field measurements and affected adjacent Work are co-ordinated.
- .8 Contractor's responsibility for errors and omissions in submission is not relieved by Departmental Representative's review of submittals.
- .9 Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Departmental Representative review.
- .10 Keep one reviewed copy of each submission on site.
- .11 Submit number of hard copies specified for each type and format of submittal and also submit in electronic format as pdf files. Forward pdf, NMSEdit Professional spp, MS Word, MS Excel, MS Project and Autocad dwg files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.

1.2 SHOP DRAWINGS AND PRODUCT DATA

- .1 The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.
- .2 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario of Canada.
- .3 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where articles or equipment attach or connect to other articles or equipment, indicate that such items have been co-ordinated, regardless of Section under which adjacent items will be supplied and installed. Indicate cross references to design drawings and specifications.
- .4 Allow 5 working days for Departmental Representative's review of each submission.
- .5 Adjustments made on shop drawings by Departmental Representative are not intended to change Contract Amount. If adjustments affect value of Work, state such in writing to Departmental Representative prior to proceeding with Work.
- .6 Make changes in shop drawings as Departmental Representative may require, consistent with Contract Documents. When resubmitting, notify Departmental Representative in writing of revisions other than those requested.
- .7 Accompany submissions with transmittal letter, in duplicate, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .4 Identification and quantity of each shop drawing, product data and sample.
 - .5 Other pertinent data.
- .8 Submissions shall include:
 - .1 Date and revision dates.
 - .2 Project title and number.
 - .3 Name and address of:
 - .1 Subcontractor.
 - .2 Supplier.
 - .3 Manufacturer.
 - .4 Contractor's stamp, signed by Contractor's authorized representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
 - .5 Details of appropriate portions of Work as applicable:
 - .1 Fabrication.
 - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
 - .3 Setting or erection details.
 - .4 Capacities.

- .5 Performance characteristics.
 - .6 Standards.
 - .7 Operating weight.
 - .8 Wiring diagrams.
 - .9 Single line and schematic diagrams.
 - .10 Relationship to adjacent work.
 - .9 After Departmental Representative's review, distribute copies.
 - .10 Submit and one electronic copy of shop drawings for each requirement requested in specification Sections and as Departmental Representative may reasonably request.
 - .11 Submit one electronic copy of product data sheets or brochures for requirements requested in specification Sections and as requested by Departmental Representative where shop drawings will not be prepared due to standardized manufacture of product.
 - .12 Submit one electronic copy of test reports for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Report signed by authorized official of testing laboratory that material, product or system identical to material, product or system to be provided has been tested in accord with specified requirements.
 - .2 Testing must have been within 3 years of date of contract award for project.
 - .13 Submit one electronic copy of certificates for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Statements printed on manufacturer's letterhead and signed by responsible officials of manufacturer of product, system or material attesting that product, system or material meets specification requirements.
 - .2 Certificates must be dated after award of project contract complete with project name.
 - .14 Submit one electronic copy of manufacturers instructions for requirements requested in specification Sections and as requested by Departmental Representative.
 - .1 Pre-printed material describing installation of product, system or material, including special notices and Material Safety Data Sheets concerning impedances, hazards and safety precautions.
 - .15 Submit one electronic copy of Manufacturer's Field Reports for requirements requested in specification Sections and as requested by Departmental Representative.
 - .16 Documentation of the testing and verification actions taken by manufacturer's representative to confirm compliance with manufacturer's standards or instructions.
 - .17 Submit one electronic copy of Operation and Maintenance Data for requirements requested in specification Sections and as requested by Departmental Representative.
 - .18 Delete information not applicable to project.
 - .19 Supplement standard information to provide details applicable to project.
-

- .20 If upon review by Departmental Representative, no errors or omissions are discovered or if only minor corrections are made, copies will be returned and fabrication and installation of Work may proceed. If shop drawings are rejected, noted copy will be returned and resubmission of corrected shop drawings, through same procedure indicated above, must be performed before fabrication and installation of Work may proceed.
- .21 The review of shop drawings by Public Works and Government Services Canada (PWGSC) is for sole purpose of ascertaining conformance with general concept.
 - .1 This review shall not mean that PWGSC approves detail design inherent in shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting requirements of construction and Contract Documents.
 - .2 Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of sub-trades.

1.3 PHOTOGRAPHIC DOCUMENTATION

- .1 Submit electronic copy of colour digital photography in jpg format, fine resolution monthly with progress statement.
- .2 Project identification: name and number of project and date of exposure indicated.
- .3 Number of viewpoints: 4 locations.
 - .1 Viewpoints and their location as determined by Departmental Representative.
- .4 Frequency of photographic documentation: monthly.

1.4 CERTIFICATES AND TRANSCRIPTS

- .1 Immediately after award of Contract, submit Workers' Safety and Insurance Board Experience Report.

1.5 FEES, PERMITS AND CERTIFICATES

- .1 Provide authorities having jurisdiction with information requested.
- .2 Pay fees and obtain certificates and permits required.
- .3 Furnish certificates and permits.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

1 GENERAL

1.01 PURPOSE

- .1 To ensure that both the construction project and the institutional operations may proceed without undue disruption or hindrance and that the security of the Institution is maintained at all times.

1.02 REFERENCES

- .1 Canadian Standards Association (CSA):
 - .1 CSA Z317.13-12, Infection Control during Construction or Renovation of Health Care Facilities

1.03 DEFINITIONS

- .1 "Contraband" means:
 - .1 An intoxicant, including alcoholic beverages, drugs and narcotics.
 - .2 Tobacco or associated tobacco products.
 - .3 An igniting device, lighter or matches.
 - .4 A weapon or a component thereof, ammunition for a weapon, and anything that is designed to kill, injure or disable a person or that is altered so as to be capable of killing, injuring or disabling a person, when possessed without prior authorization.
 - .5 An explosive or a bomb or a component thereof.
 - .6 Currency over any applicable prescribed limit, \$25.00 when possessed by a visitor without prior authorization.
 - .7 Any item not described in paragraphs 1.03.1.1 to 1.03.1.6 that could jeopardize the security of a Penitentiary or the safety of persons, when that item is possessed without prior authorization.
 - .2 "Unauthorized Smoking and related Items" means all smoking items including, but not limited to, cigarettes, cigars, tobacco, chewing tobacco, cigarette making machines, matches and lighters.
 - .3 "Commercial Vehicle" means any motor vehicle used for the shipment of material, equipment and tools required for the construction project.
 - .4 "CSC" means Correctional Service Canada.
 - .5 "Director" means Director, Warden or Superintendent of the Institution as applicable.
 - .6 "Construction Employees" means persons working for the General Contractor, the sub-contractors, equipment operators, material suppliers, testing and inspection companies and regulatory agencies.
 - .7 "Departmental Representative" means the project manager from Public Works and Government Services Canada.
-

- .8 "Perimeter" means the fenced or walled area of the Institution that restrains the movement of the inmates.
- .9 "Construction Limits" means the area as shown on the contract drawings that the Contractor will be allowed to work. This area may or may not be isolated from the security area of the Institution.

1.04 PRELIMINARY PROCEEDINGS

- .1 Prior to the commencement of work, the Contractor shall meet with the Director or his/her representative to:
 - .1 Discuss the nature and extent of all activities involved in the Project.
 - .2 Establish mutually acceptable security procedures in accordance with this instruction and the institution's particular requirements.
 - .3 Discuss scheduling of the work, in conjunction with security procedures, with Departmental Representative to ensure that the Control Post remains operational twenty four (24) hours a day at all times during construction period.
- .2 Contractor shall:
 - .1 Ensure that all Construction Employees are aware of the security requirements.
 - .2 Ensure that a copy of the security requirements is always prominently on display at the job site.
 - .3 Co-operate with institutional personnel in ensuring that security requirements are observed by all Construction Employees.

1.05 CONSTRUCTION EMPLOYEES

- .1 Submit to the Director a list of the names with date of birth of all Construction Employees to be employed on the construction site and a security clearance form for each employee.
 - .2 Allow two (2) weeks for processing of security clearances. Employees will not be admitted to the Institution without a valid security clearance in place and a recent picture identification such as a provincial driver's license. Security clearances obtained from other CSC Institutions are not valid at this Institution.
 - .3 The Director may require that facial photographs may be taken of Construction Employees and these photographs may be displayed at appropriate locations in the Institution or in an electronic database for identification purposes. The Director may require that Photo ID cards be provided for all Construction Employees. ID cards will then be left at the designated entrance to be picked upon arrival at the institution and shall be displayed prominently on the Construction Employees' clothing at all time while Construction Employees are in the institution.
 - .4 Entry to Institutional Property will be refused to any person there may be reason to believe may be a security risk.
-

- .5 Any person employed on the construction site will be subject to immediate removal from Institutional Property if they:
 - .1 Appear to be under the influence of alcohol, drugs or narcotics.
 - .2 Behave in an unusual or disorderly manner.
 - .3 Are in possession of contraband.
- .6 Smoking is prohibited anywhere on CSC property.

1.06 VEHICLES

- .1 All unattended vehicles on CSC property shall have windows closed; doors and trunks shall be locked and keys removed. The keys shall be securely in the possession of the owner or an employee of the company that owns the vehicle.
- .2 The Contractor shall advise the Director twenty four (24) hours in advance to the arrival on the site of heavy equipment such as concrete trucks, cranes, etc.
- .3 Vehicles being loaded with soil or other debris, or any vehicle considered impossible to search, must be under constant supervision by CSC staff or Commissionaires working under the authority of the Director.
- .4 The Director may limit at any time the number and type of vehicles allowed within the Institution.
- .5 Drivers of delivery vehicles for material required by the project may require security clearances and must remain with their vehicle the entire time that the vehicle is in the Institution. The Director will require that these vehicles be escorted by Institutional Staff or Commissionaires while in the Institution.
- .6 If the Director permits trailers to be left inside the secure perimeter of the Institution, these trailer doors will be locked at all times. All windows will be securely locked when left unoccupied. All trailer windows shall be covered with expanded metal mesh. All storage trailers inside and outside the perimeter shall be locked when not in use.
- .7 With the approval of the Director, certain equipment may be permitted to remain on the construction site overnight or over the weekend. This equipment must be securely locked, with the battery removed. The Director may require that the equipment be secured with a chain and padlock to another solid object.

1.07 PARKING

- .1 Parking area(s) to be used by Construction Employees will be designated by the Director. Parking in other locations will be prohibited and vehicles may be subject to removal.

1.08 SHIPMENTS

- .1 All shipments of project material, equipment and tools shall be addressed in the Contractor's name to avoid confusion with the Institution's own shipments. The Contractor must have his/her own employees on site to receive any deliveries or shipments. CSC staff will NOT accept receipt of deliveries or shipments of any material, equipment or tools.
-

1.09 TELEPHONES

- .1 There will be no installation of telephones, Facsimile machines and computers with Internet connections permitted within the perimeter of the Institution unless prior approval of the Director is received.
- .2 The Director will ensure that approved telephones, facsimile machine and computers with internet connections are located where they are not accessible to inmates. All computers will have an approved password protection that will stop an internet connection to unauthorized personnel.
- .3 Wireless cellular and digital telephones, including but not limited to devices for telephone messaging, pagers, BlackBerries, telephone used as 2-way radios, are not permitted within the Institution unless approved by the Director. If wireless cellular telephones are permitted, the user will not permit their use by any inmate.
- .4 The Director may approve but limit the use of two way radios.

1.10 WORK HOURS

- .1 Work hours within the Institution are: Monday to Friday 07:30 to 11:45 and 12:00 to 15:30. Entry to the Institution is through the main entrance. Construction vehicles and Contractors will be escorted into the institution between the hours of 07:30 and 15:30.
- .2 Work will not be permitted during weekends and statutory holidays without the permission of the Director. A minimum of fourteen (14) days advance notice will be required to obtain the required permission. In case of emergencies or other special circumstances, this advance notice may be waived by the Director.

1.11 OVERTIME WORK

- .1 No overtime work will be allowed without permission of the Director. Give a minimum forty (40) working hours advance notice when overtime work on the construction project is necessary and approved. If overtime work is required because of an emergency such as the completion of a concrete pour or work to make the construction safe and secure, the Contractor shall advise the Director as soon as this condition is known and follow the directions given by the Director. Costs to the Crown for such events may be attributed to the Contractor.
- .2 When overtime work, weekend, or statutory holiday work is required and approved by the Director, extra staff members may be posted by the Director or his/her designate, to maintain the security surveillance. The Departmental Representative may post extra staff for inspection of construction activities. The actual cost of this extra staff may be subject to reclamation by the Crown.

1.12 TOOLS AND EQUIPMENT

- .1 Maintain a complete list of all tools and equipment to be used during the construction project. Make this inventory available for inspection when required.
-

- .2 Throughout the construction project maintain up-to-date the list of tools and equipment specified above.
- .3 Keep all tools and equipment under constant supervision, particularly power-driven tools files, saw blades, rod saws, wire, rope, ladders and any sort of jacking device.
- .4 Store all tools and equipment in approved secure locations.
- .5 Lock all tool boxes when not in use. Keys to remain in the possession of the employees of the Contractor. Scaffolding shall be secured and locked when not erected and when erected, will be secured in a manner agreed upon with the Institutional designate.
- .6 All missing or lost tools or equipment shall be reported immediately to the Director.
- .7 The Director will ensure that the security staff members carry out checks of the Contractor's tools and equipment against the list provided by the Contractor. These checks may be carried out at the following intervals:
 - .1 At the beginning and conclusion of every construction project.
 - .2 Weekly, when the construction project extends longer than a one week period.
 - .3 The Contractor may be subject to random checks by security staff to ensure proper storage and security of tools throughout the project.
- .8 Certain tools/equipment such as hacksaw blades are highly controlled items. The Contractor will be given at the beginning of the day, a quantity that will permit one day's work. Used blades will be returned to the Director's representative at the end of each day.
- .9 If torches or grinders are required tools to perform Work, Contractor must complete a Hot Work Permit as supplied by CSC. Completed original form(s) are copied and posted on the work site in a conspicuous location. Original documents are to remain with the Institutional Fire Chief.

1.13 KEYS

- .1 Security Hardware Keys:
 - .1 The Contractor shall arrange with the security hardware supplier/installer to have the keys for the security hardware to be delivered directly to Institution, specifically the Security Maintenance Officer (SMO).
 - .2 The Security Maintenance Officer (SMO) will provide a receipt to the Contractor for security hardware keys.
 - .3 The Contractor will provide a copy of the above-mentioned receipt to the Departmental Representative.
- .2 Other Keys:
 - .1 The Contractor will use standard construction cylinders for locks for his/her use during the construction period.
 - .2 The Contractor will issue instructions to his/her employees and sub-trades, as necessary, to ensure safe custody of the construction set of keys.
 - .3 Upon completion of each phase of the construction, the CSC representative will, in conjunction with the lock manufacturer:
 - .1 Prepare an operational keying schedule.

- .2 Accept the operational keys and cylinders directly from the lock manufacturer.
- .3 Arrange for removal and return of the construction cores and install the operational core in all locks.
- .3 Upon putting operational security keys into use, the CSC construction escort shall obtain these keys as they are required from the Security Maintenance Officer (SMO) and open doors as required by the Contractor. The Contractor shall issue instructions to his/her employees advising them that all security keys shall always remain with the CSC construction escort.

1.14 SECURITY HARDWARE

- .1 Turn over all removed security hardware to the Director of the Institution for disposal or for safekeeping until required for re-installation.

1.15 PRESCRIPTION DRUGS

- .1 Employees of the Contractor who are required to take prescription drugs during the workday shall obtain approval of the Director to bring a one day supply only into the Institution.

1.16 SMOKING RESTRICTIONS

- .1 Contractors and construction employees are not permitted to smoke inside correctional facilities or outdoors within the perimeter of a correctional facility and must not possess unauthorized smoking items within the perimeter of a correctional facility.
- .2 Contractors and construction employees who are in violation of this policy will be requested to immediately cease smoking or dispose of any unauthorized smoking items and, if they persist, will be directed to leave the institution.
- .3 Smoking is only permitted outside the perimeter of a correctional facility in an area to be designated by the Director. Smoking breaks are limited in frequency at the discretion of the Director and may not be permitted once workers have entered the site for the day.

1.17 CONTRABAND

- .1 Weapons, ammunition, explosives, alcoholic beverages, drugs and narcotics are prohibited on Institutional Property.
 - .2 Discovery of Contraband on the construction site and the identification of the person(s) responsible for the Contraband shall be reported immediately to the Director.
 - .3 Contractors shall be vigilant with both their staff and the staff of their sub-contractors and suppliers that the discovery of Contraband may result in cancellation of the security clearance of the affected employee. Serious infractions may result in the removal of the company from the Institution for the duration of the construction.
-

- .4 Presence of arms and ammunition in vehicles of Contractors, sub-contractors and suppliers or employees of these will result in the immediate cancellation of security clearances for the driver of the vehicle.

1.18 SEARCHES

- .1 All persons entering Institutional property may be subject to search.
- .2 When the Director suspects, on reasonable grounds, that an employee of the Contractor is in possession of Contraband or unauthorized items, he/she may order that person to be searched.
- .3 All employees entering the Institution may be subject to screening of personal effects for traces of Contraband drug residue.

1.19 ACCESS TO AND REMOVAL FROM INSTITUTION PROPERTY

- .1 Construction personnel will not be admitted to the Institution after indicated working hours, unless approved by the Director.

1.20 MOVEMENT OF VEHICLES

- .1 Commercial vehicles will be allowed to enter the Institution via sally port entrance.

1.21 MOVEMENT OF CONSTRUCTION EMPLOYEES ON INSTITUTIONAL PROPERTY

- .1 Subject to the requirements of good security, the Director will permit the Contractor and his/her employees as much freedom of action and movement as is possible.
- .2 However, notwithstanding paragraph above, the Director may:
 - .1 Prohibit or restrict access to any part of the Institution.
 - .2 Require that in certain areas of the Institution, either during the entire construction project or at certain intervals, Construction Employees only be allowed access when accompanied by a member of the CSC security staff.
- .3 During the lunch and coffee/health breaks, all employees will remain within the construction site. Employees are not permitted to eat in the officer's lounge and dining room.

1.22 SURVEILLANCE AND INSPECTION

- .1 Construction activities and all related movement of personnel and vehicles will be subject to surveillance and inspection by CSC security staff members to ensure that established security requirements are met.
 - .2 CSC staff members will ensure that an understanding of the need to carry out surveillance and inspections, as specified above, is established among Construction Employees and maintained throughout the construction project.
-

1.23 STOPPAGE OF WORK

- .1 The Director may request at any time that the Contractor, his/her employees, sub-contractors and their employees not enter or leave the work site immediately due to a security situation occurring within the Institution. The Contractor's site supervisor shall note the name of the staff member making the request and the time of the request and obey the order as quickly as possible.
- .2 The Contractor shall advise the Departmental Representative within 24 hours of this delay to the progress of the work.

1.24 CONTACT WITH INMATES

- .1 Unless specifically authorized, it is forbidden to come into contact with inmates, to talk with them, to receive objects from them or to give them objects. Any employee doing any of the above will be removed from the site and his/her security clearance revoked.
- .2 It is forbidden to take pictures of inmates, of CSC staff members or of any part of the Institution other than those required as part of this Contract.

1.25 COMPLETION OF CONSTRUCTION PROJECT

- .1 Upon completion of the construction project or, when applicable, the takeover of a facility, the Contractor shall remove all remaining construction material, tools and equipment that are not specified to remain in the Institution as part of the construction contract.

2 PRODUCTS

2.01 NOT USED

- .1 Not used.

3 EXECUTION

3.01 NOT USED

- .1 Not used.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES

- .1 Canadian Standards Association (CSA): Canada
 - .1 CSA S350-M1980(R2003), Code of Practice for Safety in Demolition of Structures.
- .2 National Building Code 2010 (NBC):
 - .1 NBC 2010, Division B, Part 8 Safety Measures at Construction and Demolition Sites.
- .3 National Fire Code 2010 (NFC):
 - .1 NFC 2010, Division B, Part 5 Hazardous Processes and Operations, subsection 5.6.1.3 Fire Safety Plan.
- .4 Province of Ontario:
 - .1 Occupational Health and Safety Act Revised Statutes of Ontario 1990, Chapter O.1 as amended, and Regulations for Construction Projects, O. Reg. 213/91 as amended.
 - .2 O. Reg. 490/09, Designated Substances.
 - .3 Workplace Safety and Insurance Act, 1997.
 - .4 Municipal statutes and authorities.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Submit site-specific Health and Safety Plan: Within 7 days after date of Notice to Proceed and prior to commencement of Work. Health and Safety Plan must include:
 - .1 Results of site specific safety hazard assessment.
 - .2 Results of safety and health risk or hazard analysis for site tasks and operation.
 - .3 Measures and controls to be implemented to address identified safety hazards and risks.
- .3 Provide a Fire Safety Plan, specific to the work location, in accordance with NBC, Division B, Article 8.1.1.3 prior to commencement of work. The plan shall be coordinated with, and integrated into, the existing Facility Emergency Procedures and Evacuation Plan in place at the site. Departmental Representative will provide Facility Emergency Procedures and Evacuation Plan. Deliver two copies of the Fire Safety Plan to the Departmental Representative not later than 14 days before commencing work.
- .4 Contractor's and Sub-contractors' Safety Communication Plan.
- .5 Contingency and Emergency Response Plan addressing standard operating procedures specific to the project site to be implemented during emergency situations. Coordinate plan with existing Facility Emergency Response requirements and procedures provided by Departmental Representative.

- .6 Departmental Representative will review Contractor's site-specific Health and Safety Plan and provide comments to Contractor within 3 days after receipt of plan. Revise plan as appropriate and resubmit plan to Departmental Representative within 3 days after receipt of comments from Departmental Representative.
- .7 Departmental Representative's review of Contractor's final Health and Safety plan should not be construed as approval and does not reduce the Contractor's overall responsibility for construction Health and Safety.
- .8 Submit names of personnel and alternates responsible for site safety and health.
- .9 Submit records of Contractor's Health and Safety meetings when requested.
- .10 Submit 3 copies of Contractor's authorized representative's work site health and safety inspection reports to Departmental Representative weekly.
- .11 Submit 3 copies of Contractor's authorized representative's work site health and safety inspection reports to Departmental Representative, weekly.
- .12 Submit copies of orders, directions or reports issued by health and safety inspectors of the authorities having jurisdiction.
- .13 Submit copies of incident and accident reports.
- .14 Submit Material Safety Data Sheets (MSDS).
- .15 Submit Workplace Safety and Insurance Board (WSIB)- Experience Rating Report.
- .16 Medical Surveillance: where prescribed by legislation, regulation or safety program, submit certification of medical surveillance for site personnel, in accordance with O. Reg. 490, prior to commencement of Work, and submit additional certifications for any new site personnel to Departmental Representative.
- .17 File Notice of Project with Provincial authorities prior to commencement of Work.

1.3 WORK PERMIT

- .1 Obtain building permits related to project prior to commencement of Work.

1.4 SAFETY ASSESSMENT

- .1 Perform site specific safety hazard assessment related to project.

1.5 MEETINGS

- .1 Schedule and administer Health and Safety meeting with Departmental Representative prior to commencement of Work.

1.6 REGULATORY REQUIREMENTS

- .1 Comply with the Acts and regulations of the Province of Ontario.
- .2 Comply with specified standards and regulations to ensure safe operations at site.

1.7 PROJECT/SITE CONDITIONS

- .1 Work at site will involve contact with:
 - .1 Silica in concrete.

1.8 GENERAL REQUIREMENTS

- .1 Develop written site-specific Health and Safety Plan based on hazard assessment prior to beginning site Work and continue to implement, maintain, and enforce plan until final demobilization from site. Health and Safety Plan must address project specifications.
- .2 Departmental Representative may respond in writing, where deficiencies or concerns are noted and may request re-submission with correction of deficiencies or concerns either accepting or requesting improvements.
- .3 Relief from or substitution for any portion or provision of minimum Health and Safety standards specified herein or reviewed site-specific Health and Safety Plan shall be submitted to Departmental Representative in writing.

1.9 COMPLIANCE REQUIREMENTS

- .1 Comply with Ontario Occupational Health and Safety Act, R.S.O. 1990 Chapter 0.1, as amended.

1.10 RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial and local statutes, regulations, and ordinances, and with site-specific Health and Safety Plan.
- .3 Where applicable the Contractor shall be designated "Constructor", as defined by Occupational Health and Safety Act and Regulations for Construction Projects for the Province of Ontario.

1.11 UNFORSEEN HAZARDS

- .1 Should any unforeseen or peculiar safety-related factor, hazard, or condition become evident during performance of Work, immediately stop work and advise Departmental Representative verbally and in writing.
- .2 Follow procedures in place for Employees Right to Refuse Work as specified in the Occupational Health and Safety Act for the Province of Ontario.

1.12 HEALTH AND SAFETY CO-ORDINATOR

- .1 Employ and assign to Work, competent and authorized representative as Health and Safety Co-ordinator. Health and Safety Co-ordinator must:
 - .1 Have working knowledge of occupational safety and health regulations.
 - .2 Be responsible for completing Contractor's Health and Safety Training Sessions and ensuring that personnel not successfully completing required training are not permitted to enter site to perform Work.
 - .3 Be responsible for implementing, enforcing daily and monitoring site-specific Contractor's Health and Safety Plan.
 - .4 Be on site during execution of Work and report directly to and be under direction of site supervisor.

1.13 POSTING OF DOCUMENTS

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province of Ontario, and in consultation with Departmental Representative.
 - .1 Contractor's Safety Policy.
 - .2 Constructor's Name.
 - .3 Notice of Project.
 - .4 Name, trade, and employer of Health and Safety Representative or Joint Health and Safety Committee members (if applicable).
 - .5 Ministry of Labour Orders and reports.
 - .6 Occupational Health and Safety Act and Regulations for Construction Projects for Province of Ontario.
 - .7 Address and phone number of nearest Ministry of Labour office.
 - .8 Material Safety Data Sheets.
 - .9 Written Emergency Response Plan.
 - .10 Site Specific Safety Plan.
 - .11 Valid certificate of first aider on duty.
 - .12 WSIB "In Case of Injury At Work" poster.
 - .13 Location of toilet and cleanup facilities.

1.14 CORRECTION OF NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative may stop Work if non-compliance of health and safety regulations is not corrected.

1.15 BLASTING

- .1 Blasting or other use of explosives is not permitted without prior receipt of written instruction by Departmental Representative.

1.16 POWDER ACTUATED DEVICES

- .1 Powder actuated devices are not permitted.
-

1.17 WORK STOPPAGE

- .1 Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations for Work.
- .2 Assign responsibility and obligation to Health and Safety Coordinator to stop or start Work when, at Health and Safety Coordinator's discretion, it is necessary or advisable for reasons of health or safety. Departmental Representative may also stop Work for health and safety considerations.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not used.

END OF SECTION

Part 1 GENERAL

1.1 GENERAL

- .1 This section specifies general requirements and procedures for fire safety. Additional requirements may be specified in individual sections elsewhere in specifications.

1.2 REPORTING FIRES

- .1 The Departmental Representative will co-ordinate arrangements for the Contractor to be briefed at the pre-construction meeting concerning Building's fire safety protocol.
- .2 The Departmental Representative will supply a copy of "Fire Safety Emergency Evacuation Plan" in effect for this building. Contractor shall comply with outlined fire safety requirements.
- .3 Know location of nearest fire alarm box and telephone, including emergency phone number.
- .4 Report immediately all fire incidents to Fire Department as follows:
 - .1 activate nearest fire alarm box; or
 - .2 telephone.
- .5 Person activating fire alarm box will remain at box to direct Fire Department to scene of fire.
- .6 When reporting fire by telephone, give location of fire, name or number of building and be prepared to verify the location.

1.3 FIRE WATCH

- .1 Appoint a Fire Watch at locations where welding and soldering, torching or roofing is to take place.
- .2 A dedicated Fire Watch is not required. A competent person from the workforce on site may be assigned as Fire Watch for duration of work.
- .3 Assign a person who is knowledgeable in the correct use of fire extinguishers on the project.
- .4 Have work inspected by the Fire Watch up to 1.5 hours after work stoppage for each work period.

1.4 INTERIOR AND EXTERIOR FIRE PROTECTION AND ALARM SYSTEMS

- .1 Fire protection and alarm system will not be:
 - .1 obstructed;
 - .2 shut-off; or
 - .3 left inactive at end of working day or shift.
- .2 Fire hydrants, standpipes and hose systems will not be used for other than fire-fighting purposes unless authorized by Departmental Representative.

- .3 Provide and maintain free access to fire extinguishing equipment. Maintain exit facilities. Keep means of egress free from materials, equipment and obstructing.

1.5 FIRE EXTINGUISHERS

- .1 Supply fire extinguishers, as necessary to protect work in progress and contractor's physical plant on site.

1.6 BLOCKAGE OF ROADWAYS

- .1 Advise Departmental Representative of any work that would impede fire apparatus response. This includes violation of minimum required overhead clearance.

1.7 SMOKING PRECAUTIONS

- .1 Smoking is not permitted within areas of work or site storage.

1.8 RUBBISH AND WASTE MATERIALS

- .1 Rubbish and waste materials are to be kept to a minimum.
- .2 Burning of rubbish is prohibited.
- .3 Remove all rubbish from work site at end of work day or shift or as directed.
- .4 Storage:
 - .1 Store oily waste in approved receptacles to ensure maximum cleanliness and safety.
 - .2 Deposit greasy or oily rags and materials subject to spontaneous combustion in approved receptacles and remove from site daily or at the end of each shift.

1.9 FLAMMABLE AND COMBUSTIBLE LIQUIDS

- .1 Handling, storage and use of flammable and combustible liquids are to be governed by the current National Fire Code of Canada.
 - .2 Flammable and combustible liquids such as gasoline, kerosene and naphtha will be stored for use in designated lay down area outside of the Perimeter in quantities not exceeding 45 litres provided they are stored in approved safety cans bearing Underwriters' Laboratory of Canada or Factory Mutual seal of approval. Storage of quantities of flammable and combustible liquids exceeding 45 litres for work purposes requires permission of local Departmental Representative.
 - .3 Transfer of flammable and combustible liquids is prohibited within buildings or jetties.
 - .4 Transfer of flammable and combustible liquids will not be carried out in vicinity of open flames or any type of heat-producing devices.
 - .5 Flammable liquids having a flash point below 38°C such as naphtha or gasoline will not be used as solvents or cleaning agents.
 - .6 Flammable and combustible waste liquids, for disposal, will be stored in approved containers located in a safe ventilated area. Quantities are to be kept to a minimum and Fire Department is to be notified when disposal is required.
-

1.10 HAZARDOUS SUBSTANCES

- .1 Work entailing use of toxic or hazardous materials, chemicals and/or explosives, or otherwise creating hazard to life, safety or health, will be in accordance with National Fire Code of Canada.
- .2 Obtain from local Departmental Representative a "Hot Work" permit for work involving welding, burning or use of blow torches and salamanders, in buildings or facilities.
- .3 When Work is carried out in dangerous or hazardous areas involving use of heat, provide fire watchers equipped with sufficient fire extinguishers. Determination of dangerous or hazardous areas along with level of protection necessary for Fire Watch is at discretion of the Departmental Representative. Contractors are responsible for providing fire watch service for work on a scale established and in conjunction with Departmental Representative at pre-construction meeting.
- .4 Where flammable liquids, such as lacquers or urethanes are to be used, proper ventilation will be assured and all sources of ignition are to be eliminated. Departmental Representative is to be informed prior to and at cessation of such work.
- .5 WHMIS sheets for all hazardous materials are to be available on site at all times and additional copies are to be provided to Departmental Representative prior to bringing materials on site.

1.11 WELDING, BURNING AND CUTTING

- .1 Contractor performing work of this section must notify Departmental Representative in advance of commencing work.
- .2 Use non-combustible shields for electric and gas welding or cutting executed within 3 m of combustible material or in occupied spaces.
- .3 Place cylinders supplying gases as close to work as possible. Secure cylinders in upright position, free from exposure to sun or high temperature.
- .4 Locate fire extinguishing equipment near all welding, cutting and soldering operations.
- .5 Contractor's mechanics shall be properly equipped with required protective clothing, including goggles or welding hood or face mask, gloves, etc.
- .6 Contractor is responsible for the protection of his work and the Departmental Representative's property.
- .7 Provide Fire Watch on standby with approved fire extinguisher while burning or welding is in progress.

1.12 QUESTIONS AND/OR CLARIFICATIONS

- .1 Direct any questions or clarification on Fire Safety in addition to above requirements to local Departmental Representative.

1.13 FIRE INSPECTION

- .1 Site inspections will be coordinated through Departmental Representative.
- .2 Allow local Departmental Representative unrestricted access to work site.

- .3 Co-operate with Departmental Representative during routine fire safety inspection of work site.
- .4 Immediately remedy all unsafe fire situations observed by Departmental Representative.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not used.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES AND CODES

- .1 Perform Work in accordance with National Building Code of Canada (NBC) 2010, National Fire Code of Canada (NFC) 2010 including all amendments up to bid closing date and other codes of provincial or local application provided that in case of conflict or discrepancy, more stringent requirements apply as directed by the Departmental Representative.
- .2 Meet or exceed requirements of:
 - .1 Contract documents.
 - .2 Specified standards, codes and referenced documents.

1.2 HAZARDOUS MATERIAL DISCOVERY

- .1 Stop work immediately and notify Departmental Representative if materials which may contain designated substances or PCB's, other than those identified in Section 01 11 01 are discovered in course of work.

1.3 BUILDING AND SITE SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions.

1.4 RELICS AND ANTIQUITIES

- .1 Relics and antiquities, and items of historical or scientific interest such as cornerstones and contents, commemorative plaques, inscribed tables, and similar objects found on site shall remain the property of the Owner. Protect such articles and request directives from Departmental Representative.
- .2 Should historic objects be uncovered during excavating, stop work immediately and notify the Departmental Representative. Do not resume work until directed to by the Departmental Representative.
- .3 Departmental Representative's archaeology staff will monitor the project work and may require temporary stop of work to carry out site investigations.
- .4 Protect subsurface historic features, profiles and ground, at the location indicated as archaeological find on Drawing L-1.

1.5 IAQ - INDOOR AIR QUALITY

- .1 Comply with CSA-Z204-94(R1999), Guideline for Managing Indoor Air Quality in Office Buildings and CSA B651-12.

1.6 ACCESSIBLE DESIGN

- .1 Comply with CSA B651-12, Accessible Design for the Built Environment, unless specified otherwise. In any case of conflict or discrepancy between the building codes and CSA B651, the requirements of CSA B651 shall apply.

1.7 STATISTICAL INFORMATION

- .1 Provide statistical information to Departmental Representative:
 - .1 Within ten working days after March 31 and September 30 occurring between commencement of work and final completion
 - .2 Within ten working days after final completion.
- .2 Include in statistical information:
 - .1 Statement of total person days of labour used on site in performance of contract, including labour provided under sub-contracts.
 - .2 Estimate of total value in dollars of material delivered to site and installed, including material provided and installed under sub-contracts.
- .3 This information is required by Government of Canada solely to provide statistics that will aid in assessing socio-economic benefits of this project.

1.8 TAXES

- .1 Pay applicable Federal, Provincial and Municipal taxes.

1.9 EXAMINATION

- .1 Examine existing conditions and determine conditions affecting work.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 ABBREVIATIONS AND ACRONYMS

- .1 The abbreviations and acronyms are commonly found in the Project Manual and represent the associated organizations or terms.

1.2 MATERIALS, EQUIPMENT AND METHODS

- .1 A:
- .1 AB: anchor bolt.
 - .2 AC: acoustic.
 - .3 AC PAN: acoustic panel.
 - .4 ACU: acoustic unit ceiling.
 - .5 AFF: above finished floor.
 - .6 AC PLAS: acoustic plaster.
 - .7 ACT: acoustic tile.
 - .8 ACR CU LVR: acrylic cube louvre.
 - .9 ADH: adhesive.
 - .10 ADJ: adjustable.
 - .11 A/C: air conditioner.
 - .12 AHU: air handling unit.
 - .13 AL: aluminum.
 - .14 ANOD: anodized.
 - .15 APPROX: approximate.
 - .16 ARCH: architecture.
 - .17 ARCH BLK: architectural block.
 - .18 AVB: air vapour barrier.
- .2 B:
- .1 B: base.
 - .2 BEAST: benthic assessment of sediment.
 - .3 BH: bore hole.
 - .4 BHP: brake horse power.
 - .5 BL: bottom layer.
 - .6 BLK: block.
 - .7 BLKD: bulkhead.
 - .8 BM: beam.
 - .9 BOT: bottom.
 - .10 BMP: best management practice.
 - .11 B PL: base plate.
-

- .12 BRG: bearing.
- .13 BRK: brick.
- .14 BSMT: basement.
- .15 BTEX: benzene, toluene, ethylbenzene and xylenes.
- .16 BUR: built-up roof.
- .3 C:
 - .1 CAL: caliper.
 - .2 CANTIL: cantilever.
 - .3 CB: catch basin.
 - .4 CC: centre to centre.
 - .5 CCN: contemplated change notice.
 - .6 CDF: controlled density fill.
 - .7 CEC: Canadian Electrical Code.
 - .8 CF: chair fabric.
 - .9 CHAN: channel.
 - .10 CHS: Canadian hydrographic service.
 - .11 CJ: construction joint.
 - .12 CL: centreline.
 - .13 CK: cork.
 - .14 CLG: ceiling.
 - .15 CLR: clear.
 - .16 COL: column.
 - .17 CONC: concrete.
 - .18 CONC BLK: concrete block.
 - .19 CONC BRK: concrete brick.
 - .20 CONT: continuous.
 - .21 CONT J: control joint.
 - .22 COMPL: complete.
 - .23 CM: centimetre. (Nursery stock).
 - .24 CP: circulating pump.
 - .25 CPL: cement plaster.
 - .26 CPM: critical path method.
 - .27 CPT: carpet.
 - .28 CPTT: carpet tile.
 - .29 CT: ceramic tile.
 - .30 CTE: connect to existing.
 - .31 CV: control valve.
 - .32 CVT: conductive vinyl tile.
 - .33 C/W: complete with.

- .4 D:
- .1 D: deep.
 - .2 dB: decibels.
 - .3 DB: dry-bulb.
 - .4 DD: dutch door.
 - .5 DEG: degree.
 - .6 DF: drinking fountain.
 - .7 DIA: diameter.
 - .8 DIM: dimension.
 - .9 DL: dead load.
 - .10 DMNT: demountable.
 - .11 DP: dampproofing.
 - .12 DR: door.
 - .13 DRP: drapery.
 - .14 DWL: dowel.
- .5 E:
- .1 EA: each.
 - .2 EC: epoxy coating.
 - .3 ECF: engineered containment facility.
 - .4 EE: each end.
 - .5 EF: each face (architectural/structural).
 - .6 EF: exhaust fan (mechanical/electrical).
 - .7 EL: elevation.
 - .8 ELEC: electric.
 - .9 ELEV: elevator.
 - .10 EM: expanded metal.
 - .11 ENCL: enclosure.
 - .12 EQ: equal.
 - .13 ET: expansion tank.
 - .14 EXH: exhaust.
 - .15 EXIST: existing.
 - .16 EXPJ: expansion joint.
 - .17 EXP STRUCT: exposed structure.
 - .18 EXT: exterior.
 - .19 EW: each way.
 - .20 EWT: entering water temperature.
- .6 F:
- .1 FC: fuel contributed.
 - .2 FD: floor drain.
-

- .3 FDN: foundation.
- .4 FEAT W: feature wall.
- .5 FEXT: fire extinguisher.
- .6 FH: fire hose.
- .7 FHC: fire hose cabinet.
- .8 FHR: fire hose rack.
- .9 FIN: finish.
- .10 FIP: federal identity program.
- .11 FL: floor.
- .12 FLD: field.
- .13 FLUOR: fluorescent.
- .14 FR: frame.
- .15 FRR: fire resistance rating.
- .16 FTG: footing.
- .7 G:
 - .1 GALV: galvanized steel.
 - .2 GB: grab bar.
 - .3 GBD: gypsum board.
 - .4 GC: General Conditions.
 - .5 GF: ground floor.
 - .6 GFCI: ground fault circuit interrupter.
 - .7 GL: glass or glazing.
 - .8 GL BLK: glass block.
 - .9 GPC: gypsum plaster ceiling.
 - .10 GPW: gypsum plaster wall.
 - .11 GT: glass tile.
- .8 H:
 - .1 HB: hose bib.
 - .2 HC: hollow core.
 - .3 HCWD: hollow core wood door.
 - .4 HD: hand dryer.
 - .5 HDW: hardware.
 - .6 HDWD: hardwood.
 - .7 HEX: heat exchanger.
 - .8 HM: hollow metal.
 - .9 HOR: horizontal.
 - .10 HOR EF: horizontal each face.
 - .11 HP: hydro pole.
 - .12 HPA: Hamilton Port Authority.

.13	HR: hour.
.14	HRV: heat recovery ventilator.
.15	HT: height.
.16	HTR: heater.
.17	HUM: humidifier.
.18	HWT: hot water tank.
.19	HYD: hydrant.
.20	HZ: Hertz frequency, cycles per second.
.9	I:
.1	ICF: insulated concrete formwork.
.2	ID: inside diameter.
.3	INS: insulation.
.4	INTLK: interlock.
.10	J:
.1	JT: joint.
.11	K:
.1	KPL: kick plate.
.12	L:
.1	LAT: leaving air temperature.
.2	LAV: lavatory.
.3	LDG: landing.
.4	LG: long.
.5	LINO: linoleum.
.6	LL: live load.
.7	LT: light.
.8	LWT: leaving water temperature.
.13	M:
.1	MAS: masonry.
.2	MAS FL: masonry flashing.
.3	MAX: maximum.
.4	MBG: metal bar grating.
.5	MCL: metal cube louver.
.6	MECH: mechanical.
.7	MET: metal.
.8	MET DK: metal deck.
.9	MET FL: metal flashing.
.10	MET GRID CLG: metal grid ceiling.
.11	MET GRTG: metal grating.

- .12 MET LIN CLG: metal linear ceiling.
 - .13 MET T PTN: metal toilet partition.
 - .14 MH: maintenance hole.
 - .15 MIN: minimum.
 - .16 MLP: metal lath and plaster.
 - .17 MO: masonry opening.
 - .18 MR: marble.
 - .19 MT: metal threshold.
 - .20 MWP: membrane waterproofing.
 - .14 N:
 - .1 NBC: national building code.
 - .2 NC: normally closed.
 - .3 NF: near face.
 - .4 NFC: national fire code.
 - .5 NIC: not in contract.
 - .6 NO: number.
 - .7 NRC: noise reduction coefficient.
 - .8 NRP: non removable pin.
 - .9 NTS: not to scale.
 - .15 O:
 - .1 OA: outside air.
 - .2 OBC: Ontario building code.
 - .3 OC: on centre.
 - .4 OD: outside diameter.
 - .5 OPNG: opening.
 - .6 OPR: operator.
 - .7 OVHD: overhead.
 - .8 OWSJ: open web steel joist.
 - .16 P:
 - .1 P: prefinished.
 - .2 PAH: polynuclear aromatic hydrocarbons.
 - .3 PARG: parging.
 - .4 PCC: precast concrete.
 - .5 PCT: porcelain ceramic tile.
 - .6 PED ACS FLG: pedestal access flooring.
 - .7 PF: panel fabric.
 - .8 PH: phase.
 - .9 PL: plate.
 - .10 PLAM: plastic laminate.
-

- .11 PLAS: plaster.
- .12 PLYWD: plywood.
- .13 PR: pair.
- .14 PREFAB: prefabricated.
- .15 PREFIN: prefinished.
- .16 PRESS: pressure.
- .17 PRFL: profile.
- .18 PRV: pressure regulating valve.
- .19 PT: paint.
- .20 PTD: paper towel dispenser.
- .21 PTN: partition.
- .22 PVC: polyvinyl chloride.
- .17 Q:
 - .1 QTB: quarry tile base.
 - .2 QTF: quarry tile floor.
 - .3 QTR: quarry tile roof.
- .18 R:
 - .1 R: radius.
 - .2 RA: return air.
 - .3 RAD: return air damper.
 - .4 RB: resilient base.
 - .5 RC: reinforced concrete.
 - .6 RCPT: receptacle.
 - .7 RD: roof drain.
 - .8 REINF: reinforced/reinforcing.
 - .9 REQD: required.
 - .10 REQT: requirement.
 - .11 RFT: rubber floor tile.
 - .12 RM: room.
 - .13 RO: rough opening.
 - .14 RP: radiant panel.
 - .15 RRS: recycled rubber sheet.
 - .16 RRT: recycled rubber tile.
 - .17 RSD: rolling steel door.
 - .18 RSF: rubber sheet flooring.
 - .19 RT: rubber tile.
 - .20 RTU: roof top unit.
 - .21 RWL: rain water leader.

- .19 S:
- .1 SA: supply air.
 - .2 SAN SEW: sanitary sewer.
 - .3 SCHED: schedule.
 - .4 SC: solid core.
 - .5 SCRΝ: screen.
 - .6 SCWD: solid core wood door.
 - .7 SD: smoke developed.
 - .8 SDT: static dissipative tile.
 - .9 SECT: section.
 - .10 SH: sill height.
 - .11 SIM: similar.
 - .12 SL: sliding.
 - .13 SLR: sealer.
 - .14 SPEC: specification.
 - .15 SS: stainless steel.
 - .16 STD: standard.
 - .17 STL: steel.
 - .18 STL BM: steel beam.
 - .19 STC: sound transmission class.
 - .20 STL FL DK: steel floor deck.
 - .21 STL PL: steel plate.
 - .22 STN: stone.
 - .23 STR: structure or structural.
 - .24 ST SEW: storm sewer.
 - .25 S&U: stain and urethane.
 - .26 S&V: stain and varnish.
 - .27 SVT: solid vinyl tile.
- .20 T:
- .1 T: top.
 - .2 T&B: top and bottom.
 - .3 TCB: turbidity control plan.
 - .4 TEL: telephone.
 - .5 TER: terrazzo.
 - .6 TERT: terrazzo tile.
 - .7 THKNS: thickness.
 - .8 THR: threshold.
 - .9 TMPD: tempered.
 - .10 TOPG: topping.
-

- .11 TRANSV: transverse.
 - .12 TYP: typical.
 - .21 U:
 - .1 U: urethane.
 - .2 U/C: undercut.
 - .3 UGRD: underground.
 - .4 UNO: unless noted otherwise.
 - .5 UOS: unless otherwise specified.
 - .6 U/S: underside.
 - .7 UR: urinal.
 - .22 V:
 - .1 V: volt.
 - .2 VCF: vinyl coated fabric.
 - .3 VCT: vinyl composition tile.
 - .4 VEL: velocity.
 - .5 VERT: vertical.
 - .6 VERT B: vertical blinds.
 - .7 VERT EF: vertical each face.
 - .8 VSF: vinyl sheet flooring.
 - .9 VPT: vinyl plank flooring.
 - .10 VT: vinyl tile.
 - .11 VWC: vinyl wall covering.
 - .23 W:
 - .1 WB: wet-bulb.
 - .2 WC: water closet.
 - .3 W-C: wall connectors.
 - .4 WD: wood.
 - .5 WDV: wood veneer.
 - .6 WG: water gauge.
 - .7 WH: wall hydrant.
 - .8 WHMIS: workplace hazardous materials information system.
 - .9 WP: waterproofing.
 - .10 WR: washroom.
 - .11 WSIB: workplace safety and insurance board.
 - .12 WT: weight.
 - .13 WTP: water treatment plant.
-

1.3 STANDARDS ORGANIZATIONS

- .1 Standards writing organizations:
 - .1 AA - Aluminum Association.
 - .2 ACPA - American Concrete Pipe Association.
 - .3 ANSI - American National Standards Institute.
 - .4 ASHRAE - American Society of Heating and Refrigerating and Air-Conditioning Engineers.
 - .5 ASTM - American Society for Testing and Materials.
 - .6 AWI/AWMAC - Architectural Woodwork Institute/Architectural Woodwork Manufacturers Association of Canada.
 - .7 AWWA - American Water Works Association.
 - .8 AWWA - American Water Works Association.
 - .9 BHMA - Builders Hardware Manufacturers Association.
 - .10 CCDC - Canadian Construction Documents Committee.
 - .11 CCMPA - Canadian Concrete Masonry Producers Association.
 - .12 CGSB - Canadian General Standards Board.
 - .13 CNTA - Canadian Nursery Trades Association.
 - .14 CPCA - Canadian Painting Contractors Association.
 - .15 CRCA - Canadian Roofing Contractors Association.
 - .16 CSA - Canadian Standards Association.
 - .17 CSC - Construction Specifications Canada.
 - .18 CSDMA - Canadian Steel Door Manufacturers Association.
 - .19 CSI - Construction Specifications Institute.
 - .20 CSSBI - Canadian Sheet Steel Building Institute.
 - .21 CRCA - Canadian Roofing Contractors Association.
 - .22 DHI - Door and Hardware Institute.
 - .23 EEMAC - Electrical and Electronic Manufacturer's Association of Canada.
 - .24 ESA - Electrical Safety Authority.
 - .25 FCC - Fire Commissioner of Canada.
 - .26 FSC - Forest Stewardship Council.
 - .27 GANA - Glass Association of North America.
 - .28 HMMA - Hollow Metal Manufacturers Association.
 - .29 IEEE - Institute of Electrical and Electronics Engineers Inc.
 - .30 ISO - International Organization for Standardization.
 - .31 IWFA - International Window Film Association.
 - .32 LEED - LEED Canada, Leadership in Energy and Environmental Design.
 - .33 MPI - Master Painters Institute.
 - .34 NAAMM - National Association of Architectural Metal Manufacturers.
 - .35 NCPI - National Clay Pipe Institute.
 - .36 NEMA - National Electrical Manufacturers Association.

- .37 NFPA - National Fire Protection Association.
- .38 OPSD - Ontario Provincial Standard Drawings.
- .39 OPSS - Ontario Provincial Standard Specifications.
- .40 PPI - Plastics Pipe Institute.
- .41 SDI - Steel Door Institute.
- .42 SCAQMD - South Coast Air Quality Management District.
- .43 TIA - Telecommunications Industry Association.
- .44 TIAC - Thermal Insulation Association of Canada.
- .45 TTMAC - Terrazzo Tile and Marble Association of Canada.
- .46 UL - Underwriters Laboratories.
- .47 ULC - Underwriters Laboratories of Canada.
- .48 US EPA - United States Environmental Protection Agency.
- .49 WH - Warnock Hersey.

1.4 FEDERAL GOVERNMENT DEPARTMENTS AND AGENCIES

- .1 Departments, agencies and crown corporations.
 - .1 CEAA - Canadian Environmental Assessment Agency.
 - .2 CSC - Correctional Service Canada.
 - .3 CRA - Canada Revenue Agency.
 - .4 DND - Department of National Defence.
 - .5 EC - Environment Canada.
 - .6 FHBRO - Federal Heritage Buildings Review Office.
 - .7 HC - Health Canada.
 - .8 HCD - Heritage Conservation Directorate.
 - .9 LC - Labour Canada.
 - .10 PC - Parks Canada.
 - .11 PWGSC - Public Works and Government Services Canada.
 - .12 RCMP - Royal Canadian Mounted Police.
 - .13 TBS - Treasury Board Secretariat.
 - .14 TC - Transport Canada.

1.5 PROVINCIAL GOVERNMENT DEPARTMENTS AND AGENCIES

- .1 MOEE - Ontario Ministry of Environment and Energy.
- .2 MOL - Ontario Ministry of Labour.
- .3 MTO and MOT - Ontario Ministry of Transportation.
- .4 TSSA - Technical Standards and Safety Authority.

1.6 INTERNATIONAL GOVERNMENT DEPARTMENTS AND AGENCIES

- .1 DOHMH - New York City Department of Health and Mental Hygiene, USA.
- .2 GSA - Government Services Administration, USA.

1.7 UNITS OF MEASURE METRIC

- .1 The following abbreviations of units of measure are commonly found in the Project Manual:
- .1 C: Celsius.
 - .2 cm: centimetre.
 - .3 kg: kilogram.
 - .4 kg/m^3 : kilogram per cubic metre.
 - .5 kN: kilonewton.
 - .6 kPa: kilopascals.
 - .7 kw: kilowatts.
 - .8 l/s: litre per second.
 - .9 m: metre.
 - .10 M^3 : cubic metre.
 - .11 mg/kg: milligrams per kilogram.
 - .12 mg/L: milligrams per litre.
 - .13 mm: millimetres.
 - .14 MPa: megapascal.
 - .15 NTU: nephelometric turbidity unit.
 - .16 ppm: parts per million.
 - .17 ug/L: micrograms per litre.
 - .18 ug/m^3 : micrograms per cubic metre.

1.8 UNITS OF MEASURE IMPERIAL

- .1 The following abbreviations of units of measure are commonly found in the Project Manual:
- .1 BTU: British thermal units.
 - .2 CFM: cubic feet per minute.
 - .3 F: Fahrenheit.
 - .4 ft: foot/feet.
 - .5 FPI: fins per inch.
 - .6 FPM: feet per minute.
 - .7 ga: gauge.
 - .8 gpm: gallons per minute.
 - .9 in: inches.
 - .10 lbs: pounds.
 - .11 NTU: nephelometric turbidity unit.
 - .12 psi: pounds-force per square inch.
 - .13 PSIG: PSI gauge.
 - .14 ppm: parts per million.
 - .15 RPM: revolutions per minute.
-

Part 2 PRODUCTS

2.1 NOT USED

.1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Inspection and testing, administrative and enforcement requirements.
- .2 Tests and mix designs.
- .3 Mock-ups.
- .4 Mill tests.
- .5 Equipment and system adjust and balance.

1.2 INSPECTION

- .1 Allow Departmental Representative access to Work. If part of Work is in preparation at locations other than Place of Work, allow access to such Work whenever it is in progress.
- .2 Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Departmental Representative instructions, or law of Place of Work.
- .3 If Contractor covers or permits to be covered Work that has been designated for special tests, inspections or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.
- .4 Departmental Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents. If, upon examination such work is found not in accordance with Contract Documents, correct such Work and pay cost of examination and correction. If such Work is found in accordance with Contract Documents, Departmental Representative shall pay cost of examination and replacement.

1.3 INDEPENDENT INSPECTION AGENCIES

- .1 Independent Inspection/Testing Agencies will be engaged by Departmental Representative for purpose of inspecting and/or testing portions of Work above and beyond those required of the Contractor.
- .2 Provide equipment required for executing inspection and testing by appointed agencies.
- .3 Employment of inspection/testing agencies does not relax responsibility to perform Work in accordance with Contract Documents.
- .4 If defects are revealed during inspection and/or testing, appointed agency will request additional inspection and/or testing to ascertain full degree of defect. Correct defect and irregularities as advised by Departmental Representative at no cost to Departmental Representative. Pay costs for retesting and reinspection.

1.4 ACCESS TO WORK

- .1 Allow inspection/testing agencies access to Work, off site manufacturing and fabrication plants.
 - .2 Co-operate to provide reasonable facilities for such access.
-

1.5 PROCEDURES

- .1 Notify appropriate agency and Departmental Representative in advance of requirement for tests, in order that attendance arrangements can be made.
- .2 Submit samples and/or materials required for testing, as specifically requested in specifications. Submit with reasonable promptness and in an orderly sequence so as not to cause delay in Work.
- .3 Provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.

1.6 REJECTED WORK

- .1 Remove defective Work, whether result of poor workmanship, use of defective products or damage and whether incorporated in Work or not, which has been rejected by Departmental Representative as failing to conform to Contract Documents. Replace or re-execute in accordance with Contract Documents.
- .2 Make good other Contractor's work damaged by such removals or replacements promptly.
- .3 If in opinion of Departmental Representative it is not expedient to correct defective Work or Work not performed in accordance with Contract Documents, Departmental Representative may deduct from Contract Amount difference in value between Work performed and that called for by Contract Documents, amount of which shall be determined by Departmental Representative.

1.7 REPORTS

- .1 Submit 4 copies of inspection and test reports to Departmental Representative.
- .2 Provide copies to Subcontractor of work being inspected or tested, manufacturer or fabricator of material being inspected or tested.

1.8 TESTS AND MIX DESIGNS

- .1 Furnish test results and mix designs as may be requested.
- .2 The cost of tests and mix designs beyond those called for in Contract Documents or beyond those required by law of Place of Work shall be appraised by Departmental Representative and may be authorized as recoverable.

1.9 MILL TESTS

- .1 Submit mill test certificates as requested.

1.10 EQUIPMENT AND SYSTEMS

- .1 Submit testing, adjusting and balancing reports for building equipment systems.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.
-

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Temporary utilities.

1.2 RELATED SECTIONS

- .1 Section 01 52 00 - Construction Facilities.
- .2 Section 01 56 00 - Temporary Barriers and Enclosures.

1.3 REFERENCES

- .1 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 833-R-06-004, May 2007, Developing Your Stormwater Pollution Prevention Plan - A Guide for Construction Sites.

1.4 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

1.5 INSTALLATION AND REMOVAL

- .1 Provide temporary utilities controls in order to execute work expeditiously.
- .2 Remove from site all such work after use.

1.6 DEWATERING

- .1 Provide temporary drainage and pumping facilities to keep excavations and site free from standing water.

1.7 WATER SUPPLY

- .1 Provide continuous supply of potable water for construction use.
- .2 Departmental Representative will pay for utility charges at prevailing rates.

1.8 TEMPORARY POWER AND LIGHT

- .1 Provide and pay for temporary power during construction for temporary lighting and operating of power tools.
- .2 Temporary power for electric cranes and other equipment requiring in excess of above is responsibility of Contractor.
- .3 Provide and maintain temporary lighting throughout project. Ensure level of illumination on all floors and stairs is not less than 162 lx.

1.9 TEMPORARY COMMUNICATION FACILITIES

- .1 Provide and pay for temporary telephone, fax and data hook up, lines and equipment necessary for own use and use of Departmental Representative.

1.10 FIRE PROTECTION

- .1 Provide and maintain temporary fire protection equipment during performance of Work required by governing codes, regulations and bylaws.
- .2 Burning rubbish and construction waste materials is not permitted on site.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to requirements of authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Construction aids.
- .2 Office and sheds.
- .3 Parking.
- .4 Project identification.

1.2 REFERENCES

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-1.189-2000, Exterior Alkyd Primer for Wood.
 - .2 CAN/CGSB-1.59-97, Alkyd Exterior Gloss Enamel.
- .2 Canadian Standards Association (CSA International)
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.
 - .2 CSA 0121-08(R2013), Douglas Fir Plywood.
 - .3 CSA Z797-09(R2014), Code of practice for Access Scaffold.
 - .4 CAN/CSA-Z321-96(R2006), Signs and Symbols for the Occupational Environment, withdrawn but still available from CSA, CCOHS and Techstreet.
- .3 U.S. Environmental Protection Agency (EPA)/ Office of Water
 - .1 EPA 833-R-06-004, May 2007, Developing Your Stormwater Pollution Prevention Plan - A Guide for Construction Sites.

1.3 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.

1.4 INSTALLATION AND REMOVAL

- .1 Prepare site plan indicating proposed location and dimensions of area to be fenced and used by Contractor, number of trailers to be used, avenues of ingress/egress to fenced area and details of fence installation.
- .2 Identify areas which have to be gravelled to prevent tracking of mud.
- .3 Indicate use of supplemental or other staging area.
- .4 Provide construction facilities in order to execute work expeditiously.
- .5 Remove from site all such work after use.

1.5 HOISTING

- .1 Provide, operate and maintain hoists/cranes required for moving of workers, materials and equipment. Make financial arrangements with Subcontractors for use thereof.

- .2 Hoists/cranes shall be operated by qualified operator.
- .3 Provide notification in accordance with Section 01 35 13 – Special Project Procedures for Correctional Service Canada and Security Requirements prior to delivery of hoists/cranes to site.
- .4 Hoists and cranes shall be removed from site at the end of each work day.

1.6 SITE STORAGE/LOADING

- .1 Confine work and operations of employees to areas defined by Contract Documents. Do not unreasonably encumber premises with products.
- .2 Do not load or permit to load any part of Work with a weight or force that will endanger the Work.

1.7 CONSTRUCTION PARKING

- .1 Parking will be permitted on site in designated areas outside perimeter walls, and as directed by the Director, in accordance with Section 01 35 13.

1.8 SECURITY

- .1 Pay for responsible security personnel to guard site and contents of site after working hours and during holidays.
- .2 Coordinate with Section 01 35 13.

1.9 OFFICES

- .1 Provide office heated to 22°C, lighted 750 lx and ventilated, of sufficient size to accommodate site meetings and furnished with drawing laydown table.
- .2 Provide a clearly marked and fully stocked first-aid case in a readily available location.
- .3 Subcontractors may provide their own offices as necessary. Direct location of these offices.

1.10 STORAGE

- .1 Provide and maintain, in a clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
- .2 Locate materials not required to be stored in weatherproof sheds on site in a manner to cause least interference with work activities.

1.11 SANITARY FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take such precautions as required by local health authorities. Keep area and premises in sanitary condition.

1.12 CONSTRUCTION SIGNAGE

- .1 No other signs or advertisements, other than warning signs, are permitted on site.

- .2 Signs and notices for safety and instruction shall be in both official languages. Graphic symbols shall conform to CAN/CSA-Z321.
- .3 Maintain approved signs and notices in good condition for duration of project, and dispose of off site on completion of project or earlier if directed by Departmental Representative.

1.13 CLEAN-UP

- .1 Remove construction debris, waste materials, packaging material from work site daily.
- .2 Clean dirt or mud tracked onto paved or surfaced roadways.
- .3 Store materials resulting from demolition activities that are salvageable.
- .4 Stack stored new or salvaged material.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Barriers.
- .2 Fire Routes.

1.2 RELATED SECTIONS

- .1 Section 01 51 00 - Temporary Utilities.
- .2 Section 01 52 00 - Construction Facilities.

1.3 REFERENCES

- .1 Canadian General Standards Board (CGSB):
 - .1 CAN/CGSB-1.189-2000, Exterior Alkyd Primer for Wood.
 - .2 CAN/CGSB-1.59-97, Alkyd Exterior Gloss Enamel.
- .2 Canadian Standards Association (CSA):
 - .1 CSA O121-08(R2013), Douglas Fir Plywood.

1.4 INSTALLATION AND REMOVAL

- .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.

1.5 WEATHER ENCLOSURES

- .1 Provide weather tight closures to unfinished door and window openings, tops of shafts and other openings in floors and roofs.
- .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work for temporary heat.
- .3 Design enclosures to withstand wind pressure and snow loading.

1.6 FIRE ROUTES

- .1 Maintain access to property including overhead clearances for use by emergency response vehicles.

1.7 PROTECTION OF BUILDING FINISHES

- .1 Provide protection for finished and partially finished building finishes and equipment during performance of Work.
 - .2 Provide necessary screens, covers, and hoardings.
 - .3 Confirm with Departmental Representative locations and installation schedule 3 days prior to installation.
 - .4 Be responsible for damage incurred due to lack of or improper protection.
-

Part 2 PRODUCTS

2.1 NOT USED

.1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Product quality, availability, storage, handling, protection, and transportation.
- .2 Manufacturer's instructions.
- .3 Quality of Work, coordination and fastenings.
- .4 Existing facilities.

1.2 RELATED SECTIONS

- .1 Section 01 45 00 - Quality Control.

1.3 REFERENCES

- .1 Within text of specifications, reference may be made to reference standards.
- .2 Conform to these standards, in whole or in part as specifically requested in specifications.
- .3 If there is question as to whether any product or system is in conformance with applicable standards, Departmental Representative reserves right to have such products or systems tested to prove or disprove conformance.
- .4 The cost for such testing will be borne by Departmental Representative in event of conformance with Contract Documents or by Contractor in event of non-conformance.
- .5 Conform to latest date of issue of referenced standards in effect on date of submission of Bids, except where specific date or issue is specifically noted.
- .6 OPSS Ontario Provincial Standard Specifications and OPSD Ontario Provincial Standard Drawings quoted in these specifications are available online at <http://www.raqsa.mto.gov.on.ca/techpubs/ops.nsf/OPSHomepage>.

1.4 QUALITY

- .1 Products, materials, equipment and articles (referred to as products throughout specifications) incorporated in Work shall be new, not damaged or defective, and of best quality (compatible with specifications) for purpose intended. If requested, furnish evidence as to type, source and quality of Products provided.
 - .2 Defective products, whenever identified prior to completion of Work, will be rejected, regardless of previous inspections. Inspection does not relieve responsibility, but is precaution against oversight or error. Remove and replace defective products at own expense and be responsible for delays and expenses caused by rejection.
 - .3 Should any dispute arise as to quality or fitness of products, decision rests strictly with Departmental Representative based upon requirements of Contract Documents.
 - .4 Unless otherwise indicated in specifications, maintain uniformity of manufacture for any particular or like item throughout building.
-

- .5 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.5 AVAILABILITY

- .1 Immediately upon signing Contract, review product delivery requirements and anticipate foreseeable supply delays for any items. If delays in supply of products are foreseeable, notify Departmental Representative of such, in order that substitutions or other remedial action may be authorized in ample time to prevent delay in performance of Work.
- .2 In event of failure to notify Departmental Representative at commencement of Work and should it subsequently appear that Work may be delayed for such reason, Departmental Representative reserves right to substitute more readily available products of similar character, at no increase in Contract Amount or Contract Time.

1.6 METRIC SIZED MATERIALS

- .1 SI metric units of measurement are used exclusively on the drawings and in the specifications for this project.
- .2 The Contractor is required to provide metric products in the sizes called for in the Contract Documents except where a valid claim can be made that a particular product is not available on the Canadian market.
- .3 Claims for exemptions from use of metric sized products shall be in writing and fully substantiated with supportive documentation. Promptly submit application to Departmental Representative for consideration and ruling. Non-metric sized products may not be used unless Contractor's application has been approved in writing by the Departmental Representative.
- .4 Difficulties caused by the Contractor's lack of planning and effort to obtain modular metric sized products which are available on the Canadian market will not be considered sufficient reasons for claiming that they cannot be provided.
- .5 Claims for additional costs due to provision of specified modular metric sized products will not be considered.

1.7 STORAGE, HANDLING AND PROTECTION

- .1 Handle and store products in manner to prevent damage, adulteration, deterioration and soiling and in accordance with manufacturer's instructions when applicable.
 - .2 Store packaged or bundled products in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work.
 - .3 Store products subject to damage from weather in weatherproof enclosures.
 - .4 Store cementitious products clear of earth or concrete floors, and away from walls.
 - .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
 - .6 Store sheet materials and lumber on flat, solid supports and keep clear of ground. Slope to shed moisture.
-

- .7 Store and mix paints in heated and ventilated room. Remove oily rags and other combustible debris from site daily. Take every precaution necessary to prevent spontaneous combustion.
- .8 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.
- .9 Touch-up damaged factory finished surfaces to Departmental Representative's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

1.8 TRANSPORTATION

- .1 Pay costs of transportation of products required in performance of Work.

1.9 MANUFACTURER'S INSTRUCTIONS

- .1 Unless otherwise indicated in specifications, install or erect products in accordance with manufacturer's instructions. Do not rely on labels or enclosures provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Departmental Representative in writing, of conflicts between specifications and manufacturer's instructions, so that Departmental Representative may establish course of action.
- .3 Improper installation or erection of products, due to failure in complying with these requirements, authorizes Departmental Representative to require removal and re-installation at no increase in Contract [Amount] [Price] or Contract Time.

1.10 QUALITY OF WORK

- .1 Ensure Quality of Work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed. Immediately notify Departmental Representative if required Work is such as to make it impractical to produce required results.
- .2 Do not employ anyone unskilled in their required duties. Departmental Representative reserves right to require dismissal from site, workers deemed incompetent or careless.
- .3 Decisions as to standard or fitness of Quality of Work in cases of dispute rest solely with Departmental Representative, whose decision is final.

1.11 CO-ORDINATION

- .1 Ensure cooperation of workers in laying out Work. Maintain efficient and continuous supervision.
- .2 Be responsible for coordination and placement of openings, sleeves and accessories.

1.12 CONCEALMENT

- .1 In finished areas, conceal pipes, ducts and wiring in floors, walls and ceilings, except where indicated otherwise.
 - .2 Before installation, inform Departmental Representative if there is interference. Install as directed by Departmental Representative.
-

1.13 REMEDIAL WORK

- .1 Perform remedial work required to repair or replace parts or portions of Work identified as defective or unacceptable. Coordinate adjacent affected Work as required.
- .2 Perform remedial work by specialists familiar with materials affected. Perform in a manner to neither damage nor put at risk any portion of Work.

1.14 FASTENINGS

- .1 Provide metal fastenings and accessories in same texture, colour and finish as adjacent materials, unless indicated otherwise.
- .2 Prevent electrolytic action between dissimilar metals and materials.
- .3 Use non-corrosive hot dip galvanized steel fasteners and anchors for securing exterior work, unless stainless steel or other material is specifically requested in affected specification Section.
- .4 Space anchors within individual load limit or shear capacity and ensure they provide positive permanent anchorage. Wood, or any other organic material plugs are not acceptable.
- .5 Keep exposed fastenings to a minimum, space evenly and install neatly.
- .6 Fastenings which cause spalling or cracking of material to which anchorage is made are not acceptable.

1.15 FASTENINGS - EQUIPMENT

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified. Use No.304 stainless steel for exterior areas.
- .3 Bolts may not project more than one diameter beyond nuts.
- .4 Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur. Use resilient washers with stainless steel.

1.16 PROTECTION OF WORK IN PROGRESS

- .1 Prevent overloading of any part of building. Do not cut, drill or sleeve any load bearing structural member, unless specifically indicated without written approval of Departmental Representative.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.
-

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Field engineering survey services to measure and stake site.
- .2 Recording of subsurface conditions found.

1.2 REFERENCES

- .1 Departmental Representative's identification of existing survey control points and property limits.

1.3 QUALIFICATIONS OF SURVEYOR

- .1 Qualified registered land surveyor, licensed to practice in Place of Work, acceptable to Departmental Representative.

1.4 SURVEY REFERENCE POINTS

- .1 Existing base horizontal and vertical control points are designated on drawings.
- .2 Locate, confirm and protect control points prior to starting site work. Preserve permanent reference points during construction.
- .3 Make no changes or relocations without prior written notice to Departmental Representative.
- .4 Report to Departmental Representative when reference point is lost or destroyed, or requires relocation because of necessary changes in grades or locations.
- .5 Require surveyor to replace control points in accordance with original survey control.

1.5 SURVEY REQUIREMENTS

- .1 Establish two permanent bench marks on site, referenced to established bench marks by survey control points. Record locations, with horizontal and vertical data in Project Record Documents.
- .2 Establish lines and levels, locate and lay out, by instrumentation.
- .3 Stake for grading, fill and topsoil placement and landscaping features.
- .4 Stake batter boards for foundations.

1.6 EXISTING SERVICES

- .1 Before commencing work, establish location and extent of service lines in area of Work and notify Departmental Representative of findings.
 - .2 Remove abandoned service lines within 2 m of structures. Cap or otherwise seal lines at cut-off points as directed by Departmental Representative.
-

1.7 LOCATION OF EQUIPMENT AND FIXTURES

- .1 Location of equipment, fixtures and outlets indicated or specified are to be considered as approximate.
- .2 Locate equipment, fixtures and distribution systems to provide minimum interference and maximum usable space and in accordance with manufacturer's recommendations for safety, access and maintenance.
- .3 Inform Departmental Representative of impending installation and obtain approval for actual location.
- .4 Submit field drawings to indicate relative position of various services and equipment when required by Departmental Representative.

1.8 RECORDS

- .1 Maintain a complete, accurate log of control and survey work as it progresses.
- .2 On completion of foundations and major site improvements, prepare a certified survey showing dimensions, locations, angles and elevations of Work.
- .3 Record locations of maintained, re-routed and abandoned service lines.

1.9 SUBMITTALS

- .1 Submit name and address of Surveyor to Departmental Representative.
- .2 On request of Departmental Representative, submit documentation to verify accuracy of field engineering work.
- .3 Submit certificate signed by surveyor certifying those elevations and locations of completed Work that conform with Contract Documents.

1.10 SUBSURFACE CONDITIONS

- .1 Promptly notify Departmental Representative in writing if subsurface conditions at Place of Work differ materially from those indicated in Contract Documents, or a reasonable assumption of probable conditions based thereon.
- .2 After prompt investigation, should Departmental Representative determine that conditions do differ materially, instructions will be issued for changes in Work as provided in Changes and Change Orders.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.
-

END OF SECTION

Part 1 GENERAL

1.1 SUBMITTALS

- .1 Submittals: in accordance with Section 01 33 00.
- .2 Submit written request in advance of cutting or alteration which affects:
 - .1 Structural integrity of elements of project.
 - .2 Integrity of weather-exposed or moisture-resistant elements.
 - .3 Efficiency, maintenance, or safety of operational elements.
 - .4 Visual qualities of sight-exposed elements.
- .3 Include in request:
 - .1 Identification of project.
 - .2 Location and description of affected Work.
 - .3 Statement on necessity for cutting or alteration.
 - .4 Description of proposed Work, and products to be used.
 - .5 Alternatives to cutting and patching.
 - .6 Written permission of affected separate contractor.
 - .7 Date and time work will be executed.

1.2 MATERIALS

- .1 Required for original installation.
- .2 Change in Materials: Submit request for substitution in accordance with Section 01 33 00.

1.3 PREPARATION

- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
- .2 After uncovering, inspect conditions affecting performance of Work.
- .3 Beginning of cutting or patching means acceptance of existing conditions.
- .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water.

1.4 EXECUTION

- .1 Execute cutting, fitting, and patching including excavation and fill to complete Work.
 - .2 Fit several parts together, to integrate with other Work.
 - .3 Uncover Work to install ill-timed Work.
 - .4 Remove and replace defective and non-conforming Work.
-

- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .9 Restore work with new products in accordance with requirements of Contract Documents.
- .10 Submit proposed materials, finishes and installation method for patching to Departmental Representative for approval, prior to patching.
- .11 Refinish surfaces to match adjacent finishes: Refinish continuous surfaces to nearest intersection. Refinish assemblies by refinishing entire unit.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse, and recycling in accordance with Section 01 74 20.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Progressive cleaning.
- .2 Final cleaning.

1.2 PROJECT CLEANLINESS

- .1 Maintain Work in tidy condition, free from accumulation of waste products and debris, other than that caused by Departmental Representative or other Contractors.
- .2 Remove waste materials from site at regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
- .3 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .4 Provide on-site containers for collection of waste materials and debris.
- .5 Provide and use clearly marked separate bins for recycling. Refer to Section 01 74 20.
- .6 Remove waste material and debris from site at end of each working day.
- .7 Store volatile waste in covered metal containers, and remove from premises at end of each working day.
- .8 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.
- .9 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.

1.3 FINAL CLEANING

- .1 When Work is Substantially Performed, remove surplus products, tools, construction machinery and equipment not required for performance of remaining Work.
 - .2 Remove waste products and debris other than that caused by others, and leave Work clean and suitable for occupancy.
 - .3 Prior to final review, remove surplus products, tools, construction machinery and equipment.
 - .4 Remove waste products and debris other than that caused by Departmental Representative or other Contractors.
 - .5 Remove waste materials from site at regularly scheduled times or dispose of as directed by Departmental Representative. Do not burn waste materials on site.
 - .6 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
 - .7 Clean and polish glass, hardware, stainless steel, baked enamel, and mechanical and electrical fixtures. Replace broken, scratched or disfigured glass.
 - .8 Clean lighting reflectors, lenses, and other lighting surfaces.
-

- .9 Inspect finishes, fitments and equipment and ensure specified workmanship and operation.
- .10 Broom clean and wash exterior walks, steps and surfaces; rake clean other surfaces of grounds.
- .11 Remove dirt and other disfiguration from exterior surfaces.
- .12 Sweep and wash clean paved areas.
- .13 Clean equipment and fixtures to a sanitary condition; clean or replace filters of mechanical equipment.
- .14 Remove snow and ice from access to building.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 INSPECTION AND DECLARATION

- .1 Contractor's Inspection: Contractor and all Subcontractors shall conduct an inspection of Work, identify deficiencies and defects, and repair as required to conform to Contract Documents.
 - .1 Notify Departmental Representative in writing of satisfactory completion of Contractor's Inspection and that corrections have been made.
 - .2 Request Departmental Representative's Inspection.
- .2 Departmental Representative's Inspection: Departmental Representative and Contractor will perform inspection of Work to identify obvious defects or deficiencies. Contractor to correct Work accordingly.
- .3 Completion: submit written certificate that following have been performed:
 - .1 Work has been completed and inspected for compliance with Contract Documents.
 - .2 Defects have been corrected and deficiencies have been completed.
 - .3 Equipment has been tested and adjusted and is fully operational.
 - .4 Operation of equipment has been demonstrated to Departmental Representative's personnel.
 - .5 Work is complete and ready for final inspection.
- .4 Final Inspection: when items noted above are completed, request final inspection of Work by Departmental Representative and Contractor. If Work is deemed incomplete by Departmental Representative, complete outstanding items and request reinspection.

1.2 CLEANING

- .1 In accordance with Section 01 74 11.
- .2 Remove waste and surplus materials, rubbish and construction facilities from the site in accordance with Section 01 74 20.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 As-built, samples, and specifications.
- .2 Equipment and systems.
- .3 Product data, materials and finishes, and related information.
- .4 Operation and maintenance data.
- .5 Spare parts, special tools and maintenance materials.
- .6 Warranties and bonds.
- .7 Final site survey.

1.2 RELATED SECTIONS

- .1 Section 01 71 00 – Examination and Preparation
- .2 Section 01 79 00 - Demonstration and Training.

1.3 SUBMISSION

- .1 Prepare instructions and data using personnel experienced in maintenance and operation of described products.
- .2 Copy will be returned after final inspection, with Departmental Representative's comments.
- .3 Revise content of documents as required prior to final submittal.
- .4 Two weeks prior to Substantial Performance of the Work, submit to the Departmental Representative, two final copies of maintenance manuals and commissioning documentation in English.
- .5 Ensure spare parts, maintenance materials and special tools provided are new, undamaged or defective, and of same quality and manufacture as products provided in Work.
- .6 If requested, furnish evidence as to type, source and quality of products provided.
- .7 Defective products will be rejected, regardless of previous inspections. Replace products at own expense.
- .8 Pay costs of transportation.

1.4 FORMAT

- .1 Organize data in the form of an instructional manual.
 - .2 Binders: vinyl, hard covered, 3 'D' ring, loose leaf 219 x 279 mm with spine and face pockets.
 - .3 When multiple binders are used, correlate data into related consistent groupings. Identify contents of each binder on spine.
-

- .4 Cover: Identify each binder with type or printed title 'Project Record Documents'; list title of project and identify subject matter of contents.
- .5 Arrange content by systems under Section numbers and sequence of Table of Contents.
- .6 Provide tabbed fly leaf for each separate product and system, with typed description of product and major component parts of equipment.
- .7 Text: Manufacturer's printed data, or typewritten data.
- .8 Drawings: provide with reinforced punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- .9 Provide 1:1 scaled CAD files in dwg format.

1.5 CONTENTS - EACH VOLUME

- .1 Table of Contents: provide title of project;
 - .1 Date of submission; names,
 - .2 Addresses, and telephone numbers of Contractor with name of responsible parties;
 - .3 Schedule of products and systems, indexed to content of volume.
- .2 For each product or system:
 - .1 List names, addresses and telephone numbers of subcontractors and suppliers, including local source of supplies and replacement parts.
- .3 Product Data: mark each sheet to clearly identify specific products and component parts, and data applicable to installation; delete inapplicable information.
- .4 Drawings: supplement product data to illustrate relations of component parts of equipment and systems, to show control and flow diagrams.
- .5 Typewritten Text: as required to supplement product data. Provide logical sequence of instructions for each procedure, incorporating manufacturer's instructions specified in Section 01 45 00.
- .6 Training: Refer to Section 01 79 00.

1.6 AS-BUILTS AND SAMPLES

- .1 In addition to requirements in General Conditions, maintain at the site for Departmental Representative one record copy of:
 - .1 Contract Drawings.
 - .2 Specifications.
 - .3 Amendments and addenda.
 - .4 Change Orders and other modifications to the Contract.
 - .5 Reviewed shop drawings, product data, and samples.
 - .6 Field test records.
 - .7 Inspection certificates.
 - .8 Manufacturer's certificates.
- .2 Store record documents and samples in field office apart from documents used for construction. Provide files, racks, and secure storage.

- .3 Label record documents and file in accordance with Section number listings in List of Contents of this Project Manual. Label each document "PROJECT RECORD" in neat, large, printed letters.
- .4 Maintain record documents in clean, dry and legible condition. Do not use record documents for construction purposes.
- .5 Keep record documents and samples available for inspection by Departmental Representative.
- .6 Turn one set, paper copy and electronic copy, of AS-BUILT drawings and specifications over to Departmental Representative on completion of work. Submit files on USB compatible with PWGSC encryption requirements or through email or alternate electronic file sharing service such as ftp, as directed by Departmental Representative.
- .7 If project is completed without significant deviations from Contract drawings and specifications submit to Departmental Representative one set of drawings and specifications marked "AS-BUILT".

1.7 RECORDING ACTUAL SITE CONDITIONS

- .1 Record information on set of black line opaque drawings, and in copy of Project Manual, provided by Departmental Representative.
- .2 Provide felt tip marking pens, maintaining separate colours for each major system, for recording information.
- .3 Record information concurrently with construction progress. Do not conceal Work until required information is recorded.
- .4 Contract Drawings and shop drawings: legibly mark each item to record actual construction, including:
 - .1 Measured depths of elements of foundation in relation to finish first floor datum.
 - .2 Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
 - .3 Measured locations of internal utilities and appurtenances, referenced to visible and accessible features of construction.
 - .4 Field changes of dimension and detail.
 - .5 Changes made by change orders.
 - .6 Details not on original Contract Drawings.
 - .7 References to related shop drawings and modifications.
- .5 Specifications: legibly mark each item to record actual construction, including:
 - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly optional items and substitute items.
 - .2 Changes made by Amendments and change orders.

- .6 Other Documents: maintain inspection certifications, required by individual specifications sections.

1.8 FINAL SURVEY

- .1 Submit final site survey certificate in accordance with Section 01 71 00 certifying that elevations and locations of completed Work are in conformance, or non-conformance with Contract Documents.

1.9 EQUIPMENT AND SYSTEMS

- .1 Each Item of Equipment and Each System: include description of unit or system, and component parts. Give function, normal operation characteristics, and limiting conditions. Include performance curves, with engineering data and tests, and complete nomenclature and commercial number of replaceable parts.
- .2 Operating Procedures: include start-up, break-in, and routine normal operating instructions and sequences. Include regulation, control, stopping, shut-down, and emergency instructions. Include summer, winter, and any special operating instructions.
- .3 Maintenance Requirements: include routine procedures and guide for trouble-shooting; disassembly, repair, and reassembly instructions; and alignment, adjusting, balancing, and checking instructions.
- .4 Include manufacturer's printed operation and maintenance instructions.
- .5 Provide original manufacturer's parts list, illustrations, assembly drawings, and diagrams required for maintenance.
- .6 Provide installed control diagrams by controls manufacturer.
- .7 Provide list of original manufacturer's spare parts, current prices, and recommended quantities to be maintained in storage.
- .8 Additional requirements: As specified in individual specification sections.

1.10 MATERIALS AND FINISHES

- .1 Building Products, Applied Materials, and Finishes: include product data, with catalogue number, size, composition, and colour and texture designations.
 - .2 Instructions for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
 - .3 Moisture-protection and Weather-exposed Products: include manufacturer's recommendations for cleaning agents and methods, precautions against detrimental agents and methods, and recommended schedule for cleaning and maintenance.
 - .4 Additional Requirements: as specified in individual specifications sections.
 - .5 Receive and catalogue all items. Submit inventory listing to Departmental Representative. Include approved listings in Maintenance Manual.
 - .6 Obtain receipt for delivered products and submit prior to final payment.
-

1.11 MAINTENANCE MATERIALS

- .1 Provide maintenance and extra materials, in quantities specified in individual specification sections.
- .2 Provide items of same manufacture and quality as items in Work.
- .3 Deliver to site; place and store.
- .4 Receive and catalogue all items. Submit inventory listing to Departmental Representative. Include approved listings in Maintenance Manual.
- .5 Obtain receipt for delivered products and submit prior to final payment.

1.12 SPECIAL TOOLS

- .1 Provide special tools, in quantities specified in individual specification section.
- .2 Provide items with tags identifying their associated function and equipment.
- .3 Deliver to site; place and store.
- .4 Receive and catalogue all items. Submit inventory listing to Departmental Representative. Include approved listings in Maintenance Manual.

1.13 STORAGE, HANDLING AND PROTECTION

- .1 Store spare parts, maintenance materials, and special tools in manner to prevent damage or deterioration.
- .2 Store in original and undamaged condition with manufacturer's seal and labels intact.
- .3 Store components subject to damage from weather in weatherproof enclosures.
- .4 Store paints and freezable materials in a heated and ventilated room.
- .5 Remove and replace damaged products at own expense and to satisfaction of Departmental Representative.

1.14 WARRANTIES AND BONDS

- .1 Separate each warranty or bond with index tab sheets keyed to Table of Contents listing.
 - .2 List subcontractor, supplier, and manufacturer, with name, address, and telephone number of responsible principal.
 - .3 Obtain warranties and bonds, executed in duplicate by subcontractors, suppliers, and manufacturers, within ten days after completion of the applicable item of work.
 - .4 Except for items put into use with Departmental Representative's permission, leave date of beginning of time of warranty until the Date of Certificate of Substantial Performance is determined.
 - .5 Verify that documents are in proper form, contain full information, and are notarized.
 - .6 Co-execute submittals when required.
 - .7 Retain warranties and bonds until time specified for submittal.
-

Part 2 PRODUCTS

2.1 NOT USED

.1 Not Used.

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Procedures for demonstration and instruction of equipment and systems to Departmental Representative's O&M personnel.
- .2 O&M personnel includes property facility manager, building operators, maintenance staff, security staff and technical specialists, as applicable.

1.2 DESCRIPTION

- .1 Demonstrate operation and maintenance of equipment and systems to Departmental Representative's personnel two weeks prior to date of final inspection.
- .2 Departmental Representative will provide list of personnel to receive instructions, and will coordinate their attendance at agreed-upon times.

1.3 QUALITY CONTROL

- .1 When specified in individual Sections, require manufacturer to provide authorized representative to demonstrate operation of equipment and systems, instruct Departmental Representative's personnel, and provide written report that demonstration and instructions have been completed.
- .2 Submit training schedule of time and date for demonstration and training of each item of equipment and each system in accordance with the training plan four weeks prior to designated dates, for Departmental Representative's approval.
- .3 Submit reports within one week after completion of demonstration, that demonstration and instructions have been satisfactorily completed.
- .4 Report shall give time and date of each demonstration and training, with list of persons present.

1.4 CONDITIONS FOR DEMONSTRATIONS

- .1 Provide copies of completed operation and maintenance manuals for use in demonstrations and instructions.

1.5 PREPARATION

- .1 Verify that conditions for demonstration and instructions comply with requirements.
- .2 Verify that designated O&M personnel are present.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.
-

Part 3 EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

Part 1 GENERAL

1.1 SITE CONDITIONS

- .1 Review "Designated Substance Report" and take precautions to protect environment.
- .2 If material resembling spray or trowel-applied asbestos or other designated substance be encountered, stop work, take preventative measures, and notify Departmental Representative immediately.
 - .1 Proceed only after receipt of written instructions have been received from Departmental Representative.
- .3 Notify Departmental Representative before disrupting [building] access or services.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not used.

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Inspect site with Departmental Representative and verify extent and location of items designated for removal, disposal, alternative disposal, recycling, salvage and items to remain.
- .2 Locate and protect utilities. Preserve active utilities traversing site in operating condition.
- .3 Notify and obtain approval of utility companies before starting demolition.
- .4 Disconnect, cap, plug or divert, as required, existing public utilities within the property where they interfere with the execution of the work, in conformity with the requirements of the authorities having jurisdiction. Mark the location of these and previously capped or plugged services on the site and indicate location (horizontal and vertical) on the record drawings. Support, shore up and maintain pipes and conduits encountered.
 - .1 Immediately notify Departmental Representative and utility company concerned in case of damage to any utility or service, designated to remain in place.
 - .2 Immediately notify the Departmental Representative should uncharted utility or service be encountered, and await instruction in writing regarding remedial action.

3.2 PROTECTION

- .1 Prevent movement, settlement, or damage to adjacent structures, utilities, landscaping features and building. Provide bracing and shoring required.
 - .2 Keep noise, dust, and inconvenience to occupants to minimum.
 - .3 Protect building systems, services and equipment.
-

- .4 Provide temporary dust screens, covers, railings, supports and other protection as required.

3.3 PREPARATION

- .1 Temporary Erosion and Sedimentation Control:
 - .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to: requirements of authorities having jurisdiction.
 - .2 Inspect, repair, and maintain erosion and sedimentation control measures during demolition.
 - .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal after completion of demolition work..
- .2 Protection of In-Place Conditions:
 - .1 Prevent movement, settlement, or damage to adjacent structures, utilities, and landscaping features to remain in place. Provide bracing and shoring required.
 - .2 Keep noise, dust, and inconvenience to occupants to minimum.
 - .3 Protect building systems, services and equipment.
 - .4 Provide temporary dust screens, covers, railings, supports and other protection as required.
 - .5 Do Work in accordance with Section 01 35 29.
- .3 Demolition/Removal:
 - .1 Remove items as indicated.
 - .2 Removal of Pavements, Curbs and Gutters:
 - .1 Square up adjacent surfaces to remain in place by saw cutting or other method approved by Departmental Representative.
 - .2 Protect adjacent joints and load transfer devices.
 - .3 Protect underlying and adjacent granular materials.
 - .3 Trim edges of partially demolished building elements to tolerances as defined by Departmental Representative to suit future use.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Refer to demolition drawings and specifications for items to be salvaged for reuse.
- .4 Waste Management: separate waste materials for reuse and recycling.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 02 41 99 – Construction Demolition.
- .2 Section 03 20 00 - Concrete Reinforcing.
- .3 Section 03 30 00 - Cast-In-Place Concrete.
- .4 Section 07 92 10 - Joint Sealants.

1.2 REFERENCES

- .1 Canadian Standards Association (CSA)
 - .1 CSA A23.1-14/A23.2-14, Concrete materials and methods of concrete construction/Test methods and standard practices for concrete.
 - .2 CSA O86-09, Consolidation-Engineering Design in Wood (Limit States Design).
 - .3 CSA O121-08(R2013), Douglas Fir Plywood.
 - .4 CSA O151-09, Canadian Softwood Plywood.
 - .5 CAN3-O188.0-M78, Standard Test Methods for Mat-Formed Wood Particleboards and Waferboard.
 - .6 CSA S269.1-1975(R2003), Falsework for Construction Purposes.
 - .7 CAN/CSA-S269.3-M92(R2008), Concrete Formwork.

1.3 SHOP DRAWINGS

- .1 Submit shop drawings for formwork and falsework in accordance with Section 01 33 00.
- .2 Indicate method and schedule of construction, shoring, stripping and re-shoring procedures, materials, arrangement of joints, special architectural exposed finishes, ties, liners, and locations of temporary embedded parts. Comply with CSA S269.1, for falsework drawings. Comply with CAN/CSA-S269.3, for formwork drawings.
- .3 Indicate formwork design data, such as permissible rate of concrete placement, and temperature of concrete, in forms.
- .4 Indicate sequence of erection and removal of formwork/falsework as directed by Departmental Representative.
- .5 Each shop drawing submission shall bear stamp and signature of qualified professional engineer registered or licensed in Province of Ontario, Canada.

1.4 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate and recycle waste materials in accordance with Section 01 74 20 and the Waste Reduction Workplan.
 - .2 Place materials defined as hazardous or toxic waste in designated containers.
 - .3 Ensure emptied containers are sealed and stored safely for disposal away from children.
-

- .4 Use sealers, form release and stripping agents that are non-toxic, biodegradable and have zero or low VOC's.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Formwork materials:
 - .1 For concrete without special architectural features, use wood and wood product formwork materials to CSA O121.
 - .2 For concrete with special architectural features, use formwork materials to CSA A23.1/A23.2.
- .2 Pan forms: Removable steel as indicated.
- .3 Form ties:
 - .1 For concrete not designated 'Architectural', use removable or snap-off metal ties, fixed or adjustable length, free of devices leaving holes larger than 25 mm dia. in concrete surface.
 - .2 For Architectural concrete, use snap ties complete with plastic cones and light grey concrete plugs.
- .4 Form liner:
 - .1 Plywood: medium density overlay Douglas Fir to CSA O121 square edge, urea formaldehyde free.
- .5 Form release agent: non-toxic, low VOC.
- .6 Form stripping agent: colourless mineral oil, non-toxic, low VOC, free of kerosene, with viscosity between 15 to 24 mm²/s at 40°C, flashpoint minimum 150°C, open cup.
- .7 Falsework materials: to CSA S269.1.
- .8 Sealant: to Section 07 92 00.

Part 3 EXECUTION

3.1 FABRICATION AND ERECTION

- .1 Verify lines, levels and centres before proceeding with formwork/falsework and ensure dimensions agree with drawings.
 - .2 Fabricate and erect falsework in accordance with CSA S269.1 and COFI Exterior Plywood for Concrete Formwork.
 - .3 Refer to architectural drawings for concrete members requiring architectural exposed finishes.
 - .4 Fabricate and erect formwork in accordance with CAN/CSA-S269.3 to produce finished concrete conforming to shape, dimensions, locations and levels indicated within tolerances required by CSA A23.1/A23.2.
 - .5 Align form joints and make watertight. Keep form joints to minimum.
-

- .6 Use 25 mm chamfer strips on external corners and/or 25 mm fillets at interior corners, joints, unless specified otherwise.
- .7 Form chases, slots, openings, drips, recesses, expansion and control joints as indicated.
- .8 Construct forms for architectural concrete, and place ties as indicated and/or as directed. Joint pattern not necessarily based on using standard size panels or maximum permissible spacing of ties.
- .9 Build in anchors, sleeves, and other inserts required to accommodate Work specified in other sections. Assure that all anchors and inserts will not protrude beyond surfaces designated to receive applied finishes, including painting.
- .10 Clean formwork in accordance with CSA A23.1/ A23.2, before placing concrete.

3.2 REMOVAL AND RESHORING

- .1 Leave formwork in place for following minimum periods of time after placing concrete.
 - .1 2 days for walls and sides of beams.
 - .2 2 days for columns.
 - .3 5 days for beam soffits, slabs, decks and other structural members, or 2 days when replaced immediately with adequate shoring to standard specified for falsework.
 - .4 2 days for footings and abutments.
- .2 Remove formwork when concrete has reached 75% of its design strength or minimum period noted above, whichever comes later, and replace immediately with adequate reshoring.
- .3 Provide all necessary reshoring of members where early removal of forms may be required or where members may be subjected to additional loads during construction as required.
- .4 Space reshoring in each principal direction at not more than 3000 mm apart.
- .5 Re-use formwork and falsework subject to requirements of CSA A23.1/A23.2.

END OF SECTION

Part 1 GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 03 30 00 - Cast-In-Place Concrete
- .2 Section 03 35 00 - Concrete Finishing.

1.2 REFERENCES

- .1 American Concrete Institute (ACI)
 - .1 ACI SP-66-04, ACI Detailing Manual 2004.
- .2 ASTM International
 - .1 ASTM A1064/A1064M-13, Standard Specification for Carbon-Steel Wire and Welded Wire Reinforcement, Plain and Deformed, for Concrete.
 - .2 ASTM A1060/A1060M-14, Standard Specification for Zinc-Coated (Galvanized) Steel Welded Wire Reinforcement, Plain and Deformed, for Concrete.
- .3 CSA International
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.
 - .2 CSA A23.3-14, Design of Concrete Structures.
 - .3 CSA G30.18-09, Carbon Steel Bars for Concrete Reinforcement.
 - .4 CSA G40.20-13/G40.21-13, General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel.
 - .5 CSA W186-M1990 (R2012), Welding of Reinforcing Bars in Reinforced Concrete Construction.
- .4 Reinforcing Steel Institute of Canada (RSIC)
 - .1 RSIC-2004, Reinforcing Steel Manual of Standard Practice.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Prepare reinforcement drawings in accordance with RSIC Manual of Standard Practice.
- .2 Shop Drawings:
 - .1 Submit drawings stamped and signed by Professional Engineer registered or licensed in Province of Ontario, Canada.
 - .1 Indicate placing of reinforcement and:
 - .1 Bar bending details.
 - .2 Lists.
 - .3 Quantities of reinforcement.
 - .4 Sizes, spacings, locations of reinforcement and mechanical splices if approved by Departmental Representative, with identifying code marks to permit correct placement without reference to structural drawings.

- .2 Detail lap lengths and bar development lengths to CSA A23.3, unless otherwise indicated.

1.4 QUALITY ASSURANCE

- .1 Submit in accordance with Section 01 45 00 and as described in PART 2 - SOURCE QUALITY CONTROL.
 - .1 Mill Test Report: provide Departmental Representative with certified copy of mill test report of reinforcing steel, minimum 4 weeks prior to beginning reinforcing work.
 - .2 Submit in writing to Departmental Representative proposed source of reinforcement material to be supplied.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Replace defective or damaged materials with new.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Substitute different size bars only if permitted in writing by Departmental Representative.
 - .2 Reinforcing steel: billet steel, grade 400, deformed bars to CSA G30.18, unless indicated otherwise, minimum 30% recycled content.
 - .3 Reinforcing steel: weldable low alloy steel deformed bars to CSA G30.18, minimum 30% recycled content.
 - .4 Welded steel wire and deformed steel wire reinforcement: to ASTM A1064/A1064M; and zinc-coated (galvanized) steel welded wire and deformed steel welded wire reinforcement: to ASTM A1060/A1060M. Minimum 30% recycled content for all steel wire reinforcement.
 - .1 Provide in flat sheets only and adequately chair into position to obtain the specified concrete cover. Do not lay reinforcing sheets down and hook into position after concrete has been poured.
 - .5 Chairs, bolsters, bar supports, spacers: to CSA A23.1/A23.2.
 - .6 Plain round bars: to CSA G40.20/G40.21.
-

2.2 FABRICATION

- .1 Fabricate reinforcing steel in accordance with CSA A23.1/A23.2 and Reinforcing Steel Manual of Standard Practice by the Reinforcing Steel Institute of Canada.
- .2 Obtain Departmental Representative's written approval for locations of reinforcement splices other than those shown on placing drawings.
- .3 Upon approval of Departmental Representative, weld reinforcement in accordance with CSA W186.
- .4 Ship bundles of bar reinforcement, clearly identified in accordance with bar bending details and lists.

2.3 SOURCE QUALITY CONTROL

- .1 Provide Departmental Representative with certified copy of mill test report of reinforcing steel, showing physical and chemical analysis, minimum 4 weeks prior to beginning reinforcing work.
- .2 Inform Departmental Representative of proposed source of material to be supplied.

Part 3 EXECUTION

3.1 FIELD BENDING

- .1 Do not field bend or field weld reinforcement except where indicated or authorized by Departmental Representative.
- .2 When field bending is authorized, bend without heat, applying slow and steady pressure.
- .3 Replace bars, which develop cracks or splits.

3.2 PLACING REINFORCEMENT

- .1 Place reinforcing steel in accordance with CSA A23.1/A23.2.
- .2 Use plain round bars as slip dowels in concrete.
 - .1 Paint portion of dowel intended to move within hardened.
 - .2 When paint is dry, apply thick even film of mineral lubricating grease.
- .3 Prior to placing concrete, obtain Departmental Representative's approval of reinforcing material and placement.
- .4 Ensure cover to reinforcement is maintained during concrete pour.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 03 10 00 - Concrete Forming and Accessories
- .2 Section 03 20 00 - Concrete Reinforcing
- .3 Section 03 35 00 - Concrete Finishing.

1.2 MEASUREMENT PROCEDURES

- .1 Cast-in-place concrete will not be measured but will be paid as a fixed price item.

1.3 REFERENCES

- .1 ASTM International
 - .1 ASTM A1064/A1064M-13, Standard Specification for Carbon –Steel Wire and Welded Wire Reinforcement, Plain and Deformed for Concrete.
 - .2 ASTM A1060/A1060M-14, Standard Specification for Zinc-Coated (Galvanized) Steel Welded Wire Reinforcement, Plain and Deformed, for Concrete.
 - .3 ASTM D1751-04(2013)E1, Standard Specification for Preformed Expansion Joint Filler for Concrete Paving and Structural Construction (Non extruding and Resilient Bituminous Types).
- .2 CSA International
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.
 - .2 CSA A283-06(R2011), Qualification Code for Concrete Testing Laboratories.
 - .3 CSA A3000-13, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).

1.4 ADMINISTRATIVE REQUIREMENTS

- .1 Pre-installation Meetings: in accordance with Section 01 31 19, convene pre-installation meeting one week prior to beginning concrete works.
 - .1 Ensure key personnel, site supervisor, Departmental Representative attend.
 - .2 Verify project requirements.

1.5 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
 - .2 Shop Drawings:
 - .1 Submit placing drawings prepared in accordance with plans to clearly show size, shape, location and necessary details of reinforcing.
 - .2 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.
-

- .3 At least 4 weeks prior to beginning Work, inform Departmental Representative of source of fly ash.
 - .1 Do not change source of fly ash without written approval of Departmental Representative.
- .4 At least 4 weeks prior to beginning Work, submit to Departmental Representative samples of following materials proposed for use: curing compound, joint filler, and waterstops.
- .5 Provide testing and inspection results and reports for review by Departmental Representative and do not proceed without written approval when deviations from mix design or parameters are found.
- .6 Concrete hauling time: provide for review by Departmental Representative deviations exceeding maximum allowable time of 120 minutes for concrete to be delivered to site of Work and discharged after batching.

1.6 QUALITY ASSURANCE

- .1 Provide to Departmental Representative, 4 weeks minimum prior to starting concrete work, valid and recognized certificate from plant delivering concrete.
 - .1 Quality Control Plan: provide written report to Departmental Representative verifying compliance that concrete in place meets performance requirements.

1.7 DELIVERY, STORAGE AND HANDLING

- .1 Delivery and Acceptance Requirements:
 - .1 Concrete hauling time: deliver to site of Work and discharged within 120 minutes maximum after batching.
 - .1 Do not modify maximum time limit without receipt of prior written agreement from Departmental Representative and concrete producer as described in CSA A23.1/A23.2.
 - .2 Deviations to be submitted for review by the Departmental Representative.
- .2 Concrete delivery: ensure continuous concrete delivery from plant meets CSA A23.1/A23.2.
- .3 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding, and packaging materials in accordance with Section 01 74 20.

Part 2 PRODUCTS

2.1 DESIGN CRITERIA

- .1 Alternative 1 - Performance: to CSA A23.1/A23.2, and as described in MIXES of PART 2 - PRODUCTS.

2.2 PERFORMANCE CRITERIA

- .1 Quality Control Plan: ensure concrete supplier meets performance criteria of concrete as established by Departmental Representative and provide verification of compliance as described in PART 1 - QUALITY ASSURANCE.

2.3 MATERIALS

- .1 Cement: to CAN/CSA-A3001, Type GU.
 - .1 Recycled content: in accordance with Section 01 35 21.
 - .2 Reduction in cement from Base Mix to Actual Supplementary Cementing Materials (SCMs) Mix, as percentage.
- .2 Blended hydraulic cement: Type GUB to CAN/CSA-A3001.
- .3 Supplementary cementing materials: with minimum 20% Type F fly ash replacement, by mass of total cementitious materials to CSA A3001.
- .4 Water: to CSA A23.1/A23.2.
- .5 Reinforcing bars: to CSA G30.18, Grade 400, minimum 30% recycled content.
- .6 Welded steel wire and deformed steel wire reinforcement: to ASTM A1064/A1064M; and zinc-coated (galvanized) steel welded wire and deformed steel welded wire reinforcement: to ASTM A1060/A1060M. Minimum 30% recycled content for all steel wire reinforcement.
 - .1 Provide in flat sheets only and adequately chair into position to obtain the specified concrete cover. Do not lay reinforcing sheets down and hook into position after concrete has been poured.
- .7 Premoulded joint filler:
 - .1 Bituminous impregnated fibreboard: to ASTM D1751.
- .8 Joint sealer/filler: grey to CAN/CGSB-19.24, Type 1, Class B.
- .9 Sealer: boiled linseed oil to ASTM D260 mixed with mineral spirits 1:1
- .10 Other concrete materials: to CSA A23.1/A23.2.

2.4 MIXES

- .1 Alternative 1 - Performance Method for specifying concrete: to meet Departmental Representative performance criteria to CSA A23.1/A23.2.
 - .1 Design mix to be submitted for approval by Departmental Representative.
 - .2 Ensure concrete supplier meets performance criteria as established below and provide verification of compliance as described in PART 3 - VERIFICATION.
 - .3 Provide concrete mix to meet following plastic state requirements:
Workability: free of surface blemishes, colour variations and segregation.
 - .4 Provide concrete mix to meet following hard state requirements:
 - .1 Durability and class of exposure: as noted on the drawings
 - .2 Compressive strength as noted on the drawings.
 - .3 Slump: as noted on the drawings.
 - .4 Intended application: as noted on the drawings.

- .5 Aggregate size as noted on the drawings.
- .6 Other Special requirements: as noted on the drawings.
- .5 Concrete supplier's certification.
- .6 Provide quality management plan to ensure verification of concrete quality to specified performance.

Part 3 EXECUTION

3.1 PREPARATION

- .1 Provide Departmental Representative minimum 72 hours notice to inspect reinforcing steel before each concrete pour.
- .2 Place concrete reinforcing in accordance with Section 03 20 00.
- .3 During concreting operations:
 - .1 Development of cold joints not allowed.
 - .2 Ensure concrete delivery and handling facilitates placing with minimum of rehandling, and without damage to existing structure or Work.
- .4 Protect previous Work from staining.
- .5 Clean and remove stains prior to application of concrete finishes.

3.2 INSTALLATION/ APPLICATION

- .1 Do cast-in-place concrete work in accordance with CSA A23.1/A23.2.
- .2 Sleeves and inserts:
 - .1 Cast in sleeves, ties, slots, anchors, reinforcement, frames, conduit, bolts, waterstops, joint fillers and other inserts required to be built-in.
 - .2 Sleeves and openings greater than 100 mm x 100 mm not indicated, must be reviewed by Departmental Representative.

3.3 FINISHES

- .1 All concrete slabs to have class "A" finish in accordance with CSA A23.1/A23.2 Table 21.
- .2 Formed surfaces exposed to view: sack rubbed finish.
- .3 Interior floor slabs to be left exposed requiring smooth surface: initial finishing operations followed by final finishing comprising mechanical floating and steel trowelling as specified in CSA A23.1/A23.2 to produce hard, smooth, dense trowelled surface free from blemishes.
- .4 Equipment pads: provide smooth trowelled surface.
- .5 Pavements, walks, curbs and exposed site concrete:
 - .1 Screed to plane surfaces and use aluminum floats.
 - .2 Provide round edges and joint spacings using standard tools.
 - .3 Trowel smooth to provide lightly brushed non-slip finish.

3.4 CONTROL JOINTS

- .1 Cut and Form control joints in slabs on grade at locations indicated, to CSA A23.1/A23.2 and install specified joint sealer/filler.

3.5 EXPANSION AND ISOLATION JOINTS

- .1 Install premoulded joint filler in expansion and isolation joints full depth of slab flush with finished surface to CSA A23.1/A23.2.

3.6 CURING

- .1 Use curing compounds compatible with applied finish on concrete surfaces free of bonding agents and to CSA A23.1/A23.2.

3.7 SEALING APPLICATION

- .1 After curing is complete, apply two even coats of linseed oil mixture to clean dry surfaces, each at 8 m² /L. Allow first coat to dry before applying second coat.

3.8 SITE TOLERANCES

- .1 Concrete floor slab finishing tolerance to CSA A23.1/A23.2.

3.9 FIELD QUALITY CONTROL

- .1 Concrete testing: to CSA A23.1/A23.2 by testing laboratory designated and paid for by Departmental Representative.

3.10 CLEANING

- .1 Clean in accordance with Section 01 74 11.
- .2 Use trigger operated spray nozzles for water hoses.
- .3 Designate cleaning area for tools to limit water use and runoff.
- .4 Cleaning of concrete equipment to be done in accordance with Section 01 35 29.
- .5 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Divert unused concrete materials from landfill to local quarry or facility after receipt of written approval from Departmental Representative.
 - .2 Provide appropriate area on job site where concrete trucks and be safely washed.
 - .3 Divert admixtures and additive materials from landfill to approved official hazardous material collections site after receipt of written approval from Departmental Representative.
 - .4 Do not dispose of unused admixtures and additive materials into sewer systems, into lakes, streams, onto ground or in other location where it will pose health or environmental hazard.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 02 41 99 – Construction Demolition.
- .2 Section 03 03 00 – Cast-in-place concrete.

1.2 REFERENCES

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-25.20-95, Surface Sealer for Floors.
- .2 CSA International
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.
- .3 South Coast Air Quality Management District (SCAQMD), California State
 - .1 SCAQMD Rule 1168-A2005(June 2006), Adhesives and Sealants Applications.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Provide manufacturer's printed product literature and data sheets for concrete finishes and include product characteristics, performance criteria, physical size, finish and limitations.
 - .1 Provide two copies of WHMIS MSDS. WHMIS MSDS acceptable to Labour Canada and Health and Welfare Canada for concrete floor treatment materials. Indicate VOC content in g/L.
 - .2 Include application instructions for concrete floor treatments.

1.4 ENVIRONMENTAL REQUIREMENTS

- .1 Temporary lighting:
 - .1 Minimum 1200 W light source, placed 2.5 m above floor surface, for each 40 sq m of floor being treated.
- .2 Electrical power:
 - .1 Provide sufficient electrical power to operate equipment normally used during construction.
- .3 Work area:
 - .1 Make work area water tight protected against rain and detrimental weather conditions.

- .4 Temperature:
 - .1 Maintain ambient temperature of not less than 10 degrees C from 7 days before installation to at least 48 hours after completion of work and maintain relative humidity not higher than 40% during same period.
- .5 Moisture:
 - .1 Ensure concrete substrate is within moisture limits prescribed by [flooring] manufacturer.
- .6 Safety:
 - .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials.
- .7 Ventilation:
 - .1 Ventilate area of work as directed by Departmental Representative by use of approved portable supply and exhaust fans.
 - .2 Ventilate enclosed spaces in accordance with Section 01 51 00.
 - .3 Provide continuous ventilation during and after coating application.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements:
 - .1 Deliver materials to site in original factory packaging, labelled with manufacturer's name, address.
- .3 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials in accordance with Section 01 74 20.

Part 2 PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- .1 Product quality and quality of work in accordance with Section 01 61 00.
- .2 Submit written declaration that components used are compatible and will not adversely affect finished flooring products and their installation adhesives.

2.2 CHEMICAL HARDENERS

- .1 Type 1 - Sodium silicate.
- .2 Water: potable.

2.3 SEALING COMPOUNDS

- .1 Surface sealer: to CAN/CGSB-25.20, Type 1 - solvent-based clear.
 - .2 Sealants: maximum VOC limit 250 g/L to SCAQMD Rule 1168.
-

- .3 Surface sealers are not manufactured or formulated with aromatic solvents.

2.4 CURING COMPOUNDS

- .1 Select low VOC, water-based curing compounds.

2.5 CONCRETE STAINS

- .1 Select low VOC, water-based concrete stains.

2.6 MIXES

- .1 Mixing ratios in accordance with manufacturer's written instructions.

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verify that slab surfaces are ready to receive work and elevations are as indicated on shop drawings.

3.2 PREPARATION OF EXISTING SLAB

- .1 Rub exposed sharp edges of concrete with carborundum to produce 3 mm radiused edges.
- .2 Saw cut control joints to CSA A23.1/A23.2, 24 hours maximum after placing of concrete.
- .3 Use mechanical stripping to remove chlorinated rubber or existing surface coatings.
- .4 Use protective clothing, eye protection, respiratory equipment during stripping of chlorinated rubber or existing surface coatings.

3.3 APPLICATION

- .1 Apply concrete finishing floor hardener in accordance with manufacturer's written instructions.
- .2 After floor treatment is dry, seal control joints and joints at junction with vertical surfaces with sealant.
- .3 Apply floor treatment in accordance with Sealer manufacturer's written instructions.
- .4 Clean over spray. Clean sealant from adjacent surfaces.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.

3.5 PROTECTION

- .1 Protect finished installation in accordance with manufacturer's instructions.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES

- .1 ASTM International
 - .1 ASTM A53/A53M-12, Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless.
 - .2 ASTM A123/A123M-13, Standard Specification for Zinc (Hot Dip Galvanized) Coatings on Iron and Steel Products.
 - .3 ASTM A307-14, Standard Specification for Carbon Steel Bolts, Studs, and Threaded Rod 60,000 PSI Tensile Strength.
- .2 CSA International
 - .1 CSA G40.20-13/G40.21-13, General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel.
 - .2 CSA S16-14, Design of Steel Structures.
 - .3 CSA W48-14, Filler Metals and Allied Materials for Metal Arc Welding (Developed in co-operation with the Canadian Welding Bureau).
 - .4 CSA W59-13, Welded Steel Construction (Metal Arc Welding) Metric.
- .3 Health Canada / Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for sections, plates, pipe, tubing, bolts and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit two copies of WHMIS MSDS.
 - .1 For finishes, coatings, primers, and paints applied on site: indicate VOC concentration in g/L.
- .3 Shop Drawings:
 - .1 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.
 - .2 Indicate materials, core thicknesses, finishes, connections, joints, method of anchorage, number of anchors, supports, reinforcement, details, and accessories.

1.3 QUALITY ASSURANCE

- .1 Test Reports: submit certified test reports showing compliance with specified performance characteristics and physical properties.

- .2 Certifications: submit product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Replace defective or damaged materials with new.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Steel sections and plates: to CSA G40.20/ G40.21, Grade 300W, minimum 30% recycled content.
- .2 Steel pipe: to ASTM A53/A53M standard weight, galvanized finish, minimum 30% recycled content.
- .3 Welding materials: to CSA W59.
- .4 Welding electrodes: to CSA W48 Series.
- .5 Bolts and anchor bolts: to ASTM A307.
- .6 Grout: non-shrink, non-metallic, flowable, 15 MPa at 24 hours.

2.2 FABRICATION

- .1 Fabricate work square, true, straight and accurate to required size, with joints closely fitted and properly secured.
- .2 Use self-tapping shake-proof flat headed screws on items requiring assembly by screws or as indicated.
- .3 Where possible, fit and shop assemble work, ready for erection.
- .4 Ensure exposed welds are continuous for length of each joint. File or grind exposed welds smooth and flush.

2.3 FINISHES

- .1 Galvanizing: hot dipped galvanizing with zinc coating 600 g/m², Coating Grade 85, to ASTM A123/A123M.
 - .2 Zinc primer: zinc rich, ready mix to MPI-EXT 5.2C.
-

2.4 PIPE RAILINGS

- .1 Steel pipe: 40 mm nominal outside diameter, formed to shapes and sizes as indicated.
- .2 Galvanize pipe railings after fabrication.

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for metal fabrications installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 ERECTION

- .1 Do welding work in accordance with CSA W59 unless specified otherwise.
- .2 Erect metalwork square, plumb, straight, and true, accurately fitted, with tight joints and intersections.
- .3 Provide suitable means of anchorage acceptable to Departmental Representative such as dowels, anchor clips, bar anchors, expansion bolts and shields, and toggles.
- .4 Exposed fastening devices to match finish and be compatible with material through which they pass.
- .5 Supply components for work by other trades in accordance with shop drawings and schedule.
- .6 Weld field connection.
- .7 Deliver items over for casting into concrete and building into masonry together with setting templates to appropriate location and construction personnel.
- .8 Touch-up galvanized surfaces with zinc rich primer where burned by field welding.
 - .1 Primer: maximum VOC limit 250 g/L.

3.3 PIPE RAILINGS

- .1 Install pipe railings to ramp and as indicated.
- .2 Set railing standards in concrete.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.5 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by metal fabrications installation.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Materials, preparation and application for caulking and sealants.

1.2 REFERENCES

- .1 American Society for Testing and Materials International, (ASTM)
 - .1 ASTM C920-14a, Standard Specification for Elastomeric Joint Sealants.
 - .2 ASTM D2240-05 (2010), Standard Test Method for Rubber Property - Durometer Hardness
- .2 Department of Justice Canada (Jus)
 - .1 Canadian Environmental Protection Act, 1999 (CEPA).
- .3 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
- .4 Transport Canada (TC)
 - .1 Transportation of Dangerous Goods Act, 1992 (TDGA).

1.3 SUBMITTALS

- .1 Submit product data in accordance with Section 01 33 00.
- .2 Manufacturer's product to describe.
 - .1 Caulking compound.
 - .2 Primers.
 - .3 Sealing compound, each type, including compatibility when different sealants are in contact with each other.
- .3 Submit samples in accordance with Section 01 33 00.
- .4 Submit duplicate samples of each type of material and colour.
- .5 Cured samples of exposed sealants for each color where required to match adjacent material.
- .6 Submit manufacturer's instructions in accordance with Section 01 33 00.
 - .1 Instructions to include installation instructions for each product used.

1.4 DELIVERY, STORAGE, AND HANDLING

- .1 Deliver, handle, store and protect materials in accordance with Section 01 61 00.
 - .2 Deliver and store materials in original wrappings and containers with manufacturer's seals and labels, intact. Protect from freezing, moisture, water and contact with ground or floor.
-

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.
- .3 Collect and separate for disposal paper, plastic, polystyrene, corrugated cardboard, packaging material in appropriate on-site bins for recycling in accordance with Waste Management Plan.
- .4 Place materials defined as hazardous or toxic in designated containers.
- .5 Handle and dispose of hazardous materials in accordance with the CEPA, TDGA, Regional and Municipal regulations.
- .6 Unused sealant material must not be disposed of into sewer system, into streams, lakes, onto ground or in other location where it will pose health or environmental hazard.
- .7 Divert unused joint sealing material from landfill to official hazardous material collections site approved by Departmental Representative.
- .8 Empty plastic joint sealer containers are not recyclable. Do not dispose of empty containers with plastic materials destined for recycling.
- .9 Fold up metal banding, flatten, and place in designated area for recycling.

1.6 PROJECT CONDITIONS

- .1 Environmental Limitations:
 - .1 Do not proceed with installation of joint sealants under following conditions:
 - .1 When ambient and substrate temperature conditions are outside limits permitted by joint sealant manufacturer or are below 4.4°C.
 - .2 When joint substrates are wet.
- .2 Joint-Width Conditions:
 - .1 Do not proceed with installation of joint sealants where joint widths are less than those allowed by joint sealant manufacturer for applications indicated.
- .3 Joint-Substrate Conditions:
 - .1 Do not proceed with installation of joint sealants until contaminants capable of interfering with adhesion are removed from joint substrates.

1.7 ENVIRONMENTAL REQUIREMENTS

- .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials; and regarding labelling and provision of Material Safety Data Sheets (MSDS) acceptable to Labour Canada.
 - .2 Conform to manufacturer's recommended temperatures, relative humidity, and substrate moisture content for application and curing of sealants including special conditions governing use.
-

Part 2 PRODUCTS

2.1 SEALANT MATERIALS

- .1 Do not use caulking that emits strong odours, contains toxic chemicals or is not certified as mould resistant in air handling units.
- .2 When low toxicity caulks are not possible, confine usage to areas which offgas to exterior, are contained behind air barriers, or are applied several months before occupancy to maximize offgas time.
- .3 Where sealants are qualified with primers use only these primers.

2.2 SEALANT MATERIAL DESIGNATIONS

- .1 Silicones One Part.
 - .1 To ASTM C920, primerless, Type S, Grade NS, Class 25, SWRI validated.
- .2 Flexible Epoxy Urethane Two Part.
 - .1 Solvent free, load bearing, conforming to ASTM D2240, Shore A Hardness 65-75.

2.3 SEALANT SELECTION

- .3 Perimeters of exterior openings where frames meet exterior facade of building (i.e. brick, block, precast masonry): Sealant type: Silicones One Part.
- .4 Seal interior perimeters of exterior openings as detailed on drawings: Sealant type: Silicones One Part.
- .5 Seal glazing units in doors: Sealant type: Silicones One Part, translucent colour.
- .6 Exterior joints in horizontal wearing surfaces: Sealant type: Flexible Epoxy Urethane Two Part.

2.4 JOINT CLEANER

- .1 Non-corrosive and non-staining type, compatible with joint forming materials and sealant recommended by sealant manufacturer.
- .2 Primer: as recommended by manufacturer.

Part 3 EXECUTION

3.1 PROTECTION

- .1 Protect installed Work of other trades from staining or contamination.

3.2 SURFACE PREPARATION

- .1 Examine joint sizes and conditions to establish correct depth to width relationship for installation of backup materials and sealants.
 - .2 Clean bonding joint surfaces of harmful matter substances including dust, rust, oil grease, and other matter which may impair Work.
-

- .3 Do not apply sealants to joint surfaces treated with sealer, curing compound, water repellent, or other coatings unless tests have been performed to ensure compatibility of materials. Remove coatings as required.
- .4 Ensure joint surfaces are dry and frost free.
- .5 Prepare surfaces in accordance with manufacturer's directions.

3.3 PRIMING

- .1 Where necessary to prevent staining, mask adjacent surfaces prior to priming and caulking.
- .2 Prime sides of joints in accordance with sealant manufacturer's instructions immediately prior to caulking.

3.4 BACKUP MATERIAL

- .1 Apply bond breaker tape where required to manufacturer's instructions.
- .2 Install joint filler to achieve correct joint depth and shape, with approximately 30% compression.

3.5 MIXING

- .1 Mix materials in strict accordance with sealant manufacturer's instructions.

3.6 APPLICATION

- .1 Sealant.
 - .1 Apply sealant in accordance with manufacturer's written instructions.
 - .2 Mask edges of joint where irregular surface or sensitive joint border exists to provide neat joint.
 - .3 Apply sealant in continuous beads.
 - .4 Apply sealant using gun with proper size nozzle.
 - .5 Use sufficient pressure to fill voids and joints solid.
 - .6 Form surface of sealant with full bead, smooth, free from ridges, wrinkles, sags, air pockets, embedded impurities.
 - .7 Tool exposed surfaces before skinning begins to give slightly concave shape.
 - .8 Remove excess compound promptly as work progresses and upon completion.
- .2 Curing.
 - .1 Cure sealants in accordance with sealant manufacturer's instructions.
 - .2 Do not cover up sealants until proper curing has taken place.
- .3 Cleanup.
 - .1 Clean adjacent surfaces immediately and leave Work neat and clean.
 - .2 Remove excess and droppings, using recommended cleaners as work progresses.
 - .3 Remove masking tape after initial set of sealant.

END OF SECTION

Part 1 GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 11 19 13 - Detention Doors and Frames

1.2 REFERENCES

- .1 ASTM International
 - .1 ASTM C542-05(2011), Standard Specification for Lock-Strip Gaskets.
 - .2 ASTM D2240-05(2010), Standard Test Method for Rubber Property - Durometer Hardness.
 - .3 ASTM E84-14, Standard Test Method for Surface Burning Characteristics of Building Materials.
 - .4 ASTM E330/E330M-14, Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference.
 - .5 ASTM F1233-08(2013), Standard Test Method for Security Glazing Materials and Systems.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-12.12-M90, Plastic Safety Glazing Sheets.
- .3 Environmental Choice Program (ECP)
 - .1 CCD-045-95(R2005), Sealants and Caulking Compounds.
- .4 Glass Association of North American (GANA)
 - .1 GANA Glazing Manual 50th Anniversary Edition-2008.
 - .2 GANA Laminated Glazing Reference Manual - 2009.
 - .3 GANA Sealant Manual-2008.
 - .4 GANA Laminated Glazing Reference Manual (2009).
 - .5 GANA Guide to Architectural Glass (2010).
 - .6 GANA/PGC International Protective Glazing Manual (2010).
- .5 South Coast Air Quality Management District (SCAQMD), California State, Regulation XI. Source Specific Standards
 - .1 SCAQMD Rule 1168-A2005, Adhesives and Sealants Applications.

1.3 ADMINISTRATIVE REQUIREMENTS

- .1 Arrange for site visit with Departmental Representative prior to start of Work to examine existing site conditions adjacent to demolition Work.

1.4 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
-

- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for glass, sealants, and glazing accessories and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Shop Drawings:
 - .1 Submit drawings stamped and signed by professional engineer registered or licensed in Province of Ontario, Canada.
- .4 Certificates: submit product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.
- .5 Test Reports: certified test reports showing compliance with specified performance characteristics and physical properties.
 - .1 Submit shop inspection for glass.

1.5 CLOSEOUT SUBMITTALS

- .1 Submit in accordance with Section 01 78 00.
- .2 Operation and Maintenance Data: submit operation and maintenance data for [glazing] for incorporation into manual.

1.6 QUALITY ASSURANCE

- .1 Certificates: product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.

1.7 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials off ground in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect glazing from nicks, scratches, and blemishes.
 - .3 Replace defective or damaged materials with new.

1.8 AMBIENT CONDITIONS

- .1 Ambient Requirements:
 - .1 Install glazing when ambient temperature is 10 degrees C minimum. Maintain ventilated environment for 24 hours after application.
 - .2 Maintain minimum ambient temperature before, during and 24 hours after installation of glazing compounds.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Design Criteria:
 - .1 Ensure continuity of building enclosure vapour and air barrier using glass and glazing materials as follow:
 - .1 Utilize inner light of multiple light sealed units for continuity of air and vapour seal.
 - .2 Size glass to meet physical attack standards ASTM 1915 Grade 2.
 - .3 Limit glass deflection to 1/200 with full recovery of glazing materials.
- .2 Flat Glazing:
 - .1 Plastic Safety Glazing Sheets to CAN/CGSB-12.12-M90, transparent, 16 mm total thickness as follows:
 - .1 3-ply laminated polycarbonate type.
 - .2 Acceptable Product: Lexgard M PC-500
- .3 Sealant: in accordance with Section 07 92 00.
 - .1 VOC limit 250 g/L maximum to SCAQMD Rule 1168.
 - .1 VOC limit: 5% maximum by weight to CCD-045.
 - .2 Ensure sealant does not contain chemical restrictions to CCD-045.

2.2 ACCESSORIES

- .1 Setting blocks: silicone, 80-90 Shore A durometer hardness to ASTM D2240, length of 25 mm for each square meter of glazing to suit glazing method, glass light weight and area.
 - .2 Spacer shims: silicone, 50-60 Shore A durometer hardness to ASTM D2240, 75 mm long x one half height of glazing stop x thickness to suit application. Self adhesive on one face.
 - .3 Glazing tape:
 - .1 Preformed butyl compound with integral resilient tube spacing device, 10-15 Shore A durometer hardness to ASTM D2240; coiled on release paper; black colour.
 - .2 Closed cell polyvinyl chloride foam, coiled on release paper over adhesive on two sides, maximum water absorption by volume 2%, designed for compression of 25%, to effect an air and vapour seal.
 - .4 Glazing clips: manufacturer's standard type.
 - .5 Lock-strip gaskets: to ASTM C542.
-

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrates previously installed under other Sections or Contracts are acceptable for glazing installation in accordance with manufacturer's written instructions.
 - .1 Verify that openings for glazing are correctly sized and within tolerance.
 - .2 Verify that surfaces of glazing channels or recesses are clean, free of obstructions, and ready to receive glazing.
 - .3 Visually inspect substrate in presence of Departmental Representative.
 - .4 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .5 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 PREPARATION

- .1 Clean contact surfaces with solvent and wipe dry.
- .2 Seal porous glazing channels or recesses with substrate compatible primer or sealer.
- .3 Prime surfaces scheduled to receive sealant.

3.3 INSTALLATION: EXTERIOR - DRY METHOD (PREFORMED GLAZING)

- .1 Manufacturer's Instructions: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.
- .2 Perform work in accordance with GANA Glazing Manual for glazing installation methods.
- .3 Cut glazing tape to length; install on glazing light. Seal corners by butting tape and sealing junctions with sealant in accordance with GANA Sealant Manual.
- .4 Place setting blocks at ¼ points, with edge block maximum 150 mm from corners.
- .5 Rest glazing on setting blocks and push against fixed stop with sufficient pressure to attain full contact.
- .6 Install removable stops without displacing glazing tape. Exert pressure for full continuous contact.
- .7 Trim protruding tape edge.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
 - .1 Remove traces of primer, caulking.
 - .2 Remove glazing materials from finish surfaces.
 - .3 Remove labels.

- .4 Clean glazing using approved non-abrasive cleaner in accordance with manufacturer's instructions.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .2 Waste Management: separate waste materials for reuse and recycling.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.5

PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 After installation, mark each light with an "X" by using removable plastic tape or paste.
 - .1 Do not mark heat absorbing or reflective glass units.
- .3 Repair damage to adjacent materials caused by glazing installation.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Installation only of detention hardware for:
 - .1 Section 32 31 13: Chain link fence gates.
 - .2 Section 11 19 13: Hollow metal detention doors.
- .2 Section 11 19 13: Electrical conduits on doors, frames and grille barriers.
- .3 Provisions for door position switches and electrical wiring for magnetic strikes, electric releases, electric locks.

1.2 REQUIREMENTS OF REGULATORY AGENCIES

- .1 Use only ULC listed and labelled hardware for fire doors.

1.3 HARDWARE LIST

- .1 Submit hardware schedule in accordance with Section 01 33 00.
- .2 Clearly indicate hardware proposed including make, model, material, function, finish and all other pertinent information.

1.4 SHOP DRAWINGS, PRODUCT DATA AND INSTALLATION INSTRUCTIONS

- .1 Submit shop drawings and product data in accordance with Section 01 33 00 and 01 78 00.
- .2 Clearly indicate all information required for proper preparation and application of hardware.
- .3 Submit shop drawings for each type locking device to show fabrication, layout, setting and erection details.
- .4 Measure existing opening and provide frame and door to match existing.
- .5 Furnish door and frame manufacturers with complete instructions and templates for preparation of their work to receive hardware.

1.5 MAINTENANCE DATA AND INSTRUCTIONS

- .1 Provide maintenance data, parts list and manufacturer's instructions for each type of lock, cremone bolt set, door closer, door holder, electric deadbolt, and locking device for incorporation into maintenance manual specified in Section 01 78 00.
- .2 Brief maintenance staff regarding proper care of hardware and locking devices, such as lubrication, adjustments cleaning, and general instructions.

1.6 MAINTENANCE MATERIALS

- .1 Supply two spanner tools for each size spanner screw on job.
 - .2 Supply two sets of wrenches for each type of do or closer.
-

1.7 DELIVERY AND STORAGE

- .1 Store all hardware and locking devices in locked, clean and dry area.
- .2 Package each item of hardware including fastenings, separately or in like groups of hardware, label each package as to item definition and location.
- .3 Maintain inventory list with hardware schedule.

1.8 ENGINEERING AND TECHNICAL SUPERVISION

- .1 Provide qualified engineering and technical supervision commencing at date contract is awarded and continuing until Certificate of Completion is issued.
- .2 Qualified supervisor will have been actively engaged in prison security hardware business for not less than five years.
- .3 Upon completion of work, and prior to issuance of Certificate of Completion, qualified supervisor to examine each lock, locking device, and all other detention hardware items, to ensure their proper installation and operation.

Part 2 PRODUCTS

2.1 HARDWARE ITEMS

- .1 Use one manufacturer's products only for all similar items.
- .2 Hardware for additions or alterations to existing institutions to match existing hardware for make, material, finish, and to be keyed into the existing system at the manufacturer's plant.

2.2 FASTENING DEVICES

- .1 Provide security screws, security nuts, rivets, spanner screws or other equally secure approved devices for affixing various hardware items.
- .2 Use only rivets, security screws, or security nuts at locations where maximum security against removal is required.
- .3 Use spanner screws only at locations where security against removal is not as important, and where it is necessary to remove and repair items from time to time.
- .4 Security screws and nuts to have an extra head which twists off when screw or nut is fully secured, leaving main head without holes or slots for insertion of tool for removal.
- .5 Spanner screws to have slots or holes that require a special spanner tool to remove screws.
- .6 Round head screws not acceptable except at locations approved where material is not thick enough to permit counter-sinking.
- .7 Standard screws not acceptable.
- .8 Use fasteners compatible with material through which they pass.
- .9 Exposed fastening devices to match finish of hardware.

2.3 KEYING

- .1 Keying will be provided by the Departmental Representative.

2.4 HINGES

- .1 Type 1A1:
 - .1 Styles, full surface or half surface, three-knuckle type.
 - .2 Size, 76 mm high x 102 mm minimum width.
 - .3 Hinge leaves, 10 mm thick malleable iron or steel.
 - .4 Hinge pin, 11 mm minimum diameter knurled and hardened steel (non-removable).
 - .5 Fasteners, four 10 mm diameter flat head security screws.
 - .6 Finish, CP.

2.5 KEY OPERATED LOCKS

- .1 Following features are common to all locks Type 3A:
 - .1 All have five lever tumblers of "spring temper" hard brass, each tumbler 3 mm thick and actuated by phosphor bronze spring.
 - .2 All have key cylinders of polished alloy bronze having hardness and tensile strength equal to mild steel. Each cylinder grooved to match and guide similar grooves in key.
 - .3 All operate by key type 14A1.
- .2 Type 3A1 (deadlock):
 - .1 Case and cover malleable iron and steel, size 76 mm high x 108 mm wide x 32 mm thick.
 - .2 Lockbolt brass or bronze 38 mm x 19 mm in size.
 - .3 Bolt throw 16 mm.
 - .4 Finish CP.
 - .5 Keyed one side or two sides.
 - .6 Fasteners, four 8 mm diameter flat head spanner security machine screws.

2.6 STRIKES FOR KEY OPERATED PRISON LOCKS

- .1 Type 4A1 (with dust box):
 - .1 Material, 5 mm mild steel.
 - .2 Fasteners, four 6 mm diameter flat head security screws.
 - .3 Include steel box on reverse side to protect against mortar and dust.
 - .4 Finish CP.
 - .5 Design to include round-edged lip when strike used in conjunction with springbolt lock.

2.7 DOOR POSITION INDICATOR SWITCHES (ROUGH IN FOR FUTURE OPERATION)

- .1 Fully Concealed Model:
 - .1 Switch-body case – 13 mm thick, zinc plated cold-rolled steel with 2 mm thick steel black zinc faceplate.
 - .2 Connecting arm – 8 mm thick stainless steel.
 - .3 Maximum butt size – 114 mm open width.
 - .4 Maximum door swing – 180°.
 - .5 Electrical Characteristics:
 - .1 Switch type and ratings – UL listed, single-pole, double-throw type; rated for 10 amps @ 125 or 250 VAC.
 - .2 Color-coded wire leads – 406 mm long

2.8 PULL HANDLE

- .1 Door pull type 11A5:
 - .1 Stainless Steel.
 - .2 Overall length 222 mm.
 - .3 Clearance between grip and door, 38 mm.
 - .4 Fasteners, tamper resistant screws.
 - .5 Finish C32D.

Part 3 EXECUTION

3.1 NOT USED

- .1 Not Used

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 07 92 00: Caulking of joints between frames and other building components.
- .2 Section 08 80 00: Glazing.
- .3 Section 11 19 12: Detention Hardware.

1.2 REQUIREMENTS OF REGULATORY AGENCIES

- .1 Fabricate and install fire doors and frames to NFPA 80-2013 except where specified otherwise.

1.3 SHOP DRAWINGS

- .1 Submit shop drawings in accordance with Section 01 33 00.
- .2 Clearly indicate each type material, core thickness, reinforcements, integral and removable stops, location of anchors exposed fastenings, finishes, and arrangement of hardware.
- .3 Include schedule identifying each unit, with door marks and numbers relating to numbering on drawings and in door schedule.
- .4 Submit drawings for each type of door, panel, and frame.

1.4 TESTS

- .1 Perform tests under the supervision of Departmental Representative and submit test reports certifying following minimum performance of typical flush detention door, 910 x 2130 x 50 mm in size:
 - .1 Static load: Centrally apply load of 4309 Kg (.22 kg per square centimeter) at quarter points on door. Maximum deflection must not exceed 0.38 mm after release of load.
 - .2 Rack test: Concentrate load of 1905 Kg on one unsupported corner of door. Door must not fail. Deflection must not exceed 37 mm.
- .2 Notify Departmental Representative sufficiently in advance of tests to allow for assignment of supervisory personnel.

1.5 ALTERNATIVES

- .1 Alternative designs for the specified method internal reinforcement for doors and panels may be acceptable.
 - .2 Submit for approval complete drawings, description, and test reports certifying performance for doors or panels of proposed alternative design.
-

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Sheet steel: commercial quality cold-rolled to ASTM A1008/A1008M-15, Class 1 finish.
- .2 Steel plate, shapes and bars: to CAN/CSA- G40.20-13/G40.21-13, type 230G or 260W.
- .3 Shop paint primer: to MPI# 79.
- .4 Fastening Devices:
 - .1 Provide security screws, security nuts, rivets, spanner screws or other equally secure approved devices for affixing various components.
 - .2 Use only rivets, security screws, or security nuts at locations where maximum security against removal is required.
 - .3 Use spanner screws only at locations where security against removal is not as important and where it is necessary to remove and repair items from time to time.
 - .4 Security screws and nuts to have an extra head which twists off when screw or nut is fully secured, leaving main head without holes or slots for insertion of tool for removal.
 - .5 Spanner screws to have slots or holes that require a special spanner tool to remove screws.
 - .6 Round head screws not acceptable except at locations approved where material is not thick enough to permit counter-sinking.
 - .7 Standard screws not acceptable.

2.2 HOLLOW METAL DETENTION DOORS

- .1 Fabricate hollow metal detention doors as detailed.
- .2 Doors to have 3 mm side clearance with bevelled edges where necessary to permit operating without binding.
- .3 Construct doors with 2 mm thick cold-rolled sheet steel face sheets both sides, each sheet one piece, formed to corner and meet at middle of door thickness. Provide continuous weld at meeting edges. Welds to be ground smooth and filled.
- .4 Provide internal 3.5 mm thick steel channel banding around entire outside perimeter edge of door, spot welded to face sheets at 76 mm oc. Banding to be continuous, full height and width.
- .5 Inner reinforcement to be continuous full height true truss design with triangular form, of shape which cannot be altered without changing length of sides. Flat apexes to be resistance spot welded at 70 mm oc horizontally and 76 mm oc vertically.
- .6 Fill void between each flute of reinforcement with minimum 24 kg/m³ density rock wool, or rigid fibreglass for sound-deadening and fire insulation.
- .7 Provide additional backup reinforcement of 5 mm plate welded in place at hinge reinforcing channel, factory drilled and tapped to receive hinge screws.
- .8 Pull reinforcement to be 10 mm thick x 35 x 254 mm.
- .9 Closer reinforcement to be 2.5 mm thick x 89 mm x 356 mm.

- .10 Build special pocket into door where prison lock is to be installed. Detention side of door to be finished flush and have a 3 mm internal back-up plate to protect lock. Design pocket so that removal of lock bolt is extended.
- .11 Build special 3.5 mm thick lock case support brackets internally in door where mortised institutional lock is to be installed. Brackets to firmly support case of lock on both faces to prevent it from moving in event of impact attack on door.
- .12 Provide 2.5 mm thick formed steel channels continuously around all four sides of openings for observation windows and lock pockets. Glazing stops to be removable one side only (opposite side from detention side) and held in place with Number 10-24 flat head spanner screws.
- .13 Provide all boxes and conduits required to accommodate wiring in doors where electric locks or limit switches are to be installed.
- .14 Provide drilled and tapped holes for all hardware according to templates furnished by hardware supplier.

2.3 PRESSED STEEL FRAMES

- .1 Fabricate pressed steel frames for detention doors as detailed.
- .2 Construct frames with minimum 2.5 mm thick cold-rolled sheet steel.
- .3 Corners to be fully mitered, continuously welded and ground smooth.
- .4 Stops on detention side to be formed integrally in frames, minimum 16 x 32 mm size.
- .5 Removable stops on opposite side to detention side to be held in place with 6 mm diameter flat head security screws at 203 mm centre to centre. Form stops with minimum 2.5 mm thick cold-rolled sheet steel minimum 16 x 25 mm size.
- .6 For each mortise hinge, provide 5 mm thick reinforcement full depth of jamb spot welded to frame and completely drilled and tapped.
- .7 For each surface hinge provide 10 mm thick x 35 x 254 mm long reinforcement welded to frame and completely drilled and tapped.
- .8 Provide drilled and tapped reinforcement for all hardware mountings, including door closers. Protect all mortises with steel cover boxes.
- .9 Provide all boxes and conduits required to accommodate wiring in frames and screens where electric locks or limit switches are specified.
- .10 Provide 1.6 mm thick steel masonry anchors at each jamb, at approximately 533 mm centre to centre. Each anchor 76 mm wide x 305 mm long.
- .11 Provide 2.5 mm thick x 76 mm steel angle jamb floor anchors.
- .12 Provide two steel channel or angle removable temporary spreaders welded to jambs at bottom of door opening to maintain proper alignment; provide for existing opening.

2.4 ACCESSORY COMPONENTS

- .1 Provide accessory components for hollow metal detention doors and panels as detailed, including observation windows.

2.5 PAINT

- .1 Field paint steel doors and frames in accordance with MPI EXT 5.3B - Alkyd GL-5 finish.
- .2 Protect weatherstrips from paint. Provide final finish free of scratches or other blemishes.

Part 3 EXECUTION

3.1 FRAME INSTALLATION

- .1 Set frames plumb, square, level at correct elevation.
- .2 Secure anchorages and connections to existing opening.
- .3 Brace frames rigidly in position while building-in. Install temporary horizontal and vertical wood spreaders as necessary to maintain frame alignment. Remove temporary steel and wood spreaders after frames are built-in.

3.2 DOOR AND PANEL INSTALLATION

- .1 Install doors and hardware in accordance with templates and manufacturer's instructions.
- .2 Adjust operable parts for correct function.
- .3 Co-operate with engineering supervisor provided by Detention Hardware Supplier to ensure proper installation, adjustment, and operation of hardware.
- .4 The Detention Door Manufacturer shall be employed as subcontractor to hang and adjust all doors equipped with type 16A locking devices including mechanical installation of the following type 16A locking device components:
 - .1 Mechanism housings at each door complete.
 - .2 Vertical locking columns complete.
 - .3 Bottom door guide assemblies complete.
 - .4 Mechanism housings connecting rows of cell doors to mechanical control cabinets.
 - .5 Mechanical control cabinets.
 - .6 Rubber bumpers in sliding door receiving channels.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES

- .1 American National Standards Institute (ANSI)
 - .1 ANSI C82.1-2004, American National Standard for Lamp Ballasts - Line Frequency Fluorescent Lamp Ballasts.
 - .2 ANSI C82.4-2002, American National Standard for Ballasts for High-Intensity Discharge and Low-Pressure Sodium (LPS) Lamps (Multiple-Supply Type).
- .2 American National Standards Institute/Institute of Electrical and Electronics Engineers (ANSI/IEEE)
 - .1 ANSI/IEEE C62.41-1991, Recommended Practice for Surge Voltages in Low-Voltage AC Power Circuits.
- .3 ASTM International Inc.
 - .1 ASTM F1137-00(2006), Standard Specification for Phosphate/Oil and Phosphate/Organic Corrosion Protective Coatings for Fasteners.
- .4 Canadian Standards Association (CSA International).
- .5 ICES-005-07, Radio Frequency Lighting Devices.
- .6 Underwriters' Laboratories of Canada (ULC).

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Provide manufacturer's printed product literature, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
- .3 Quality assurance submittals: provide following in accordance with Section 01 45 00.
 - .1 Manufacturer's instructions: provide manufacturer's written installation instructions and special handling criteria, installation sequence, and cleaning procedures.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00.
 - .2 Deliver materials to site in original factory packaging, labelled with manufacturer's name, address.
 - .3 Divert unused metal materials from landfill to metal recycling facility.
-

Part 2 PRODUCTS

2.1 LAMPS

- .1 Light Emitting Diode (LED) lamps to be white, 70% lumen maintenance at 50,000 hours, 4000K colour temperature, 40 Watt, rough-service rated.

2.2 FINISHES

- .1 Light fixture finish and construction to meet ULC listings and CSA certifications related to intended installation.

2.3 LUMINAIRES

- .1 High-abuse rated wall-pack type exterior luminaire, 390mm diameter, ULC listed for wet locations, suitable for wall or ceiling mount and as follows:
 - .1 Housing: Die-cast aluminum shallow casting; backplate constructed of 16 gauge aluminum.
 - .2 Face Plate: Injection-molded polycarbonate; color: matte black, eyelid design.
 - .3 Surface Conduit Box Finish: Polyester powder-coat paint, 2.0 mil thickness.
 - .4 Gasket: Die-cut closed-cell silicone.
 - .5 Lens: 3 mm, one-piece, injection-molded opal polycarbonate, attached with 4 recessed T20 stainless-steel fasteners.
 - .6 Basis-of-Design Product: Fail-Safe TR 15" Round Terrapin High Abuse LED by Cooper Industries.

Part 3 EXECUTION

3.1 INSTALLATION

- .1 Locate and install luminaires as indicated.
- .2 Provide adequate support to suit ceiling system.

3.2 WIRING

- .1 Connect luminaires to lighting circuits:
 - .1 Install flexible or rigid conduit for luminaires as indicated.

3.3 CLEANING

- .1 Clean in accordance with Section 01 74 11.
 - .1 Remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES

- .1 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 833-R-06-004, May 2007, Developing Your Stormwater Pollution Prevention Plan - A Guide for Construction Sites.

Part 2 PRODUCTS

2.1 NOT USED

- .1 Not Used.

Part 3 EXECUTION

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to sediment and erosion control plan, specific to site, or requirements of authorities having jurisdiction, whichever is more stringent.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.2 STRIPPING OF TOPSOIL

- .1 Ensure that procedures are conducted in accordance with applicable Provincial, Municipal, and Federal requirements.
 - .2 Remove topsoil before any construction procedures commence to avoid compaction of topsoil.
 - .3 Handle topsoil only when it is dry and warm.
 - .4 Remove vegetation from targeted areas by non-chemical means and dispose of stripped vegetation by alternative disposal.
 - .5 Remove brush from targeted area by non-chemical means and dispose of through alternative disposal.
 - .6 Strip topsoil to depths as directed by Departmental Representative. Avoid mixing topsoil with subsoil.
 - .7 Pile topsoil in berms in locations as directed by Departmental Representative. Stockpile height not to exceed 2.0 m.
 - .8 Dispose of unused topsoil in location as indicated by Departmental Representative.
-

- .9 Protect stockpiles from contamination and compaction.
- .10 Topsoil that has been piled for long term storage will be covered with trefoil or grass to maintain agricultural potential of soil.

3.3 PREPARATION OF GRADE

- .1 Verify that grades are correct. If discrepancies occur, notify Departmental Representative and do not commence work until instructed by Departmental Representative.
 - .1 Grade area only when soil is dry to lessen soil compaction.
 - .2 Grade soil, establishing natural contours and eliminating uneven areas and low spots, ensuring positive drainage.

3.4 PLACING OF TOPSOIL

- .1 Place topsoil only after Departmental Representative has accepted subgrade.
- .2 During dry conditions spread topsoil in uniform layers not exceeding 150 mm, over unfrozen subgrade free of standing water.
- .3 Establish traffic patterns for equipment that will prevent driving on topsoil after it has been spread to avoid compaction.
- .4 Cultivate the soil following spreading procedures.

3.5 SUB-SOILING

- .1 Following the spreading and cultivating procedures sub-soil the area to improve drainage and agricultural potential of soil.
- .2 With a vibrating sub-soiler work the area to a depth of 40 cm. Follow the contour lines of the natural grades of the area.
- .3 Cross sub-soil the area following the first pass.
- .4 Cultivate the soil with a chain harrow to de-clod the soil.

3.6 CLEANING

- .1 Proceed in accordance with Section 01 74 11.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 31 14 13 – Soil Stripping and Stockpiling
- .2 Section 31 23 33.01 – Excavation, Trenching and Backfilling.
- .3 Section 31 23 16.26 – Rock Removal.

1.2 REFERENCES

- .1 ASTM International (ASTM)
 - .1 ASTM D698-12e1, Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (600 kN-m/m³).
- .2 Ontario Provincial Standard Specifications (OPSS).
 - .1 OPSS 206 November 2009 – Construction Specification for Grading.
- .3 Underwriters' Laboratories of Canada (ULC)

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.

1.4 EXISTING CONDITIONS

- .1 Known underground and surface utility lines and buried objects are as indicated on site plan. Complete utility locate in accordance with Section 31 23 33.01 – Excavating Trenching and Backfilling.
- .2 Refer to dewatering in Section 31 23 33.01 – Excavating Trenching and Backfillin

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Fill material: Type IV Engineered backfill or selected backfill material in accordance with Section 31 23 33.01.
- .2 Excavated or graded material existing on site may be suitable to use as fill for grading work if approved by Departmental Representative.

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for rough grading installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.

- .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
- .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 STRIPPING OF TOPSOIL

- .1 Do not handle topsoil while in wet or frozen condition or in any manner in which soil structure is adversely affected as determined by Departmental Representative.
- .2 Commence topsoil stripping of areas as directed by Departmental Representative after area has been cleared of grasses and removed from site.
- .3 Strip topsoil to depths as directed by Departmental Representative. Rototill weeds and grasses and retain as topsoil on site. Avoid mixing topsoil with subsoil.
- .4 Stockpile in locations as directed by Departmental Representative. Stockpile height not to exceed 2 m.
- .5 Dispose of unused topsoil as directed by Departmental Representative off site.

3.3 GRADING

- .1 Rough grade to levels, profiles, and contours allowing for surface treatment as indicated.
- .2 Rough grade to following depths below finish grades:
 - .1 150 mm for grassed areas.
 - .2 150 mm for flowerbeds.
 - .3 150 mm for shrub beds.
 - .4 550 mm for asphalt paving.
 - .5 270 mm for concrete walks.
- .3 Slope rough grade away from building as indicated.
- .4 Grade ditches to depth as indicated.
- .5 Prior to placing fill over existing ground, scarify surface to depth of 150 mm minimum before placing fill over existing ground. Maintain fill and existing surface at approximately same moisture content to facilitate bonding.
- .6 Compact filled and disturbed areas to Standard Proctor Medium Dry Density, as follows:
 - .1 85% under landscaped areas.
 - .2 98% under paved and walk areas.
- .7 Do not disturb soil within branch spread of trees or shrubs to remain.

3.4 TESTING

- .1 Inspection and testing of soil compaction will be carried out by testing laboratory designated by Departmental Representative. Costs of tests will be paid by Departmental Representative.
 - .2 Submit testing procedure, frequency of tests, to Departmental Representative for review.
-

3.5 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.6 PROTECTION

- .1 Protect existing fencing, landscaping, bench marks, surface or underground utility lines which are to remain as directed by Departmental Representative. If damaged, restore to original or better condition unless directed otherwise.
- .2 Maintain access roads to prevent accumulation of construction related debris on roads.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Methods and requirements for excavating, trenching and backfilling for installation of storm sewers and other Underground utilities and restoration of asphalt paved areas.

1.2 MEASUREMENT PROCEDURES

- .1 Excavated materials will be measured in cubic metres in their original location.
 - .1 Excavation quantities measured will be actual volume removed within following limits:
 - .1 Width for trench excavation as indicated.
 - .2 Width for excavation for structures as indicated.
 - .3 Depth from ground elevation immediately prior to excavation, to elevation as indicated by Departmental Representative.
 - .2 Rock quantities measured will be actual volume removed within following limits:
 - .1 Width for trench excavation as indicated.
 - .2 Width for excavation for structures to be bounded by vertical planes up to 500 mm outside of and parallel to neat lines of footings as indicated.
 - .3 Depth from rock surface elevations immediately prior to excavation, to elevation as indicated.
 - .4 Volume of individual boulders and rock fragments will be determined by measuring three maximum mutually perpendicular dimensions.
- .2 Shoring, bracing, cofferdams, underpinning and de-watering of excavation will not be measured separately for payment.
- .3 Backfilling to authorized excavation limits will be measured in cubic metres compacted in place for each type of material specified.

1.3 REFERENCES

- .1 American Society for Testing and Materials International (ASTM)
 - .1 ASTM A653/A653M-13, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - .2 ASTM C117-13, Standard Test Method for Material Finer than 0.075 mm (No.200) Sieve in Mineral Aggregates by Washing.
 - .3 ASTM C136/C136M-14, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .4 ASTM D422-63(2007)e2, Standard Test Method for Particle-Size Analysis of Soils.
 - .5 ASTM D698-12e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³) (600 kN-m/m³).
 - .6 ASTM D751-06(2011), Standard Test Methods for Coated Fabrics.
 - .7 ASTM D1557-12, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³) (2,700 kN-m/m³).
 - .8 ASTM D4318-10e1, Standard Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 Canadian Standards Association (CSA International)
 - .1 CSA A3000-13, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).
 - .1 CSA A3001-13, Cementitious Materials for Use in Concrete.
 - .2 CSA A23.1-14/A23.2-14, Concrete materials and methods of concrete construction/Test methods and standard practices for concrete.
 - .3 CSA G401-14, Corrugated Steel Pipe Products.
- .4 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS 410 (November 2013) Construction Specification for Pipe Sewer Installation in Open Cut.
 - .2 OPSS 491 (November 2010) Construction Specification for Preservation, Protection, and Reconstruction of Existing Facilities.
 - .3 OPSS 805 (November 2010) Construction Specification for Temporary Erosion and Sediment Control Measures
 - .4 OPSS.MUNI (November 2013) 1004, Material Specification for Aggregates - Miscellaneous.
 - .5 OPSS.MUNI 1010 (November 2013), Material Specification for Aggregates - Base, Subbase, Select Subgrade, and Backfill Material.

- .5 U.S. Environmental Protection Agency (EPA)/ Office of Water
 - .1 EPA 833-R-06-004, May 2007, Developing Your Stormwater Pollution Prevention Plan - A Guide for Construction Sites.

1.4 DEFINITIONS.

- .1 Waste material: excavated material unsuitable for use in Work or surplus to requirements.
- .2 Borrow material: material obtained from locations outside area to be graded, and required for construction of fill areas or for other portions of Work.
- .3 Recycled fill material: material, considered inert, obtained from alternate sources and engineered to meet requirements of fill areas.
- .4 Unshrinkable fill: very weak mixture of cement, concrete aggregates and water that resists settlement when placed in utility trenches, and capable of being readily excavated.

1.5 SUBMITTALS

- .1 Make submittals in accordance with Section 01 33 00.
- .2 Quality Control: in accordance with Section 01 45 00:
 - .1 Submit condition survey of existing conditions as described in EXISTING CONDITIONS article of this Section.
 - .2 Submit for review by Departmental Representative proposed dewatering and heave prevention methods as described in PART 3 of this Section.
 - .3 Submit to Departmental Representative written notice at least 7 days prior to excavation work, to ensure cross sections are taken.
 - .4 Submit to Departmental Representative written notice when bottom of excavation is reached.
 - .5 Submit to Departmental Representative testing and inspection results as described in PART 3 of this Section.
- .3 Preconstruction Submittals:
 - .1 Submit construction equipment list for major equipment to be used in this section prior to start of Work.
 - .2 Submit records of underground utility locates, indicating: location plan of existing utilities as found in field, clearance record from utility authority and location plan of relocated and abandoned services, as required.
- .4 Samples:
 - .1 Submit samples in accordance with Section 01 33 00.
 - .2 Inform Departmental Representative at least 4 weeks prior to beginning Work, of proposed source of fill materials and provide access for sampling.

1.6 QUALITY ASSURANCE

- .1 Where Departmental Representative is employee of Contractor, submit proof that Work by Departmental Representative is included in Contractor's insurance coverage.
 - .2 Submit design and supporting data at least 2 weeks prior to beginning Work.
-

- .3 Design and supporting data submitted to bear stamp and signature of qualified professional engineer registered or licensed in Province of Ontario, Canada.
- .4 Keep design and supporting data on site.
- .5 Engage services of qualified professional Engineer who is registered or licensed in Province of Ontario, Canada in which Work is to be carried out to design and inspect cofferdams, shoring, bracing and underpinning required for Work.
- .6 Do not use soil material until written report of soil test results are reviewed by Departmental Representative.
- .7 Health and Safety Requirements:
 - .1 Do construction occupational health and safety in accordance with Section 01 35 29.

1.7 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.

1.8 PROTECTION OF EXISTING FEATURES

- .1 Protect existing features in accordance with applicable local regulations and in conformance with OPSS 491.
 - .2 Erect sediment control fencing regardless of site specific items detailed on the plans.
 - .3 Temporary Erosion and Sedimentation Control:
 - .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways.
 - .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
 - .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal..
 - .4 Existing buried utilities and structures:
 - .1 Size, depth and location of existing utilities and structures as indicated are for guidance only. Completeness and accuracy are not guaranteed.
 - .2 Prior to commencing excavation Work, notify Departmental Representative or authorities having jurisdiction, establish location and state of use of buried utilities and structures. Departmental Representative or authorities having jurisdiction to clearly mark such locations to prevent disturbance during Work.
 - .3 Confirm locations of buried utilities by careful test excavations.
 - .4 Maintain and protect from damage, water, sewer, gas, electric, telephone and other utilities and structures encountered.
 - .5 Where utility lines or structures exist in area of excavation, obtain direction of Departmental Representative before removing re-routing.
 - .6 Record location of maintained, re-routed and abandoned underground lines.
 - .7 Confirm locations of recent excavations adjacent to area of excavation.
-

- .5 Existing buildings and surface features:
 - .1 Conduct, with Departmental Representative, condition survey of existing buildings, trees and other plants, lawns, fencing, service poles, wires, pavement, survey bench marks and monuments which may be affected by Work.
 - .2 Protect existing buildings and surface features from damage while Work is in progress. In event of damage, immediately make repair to approval of Departmental Representative.
 - .3 Where required for excavation, cut tree roots or branches as approved by Departmental Representative and in accordance with appropriate section.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Granular material: to OPSS.MUNI 1010.
 - .2 Sand: clean, washed, minimum 100% passing 4.75 mm sieve, maximum 5% passing 0.075 mm sieve to OPSS.MUNI 1004.
 - .3 Drainage material: 19 mm crushed stone or 19 to 63 mm clean gravel to OPSS.MUNI 1004.
 - .4 Unshrinkable fill: in accordance with OPSS 1359, Material Specification for Unshrinkable Backfill.
 - .5 Geotextiles: to Section 31 32 19.01.
-

Part 3 EXECUTION

3.1 SITE PREPARATION

- .1 Remove obstructions, ice and snow, from surfaces to be excavated within limits indicated.
- .2 Cut pavement or sidewalk neatly along limits of proposed excavation in order that surface may break evenly and cleanly.

3.2 PREPARATION/ PROTECTION

- .1 Protect existing features in accordance with Section 01 56 00 and applicable local regulations.
- .2 Keep excavations clean, free of standing water, and loose soil.
- .3 Where soil is subject to significant volume change due to change in moisture content, cover and protect to Departmental Representative approval.
- .4 Protect natural and man-made features required to remain undisturbed. Unless otherwise indicated or located in an area to be occupied by new construction, protect existing trees from damage.
- .5 Protect buried services that are required to remain undisturbed.

3.3 STRIPPING OF TOPSOIL

- .1 Begin topsoil stripping of areas as indicated after area has been cleared of weeds and grasses and removed from site.
- .2 Strip topsoil to depths as indicated.
 - .1 Do not mix topsoil with subsoil.
- .3 Stockpile in locations as directed by Departmental Representative.
 - .1 Stockpile height not to exceed 2 m and should be protected from erosion.
- .4 Dispose of unused topsoil as directed by Departmental Representative.

3.4 STOCKPILING

- .1 Stockpile fill materials in areas designated by Departmental Representative.
 - .1 Stockpile granular materials in manner to prevent segregation.
- .2 Protect fill materials from contamination.
- .3 Implement sufficient erosion and sediment control measures to prevent sediment release off construction boundaries and into water bodies.

3.5 COFFERDAMS, SHORING, BRACING AND UNDERPINNING

- .1 Maintain sides and slopes of excavations in safe condition by appropriate methods and in accordance with Section 01 35 29.
 - .1 Where conditions are unstable, Departmental Representative to verify and advise methods.

- .2 Obtain permit from authority having jurisdiction for temporary diversion of water course.
- .3 Construct temporary Works to depths, heights and locations as directed by Departmental Representative.
- .4 During backfill operation:
 - .1 Unless otherwise indicated or directed by Departmental Representative, remove sheeting and shoring from excavations.
 - .2 Do not remove bracing until backfilling has reached respective levels of such bracing.
- .5 Upon completion of substructure construction:
 - .1 Remove cofferdams, shoring and bracing.
 - .2 Remove excess materials from site and restore watercourses as directed by Departmental Representative.

3.6 DEWATERING AND HEAVE PREVENTION

- .1 Keep excavations free of water while Work is in progress.
 - .2 Dewater in accordance with OPSS 517 Construction Specification for Dewatering of Pipeline, Utility and Associated Structure Excavation and OPSS 518 Construction Specification for Control of Water from Dewatering Operations.
 - .3 Submit for Departmental Representative approval details of proposed dewatering or heave prevention methods, such as dikes, well points, and sheet pile cut-offs.
 - .4 Avoid excavation below groundwater table if quick condition or heave is likely to occur. Prevent piping or bottom heave of excavations by groundwater lowering, sheet pile cut-offs, or other means.
 - .5 Protect open excavations against flooding and damage due to surface run-off.
 - .6 Dispose of water in manner not detrimental to public and private property, or any portion of Work completed or under construction.
 - .7 Provide settling basins, or other treatment facilities to remove suspended solids or other materials before discharging to storm sewers, water courses or drainage areas.
-

3.7 EXCAVATION

- .1 Advise Departmental Representative at least 7 days in advance of excavation operations for initial cross sections to be taken.
- .2 Excavate to lines, grades, elevations and dimensions as indicated.
- .3 Remove concrete, paving, walks and other obstructions encountered during excavation in accordance with Section 02 41 13.
- .4 Excavation must not interfere with bearing capacity of adjacent foundations.
- .5 Do not disturb soil within branch spread of trees or shrubs that are to remain.
 - .1 If excavating through roots, excavate by hand and cut roots with sharp axe or saw.
- .6 For trench excavation, unless otherwise authorized by Departmental Representative in writing, do not excavate more than 30 m of trench in advance of installation operations and do not leave open more than 15 m at end of day's operation.
- .7 Keep excavated and stockpiled materials safe distance away from edge of trench as directed by Departmental Representative.
- .8 Restrict vehicle operations directly adjacent to open trenches.
- .9 Dispose of surplus and unsuitable excavated material off site].
- .10 Do not obstruct flow of surface drainage or natural watercourses.
- .11 Earth bottoms of excavations to be undisturbed soil, level, free from loose, soft or organic matter.
- .12 Notify Departmental Representative when bottom of excavation is reached.
- .13 Obtain Departmental Representative approval of completed excavation.
- .14 Remove unsuitable material from trench bottom including those that extend below required elevations to extent and depth as directed by Departmental Representative.
- .15 Correct unauthorized over-excavation as follows:
 - .1 Fill under other areas with granular fill compacted to not less than 98 % of corrected maximum dry density.
 - .2 No payment will be made for over excavation works.
- .16 Hand trim, make firm and remove loose material and debris from excavations.
 - .1 Where material at bottom of excavation is disturbed, compact foundation soil to density at least equal to undisturbed soil.
 - .2 Clean out rock seams and fill with concrete mortar or grout to approval of Departmental Representative.

3.8 BEDDING AND SURROUND OF UNDERGROUND SERVICES

- .1 Granular bedding and backfill: in accordance with Section 31 05 17 - Aggregates: General and following requirements:

- .1 Granular materials to OPSS 1010 – Material Specification for Aggregates – Base, Sub-base, Select Subgrade and Backfill Material with the following amendment:
 - .1 OPSS 1010 is amended to indicate that Granular A and B shall be crushed limestone.
- .2 Place and compact granular material for bedding.
- .3 Place bedding to depth as required in minimum 150 mm layers and compact to 95% SPD.
- .4 Bedding shall be carefully shaped to receive the bottom of the pipe.
- .5 Place bedding and surround material in unfrozen condition.
- .6 Surround material for pipe shall be placed in minimum 150 mm layers and compacted to 95% Standard Proctor Density.
- .7 Surround material to be placed over pipe to a minimum 300 mm above top of pipe.
- .8 Compact each layer from pipe invert to mid height of pipe to at least 95% of corrected maximum dry density 95% maximum density to ASTM D 698.
- .9 Compact each layer from mid height of pipe to underside of backfill to at least 90% of corrected maximum dry density 90% maximum density to ASTM D 698.

3.9 BACKFILLING

- .1 Do not proceed with backfilling operations until completion of following:
 - .1 Departmental Representative has inspected and approved installations.
 - .2 Departmental Representative has inspected and approved of construction below finish grade.
 - .3 Inspection, testing, approval, and recording location of underground utilities.
 - .4 Removal of concrete formwork.
 - .5 Removal of shoring and bracing; backfilling of voids with satisfactory soil material.
- .2 Areas to be backfilled to be free from debris, snow, ice, water and frozen ground.
- .3 Do not use backfill material which is frozen or contains ice, snow or debris.
- .4 Place backfill material in uniform layers not exceeding 150 mm compacted thickness up to grades indicated. Compact each layer before placing succeeding layer.
- .5 Backfilling around installations:
 - .1 Place bedding and surround material as specified elsewhere.
 - .2 Do not backfill around or over cast-in-place concrete within 24 hours after placing of concrete.

- .3 Where temporary unbalanced earth pressures are liable to develop on walls or other structures:
 - .1 Permit concrete to cure for minimum 14 days or until it has sufficient strength to withstand earth and compaction pressure and approval obtained from Departmental Representative.
 - .2 If approved by Departmental Representative, erect bracing or shoring to counteract unbalance, and leave in place until removal is approved by Departmental Representative.

3.10 RESTORATION

- .1 Upon completion of Work, remove waste materials and debris in accordance to Section 01 74 20, trim slopes, and correct defects as directed by Departmental Representative.
- .2 Replace topsoil as directed by Departmental Representative.
- .3 Reinstate lawns to elevation which existed before excavation.
- .4 Reinstate pavements and sidewalks disturbed by excavation to thickness, structure and elevation which existed before excavation.
- .5 Clean and reinstate areas affected by Work as directed by Departmental Representative.
- .6 Use temporary plating to support traffic loads over unshrinkable fill for initial 24 hours.
- .7 Protect newly graded areas from traffic and erosion and maintain free of trash or debris.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 31 11 23 – Aggregate Base Courses
- .2 Section 31 23 33.01 – Excavating, Trenching and Backfilling

1.2 REFERENCES

- .1 ASTM International
 - .1 ASTM C117-13, Standard Test Methods for Material Finer Than 0.075 mm Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C131/C131M-14, Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine.
 - .3 ASTM C136/C136M-14, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .4 ASTM D422-63(2007)e2, Standard Test Method for Particle-Size Analysis of Soils.
 - .5 ASTM D698-12e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400ft-lbf/ft³) (600kN-m/m³).
 - .6 ASTM D1557-09, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000ft-lbf/ft³) (2,700kN-m/m³).
 - .7 ASTM D1883-14, Standard Test Method for CBR (California Bearing Ratio) of Laboratory Compacted Soils.
 - .8 ASTM D4318-10e1, Standard Test Methods for Liquid Limit, Plastic Limit and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 832/R-92-005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.
- .4 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS.MUNI 501 (November 2014), Construction Specification for Compacting
 - .2 OPSS.MUNI 1004 (November 2013), Material Specification for Aggregates - Miscellaneous.
 - .3 OPSS.MUNI 1010 (November 2013), Material Specification for Aggregates - Base, Sub-base, Select Subgrade, and Backfill Material.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00.

- .2 Storage and Handling Requirements:
 - .1 Store materials in accordance with erosion and sedimentation control plan.
 - .2 Replace defective or damaged materials with new.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Granular sub-base material: Type II material in accordance with Section 31 23 33.01 and following requirements:
 - .1 Gradations to be within limits specified when tested to ASTM C 136 and ASTM C 117. Sieve sizes to CAN/CGSB-8.2

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrate previously installed under other Sections or Contracts are acceptable for granular sub-base installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 PRECEDENCE

- .1 Workmanship and placement should meet the requirements of Section 31 23 33.01 – Excavating, Trenching and Backfilling.

3.3 PLACING

- .1 Place granular sub-base after subgrade is inspected and approved by Departmental Representative.
 - .2 Construct granular B sub-base to depth and grade in areas indicated.
 - .3 Ensure no frozen material is placed.
 - .4 Place material only on clean unfrozen surface, free from snow or ice.
 - .5 Begin spreading sub-base material on crown line or high side of one-way slope.
 - .6 Place granular sub-base materials using methods which do not lead to segregation or degradation.
 - .7 For spreading and shaping material, use spreader boxes having adjustable templates or screeds which will place material in uniform layers of required thickness.
 - .8 Place material to full width in uniform layers not exceeding 150 mm compacted thickness.
-

- .1 Departmental Representative may authorize thicker lifts if specified compaction can be achieved.
- .9 Shape each layer to smooth contour and compact to specified density before succeeding layer is placed.
- .10 Remove and replace portion of layer in which material has become segregated during spreading.

3.4 **COMPACTION**

- .1 Compaction equipment to be capable of obtaining required material densities.
- .2 Compaction to conform to OPSS.MUNI 501 Construction Specification for Compacting.
- .3 Efficiency of equipment not specified to be proved at least as efficient as specified equipment at no extra cost and written approval must be received from Departmental Representative before use.
- .4 Equipped with device that records hours of actual work, not motor running hours.
- .5 Compact to 100% maximum dry density in accordance with ASTM D698.
- .6 Shape and roll alternately to obtain smooth, even and uniformly compacted sub-base.
- .7 Apply water as necessary during compaction to obtain specified density.
- .8 In areas not accessible to rolling equipment, compact to specified density with mechanical tampers approved by Departmental Representative.
- .9 Correct surface irregularities by loosening and adding or removing material until surface is within specified tolerance.

3.5 **PROOF ROLLING**

- .1 Obtain written approval from Departmental Representative to use non-standard proof rolling equipment.
- .2 Proof roll at level in sub-base as indicated.
 - .1 If non-standard proof rolling equipment is approved, Departmental Representative will determine level of proof rolling.
- .3 Make sufficient passes with proof roller to subject every point on surface to three separate passes of loaded tire.
- .4 Where proof rolling reveals areas of defective subgrade:
 - .1 Remove sub-base and subgrade material to depth and extent as directed by Engineer.
 - .2 Backfill excavated subgrade in accordance with Section 31 23 16.
 - .3 Replace sub-base material and compact.
- .5 Where Proof rolling reveals areas of defective sub-base, remove and replace in accordance with this section at no extra cost.

3.6 QUALITY CONTROL TESTING

- .1 Inspection and testing of granular sub-base compaction shall be carried out by a testing firm designated by PWGSC and Departmental Representative.
 - .1 Minimum testing frequency: 1 test per 2,000 m²/lift.
- .2 Compaction test results shall be submitted to Departmental Representative for review and approval as they become available.
- .3 Any tests with failing results will be rectified and retested at the Contractor's expense.

3.7 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

3.8 SITE TOLERANCES

- .1 Finished sub-base surface to be within 10 mm of elevation as indicated but not uniformly high or low.

3.9 PROTECTION

- .1 Maintain finished sub-base in condition conforming to this section until succeeding base is constructed, or until granular sub-base is accepted by Departmental Representative.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 32 11 16.01 - Granular Sub-base.
- .2 Section 31 23 33.01 – Excavating, Trenching and Backfilling.

1.2 REFERENCES

- .1 American Society for Testing and Materials (ASTM)
 - .1 ASTM C117-13, Standard Test Methods for Material Finer Than 0.075 mm Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C131/C131M-14, Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine.
 - .3 ASTM C136/C136M-14, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .4 ASTM D698-12e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400ft-lbf/ft³) (600kN-m/m³).
 - .5 ASTM D1557-09, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000ft-lbf/ft³) (2,700kN-m/m³).
 - .6 ASTM D1883-07e2, Standard Test Method for CBR (California Bearing Ratio) of Laboratory Compacted Soils.
 - .7 ASTM D4318-10e1, Standard Test Methods for Liquid Limit, Plastic Limit and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS.MUNI 501 (November 2014), Construction Specification for Compacting
 - .2 OPSS.MUNI 1004 (November 2013), Material Specification for Aggregates - Miscellaneous.
 - .3 OPSS.MUNI 1010 (November 2013), Material Specification for Aggregates - Base, Sub-base, Select Subgrade, and Backfill Material.

1.3 DELIVERY, STORAGE, AND HANDLING

- .1 Deliver and stockpile aggregates in accordance with Section 01 61 00. Stockpile minimum 50% of total aggregate required prior to beginning operation.
- .2 Store cement in weathertight bins or silos that provide protection from dampness and easy access for inspection and identification of each shipment.

1.4 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate and recycle waste materials in accordance with Section 01 74 20.
- .2 Divert unused granular material from landfill to local facility as approved by Departmental Representative.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Granular base: Type II material in accordance with Section 31 23 33.01 and following requirements:
 - .1 Gradations to be within limits specified when tested to ASTM C 136 and ASTM C 117 sizes to OPSS 1010.

Part 3 EXECUTION

- 3.1** Workmanship and placement should meet the requirements of the geotechnical investigation report and Section 31 23 33.

3.2 SEQUENCE OF OPERATION

- .1 Place granular base after sub-base surface is inspected and approved by Departmental Representative.
 - .2 Placing
 - .1 Construct granular base to depth and grade in areas indicated.
 - .2 Ensure no frozen material is placed.
 - .3 Place material only on clean unfrozen surface, free from snow and ice.
 - .4 Begin spreading base material on crown line or on high side of one-way slope.
 - .5 Place material using methods which do not lead to segregation or degradation of aggregate.
 - .6 For spreading and shaping material, use spreader boxes having adjustable templates or screeds which will place material in uniform layers of required thickness.
 - .7 Place material to full width in uniform layers not exceeding 150 mm compacted thickness. Departmental Representative may authorize thicker lifts (layers) if specified compaction can be achieved.
 - .8 Shape each layer to smooth contour and compact to specified density before succeeding layer is placed.
 - .9 Remove and replace that portion of layer in which material becomes segregated during spreading.
-

3.3 COMPACTION

- .1 Compaction equipment to be capable of obtaining required material densities.
- .2 Compaction to conform to OPSS.MUNI 501 Construction Specification for Compacting.
- .3 Efficiency of equipment not specified to be proved at least as efficient as specified equipment at no extra cost and written approval must be received from Departmental Representative before use.
- .4 Equipped with device that records hours of actual work, not motor running hours.
- .5 Compact to 100% maximum dry density in accordance with ASTM D698.
- .6 Shape and roll alternately to obtain smooth, even and uniformly compacted sub-base.
- .7 Apply water as necessary during compaction to obtain specified density.
- .8 In areas not accessible to rolling equipment, compact to specified density with mechanical tampers approved by Departmental Representative.
- .9 Correct surface irregularities by loosening and adding or removing material until surface is within specified tolerance.

3.4 PROOF ROLLING

- .1 Obtain written approval from Departmental Representative to use non-standard proof rolling equipment.
- .2 Proof roll at level in sub-base as indicated.
 - .1 If non-standard proof rolling equipment is approved, Departmental Representative will determine level of proof rolling.
- .3 Make sufficient passes with proof roller to subject every point on surface to three separate passes of loaded tire.
- .4 Where proof rolling reveals areas of defective subgrade:
 - .1 Remove sub-base and subgrade material to depth and extent as directed by Engineer.
 - .2 Backfill excavated subgrade in accordance with Section 31 23 16.
 - .3 Replace sub-base material and compact.
- .5 Where Proof rolling reveals areas of defective sub-base, remove and replace in accordance with this section at no extra cost.

3.5 QUALITY CONTROL TESTING

- .1 Inspection and testing of granular sub-base compaction shall be carried out by a testing firm designated by PWGSC and Departmental Representative.
 - .1 Minimum testing frequency: 1 test per 2,000 m²/lift.
- .2 Compaction test results shall be submitted to Departmental Representative for review and approval as they become available.
- .3 Any tests with failing results will be rectified and retested at the Contractor's expense.

3.6 SITE TOLERANCES

- .1 Finished base surface to be within plus or minus 10 mm of established grade and cross section but not uniformly high or low.

3.7 PROTECTION

- .1 Maintain finished base in condition conforming to this Section until succeeding material is applied or until acceptance by Departmental Representative.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Materials and installation for asphalt paving for roads and parking areas.

1.2 RELATED SECTIONS

- .1 Section 32 11 16.01 – Granular Sub-Base.

1.3 REFERENCES

- .1 American Association of State Highway and Transportation Officials (AASHTO)
 - .1 AASHTO M320-10, Standard Specification for Performance Graded Asphalt Binder.
 - .2 AASHTO R29-14, Standard Specification for Grading or Verifying the Performance Graded of an Asphalt Binder.
 - .3 AASHTO T245-14, Standard Method of Test for Resistance to Plastic flow of Bituminous Mixtures Using Marshall Apparatus.
- .2 ASTM International
 - .1 ASTM C88-13, Standard Test Method for Soundness of Aggregates by Use of Sodium Sulphate or Magnesium Sulphate.
 - .2 ASTM C11713, Standard Test Method for Material Finer Than 0.075mm (No.200) Sieve in Mineral Aggregates by Washing.
 - .3 ASTM C123/C123M-11, Standard Test Method for Lightweight Particles in Aggregate.
 - .4 ASTM C127-15, Standard Test Method for Specific Gravity and Absorption of Coarse Aggregate.
 - .5 ASTM C128-15, Standard Test Method for Density, Relative Density (Specific Gravity), and Absorption of Fine Aggregate.
 - .6 ASTM C131/C131M-14, Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine.
 - .7 ASTM C136/C136M-14, Standard Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .8 ASTM C207-06(2011), Standard Specification for Hydrated Lime for Masonry Purposes.
 - .9 ASTM D2419-14, Standard Test Method for Sand Equivalent Value of Soils and Fine Aggregate.
 - .10 ASTM D3203/D3203M-11, Standard Test Method for Percent Air Voids in Compacted Dense and Open Bituminous Paving Mixtures.
 - .11 ASTM D4791-10, Standard Test Method for Flat Particles, Elongated Particles, or Flat and Elongated Particles in Coarse Aggregate.
- .3 Canadian General Standards Board (CGSB)

- .1 CAN/CGSB-8.1-88, Sieves Testing, Woven Wire, Inch Series.
- .2 CAN/CGSB-8.2-M88, Sieves Testing, Woven Wire, Metric.
- .4 Ontario Provincial Standard Specification
 - .1 OPSS 310 (November 2010), Construction Specification for Hot Mix Asphalt.
 - .2 OPSS 1150, Material Specifications for Hot Mix Asphalt.

1.4 PRODUCT DATA

- .1 Submittals in accordance with Section 01 33 00 – Submittal Procedures.
- .2 Submit asphalt concrete mix design and trial mix test results to Departmental Representative for review at least 4 weeks prior to beginning Work.

1.5 DELIVERY

- .1 Submit to Departmental Representative copies of freight and waybills for asphalt cement as shipments are received.
 - .1 Departmental Representative reserves right to check weights as material is received.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 All materials shall conform to OPSS 1150.
- .2 Performance graded asphalt cement: to AASHTO M320, grade PG 58 - 28 when tested to AASHTO R29.

2.2 EQUIPMENT

- .1 All equipment shall be in conformance with OPSS 310

2.3 MIX DESIGN

- .1 Mix design to be approved in writing by Departmental Representative.
- .2 Mix design to be developed by testing laboratory approved in writing by Departmental Representative.
 - .1 Do not change job-mix without prior approval of Departmental Representative. When change in material source proposed, new job-mix formula will be provided to be approved by Departmental Representative.

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for asphalt paving in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and approval to proceed is received from Departmental Representative.

3.2 PLACING

- .1 Obtain Departmental Representative's approval of base and existing surface and tack coat prior to placing asphalt.
- .2 Place asphalt concrete to thicknesses, grades and lines as indicated.
- .3 Placing conditions:
 - .1 Place asphalt mixtures only when air temperature is above 5 °C minimum.
 - .2 When temperature of surface on which material is to be placed falls below 10 °C, provide extra rollers as necessary to obtain required compaction before cooling.
 - .3 Do not place hot-mix asphalt when pools of standing water exist on surface to be paved, during rain, or when surface is damp.
- .4 Place asphalt concrete in compacted lifts of thickness as follows:
 - .1 Levelling courses to thicknesses required but not exceeding 50 mm.
 - .2 Base course (HL8) in one layer of 50 mm.
 - .3 Surface course (HL3) in one layer of maximum 50 mm.
- .5 When placing asphalt under existing fencing, fencing mesh is to be removed and replaced immediately following compaction of asphalt. Departmental Representative to approve fence reinstatement.

3.3 FINISH TOLERANCES

- .1 Finished asphalt surface to be within 5 mm of design elevation but not uniformly high or low.
- .2 Finished asphalt surface not to have irregularities exceeding 5 mm when checked with 4.5m straight edge placed in any direction.

3.4 DEFECTIVE WORK

- .1 Correct irregularities which develop before completion of rolling by loosening surface mix and removing or adding material as required.
 - .1 If irregularities or defects remain after final compaction, remove surface course promptly and lay new material to form true and even surface and compact immediately to specified density.
- .2 Repair areas showing checking, rippling, or segregation.

- .3 Adjust roller operation and screed settings on paver to prevent further defects such as rippling and checking of pavement.

END OF SECTION

Part 1 GENERAL

1.1 REFERENCES

- .1 ASTM International
 - .1 ASTM A53/A53M-12, Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated Welded and Seamless.
 - .2 ASTM A90/A90M-13, Standard Test Method for Weight of Coating on Iron and Steel Articles with Zinc or Zinc-Alloy Coatings.
 - .3 ASTM A121-13, Standard Specification for Zinc-Coated (Galvanized) Steel Barbed Wire.
 - .4 ASTM A123/A123M-13, Standard Specification for Zinc (Hot Dip Galvanized) coatings on Iron and Steel Products.
 - .5 ASTM A653/A653M-13, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - .6 ASTM C618-12a, Standard Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use as a Mineral Admixture in Concrete.
 - .7 ASTM F1664-08 (2013), Standard Specification for Poly(Vinyl Chloride) (PVC)-Coated Steel Tension Wire Used with Chain-Link Fence.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-138.1-96, Fabric for Chain Link Fence.
 - .2 CAN/CGSB-138.2-96, Steel Framework for Chain Link Fence.
 - .3 CAN/CGSB-138.3-96, Installation of Chain Link Fence.
 - .4 CAN/CGSB-138.4-96, Gates for Chain Link Fence.
 - .5 CAN/CGSB-1.181-99, Ready-Mixed Organic Zinc-Rich Coating.
- .3 CSA International
 - .1 CSA A23.1-14/A23.2-14, Concrete Materials and Methods of Concrete Construction/Test Methods and Standard Practices for Concrete.
 - .2 CAN/CSA-A3000-13, Cementitious Materials Compendium.
- .4 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 832/R-92-005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for concrete mixes, fences, posts and gates and include product characteristics, performance criteria, physical size, finish and limitations.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations.
 - .2 Store and protect fence and gate materials from damage.
 - .3 Replace defective or damaged materials with new.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Concrete mixes and materials: in accordance with Section 03 30 00.
 - .1 Nominal coarse aggregate size: 20-5.
 - .2 Compressive strength: 20 MPa minimum at 28 days.
 - .3 Additives: fly ash to CSA A3000.
 - .2 Chain-link fence fabric: to CAN/CGSB-138.1.
 - .1 Fabric Type 1, Class A, Style 1-heavy.
 - .2 Wire Size: 4.8 mm minimum (6 Gauge)
 - .3 Size of Mesh: 50.8 mm
 - .4 Barbed Edges top and bottom.
 - .5 Breaking Tensile Strength: 10,000 N•min
 - .6 Height of fabric: 3.6m or as indicated in Drawings.
 - .3 Posts, braces and rails: to CAN/CGSB-138.2, galvanized steel pipe.
 - .1 Post Type 1 hot-rolled, butt or electrical resistance welded, dimensions to Table 2, Style A heavy. Minimum yield strength: Type 2, 344 MPa:
 - .1 Line Posts: minimum 73 mm diameter, 8.6 kg/m
 - .2 Strain posts: minimum 114 mm diameter, 15.92 kg/m
 - .3 Corner, end, and gate posts: minimum 150 mm diameter, 21.0 kg/m
 - .2 Rail Type 1, Style A Heavy, dimensions to Table 2, minimum yield strength 170 MPa.
 - .3 Rail Type 2, Style A Heavy, dimensions to Table 3, minimum yield strength 344 MPa.
 - .4 Tension wire: to CAN/CGSB-138.2, single strand, galvanized steel wire.
 - .5 Tie wire fasteners: 3.7 mm galvanized steel wire at 300 m o/c.
 - .6 Tension bar: to ASTM A653/A653M, 5 x 20 mm minimum galvanized steel.
-

- .7 Gates: to CAN/CGSB-138.4, Type I hot rolled, butt or electric resistance welded; Style 1 single swing and Style 4 special sliding, frame, braces and post sizes to Table 1.
 - .1 Gates fabricated as indicated with electrically welded joints, and hot-dip galvanized after welding.
 - .2 Gate frames: to ASTM A53/A53M, standard weight, 45 mm outside diameter pipe for outside frame, 35 mm outside diameter pipe for interior bracing covered with chain link fabric identical to fabric on adjacent fence.
 - .3 Fasten fence fabric to gate with twisted selvage at top.
 - .4 Furnish swing gates with galvanized malleable iron hinges, latch and latch catch with provision and reinforcement for lockset which can be attached and operated from either side of installed gate.
 - .5 Single swing gate lock: Folger Adams FGM-86 five-tumbler mechanical model, keyed from both sides, welded to frame, with 80-4H Fence Gate Lock Keeper accessory, zinc plated finish. No substitutions will be accepted.
 - .1 Key Code to be provided by the Departmental Representative.
 - .6 Rollers: factory-lubricated, permanently sealed bearings, adjustable on shaft with locking set screw.
 - .7 Sliding Gates:
 - .1 Bottom guides: consisting of two guide wheels on a galvanized steel bracket, bolted to support posts.
 - .2 Vertical support posts: minimum 100 mm diameter galvanized steel with concrete footings.
 - .3 Sliding gate frames shall have a separate semi enclosed 'keyed' track. When track is interlocked with the 'keyed' top member and welded to it, it forms a composite structure with the top of the gate frame.
 - .4 Gate frame is supported from the track by two swivel type, self aligning, 4 wheeled, sealed lubricant, ball bearing truck assemblies.
- .8 Fittings and hardware: to CAN/CGSB-138.2, galvanized steel.
 - .1 Tension bar bands: 3 x 20 mm minimum galvanized steel aluminum spaced at 300 mm o/c vertically.
 - .2 Post caps to provide waterproof fit, to fasten securely over posts and to carry top rail.
 - .3 Overhang tops to provide waterproof fit, to hold top rails and outward and inward projection to hold barbed wire overhang. Provide projection with clips or recesses to hold 3 strands of barbed wire spaced 100 mm apart.
 - .4 Include projection with clips or recesses to hold 3 strands of barbed wire spaced 100 mm apart.
 - .5 Projection of approximately 300 mm long to project from fence at 45 degrees above horizontal.
 - .6 Turnbuckles to be drop forged.

- .9 Bands: galvanized steel 6 x 25 mm, offset and centered type as required.
- .10 Clips: galvanized sheet metal, 3.8 mm.
- .11 Organic zinc rich coating: to CAN/CGSB-1.181.
- .12 Barbed wire: to ASTM A121 2 mm diameter galvanized steel wire 4 point barbs 125 mm spacing.
- .13 Barbed tape concertina:
 - .1 Galvanized, 20 mm x 0,5 mm steel barbed tape.
 - .2 Barbs 19 mm long, 45 mm o.c.
 - .3 Core wire 2.5 mm diameter high tensile spring steel, galvanized.
 - .4 Barbed tape cold-clenched over core wire.
 - .5 Coil diameter 710 mm, minimum installed diameter of 635 mm.
 - .6 Installed loop spacing: maximum 230 mm.
- .14 Grounding rod: 16 mm diameter copperweld rod, 3 m long.
- .15 Sliding Gate Locking:
 - .1 When device is in closed position, it is to be impossible to move gate to open position except by mechanical operator provided.
 - .2 Locking to be accomplished by keyless locking device engaging gate in three places in vertical front locking pilaster.
 - .3 When gate is in open position, all openings in vertical front locking pilaster to be completely closed.
 - .4 Provide manual control mechanism in special pilaster for unlocking and operating door by crank. Locate crank 914 mm above ground.
 - .5 Provide special pilaster with a hinged and locked door of same material to enclose and protect crank handle and mechanism. Door on pilaster to have one pair hinges Type 1A1, one cylinder shield Type 11A2, one pull handle Type 11A5 and one deadlock Type 3A9.
 - .6 Provide supporting structures connected with track box and housing. Track to be formed structural steel.
 - .7 Hang each gate on three trolley hangers of ample capacity.
 - .8 Provide base plates with forged or welded steel guides.
 - .9 Provide support columns at open end of gate travel.
 - .10 Finish CP, except track and door rollers.

2.2 FINISHES

- .1 Galvanizing:
 - .1 For chain link fabric: to CAN/CGSB-138.1 Grade 2. Average mass of zinc coating: minimum 610 g/m² of uncoated wire.
 - .2 For pipe: 550 g/m² minimum to ASTM A90.
 - .3 For barbed wire: to ASTM A121, Class 2.
 - .4 For other fittings: to ASTM A123/A123M, minimum Coating Grade 85, minimum 600 g/m².

Part 3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify conditions of substrate previously installed under other Sections or Contracts are acceptable for fence and gate installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Departmental Representative.

3.2 ERECTION OF FENCE

- .1 Erect fence along lines as indicated and to CAN/CGSB-138.3.
- .2 Excavate post holes to dimensions and depth indicated.
- .3 Space line posts maximum 2.5 m apart, measured parallel to ground surface.
 - .1 Space straining posts at equal intervals not to exceed 60 m if distance between end or corner posts on straight continuous lengths of fence over reasonably smooth grade, is greater than 60 m.
 - .1 Install additional straining posts at sharp changes in grade and where directed by Departmental Representative.
 - .2 Install corner post where change in alignment exceeds 10 degrees.
 - .3 Install end posts at end of fence and at buildings.
 - .1 Install gate posts on both sides of gate openings.
- .4 Place concrete in post holes then embed posts into concrete to depths indicated.
 - .1 Extend concrete 50 mm above ground level and slope to drain away from posts.
 - .2 Brace to hold posts in plumb position and true to alignment and elevation until concrete has set.
- .5 Install fence fabric after concrete has cured, minimum of 5 days.
- .6 Wire mesh shall be continuous from top to bottom and shall be applied on the inside of the posts.
- .7 Install brace between end and gate posts and nearest line post, placed in centre of panel and parallel to ground surface.
 - .1 Install braces on both sides of corner and straining posts in similar manner.
- .8 Install overhang tops and caps.
- .9 Install top and bottom rail between posts and fasten securely to posts with waterproof caps.
- .10 Fence fabric shall be pulled taut before fixing in place. Tautness when fixed in place is to be established by pull tests. The application of a 12 kg perpendicular pull at midpoint of the mesh panel shall show a displacement of no more than 30 mm from the fence at rest plane.

- .11 Fasten fence fabric to end, corner, gate and straining posts with tension bar secured to post with tension bar bands spaced at 300 mm intervals.
 - .1 Knuckled selvedge at bottom.
 - .2 Twisted selvedge at top.
- .12 Secure fabric to top rails, line posts and bottom rail with tie wires at 300 mm intervals. Give tie wires minimum two twists.
- .13 Secure bottom rail to ground barrier with galvanized anchor clamp.
- .14 Stretch 3 strands of barbed wire taut over extension arms with top strand 305 mm above fabric, secure to end and gate posts with bands. Install barbed wire strands and clip securely to lugs of each projection.
- .15 Secure barbed tape concertina to barbed wire with wire ties at 130 mm spacing, maximum tape separation 230 mm.
- .16 Install grounding rods as indicated.

3.3 INSTALLATION OF SLIDING GATES AND SWING GATES

- .1 Install gates in locations as indicated.
- .2 Level ground between gate posts and set gate bottom approximately 40 mm above ground surface.
- .3 Install gate stops where indicated.
- .4 Install provisions including reinforcement for lockset.

3.4 TOUCH UP

- .1 Clean damaged surfaces with wire brush removing loose and cracked coatings. Apply two coats of organic zinc-rich paint to damaged areas.
 - .1 Pre-treat damaged surfaces according to manufacturers' instructions for zinc-rich paint.

3.5 GROUNDING

- .1 Install grounding rods as indicated or directed.

3.6 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
 - .1 Clean and trim areas disturbed by operations. Dispose of surplus excavated material.
- .3 Waste Management: separate waste materials for reuse and recycling.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 31 14 13 Soil Stripping and Stockpiling.

1.2 REFERENCES

- .1 Agriculture and Agri-Food Canada
 - .1 The Canadian System of Soil Classification, Third Edition, 1998.
- .2 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 833-R-06-004, May 2007, Developing Your Stormwater Pollution Prevention Plan - A Guide for Construction Sites.
- .3 Canadian Nursery Landscape Association (CNLA)
 - .1 Canadian Standards for Nursery Stock, 8th Edition, 2006.
- .4 Ontario Provincial Standard Specification (OPSS)
 - .1 OPSS 802 (November 2010) Construction Specification for Topsoil

1.3 DEFINITIONS

- .1 Compost:
 - .1 Mixture of soil and decomposing organic matter used as fertilizer, mulch, or soil conditioner.
 - .2 Compost is processed organic matter containing 40% or more organic matter as determined by Walkley-Black or Loss On Ignition (LOI) test.
 - .3 Product must be sufficiently decomposed (i.e. stable) so that any further decomposition does not adversely affect plant growth (C:N ratio below 25), and contain no toxic or growth inhibiting contaminants.
 - .4 Composed bio-solids to: CCME Guidelines for Compost Quality.

1.4 SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00.
- .2 Quality control submittals:
 - .1 Soil testing: submit certified test reports showing compliance with specified performance characteristics and physical properties as described in PART 2 - SOURCE QUALITY CONTROL.
 - .2 Certificates: submit product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.
- .2 Divert unused soil amendments from landfill to official hazardous material collections site approved by Departmental Representative.
- .3 Do not dispose of unused soil amendments into sewer systems, into lakes, streams, onto ground or in locations where it will pose health or environmental hazard.

Part 2 PRODUCTS

2.1 TOPSOIL

- .1 Topsoil to conform to OPSS 802
 - .1 Contain no toxic elements or growth inhibiting materials.
 - .2 Finished surface free from:
 - .1 Debris and stones over 50 mm diameter.
 - .2 Course vegetative material, 10 mm diameter and 100 mm length, occupying more than 2% of soil volume.
 - .3 Consistence: friable when moist.

2.2 SOIL AMENDMENTS

- .1 Fertilizer:
 - .1 Fertility: major soil nutrients present in following amounts:
 - .2 Nitrogen (N): 20 to 40 micrograms of available N per gram of topsoil.
 - .3 Phosphorus (P): 40 to 50 micrograms of phosphate per gram of topsoil.
 - .4 Potassium (K): 75 to 110 micrograms of potassium per gram of topsoil.
 - .5 Calcium, magnesium, sulfur and micro-nutrients present in balanced ratios to support germination and/or establishment of intended vegetation.
 - .6 Ph value: 6.5 to 8.0.
- .2 Peatmoss:
 - .1 Derived from partially decomposed species of Sphagnum Mosses.
 - .2 Elastic and homogeneous, brown in colour.
 - .3 Free of wood and deleterious material which could prohibit growth.
 - .4 Shredded particle minimum size: 5 mm.
- .3 Sand: washed coarse silica sand, medium to course textured.
- .4 Organic matter: compost Category A in accordance with CCME PN1340, unprocessed organic matter, such as rotted manure, hay, straw, bark residue or sawdust, meeting the organic matter, stability and contaminant requirements.
- .5 Use composts meeting Category B requirements for land fill reclamation and large scale industrial applications.
- .6 Limestone:
 - .1 Ground agricultural limestone.

- .2 Gradation requirements: percentage passing by weight, 90% passing 1.0 mm sieve, 50% passing 0.125 mm sieve.
- .7 Fertilizer: industry accepted standard medium containing nitrogen, phosphorous, potassium and other micro-nutrients suitable to specific plant species or application or defined by soil test.

2.3 SOURCE QUALITY CONTROL

- .1 Advise Departmental Representative of sources of topsoil to be utilized with sufficient lead time for testing.
- .2 Contractor is responsible for amendments to supply topsoil as specified.
- .3 Soil testing by recognized testing facility for PH, P and K, and organic matter.
- .4 Testing of topsoil will be carried out by testing laboratory designated by Departmental Representative.
- .1 Soil sampling, testing and analysis to be in accordance with Provincial standards.

Part 3 EXECUTION

3.1 PREPARATION OF EXISTING GRADE

- .1 Verify that grades are correct.
 - .1 If discrepancies occur, notify Departmental Representative and do not commence work until instructed by Departmental Representative.
- .2 Grade soil, eliminating uneven areas and low spots, ensuring positive drainage.
- .3 Remove debris, roots, branches, stones in excess of 50 mm diameter and other deleterious materials.
 - .1 Remove soil contaminated with calcium chloride, toxic materials and petroleum products.
 - .2 Remove debris which protrudes above surface.
 - .3 Dispose of removed material off site.

3.2 PLACING AND SPREADING OF TOPSOIL/PLANTING SOIL

- .1 Place topsoil after Departmental Representative has accepted subgrade.
- .2 Spread topsoil in uniform layers not exceeding 150 mm.
- .3 For sodded areas keep topsoil 15 mm below finished grade.
- .4 Spread topsoil [as indicated] to following minimum depths after settlement.
 - .1 100 mm for seeded areas.
 - .2 100 mm for sodded areas.
- .5 Manually spread topsoil/planting soil around trees, shrubs and obstacles.

3.3 SOIL AMENDMENTS

- .1 Commercial processing and thorough mixing of the growing medium components shall be done thoroughly by a mechanized screening process. No hand mixing shall occur. The resulting product shall be homogeneous mixture having the required properties throughout. Product shall not be stored for excessive periods if a fertilizer component has been mixed.
- .2 Contaminations of components or finished media shall be avoided by keeping amendments in closed bags or by covering outdoor piles.
- .3 Mixes containing a significant amount of peat moss shall not be permitted to dry out. The moisture content of the peat moss at the time of mixing shall not be less than 60% to 75%.
- .4 Growing medium shall be moist (25% to 75% of field capacity) but not wet, muddy or frozen when placed.

3.4 FINISH GRADING

- .1 Grade to eliminate rough spots and low areas and ensure positive drainage.
 - .1 Prepare loose friable bed by means of cultivation and subsequent raking.
- .2 Consolidate topsoil to required bulk density using equipment approved by Departmental Representative.
 - .1 Leave surfaces smooth, uniform and firm against deep footprinting.

3.5 ACCEPTANCE

- .1 Departmental Representative will inspect and test topsoil in place and determine acceptance of material, depth of topsoil and finish grading.

3.6 CLEANING

- .1 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

END OF SECTION

Part 1 GENERAL

1.1 RELATED SECTIONS

- .1 32 91 19.13 Topsoil Placement and Grading

1.2 REFERENCES

- .1 Ontario Provincial Standard Specification (OPSS)
 - .1 OPSS 803 (November 2010) Construction Specification for Sodding.

1.3 ADMINISTRATIVE REQUIREMENTS

- .1 Scheduling:
 - .1 Schedule sod laying to coincide with preparation of soil surface.
 - .2 Schedule sod installation when frost is not present in ground.

1.4 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for sod, and include product characteristics, performance criteria, physical size, finish and limitations
- .3 Certificates: submit product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements of seed mix, seed purity, and sod quality.
- .4 Test Reports: submit certified test reports showing compliance with specified performance characteristics and physical properties of seed mix, seed purity, and sod quality.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 and with manufacturer's written instructions.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Number One Turf Grass Nursery Sod: sod that has been especially sown and cultivated in nursery fields as turf grass crop.
 - .1 Turf Grass Nursery Sod types:
 - .1 Number One Kentucky Bluegrass Sod: Nursery Sod grown solely from seed of cultivars of Kentucky Bluegrass, containing not less than 50% Kentucky Bluegrass cultivars.

2.2 SOURCE QUALITY CONTROL

- .1 Obtain written approval from Departmental Representative of sod at source.
- .2 When proposed source of sod is approved, use no other source without written authorization from Departmental Representative.

Part 3 EXECUTION

3.1 PREPARATION

- .1 Verify that grades are correct and prepared in accordance with Section 32 91 19.13. If discrepancies occur, notify Departmental Representative and commence work when instructed by Departmental Representative.
- .2 Do not perform work under adverse field conditions such as frozen soil, excessively wet soil or soil covered with snow, ice, or standing water.
- .3 Fine grade surface free of humps and hollows to smooth, even grade, surface to drain naturally.
- .4 Remove and dispose of weeds; debris; stones; soil contaminated by oil, gasoline and other deleterious materials; in accordance with Section 01 74 20.

3.2 SOD PLACEMENT

- .1 Ensure sod placement is done under supervision of certified Landscape Planting Supervisor.
- .2 Lay sod within 24 hours of being lifted if air temperature exceeds 20 degrees C.
- .3 Lay sod sections in rows, joints staggered. Butt sections closely without overlapping or leaving gaps between sections. Cut out irregular or thin sections with sharp implements.
- .4 Roll sod as directed by Departmental Representative. Provide close contact between sod and soil by light rolling. Use of heavy roller to correct irregularities in grade is not permitted.

3.3 SOD PLACEMENT ON SLOPES AND PEGGING

- .1 Install and secure geotextile fabric in areas indicated, in accordance with manufacturer's instructions.
- .2 Start laying sod at bottom of slopes.

3.4 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
 - .2 Keep pavement and area adjacent to site clean and free from mud, dirt, and debris at all times.

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.

- .1 Clean and reinstate areas affected by Work.

3.5 PROTECTION BARRIERS

- .1 Protect newly sodded areas from deterioration as directed by Departmental Representative.
- .2 Remove protection as directed by Departmental Representative.

3.6 MAINTENANCE DURING ESTABLISHMENT PERIOD

- .1 Perform following operations from time of installation until acceptance.
 - .1 Water sodded areas in sufficient quantities and at frequency required to maintain optimum soil moisture condition to depth of 75 to 100 mm.
 - .2 Cut grass to 50 mm when or prior to it reaching height of 75 mm.
 - .3 Maintain sodded areas weed free.
 - .4 Temporary barriers or signage to be maintained where required to protect newly established sod.

3.7 ACCEPTANCE

- .1 Turf Grass Nursery Sod areas will be accepted by Departmental Representative provided that:
 - .1 Sodded areas are properly established.
 - .2 Sod is free of bare and dead spots.
 - .3 Sodded areas have been cut minimum 2 times prior to acceptance.
- .2 Areas sodded in fall will be accepted in following spring one month after start of growing season provided acceptance conditions are fulfilled.
- .3 When environmental conditions allow, all sodded areas showing shrinkage cracks shall be top-dressed and seeded with a seed mix matching the original.

3.8 MAINTENANCE DURING WARRANTY PERIOD

- .1 Perform following operations from time of acceptance until end of warranty period:
 - .1 Water sodded areas at weekly intervals to obtain optimum soil moisture conditions to depth of 100 mm.
- .2 Repair and resod dead or bare spots to satisfaction of Departmental Representative.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Materials and installation for constructing new outfall structures, precast and cast-in-place maintenance holes and catch basins.

1.2 RELATED SECTIONS

- .1 Section 31 23 33.01 - Excavation, Trenching and Backfilling.
- .2 Section 33 41 00 – Storm Utility Drainage Piping.

1.3 MEASUREMENT PROCEDURES

- .1 All references to Measurement for Payment referred to in the referenced OPSS are to be disregarded and do not apply to this contract.
- .2 Shoring, bracing, cofferdams, underpinning and de-watering of excavation will not be measured separately for payment.

1.4 REFERENCES

- .1 American Society for Testing and Materials (ASTM International)
 - .1 ASTM A48/A48M-03(2012), Standard Specification for Gray Iron Castings.
 - .2 ASTM A123/A123M-13, Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products.
 - .3 ASTM C136-06, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .4 ASTM C139-11, Standard Specification for Concrete Masonry Units for Construction of Catch Basins and Manholes.
 - .5 ASTM C478M-09, Standard Specification for Precast Reinforced Concrete Manhole Sections (Metric).
 - .6 ASTM C618-12, Standard Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete.
 - .7 ASTM D698-07e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³ (600 kN-m/m³)).
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 Canadian Standards Association (CSA International)
 - .1 CAN/CSA-A3000-13, Cementitious Materials Compendium. Includes:
 - .2 CSA-A23.1-09/A23.2-09 R2014, Concrete materials and methods of concrete construction/Test methods and standard practices for concrete.
 - .3 CSA-A165 Series-04, CSA Standards on Concrete Masonry Units.
 - .4 CAN/CSA-G30.18-09, Carbon steel bars for concrete reinforcement.

- .4 Gouvernement du Québec, Ministère des Transports
 - .1 Cahier des charges et devis généraux (CCDG) - 2015.
- .5 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS 407 (November 2007), Construction Specification for Maintenance Hole, Catch Basin, Ditch Inlet and Valve Chamber Installation.
 - .2 OPSS 408 (November 2014), Construction Specifications for Adjusting or Rebuilding Maintenance Holes, Catch Basins, Ditch Inlets and Valve Chambers.
 - .3 OPSS.MUNI 1350 (November 2014), Material Specification for Concrete – Materials and Production
 - .4 OPSS 1351(November 2009), Material Specification for Precast Reinforced Concrete Components for Maintenance Holes, Catch Basins, Ditch Inlets and Valve Chambers.

1.5 SUBMITTALS

- .1 Submittals in accordance with Section 01 33 00.
- .2 Submit manufacturer's test data and certification at least 4 weeks prior to beginning Work. Include manufacturer's drawings, information and shop drawings where pertinent.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate and recycle waste materials in accordance with Section 01 74 20.
 - .2 Divert unused metal and wiring materials from landfill to metal recycling facility as approved by Departmental Representative.
 - .3 Divert unused concrete materials from landfill to local facility as approved by Departmental Representative.
 - .4 Divert unused aggregate materials from landfill to facility for reuse as approved by Departmental Representative.
 - .5 Fold up metal banding, flatten and place in designated area for recycling.
-

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Concrete reinforcement: in accordance with OPSS.MUNI 1440 Material Specification for Steel Reinforcement for Concrete.
- .2 Precast catch basin units: to OPSS 1351 and OPSD 705.010. Frame and cover to OPSD 400.010
- .3 Pre-cast manhole units: OPSD 701.010.
- .4 Manhole frame and cover to OPSD 401.010 Type B Open Cover.
- .5 Unshrinkable fill: in accordance with OPSS 1359 Material Specification for Unshrinkable Fill

Part 3 EXECUTION

3.1 EXCAVATION AND BACKFILL

- .1 Excavate and backfill in accordance with Section 31 23 33.01.
- .2 Obtain approval of Departmental Representative before installing, maintenance holes or catch basins.

3.2 CONCRETE WORK

- .1 Do concrete work in accordance with Section 03 30 00 and in accordance with OPSS 407 Construction Specification for Maintenance Hole, Catch Basin, Ditch Inlet And Valve Chamber Installation..
- .2 Place concrete reinforcement in accordance with Section 03 20 00.
- .3 Position metal inserts in accordance with dimensions and details as indicated.

3.3 INSTALLATION

- .1 Construct units in accordance with details indicated, plumb and true to alignment and grade.
 - .2 Complete units as pipe laying progresses. Maximum of three units behind point of pipe laying will be allowed.
 - .3 Dewater excavation to approval of Departmental Representative and remove soft and foreign material before placing concrete base.
 - .4 Cast bottom slabs directly on undisturbed ground.
 - .5 Set precast concrete base on 150 mm minimum of granular bedding compacted to 100% corrected maximum dry density.
-

- .6 Precast units:
 - .1 Set bottom section of precast unit in bed of cement mortar and bond to concrete slab or base. Make each successive joint watertight with Departmental Representative approved rubber ring gaskets, bituminous compound, cement mortar, epoxy resin cement, or combination thereof.
 - .2 Clean surplus mortar and joint compounds from interior surface of unit as work progresses.
 - .3 Plug lifting holes with precast concrete plugs set in cement mortar or mastic compound.
 - .7 For sewers:
 - .1 Place stub outlets and bulkheads at elevations and in positions indicated.
 - .2 Bench to provide a smooth U-shaped channel. Side height of channel to be 0.75 times diameter of sewer. Slope adjacent floor at 1 in 20. Curve channels smoothly. Slope invert to establish sewer grade.
 - .8 Compact granular backfill to 95% corrected maximum dry density.
 - .9 Installing units in existing systems:
 - .1 Where new unit is to be installed in existing run of pipe, ensure full support of existing pipe during installation, and install new unit as specified.
 - .2 Make joints watertight between new unit and existing pipe.
 - .3 Where deemed expedient to maintain service around existing pipes and when systems constructed under this Project are ready to be put in operation, complete installation with appropriate break-outs, removals, redirection of flows, blocking unused pipes or other necessary work.
-

- .10 Set frame and cover to required elevation on no more than three adjustment units. Parge and make smooth and watertight.
- .11 Place frame and cover on top section to elevation as indicated. If adjustment required use concrete ring.
- .12 Clean units of debris and foreign materials. Remove fins and sharp projections. Prevent debris from entering system.
- .13 Install safety platforms in maintenance holes having depth of 5 m or greater, as indicated.
- .14 Weld covers in place after installation and when approved by Departmental Representative.

3.4 ADJUSTING TOPS OF EXISTING UNITS

- .1 Remove existing gratings, frames and store for re-use at locations designated by Departmental Representative.
- .2 Sectional units:
 - .1 Raise or lower straight walled sectional units by adding or removing precast sections as required.
 - .2 Raise or lower tapered units by removing cone section, adding, removing, or substituting riser sections to obtain required elevation, then replace cone section. When amount of raise is less than 600 mm use standard maintenance hole, modoloc or grade rings.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Materials and installation for storm sewer.

1.2 RELATED SECTIONS

- .1 Section 31 23 10 - Excavating, Trenching and Backfilling.
- .2 Section 33 05 14 – Manholes and Catchbasins.
- .3 Section 33 46 16 - Sub-Drainage Piping

1.3 REFERENCES

- .1 ASTM International
 - .1 ASTM D3034-, Standard Specification for Type PSM Poly (Vinyl Chloride) (PVC) Sewer Pipe and Fittings.
 - .2 ASTM F794-, Standard Specification for Poly(Vinyl Chloride) (PVC) Profile Gravity Sewer Pipe and Fittings Based on Controlled Inside Diameter.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-M89, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .3 CSA International
 - .1 CAN/CSA-A3000-08, Cementitious Materials Compendium.
 - .2 CSA A257 Series-M92(R2009), Standards for Concrete Pipe.
 - .3 CAN/CSA-B1800-06, Thermoplastic Non-pressure Pipe Compendium - B1800 Series.
- .4 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS 407 (November 2007), Construction Specification for Maintenance Hole, Catch Basin, Ditch Inlet, and Valve Chamber Installation
 - .2 OPSS 410 (November 2013), Construction Specification for Pipe Sewer Installation in Open Cut
 - .3 OPSS 1840 (November 2006), Material Specifications for Polyethylene Pipe
 - .4 OPSS 1841 (November 2009), Material Specifications for PVC Pipe

1.4 SCHEDULING

- .1 Schedule Work to minimize interruptions to existing services and to maintain existing flow during construction.
- .2 Submit schedule of expected interruptions for approval and adhere to approved schedule.

1.5 SUBMITTALS

- .1 Submit shop drawings in accordance with Section 01 33 00 – Submittal Procedures.

- .2 Inform Departmental Representative at least 7 days prior to beginning Work, of proposed source of bedding materials and provide access for sampling.
- .3 Submit manufacturer's test data and certification at least 7 days prior to beginning Work.
- .4 Certification to be marked on pipe.
- .5 Submit to Departmental Representative 1 copy of manufacturer's installation instructions.

1.6 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with manufacturer's written instructions.
- .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
- .3 Storage and Handling Requirements:
 - .1 Store materials in accordance with manufacturer's recommendations.
 - .2 Store and protect pipes from damage.
 - .3 Replace defective or damaged materials with new.
- .4 Packaging Waste Management: remove for reuse and return by manufacturer of pallets, crates, padding and packaging materials as specified in Construction Waste Management Plan in accordance with Section 01 74 20.

Part 2 PRODUCTS

2.1 PLASTIC PIPE

- .1 Type PSM Poly Vinyl Chloride (PVC): to ASTM D3034 .
 - .1 Standard Dimensional Ratio (SDR): 35.
 - .2 Locked-in gasket and integral bell system.
 - .3 Nominal lengths: 4 m.
- .2 Corrugated polyethylene pipe: high density to CSA B182.4 or CSA B182.6 and having a stiffness of 320 kPa and smooth interior wall.

2.2 PIPE BEDDING AND SURROUND MATERIAL

- .1 Granular material in accordance with the following requirements:
 - .1 OPSS 1010, Granular A, maximum size 19 mm.
 - .2 Crushed or screened stone, gravel or sand.
 - .3 Gradations to be within limits specified when tested to ASTM C136 and ASTM C117. Sieve sizes to CAN/CGSB-8.1.
- .2 Table:

Sieve Designation (mm)	% Passing	
	Stone/Gravel	Gravel/Sand
200	-	-

75	-	-
50	-	-
38.1	-	-
25	100	-
19	-	-
12.5	65-90	100
9.5	-	-
4.75	35-55	50-100
2.00	-	30-90
0.425	10-25	10-50
0.180	-	-
0.075	0-8	0-10

- .3 Concrete mixes and materials for bedding, cradles, encasement, supports: in accordance with Section 03 30 00.

2.3 BACKFILL MATERIAL

- .1 In accordance with Section 31 23 33 and OPSS 410

Part 3 EXECUTION

3.1 PREPARATION

- .1 Clean pipes and fittings of debris and water before installation, and remove defective materials from site to approval of Departmental Representative.

3.2 TRENCHING

- .1 Do trenching Work in accordance with Section 31 23 33.01.
.2 Do not allow contents of sewer or sewer connection to flow into trench.

3.3 GRANULAR BEDDING

- .1 Place bedding in unfrozen condition.
.2 Place granular bedding material in uniform layers not exceeding 150 mm compacted thickness to depth of 300 mm above obvert of pipe.
.3 Shape bed true to grade and to provide continuous, uniform bearing surface for pipe.
.1 Do not use blocks when bedding pipes.
.4 Shape transverse depressions as required to suit joints.
.5 Compact each layer full width of bed to at least 95 % maximum density to ASTM D698.
.6 Fill excavation below bottom of specified bedding adjacent to manholes or catch basins with compacted bedding material.

3.4 INSTALLATION

- .1 When any stoppage of Work occurs, restrain pipes as directed by Departmental Representative, to prevent "creep" during down time.

- .2 Make watertight connections to manholes and catch basins.
 - .1 Use shrinkage compensating grout when suitable gaskets are not available.
- .3 Use prefabricated saddles or approved field connections for connecting pipes to existing sewer pipes.
 - .1 Joint to be structurally sound and watertight.
- .4 Temporarily plug open upstream ends of pipes with removable watertight concrete, steel or plastic bulkheads.

3.5 PIPE SURROUND

- .1 Place surround material in unfrozen condition.
- .2 Upon completion of pipe laying, and after Departmental Representative has inspected pipe joints, surround and cover pipes as indicated.
 - .1 Leave joints and fittings exposed until field testing is completed.
- .3 Hand place surround material in uniform layers not exceeding 150 mm compacted thickness as indicated.
- .4 Place layers uniformly and simultaneously on each side of pipe.
- .5 Compact each layer from pipe invert to springline of pipe to at least 95% maximum density to ASTM D698.
- .6 Compact each layer from springline of pipe to underside of backfill to at least 95% maximum density to ASTM D698.
- .7 When field test results are acceptable to Departmental Representative, place surround material at pipe joints.

3.6 BACKFILL

- .1 Place backfill material in unfrozen condition.
- .2 Place backfill material, above pipe surround, in uniform layers not exceeding 300 mm compacted thickness up to grades as indicated.
- .3 Under paving and walks, compact backfill to at least 95% maximum density to ASTM D698. In other areas, compact backfill to at least 90% maximum density to ASTM D698.

3.7 FIELD TESTS AND INSPECTIONS

- .1 Repair or replace pipe, pipe joint or bedding found defective.
- .2 Remove foreign material from sewers and related appurtenances by flushing with water.
- .3 Testing to be completed as per OPSS 410.
- .4 Repair or replace pipe, pipe joint or bedding found defective.
- .5 Television and photographic inspections:
 - .1 Carry out inspection of installed sewers by television camera, photographic camera as per OPSS 409
 - .2 Provide means of access to permit Departmental Representative to do inspections.

3.8 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11.
- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 20.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION

Part 1 GENERAL

1.1 SECTION INCLUDES

- .1 Materials and installation for constructing sub-drains with knitted sock geotextile filter material.

1.2 RELATED SECTIONS

- .1 Section 31 23 33.01 - Excavating Trenching and Backfilling.

1.3 MEASUREMENT PROCEDURES

- .1 Supply and installation of sub-drainage including, trenching, backfill, bedding, granular filter material and geotextile will be measured horizontally from manhole face to manhole face in metres of each pipe size and depth class installed.

1.4 REFERENCES

- .1 American Society for Testing and Materials International, (ASTM)
 - .1 ASTM C136-05, Standard Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .2 ASTM D698-12e1, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³ (600 kN-m/m³)).
- .2 Bureau de normalisation du Québec (BNQ)
 - .1 BNQ 3624-115, Polyethylene (PE) Pipe and Fittings-Flexible Corrugated Pipes for Drainage-Characteristics and Test Methods.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1-88, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CAN/CGSB-8.2-M88, Sieves, Testing, Woven Wire, Metric.
- .4 Canadian Standards Association (CSA International)
 - .1 CSA B1800-15, Plastic Non-pressure Pipe Compendium - B1800 Series (Consists of B181.1, B181.2, B181.3, B181.5, B182.1, B182.2, B182.4, B182.6, B182.7, B182.8 and B182.11).
 - .1 CSA B182.1-02, Plastic Drain and Sewer Pipe and Pipe Fittings.
- .5 Ontario Provincial Standard Specifications
 - .1 OPSS 405 (November 2008) Construction Specification for Pipe Sub-Drains .
 - .2 OPSS 1840 (November 2006), Material Specifications for Polyethylene Pipe
 - .3 OPSS 1841 (November 2009), Material Specifications for PVC Pipe

1.5 SUBMITTALS

- .1 Submit samples in accordance with Section 01 33 00.

- .2 Submit manufacturer's test data and certification that drain pipe materials meet requirements of this Section at least 4 weeks prior to beginning Work.

- .3 Certification to be marked on pipe.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 20.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.

Part 2 PRODUCTS

2.1 MATERIALS

- .1 Perforated plastic pipe and fittings: to CAN/CSA-B182.1. Nominal pipe sizes 100, 150 mm. Pipe to be complete with knitted sock geotextile material
- .2 Corrugated polyethylene pipe to OPSS 1840 and BNQ 3624-115. Pipe to be complete with knitted sock geotextile material.
- .3 Bedding gravel or crushed stone; hard, durable particles, graded evenly in size from 16 to 8 mm.
- .4 Granular filter material in accordance with the following requirements:
 - .1 Screened stone or gravel.

Part 3 EXECUTION

3.1 TRENCHING

- .1 Do excavating, trenching and backfilling in accordance with Section 31 23 33.01.
- .2 Place bedding material after approval of trench by Departmental Representative.

3.2 BEDDING

- .1 Place 100 mm layer of bedding material to full trench width and compact to minimum 95% of corrected maximum dry density.

3.3 INSTALLATION OF PIPE SUB-DRAINS

- .1 Lay pipe drains on prepared bed, true to line and grade with inverts smooth and free of sags or high points.
 - .1 Ensure barrel of each pipe is in contact with bed throughout full length.
- .2 Begin laying at outlet and proceed in upstream direction.
- .3 Lay perforated pipes with perforations at 4 o'clock and 8 o'clock positions.
- .4 Lay bell and spigot pipe with bell ends facing upstream.
 - .1 Do not mortar joints.
- .5 Make joints tight in accordance with manufacturer's instructions.

- .6 Make watertight connections to existing drains, new or existing manholes and catch basins where indicated or as directed by Departmental Representative.
- .7 Plug open upstream ends of pipes with watertight concrete, steel or wood bulkheads.
- .8 Surround pipe with bedding gravel and compact as directed by Departmental Representative.
- .9 Backfill remainder of trench to Section 31 23 33.01.
- .10 Do not place bedding surround and backfill materials in frozen condition.
- .11 Protect sub-drains against flotation during installation.

END OF SECTION