

PART 1 - GENERAL

- | | | |
|--|----|---|
| 1.1 REFERENCES | .1 | Section 010010 – General Instructions |
| 1.2 <u>MEASUREMENT FOR PAYMENT</u> | .1 | No measurement for payment will be made under this section. Include costs in items where required. |
| 1.3 <u>ACTION AND INFORMATIONAL SUBMITTALS</u> | .1 | Submittals: in accordance with Section 013300 - Submittal Procedures. |
| | .2 | Submit written request in advance of cutting or alteration which affects: <ul style="list-style-type: none">.1 Structural integrity of elements of project..2 Integrity of weather-exposed or moisture-resistant elements..3 Efficiency, maintenance, or safety of operational elements..4 Visual qualities of sight-exposed elements..5 Work of Departmental Representative or separate contractor. |
| | .3 | Include in request: <ul style="list-style-type: none">.1 Identification of project..2 Location and description of affected Work..3 Statement on necessity for cutting or alteration..4 Description of proposed Work, and products to be used..5 Alternatives to cutting and patching..6 Effect on Work of Departmental Representative or separate contractor..7 Written permission of affected separate contractor..8 Date and time work will be executed. |
| 1.4 <u>MATERIALS</u> | .1 | Required for original installation. |
| | .2 | Change in Materials: Submit request for substitution in accordance with Section 013300 - Submittal Procedures. |
| 1.5 <u>PREPARATION</u> | .1 | Inspect existing conditions, including elements subject to damage or movement during cutting and patching. |
| | .2 | After uncovering, inspect conditions affecting performance of Work. |
| | .3 | Beginning of cutting or patching means acceptance of existing conditions. |
| | .4 | Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage. |
| | .5 | Provide protection from elements for areas which are to be exposed by uncovering work; maintain excavations free of water. |
| | .6 | Before commencing work, establish location and extent of all buried and underground utilities and service lines in area of Work and notify Departmental Representative of findings. |

1.6 EXECUTION

- .1 Execute cutting, fitting, and patching including excavation and fill, to complete Work.
- .2 Fit several parts together, to integrate with other Work.
- .3 Remove and replace defective and non-conforming Work.
- .4 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .5 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .6 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .7 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .8 Restore work with new products in accordance with requirements of Contract Documents.
- .9 Fit Work to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.

1.7 WASTE MANAGEMENT AND
DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 017421 - Construction/Demolition Waste Management And Disposal.

PART 2 - PRODUCTS

NOT USED.

PART 3 - EXECUTION

NOT USED.

***** END OF SECTION *****