

## **PART 1 - GENERAL**

### **1.1 REFERENCES**

- .1 CSA International
  - .1 CSA C22.2 No.42-10, General Use Receptacles, Attachment Plugs and Similar Devices.
  - .2 CAN/CSA C22.2 No.42.1-00(R2009), Cover Plates for Flush-Mounted Wiring Devices (Bi-national standard, with UL 514D).
  - .3 CSA C22.2 No.55-M1986(R2012), Special Use Switches.
  - .4 CSA C22.2 No.111-10, General-Use Snap Switches (Bi-national standard, with UL 20).

### **1.2 ACTION AND INFORMATIONAL SUBMITTALS**

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
  - .1 Submit manufacturer's instructions, printed product literature and data sheets for wiring devices and include product characteristics, performance criteria, physical size, finish and limitations.

### **1.3 CLOSEOUT SUBMITTALS**

- .1 Submit in accordance with Section 01 78 00 - Closeout Submittals.
- .2 Operation and Maintenance Data: submit operation and maintenance data for wiring devices for incorporation into manual.

### **1.4 DELIVERY, STORAGE AND HANDLING**

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
  - .2 Delivery and Acceptance Requirements: deliver materials to site in original factory packaging, labelled with manufacturer's name and address.
  - .3 Storage and Handling Requirements:
    - .1 Store materials off ground indoors and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
    - .2 Store and protect wiring devices from nicks, scratches, and blemishes.
    - .3 Replace defective or damaged materials with new.
-

- .4 Packaging Waste Management: remove for reuse and return of packaging materials as specified in Construction Waste Management Plan Waste Reduction Workplan in accordance with Section 01 74 21 - Construction/ Demolition Waste Management and Disposal.

## **1.5 MEASUREMENT FOR PAYMENT**

- .1 No separate measurement for payment shall be made for items under this section. Include costs incidental in the Lump Sum Amount of work on the Combined Price Form.

## **PART 2 - PRODUCTS**

### **2.1 SWITCHES**

- .1 20 A, 120 V, single pole, switches to: CSA C22.2 No.55 and CSA C22.2 No.111.
- .2 Manually-operated general purpose AC switches with following features:
  - .1 Terminal holes approved for No. 10 AWG wire.
  - .2 Silver alloy contacts.
  - .3 Urea or melamine moulding for parts subject to carbon tracking.
  - .4 Suitable for back and side wiring.
  - .5 Ivory toggle.
- .3 Toggle operated fully rated for tungsten filament and fluorescent lamps, and up to 80% of rated capacity of motor loads and heating loads.
- .4 Switches of one manufacturer throughout project.

### **2.2 RECEPTACLES**

- .1 Duplex receptacles, CSA type 5-20R, 125 V, 20 A, U ground, to: CSA C22.2 No.42 with following features:
    - .1 Ivory urea moulded housing.
    - .2 Suitable for No. 10 AWG for back and side wiring.
    - .3 Break-off links for use as split receptacles.
    - .4 Eight back wired entrances, four side wiring screws.
    - .5 Triple wipe contacts and rivetted grounding contacts.
  - .2 Other receptacles with ampacity and voltage as indicated.
  - .3 Receptacles of one manufacturer throughout project.
-

### **2.3 COVER PLATES**

- .1 Cover plates for wiring devices to: CSA C22.2 No.42.1.
- .2 Plastic ivory cover plates, thickness 2.5 mm for wiring devices mounted in flush-mounted outlet box.
- .3 Cover plates from one manufacturer throughout project.

## **PART 3 - EXECUTION**

### **3.1 INSTALLATION**

- .1 Switches:
  - .1 Install single throw switches with handle in "UP" position when switch closed.
  - .2 Install switches in gang type outlet box when more than one switch is required in one location.
  - .3 Mount toggle switches at height in accordance with Section 26 05 00 - Common Work Results for Electrical unless indicated otherwise.
- .2 Receptacles:
  - .1 Install receptacles in gang type outlet box when more than one receptacle is required in one location.
  - .2 Mount receptacles at height in accordance with Section 26 05 00 - Common Work Results for Electrical unless indicated otherwise.
  - .3 Where split receptacle has one portion switched, mount vertically and switch upper portion.
- .3 Cover plates:
  - .1 Install suitable common cover plates where wiring devices are grouped.

### **3.2 WIRING**

- .1 Connect wiring devices and switches to power circuit.
- .2 Utilize an individual, dedicated neutral conductor for each power circuit. Common or shared neutrals are not permitted.

### **3.3 CLEANING**

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
    - .1 Leave Work area clean at end of each day.
  - .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and
-

equipment in accordance with Section 01 74 11 - Cleaning.

- .3 Waste Management: separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
  - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

### **3.4 PROTECTION**

- .1 Protect installed products and components from damage during construction.
- .2 Protect stainless steel cover plate finish with paper or plastic film until painting and other work is finished.
- .3 Repair damage to adjacent materials caused by wiring device installation.