

Part 1 General

1.1 SUMMARY

- .1 Section Includes:
 - .1 Materials and installation for low voltage control system designed to provide remote switching of lighting loads by use of:
 - .1 Low voltage momentary contact switches.
 - .2 Sustainable requirements for construction and verification.

1.2 SUBMITTALS

- .1 Refer to Division 1 for submittals.

1.3 DELIVERY, STORAGE, AND HANDLING

- .1 Packing, shipping, handling and unloading:
 - .1 Deliver, store and handle in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Deliver, store and handle materials in accordance with manufacturer's written instructions.

Part 2 Products

2.1 MATERIALS

- .1 Control system: To match existing.

2.2 REMOTE CONTROL SWITCHES

- .1 Single pole, double throw, momentary contact, standard duty, rated 15 A, 25 V, double push-button action with pilot lights.
- .2 Douglas 2-wire HID low voltage switches or approved equivalent (to match existing).

2.3 LOW VOLTAGE RELAYS

- .1 Electrically operated by momentary impulse, mechanically latched until activated.
- .2 Two coil solenoid type with one coil to close relay contacts and one coil to open relay contacts.
- .3 Operating voltage: 24 V, AC.
- .4 Load contacts: 20 A, 120 V, AC.

- .5 Auxiliary contacts for pilot light.
- .6 Coloured pre-stripped leads.
- .7 Douglas 2-wire HID low voltage relays or approved equivalent (to match existing).

2.4 CONTROL TRANSFORMER

- .1 Low voltage power Class 2, input 120 V, AC, 60 Hz, output 20 VA at 24 V.

Part 3 Execution

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheet.

3.2 INSTALLATION

- .1 Switches:
 - .1 Install switches in gang type outlet box when more than one switch is required in one location.
 - .2 Mount switches at height in accordance with Section 26 05 00 - Common Work Results - Electrical.
- .2 Locate and install all other equipment in accordance with manufacturer's recommendations and as indicated.

3.3 FIELD QUALITY CONTROL

- .1 Site Tests:
 - .1 Perform tests in accordance with Section 26 05 00 - Common Work Results - for Electrical.
- .2 Actuate control units in presence of Departmental Representative to demonstrate lighting circuits are controlled as designated.
- .3 Manufacturer's Field Services:
 - .1 Obtain written report from manufacturer verifying compliance of Work, in handling, installing, applying, protecting and cleaning of product and submit Manufacturer's Field Reports as described in PART 1 - SUBMITTALS.

3.4 CLEANING

- .1 Upon completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION