

Approved: 2003-12-31

Part 1 General

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 - Construction/Demolition Waste Management And Disposal.
- .3 Section 01 78 00 - Closeout Submittals.
- .4 Section 06 20 00 - Finish Carpentry.
- .5 Section 06 40 00 - Architectural Woodwork.
- .6 Section 08 14 16 - Flush Wood Doors.

1.2 REFERENCES

- .1 American National Standards Institute (ANSI)
 - .1 ANSI 208.1-99, Particleboard.
 - .2 ANSI A208.2-02, Medium Density Fibreboard (MDF) for Interior Applications.
- .2 American Society for Testing and Materials International, (ASTM)
 - .1 ASTM D2832-92(R1999), Standard Guide for Determining Volatile and Nonvolatile Content of Paint and Related Coatings.
 - .2 ASTM D5116-97, Standard Guide For Small-Scale Environmental Chamber Determinations of Organic Emissions From Indoor Materials/Products.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-71.20-M88, Adhesive, Contact, Brushable.
- .4 Canadian Standards Association (CSA International)
 - .1 CSA O112-M1977(R2001), Standards for Wood Adhesives.
 - .2 CSA O112.5-1.1-Series-M-1977(R2001), Urea Resin Adhesives for Wood (Room- and High-Temperature Curing).
 - .3 CSA O112.7-1.1-Series M-1977(R2001), Resorcinol and Phenol-Resorcinol Resin Adhesives for Wood (Room- and Intermediate-Temperature Curing).
 - .4 CSA O121-M1978(R1998), Douglas Fir Plywood.
 - .5 CAN/CSA O141-91(R1999), Softwood Lumber.
 - .6 CSA O151-M1978(R1998), Canadian Softwood Plywood.
 - .7 CSA O153-M1980(R1998), Poplar Plywood.
- .5 Environmental Choice Program (EPC)
 - .1 CCD-044-95, Adhesives.
 - .2 CCD-045-95, Sealants and Caulking Compounds.

- .3 CCD-048-95, Surface Coatings Recycled Water-borne.
- .4 CCD-047a-98, Paints - Surface Coatings.
- .5 CCD-048b-98, Stains - Surface Coatings.
- .6 CCD-048c-98, Varnishes - Surface Coatings.
- .6 National Electrical Manufacturers Association (NEMA)
 - .1 NEMA LD3-2000, High Pressure Decorative Laminates.

1.3 SUBMITTALS

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data sheet in accordance with Section 01 33 00 - Submittal Procedures.
 - .2 Submit two copies of WHMIS MSDS - Material Safety Data Sheets in accordance with Section 01 33 00 - Submittal Procedures. Indicate VOC's for adhesives, solvents and cleaners.
- .2 Samples:
 - .1 Submit samples in accordance with Section 01 33 00- Submittal Procedures.
 - .2 Submit duplicate samples of joints, edging, cutouts and postformed profiles.
- .3 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.
- .4 Closeout Submittals:
 - .1 Provide maintenance data for laminate work for incorporation into manual specified in Section 01 78 00 - Closeout Submittals.

1.4 QUALITY ASSURANCE

- .1 Test Reports: Certified test reports showing compliance with specified performance characteristics and physical properties.
- .2 Certificates: Product certificates signed by manufacturer certifying materials comply with specified performance characteristics and criteria and physical requirements.
- .3 Pre-installation Meetings: Conduct pre-installation meeting to verify project requirements, manufacturer's installation instructions and manufacturer's warranty requirements.

1.5 DELIVERY, STORAGE, AND HANDLING

- .1 Storage and Protection:
 - .1 Deliver, handle, store and protect materials of this section in accordance with Section 01 61 00 - Common Product Requirements.
 - .2 Maintain relative humidity between 25 and 60% at 22 degrees C during storage and installation.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Divert reusable materials for reuse at nearest used building materials facility or similar type facility.
- .2 Divert unused caulking, sealants, surface coatings and adhesive materials from landfill through disposal at a special wastes depot.

Part 2 Products

2.1 MATERIALS

- .1 Laminated plastic for flatwork: to NEMA LD 3.
 - .1 Type: General purpose.
 - .2 Grade: HGS.
 - .3 Size: 1.1 mm thick.
 - .4 Colour: multilayered.
 - .5 Pattern: to be selected by PWGSC Representative from manufacturer's standard range.
 - .6 Finish: to be selected by PWGSC Representative from manufacturer's standard range.
- .2 Plywood core: to CSA O121 CSA O151 CSA O153 solid two sides, Grade B, 19 mm thick.
- .3 Laminated plastic adhesive: contact adhesive to CAN/CGSB-71.20.
 - .1 Test for acceptable VOC emissions in accordance with ASTM D2369 and ASTM D2832.
- .4 Sealer: water resistant sealer or glue acceptable to laminate manufacturer.
 - .1 Test for acceptable VOC emissions in accordance with ASTM D2369 and ASTM D2832.
- .5 Draw bolts and splines: as recommended by fabricator.

2.2 FABRICATION

- .1 Comply with NEMA LD 3, Annex A.
- .2 Obtain governing dimensions before fabricating items which are to accommodate or abut appliances, equipment and other materials.
- .3 Ensure adjacent parts of continuous laminate work match in colour and pattern.
- .4 Veneer laminated plastic to core material in accordance with adhesive manufacturer's instructions. Ensure core and laminate profiles coincide to provide continuous support and bond over entire surface. Use continuous lengths up to 3000 mm. Keep joints 600 mm from sink cutouts.

- .5 Use straight self-edging laminate strip for flatwork to cover exposed edge of core material. Chamfer exposed edges uniformly at approximately 20 degrees. Do not mitre laminate edges.
- .6 Apply laminate backing sheet to reverse side of core of plastic laminate work.

Part 3 Execution

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: Comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.

3.2 INSTALLATION

- .1 Install work plumb, true and square, neatly scribed to adjoining surfaces.
- .2 Make allowances around perimeter where fixed objects pass through or project into laminated plastic work to permit normal movement without restriction.
- .3 Use draw bolts and splines in countertop joints. Maximum spacing 450 mm on centre, 75 mm from edge. Make flush hairline joints.
- .4 Provide cutouts for inserts, grilles, appliances, outlet boxes and other penetrations. Round internal corners, chamfer edges and seal exposed core.
- .5 At junction of laminated plastic counter back splash and adjacent wall finish, apply small bead of sealant.
- .6 Site apply laminated plastic to units as indicated. Adhere laminated plastic over entire surface. Make corners with hairline joints. Use full sized laminate sheets. Make joints only where approved. Slightly bevel arrises.
- .7 For site application, offset joints in plastic laminate facing from joints in core.

3.3 PROTECTION

- .1 Cover finished laminated plastic wood metallic veneered surfaces with heavy kraft paper or put in cartons during shipment. Protect installed laminated surfaces by approved means. Do not remove until immediately before final inspection.

3.4 CLEANING

- .1 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .2 Perform care and cleaning with NEMA LD 3, Annex B.
- .3 Remove traces of primer, caulking, epoxy and filler materials; clean doors and frames.

END OF SECTION