

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
1	AIRR-01	Air Compressor - Portable SEE AIRR-04 and SHEL-15	<ul style="list-style-type: none"> - To be compatible with AIRR-04 and SHEL-15 - Oil-free pump - 120V motor - 10 amps - Minimum 94.6 liter (2.5 gal) hot dog style tank - Water drain valve and rubber feet - Minimum 150 psi max tank pressure - Minimum 2.6 SCFM @ 90 psi as per ISO 1217 - Maximum weight 11 kg (24 lbs) - Portable - No specific colour required 	C2025 150 psi, 2.5 gal Oil-Free Hot dog Compressor SEE AIRR-04 and SHEL-15	Porter-Cable	Colour: Red	1	YES	NO
2	AIRR-02	Commercial Portable Air Blower	<ul style="list-style-type: none"> - Rotationally molded polyethylene construction with carrying handle and cord wrap - Motor: minimum 0.5 hp (373 watts), continuous duty, capacitor start, thermally protected, four point motor mount - Fan speeds: High – 1600 rpm minimum; Medium – 1350 rpm minimum; Low – 1050 rpm minimum - Three (3) speed airflow: High – 3000 cfm (84 m3/min.) minimum; Medium – 2500 cfm (70 m3/min.) minimum; Low – 2000 cfm (56 m3/min.) minimum - Power Cable: 7.3-7.9m (24-26 ft.) 16/3 SJTW with three-wire molded plug - 120 volt AC, 60 Hz - Weight: maximum 15 kg (33.5 lbs) - UL (Underwriters Laboratories) Listed to U.S. and Canadian safety standards - Portable - No specific colour required 	Air Mover 3 (AM3)	Windsor Commercial Cleaning Equipment	Colour: Blue	4	YES	NO
3	AIRR-03	Air Compressor - Portable	<ul style="list-style-type: none"> - Commercial Grade - 115 Volt, 5 hp - Minimum 20 gal compressor, 125 max. psi, 7.8CFM @ 90 psi - Stainless steel valve and cast iron pumps - Manual reset for overload protection - Pressure switch with on/off and universal coupler - Belt driven - Flywheels design - Portable - No specific colour required 	No Listed Product Specified.			1	YES	NO
4	AIRR-04	Portable Air Compressor - Hose SEE AIRR-01 and AIRR-05	<ul style="list-style-type: none"> - To be compatible with AIRR-01 and AIRR-05 - Size: minimum 10mm (3/8") diameter x 14.9-15.5m (49-51ft) length - Protective cover included - Heavy-duty spiral reinforcement - Abrasion resistant, non-marring - 6.35mm (1/4") NPT (National Pipe Thread) male brass fittings with ferrules on both ends - No specific colour required 	60250 3/8" by 50ft Air Hose	Porter-Cable	Vinyl Colour: Red	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
5	AIRR-05	Air Compressor - Spring Retractable Hose Reel SEE AIRR-04	<ul style="list-style-type: none"> - To be compatible with AIRR-04 - Spring retractable hose reel - Must be wall mountable - Powder coated finish for corrosion resistance - Swivel design - Hose to be plumbed into the base - De-clutching arbor - Quiet speed latch - Steel construction - Can accommodate a hose of minimum 10mm (3/8") diameter and 14.9-15.5m (49-51ft) long. - To accommodate pressure of minimum 300 psi - Size: 406-457mm (16-18") W x 127-178mm (5-7") D x 432-483mm (17-19") H - No specific colour required 	5605 OLP	Reelcraft	Colour: Red	1	YES	NO
6	BROM-01	Broom - Includes Head and Handle SEE BROM-03	<ul style="list-style-type: none"> - To be compatible with BROM-03 Handle: <ul style="list-style-type: none"> - Aluminum with nylon tip - 1194-1245mm (47-49") long handle Head: <ul style="list-style-type: none"> - Fine synthetic fibre bristles - Fibres to be fused into the block - Water and chemical resistant - No specific colour required 	Broom Head: Trailblazer Upright Broom Head #772 1219mm (48") L Broom Handle: Aluminum Handle with Threaded Tip #2408	Atlas Graham	Colour: Grey	18	YES	NO
7	BROM-03	Dust Pan - Long Handle SEE BROM-01	<ul style="list-style-type: none"> - To be compatible with BROM-01 - Adjustable handle grip - Heavy-duty rear wheels - Size: 279-330mm (11-13") x 305-356mm (12-14") x 102-152mm (4-6") - Handle length: minimum 762mm (30") - No specific colour required 	FG253100BLA Size: 287mm (11.3") x 325mm (12.8") x 127mm (5")	Rubbermaid Commercial Products	Colour: Black	18	YES	NO
8	CAGE-01	Cage - High Open Wire Mesh Lockable Cage with one (1) adjustable shelf	<ul style="list-style-type: none"> - Must fit within building elevator dimensions: 914mm (3'-0") W x 2134mm (7") L x and 1981mm (6'-6") H - Heavy-duty chrome construction - Open wire mesh - Lockable - Includes aluminum dolly with wrap-around bumpers - Size: 584-635mm (23-25") L x 889-940mm (35-37") D x 1499-1549mm (59-61") H - 114-140mm (4.5-5.5") diameter casters - two (2) fixed and two (2) swivel - One (1) adjustable chrome shelf - Finish: Chrome 	Heavy-Duty Model - Chrome SEC53LC Caster: B5P/B5PB Size: 610mm (24") L x 914mm (36") D x 1739mm (68 7/16") H Accessories: A2448NC Intermediate Shelf - One (1) adjustable shelf	Metro Storage Systems	Chrome	19	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
9	CART-01	Cart - Cleaning Includes Zippered Yellow Bag	<ul style="list-style-type: none"> - All building components must fit within the building elevator dimension requirement: 914mm (3'-0") W, 1981mm (6'-6") L, and 1981mm (6'-6") H - To include heavy duty zippered vinyl bag - Three (3) shelves - Minimum 5 cu.ft. of storage space - Fits a 889mm (35") x 1270mm (50") garbage bag - Locking bucket attachment - Includes two (2) removable minimum 9.4 liter (10 quart) caddies - Rubber tool grips to hold handles upright - Lobby dust pan and vacuum holder - Non-rusting aluminum and structural web plastic construction - Comfort grip cart handle - Hooks to hold up to four (4) safety signs - Size: 1245-1295mm (49-51") L x 533-584mm (21-23") D x 940-991mm (37-39") H - 95-108mm (3.75-4.25") swivel casters (at front) and 178-229mm (7-9") rubber wheels (at back) - Vinyl bag colour: Yellow - Cart colour: Black 	<p>Order # FG9T7200BLA</p> <p>9T72 High Capacity Cleaning Cart</p> <p>High Capacity Vinyl Replacement Bag: 9T80</p> <p>Size: 1264mm (49.8") L x 552mm (21.8") D x 975mm (38.4") H</p>	Rubbermaid Commercial Products	Vinyl Bag: Yellow Cart: Black	37	YES	NO
10	CART-13	Cart-Mail	<ul style="list-style-type: none"> - Four (4) sided edging to keep items secure - All plastic design - Heavy-duty construction - Size: 889-940mm (35-37") L x 584-635mm (23-25") D x 787-838mm (31-33") H - Capacity minimum 181 kg (400 lbs) - Colour: Black 	<p>UCR</p> <p>Size: 914mm (36") L x 610mm (24") D x 813mm (32") H</p>	Secure Mailing Systems Inc.	Finish: Plastic Colour: Black	4	YES	NO
11	CART-15	Cart-Open Wire Mesh	<ul style="list-style-type: none"> - Chrome-plated carbon steel construction - Rust resistant - Two (2) adjustable shelves - Minimum 127mm (5") lockable wheels - Size: 889-940mm (35-37") L x 432-483mm (17-19") D x 1016-1067mm (40-42") H - Adjustable shelf height in 19-32mm (0.75-1.25") increments - 363 Kg (800 lb) or more capacity per shelf - Solid polyurethane 114-140mm (4.5-5.5") lockable swivel casters - NSF Certified (National Sanitary Foundation) - Finish: Chrome 	<p>H-2659</p> <p>Size: 915mm (36") L x 457mm (18") D x 1041mm (41") H</p>	ULINE	Chrome-plated carbon steel	2	YES	NO
12	CLMP-01	Clamps For Matting, Wall Mounted	<ul style="list-style-type: none"> - Size: minimum 3mm (1/8") x 38mm (1 1/2") base - Durable decal - Durable block - Formed top - Stainless steel spring - Welded axle - Wall mountable - No specific colour required 	82SSD	Hamel Manufacturing	Stainless Steel	5	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
13	CURT-01	Shower Curtain - Includes Rod, Hooks and Curtain	Shower rod: - To be compatible with shower rod hooks - rod constructed of 18-8 S, type-304, 18-gauge (1.2mm) stainless steel tubing - Size: 25-32mm (1-1.25") dia. stainless steel - Rod length: 1524mm (60") - Can be cut to size - Finish: non-rust grey or silver Hooks: - To be compatible with shower rod - Size: 35mm (1-3/8") W x 65mm (2-9/16") H - Hooks to be made of 18-8S, type 304, minimum 2mm (0.09") diameter steel - Hooks snap open at bottom - Finish: non-rust grey or silver Curtain: - Size: minimum 1778mm (70") W x minimum 1828mm (72") H x minimum 0.2mm(0.008") thick - Must contain antibacterial and flame retardant agents - Nickel-plated brass grommets along top, one every 127-178mm (5-7") - Bottom and sides are hemmed - Shower curtain material: Opaque, matte vinyl 0.2mm (0.008") thick - Colour: White	Shower Rod: B-6047x60 - Classic Series, Extra Heavy Duty Shower Curtain Hook: 204-1 Shower Curtain: 204-3 Size: 1778mm (70") W x 1829mm (72") H	Bobrick Washroom Equipment Inc.	Shower Hook: Stainless Steel Shower Rod: Stainless Steel Shower Curtain: Matt White	16	YES	NO
14	CURT-02	Industrial Curtain - Heavy-duty, Strip Curtains, Includes Mounting Hardware	- Entrance opening width 1676mm (66") plus minimum 150mm (6") overlap (76mm (3") on each side) - Entrance opening height 2133mm (84") plus minimum 127mm (5") overlap - Anti-static, clear, low temperature grade, non-porous clear vinyl 178-229mm (7-9") wide x 10mm (.40") thick clear flexible PVC curtains strips with 50% overlap on trolley hooks - Bi-parting, open-top plastic on trolley hooks - Stainless steel grommets - Top double heat-sealed hems - Curtain to remain flexible at temperatures as low as -28 C (-20 F) Track: - Stainless steel rounded rod track - Universal connectors for mounting to ceiling, flush with wall or suspended with threaded rod - Sliding track - Ceiling mountable - Includes mounting hardware - Finish: Clear vinyl	SD-8-50-BPWM-72-89 Track: Ceiling mounted	TMI LLC Managing Environments	Finish: Clear vinyl	1	YES	NO
15	DOLL-01	Barrel Container Dolly - Square for Recycle and Waste Barrel Containers SEE RECY-02	- To be compatible with RECY-02 - All plastic construction - Rust, chip and dent resistant - Heavy-duty wheels with swivel capabilities - Minimum 136 Kg (300 lb.) continuous static load rating - Size: 419-445mmmm (16.5"-17.5") W x 419-445mmmm (16.5"-17.5") D x 140-165mm (5.5-6.5") H - Colour: Black	Order # FG353000 BLA 3530 BRUTE® Square Dolly for 3526, & 3536 Containers, Size: 438mm (17.2") W x 438mm (17.2") D x 159mm (6.2") H	Rubbermaid Commercial Products	Colour: Black	18	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
16	DOLL-02	Barrel Container Dolly - Round for Recycle and Waste Barrel Containers SEE WAST-06 SEE WAST-09	- To be compatible with WAST-06 & WAST-09 - All plastic construction - Rust, chip and dent resistant - Heavy-duty wheels with swivel capabilities - Minimum 136 kg (300 lb.) continuous static load rating - Size: 445-470mm (17.5-18.5") diameter x 152-178mm (6-7") H - Colour: Black	Order# FG264000 BLA 2640 BRUTE® Dolly for 2620, 2632, & 2643, 2655 Containers, Size: 464mm (18.2") diameter x 168mm (6.6") H	Rubbermaid Commercial Products	Colour: Black	16	YES	NO
17	DRIL-02	Drill Press - Floor Model	- 430mm (17") Drill Press - Commercial Grade with emergency shut-off - Floor model - Capacity: minimum 19mm (3/4") - Chuck Size: minimum 17mm (5/8") - Swing: minimum 430mm (17") - Stroke: minimum 83mm (3-1/4") - Maximum Distance Chuck To Table: 577mm (22-3/4") - Maximum Distance Chuck To Base: 1117mm (44") - Table Size: minimum 350mm (13-3/4") - Spindle Taper: MT#2 - Speeds (RPM): 16 speed (240-3400) - Motor: 12 Amp. at 110V, 6 Amp. at 220V - Voltage: 110/220V, 1 phase, 60Hz - Pre-wired At: 110V - Size: 343-368mm (13.5"-14.5") W x 622-648mm (24.5-25.5") D x 1600-1651mm (63-65") H - No specific colour required	No Listed Product Specified.		2	YES	NO	
18	ESCL-01	Escalator Cleaner - Floor Model	- Foot pedal operated brake and brush heads - Tank-in-tank system - Floor model - Short brush head - One-button operation - Handle folds down - Four (4) hoses - Two (2) counter-rotating, motor-driven roller brushes - Centering skid - Outboard deflectors - Solution capacity: minimum 34.8 litres (9.2 gal) - Recovery capacity: minimum 34.8 litres (9.2 gal) - Power supply: 120V/60 Hz - Brush speed: pick-up/washing brush: 870/1090 rpm - Brush motor: minimum 1.5 hp (1100 watts) - Suction motor: minimum 1.1 hp (800 watts) - Water flow rate: minimum 15.8 gal/hr. (60 l/hr.) - Pressure: minimum 58-101.5 psi (4-7 bar) - No specific colour required	Treadway 1.310-108.0	Windsor Commercial Cleaning Equipment	Colour: Blue	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
19	FLOR-01	Floor Sweeper - Walk-Behind, Multi-surface, Battery Powered	<ul style="list-style-type: none"> - Self-cleaning filter - Walk-behind model - Vacuum shutoff when sweeping wet areas - On-board battery charger - Adjustable handle bar - Sealed battery for up to 2.5 hours of continuous cleaning - Self levelling system - Pre-programmed working settings - Micro dust filtration - Tool-free dust filter, main brush & side brush replacement - Maximum working width: 625mm (24") - Productivity (at max speed): 2880 sq.m. (31,000 sq.ft.) - Power supply: battery 12V/45Ah - Filter surface: 1 sq.m. (10 sq.ft.) - Electric filter shaker: Automatic - Gel batteries - Noise level: Maximum 55 db(A) - No specific colour required 	SmartVac 464 Sweeper Gel Batteries	IPC Eagle	Colour: Green	1	YES	NO
20	FLOR-02	Floor Auto Scrubber - Walk-Behind, Battery Powered	<ul style="list-style-type: none"> - Walk behind model - Working width: minimum 43cm (17") - Squeegee width: minimum 69cm (27") - Walk behind model - Solution tank: minimum 40L - Recovery tank: minimum 40L - Power consumption: 900W - Rated voltage: 24V - Battery capacity: 50-70Ah/C5 - Battery run time: minimum 2h - Gel Batteries - Turning circle: maximum 1.12 m - Brush system: 1 x 43cm - Brush pressure: 40/43 kg - Working speed (power): 3.0-4.5 km/h - Power cord length of integrated battery charger: minimum 3m - Sound level: 58dB(A) or less - Rotationally molded, polyethylene base - Adjustable handle - Two finger operation trigger - Self-drive - Size: 118-1168mm (44"-46") L x 432-483mm (17"-19") W x 1168-1219mm (46"-48") H - No specific colour required 	Taski swingo 755 B Gel Batteries Self-drive	Taski Diversey	Colour: Orange	1	YES	NO
21	FLOR-03	Floor Burnisher - Walk-Behind, Battery Powered	<ul style="list-style-type: none"> - Walk behind model - Pad width: minimum 508mm (20") - Maximum productivity rate: 2500 m²/hr - Transport mode: Self propelled, variable speed, continuous 0.2 hp transaxle - Two (2) 178-228mm (7-9") non-marking main wheels and one (1) 64-102mm (2.5-4") non-marking caster - HEPA filter - Pad motor: 3 hp, 2.24 kW - Pad motor speed: minimum 2000 rpm - nominal load / minimum 2500 rpm - no load - Pad pressure: variable; 15-45 lb / 7-20 kg - Pad driver: flexible, full pad contact - Sound level: maximum 70 DBA - Coverage rate per hour: minimum 1951 sq.m. (21,000 sq.ft.) - Gel battery - Battery: minimum 2.4 hours at nominal load; minimum 3 hours at minimum load - No specific colour required 	608344 SpeedGleam/Plus AGM battery	Nobles	Colour: Dark Green	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
22	FLOR-04	Floor Burnisher - Hand Held	<ul style="list-style-type: none"> - Hand held - Cast aluminum base - Minimum 508mm (20") pad diameter - Productivity per hour: minimum 844 sq.m. (9,090 sq.ft.) - Dual switch levers with safety lock-out switch - Steel-plated handle tube - Carbon brush wear indicators - Pad speed: 1500 rpm - Voltage: 115 V - Motor horsepower: 1.5 hp - Power consumption: 15 amp - Minimum 15m (50 ft.) power cord length - Sound level: maximum 70 DBA - No specific colour required 	Model # B-1500 495460 Cast aluminum base	Pacific Floor Care	Colour: Black Cast aluminum base	3	YES	NO
23	FLOR-06	Floor Buffer - Hand Held	<ul style="list-style-type: none"> - Hand held - Adjustable handle - Rotationally molded, polyethylene base: 480mm (19") - Two finger operation trigger - Speed: 175-320 rpm - Motor Power: permanent magnet, minimum 1.5 hp (3200 rpm) - Volt: 115 AC - Amps: Low: 10 A, High: 13 A - Gear box: 3 Idler Ratio 11:1 - Power cord: 15m (50') - 18m (60') - Weight: 36-39 Kg (80-85 lbs) - Noise level: 63 dB or less - CSA (Canadian Standards As 	Model # 19915 (19" TX) Integra Dual Speed Polisher	Dustbane	Colour: Blue	2	YES	NO
24	FLOR-07	Floor Finish Applicator System & Fill Station - Hard Flooring Surfaces, Portable	<ul style="list-style-type: none"> - Portable - Can clean hard surface flooring <u>Applicator Kit:</u> <ul style="list-style-type: none"> - One (1) aluminum handle with dispense trigger - One (1) 432mm (17") applicator pad holder - Two (2) 457mm (18") applicator pads - Low drag microfiber mop - One (1) canvas backpack pouch with adjustable straps, reusable; holds minimum 7 liters (1.8 gallons) <u>One (1) Fill Station:</u> <ul style="list-style-type: none"> - Five (5) reusable pouches (pouches must be able to hold 3M Scotchguard stone floor protector) - One (1) fill system - 10 blank labels (for chemical identification) - No specific colour required 	55433 Easy Shine Applicator Kit 59175 Easy shine Fill Station	3M	Not applicable	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
25	FLOR-08	Upholstery and Carpet Cleaner / Extractor - Walk-Behind, Includes Accessories	<ul style="list-style-type: none"> - Walk behind model - Polyethylene construction - Cleaning width: minimum 508mm (20") - Solution and recovery tank capacity: minimum 45.5 L (12 gal.) - Minimum 1.8 hp three (3) stage vacuum motor with 135" water lift and 95 cfm of airflow - Adjustable, spring-loaded vacuum shoe - Minimum cleaning rate: 372 sq.m. (4000 sq.ft.)/hour - Removable spray bar with twist-off jets - 15-18m (50-60') L power cord - Minimum 130 psi pump providing a flow rate up to 1.2 gpm - Solution and Vac Hose complete 6m (20') x 38mm (1-1/2") - Noise level: 60db or less - 15m (50') pre-spray hose and gun - Steel box to hold chemical - Chemical dispensing system - High / low volume water feed system - Brush speed: minimum 600 RPM - Voltage: 120 V60 HZ Accessories: - 1219mm (4') hand tool - aluminum construction, fits 38mm (1-1/2") hose - Solution and vac hose minimum six (6) metersx38mm (20'x1-1/2") - Wand - three (3) jet stainless steel with hand grip - No specific colour required 	Machine: AV12QX Hand tool: 1110APE - 4' hand tool, aluminum - fits 1-1/2" hose Wand: 12300PE - Three jet s/s wand with hand grip To include "Smart Kit": 8020280 To include Solution and Vac Hose complete 20' x 1-1/2"	NaceCare Solutions	Colour: blue	2	YES	NO
26	FUME-01	Fume Extractor - Welding & Dust, Portable	<ul style="list-style-type: none"> - Portable - Equipped with a N24 fan for a maximum air flow capacity of 1000 m³/h (600 CFM) - Fume hood to be on wheels and be lockable - Integrated silencer - Filter control system with automatic cleaning that starts when the air flow is too low - Extraction arm: 2500-3500mm (98-137") extraction arm - Dust-free emptying dust bin - Polyester filter cartridges - Silencer - Integrated LCD display - 9753mm (31') power cable - Automatic damper - Noise level: maximum 66dB(A) - Hose dia. 1152-178mm (6-7") - IP class: 54 - No specific colour required 	No Listed Product Specified.			1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANFACTORER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
27	FUME-02	Sand Blasting & Fume Extractor Semi-Industrial Suction Cabinet, Floor Model	<ul style="list-style-type: none">- Semi-industrial suction sandblasting cabinet- Floor model- Overall size: 1189-1041mm (39-41") W x 1041-1092mm (41-43") D x 1676-1727mm (66-68") H- Interior dimensions: 660mm (26") W x 914mm (36") D x 787mm (31") H- Filtration: 1.2 sq.m. (13 sq.ft.)- 1/2 HP, 3450 RPM, 115 V TEFC Motor- Dust collector-ventilation; minimum 400 CFM- Natural latex gloves with nylon gauntlets- Single door opening- 330mm (13") x 533mm (21") window with plastic protector- Foot pedal blast control- Two (2) 100w halogen bulbs- Regulator and gauge air control- Adjustable louver air vent- 3mm (1/8") perforated steel screen drawer- Minimum capacity 136kg (300 lb)- 83-102mm (3.25-4") dia. return hose- Ceramic 5/16" nozzle, 5/32" air jet, minimum 34 CFM- Minimum thickness 14 gauge steel construction- Dust collector bag: 356-406mm (14-16") dia. x 1651-1702mm (65-67") H- Abrasive recycler included- CSA approved- No specific colour required	626104 Ecab 3 Series Suction Cabinet Dust collector DB13 (dust bag) Size: 1016mm (40") W x 1067mm (42") D x 1702mm (67") H	Canablast	Colour: Blue	1	YES	NO
28	GARM-01	Garment Rack - Heavy Duty Mobile Garment Rack - Includes Top and Bottom Shelves	<ul style="list-style-type: none">- All building components must fit within the building elevator dimensions: 914mm (3'-0") W, 1981mm (6'-6") L, and 1981mm (6'-6") H- Size: 1575-1626mm (62-64") L x 559-610mm (22-24") W x 1956-2007mm (77-79") H- Steel construction- Two (2) shelves - one above hang rail and one on bottom- Base: steel, minimum thickness 14 gauge- Uprights: minimum thickness 16 gauge, minimum odd. 1-5/16"; 1829mm (6') H- Hang rail: minimum thickness 16 gauge, minimum o.d. 1-5/16"; minimum 1524mm (5') L; mounted at maximum 1524mm (5') H- 227 Kg (500 lb) or more capacity- Minimum 127mm (5") non-marking casters with revolving bumpers- Steering handles- Nestable- Finish: Powder-coated- Colour: Black	360729BLK Heritage Z-Rack - Casters: Two brake casters on each unit Size: 1600mm (63") L x 584mm (23") D x 1981mm (78") H	Quality Fabricators	Finish: Powder-coated Colour: Black	1	YES	NO
29	GRIN-01	Bench Grinder - Table Model, Two (2) Wheel, 7" Dia.	<ul style="list-style-type: none">- Table model- 165191mm (6.5-7.5") grinder- Minimum 0.5 HP- 115V, 3.4 amp- Minimum 3600 RPM- Wheel guards are non-exhaust type- Furnished with GA10 eye shields- Commercial grade- Arbor size: 32mm (1.25")- To include two (2) grinding wheels 165191mm (6.5-7.5") x 25mm (1") x 15mm (5/8"); 36-grit and 60-grit- No specific colour required	No Listed Product Specified.			5	YES	NO
30	Deleted								

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
31	HOLD-01	Utility Holder - Mop & Broom Three (3) Holders, Wall Mounted	<ul style="list-style-type: none"> - Wall mounted <u>Backplate:</u> - Size: 584-635mm (23-25") W x 51-102mm (2-4") D x 76-127mm (3-5") H - Minimum thickness 22 gauge stainless steel - Exposed surfaces stainless steel - Finish: Satin <u>Holders:</u> - Three (3) holders - Spring-activated rubber cams on plated steel retainers - Holds a mop or broom with a diameter between 16mm (5/8") and 25.4mm (1") 	9953	Bradley Corp.	Material: Stainless Steel Finish: Satin	6	YES	NO
32	HOOK-01	Coat Rack - Complete with 12 qty. Hangers, Wall Mounted	<ul style="list-style-type: none"> - Wall mountable - 1194-1245mm (47-49") W x 305-356mm (12-14") D - Minimum three (3) shelf tubes - Hang bar to include three (3) hangers per foot - total twelve (12) - Rustproof - Satin Aluminum finish 	9339 Size: 1219mm (48") W x 330mm (13") D	Specialty Store Services	Satin Aluminum finish	2	YES	NO
33	HOOK-02	Hook - Wall mount	<ul style="list-style-type: none"> - Wall mount - Hook support extends from bottom pivot - With magnet for holding in closed position - Size: 165-191mm (6.5-7.5")H x 13-25mm (0.5-1")W x 13-38mm (0.5-1.5")D - Extended depth: 152-191mm (6-7.5")D - Size: 305mm (11") - 457mm (19")H x 13-19mm (0.5-0.75") - 19-32mm (0.75-1.25")W - Zinc alloy construction - Finish: Polished Chrome 	844.33.230 Folding Coat Hook Size: 177mm (7")H x 13mm (0.5")W x 19mm (0.75")D Extended depth: 171mm (6.75")D	Hafele	Finish: Polished Chrome	1	YES	NO
34	HOSE-01	Hose - Used for the Slop Sink, Includes Faucet Hose Adapter	<ul style="list-style-type: none"> - 1524mm (5') length - Includes rubber faucet adapter to attach to slop sink 	UNGWH180 Easy Adapter Hose 1829mm (6') supply / fill hose Includes rubber faucet adapter	Acklands Grainger Industrial	Colour: Clear	1	YES	NO
35	KCAB-02	Key Cabinet - Double Key System, 240 Keys Wall Mounted	<p>Double key file / security system</p> <ul style="list-style-type: none"> - Minimum 240 key capacity - Size: 406-457mm (16-18") W x 100-150mm (4-6") D x 508-559mm (20-22") H - Heavy-duty, minimum thickness 20-gauge steel body - Minimum thickness 18-gauge steel door - Cabinet includes a disc-tumbler lock with two keys - Wall-mounted - Includes: red octagon key tags and white oval key tags same amount as key capacity, cross reference key guide, key loan record sheet, key receipt slip, brass key receipt holders, and key collection envelopes. <p>Extra Accessories:</p> <ul style="list-style-type: none"> - Key tags, red octagon, numbered; approx. qty. twenty (20) - Key tags, white oval, numbered; approx. qty. twenty (20) - Key collection envelopes, approx. qty. one hundred (100) - Brass key receipt holders, approx. qty. one hundred (100) - Key loan record sheets, approx. qty. twenty-four (24) - Cross reference index binder, 90-240 keys, qty. one (1) - Key receipt slips, approx. qty. two hundred and fifty (250) 	No Listed Product Specified.			1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
36	LADD-01	Ladder - Step Extra-Heavy Duty Aluminum	<ul style="list-style-type: none"> - Size: minimum 1829mm (6') - Open height: 1702-1753mm (67-69") - Heavy duty aluminum step - Minimum 76mm (3") slip-resistant serrated aluminum steps - Co-polymer utility top - Heavy duty hinged utility tray - Zinc-coated steel spreader arms - Meets or exceeds CSA (Canadian Standards Association) Grade 1A, ANSI Type 1A - Load capacity: minimum 136 kg (300 lbs.) - No specific colour required 	3400 Series Model #3406 1829mm (6 ft.) ladder	Featherlite Industrial Ladders	Finish: Aluminum	4	YES	NO
37	LADD-02	Ladder - Step Extra-Heavy Duty Aluminum	<ul style="list-style-type: none"> - Size: minimum 2438mm (8') - Open height: 2286-2337mm (90-92") - Heavy duty aluminum step - Minimum 76mm (3") slip-resistant serrated aluminum steps - Co-polymer utility top - Heavy duty hinged utility tray - Zinc-coated steel spreader arms - Meets or exceeds CSA (Canadian Standards Association) Grade 1A, ANSI Type 1A - Load capacity: minimum 136 kg (300 lbs) - No specific clour required 	3400 Series Model # 3408 2438mm (8 ft.) H ladder	Featherlite Industrial Ladders	Finish: Aluminum	2	YES	NO
38	LADD-03	Ladder - Hook Wall mount	<ul style="list-style-type: none"> - Soft grip coating protection - Powder-coated steel for durability - Load capacity: minimum 22.7 Kg (50 lbs) - Mounted directly to wall - No specific colour required 	Fast Track - SE06	Rubbermaid Commercial Products	Finish: Powder-coated steel	6	YES	NO
39	LAMP-01	Lamp - Desk	<ul style="list-style-type: none"> - LED Light - Seven (7) settings of dimmability - Articulated arm and shade - PIR motion sensor - Advanced MCX LED technology - One-touch positioning - Even plane of illumination casts just one shadow - Folds away when not in use - Universal power supply - Power consumption: minimum 7 watts - Light output: minimum 225 lumens - Efficacy: minimum 32 lumens per watt - Runs on 100 to 240 volt power - Correlated colour temperature (CCT): 3000-3300K - Colour Rendering Index (CRI): minimum 89 - LM-79 tested - LM-80 data available - Rated life of 45,000-50,000 hours (L70) - Compliant with Restriction of Hazardous Substances Directive (RoHS) and Waste Electrical and Electronic Equipment Directive (WEEE) - Colour: Black 	EV-N-B-B Element Vision LED Light	Humanscale	Colour: Black	171	YES	NO
40	LAMP-02	Lamp - Desk, (SI Booths)	<ul style="list-style-type: none"> - 279-330mm (11-13") gooseneck - Built-in dimmer - Enclosed bottom plate - Power supply included - 12 Volt operation - Wattage: 1.5 watts - Light output at 305mm (12"): 350-400 Lux - Colour temperature: 3500-4000K - CRI: minimum 85 Ra - Average life at 12V: 55,000-65,000 hours - Colour: Black 	LW-12-LED	LittLite	Colour: Black	26	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
41	LAUN-03	Ironing Board Fold-Away Vertical Wall Mounted; Includes Cover and Mounting Hardware	- Ironing surface dimensions: approximately 356-406mm (14-16") W x 991-1041mm (39-41") H - Fold away dimensions: approximately 356-406mm (14-16") W x 76-127mm (3-5") D x 737-787mm (29-31") H - Weight: 10.8 -11.3Kg (24 to 25lbs) - Wall-mounted vertical fold-away ironing board - Wall mounting hardware included - Chrome-plated iron rest - Padded cloth cover - Colour: Light Neutral Colour	Model # OSUV-01 Size: 381mm (15") W x 101mm (4") D x 762mm (30") H, folded	Better LifeStyle Products	Cover Colour: Natural	4	YES	NO
42	LAUN-04	Iron holder - Wall Mount	- Wall-mounted - Durable heat resistant thermoset plastic construction - Size: 102-152mm (4-6") W x 76-127mm (3-5") D x 356-406mm (14-16") H - Colour: White	2455-06 Order # FG245506 Size: 133mm (5.2") W x 102mm (4") D x 394mm (15.5")	Rubbermaid Commercial Products	Colour: White	4	YES	NO
43	LAUN-05	Laundry Cart - Double Linen Bags; Includes Retaining Ring and Foot Pedestal System SEE LAUN-09 AND LAUN-10	- To be compatible with LAUN-09 and LAUN-10 - Rust-proof stainless steel frame - Two (2)-bag configuration - Lids for each compartment - Retaining ring to hold bags securely in place - Full-swivel wheels - Foot pedal operating system - Size: 635-686mm (25-27") L x 457-508mm (18-20") D x 914-965mm (36-38") H	LCC-2000-2 Size: 660mm (26") L x 483mm (19") D x 940mm (37") H	MIP Canada Inc.	Frame: Stainless Steel	8	YES	NO
44	LAUN-07	Clothes Hanger - Cluster Open Hook- hardwood	- Light waxed hardwood hanger - Minimum 38.2mm (1-1/2") nickel plated steel open hook - Wood stain: Walnut	MG17H: Light Waxed Hardwood hanger in with 38.2mm (1-1/2") nickel plated steel open hook	Magnuson Group	Wood Stain: Walnut	1120 singular	YES	NO
45	LAUN-08	Iron - Hand Held with Steam	- Anti-scorch technology - Auto shut-off - Non-dripping system - Pointed detailer tip - Rapid heating - minimum 1800 watts - 3m-3.7m (10'-12') cord with 360 degree pivot - 325-385ml (11-13 oz.) water tank minimum - Scratch resistant sole plate - Controlled steam blasts - Colour: Grey	TG1100 Smart Iron	Oliso Inc.	Colour: Grey	5	YES	NO
46	LAUN-09	Laundry Bag - Standard Design, Nylon SEE LAUN-05	- To be compatible with LAUN-05 - Size: 686-737mm (27-29") x 940-991mm (37-39") - Washable - Impermeable barrier and sealed seams - Draw cord with closure - Nylon fabric - Not tapered - Colour: Green	LB/GR Size: 699mm (27-1/2") x 965mm (38")	MIP Canada Inc.	Colour: Green	2	YES	NO
47	LAUN-10	Laundry Bag - Standard Design, Nylon SEE LAUN-05	- To be compatible with LAUN-05 - Size: 686-737mm (27-29") x 940-991mm (37-39") - Washable - Impermeable barrier and sealed seams - Draw cord with closure - Nylon fabric - Not tapered - Colour: White	LB/WH Size: 699mm (27-1/2") x 965mm (38")	MIP Canada Inc.	Colour: White	10	YES	NO
48	MATS-02	Floor Mat - Carpet Entrance Mat	- Dimensions: 1778-1880mm (70-74") W x 762-914mm (30-36") D - Olefin fiber - Stain and mildew resistant - Vinyl backing and border - Colour: Black	CEM Size: 1829mm(72") L x 914mm (36") W	American Floor Mats-	Colour: Black	16	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
49	MATS-03	Floor Mat - Seasonal Weather Mats, Roll	<ul style="list-style-type: none"> - Face Weight: minimum 814g/sq. m, (24oz/sq. yd.) - Gauge: minimum 10cm (1/12")/ 47.2 rows - Stiches per cm: minimum 31.5 stiches/10cm (8.0 stiches/inch) - Pile height average: 5mm (0.187") - Fiber system: TDX* Nylon Dye Method: 100% Solution Dyed - Soil/Stain protection - Colour-fastness to light: 4 after 100 hours (AATCC 16E) - Fluorine: Minimum 500 ppm - No antimicrobials added to product (ASTM E2471-05) - Electrostatic Propensity: 1.5 kv (AATCC 134) - Surface flammability: Passes CPSC FF 1-70 (ASTM D-2859) - Flooring Radiant Panel: Class 1 (mean average CRF: 0.45 w/sq. cm or higher) (ASTM E-648) - Smoke Generation: Less than 450 (ASTM E-662) - Colour: Black Sizes: <ul style="list-style-type: none"> - 11713L x 1831W, Qty. 1 (Located in Vestibule 100) - 3624L x 1525W, Qty. 1 (Located in Vestibule 160a) - 2609L x 4883W, Qty. 1 (Located in east Corridor 110) - 11713L x 5486W, Qty. 1 (Located in Vestibule 100) - 7933L x 1907W, Qty. 1 (Located in west Corridor 101) - 3938L x 7398W, Qty. 1 (1959 lobby 150) - 1580L x 3722W, Qty. 1 (Located in Vestibule 160c) - 4389L x 2901W, Qty. 1 (1959 lobby 150) - 5611L x 1276W, Qty. 1 (Located in Vestibule 160c) - All sizes to be site verified after contract award 	<ul style="list-style-type: none"> Abrasive Action II 02578 PowerBond ethos cushion - 11713L x 1831W, Qty. 1 (Located in Vestibule 100) - 3624L x 1525W, Qty. 1 (Located in Vestibule 160a) - 2609L x 4883W, Qty. 1 (Located in east Corridor 110) - 11713L x 5486W, Qty. 1 (Located in Vestibule 100) - 7933L x 1907W, Qty. 1 (Located in west Corridor 101) - 3938L x 7398W, Qty. 1 (1959 lobby 150) - 1580L x 3722W, Qty. 1 (Located in Vestibule 160c) - 4389L x 2901W, Qty. 1 (1959 lobby 150) - 5611L x 1276W, Qty. 1 (Located in Vestibule 160c) All sizes to be site verified after contract award 	Tandus / Centiva	Colour Name & No: Charcoal 19100 - Product Collection: Jhane Barnes	2	YES	NO
50	MIRR-02	Mirror - Full Length	<ul style="list-style-type: none"> - Glass mirror with stainless steel angle frame - Snap locking design - 6mm (1/4") select float glass - All edges protected by plastic filler strips - Back is protected by full-size, shock-absorbing, water-resistant, nonabrasive, 5mm (3/16") thick polyethylene padding - Frame: 18-8 S, type 304, heavy-gauge stainless steel - 13-25mm x 13-25mm (0.5-1" x 0.5-1") angle - Manufactured to a tolerance ± 3.2mm (1/8") - Size: 584-635mm (23-25") x 1499-1549mm (59-61") - Frame: Stainless Steel - Finish: Vertical Grain Satin 	B-290 2460 Glass Mirror with SS Angle Frame Size: 610mm (24") W x 1524mm (60") H Angle: 19mm x 19mm (3/4" x 3/4") Snap Locking Design	Bobrick Washroom Equipment Inc.	Frame: Stainless Steel Finish: Vertical Grain Satin	30	YES	NO
51	MOPB-01	Bucket and Wringer - Downpress Bucket & Wringer	<ul style="list-style-type: none"> - Wringer & Bucket to be compatible Bucket: <ul style="list-style-type: none"> - 24.6-37.8 liter (26-40 quart) capacity - Molded graduations to facilitate accurate measurements - Flared base - Opening for mop access with the wringer attached - Colour: Blue Downpress Wringer: <ul style="list-style-type: none"> - Injection molded with high density polymer - Smooth surface - Gears and pressure plates are fiber-reinforced nylon - Wrings all wet mops from 340 g to 900 g (12 oz. to 32 oz.) - Downward pressure style - Colour: Blue 	Downpress Wringer: 134710 Bucket: 134725 with 3" casters	Vileda Professional	Wringer: Blue Bucket: Blue	20	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
52	MOPH-01	Mop Head - MicroFiber Tube Mop See MOPH-02	<ul style="list-style-type: none"> - To be compatible with MOPH-02 - Headband and tailband construction - 19-32mm (0.75-1.25") PVC mesh Headband - Striped tube design - Machine washable - To withstand laundry cycles at 200F with detergents and bleach - Microfiber yarn tub mop - Requires no adapters or new flat-mopping handles or frames - No specific colour required 	T813-06	Rubbermaid Commercial Products	Colour: Grey	20	YES	NO
53	MOPH-02	Mop Handle - Fiberglass Handle See MOPH-01	<ul style="list-style-type: none"> - To be compatible with MOPH-02 - 178-203mm (7-8") Head - Injection molded head - Rust and corrosion resistant - Fibreglass shaft - Non-marring - Size: 1346-1397mm (53-55") L - Weight: maximum 0.9 Kg (2lbs) - No specific colour required 	Model: 84 1372mm (54") long mop handle	IMPACT	Material: Fiberglass Colour: orange	20	YES	NO
54	MOVE-01	Moving Blanket - Cotton	<ul style="list-style-type: none"> - Filling: minimum density 1.13kg (40 oz.) - Size: 1803-1854mm (71-73") x 2007-2057mm (79-81") - Weight: maximum 2.5kg (5.5 lbs) - Zig-zag stitching - Cotton and polyester material - Colour: Blue 	PF460 Size: 1829mm (72") x 2032mm (80")	Kleton	Colour: Blue	75	YES	NO
55	OHSE-11	Safety Cabinet - Blue for Corrosives & Flammables	<ul style="list-style-type: none"> - Minimum 170 litre (45 Gallon) - Two (2)-door - manual close. Opens to a full 180 degrees and self latches when pushed closed - Two (2) galvanized steel adjustable shelves - 18-gauge minimum thickness double wall steel construction - Dual vents - Grounding connector - Leakproof sills - Three (3)-point self latching doors open to 180 degrees - Leveling feet - Paint finish and separate polyethylene liner for the bottom sump to resist acids, bases and solvents - Meets National Fire Protection Association (NFPA) 30 and Occupational Safety and Health Administration (OSHA) regulations - Size: 1067-1118mm (42-44") W x 432-483mm (17-19") D x 1626-1676mm (64-66") H - Material: 18 Ga CR Steel - Colour: Blue 	Model # 894502 Sure-Grip Ex Corrosives/Acid Steel Safety Cabinet Size: 1092mm (43") W x 457mm (18") D x 1651mm (65") H	Justrite	Material: 18 Ga CR Steel Colour: Blue	5	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
56	OHSE-12	Safety Cabinet - Yellow for Flammables	<ul style="list-style-type: none"> - Minimum 170 liter (45 Gallon) - Two (2)-door - manual close. Opens to a full 180 degrees and self latches when pushed closed - Two (2) galvanized steel adjustable shelves - Leak-proof minimum 51mm (2") bottom sump - 18-gauge minimum thickness double-wall steel construction - Welded steel with minimum 38mm (1-1/2") insulating air space for fire resistance - Two (2) doors self-latch automatically when a fusible link melts at 74 degrees C (165 degrees F) under fire conditions - Grounding connector - Cylinder lock and key set or accepts an optional padlock - Meets National Fire Protection Association (NFPA) 30 and Occupational Safety and Health Administration (OSHA) regulations - Size: 1067-1118mm (42-44") W x 432-483mm (17-19") D x 1626-1676mm (64-66") H - Material: 18 Ga CR Steel - Colour: Yellow 	<p>Model # 894500</p> <p>Sure Grip Ex Flammable Safety Cabinet</p> <p>Size: 1092mm (43") W x 457mm (18") D x 1651mm (65") H</p>	Justrite	Material: 18 Ga CR Steel Colour: Yellow	6	YES	NO
57	OHSE-13	Safety Cabinet - Red for Flammables	<ul style="list-style-type: none"> - 18-gauge minimum thickness double-walled steel construction with minimum 38mm (1-1/2") insulating air space for fire resistance - Three (3)-point self-latching door system for positive door closure - manual doors - Doors open to a full 180 degrees and self latches when pushed closed - Three (3) stainless steel bullet latches - Pad lockable handle with slip resistant grip - Rounded safety door corners to reduce accidental nicks or cuts - Reflective labeling in English and French - Sloped shelves to direct incidental spills to back and bottom of leak-proof sump - Adjustable shelves on 64-83mm (2.5-3.25") centers - Shelves to meet ANSI standards - minimum 136 Kg (350 lb.) load capacity - Painted with lead-free hybrid powder paint - Meets National Fire Protection Association (NFPA) 30 and Occupational Safety and Health Administration (OSHA) regulations - Size: 1067-1118mm (42-44") W x 432-483mm (17-19") D x 1626-1676mm (64-66") H - Material: 18 Ga CR Steel - Colour: Red 	<p>Model # 894501</p> <p>Sure Grip Ex Flammable Safety Cabinet</p> <p>Size: 1092mm (43") W x 457mm (18") D x 1651mm (65") H</p>	Justrite	Material: 18 Ga CR Steel Colour: Red	4	YES	NO
58	OHSE-19	Floor Mat - Antifatigue Solid Top	<ul style="list-style-type: none"> - Size: 889-940mm (35-37") W x 1499-1549mm (59-61") D - Deck plate surface fused to foam backing - Interior sponge construction - Resistant to fluids and chemicals - Slip-resistant surface - Beveled edges and rounded corners - 3mm (1/8") extruded vinyl surface with diamond pattern - Size: 1499-1549mm (59-61") L x 889-940mm (35-37") W - Colour: Black 	<p>540 Supreme with Zedlan foam backing</p> <p>Heavy duty, slip-resistant surface tolerates cart traffic</p> <p>Size: 1525mm (60") L x 914mm (36") W</p>	Crown Mats and Matting	Colour: Black	6	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
59	OHSE-20	Spill Kit - Wheeled Hazmat	<ul style="list-style-type: none"> - Includes hazmat kit - Minimum 189 litres (50 Gallon) capacity - Absorbs minimum 132.5 litres (35 gallons) - 127-178mm (5-7") polyolefin wheels - X-rated for packing groups I, II and III - Complies with HAZWOPER Regulation 29 CFR 1910.120 (j) (1) (vii) - Holds a DOT container for absorbents - Meets 49 CFR173.3(c) DOT requirements for salvage drums - Overpack Dimensions: 610-660mm (24-26") dia. x 991-1041mm (39-41") H Includes Hazmat kit, containing: <ul style="list-style-type: none"> - 50 Pads - 406mm (16") x 508mm (20") - Four (4) Socks - 76mm (3") x 3657.6mm (12') - Five (5) Socks - 76mm (3") x 1219mm (4') - Four (4) Pillows - 457mm (18") x 457mm (18") - Five (5) Disposable Bags 1 Pair Nitrile Gloves - One (1) Pair Goggles - One (1) Emergency Response Guidebook - No specific colour required 	KIT507 DAWG® 50 Gallon Wheeled Overpack Spill Kits	Seton	Colour: Yellow	3	YES	NO
60	OHSE-25	Spill Kit - Universal, 5-Gallon	<ul style="list-style-type: none"> - Spill Type: Universal - Container Type: Polyethylene pail - Container capacity: minimum 19 Liters (5 Gallons) - Colour: White Contents: <ul style="list-style-type: none"> - Five (5) Sorbent Socks 76mm (3") x 1220mm (48") - One (1) Pair Nitrile Gloves, 2XL (11) - One (1) Pair Safety Goggles (One Size) - Two (2) Disposal Bags 660mm (26") x 914mm (36") 	Model SE1160	Zenith Safety Products	Colour: White	2	YES	NO
61	OHSE-26	Spill Kit - Universal, 30-Gallon	<ul style="list-style-type: none"> - Spill Type: Universal - Container Type: Polyethylene Drum - Container capacity: minimum 113.5 Liter (30 Gallons) - Colour: Blue drum Contents: <ul style="list-style-type: none"> - Seventy five (75) sorbent pads, minimum 381mm (15") x 431mm (17") - Four (4) sorbent socks, minimum 75mm (3") x 3048mm (120") - One (1) drain cover 914mm (36") x 914mm (36") - One (1) caution tape, minimum 75mm (3") x 91m (300') - Two (2) pairs nitrile gloves, 2XL - Two (2) pairs safety goggles (one size) - Two (2) microporous coveralls, XL - Five (5) disposal bags, minimum 660mm (26") x 914mm (36") 	Model SE1165	Zenith Safety Products	Colour: Blue drum	1	YES	NO
62	OHSE-27	Absorbents - Volcanic Ash	<ul style="list-style-type: none"> - Non-corrosive, non-toxic product that offers the best absorbency - Absorbs almost twice as much as other products in water or oil - Can be used in all applications, even for toxic waste absorption - Absorbs spills in no time leaving floor safe and dry - Bag size: 8-10 kg (18-22 lbs) - No specific colour required 	SAJ503	Zenith Safety Products	No specific colour required.	12	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
63	OHSE-28	Drain Seal Square Mat	<ul style="list-style-type: none"> - Size: 889-940mm (35-37") L x 889-940mm (35-37") W x 6-19mm(0.25-0.75") H - Maximum 9 kg (20lbs) - Both sides will quickly seal drains - Flexible polyurethane material with reinforced, tear-resistant mesh - One (1) unit per box easily cuts to special shapes, sizes - Cleans with soap and water - Prevents contaminants from entering drain - Resists oil, water and most aggressive chemicals; non-absorbing - Colour: Orange 	<p>Model SEI093</p> <p>Size: 914mm L (36") x 914mm (36") W x 10mm (3/8") H</p>	Zenith Safety Products	Colour: Safety orange	3	YES	NO
64	OHSE-29	Dome Security Mirror - Suspended 360 Degree Full Dome Mirror	<ul style="list-style-type: none"> - Four (4)-way dome panoramic 360 degree - Unbreakable acrylic - 432-483mm (17-19") diameter - Weight range: 2.7-3.1 kg (6-7 lbs) - Suspended from ceiling - Trim colour: Black 	SMDM-18 457mm (18") 360 degree dome security mirror, suspended	Superior Mirror	Trim colour: Black	1	YES	NO
65	OHSE-30	Dome Security Mirror - Full Dome Mirror	<ul style="list-style-type: none"> - Four (4)-way drop-in dome panoramic 360 degree - Unbreakable acrylic - 432-483mm (17-19") diameter - Weight range: 2.7-3.1 kg (6-7 lbs) - Trim colour: Black 	SMD-1824 457mm (18") 360 degree drop-in dome acrylic mirror with panel	Superior Mirror	Trim colour: Black	4	YES	NO
66	OHSE-31	Dome Security Mirror - Half Dome Mirror	<ul style="list-style-type: none"> - Three (3)-way mount at intersection of wall and ceiling - 180 degree - Unbreakable acrylic - Weight range: 1.8-2.2 kg (4-5 lbs) - Trim colour: Black 	SMHD-18 457mm (18") dome 180 degree acrylic mirror	Superior Mirror	Trim colour: Black	51	YES	NO
67	OHSE-32	Dome Security Mirror - Quarter Dome Mirror	<ul style="list-style-type: none"> - Two (2)-way, mounts in corner - Unbreakable acrylic - 432-483mm (17-19") diameter - Weight range: 1.3-1.8 kg (3-4 lbs) - Trim colour: Black 	SMQD-26 508mm (20") 90 degree security mirror	Superior Mirror	Trim colour: Black	36	YES	NO
68	PAIL-01	Pail - Beverage Cart Square, Includes Lid	<ul style="list-style-type: none"> - Must be compatible with lid - Made of molded, high-density white polyethylene - To have carrying handle - To have built-in hand grips - Nest easily when empty - Easy to separate - Maximum height to be 336mm (13-1/4") - Dimensions: 229-279mm (9-11") W x 229-279mm (9-11") D (round pail is acceptable as long as it respects maximum height) - Minimum capacity to be 15 Litres (4 gallons) - Minimum weight capacity 36 lbs - Colour: white - Lid: - Must be compatible with pail - Made of molded, high-density white polyethylene - To have built-in hand grips - Colour: white 	<p>Pail: S-13650</p> <p>Size: 250mm (10") W x 250mm (10") D x 336mm (13") H</p> <p>Lid: S-13651</p>	Uline	Colour: White	24	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
69	POST-01	Strapping Machine - Floor Model	<ul style="list-style-type: none"> - Floor model - Adjustable table height from 760mm (30") to 940mm (37") - Hinged stainless top plate - Mechanical outside tension control - Rigid casters with brake - P.C. Board electric control - Power Requirement: 11V, 50/60Hz 1HP - Strap width: 6mm (1/4") - 15.5mm (5/8") - Strap tension: 15kg (33lbs) - 45kg (100lbs) - Net weight: maximum 85kg (187 lbs) - Size: 864-914mm (34-36") L x 559-610mm (22-24") D x 737-787mm (29-31") H - No specific colour required 	<p>TP-202</p> <p>Option: Adjustable table height from 760mm (30") to 930mm (37")</p> <p>Size: 900mm (35") L x 587mm (23") D x 760mm (30") H</p>	Transpak	Colour: Dark Blue	1	YES	NO
70	POST-04	Mail Sorter Unit - Complete with Base & Worksurface	<ul style="list-style-type: none"> - 279mm (11") and 305mm (12") W pockets for mail sorting - Minimum 25mm (1") thick standard low-pressure laminate work surface is 660-711mm (26-28") D and adjusts within cabinet on 12.7mm (1/2") H increments - All-welded steel cabinet construction - Steel back panel of cabinet has one (1) 70-83mm (2.75-3.25") diameter cable management cut-out - Shelves adjust on 12.7mm (1/2") H increments - Size: 889-940mm (35-37") W x 508-559mm (20-22") D x 2007-2057mm (79-81") H - Finish: Black - Edging: Black 	<p>SA3680G1</p> <p>Kwik-File Satellite Sorter</p> <p>Two (2) Columns at 11" wide</p> <p>Size: 914mm (36") W x 533mm (21") D x 2032mm (80") H</p>	Mayline Company	Finish: Black Edging: Black	1	YES	YES
71	RECY-01	Recycle Container - Office	<ul style="list-style-type: none"> - Contains post-consumer recycled resin (PCR) - Size: 356-406mm (14-16") L x 229-279mm (9-11") W x 356-406mm (14-16") H - Minimum capacity: 27 litres (28-1/8 qt.) - Universal recycling symbol printed in white on side of recycling container - Colour: Blue with white printing 	<p>2956-73</p> <p>FG295673</p> <p>Desk-side recycling container with universal recycle symbol</p> <p>Size: 356mm (14") L x 254mm L (10") x 381mm (15") H</p>	Rubbermaid Commercial Products	Colour: Blue with white printing	440	YES	NO
72	RECY-02	Recycle - Barrel Container Heavy Duty, Square SEE DOLL-01	<ul style="list-style-type: none"> - Must be compatible with DOLL-01 - Square shaped - Contains post-consumer recycled resin (PCR) construction - Size: 584-635mm (23-25") L x 584-635mm (23-25") W x 711-762mm (28-30") H - Volume capacity : minimum 152 litres (40 gal) - Universal recycling symbol printed in white on side of recycling container - Colour: Blue with white printing 	<p>3536-73 BRUTE®</p> <p>FG353673</p> <p>Square Recycling Container without Lid</p> <p>Size: 597mm (23.5") W x 597mm (23.5") D x 737mm (29") H</p>	Rubbermaid Commercial Products	Colour: Blue with white printing	18	YES	NO
73	SAND-01	Belt Disc Sander - Table Model	<ul style="list-style-type: none"> - Table model - Sanding Belts: S8-436L - Size 101mm (4") x 915mm (36") minimum - Belt Disc Sander - Size 150mm (6") diameter minimum - Belt lift 0-90°, 2000SFPM - Disc Speed 3450 SFPM - Motor 5.2A, 110V, 1 phase 60Hz - Voltage: 110V, 1 phase, 60Hz - Motor is sealed ball bearing construction - Adjustable tilting tables - Belt tracking system - Commercial grade - Size: 406-457mm (16-18") L x 330-381mm (13-15") W x 254-305mm (10-12") H - Maximum weight: 16 Kg (36 lbs) - No specific colour required 	KC-705L-5	King Canada Industrial Inc.	Non applicable	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
74	SANI-01	Hand Sanitizer - Freestanding Stand and Touch Free Dispenser	<ul style="list-style-type: none"> - Must be compatible with: Deb® Instant FOAM IFS1TF - Freestanding - Dispenser to be touch free - To have a drip tray - Battery operated - Includes signage (English/French) - Stand Colour: Black - Dispenser Colour: Black 	<p align="center">92752</p> <p>Must be compatible with: Deb® Instant FOAM IFS1TF</p>	DEB Group	Stand Colour: Black Dispenser Colour: Black	52	YES	NO
75	SECU-02	Blue Bag	<ul style="list-style-type: none"> - Re-useable minimum 2000 trips - Tamper evident zipper closure - Minimum weight capacity 3.2 kg (7 lbs) - Construction: Water-resistant polyvinyl chloride (PVC)-coated nylon - Size: 279-330mm (11-13") W x 381-432mm (15-17") H - Includes a reversible address card - Colour: Blue 	<p align="center">RLG52106</p> <p>304mm (12") W x 406mm (16") H</p>	The RO-EL Group	Colour: Blue	450	YES	NO
76	SHEL-01	Utility Shelf - Wall Mounted; Five (5) qty. Hooks / Four (4) qty. Holders,	<ul style="list-style-type: none"> - Shelf and Bracket: 18 gauge minimum thickness stainless steel - Five (5) qty. Hooks & Four (4) qty. Holders - Hooks: 14 gauge minimum thickness stainless steel - Holders: Spring-activated rubber cams on plated steel retainers, to hold a mop or broom handle with a diameter 13mm (0.5") - 32mm (1.25") - Exposed surfaces in satin finish 	<p align="center">9934</p> <p>Size: 1118mm (44") W x 203mm (8") D x 349mm (13.75") H</p>	Bradley Corp.	Hook Metal: Stainless Steel 14 ga. Shelf & Bracket: Stainless Steel 18 ga. Finish: Satin	40	YES	NO
77	SHEL-02	Hooks - Wall Mounted; Hat and Coat Rack;	<ul style="list-style-type: none"> - Surface-mounted hat and coat rack - Backplate: 22 gauge minimum thickness stainless steel - Hooks: Six (6) Hooks; 14 gauge minimum thickness stainless steel - Size: 1499-1549mm (59-61") W x 51-76mm (2-3") D x 178-229mm (7-9") H - Hooks: six (6) - Exposed surfaces in satin finish 	<p align="center">9946</p> <p>Size: 1524mm (60") W x 64mm (2.5") D x 184mm (7.25") H</p>	Bradley Corp.	Metal: Stainless Steel 14 ga. Finish: Satin	1	YES	NO
78	SHOE-01	Shoe Polisher - Portable, Electric	<ul style="list-style-type: none"> - Portable - Minimum two (2) brushes included - Die-cast zinc alloy polisher - Electroplated finish - Toe-tip control switch - 110 volt - Frame Colour: Black - Brushes: Black 	<p align="center">BECK Deluxe Shoe Polisher</p> <p>Two (2) Brushes Included 110 Volt</p>	SEA Products	Frame Colour: Black Brushes: Black	4	YES	NO
79	SHOV-01	Safety Shovel - Two-Piece	<ul style="list-style-type: none"> - Size: 254-305mm(10-12") L x 330-381mm (13-15") W x 965-1016mm (38-40") H - Handle: Standard D-grip - Medium Blade - Non-sparking polypropylene - Corrosion-proof and chemical resistant - Anti-static agent in blade - Two (2)-piece construction disassembles - Locking mechanism - Working temperature range: minimum -30°C (-22°F) to minimum 80°C (176°F) - Variety of blade and handle configurations - No specific colour required 	6892SS	Remco Products Inc.	Colour: Black and green	3	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
80	SIGN-01	"Caution" Sign - Floor	<ul style="list-style-type: none"> - Durable plastic construction - Bi-Lingual "Caution" in English and French text (Two-Sided) - Corrosion and fade resistant - Plastic arm to allow non-obstructive placement - Flexible locking-style hanger - Size: 254-305mm (10-12") W x 279-330mm (11-13") D (open) x 610-660mm (24-26") H - Folding design - Caution warning messages imprinted in English and French on two (2) sides - ANSI compliant graphics - graphic to be of man slipping within triangular shape - Colour: Two-sided bright yellow to meet Occupational Safety and Health Administration (OSHA) requirements 	<p>6112 Floor Sign</p> <p>Bi-Lingual "Caution" in English and French text (Two-Sided)</p> <p>Size: 279mm (11") W x 305mm (12") D x 635mm (25") H (open)</p>	Rubbermaid Commercial Products	Colour: Yellow	108	YES	NO
81	SIGN-02	"Closed for Cleaning" Sign - Hanging	<ul style="list-style-type: none"> - Sign and pole combination blocks doorway - Minimum 5mm (3/16") grommets on all four (4) corners - Torsion action to secure pole - Soft, pliable sign - Bi-lingual "Closed for Cleaning" in English and French - Size: 1245-1295mm (49-51") W (max. open) x 19-32mm (0.75-1.25") D x 305-356mm (12-14") H - Colour: Yellow 	<p>9S16 Site Safety Hanging Sign</p> <p>Bi-Lingual "Closed for Cleaning" in English and French</p> <p>Size: 1270mm (50") W (max. open) x 25mm (1") D x 330mm (13") H</p>	Rubbermaid Commercial Products	Colour: Yellow	19	YES	NO
82	SLAT-01	Slatboard - Includes Wall Mounted Panel & Peg Hooks	<ul style="list-style-type: none"> - Panels to be 22 gauge minimum thickness steel construction - Powder coat finish - Panels made of 64-89mm (2.5-3.5") high individual slats and spaces on 64-89mm (2.5-3.5") centers when assembled - Colour: White - Accessory: - 229-279mm (9-11") long peg hook - 36 chrome peg hooks required 	<p>-WB613320WH Slatwall Panel-package of four (4)</p> <p>Size: 1219mm (48") W x 1219mm (48") H</p> <p>Included Slatwall Accessories items:</p> <p>T9A331353- 10"L Peg Hook-three (3) packages of twelve (12) required (total of 36 hooks)</p>	Global Industrial Canada Inc.	Slatboard Finish: White Powder Coat Peg Hook Finish: Chrome	3	YES	NO
83	STAN-01	Stanchion - Complete with base post & retractable belt SEE STAN-02	<ul style="list-style-type: none"> - Must be compatible with STAN-02 - Powder-coated post - Size: 940-991mm (37-39") H x 38-64mm (1.5-2.5") dia. post, 330-381mm (13-15") dia. base - Maximum 9.5kg (21lbs.) - Retractable belt - Standard tape end - Cast iron base, 330-381mm dia. (13-15") c/w with high durability, scuff-proof plastic cover - Satin black powder coated post - Black retractable belt - Black high durability, scuff-proof plastic cover (for cast iron base) - Accessories: - Two (2) sign holder adapter bracket - Colour: Black 	<p>890B Tensabarrier 890 Slimline series</p> <p>Base: 890B-STD Basics - 2286mm (7'-6") belt</p> <p>Includes a no-scuff ABS cover</p> <p>Standard tape end (STE)</p> <p>Two (2) black sign holder adapter bracket (BRACKET-HDSC)</p> <p>Size: 974mm (38.25") H, 51mm (2") dia. post, 342mm (13.5") dia. base</p>	Tensator	Post: 33S-T Satin Black powder coat, standard finish Belt: B9 Black (PMS 426)	74	YES	YES

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
84	STAN-02	Stanchion - Cart Eighteen (18) stanchions per cart SEE STAN-01	<ul style="list-style-type: none"> - Must be compatible with STAN-01 - Must fit within building elevator dimensions: 914mm (3'-0") W x 2134mm (7') L x 1981mm (6'-6") H - Transportation and storage of 18 stanchions (and accessories) - Size: 787-838mm (31-33") W x 1016-1067mm (40-42") x 1803-1854mm (71-73") H - Maximum 80 kg (175 lbs.) - Heavy gauge steel construction - 127-178mm (5-7") diameter locking casters - Padded slots to protect posts - Storage tray (for accessories) - Rubber bumpers - Colour: Powder coated black 	3035 Tensabarrier Deluxe Post Storage Cart Size: 815mm (32") W x 1040mm (41") D x 1830mm (72") H	Tensator	Colour: Black	4	YES	YES
85	STOR-06	Storage Container - Portable Stacking Tote, for Ear Pieces	<ul style="list-style-type: none"> - Reusable - Solid bottom - Stacking when closed or nesting when open - Volume of minimum 0.02 cu.m. (0.70 cu.ft.) - Lockable attached metal hinge lids - Contoured handles - Textured bottom - Quick-release label area on attached hinged cover and ends - Molded-in 10mm (0.25 to 3/8") diameter reinforced holes for standard security ties - Footprint: 483-533mm (19-21") L x 279-330mm (11-13") W x 178-229mm (7-9") H - Outside top dimensions: 483-533mm (19-21") L x 279-330mm (11-13") W - Outside bottom dimensions: 406-457mm (16-18") L x 229-279mm (9-11") W - Inside top dimensions: 432-483mm (17-19") L x 229-279mm (9-11") W - Inside bottom dimensions: 381-432mm (15-17") L x 203-254mm (8-10") W - Total weight: maximum 1.5 kg (3.3 lbs) - No specific colour required 	FP075 Stack-N-Nest FlipPak Container Stackable Totes & Lockable Hinged Lids	Orbis Corporation	Colour: Blue	30	YES	NO
86	STOR-12	Storage Racking Cantilever Bar - Stock Racking	<ul style="list-style-type: none"> - Column Height: 2108-2159mm (83-85") - Arm Length: 330-381mm (13-15") - Single-sided system - Seven (7) arms per column - Seven (7) columns - Arm end stops: pipe & socket type - Indoor use - Limited to a series of minimum 1995 kg (4400 lbs) loads side by side including the weight of the cantilever racking 	Cantilever Bar - Stock Racking	Generic Spec	No specific colour required	6	YES	NO
87	STOR-14	Storage Racking - Combination Vertical Rack	<ul style="list-style-type: none"> - Overall Dimensions: 889-940mm (35-37") W x 584-635mm (23-25") D x 2108-2159mm (83-85") H - Vertically stores bars minimum 305mm (12") long - Three (3) shelves - Minimum 203mm (8") deep arms divided into three (3) sections - Weight range: 56- 58.9 kg (125-130 lbs) - Load capacity: Minimum 1360 kg (3000 lbs) - Finish: Enamel - Colour: Blue 	RL922 Size: 915mm (36") W x 610mm (24") D x 2134mm (84") H	Kleton	Colour: Durable blue enamel finish	6	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
88	TOOL-01	Tool Cabinet - Industrial Duty Mobile Service Benches	<ul style="list-style-type: none"> - Must fit within building elevator dimensions: 914mm (3'-0") W x 2134mm (7') L x 1981mm (6'-6") H - Size: 1041-1092mm (41-43") W x 584-635mm (23-25") D x 914-965mm (36-38") H - Weight: maximum 125 Kg (275lbs) - 16-gauge minimum thickness all-welded steel construction - Laminated hardwood top - Four (4) drawers and one (1) door - Four (4) minimum dia. 127mm (5") non-marking casters - two (2) rigid casters and two (2) swivel casters with brake - Durable enamel finish - Shipped assembled - Capacity: minimum 544 Kg (1200 lbs.), evenly distributed - Top: Laminated Hardwood - Shell: Powder-coat paint - Colour: Grey 	<p>ML327</p> <p>Four (4) Drawers & One (1) Door with casters</p> <p>Size: 1066mm (42") W x 610mm (24") D x 940mm (37") H</p> <p>Load capacity 545 kg (1200 lbs.)</p>	Kleton	<p>Top: Laminated Hardwood</p> <p>Shell: Powder-coat paint</p> <p>Colour: Grey</p>	14	YES	NO
89	TOOL-02	Tool Cabinet - Professional Tool storage	<ul style="list-style-type: none"> - Must fit within building elevator dimensions: 914mm (3'-0") W x 2134mm (7') L x 1981mm (6'-6") H - Size: 1270-1321mm (50-52") W x 483-533mm (19-21") D x 1041-1092mm (41-43") H - Eleven (11) drawers - Caster Size: minimum 150mm (6") x minimum 50mm (2"), heavy-duty type - Load Rating: minimum 1587 kg (3500 lbs) - Top Surface: Thick rubber mat - Keyed locking system - Double slides on 127mm (5") or deeper drawer support 79 Kg (175 lbs) - Ball-bearing drawer slide type - Drawer slide load rating: minimum 50kg (110 lbs) - Drawer latching system - Storage Capacity: minimum 0.286 sq.m. (4433 sq.in.); 0.33 cu.m. (20,044 cu.in.) - Non-slip drawer liners - Material: Steel - Finish: Paint - Colour: Red 	<p>PCA-5211RD</p> <p>Professional Series 1308mm (51.5") wide</p> <p>Eleven (11) drawer cabinets</p> <p>Size: 1314mm (51.75") W x 508mm (20") D x 1073mm (42.25") H</p>	Waterloo Industries	<p>Material: Steel</p> <p>Finish: Paint</p> <p>Colour: Red</p>	3	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
90	TROL-01	Cleaning trolley with multi-surface, trays, buckets, mops and mop press	<u>Trolley:</u> - Designed for surface cleaning purposes. - Minimum three (3) shelves; Holds minimum two 25L pails on open bottom shelf c/w Mop press and press holder. Other shelves to hold minimum two smaller containers - Waste collection and storage area for cleaning utensils; - Drawer system for trays and boxes - One (1) plastic bin bag holder with support bars - Two (2) full trays - Two (2) 6 liter buckets with eight (8) colour coding clips - Four (4) height-adjustable 89-127mm (3.5-5") turning casters - One (1) frame holder set - One (1) extension support for garbage bag <u>Mop Press:</u> - 100% polypropylene (chassis) with stainless steel (lever) - Mop pressing; Ergonomic lever - Press Holder <u>Regular long pails:</u> - Two (2) 25 liter buckets with colour coding clips Microfiber mop: - 100% Polyester, cut pile mop Mop Frame: - Plastic frame - Plastic parts: Polypropylene, glass fiber, polyamide - Metal parts: Stainless steel	Origo 300FX Trolley: 120769 Accessories: Rectangular long pails: Two (2) 120945 Duo Press Holder: 121841 Duo Press: 120788 Micro Plus Mop: Two (2) 510822 Frame Origo Duo: Two (2) 111391 Telescopic Handle: Two (2) 119967	Vileda Professional	No specific colour required.	2	YES	NO
			<u>Mop Handle:</u> - Two (2) Telescopic handles: Aluminum construction - Adjustable from 100-180 cm - Handles to have an anti-slip top grip and colour-coded clips						
91	TRUC-01	Platform Hand Truck Heavy-Duty Platform Truck	- Chrome handle - 25-51mm (1-2") removable chrome handle - can be placed at either end of deck - Hardwood deck features minimum 51mm x 51mm (2" x 2") angle iron frame with hardwood decking - 178-229mm (7-9") dia. mold-on rubber casters - Two (2) rigid front casters and two (2) swivel back bolted-on casters - Minimum 907 Kg (2000 lbs) Capacity - Size: 1194-1245mm (47-49") L x 584-635mm (23-25") D x 254-305mm (10-12") deck height - Finish: Blue Enamel - Deck: Hardwood - Handle: Chrome	MB296 Heavy Duty Platform Truck 8" Mold-On Rubber Casters 2000 lbs Capacity Size: 1220mm (48") L x 610mm (24") D x 280mm (11") deck height	Kleton	Finish: Blue Enamel Deck: Hardwood Handle: Chrome	24	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
92	TRUC-02	Pallet Truck - Heavy Duty Manually operated	<ul style="list-style-type: none"> - Capacity: minimum 2495 Kg (5500lbs) - To include accessory 48" Load Backrest - 200-degree operational arc - Elevated height of minimum 198mm (7.8") - Three (3)-position control lever (lift, neutral, lower); fingertip control - Lowering can be actuated by hand or foot pedal release - Handle returns to an upright position once released - Large padded hand grip handle - Maximum 1334mm (52.5") turning radius - Galvanized hydraulic pump with overload relief valve - Climber rollers - Tapered forks and entry and exit rollers - Heavy-duty frame constructed of one-piece formed channel - Adjustable push rods - Cast-iron hangers - Grease fitting and pushing at all pivot points - Fork size: 1194-1245mm (47-49") L x 660-711mm (26-28")W - Frame is powder coat paint, - No specific colour required 	EPT-55 / 27x48 Galvanized Manual Pallet Truck Capacity: 5500lbs (2500kg) To Include Accessory 1219mm (48") Load Backrest	Blue Giant Equipment Corp.	Frame: Powder Coat Paint	2	YES	NO
93	TRUC-05	Pallet Truck - Semi-Electric Pallet Truck	<ul style="list-style-type: none"> - Manual Operation for lifting and lowering loads - Self-propelled movement - Ergonomic quick lift pump design only requires five (5) pumps to reach maximum lift for loads minimum 200kg (441 lbs) - Automatic neutral braking when throttle is released - Three (3)-position control handle - 229-279mm (9-11") polyurethane drive wheels with minimum 75mm (3") - polyurethane load rollers provide a smooth ride - Helper rollers - Raised height: minimum 203mm (8") - Lowered height: maximum 83mm (3.3") - Size: 660-711mm (26-28") W x 1194-1245mm (47-49") L - Battery discharge indicator included - Load capacity: minimum 1000 kg (2200 lbs.) 	Model LT469	Tenaquip (supplier)	No specific colour required.	1	YES	NO
94	VACU-01	Vacuum	<ul style="list-style-type: none"> - Wet Vacuum - Tank and head constructed in structural foam - Motor: 1,200 W, minimum 1.6 Hp - Minimum 2540mm (100") hose water lift - Airflow: 95 cfm - Minimum 76 liter (20 gallon) tank - Pumps water at a rate of minimum 227 liters (60 gallons) per minute - Dump hose included - Sump pump enabling continuous pumping of fluid - Power Cord Length: 12.8-13.7 meters (42-45') - Hose Length: 3-3.6 meters (10-12') - Weight: Maximum 38.5 KG (85 Lbs) - Pump power: 500 Watts - Output: minimum 60 gpm - Noise Level dB(A): Maximum 64 dB(A) - Speeds: One (1) Speed - Vacuum Motor Stages: Two (2) Stages - Type: Centrifugal - Ball float wet shut-off - Structural foam tank and head to be rustproof - Float activated sump pump - Submersible pump made of high-impact plastics - Motor to have a stainless steel shaft and triple seal system and has a thermal protection device to prevent overheating - No specific colour required 	WV 1800P WV 1800 Series High Capacity Wet Vacuum	Nace Care Solutions	Colour: Blue	6	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
95	VACU-02	Backpack Vacuum	<ul style="list-style-type: none"> - One (1) 38-51mm (1.5-2") static-dissipating vacuum hose - One (1) minimum 15 meter (50') extension cord - Two (2) Intercept filters - Watts: 1188 W - Weight: maximum 4.5 Kg (10 lbs) - Decibels: maximum 67 DBA - Airflow: 150 CFM - Static Lift: 2540mm (100") - Amps: 9.9 A - Capacity: 6.6L (6 qt.) - Gel batteries - Four (4) level filtration: 4703 sq. cm (728.95 sq. in) with HEPA level filtration - 9.4 liters (10 quart) filter trap - Ergonomic and adjustable harness - Integrated tool belt - Includes a thermal protector shut-off switch Accessories: <ul style="list-style-type: none"> - 343-368mm (13.5-14.5") floor tool - Wand: 1067mm to 1499mm (42" to 59") aluminum telescoping wand that extend - 419-445mm (16.5-17.5") crevice tool - 64-89mm (2.5-3.5") dust brush with reducer - 114-140mm (4.5-5.5") - No specific colour required 	<p>Super QuarterVac HEPA</p> <p>Includes: One (1) 38mm (1-1/2") static-dissipating vacuum hose, one (1) 15 meter (50') extension cord and two (2) Intercept Micro® Filters</p> <p>Wand: 106290</p> <p>Tool kit: 107100</p>	ProTeam		1	YES	NO
96	VACU-03	Vacuum - Upright 15" wide	<ul style="list-style-type: none"> - Vacuum Motor: High performance, two-stage, minimum 1.6 hp (1200 watts), minimum 90" (228 cm) waterlift, minimum 105 cfm (50 l/s) airflow - Housing: injection molded, high-impact ABS plastic - On-board extension hose - Brush Drive: Non-slip toothed belt, enclosed, electronic safety clutch and speed control - Brush Speed: minimum 5400 brush contacts per minute, minimum 2700 rpm - Brush Motor: Automatically sets brush height for type of flooring - electronic sensor - Dust Bag: Triple-layer bag, minimum 5.3 L (323 cu.in.), enclosed, top-loading - Filtration: minimum 99.6% at 0.3 microns, minimum 490 sq.cm (76 sq.in.) filtration area HEPA filter, minimum 99.97% at 0.3 microns - Wheels: 51-75mm (2-3") diameter rubberized - Power cord: 12.2m-15.2 (40'-50'), double insulated - Electrical: 120V, 60 cycle 230V, 50 Hz - Agency Approval: Underwriters Laboratories (UL) Listed to U.S. and Canadian Safety Standards - Working Width: 356-406mm (14-16") - Height: 1143-1194mm (45-47") - Handle Weight: maximum 0.7 kg (1.5 lbs) (Weight with power cord: maximum 8.2 kg (18 lbs)) - Tools: On-board crevice and upholstery tools, dusting brush and clip - Industry approvals: CRI Indoor Air Quality Testing Program - Operating sound Level: maximum 69 DBA - No specific colour required 	<p>SRXP15</p> <p>Model No: 1.012-027.0</p>	Windsor Commercial Cleaning Equipment	Colour: Blue and Grey	18	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
97	VACU-04	Vacuum - Upright 12" wide	<ul style="list-style-type: none"> - Vacuum Motor: High performance, two-stage, minimum 1.6 hp (1200 watts), minimum 90" (228 cm) waterlift, minimum 105 cfm (50 l/s) airflow - Housing: Injection molded, high-impact ABS plastic - Brush Drive: Non-slip toothed belt, enclosed, electronic safety clutch & speed control - Brush Speed: minimum 5400 brush contacts per minute, minimum 2700 rpm - Brush Motor: Automatically sets brush height for type of flooring - electronic sensor - Dust Bag: Triple-layer bag, minimum 5.3L (323 cu.in.), enclosed, top-loading - Filtration: minimum 99.6% at 0.3 microns, minimum 490 cu.cm (76 cu.in.) filtration area optional HEPA filter, minimum 99.97% at 0.3 microns - Wheels: 50-75mm (2-3") dia. rubberized - Power cord: 12.2m-15.2 (40'-50'), double insulated - Electrical: Operates on 120V, 60 cycle 230V, 50 Hz - Agency Approval: Underwriters Laboratories (UL) Listed to U.S. and Canadian Safety Standards - Working width: 279-330mm (11-13") - Height: 1143-1194mm (45-47") - Handle Weight: maximum 0.7 kg (1.5 lbs) (Weight with power cord: maximum 8.2 kg (18 lbs)) - Tools: On-board crevice and upholstery tools, dusting brush and clip - Industry approvals: CRI Indoor Air Quality Testing Program - Operating sound Level: maximum 69 DBA - No specific colour required 	SRXP12 Model No: 1.012-024.0	Windsor Commercial Cleaning Equipment	Colour: Blue and Grey	18	YES	NO
98	WISE-01	Vise - Swivel Base, Table Model	<ul style="list-style-type: none"> - Swivel base vise - Jaw width: 76-127mm (3-5") - Jaw opening: minimum 127mm (5") - Throat Depth: minimum 55mm (2-5/32") - Grey iron castings construction - Fully enclosed spindle with smooth operation - Anvil back - Chrome finished handle - 360° swivel base - No specific colour required 	TEX251 Jaw width 4, jaw opening 7, thread depth 24/32 , 26.4 Lb	Aurora Tools	Not Applicable	4	YES	NO
99	WISE-02	Vise - Swivel Base, Table Model	<ul style="list-style-type: none"> - Swivel base vise - Jaw width: 178-229mm (7-9") - Jaw opening: minimum 203mm (8") - Throat Depth: minimum 101mm (4") - Grey iron castings construction - Fully enclosed spindle with smooth operation - Anvil back - Chrome finished handle - 360° swivel base - No specific colour required 	TEX253 Jaw width 8, jaw opening 8, thread depth 4 , 96.8 lb.	Aurora Tools	Not Applicable	6	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
100	WASH-01	Pressure Washer	<ul style="list-style-type: none"> - 8.5-9.5m (28-31') pressure hose - Spray Gun with wand and nozzle - Wall bracket - Remote box switch - Motor: 3HP TEFC - Volts: 230V - Motor Speed: minimum 1750RPM - Power cord: 7 Meters (23') - Pump: Interpump triplex plunger - Pressure: minimum 1500 psi - Flow: minimum 11 L/mini. (3 gal/min.) - Size: 656-737mm (27-29") x 508-559mm (20-22") x 330-381mm (13-15") - Chemical: Integral adjustable low - pressure injector - Unloader: Integral adjustable unloader - No specific colour required 	MPU4500EXUP 30' Pressure Hose Gun with Wand Nozzle Wall Bracket Remote Box Switch Motor: 3HP TEFC Volts: 230V Motor Speed: 1750RPM Pressure: 1500 psi Flow: 11 L/min. (3 gal/min.)	Dynablast	Not Applicable	1	YES	NO
101	WASH-02	Pump Sprayer - Portable	<ul style="list-style-type: none"> - Heavy duty minimum 11 liter (3 gallon) sprayer - Carry strap - Rigid thermoplastic polymer tank - 76-102mm (3-4") mouth opening - 229-279mm (9-11") polymer pump - Discharge valve and pressure relief valve - 1016-1118mm (40-44") L polyethylene lined hose - Flexible 381-432mm (15-17") wand - Hose spring - In line filter - Polymer adjustable and fixed fan spray tips - Pivoting external carry handle - No specific colour required 	300HDPI - Heavy Duty 3 Gallon Sprayer 3 gallon operating capacity, Rigid thermoplastic Polymer Tank Extra wide 3-1/4" Mouth Opening, Discharge valve and pressure relief valve 42" poly lined hose, 16" wand In line filter, Polymer adjustable and fixed fan spray tips Pivoting external carry handle	Gilmour Commercial	Colour: Black	2	YES	NO
102	WASH-03	Fabric Steamer - Floor Model, Mobile	<ul style="list-style-type: none"> - Die cast aluminum outer housing - Easy-to-read water level sight gauge - 1524-1829mm (5-6") Hose - 127-178mm (5-7") plastic head - 360 degree swivel casters - Minimum 1500 watt heating element - 50/60 Hertz electrical system - Stainless steel boiler tank - Minimum 4 Liters (1 Gallon) water tank - No water lines - Colour-coded high temperature wiring - Preheat and steam settings - Steams for 1.5 to 2 hours per filling - Automatic shut-off - 360 degree swivel casters - Size: 483-533mm (19-21") W x 254-305mm (10-12") D x 1524-1575mm (60-62") H - No specific colour required 	J-4000 Jiffy Steamer from the Pro-Line Series Standard 6" Plastic Head 1500 watt Incoloy Heating element 304 Stainless Steel boiler tank Colour-coded high temperature wiring Convenient Preheat and Steam Settings 360 degree Swivel Casters	Jiffy Steamer, LLC	Colour: Grey	1	YES	NO
103	WASH-04	Can Washer - For Recycling & Waste Containers, Floor Model	<ul style="list-style-type: none"> - Non-electrical - Foot pedal operated - Can wash up to a 19 Liter (5 gallon) pail or bucket - Jet spray nozzle - Fastens to floor - Plumbed installation for cold water only - Automatic safety locks - Removable drain screen - Installation for cold and hot water - Two (2) hand shutoff valves, two (2) shock - Height: 711-762mm (28-30") - Diameter: 660-711mm (26-28") - Stainless Steel Bowl - Cast Iron Legs 	Aervoid 5-B Aervoid Jet Can Washer Foot pedal operated Installation for cold and hot water Two (2) hand shutoff valves, two (2) shock	Chicago Can Company	Stainless Steel Bowl Cast Iron Legs	1	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
104	WASH-05	Steamer - Multi-use Commercial Steam Cleaner / Extractor, Wet/Dry Vacuum, Floor Model, Mobile	<ul style="list-style-type: none"> - Functions: steam cleaner, steam extractor, and wet/dry vacuum - Steams in conjunction with a vacuum function - 25-piece accessory kit included - Minimum 2L detergent tank - Minimum 87 PSI operating pressure - Adjustable pressure control - Minimum 7L water capacity/5L waste water capacity - Light and sound indicators when water level is low - Wattage: 1700W - 2 elements - Boiler temperature: 150-160°C (302-320°F) - Tip temperature: minimum 118°C (245°F) - Electrical cord length: 4.9m (16') - 6m (20') - Steam hose length: 2.7m (9')- 3.4m (11') - Tank construction: 18/10 stainless steel - Overpressure exhaust valve - Pressure switch for pressure control - Safety thermostats and thermofuse to control temperature in the boiler - Low tension handle controls - Size: 787-838mm (31-33") W x 483-533mm (19-21") D x 991-1041mm (39-41") H - No specific colour required 	Enviromate FLEX EF700	Reliable Corporation	Stainless steel	1	YES	NO
105	WAST-01	Waste Container	<ul style="list-style-type: none"> - All-plastic construction; chip, rust and dent resistant - Rolled rim - Size: 229-279mm (9-11") W x 330-381mm (13-15") D x 356-406mm (14-16") H - Capacity: Minimum 26.6 L (28 1/8 qt.) - Colour: Black 	FG295600 BLA 2956 Wastebasket, Medium Size: 260mm (10.2") W x 365mm (14.4") D x 381mm (15") H	Rubbermaid Commercial Products	Colour: Black	523	YES	NO
106	WAST-04	Waste Collector - Heavy-duty, Mobile, Complete with Slim Waste Container	<ul style="list-style-type: none"> - High capacity: Minimum 454.25 liters (120 gallons), minimum 181.5 kg (400 lbs) - Easy-access rear doors - Waste sortation containers and can liner retainer - Built in garbage bag holder - Interior sortation container - Integrated storage for cleaning supplies - No lid - Size: 1295-1346mm (51-53") L x 686-737mm (27-29") W x 1067-1118mm (42-44") H - Waste collector colour: Black - Interior container colour: Yellow 	FG9W7100 BLA 9W71 Mega Brute Mobile Waste Collector-3 pack Include Slim Jim Container and Can Liner Retainer - 3540 Capacity: 120 gallons No lid	Rubbermaid Commercial Products	Waste Collector: Colour: Black Interior Container: Colour: Yellow	2	YES	NO
107	WAST-05	Waste Container - Half Barrel	<ul style="list-style-type: none"> - Must accept a 660mm (26") x 914mm (36") garbage bag - Crack resistant - Half round shape - Size: 508-559mm (20-22") L x 254-305mm (10-12") W x 686-737mm(27-29") H - Capacity: minimum 79.5 Liter (21 gal) - No lid - Colour: Gray 	FG352000 GRAY 3520 Untouchable® Half Round Container Capacity: 21 gallons Size: 533mm (21") W x 279mm (11") D x 711 (28")mm H	Rubbermaid Commercial Products	Colour: Gray	27	YES	NO
108	WAST-06	Waste Container - Round Heavy Duty Barrel SEE DOLL-02	<ul style="list-style-type: none"> - To be compatible with DOLL-02 - Capacity: minimum 121 liters (32 gallon) - Must accept 889mm (35") x 1270mm (50") garbage bags - All-plastic construction: rust, chip, peel and dent resistant - Reinforced rims - Built-in handles - Double-ribbed base - No lid - Meets Hazard Analysis and Critical Control Points (HACCP) guidelines - Size: 533-584mm (21-23") diameter x 686-737mm (27-29") H - Colour: Gray 	FG263200 GRAY 2632 BRUTE® Container without Lid Capacity: 32 gallons Size: 557mm (21.9") diameter x 705mm (27.8") H	Rubbermaid Commercial Products	Colour: Gray	8	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
109	WAST-08	Waste/Recycle Unit - Two (2) bins connected to create one (1) unit	<ul style="list-style-type: none"> - Two (2) bins required per unit - Rigid plastic liner and lift handles to meet UL94 flammability standard - Lid: Square opening with a durable finish - one lid each bin - Size: 229-279mm (9-11") x 432-483mm (17-19") x 889-940mm (35-37") - Capacity: 60.5 litres (16 gallon) - 64.3 litres (17 gallon) - Elevated feet - Fingerprint proof - No signage/label required - Connectors required to connect two (2) bins together to create one (1) unit. - Body Colour: Black - Top Colour: Metal/Grey 	<p>Kaleidoscope XL Series™ RC-KD17 - 17 Gallon</p> <p>Two (2) bins required (1 Waste & 1 Recycle) to create one (1) WAST-08 unit</p> <p>Includes rigid plastic liner and lift handles</p> <p>Lid: RC-KD TOP 17 SQ OPEN - one lid each bin - total required two (2) per WAST-08 unit</p> <p>Connectors required to connect two (2) bins together to create one (1) unit.</p> <p>Note: No signage/label required Size: 241mm (9.5") W x 464mm (18.25") D x 902mm (35.5") H</p>	Ex-Cell Kaiser Manufacturing & Design	Body Finish: Black Texture (BLX)	2	YES	NO
110	WAST-09	Waste - Barrel Container Round Heavy Duty Barrel SEE DOLL-02	<ul style="list-style-type: none"> - To be compatible with AIRR-04 - Capacity: Minimum 76 liter (20 gallon) - Size: 483-533mm (19-21") Dia. x 559-610mm (22-24") H - All-plastic construction; rust, chip, peel and dent resistant - Reinforced rims - Built-in handles - Double-ribbed base - No lid - Meets Hazard Analysis and Critical Control Points (HACCP) guidelines - Colour: Gray 	<p>FG262000 GRAY</p> <p>2620 BRUTE® Container without Lid</p> <p>Capacity: 20 Gallons</p> <p>Size: 492mm (19.4") diameter x 582mm (22.9") H</p>	Rubbermaid Commercial Products	Colour: Gray	8	YES	NO
111	XRAY-09	X-Ray Tray Pass-Through Tote Box	<ul style="list-style-type: none"> - Polyethylene (Biphenyl A-free) construction - Size: 432-483mm (17-19") L x 279-330mm (11-13") W x 127-178mm (5-7") D - Capacity: minimum 13.2 L (3 1/2 gal) - Colour: Clear/White 	<p>FG350900 WHT</p> <p>3509 Food/Tote Box</p> <p>Size: 457mm (18") L x 305mm (12") W x 152mm (6") H</p>	Rubbermaid Commercial Products	Colour: Clear/White	30	YES	NO
112	LIGH-01	LED Retractable 50ft Cord Reel Dual Hanging Hooks (4 per pack)	<ul style="list-style-type: none"> - Retractable cord reel - Cord reel 12m-15.24m (40-50 ft.) - Powder coated steel housing reel - LED lamps - Intensity: 450 lumens minimum - On/Off switch built into handle - Brightness levels: Minimum quantity of two (2) - Dual hanging hooks rotate 360° - Top and bottom protective bumpers - Includes reel hanging hardware - Colour box packaging - Cord type: SJT - Gauge: 18/2 minimum thickness - Total max. rating: 3.9W, 120V - Max. power: 3.9W - Max. voltage: 120V - Master pack: 4 	5050SM	Alert Stamping & Manufacturing	Colour: No specific colour required.	10	YES	NO

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
113	TRUC-03	Semi-Electric Pallet Mover	<ul style="list-style-type: none"> Standard manual pallet truck-style pumping operation - Self-propelled movement - Built-in charger - Battery discharge indicator w/ automatic cut-off. - Capacity: 1500kg (3300 lbs.) minimum - Weight: 175kg (385 lbs.) maximum - Load centre: 559-610mm (22-24") - Wheelbase: 1270mm (50") minimum - Lowered fork height: 64mm (2.5") maximum - Raised fork height: 178-229mm (7-9") - Handle Height: 1295mm (51") maximum - Fork blade width: 127-178mm (5-7") - Fork overall width: 660-711mm (26-28") - Fork length: 1168-1270mm (46-50") - Overall length: 1676-1778mm (66-70") - Turning radius: 1524mm (60") maximum - Travel speed (laden / unladen): 4.1/4.5kph (2.6/2.8 mph) - Max. gradeability (laden / unladen): 4/10 % - Battery voltage: 2 x 12V/38 	Model: ESET33N	Mobile	Colour: No specific colour required.	1	YES	NO
114	WAST-10	Waste/Recycle Unit - Waste/Recycle Unit - Five (5) bins connected to create one (1) unit.	<ul style="list-style-type: none"> - Five (5) bins required per unit - Rigid plastic liner and lift handles to meet UL94 flammability standard - Lid: Square opening with a durable finish - one lid each bin - Size: 229-279mm (9-11") x 432-483mm (17-19") x 889-940mm (35-37") - Capacity: 60.5 litres (16 gallon) - 64.3 litres (17 gallon) - Elevated feet - Fingerprint proof - No signage/label required - Connectors required to connect five (5) bins together to create one (1) unit. - Body Colour: Black - Top Colour: Metal/Grey 	Kaleidoscope XL Series™ RC-KD17 - 17 Gallon Five (5) bins required (1 Waste & 4 Recycle) to create one (1) WAST-XX unit Includes rigid plastic liner and lift handles Lid: RC-KD TOP 17 SQ OPEN - one lid each bin - total required five (5) per WAST-XX unit Connectors required to connect five (5) bins together to create one (1) unit. Note: No signage/label required Size: 241mm (9.5") W x 464mm (18.25") D x 902mm (35.5") H	Ex-Cell Kaiser Manufacturing & Design	Body Finish: Black Texture (BLX)	3	YES	NO
115	DELETED								
116	DELETED								

Group B: MAINTENANCE, HANDLING AND WASTE MANAGEMENT

Attachment 1b to Annex A

LISTED PRODUCT									
ITEM NO.	COMPONENT CODE	COMPONENT NAME/DESCRIPTION	SPECIFICATIONS FOR EQUIVALENT PRODUCTS	PRODUCT NUMBER/DESCRIPTION	MANUFACTURER	COLOUR/FINISH	QUANTITY	DELIVERY REQUIRED (Yes/No)	INSTALL REQUIRED (Yes/No)
117	TOOL-03	10" x 18" Metal Cutting Bandsaw	<ul style="list-style-type: none"> Cutting capacity at 90 deg: rectangle minimum 254mm x 457mm (10" x 18"); round minimum 254mm (10") dia. Cutting capacity at 45 deg: rectangle minimum 178mm x 238mm (7" x 9-3/8"); round minimum 254mm (10") dia. Four speeds (114, 196, 288, 377 RPM) Blade size: 3099mm x 25mm x 8mm (122" x 1" x 0.32") 2 HP motor, 15A, 1-phase, 60Hz, 220V Size: 1727-1829mm x 635-737mm x 1016-1118mm (68-72" x 25-29" x 40-44") Weight: 288 kg (634 lbs.) maximum 	Commercial-grade metal cutting bandsaw (horizontal) Model: TLZ123	King Canada Industrial Inc.	Colour: No specific colour required.	1	YES	NO
118	OHSE-33	Industrial parts washing system	<ul style="list-style-type: none"> Size: 914-1016mm (36-40")L x 889-991mm (35-39"W) x 1041-1143mm (41-45")H Load capacity: 227kg (500 lbs.) minimum To include 6 x 20L of BioCircle cleaning solution Care service package to include at a minimum: <ul style="list-style-type: none"> 6 scheduled maintenance calls / year Use of the Bio-Circle parts washer Start-up of the BioCircle system and employee training. 	<ul style="list-style-type: none"> Item: Industrial parts washing system Manufacturer: BioCircle Starter Kit Maxi Model: AD503 To include 6 x 20L of BioCircle cleaning solution (AD008) 	King Canada Industrial Inc.	Colour: No specific colour required.	1	YES	NO
119	VACU-05	Vacuum	<ul style="list-style-type: none"> Convertible blower port Quiet-running motor On-board tool storage Large drain plug Heavy-duty rear wheel dolly and handle Tank capacity: 75L (16.5 gal) minimum Peak HP: 6.5 minimum CFM: 195 minimum Cord length: 5.5m (18ft.) minimum Weight: 13kg (29 lbs.) maximum To include 64mm (2-1/2") 9-piece accessory package and filter kit. 	NI799	Shop-Vac	Colour: No specific colour required.	4	YES	NO