

Part 1 General

1.1 REFERENCES

- .1 The Aluminum Association Inc. (AAI)
 - .1 AAI-Aluminum Sheet Metal Work in Building Construction-2002.
 - .2 AAI DAF45-03, Designation System for Aluminum Finishes.
- .2 American Society for Testing and Materials International (ASTM)
 - .1 ASTM A167-99(2004), Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.
 - .2 ASTM A240/A240M-07e1, Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications.
 - .3 ASTM A606-04, Standard Specification for Steel, Sheet and Strip, High-Strength, Low-Alloy, Hot-Rolled and Cold-Rolled, with Improved Atmospheric Corrosion Resistance.
 - .4 ASTM A653/A653M-07, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - .5 ASTM A792/A792M-06a, Standard Specification for Steel Sheet, 55% Aluminum-Zinc Alloy-Coated by the Hot-Dip Process.
 - .6 ASTM B32-04, Standard Specification for Solder Metal.
 - .7 ASTM B370-03, Standard Specification for Copper Sheet and Strip for Building Construction.
 - .8 ASTM D523-89(1999), Standard Test Method for Specular Gloss.
 - .9 ASTM D822-01(2006), Standard Practice for Filtered Open-Flame Carbon-Arc Exposures of Paint and Related Coatings.
- .3 Canadian Roofing Contractors Association (CRCA)
 - .1 Roofing Specifications Manual 1997.
- .4 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.32-M77, Sheathing, Membrane, Breather Type.
 - .2 CAN/CGSB-93.1-M85, Sheet Aluminum Alloy, Prefinished, Residential.
- .5 Canadian Standards Association (CSA International)
 - .1 CSA A123.3-05, Asphalt Saturated Organic Roofing Felt.
 - .2 AAMA/WDMA/CSA 101/I.S.2/A440-2008, Standard/Specification for Windows, Doors, and Unit Skylights.
 - .3 CSA B111-1974(R2003), Wire Nails, Spikes and Staples.
- .6 Green Seal Environmental Standards
 - .1 Standard GS-03-93, Anti-Corrosive Paints.
 - .2 Standard GS-11-97, Architectural Paints.
 - .3 Standard GS-36-00, Commercial Adhesives.
- .7 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Material Safety Data Sheets (MSDS).
- .8 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.

- .9 Product Data:
 - .1 Submit manufacturer's printed product literature for sheet metal flashing systems materials, specifications and datasheet and include product characteristics, performance criteria, physical size, finish and limitations.
 - .2 Submit two copies WHMIS MSDS - Material Safety Data Sheets
- .10 Shop Drawings:
 - .1 Shop drawings: submit drawings requested by Departmental Representative.
- .11 Samples:
 - .1 Submit duplicate 50 x 50 mm samples of each type of sheet metal material, finishes and colours.
- .12 Quality assurance submittals: submit following in accordance with Section 01 33 00.
 - .1 Manufacturer's Instructions: submit manufacturer's installation instructions and special handling criteria, installation sequence, cleaning procedures.

1.2 QUALITY ASSURANCE

- .1 Building 88 is a Heritage Building having a 'Classified' designation. All work is to respect the original design.
- .2 Pre-Installation Meetings: convene pre-installation meeting one week prior to beginning work of this Section and on-site installation, with contractor's representative and Departmental Representative to:
 - .1 Verify project requirements.
 - .2 Review installation and substrate conditions.
 - .3 Co-ordination with other building subtrades.
 - .4 Review manufacturer's installation instructions and warranty requirements.

1.3 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with manufacturer's instructions.
- .2 Waste Management and Disposal:
 - .1 Separate waste materials for recycling.

Part 2 Materials

2.1 Prefinished steel with factory applied silicone modified polyester,

- .1 Class F1S, Series 8000.
- .2 Colour selected by Owner / Departmental Representative from manufacturer's standard range.
- .3 Specular gloss: 30 units +/- 5 in accordance with ASTM D523.
- .4 Coating thickness: to be not less than 25 micrometres.
- .5 Resistance to accelerated weathering for chalk rating of 8, colour fade 5 units or less and erosion rate less than 20% to ASTM D822 as follows:

- .1 Outdoor exposure period 1000 hours.
- .2 Humidity resistance exposure period 1000 hours.
- .3 Base metal thickness 0.58 mm (26 gauge) unless indicated otherwise. Base metal to be hot-dipped galvanized steel with coating designation Z7275 (G90).

2.2 ACCESSORIES

- .1 Isolation coating: alkali resistant bituminous paint.
- .2 Plastic cement: to CAN/CGSB 37.5.
 - .1 Maximum VOC limit 50 g/L to SCAQMD Rule 1168 to GSES GS-36.
- .3 Underlay for metal flashing: SBS polymer modified membrane.
- .4 Sealants:
 - .1 Maximum VOC limit 50g/L to SCAQMD Rule 1168 to GSES GS-36.
- .5 Cleats: of same material, and temper as sheet metal, minimum 50 mm wide. Thickness:48 mm.
- .6 Fasteners: of same material as sheet metal, to CSA B111, flat head roofing nails of length and thickness suitable for metal flashing application.
- .7 Washers: of same material as sheet metal, 1 mm thick with rubber packings.
- .8 Touch-up paint: as recommended by prefinished material manufacturer.
 - .1 Maximum VOC limit 50 150 g/L to Standard GS-11 to SCAQMD Rule 1113.

2.3 FABRICATION

- .1 Fabricate metal flashings and other sheet metal work in accordance with applicable CRCA 'FL' series details and as indicated.
- .2 Form pieces in 2400 mm maximum lengths.
 - .1 Make allowance for expansion at joints.
- .3 Hem exposed edges on underside 12 mm.
 - .1 Mitre and seal corners with sealant.
- .4 Form sections square, true and accurate to size, free from distortion and other defects detrimental to appearance or performance.
- .5 Apply isolation coating to metal surfaces to be embedded in concrete or mortar.

2.4 METAL FLASHINGS

- .1 Form flashings, copings and fascias to profiles indicated of .48 mm thick galvanized steel, prefinished

2.5 REGLETS AND CAP FLASHINGS

- .1 Form recessed surface mounted reglets of 0.48 mm thick sheet metal to be built-in concrete masonry work for base flashings as detailed in accordance with CRCA FL series details, FL.

- .1 Provide slotted fixing holes and steel/plastic washer fasteners.
- .2 Cover face and ends with plastic tape

2.6 ALUMINIUM ELEMENTS

- .1 A-101/I.S.2/A440, for coating Classes 1, 2 and 3 respectively.

Part 3 Execution

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations, including product technical bulletins, handling, storage and installation instructions, and datasheets.

3.2 INSTALLATION

- .1 Install sheet metal work in accordance with CRCA FL series details, FL as detailed.
- .2 Use concealed fastenings except where approved before installation.
- .3 Provide underlay under sheet metal.
 - .1 Secure in place and lap joints 100 mm.
- .4 Lock end joints and caulk with sealant.
- .5 Install surface mounted reglets true and level, and caulk top of reglet with sealant.
- .6 Insert metal flashing into reglets under cap flashing to form weather tight junction.
- .7 Turn top edge of flashing into recessed reglet or mortar joint minimum of 25 mm. Lead wedge flashing securely into joint.
- .8 Caulk flashing at reglet, cap flashing with sealant.
- .9 Install pans, where shown around items projecting through roof membrane.

3.3 CLEANING

- .1 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.
- .2 Leave work areas clean, free from grease, finger marks and stains.

END OF SECTION 07 62 00