



DETAILED SCOPE OF WORK

7. BOLLARD C - S13 (10-473)
 - a. REMOVE BOLLARD COVER CLEATS
 - b. CLEAN AND COAT BOLLARDS, CONNECTING MEMBERS, ANCHOR PLATES AND COVER CLEATS
 - c. REINSTALL BOLLARD COVER CLEATS USING NEW FASTENERS
8. BASCULE FRAME - S13 (10-473)
 - a. SANDBLAST/POWER WASH AND CLEAN ALL STRUCTURAL COMPONENTS
 - b. INSPECT ALL WELDS
 - c. REMOVE CORRODED WELDS FROM JOINTS AND RE-WELD
 - d. REPLACE CORRODED FASTENERS
 - e. REMOVE CORRODED ANCHOR BOLTS AND NUTS
 - f. INSTALL NEW ANCHOR BOLTS AND NUTS
 - g. REPLACE CORRODED STIFFENER PLATES FROM FRAME BASE MEMBERS AT NORTH BASCULE FRAME
 - h. INSPECT LOWER JOINTS OF DIAGONALS AT NORTH BASCULE FRAME AND RE-WELD AS NECESSARY
 - i. PROVIDE DRAIN HOLES AT LOWER DIAGONAL JOINTS
 - j. & k. SUPPLY AND APPLY AN EPOXY BASED, TWO-COMPONENT, MICROBIALY-INDUCED-CORROSION RESISTANT COATING TO LOWER FRAME, DIAGONALS, CROSS MEMBERS AND COLUMNS (GEAR RACK EXCLUDED) & UPPER STRUCTURAL MEMBERS

drawing design

BASCULE FRAME FENDER
DRIVE UNIT AND
BOLLARD C

designed V.L. conçu

date SEP. 2015

drawn M.Z. dessiné

date NOV. 5, 2015

approved approuvé

date

project number no. du projet

project number no. du projet

drawing no. no. du dessin

S13

E-DRM/000-E 531132 Version 1