
**Washroom Buildings Recapitalization
Buildings 32, 34 & 38
Newman Sound Campground
Terra Nova National Park, NL
Proj. No.: R.079272.001**

Issued April 4, 2016

Section 06 05 73 – Wood Treatment

Page 1 of 2

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.

1.2 **REFERENCES**

- .1 American Wood-Preservers' Association (AWPA)
 - .1 AWP M2, Standard Inspection of Treated Wood Products.
 - .2 AWP M4, Standard for the Care of Preservative-Treated Wood Products.
- .2 Canadian Standards Association (CSA)
 - .1 CSA O80 Series, Wood Preservation.

1.3 **CERTIFICATES**

- .1 For products treated with preservative by pressure impregnation submit following information certified by authorized signing officer of treatment plant:
 - .1 Information listed in AWP M2 and revisions specified in CSA O80 Series, Supplementary Requirement to AWP M2 applicable to specified treatment.
 - .2 Acceptable types of paint, stain, and clear finishes that may be used over treated materials to be finished after treatment.

1.4 **WASTE MANAGEMENT AND DISPOSAL**

- .1 Do not dispose of preservative treated wood through incineration.
- .2 Do not dispose of preservative treated wood with other materials destined for recycling or reuse.
- .3 Dispose of treated wood, end pieces, wood scraps and sawdust at sanitary landfill approved by Departmental Representative.
- .4 Dispose of unused wood preservative material at official hazardous material collections site approved by Departmental Representative.
- .5 Do not dispose of unused preservative material into sewer system, into streams, lakes, onto ground or in other location where they will pose health or environmental hazard.

**Washroom Buildings Recapitalization
Buildings 32, 34 & 38
Newman Sound Campground
Terra Nova National Park, NL
Proj. No.: R.079272.001**

Issued April 4, 2016

Section 06 05 73 – Wood Treatment

Page 2 of 2

PART 2 **PRODUCTS**

2.1 **MATERIALS**

- .1 Preservative: to CAN/CSA-O80 Series standards, ACQ (Alkaline Copper Quaternary) Only.

PART 3 **EXECUTION**

3.1 **APPLICATION: PRESERVATIVE**

- .1 Treat lumber to CAN/CSA- O80 Series.
- .2 Following water-borne preservative treatment, dry material to maximum moisture content of 19%.

3.2 **APPLICATION: FIELD TREATMENT**

- .1 Comply with AWPA M4 and revisions specified in CAN/CSA-O80 Series, Supplementary Requirements to AWPA Standard M2.
- .2 Treat all field cuts with two (2) coats of ACQ (Alkaline Copper Quaternary)
- .3 Remove chemical deposits on treated wood to receive applied finish.

END OF SECTION