
Washroom Buildings Recapitalization
Buildings 32, 34 & 38
Newman Sound Campground
Terra Nova National Park, NL
Proj. No.: R.079272.001
Section 26 53 00 – Exit Signs

Page 1 of 3

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 00 - Cleaning and Waste Management.
- .3 Section 26 05 00 - Common Work Results – Electrical.

1.2 **REFERENCES**

- .1 Atomic Energy Control Board Regulations
- .2 Canadian Code for Preferred Packaging
- .3 Canadian Standards Association (CSA)
 - .1 CSA C22.2 No.141, Unit Equipment for Emergency Lighting.
 - .2 CSA C860, Performance of Internally-Lighted Exit Signs.
- .4 National Fire Protection Association (NFPA)
 - .1 NFPA 101, Life Safety Code.

1.3 **SUBMITTALS**

- .1 Product Data:
 - .1 Submit manufacturer’s printed product literature, specifications and datasheets and include product characteristics, performance criteria, physical size, finish and limitations.
- .2 Manufacturer’s Instructions: Provide to indicate special handling criteria, installation sequence, cleaning procedures and disposal.

PART 2 **PRODUCTS**

2.1 **SELF-POWERED UNITS**

- .1 Exit lights: to CSA C22.2 No.141-10 and CSA C860, packaged in accordance with the Canadian Code for Preferred Packaging guidelines.
- .2 Durable, extruded, one piece aluminum housing and face plates.
- .3 White LED light source.

Washroom Buildings Recapitalization
Buildings 32, 34 & 38
Newman Sound Campground
Terra Nova National Park, NL
Proj. No.: R.079272.001
Section 26 53 00 – Exit Signs

Page 2 of 3

- .4 Provide two pictogram films per face, for direction selection.
- .5 Energy efficient – consume less than 2.5 Watts in AC or DC mode.
- .6 Running Man.
- .7 Supply voltage: 120 V, ac.
- .8 Output voltage: 12 V dc.
- .9 Operating time: minimum 90 minutes.
- .10 Battery: sealed, maintenance free, warranty to Section 26 52 00 – Emergency Lighting, 1.5 – Emergency Lights.
- .11 Signal lights: solid state, for 'AC Power ON'.
- .12 Mounting: suitable for universal mounting directly on junction box and c/w knockouts for conduit. Removable or hinged front panel for easy access to batteries.
- .13 Cabinet: finish: standard.
- .14 Auxiliary equipment:
 - .1 Test switch.

2.2 DESIGN X1

- .1 Recessed, wall, end to wall, ceiling mounting as indicated.

PART 3 EXECUTION

3.1 INSTALLATION

- .1 Install exit lights to manufacturer's recommendations, listing requirements, NFPA standard and local regulatory requirements.
- .2 Connect fixtures to exit light circuits using RW90 wire in EMT conduit.
- .3 Connect emergency lamp sockets to emergency circuits.
- .4 Ensure that exit light circuit breaker is locked in on position.
- .5 Provide tests in accordance with Section 26 05 00 – Common Work Results - Electrical and Division 01.

**Washroom Buildings Recapitalization
Buildings 32, 34 & 38
Newman Sound Campground
Terra Nova National Park, NL
Proj. No.: R.079272.001
Section 26 53 00 – Exit Signs**

Page 3 of 3

3.2 CLEANING

- .1 Proceed in accordance with Section 01 74 00 – Cleaning and Waste Management.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION