

PART 1 - GENERAL

- 1.1 MEASUREMENT FOR PAYMENT
- .1 Removal of Asphalt Sidewalks - Removal of asphalt sidewalks will be measured in square metres (m<sup>2</sup>).
  - .2 Removal of Asphalt Pavement - Removal of asphalt pavement designated in the contract document or as directed by the Departmental Representative shall be measured by the square metre (m<sup>2</sup>), for thicknesses up to 100 mm. Thicknesses over 100 mm shall be paid by the square meter (m<sup>2</sup>) unit price, prorated on the basis of the price per 100 mm.
  - .3 Include incidental to this cost, all costs for the removal and disposal of existing granular materials in areas requiring full-depth asphalt replacement.
  - .4 The cost for saw cutting asphalt shall be incidental.
  - .5 If the Contractor removes or damages pavement or surfaces beyond the limits specified, such pavement and surfaces shall be replaced or repaired at the expense of the Contractor.

PART 2 - PRODUCTS

- 2.1 - NOT USED .1 NOT USED.

PART 3 - EXECUTION

- 3.1 PREPARATION
- .1 Prior to beginning removal operation, inspect and verify with Departmental Representative areas, depths and lines of asphalt pavement to be removed.
- 3.2 PROTECTION
- .1 Protect existing pavement not designated for removal, light units and structures from damage. In event of damage, immediately replace or make repairs to approval of Departmental Representative at no additional cost.

3.3 REMOVAL

- .1 Remove existing asphalt pavement to lines and grades as indicated on drawings.
- .2 Use equipment and methods of removal and hauling which do not damage or disturb underlying pavement.
- .3 Prevent contamination of removed asphalt pavement by topsoil, underlying gravel or other materials.
- .4 Provide for suppression of dust generated by removal process.
- .5 Remove existing asphalt pavement from site to approved landfill