

Part 1 General

- | | | |
|---------------------------------------|----|---|
| <u>1.1 REFERENCES</u> | .1 | American Society for Testing and Materials (ASTM) |
| | .1 | ASTM A 167-09, Standard Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip. |
| | .2 | Canadian Standards Association (CSA) |
| | .1 | CAN/CSA-B651-12, Accessible Design for the Built Environment. |
| <u>1.2 SUBMITTALS</u> | .1 | Submit manufacturer's product data sheets in accordance with Section 01 33 00. |
| | .2 | Indicate size and description of components, base material, surface finish inside and out, hardware and locks, attachment devices, description of rough-in-frame, building-in details of anchors for grab bars. |
| <u>1.3 CLOSEOUT
SUBMITTALS</u> | .1 | Provide maintenance data for accessories for incorporation into manual specified in Section 01 78 00. |
| <u>1.4 EXTRA
MATERIALS</u> | .1 | Provide special tools required for accessing, assembly/disassembly or removal for toilet and bath accessories |
| | .2 | Deliver special tools to Departmental Representative. |

Part 2 Products

- | | | |
|--------------------------|----|--|
| <u>2.1 COMPONENTS</u> | .1 | Toilet Tissue Dispenser: surface mounted, double roll type, stainless steel. |
| | .1 | Acceptable Products: American Specialties 0715, Bobrick B-265, Gamco TTD-2. |
| | .2 | Quantity: one per toilet compartment. |

- .1 Soap Dispenser: Surface mounted liquid soap, 1.14 L capacity.
 - .1 Acceptable Products: American Specialties 0347, Bobrick B-2111, Gamco G-16AP.
 - .2 Quantity: Refer to Drawings for locations.
- .2 Paper Towel Dispenser: for folded paper towels, stainless steel cabinet, surface mounted.
 - .1 Quantity: Refer to Drawings.
 - .2 Acceptable Products: American Specialties 210, Bobrick B-262, Gamco TD-2.
 - .3 Quantity: Refer to Drawings.
- .3 Mirrors, fixed: 6 mm tempered glazing, satin finish stainless steel angle frame, complete with concealed mounting hardware.
 - .1 Acceptable Products: American Specialties 0600, Bobrick B-290, Gamco A Series.
 - .2 Size: 460mm x 760mm.
 - .3 Quantity: Refer to Drawings for locations.
- .1 Waste Receptacle: surface mounted, 75.7 litres.
 - .2 Acceptable Products: Bobrick B-275, Gamco WR-1, American Specialties 825.
- .4 Coat Hook Strip
 - .1 Type 304 stainless steel, satin finish, 1.2 mm thickness, Hooks are 25 mm, 165mm H; project 55mm from wall of 2.8 mm thick . Mounting strip is 610 mm long x 100mm high and has 6mm return.
 - .2 Quantity: Refer to Drawings for locations
 - .3 Acceptable products: Bobrick Model 232x24, American specialties model 1307-3, Gamco Model HCS-1.

Part 3 Execution

3.1 INSTALLATION .1

Install and secure accessories rigidly in place as follows:

- .1 Stud walls: install steel back-plate to stud prior to plaster or drywall finish. Provide plate with threaded studs or plugs.
- .2 Hollow masonry units or existing plaster/drywall: use toggle bolts drilled into cell/wall cavity.
- .3 Solid masonry, marble, stone or concrete: use bolt with lead expansion sleeve set into drilled hole.
- .2 Use tamper proof screws/bolts for fasteners.
- .3 Fill units with necessary supplies shortly before final acceptance of building.

3.2 SCHEDULE

- .1 Locate accessories where indicated. Exact locations determined by Departmental Representative.
- .2 Refer to Drawings for quantities unless otherwise indicated.

END OF SECTION