



1 OFF MAIN CARGO ROPE DYFORM	34 LR, 200 kg/mm ² , 19mm DIA. x165m LONG	THIMBLE ONE END OTHER END PLAIN
1 OFF TOPPING ROPE	6 x36, FIBRE CORE, 200 kg/mm ² , 26mm DIA. x165m LONG	" " " " " "
2 OFF COMPENSATOR ROPES	6 x36 DYFORM	G (6) 200kg/mm ² , 26mm DIA. x14m LONG THIMBLE BOTH ENDS
2 OFF SLEWING ROPES	6 x36 FIBRE CORE, 200 kg/mm ² , 26 mm DIA. x130m LONG	THIMBLE ONE END OTHER END PLAIN
1 OFF AUX CARGO ROPE	6 x36 " " " " 180 " " " " x81m LONG	" " " " " "
1 OFF " " " "	6 x36 " " " " 200 " " " " x85 m LONG	" " " " " "

NOTE: * - SAFE WORKING LOADS FOR SINGLE SHEAVES INDICATED IN THAT COLUMN.
ARE TAKEN AS ONE HALF WORKING LOADS OF HOOK FITTINGS IN ACCORDANCE
WITH CHAPT. 9, SECT. I OF THE "CODE FOR LIFTING APPLIANCE IN A MARINE ENVIRONMENT"
FROM Lloyd's Register of Shipping. SEE ALSO TABLE 9.11, NOTES 1 & 5

[illegible]