

| SUBSURFACE PROFILE | | | | SAMPLE | | | | | Standard Penetration Test "N" Value per 300 mm | | | |
|-------------------------------|--------|---|---------------|-------------|------------|-----------|--------------|---------|---|--|--|--|
| Depth below Ground Surface | Symbol | Geologic Description | Elevation (m) | Sample Type | Sample No. | "N" Value | Recovery (%) | RQD (%) | | | | |
| | | | | | | | | | | | | |
| 0 ft 0 m | | Ground Surface | 3.35 | | | | | | | | | |
| 1 | | Asphalt. | | | | | | | | | | |
| 2 | | SPT: 28 / 24 / 18 / 22. CFEM: Gravel and Sand, trace Silt/Clay. | 2.64 | SS | 1 | 42 | 17 | | | | | |
| 3 | | Overburden: Gravel. | 1.88 | | | | | | | | | |
| 4 | | | | | | | | | | | | |
| 5 | | SPT: 6 / 4 / 4 / 2. No sample recovery. | 1.26 | SS | 2 | 8 | 0 | | | | | |
| 6 | | | | | | | | | | | | |
| 7 | | Overburden: Gravel and cobbles. | 0.672 | | | | | | | | | |
| 8 | | | | | | | | | | | | |
| 9 | | Bedrock: Blue-grey fine grained sandstone. | 0.367 | | | | | | | | | |
| 10 | | SS3: "N" Value = 52; Recovery = 0%. SPT: 2 for 0.04 m / 52 for 0.0 m, bouncing (Refusal). No sample recovery. | | RC | - | | 99 | 61 | | | | |
| 11 | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | |
| 15 | | Bedrock: Blue-grey fine grained sandstone. | | | | | | | | | | |
| 16 | | | | | | | | | | | | |
| 17 | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | |
| 19 | | End of Borehole | -2.64 | | | | | | | | | |
| 20 | | | | | | | | | | | | |
| 21 | | | | | | | | | | | | |
| 22 | | | | | | | | | | | | |
| 23 | | | | | | | | | | | | |