

PART 1 - GENERAL

- 1.1 DESCRIPTION .1 This section specifies requirements for supply and installation of timber stop logs.
- 1.2 DIMENSIONS .1 Check existing site dimensions and report discrepancies to DR before commencing work.
- 1.3 PROTECTION .1 Avoid dropping, bruising or breaking of wood fibres.
- 1.4 DELIVERY AND STORAGE .1 Store timber horizontally, evenly supported and open piled to permit air circulation when stored for prolonged period.
- 1.5 MEASUREMENT OF PAYMENT .1 Untreated Dimension Timber: As specified including all plant, material, labour and equipment will be measured by the cubic metre (m³) of timber supplied and installed in place including galvanized metal handles in slop logs.
- .2 Payment for timber will be made on the basis of volume calculated from sizes as indicated on drawing.

PART 2 - PRODUCTS

- 2.1 TIMBER MATERIALS .1 Timber: Use timber graded and stamped in accordance with applicable grading rules and standards of associations or agencies approved to grade lumber by Canadian Lumber Standards Administration Board of CSA.
- .2 Species:
.1 Hardwood: D. Fir (Untreated).
- .3 Grade: Select Structural.
- .4 Grading Authority: NLGA

PART 3 - EXECUTION

- 3.1 PREPARATION .1 Install structural timbers to details shown on drawings or specified.
- 3.2 STOP LOGS .1 Supply timbers as per drawings.