

1 GENERAL

1.1 RELATED REQUIREMENTS

- .1 Section 35 31 33.01 - Excavation, Trenching and Backfilling.

1.2 REFERENCES

- .1 ASTM International
 - .1 ASTM D 4791-10, Standard Test Method for Flat Particles, Elongated Particles, or Flat and Elongated Particles in Coarse Aggregate.
- .2 U.S. Environmental Protection Agency (EPA)/Office of Water
 - .1 EPA 832/R-92-005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.3 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Samples:
 - .1 Allow continual sampling by Departmental Representative during production.
 - .3 Provide Departmental Representative with access to source and processed material for sampling.
 - .4 Install sampling facilities at discharge end of production conveyor, to allow Departmental Representative to obtain representative samples of items being produced. Stop conveyor belt when requested by Departmental Representative to permit full cross section sampling.
 - .5 Provide front end loader or other suitable equipment including trained operator for stockpile sampling as necessary. Move samples to storage place as directed by Departmental Representative.
 - .6 Supply new or clean sample bags or containers according appropriate to aggregate materials.
 - .7 Pay cost of sampling and testing of aggregates which fail to meet specified requirements.
- .4 Sustainable Design Submittals:
 - .1 Erosion and Sedimentation Control: submit copy of erosion and sedimentation control plan in accordance with authorities having jurisdiction.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Transportation and Handling: handle and transport aggregates to avoid segregation, contamination and degradation.
- .3 Storage: store washed materials or materials excavated from underwater 24 hours minimum to allow free water to drain and for materials to attain uniform water content.

2 PRODUCTS

2.1 MATERIALS

- .1 Aggregate quality: sound, hard, durable material free from soft, thin, elongated or laminated particles, organic material, clay lumps or minerals, free from adherent coatings and injurious amounts of disintegrated pieces or other deleterious substances.
- .2 Flat and elongated particles of coarse aggregate: to ASTM D 4791.
 - .1 Greatest dimension to exceed 5 times least dimension.
- .3 Fine aggregates satisfying requirements of applicable section to be one, or blend of following:
 - .1 Screenings produced in crushing of quarried rock, boulders, gravel or slag.
 - .2 Reclaimed asphalt pavement.
 - .3 Reclaimed concrete material.
- .4 Coarse aggregates satisfying requirements of applicable section to be one of or blend of following:
 - .1 Crushed rock.
 - .2 Gravel and crushed gravel composed of naturally formed particles of stone.
 - .3 Light weight aggregate, including slag and expanded shale.

2.2 SOURCE QUALITY CONTROL

- .1 Inform Departmental Representative of proposed source of aggregates and provide access for sampling 4 weeks minimum before starting production.
- .2 If materials from proposed source do not meet, or cannot reasonably be processed to meet, specified requirements, locate alternative source.
- .3 Advise Departmental Representative 4 weeks minimum in advance of proposed change of material source.
- .4 Acceptance of material at source does not preclude future rejection if it fails to conform to requirements specified, lacks uniformity, or if its field performance is found to be unsatisfactory.

3 EXECUTION

3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions are acceptable for topsoil stripping.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.

3.2 PREPARATION

- .1 Aggregate source preparation:
 - .1 Prior to excavating materials for aggregate production, clear and grub area

- to be worked, and strip unsuitable surface materials. Dispose of cleared, grubbed and unsuitable materials as approved by authority having jurisdiction.
- .2 Where clearing is required, leave screen of trees between cleared area and roadways as directed.
 - .3 Clear, grub and strip area ahead of quarrying or excavating operation sufficient to prevent contamination of aggregate by deleterious materials.
 - .4 When excavation is completed dress sides of excavation to nominal 1.5:1 slope, and provide drains or ditches as required to prevent surface standing water.
 - .5 Trim off and dress slopes of waste material piles and leave site in neat condition.
 - .6 Provide silt fence or other means to prevent contamination of existing watercourse or natural wetland features.
- .3 Processing:
- .1 Process aggregate uniformly using methods that prevent contamination, segregation and degradation.
 - .2 Blend aggregates, as required, including reclaimed materials that meet physical requirements of specification is permitted in order to satisfy gradation requirements for material and, percentage of crushed particles, or particle shapes specified.
 - .1 Use methods and equipment approved in writing by Departmental Representative.
- .4 When operating in stratified deposits use excavation equipment and methods that produce uniform, homogeneous aggregate gradation.
- .5 Where necessary, screen, crush, wash, classify and process aggregates with suitable equipment to meet requirements.
- .1 Use only equipment approved in writing by Departmental Representative.
- .6 Stockpiling:
- .1 Stockpile aggregates on site in locations as indicated unless directed otherwise by Departmental Representative. Do not stockpile on completed pavement surfaces.
 - .2 Stockpile aggregates in sufficient quantities to meet project schedules.
 - .3 Stockpiling sites to be level, well drained, and of adequate bearing capacity and stability to support stockpiled materials and handling equipment.
 - .4 Except where stockpiled on acceptably stabilized areas, provide compacted sand base not less than 300 mm in depth to prevent contamination of aggregate. Stockpile aggregates on ground but do not incorporate bottom 300 mm of pile into Work.
 - .5 Separate different aggregates by strong, full depth bulkheads, or stockpile far enough apart to prevent intermixing.
 - .6 Do not use intermixed or contaminated materials. Remove and dispose of rejected materials as directed by Departmental Representative within 48 hours of rejection.
 - .7 Stockpile materials in uniform layers of thickness as follows:
 - .1 Maximum 1.5 m for coarse aggregate and base course materials.
 - .2 Maximum 1.5 m for fine aggregate and sub-base materials.
 - .3 Maximum 1.5 m for other materials.
 - .8 Uniformly spot-dump aggregates delivered to stockpile in trucks and build up stockpile as specified.
 - .9 Do not cone piles or spill material over edges of piles.
 - .10 Do not use conveying stackers.

- .11 During winter operations, prevent ice and snow from becoming mixed into stockpile or in material being removed from stockpile.

3.3 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.
- .3 Leave aggregate stockpile site in tidy, well drained condition, free of standing surface water.
- .4 Waste Management: separate waste materials in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
 - .1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.
- .5 For temporary or permanent abandonment of aggregate source, restore source to condition meeting requirements of authority having jurisdiction.
- .6 Restrict public access to temporary or permanently abandoned stockpiles by means acceptable to Departmental Representative.

END OF SECTION

1 GENERAL

1.01 RELATED REQUIREMENTS

- .1 Section 31 23 33.01 - Excavation, Trenching and Backfilling.
- .2 Section 01 33 00 - Submittal Procedures

1.02 REFERENCES

- .1 ASTM International
 - .1 ASTM A 123/A 123M-09, Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products.
 - .2 ASTM D 4491-99a(2009), Standard Test Methods for Water Permeability of Geotextiles by Permittivity.
 - .3 ASTM D 4595-09, Standard Test Method for Tensile Properties of Geotextiles by the Wide-Width Strip Method.
 - .4 ASTM D 4716-08, Standard Test Method for Determining the (In-Plane) Flow Rate Per Unit Width and Hydraulic Transmissivity of a Geosynthetic Using a Constant Head.
 - .5 ASTM D 4751-04, Standard Test Method for Determining Apparent Opening Size of a Geotextile.
- .2 Canada Green Building Council (CaGBC)
 - .1 LEED Canada-NC Version 1.0-2004, LEED (Leadership in Energy and Environmental Design): Green Building Rating System Reference Package For New Construction and Major Renovations (including Addendum 2007).
 - .2 LEED Canada-CI Version 1.0-2007, LEED (Leadership in Energy and Environmental Design): Green Building Rating System Reference Guide For Commercial Interiors.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-4.2 No. 11.2-2004, Textile Test Methods - Bursting Strength - Ball Burst Test (Extension of September 1989).
 - .2 CAN/CGSB-148.1, Methods of Testing Geotextiles and Complete Geomembranes.
 - .1 No.2-M85, Methods of Testing Geosynthetics - Mass per Unit Area.
 - .2 No.3-M85, Methods of Testing Geosynthetics - Thickness of Geotextiles.
 - .3 No.6.1-93, Methods of Testing Geotextiles and Geomembranes - Bursting Strength of Geotextiles Under No Compressive Load.
 - .4 No.7.3-92, Methods of Testing Geotextiles and Geomembranes - Grab Tensile Test for Geotextiles.
 - .5 No. 10-94, Methods of Testing Geosynthetics - Geotextiles - Filtration Opening Size.
- .4 CSA International
 - .1 CSA G40.20/G40.21-04(R2009), General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel.
- .5 Ontario Provincial Standard Specifications (OPSS)
 - .1 OPSS 1860-November 2010, Material Specification for Geotextiles.

1.02 MEASUREMENT FOR PAYMENT

- .1 Measure supply and installation of geotextiles in square meters of surface covered by material. No allowance will be made for secure pins and overlaps.

1.03 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for geotextiles and include product characteristics, performance criteria, physical size, finish and limitations.

1.04 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Storage and Handling Requirements:
 - .1 Store materials off ground in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect geotextiles from direct sunlight and UV rays.
 - .3 Replace defective or damaged materials with new.
- .3 Packaging Waste Management: as specified in Construction Waste Management Plan.

2 PRODUCTS

2.01 MATERIAL

- .1 Geotextile: woven synthetic fibre fabric, supplied in rolls.
 - .1 Width: 2 m minimum.
 - .2 Seam: Minimum of 1m seam with at least 300mm of geotextile on both sides of seam.
 - .3 Composed of: minimum 85% by mass of polypropylene, polyester with inhibitors added to base plastic to resist deterioration by ultra-violet and heat exposure for 60 days.
- .2 Physical properties:
 - .1 Thickness: to CAN/CGSB-148.1, No.3.
 - .2 Mass per unit area: to CAN/CGSB-148.1, No.2.
 - .3 Tensile strength and elongation in any principal direction: to ASTM D 4595.
 - .1 Tensile strength: minimum 400 N, wet condition.
 - .2 Elongation at break: maximum 25%.
 - .3 Seam strength: equal to or greater than tensile strength of fabric.
 - .4 Grab tensile strength and elongation: to [CAN/CGSB-148.1, No.7.3].
 - .1 Breaking force: minimum 200 N, wet condition.
 - .2 Elongation at future: maximum 50%.
- .3 Hydraulic properties:
 - .1 Apparent opening size (AOS): to ASTM D 4751.
 - .2 Filtration opening size (FOS): to CAN/CGSB-148.1 No.10.
 - .3 Transmissivity: to ASTM D 4716.

- .4 Permittivity: to ASTM D 4491 pers.
- .4 Securing pins and washers: to CSA G40.21, Grade 300W, hot-dipped galvanized with minimum zinc coating of 600 g/m² to ASTM A 123/A 123M.
- .5 Factory seams: sewn in accordance with manufacturer's recommendations.
- .6 Thread for sewn seams: equal or better resistance to chemical and biological degradation than geotextile.

3 EXECUTION

3.01 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for geotextile material installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied.

3.02 INSTALLATION

- .1 Place geotextile material by unrolling onto graded surface in orientation, manner and locations indicated and retain in position with secure pins or an approved alternative.
- .2 Place geotextile material smooth and free of tension stress, folds, wrinkles and creases.
- .3 Place geotextile material on sloping surfaces in one continuous length from toe of slope to upper extent of geotextile.
- .4 Overlap each successive strip of geotextile 600 mm over previously laid strip.
- .6 Pin successive strips of geotextile with securing pins.
- .7 Protect installed geotextile material from displacement, damage or deterioration before, during and after placement of material layers.
- .8 After installation, cover with overlying layer within 4 hours of placement.
- .9 Replace damaged or deteriorated geotextile to approval of Departmental Representative.
- .10 Place and compact soil layers in accordance with Section 31 23 33.01 - Excavating, Trenching and Backfilling.

3.03 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
 - .1 Leave Work area clean at end of each day.

- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.

3.04 PROTECTION

- .1 Vehicular traffic not permitted directly on geotextile.

END OF SECTION

1 GENERAL

1.01 RELATED REQUIREMENTS

- .1 Section 31 23 33.01 - Excavation, Trenching and Backfilling.
- .2 Section 01 33 00 - Submittal Procedures

1.01 DESCRIPTION

- .1 The section consists of the supply, installation, maintenance and removal of sediment control fence.

1.02 MEASUREMENT FOR PAYMENT

- .1 Measure Supply, Installation of Sediment Control fence in linear meters installed, as specified under this section.
 - .1 Maintenance of Sediment Control Fence will be incidental to this section.

1.03 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Product Data:
 - .1 Submit manufacturer's instructions, printed product literature and data sheets for geotextiles and include product characteristics, performance criteria, physical size, finish and limitations.

1.04 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements and with manufacturer's written instructions.
- .2 Storage and Handling Requirements:
 - .1 Store materials off ground in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
 - .2 Store and protect geotextiles from direct sunlight and UV rays.
 - .3 Replace defective or damaged materials with new.
- .3 Packaging Waste Management: as specified in Construction Waste Management Plan.

2 PRODUCTS

2.01 MATERIAL

- .1 All materials shall be supplied by the Contractor.
- .2 The fence may be prefabricated or constructed on site from the specified components.
- .3 The fabric shall conform to the requirements of 601.2, Type W1, geotextile.

- .4 Wooden, Metal or Synthetic Post or Stake, minimum 1200mm long.

3 EXECUTION

3.01 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for geotextile material installation in accordance with manufacturer's written instructions.
 - .1 Visually inspect substrate in presence of Departmental Representative.
 - .2 Inform Departmental Representative of unacceptable conditions immediately upon discovery.
 - .3 Proceed with installation only after unacceptable conditions have been remedied.

3.02 INSTALLATION

- .1 The Contractor shall carry out the Work as indicated in the Contract Documents and/or as specifically directed by the Departmental Representative.
- .2 The sediment control fence shall be installed as per manufacturer's instructions or as specified by the Departmental Representative.
 - .1 In areas of potential sheet flow runoff, where construction activity cause the drainage run-off to transport sediment(s), the Contractor shall ensure that sediment control fences are properly located for effective runoff control.
 - .2 The Contractor will install sediment control fences, after consultation and agreement with the Departmental Representative.
- .3 The Contractor shall maintain the sediment control fence in a functional condition continuously from the time of installation until the completion of the Contract or removal.
- .4 The Contractor shall inspect all sediment control fences after each rainfall and at least daily during periods of prolonged rainfall.
- .5 The Contractor shall immediately repair any damage to sediment control fences or parts thereof.
- .6 The Contractor shall remove retained sediment prior to it having accumulated to a level approximately but not exceeding on-half the height of the fence, and this sediment shall be disposed of at a location at least 30m away from any watercourse, and in such a manner that the sediment will not be returned to the Work Area or the watercourse; or
 - .1 Subject to the Departmental Representative, the Contractor may install a second, back-up sediment control fence.
- .7 The Contractor shall remove all sediment control fence and the time of such removal shall be subject to the Departmental Representative's approval, but in cases shall occur prior to the completion of the Contract.
 - .1 Sediment Control Fence removed shall become the property of the Contractor and shall be disposed of outside of Work site, at a Registered Disposal Site.

- .2 If the Departmental Representative notifies the Contractor in writing, prior to the completion of the Contract, that all or any part of the sediment control fence is to remain in place, the Contractor shall be deemed to have completed his obligations for that portion of the sediment control fence, under this item and the sediment control fence shall become the property of the Owner.
- .8 At the time of removal, the Contractor shall excavate any remaining sediment and dispose of it at a location at least 30m from any watercourse, and in such a manner that the sediment will not be returned to the Work Area or the watercourse and shall dress and seed the area of the removed fence and sedimentation, to the satisfaction of the Departmental Representative.

3.03 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 - Cleaning.
.1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment in accordance with Section 01 74 11 - Cleaning.

END OF SECTION

Approved: 2006-09-30

Part 1 General

1.1 RELATED REQUIREMENTS

- .1 Section 32 91 19.13 Topsoil Placement, Grading, and Capping
- .2 Section 01 33 00 - Submittal Procedures.
- .3 Section 01 35 29.06 - Health and Safety Requirements.
- .4 Section 31 05 16 - Aggregate Materials
- .5 Section 31 32 19.01 - Geotextile soil stabilization
- .6 Section 02 41 16 - Selective Site Demolitions

1.2 REFERENCE STANDARDS

- .1 U.S. Environmental Protection Agency (EPA)/Office of Water
 - .1 EPA 832R92005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.3 DEFINITIONS

- .1 Unclassified excavation: excavation of deposits of whatever character encountered in Work.
- .2 Topsoil:
 - .1 Material capable of supporting good vegetative growth and suitable for use in top dressing, landscaping and seeding.
 - .2 Material reasonably free from subsoil, clay lumps, brush, objectionable weeds, and other litter, and free from cobbles, stumps, roots, and other objectionable material larger than 25 millimeters in any dimension.
- .3 Waste material: excavated material unsuitable for use in Work or surplus to requirements.
- .4 Borrow material: material obtained from locations outside area to be graded, and required for construction of fill areas or for other portions of Work.
- .5 Recycled fill material: material, considered inert, obtained from alternate sources and engineered to meet requirements of fill areas.
- .6 Unsuitable materials:
 - .1 Weak, chemically unstable, and compressible materials.
 - .2 Frost susceptible materials:
 - .1 Fine grained soils with plasticity index less than 10 when tested to ASTM D4318, and gradation within limits specified

when tested to ASTM D422 OR ASTM C136: Sieve sizes to CAN/CGSB-8.1.

.2 Table:

Sieve Designation	% Passing
2.00 mm	100
0.10 mm	45 - 100
0.02 mm	10 - 80
0.005 mm	0 - 45

.3 Coarse grained soils containing more than 20 % by mass passing 0.075 mm sieve.

.7 Unshrinkable fill: very weak mixture of cement, concrete aggregates and water that resists settlement when placed in utility trenches, and capable of being readily excavated.

1.4 ACTION AND INFORMATIONAL SUBMITTALS

.1 Make submittals in accordance with Section 01 33 00 - Submittal Procedures.

.2 Preconstruction Submittals:

.1 Submit construction equipment list for major equipment to be used in this section prior to start of Work.

.2 Submit records of underground utility locates, indicating: location plan of existing utilities as found in field, and location plan of relocated and abandoned services, as required.

.3 Samples:

.1 Submit samples in accordance with Section 01 33 00 - Submittal Procedures.

.2 Inform Departmental Representative at least 4 weeks prior to beginning Work, of proposed source of fill and/or topsoil materials and provide access for sampling.

1.5 QUALITY ASSURANCE

.1 Qualification Statement: submit proof of insurance coverage for professional liability.

.2 Submit design and supporting data at least 2 weeks prior to beginning Work.

.3 Design and supporting data submitted to bear stamp and signature of qualified professional engineer registered or licensed in Territory or Province where Work is to be conducted, Canada.

.4 Keep design and supporting data on site.

.5 Engage services of qualified professional Engineer who is registered or licensed in the Province or Territory, which Work is to be carried out to design and inspect cofferdams, shoring, bracing and underpinning required for Work.

- .8 Where utility lines or structures exist in area of excavation, obtain direction of Departmental Representative before removing or re-routing.
- .9 Record location of maintained, re-routed and abandoned underground lines.
- .10 Confirm locations of recent excavations adjacent to area of excavation.
- .3 Existing buildings and surface features:
 - .1 Conduct, with Departmental Representative, condition survey of existing buildings, trees and other plants, lawns, fencing, service poles, wires, rail tracks, pavement, survey bench marks and monuments which may be affected by Work.
 - .2 Protect existing buildings and surface features from damage while Work is in progress. In event of damage, immediately make repair as directed by Departmental Representative.
 - .3 Where required for excavation, cut roots or branches as directed by Departmental Representative.

Part 2 Products

2.1 MATERIALS

- .1 Type 1 and Type 2 fill: properties to Section 31 05 16 - Aggregate Materials and the following requirements:
 - .1 Crushed, pit run or screened stone, gravel or sand.
 - .2 Gradations to be within limits specified when tested to ASTM C136, ASTM C117. Sieve sizes to CAN/CGSB-8.2.
 - .3 Table:

Sieve Designation	% Passing	
Type 1	Type 2	
75 mm	-	100
50 mm	-	-
37.5 mm	-	-
25 mm	100	-
19 mm	75-100	-
12.5 mm	-	-
9.5 mm	50-100	-
4.75 mm	30-70	22-85
2.00 mm	20-45	-
0.425 mm	10-25	5-30
0.180 mm	-	-
0.075 mm	3-8	0-10

- .2 Type 3 fill: selected material from excavation or other sources, approved by Departmental Representative for use intended, unfrozen and free from rocks larger than 75 mm, cinders, ashes, sods, refuse or other deleterious materials.

- .3 Unshrinkable fill: proportioned and mixed to provide:
 - .1 Maximum compressive strength of 0.4 MPa at 28 days.
 - .2 Maximum cement content of 25 kg/m³: to CSA-A3001, Type GU.
 - .3 Minimum strength of 0.07MPa at 24 h.
 - .4 Concrete aggregates: to CSA-A23.1/A23.2.
 - .5 Cement: Type GU.
 - .6 Slump: 160 to 200 mm.
- .4 Shearmat: honeycomb type bio-degradable cardboard 100 mm thick, treated to provide sufficient structural support for poured concrete until concrete cured.
- .5 Geotextile soil stabilization: to Section 31 32 19.01 - Geotextile soil stabilization.

Part 3 Execution

3.1 TEMPORARY EROSION AND SEDIMENTATION CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.2 SITE PREPARATION

- .1 Remove obstructions, ice and snow, from surfaces to be excavated within limits indicated in SOW.
- .2 Cut pavement or sidewalk neatly along limits of proposed excavation in order that surface may break evenly and cleanly in accordance with Section 02 41 13 - Selective Site Demolition.
- .3 Remove other obstructions identified in the SOW (*i.e.*, fencing, outside stairs, *etc.*) prior to excavation. These obstructions are to be returned to their original place and condition once work is completed. Note: if identified, outside stairs (with railing as required by code) to be replaced following remediation to fit new grades.
- .4 Minimum area to be excavated with backfill consisting of 0.3 m of compacted topsoil, and/or as indicated in the SOW.
- .5 Remove trees, bushes from surfaces to be excavated within limits as indicated by Departmental Representative.

3.3 PREPARATION/PROTECTION

- .1 Protect existing features in accordance with applicable local regulations.
- .2 Keep excavations clean, free of standing water, and loose soil.
- .3 Where soil is subject to significant volume change due to change in moisture content, cover and protect to Departmental Representative satisfaction.
- .4 Protect natural and man-made features required to remain undisturbed. Unless otherwise indicated or located in an area to be occupied by new construction, protect existing trees from damage.
- .5 Protect buried services that are required to remain undisturbed.

3.4 STRIPPING OF TOPSOIL

- .1 Remove sod/weeds and topsoil to depth indicated in SOW as directed by the Departmental Representative.
- .2 Place sod/weeds and topsoil directly in truck for offsite disposal at a provincially approved disposal facility.
- .3 Do not place excavated sod/weeds or topsoil on ground surface.

3.5 STOCKPILING

- .1 Stockpile fill materials in areas designated by Departmental Representative.
 - .1 Stockpile granular materials in manner to prevent segregation.
- .2 Protect fill materials from contamination.
- .3 Implement sufficient erosion and sediment control measures to prevent sediment release off construction boundaries and into water bodies.

3.6 COFFERDAMS, SHORING, BRACING AND UNDERPINNING

- .1 Maintain sides and slopes of excavations in safe condition by appropriate methods and in accordance with Section 01 35 29.06 - Health and Safety Requirements.
- .2 Obtain permit from authority having jurisdiction for temporary diversion of water course.
- .3 Construct temporary Works to depths, heights and locations as approved by DCC Representative.
- .4 During backfill operation:
 - .1 Unless otherwise indicated or directed by Departmental Representative, remove sheeting and shoring from excavations.
 - .2 Do not remove bracing until backfilling has reached respective levels of such bracing.

- .1 If excavating through roots, excavate by hand and cut roots with sharp axe or saw.
- .6 For trench excavation, unless otherwise authorized by Departmental Representative in writing, do not excavate more than 30 m of trench in advance of installation operations and do not leave open more than 15 m at end of day's operation.
- .7 Keep excavated and stockpiled materials safe distance away from edge of trench as directed by Departmental Representative.
- .8 Restrict vehicle operations directly adjacent to open trenches.
- .9 Dispose of surplus and unsuitable excavated material off site at an approved facility.
- .10 Do not obstruct flow of surface drainage or natural watercourses.
- .11 Earth bottoms of excavations to be undisturbed soil, level, free from loose, soft or organic matter.
- .12 Notify Departmental Representative when bottom of excavation is reached.
- .13 Obtain Departmental Representative approval of completed excavation.
- .14 Remove unsuitable material from trench bottom including those that extend below required elevations to extent and depth as directed by Departmental Representative.
- .15 Correct unauthorized over-excavation as follows:
 - .1 Fill with clean and approved backfill material.
- .16 Hand trim, make firm and remove loose material and debris from excavations.
 - .1 Where material at bottom of excavation is disturbed, compact foundation soil to density at least equal to undisturbed soil.

3.9 FILL TYPES AND COMPACTION

- .1 Use types of fill as indicated or specified below. Compaction densities are percentages of maximum densities obtained from ASTM D698, ASTM D1557, in accordance with Section 31 05 10 - Corrected Maximum Dry Density for Fill.
 - .1 Exterior side of perimeter walls: use Type 3 fill to subgrade level. Compact to 95% of corrected maximum dry density.
 - .2 Within building area: use Type 2 to underside of base course for floor slabs. Compact to 100 % of corrected maximum dry density.
 - .3 Under concrete slabs: provide 150 mm compacted thickness base course of Type 1 fill topped with shearmat filler as indicated to underside of slab. Compact base course to 100 %.
 - .4 Retaining walls: use Type 2 fill to subgrade level on high side for minimum 500 mm from wall and compact to 95 %. For remaining portion, use Type 3 fill compacted to 95 %.

- .7 Consolidate and level unshrinkable fill with internal vibrators.
- .8 Install drainage or filter system in backfill as indicated by Departmental Representative.
- .9 Backfill with topsoil as described in Section 32 91 19 13 Topsoil Placement, Grading and Capping.

3.12 RESTORATION

- .1 Upon completion of Work, remove waste materials and debris, trim slopes, and correct defects as directed by Departmental Representative.
- .2 Replace topsoil as directed by Departmental Representative.
- .3 Reinstate lawns to elevation which existed before excavation.
- .4 Reinstate pavements and sidewalks disturbed by excavation to thickness, structure and elevation which existed before excavation.
- .5 Clean and reinstate areas affected by Work as directed by Departmental Representative.
- .6 Use temporary plating to support traffic loads over unshrinkable fill for initial 24 hours.
- .7 Protect newly graded areas from traffic and erosion and maintain free of trash or debris.

END OF SECTION