

DOMESTIC WATER HEATER 1/M2
SCALE : N.T.S.

DOMESTIC WATER HEATER SCHEDULE

UNIT NO.	MFGR	MODEL	WATER CAPACITY (L)	WATER SUPPLY		ELECTRICAL		REMARKS
				INLET (mm)	OUTLET (mm)	V/ø	POWER (kW)	
DWH–1	RHEEM	EGSP15	55	20	20	208/1	3.0	C/W DRAIN PAN PIPED TO NEAREST SANITARY
DWH–2	RHEEM	EGSP15	55	20	20	208/1	3.0	C/W DRAIN PAN PIPED TO NEAREST SANITARY

PLUMBING FIXTURE SCHEDULE

TAG	DESCRIPTION	MATERIAL	ACCESSORIES	DCW	DHW	SAN
SK–1	SELF RIMMING SINGLE BASIN KITCHEN SINK KINDRED MODEL QSL2020/8/1	20 GAUGE STAINLESS STEEL	FAUCET: SINGLE HANDLE FAUCET, CHROME PLATED, CENTER HOLE ONLY, LEAD FREE BRASS CONSTRUCTION, VOLUME CONTROL AND HOT WATER LIMIT STOP CARTRIDGE, VANDAL RESISTANT 1.9 LPM (0.5 GPM) PRESSURE COMPENSATING NON–AERATING SPRAY OUTLET, 241 MM (9–1/2") PROJECTION RIGID CAST BRASS SPOUT. CHICAGO FAUCET MODEL 430–E2805–ABCP MIXING VALVE: POINT OF USE THERMOSTATIC WATER MIXING VALVE, BRONZE BODY, TEMPERATURE ADJUSTMENT, BUILT–IN CHECKS, HOUSED IN 127 MM X 86 MM X 81 MM (5" X 3–3/8" X 3–3/16") ENCLOSURE. SET VALVE TEMPERATURE AT 46 °C (115 °F). AMERICAN STANDARD MODEL 605XTMV1070	15	15	40
SK–2	SELF RIMMING DOUBLE BASIN KITCHEN SINK KINDRED MODEL QDL3120/8/1	20 GAUGE STAINLESS STEEL	FAUCET: SINGLE HANDLE FAUCET, CHROME PLATED, CENTER HOLE ONLY, LEAD FREE BRASS CONSTRUCTION, VOLUME CONTROL AND HOT WATER LIMIT STOP CARTRIDGE, VANDAL RESISTANT 1.9 LPM (0.5 GPM) PRESSURE COMPENSATING NON–AERATING SPRAY OUTLET, 241 MM (9–1/2") PROJECTION RIGID CAST BRASS SPOUT. CHICAGO FAUCET MODEL 430–E2805–ABCP MIXING VALVE: POINT OF USE THERMOSTATIC WATER MIXING VALVE, BRONZE BODY, TEMPERATURE ADJUSTMENT, BUILT–IN CHECKS, HOUSED IN 127 MM X 86 MM X 81 MM (5" X 3–3/8" X 3–3/16") ENCLOSURE. SET VALVE TEMPERATURE AT 46 °C (115 °F). AMERICAN STANDARD MODEL 605XTMV1070	15	15	40
DF–1	WALL HUNG BI–LEVEL DRINKING FOUNTAIN C/W BOTTLE FILL ELKAY MODEL LZSTL8WSLK	–	FOUNTAIN: GRANITE VINYL CLAD STEEL COOLER, GALVANIZED STEEL STRUCTURAL CHASSIS, EASY–TOUCH FRONT AND SIDE PUSHBAR CONTROLS. BOTTLE FILL: TOUCHLESS SENSOR ACTIVATION WITH AUTO 20 SECOND SHUT OFF, 1.5 GPM QUICK FILL, DIGITAL DISPLAY BOTTLE COUNTER, LED VISUAL FILTER REPLACEMENT NOTICE. CARRIER: HEAVY–DUTY ONE PIECE STEEL HANGER.	15	15	30

Public Works and Government Services Canada
Travaux Publics et Services gouvernementaux Canada

FOWLER BAULD & MITCHELL
architecture
Fowler Bauld & Mitchell Ltd.
PO Box 814, Suite 102
1600 Hollis Street
Halifax, Nova Scotia B3J 2R7
Tel: 902 422 4100
Fax: 902 423 3043
architects@fbm.ns.ca
www.fbm.ns.ca

CBCL LIMITED
Consulting Engineers
ISO 9001 CERTIFIED

REGISTERED PROFESSIONAL ENGINEER
Province of New Brunswick
M7870
Pierre Arsenault
Member
September 13th, 2016
Date
Membre de l'Association des ingénieurs professionnels du Nouveau-Brunswick

revisions		date
1	ISSUED FOR TENDER	SEP 13 2016

project / projet
CORRECTIONAL SERVICES CANADA 2ND FLOOR FIT–UP

drawing / dessin
PLUMBING DETAILS & SCHEDULES

designed PA / conçu
date
drawn PA / dessiné
date
approved / approuvé
date
Tender / Soumission
PWGSC Project Manager / Administrateur de projets TPSGC
project number / no. du projet
R.083937.002
drawing no. / no. du dessin
M3

E–DRM/GDD–E: 544592

PWGSC AO (2004)