



**GROS MORNE NATIONAL PARK
PORT AU CHOIX VISITOR CENTRE UPGRADES
PN: 1135**

**TECHNICAL SPECIFICATIONS
“Issued for Tender”**

Prepared for: **Gros Morne National Park**
Western Newfoundland & Labrador
P.O. Box 130
Rocky Harbour, NL
A0K 4N0

Prepared by: **Anderson Engineering Consultants Ltd.**
Suite 103, 3 Union Street
Corner Brook, NL
A2H 5M7

Date: September 20, 2016



DIVISION 1 - GENERAL REQUIREMENTS

Section 01 11 00 - Summary of Work	1
Section 01 21 00 - Allowances	1
Section 01 29 83 – Payment Procedures: Testing Laboratory Services	2
Section 01 31 00 – Project Management and Coordination	4
Section 01 32 00 - Construction Progress Documentation	2
Section 01 33 00 - Submittal Procedures.....	4
Section 01 35 29.06 - Health & Safety Requirements.....	13
Section 01 35 43 - Environmental Procedures.....	2
Section 01 41 00 - Regulatory Requirements	1
Section 01 45 00 - Quality Control.....	3
Section 01 51 00 - Temporary Utilities	4
Section 01 52 00 - Construction Facilities	3
Section 01 56 00 - Temporary Barriers & Enclosures.....	3
Section 01 61 00 - Common Product Requirements.....	6
Section 01 73 00 - Execution.....	3
Section 01 74 11 - Cleaning	2
Section 01 74 21 - Construction/Demolition Waste Management Disposal	4
Section 01 77 00 - Closeout Procedures.....	2
Section 01 78 00 - Closeout Submittals.....	4

DIVISION 2 – EXISTING CONDITIONS

Section 02 41 13 - Selective Site Demolition.....	4
Section 02 41 16 - Structure Demolition	6

DIVISION 3 – CONCRETE

Section 03 10 00 - Concrete Forming & Accessories.....	4
Section 03 20 00 - Concrete Reinforcing.....	4
Section 03 30 00 - Cast-in-Place Concrete	10
Section 03 35 00 - Concrete Finishing.....	3

DIVISION 6 – WOOD/PLASTIC COMPOSITES

Section 06 05 73 – Wood Treatment	3
Section 06 10 00 – Rough Carpentry.....	4
Section 06 20 00 – Finish Carpentry	4
Section 06 40 00 – Architectural Woodwork	4

DIVISION 7 – THERMAL/MOISTURE

Section 07 21 13 – Board Insulation.....	3
Section 07 21 16 – Blanket Insulation	2
Section 07 26 00 – Vapour Retarders	2
Section 07 27 00.01 – Air Barriers – Descriptive or Proprietary.....	5
Section 07 31 13.13 – Fiberglass-Reinforced Asphalt Shingles.....	4
Section 07 46 23 – Wood Siding – Prefinished	4
Section 07 62 00 – Sheet Metal Flashing and Trim.....	3

DIVISION 8 – OPENINGS

Section 08 11 00 – Metal Doors and Frames.....	5
Section 08 53 13 – Vinyl Windows.....	4
Section 08 71 00 – Door Hardware	6
Section 08 80 50 – Glazing.....	5

DIVISION 9 – FINISHES

Section 09 21 16 – Gypsum Board Assemblies.....	5
Section 09 91 13 – Exterior Painting.....	12
Section 09 91 23 – Interior Painting.....	13

DIVISION 31 – EARTHWORK

Section 31 00 00.01 - Earthwork and Related Work	5
Section 31 05 10 - Corrected Maximum Dry Density for Fill.....	2
Section 31 05 16 - Aggregate Materials	5
Section 31 22 13 - Rough Grading	3
Section 31 23 33.01 - Excavating, Trenching and Backfilling.....	9

DIVISION 32 – EXTERIOR IMPROVEMENTS

Section 32 11 16.01 – Granular Sub-Base.....	3
Section 32 11 23 – Aggregate Base Courses	3

List of Drawings

Cover

SP1.0 Existing Site Plan - Deconstruction
D1.0 Existing Floor Plan - Deconstruction
D1.1 Existing Elevations - Deconstruction
D1.2 Existing Building Sections - Deconstruction
D1.3 Existing Wall Sections and Details - Deconstruction
D1.4 Existing Wall Section - Deconstruction
F1.0 Foundation Plan, Concrete Pad Plan and Details – New Work
A1.0 Floor Plan – New Work
A1.1 Elevations – New Work
A1.2 Wall Sections – New Work
A1.3 Wall Sections – New Work
A1.4 Wall Sections – New work
A1.5 Wall Sections – New Work
A1.6 Wall Section – New Work
A1.7 Wall Sections and Details – New Work
A1.8 Door and Window Schedules, Finish Schedule
A1.9 General Notes, Specifications
ME1.0 Mechanical/Electrical Floor Plan – New Work

PART 1 **GENERAL**

1.1 **WORK COVERED BY CONTRACT DOCUMENTS**

- .1 The total rehabilitation of the Port au Choix Visitor Centre building envelope systems including, but not necessarily limited to: demolition and replacement of existing wood siding, air barrier, eaves soffits, doors, windows, shingles, exterior lighting, concrete pads and walkways, and miscellaneous finishes.

Also included is the construction of a new concrete exterior deck.

1.2 **CONTRACTOR USE OF PREMISES**

- .1 Contractor will have restricted use of site (see Limits of Contract).
- .2 Coordinate use of premises under direction of Owner's Representative.
- .3 Obtain and pay for use of additional storage or work areas needed for operations under this Contract.
- .4 Remove or alter existing work to prevent injury or damage to portions of existing work which remain.
- .5 Repair or replace portions of existing work which have been altered during construction operations to match existing or adjoining work, as directed by Owner's Representative.

1.3 **ON-SITE DOCUMENTS**

- .1 Maintain at job site documents as indicated in Section 01 31 00 – Project Management and Coordination.

1.4 **CONTRACT DOCUMENTS**

- .1 Legends and schedules in the Issued for Tender Drawings take precedence over the Technical Specifications with respect to products and materials identified.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 GENERAL

1.1 CASH ALLOWANCES

- .1 Include in Contract Price, cash allowances as stated herein:
 - .1 \$20,000.00 for damaged material removal and replacement.
 - .2 \$2,000.00 for testing.
- .2 Expend each allowance as directed by Owner's Representative. The cash allowance may be re-directed to cover other required items. Change orders, if required, will not be issued until cash allowance funds are depleted.
- .3 Cash allowances, unless otherwise specified, cover net cost to Contractor of services, products, construction machinery and equipment, freight, handling, unloading, storage installation and other authorized expenses incurred in performing Work.
- .4 Each cash allowance will be adjusted to actual cost as defined hereunder and contract price will be amended accordingly by written order.
- .5 Contract Price will be adjusted by written order to provide for an excess or deficit to each cash allowance.
- .6 Progress payments for work and material authorized under cash allowances will be made in accordance with contract terms of payment.
- .7 The Contract Price and not cash allowance, includes contractor's overhead and profit in connection with such cash allowance.
- .8 Progress payments on accounts of work authorized under cash allowances shall be included in monthly certificate for payment.
- .9 Schedule shall be prepared jointly by Owner's Representative and Contractor to show when items called for under cash allowances must be authorized by Owner's Representative for ordering purposes so that progress of work will not be delayed.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Inspecting and testing by inspecting firms or testing laboratories designated by Owner's Representative

1.2 **RELATED REQUIREMENTS SPECIFIED ELSEWHERE**

- .1 Particular requirements for inspection and testing to be carried out by testing laboratory designated by Owner's Representative are specified under various sections.

1.3 **APPOINTMENT AND PAYMENT**

- .1 Owner's Representative will appoint a testing laboratory to carry out testing as required by this contract. Unless otherwise specified, the Owner shall be responsible to pay for all testing. The general contractor shall provide for review all testing documents to the owner's representative for approval prior to submission of monthly progress claims.
 - .1 Inspection and testing required by laws, ordinances, rules, regulations or orders of public authorities.
 - .2 Inspection and testing performed exclusively for Contractor's convenience.
 - .3 Testing, adjustment and balancing of conveying systems, mechanical and electrical equipment and systems.
 - .4 Mill tests and certificates of compliance.
 - .5 Tests specified to be carried out by Contractor under the supervision of Owner's Representative.
 - .6 Additional tests specified in the following paragraph.
- .2 Where tests or inspections by designated testing laboratory reveal Work not in accordance with contract requirements, pay costs for additional tests or inspections as required by Owner's Representative to verify acceptability of corrected work.

1.4 **CONTRACTOR'S RESPONSIBILITIES**

- .1 Provide labour, equipment and facilities to:
 - .1 Provide access to Work to be inspected and tested.
 - .2 Facilitate inspections and tests.
 - .3 Make good Work disturbed by inspection and test.
 - .4 Provide storage on site for laboratory's exclusive use to store equipment and cure test samples.
- .2 Notify Owner's Representative sufficiently in advance of operations to allow for assignment of laboratory personnel and scheduling of test.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135
Section 01 29 83 – Payment Procedures:

September 2016

Testing Laboratory Services

Page 2 of 2

- .3 Where materials are specified to be tested, deliver representative samples in required quantity to testing laboratory.
- .4 Pay costs for uncovering and making good Work that is covered before required inspection or testing is completed and approved by Owner's Representative.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Coordination work with other contractors and subcontractors under administration of Owner's Representative.
- .2 Scheduled project meetings.

1.2 **RELATED SECTIONS**

- .1 Section 01 11 00 - Summary of Work.

1.3 **DESCRIPTION**

- .1 Coordination of progress schedules, submittals, use of site, temporary utilities, construction facilities, and construction Work, with progress of Work of other contractors and subcontractors under instructions of Owner's Representative.

1.4 **PROJECT MEETINGS**

- .1 Project meetings to be held at times and locations as determined by Owner's Representative.
- .2 The General Contractor will arrange project meetings with the Owner's Representative and will be responsible to record and distribute minutes.

1.5 **CONSTRUCTION ORGANIZATION AND START-UP**

- .1 Within 10 days after award of Contract, request a meeting of parties in contract to discuss and resolve administrative procedures and responsibilities.
- .2 Establish time and location of meetings and notify parties concerned minimum 5 days before meeting.
- .3 Agenda to include following:
 - .1 Appointment of official representative of participants in Work.
 - .2 Schedule of Work, progress scheduling in accordance with Section 01 32 00 - Construction Progress Documentation.
 - .3 Schedule of submission of shop drawings, samples, colour chips, etc. in accordance with Section 01 33 00 - Submittal Procedures.
 - .4 Requirements for temporary facilities, site sign, offices, storage sheds, utilities, fences in accordance with Section 01 51 00 - Temporary Utilities.
 - .5 Delivery schedule of specified equipment in accordance with Section 01 32 00 - Construction Progress Documentation.
 - .6 Site security in accordance with Section 01 52 00 - Construction Facilities.

Gros Morne National Park

Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 31 00 - Project Management and Coordination

Page 2 of 4

- .7 Proposed changes, change orders, procedures, approvals required, mark-up percentages permitted, time extensions, overtime, and administrative requirements.
- .8 Record drawings in accordance with Section 01 78 00 - Closeout Submittals.
- .9 Maintenance manuals in accordance with Section 01 78 00 - Closeout Submittals.
- .10 Take-over procedures, acceptance, and warranties in accordance with Section 01 77 00 - Closeout Procedures and 01 78 00 - Closeout Submittals.
- .11 Monthly progress claims, administrative procedures, photographs, and holdbacks.
- .12 Appointment of inspection and testing agencies or firms in accordance with Section 01 45 00 - Quality Control.
- .13 Insurances and transcript of policies.
- .4 Comply with Owner's Representative's allocation of mobilization areas of site; for field offices and sheds, for access, traffic, and parking facilities.
- .5 During construction coordinate use of site and facilities through Owner's Representative's procedures for intra-project communications: Submittals, reports and records, schedules, coordination of drawings, recommendations, and resolution of ambiguities and conflicts.
- .6 Comply with instructions of Owner's Representative for use of temporary utilities and construction facilities.

1.6 ON-SITE DOCUMENTS

- .1 Maintain at job site, one copy each of the following:
 - .1 Contract drawings.
 - .2 Specifications.
 - .3 Addenda.
 - .4 Reviewed shop drawings.
 - .5 List of outstanding shop drawings.
 - .6 Change orders.
 - .7 Other modifications to Contract.
 - .8 Field test reports.
 - .9 Copy of approved Work schedule.
 - .10 Health and Safety Plan and other Safety related documents.
 - .11 Manufacturers' installation and application instructions.
 - .12 Labour conditions and wage schedules.
 - .13 Other documents as specified.

1.7 SCHEDULES

- .1 Submit preliminary construction progress schedule in accordance with Section 01 32 00 - Construction Progress Documents to Owner's Representative coordinated with Owner's Representative's project schedule. Schedule to show anticipated progress stages and final completion of work within time period required by contract documents.

- .2 After review, revise and resubmit schedule to comply with project schedule requirements.
- .3 During progress of Work revise and resubmit at project progress meetings or as directed by Owner's Representative.

1.8 SUBMITTALS

- .1 Make submittal to Owner's Representative for review.
- .2 Submit preliminary shop drawings, product data and samples in accordance with Section 01 33 00 – Submittal Procedures for review for compliance with Contract Documents; for field dimensions and clearances, for relation to available space, and for relation to Work of other contracts. After review, revise and resubmit for transmittal to Owner's Representative.
- .3 Submit requests for payment for review to Owner's Representative.
- .4 Submit requests for interpretation of Contract Documents, and obtain instructions through Owner's Representative.
- .5 Process change orders through Owner's Representative.
- .6 Deliver closeout submittals for review by Owner's Representative.

1.9 COORDINATION DRAWINGS

- .1 Provide information required by Owner's Representative for preparation of coordination drawings.
- .2 Review and approve revised drawings for submittal to Owner's Representative.
- .3 Owner's Representative may furnish additional drawings for clarification. These additional drawings have same meaning and intent as if they were included with plans referred to in contract documents.

1.10 CLOSEOUT PROCEDURES

- .1 Notify Owner's Representative when Work is considered ready for Substantial Performance.
- .2 Accompany Owner's Representative on preliminary inspection to determine items listed for completion or correction.
- .3 Comply with Owner's Representative's instructions for correction of items of Work listed in executed certificate of Substantial Performance and for access to Owner-occupied areas.
- .4 Notify Owner's Representative of instructions of items of Work determined in Owner's Representative's final inspection.

Gros Morne National Park

Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 31 00 - Project Management and Coordination

Page 4 of 4

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 77 00 - Closeout Procedures.

1.2 **SCHEDULES REQUIRED**

- .1 Submit schedules as follows:
 - .1 Construction Progress Schedule.
 - .2 Submittal Schedule for Shop Drawings and Product Data.
 - .3 Submittal Schedule for Samples.
 - .4 Product Delivery Schedule.
 - .5 Shutdown or closure activity.

1.3 **FORMAT**

- .1 Prepare schedule in form of a horizontal bar chart.
- .2 Provide a separate bar for each major item of work, trade or operation.
- .3 Split horizontally for projected and actual performance.
- .4 Provide horizontal time scale identifying first work day of each week.
- .5 Format for listings: chronological order of start of each item of work.
- .6 Identification of listings: By Systems description.

1.4 **SUBMISSION**

- .1 Submit initial format of schedules within 15 working days after award of Contract.
- .2 Submit schedules in electronic format, forward on disc as PDF files.
- .3 Submit one opaque reproduction, plus 2 copies to be retained by Owner's Representative.
- .4 Owner's Representative will review schedule and return review copy within 10 days after receipt.
- .5 Resubmit finalized schedule within 7 days after return of review copy.
- .6 Submit revised progress schedule with each application for payment.
- .7 Distribute copies of revised schedule to:
 - .1 Job site office.
 - .2 Subcontractors.
 - .3 Other concerned parties.

- .8 Instruct recipients to report to Contractor within 10 days, any problems anticipated by timetable shown in schedule.

1.5 CRITICAL PATH SCHEDULING

- .1 Include complete sequence of construction activities.
- .2 Include dates for commencement and completion of each major element of construction as follows.
 - .1 Site excavation.
 - .2 Foundation Work.
- .3 Show projected percentage of completion of each item as of first day of month.
- .4 Indicate progress of each activity to date of submission schedule.
- .5 Show changes occurring since previous submission of schedule:
 - .1 Major changes in scope.
 - .2 Activities modified since previous submission.
 - .3 Revised projections of progress and completion.
 - .4 Other identifiable changes.
- .6 Provide a narrative report to define:
 - .1 Problem areas, anticipated delays, and impact on schedule.
 - .2 Corrective action recommended and its effect.
 - .3 Effect of changes on schedules of other prime contractors.

1.6 SUBMITTALS SCHEDULE

- .1 Include schedule for submitting shop drawings, product data, and samples.
- .2 Indicate dates for submitting, review time, resubmission time, last date for meeting fabrication schedule.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 GENERAL

1.1 SECTIONS INCLUDE

- .1 Shop drawings and product data.
- .2 Samples.
- .3 Certificates and transcripts.

1.2 RELATED SECTIONS

- .1 Section 01 32 00 – Construction Progress Documentation.
- .2 Section 01 45 00 – Quality Control
- .3 Section 01 78 00 – Closeout Submittals

1.3 ADMINISTRATIVE

- .1 This section specifies general requirements and procedures for contractor's submissions of shop drawings, product data, samples and mock-ups to Owner's Representative for review. Submit promptly and in orderly sequence to not cause delay in Work. Failure to submit in ample time is not considered sufficient reason for an extension of Contract Time and no claim for extension by reason of such default will be allowed.
- .2 Do not proceed with work until relevant submissions are reviewed by Owner's Representative.
- .3 Present shop drawings, product data, samples and mock-ups in SI Metric units.
- .4 Where items or information is not produced in SI Metric units converted values are acceptable.
- .5 Review submittals prior to submission to Owner's Representative. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents. Submittals not stamped, signed, dated and identified as to specific project will be returned without being examined and shall be considered rejected.
- .6 Notify Owner's Representative, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.
- .7 Verify field measurements and affected adjacent Work are coordinated.
- .8 Contractor's responsibility for errors and omissions in submission is not relieved by Owner's Representative's review of submittals.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 33 00 – Submittal Procedures

Page 2 of 4

- .9 Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Owner's Representative review of submission, unless Owner's Representative gives written acceptance of specific deviations.
- .10 Make any changes in submissions which Owner's Representative may require consistent with Contract Documents and resubmit as directed by Owner's Representative. When resubmitting, notify Owner's Representative in writing of revisions other than those requested.
- .11 Notify Owner's Representative, in writing, when resubmitting, of any revisions other than those requested by Owner's Representative.
- .12 Keep one reviewed copy of each submission on site.

1.4 SUBMITTALS

- .1 The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.
- .2 Coordinate each submission with requirements of work and Contract Documents. Individual submissions will not be reviewed until all related information is available.
- .3 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes and other information necessary for completion of Work. Where articles or equipment attach or connect to other articles or equipment, indicate that such items have been coordinated, regardless of Section under which adjacent items will be supplied and installed. Indicate cross references to design drawings and specifications.
- .4 Allow 10 days for Owner's Representative review of each submission.
- .5 Adjustments made on shop drawings by Owner's Representative are not intended to change contract price. If adjustments affect value of Work, state such in writing to Owner's Representative immediately after receipt of approval of shop drawings. If value of work is to change a change order must be issued prior to proceeding with work.
- .6 Accompany submissions with transmittal letter, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .4 Identification and quantity of each shop drawing, product data and sample.
 - .5 Other pertinent data.
- .7 Submissions shall include:
 - .1 Date and revision dates.
 - .2 Project title and number.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 33 00 – Submittal Procedures

Page 3 of 4

- .3 Name and address of:
 - .1 Subcontractor.
 - .2 Supplier.
 - .3 Manufacturer.
- .4 Contractor's stamp, signed by Contractor's authorized representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
- .5 Details of appropriate portions of Work as applicable:
 - .1 Fabrication.
 - .2 Layout, showing dimensions, including identified field dimensions, and clearances.
 - .3 Setting or erection details.
 - .4 Capacities.
 - .5 Performance characteristics.
 - .6 Standards.
 - .7 Operating weight.
 - .8 Wiring diagrams.
 - .9 Single line and schematic diagrams.
 - .10 Relationship to adjacent work.
- .8 After Owner's Representative review, distribute copies.
- .9 Submit 3 prints plus one electronic copy in PDF format of shop drawings for each requirement requested in specification Sections and as Owner's Representative may reasonably request.
- .10 Submit electronic copy in PDF format of product data sheets or brochures for requirements requested in Specification Sections and as requested by Owner's Representative where shop drawings will not be prepared due to standardized manufacture of product.
- .11 Delete information not applicable to project.
- .12 Supplement standard information to provide details applicable to project.
- .13 Cross-reference product data information to applicable portions of Contract Documents.
- .14 If upon review by Owner's Representative, no errors or omissions are discovered or if only minor corrections are made, copies will be returned and fabrication and installation of work may proceed. If shop drawings are rejected, noted copy will be returned and resubmission of corrected shop drawings, through same procedure indicated above, must be performed before fabrication and installation of work may proceed.
- .15 Samples: examples of materials, equipment, quality, finishes, workmanship. Label samples with origin and intended use.

- .16 Notify Owner's Representative in writing, at time of submission of deviations in samples from requirements of contract documents.
- .17 Where colour, pattern or texture is criterion, submit full range of samples.
- .18 Adjustments made on samples by Owner's Representative are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Owner's Representative prior to proceeding with Work.
- .19 Make changes in samples, which Owner's Representative may require, consistent with Contract Documents.
- .20 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

1.5 MOCK-UPS

- .1 Erect mock-ups in accordance with Section 01 45 00 - Quality Control.

1.6 PROGRESS PHOTOGRAPHS

- .1 Progress photograph to be electronically formatted and labelled as to location and view.

1.7 SHOP DRAWINGS REVIEW

- .1 The review of shop drawings by Owner's Representative is for the sole purpose of ascertaining conformance with the general concept. This review shall not mean that Owner's Representative approves the detail design inherent in the shop drawings, responsibility for which shall remain with the Contractor submitting same, and such review shall not relieve the Contractor of responsibility for errors or omissions in the shop drawings or of responsibility for meeting all requirements of the construction and contract documents. Without restricting the generality of the foregoing, the Contractor is responsible for dimensions to be confirmed and correlated at the job site, for information that pertains to fabrication processes or to techniques of construction and installation and for co-ordination of the work of all sub-trades.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **REFERENCES**

- .1 Canadian Standards Association (CSA)
 - .1 CAN/CSA-Z259.1 Body Belts and Saddles for Work Positioning and Travel Restraint.
 - .2 CAN/CSA-Z259.10 Full body Harnesses.
 - .3 CAN/CSA-Z259.11 Energy Absorbers and Lanyards.
 - .4 CAN/CSA-Z259.2.1 Fall Arresters, Vertical Lifelines and Rails.
 - .5 FCC No. 301 Standard for Construction Operations.
 - .6 CSA Z797, Code of Practice for Access Scaffold.
- .2 FCC No. 302 Standard for Welding and Cutting.
- .3 Transportation of Dangerous Goods Act Regulations.
- .4 Newfoundland Occupational Health and Safety Act, Amended
- .5 Consolidated Newfoundland and Regulations 1149 WMIS Regulations Under the Occupational Health and Safety Act
- .6 Consolidated Newfoundland and Regulations Occupational Health and Safety Regulations under the Occupational Health and Safety Act.
- .7 Canada Labour Code, Part 2.
- .8 National Building Code of Canada.
- .9 Department of Transportation and Works Occupational Health and Safety Manual.

1.2 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 35 43 - Environmental Procedures.
- .3 Section 01 41 00 - Regulatory Requirements.

1.3 **SUBMITTALS**

- .1 At least 10 (ten) working days prior to commencing any site work: submit to Owner's Representative copies of:
 - .1 A complete Site Specific Health and Safety Plan.
 - .2 If work entails confined space, submit the following:

- .1 Copies of confined space entry training certificates acceptable to WHSCC, as well as copies of confined space entry programs, confined space assessment, safe work practices and rescue plans.
- .2 Acceptance of the Site Specific Health and Safety Plan and other submitted documents by the Owner's Representative shall only be viewed as acknowledgement that the contractor has submitted the required documentation under this specification section.
- .3 Owner's Representative makes no representation and provides no warranty for the accuracy, completeness and legislative compliance of the Site Specific Health and Safety Plan and other submitted documents by this acceptance.
- .4 Responsibility for errors and omissions in the Site Specific Health and Safety Plan and other submitted documents is not relieved by acceptance by Owner's Representative.

1.4 OCCUPATIONAL HEALTH AND SAFETY (SITE SPECIFIC HEALTH AND SAFETY PLANS)

- .1 Conduct operations in accordance with latest edition of the Newfoundland Occupational Health and Safety (OH&S) Act and Regulations, with specific reference to codes and standards referenced therein, and the Department of Transportation and Works Occupational Health and Safety Manual (http://www.tw.gov.nl.ca/publications/ohs_full.pdf).
- .2 Prepare a detailed Site Specific Health and Safety Plan that shall identify, evaluate and control job specific hazards and the necessary control measures to be implemented for managing hazards.
- .3 Provide a copy of the Site Specific Health and Safety Plan upon request to Occupational Health and Safety Branch, Services NL, Province of Newfoundland and Labrador and the Owner.
- .4 The written Site Specific Health and Safety Plan shall incorporate the following:
 - .1 Hazard assessment results.
 - .2 Engineering and administrative demonstrative controls (work-practices and procedures) to be implemented for managing identified and potential hazards, and comply with applicable federal and provincial legislation and more stringent requirements that have been specified in these specifications.
 - .3 An organizational structure which shall establish the specific chain of command and specify the overall responsibilities of contractor's employees at the work site.
 - .4 A comprehensive workplan which shall:
 - .1 define work tasks and objectives of site activities/operations and the logistics and resources required to reach these tasks and objectives.
 - .2 establish personnel requirements for implementing the plan, and
 - .5 A personal protective equipment (PPE) Program which shall detail PPE:
 - .1 Selection criteria based on site hazards.

- .2 Use, maintenance, inspection and storage requirements and procedures.
- .3 Decontamination and disposal procedures.
- .4 Inspection procedures prior to during and after use, and other appropriate medical considerations.
- .5 Limitations during temperature extremes, heat stress and other appropriate medical consideration.
- .6 An emergency response procedure, refer to Clause 1.5 Supervision and Emergency Response Procedure of this section for requirements.
- .7 A hazard communication program for informing workers, visitors and individuals outside of the work area as required. This will include but not be limited to a visitor safety and orientation policy and program that will include education on hazards, required PPE and accompaniment while on site.
- .8 A hearing conservation program in accordance with the OHS Regulations.
- .9 A recent (current year) inspection form for all powered mobile equipment that will be used in fulfilling the terms of the contract. The inspection form shall, at a minimum, state that the equipment is in a safe operating condition.
- .10 A complete listing of employee names, their driver's license classification, expiry date, endorsements and the type of equipment that they are qualified to operate for the complete scope of work for this project. The Driver's License Number should not be provided as this is confidential information. Provision of the License Number may breach *PIPEDA* - the Personal Information Protection and Electronic Documents Act. (Federal Act) or *ATIPPA - Access to Information and Protection of Privacy Act - Part IV*. (Provincial Act of Newfoundland and Labrador). This shall also include documentation where required of certification in power line hazards.
- .11 An acceptable parking policy for all powered mobile equipment to be used on this project. The policy shall, at a minimum, be based on a hazard assessment that considers factors such as equipment type, potential for roll over, load capacity of the parking area, pedestrian and vehicular traffic, and potential for equipment tampering, equipment energy, and equipment contact with power lines.
- .12 A health and safety training program which includes a safety training matrix.
- .13 General safety rules.
- .5 Periodically review and modify as required each component of the Site Specific Health and Safety Plan when a new hazard is identified during completion of work and when an error or omission is identified in any part of the Site Specific Health and Safety Plan.
- .6 Review the completeness of the hazard assessment immediately prior to commencing work, when a new hazard is identified during completion of work and when an error or omission is identified.
- .1 Be solely responsible for investigating, evaluating and managing any report of actual or potential hazards.
- .2 Clearly define accident incident investigation procedures.
- .3 Clearly define policy and processes for early and safe return to work.

- .4 Retain copies of all completed hazard assessments at the project site and make available to the Owner's Representative immediately upon request.
- .7 Implement all requirements of the Site Specific Health and Safety Plan.
 - .1 Ensure that every person entering the project site is informed of requirements under the Site Specific Health and Safety Plan.
 - .2 Take all necessary measures to immediately implement any engineering controls, administrative controls, personal protective equipment required or termination of work procedures to ensure compliance with the Site Specific Health and Safety Plan.

1.5 SUPERVISION AND EMERGENCY RESCUE PROCEDURE

- .1 Carry out work under the direct supervision of competent persons responsible for safety by ensuring the work complies with the appropriate section of OH&S Act and Regulations
- .2 Assign a sufficient number of supervisory personnel to the work site.
 - .1 Any person assigned to supervisory duties shall not conduct significant work in relation to the contract that inhibits them from the ability to properly supervise the work site.
- .3 Provide a suitable means of communications and check-in for workers required to work alone.
- .4 Develop an emergency rescue plan for the job site and ensure that supervisors and workers are trained in the emergency rescue plan.
- .5 The emergency response plan shall address, as a minimum:
 - .1 Pre-emergency planning.
 - .2 Personnel roles, lines of authority and communication.
 - .3 Emergency recognition and prevention.
 - .4 Safe distances and places of refuge.
 - .5 Site security and control
 - .6 Evacuation routes and procedures
 - .7 Decontamination procedures which are not covered by the site specific safety and health plan.
 - .8 Emergency medical treatment and first aid.
 - .9 Emergency alarm, notification and response procedures including procedures for reporting incidents to local, provincial and federal government departments.
 - .10 PPE and emergency equipment.
 - .11 Procedures for handling emergency incidents.
 - .12 Site specific emergency response training requirements and schedules.
- .6 The emergency response procedures shall be rehearsed regularly as part of the overall training program.

- .7 Provide adequate first aid facilities for the jobsite and ensure that a minimum number of workers are trained in first aid in accordance with the First Aid Regulations.

1.6 CONTRACTORS SAFETY OFFICER

- .1 The contractor shall employ a Contractor's Safety Officer (CSO) who shall have as a minimum:
- .1 Completed training in hazardous materials management and response/protocols.
 - .2 Completed training in the use, maintenance of fall protection systems certified by WHSCC at a minimum.
 - .3 Completed training in the erection and inspection of scaffolding.
 - .4 Completed training in confined space entry protocols, techniques and rescue plans, certified by WHSCC at a minimum.
 - .5 Completed supervisory training.
 - .6 Completed training in records and statistics.
 - .7 Completed training in hazard identification, inspections, analysis and control.
 - .8 Completed training in WHMIS.
 - .9 Completed training in health and safety program content.
 - .10 Completed training in investigations and reporting.
 - .11 Completed training in occupational health/hygiene.
 - .12 Completed training in employee training and communication.
 - .13 Completed training in Emergency Preparedness and First Aid.
 - .14 A working knowledge of occupational safety and health legislation and regulations (specific to Newfoundland and Labrador).
 - .15 A working knowledge of safe work practices required for execution of the work and operation of equipment specific to the project.
 - .16 A working knowledge of site safety and house keeping.
 - .17 A working knowledge of preventative maintenance program for Construction Site Equipment.
- .2 The CSO shall:
- .1 Be responsible for implementing, daily enforcement, monitoring and updating of the Site Specific Health and Safety Plan.
 - .2 Be responsible for the delivery of the site safety orientation and ensure that the personnel who have not been orientated are not permitted to enter the site.
 - .3 Report directly to and be under direction of the site superintendent or Contractor's Project Manager.
 - .4 Prior to mobilization on-site, hold an orientation meeting with the contractors, subcontractors and Owner's Representative to review project occupational health and safety. Include but not limit meeting to a review of:
 - .1 Site Specific Health and Safety Plan.
 - .2 Construction Safety Measures.

- .3 Supervision and Emergency Rescue Procedures.
- .4 Hazard Assessments
- .5 Maintain a daily log of inspections, meetings, infractions and mitigating measures. Log is to be filed daily and copied to the site superintendent and Owner's Representative.

1.7 HEALTH AND SAFETY COMMITTEE

- .1 Establish an Occupational Health and Safety Committee where ten or more workers are employed on the job site as per the OH&S Act and Regulations.

1.8 RESPONSIBILITY

- .1 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
- .2 Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial and local statutes, regulations, and ordinances, and with Site Specific Health and Safety Plan.
- .3 Where life safety risks exist, the contractor must stop the work until such time as the risk can be mitigated to a safe level.
- .4 Take appropriate steps to ensure that the hazards are mitigated to a safe level, workers are notified of the hazards and how to protect themselves. As well, workers must be provided with any new safe work practices or information regarding mitigation of the risk.

1.9 UNFORSEEN HAZARDS

- .1 Should any unforeseen or peculiar safety-related factor, hazard, or condition become evident during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction. Advise Owner's Representative verbally and in writing.

1.10 INSTRUCTION AND TRAINING

- .1 Workers shall not participate in or supervise any activity on the work site until they have been trained to a level required by this job function and responsibility. Training shall as a minimum thoroughly cover the following:
 - .1 Federal and Provincial Health and Safety Legislation requirements including roles and responsibilities of workers and person(s) responsible for implementing, monitoring and enforcing health and safety requirements.
 - .2 Safety and health hazards associated with working on a contaminated site including recognition of symptoms and signs which might indicate over exposure to hazards.

- .3 Limitations, use, maintenance and disinfection-decontamination of personal protective equipment associated with completing work.
- .4 Limitations, use, maintenance and care of engineering controls and equipment.
- .5 Limitations and use of emergency notifications and response equipment including emergency response protocol.
- .6 Work practices and procedures to minimize the risk of an accident and hazardous occurrence from exposure to a hazard.
- .2 Provide and maintain training of workers, as required, by Federal and Provincial legislation.
- .3 Provide copies of all training certificates to Owner's Representative for review, before a worker is to enter the work site.
- .4 Authorized visitors shall not access the work site until they have been:
 - .1 Notified of the names of persons responsible for implementing, monitoring and enforcing the Site Specific Health and Safety Plan.
 - .2 Briefed on safety and health hazards present on the site.
 - .3 Instructed in the proper use and limitations of personal protective equipment.
 - .4 Briefed on the emergency response protocol including notification and evacuation process.
 - .5 Informed of practices and procedures to minimize risks from hazards and applicable to activities performed by visitors.
 - .6 Accompanied while on site, and provided with the appropriate PPE.
- .5 All workers will be instructed and trained on the hazards associated with work they will perform and how to protect themselves. This will include a review of all safe work practices, the reporting and documentation of hazards, reporting accidents and injuries as well as, formal training in areas of high risk (i.e. fall protection, power line hazards, traffic control persons training).
- .6 The work site shall have the appropriate number of persons trained in emergency and Standard First Aid according to the First Aid Regulations.

1.11 CONSTRUCTION SAFETY MEASURES

- .1 Observe construction safety measures of National Building Code, latest edition, Provincial Government, OH&S Act and Regulations, Workplace Health and Safety Compensation Commission and Municipal Authority provided that in any case of conflict or discrepancy more stringent requirements shall apply.
- .2 Administer the project in a manner that will ensure, at all times, full compliance with Federal and Provincial Acts, regulations and applicable safety codes and the Site Specific Health and Safety Plan.

- .3 Provide Owner's Representative with copies of all orders, directions and any other documentation, issued by the Occupational Health and Safety Branch, Services NL, immediately after receipt.

1.12 POSTING OF DOCUMENTS

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province and authority having jurisdiction, and in consultation with Owner's Representative.

1.13 HEALTH AND SAFETY MONITORING

- .1 Periodic inspections of the contractor's work may be carried out by the Owner's Representative to maintain compliance with the Health and Safety Program. Inspections will include visual inspections as well as testing and sampling as required.
- .2 The contractor shall be responsible for any and all costs associated with delays as a result of contractor's failure to comply with the requirements outlined in this section.

1.14 NOTIFICATION

- .1 For projects exceeding thirty (30) days or more, the contractor shall, prior to the commencement of work, notify in writing the Occupational Health and Safety Branch, Services NL with the following information:
 - .1 Name and location of construction site.
 - .2 Company name and mailing address of contractor doing the work.
 - .3 The number of workers to be employed.
 - .4 A copy of the Site Specific Health and Safety Plan if requested.

1.15 CORRECTION OF NON-COMPLIANCE

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Owner's Representative.
- .2 Provide Owner's Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Owner's Representative may stop work if non-compliance of health and safety regulations is not corrected.

1.16 WHMIS

- .1 Ensure that all controlled products are in accordance with the Workplace Hazardous Materials Information System (WHMIS) Regulations and Chemical Substances of the OH&S Act and Regulations regarding use, handling, labelling, storage, and disposal of hazardous materials.

- .2 Deliver copies of relevant Material Safety Data Sheets (MSDS) to job site and the Owner's Representative. The MSDS must be acceptable to Labour Canada and Health and Welfare Canada for all controlled products that will be used in the performance of this work.
- .3 Train workers required to use or work in close proximity to controlled products as per OH&S Act and Regulations.
- .4 Label controlled products at jobsite as per OH&S and Regulations.
- .5 Provide appropriate emergency facilities as specified in the MSDS where workers might be exposed to contact with chemicals, e.g. eye-wash facilities, emergency shower.
 - .1 Workers to be trained in use of such emergency equipment.
- .6 Contractor shall provide appropriate personal protective equipment as specified in the MSDS where workers are required to use controlled products.
 - .1 Properly fit workers for personal protective equipment
 - .2 Train workers in care, use and maintenance of personal protective equipment.
- .7 No controlled products are to be brought on-site without prior approved MSDS.
- .8 The MSDS are to remain on site at all times.

1.17 OVERLOADING

- .1 Ensure no part of work or associated equipment is subjected to loading that will endanger its safety or will cause permanent deformation.

1.18 FALSEWORK

- .1 Design and construct falsework in accordance with CSA S269.1.

1.19 SCAFFOLDING

- .1 Design, erect, inspect, operate, modify, and dismantle scaffolding in accordance with CSA Z797, the OH&S Act and Regulations, and the scaffold manufacturer's written instructions.
- .2 Provide trained and certified Competent Scaffold Erectors for all scaffold erection, modification and dismantling.
- .3 Conduct and document daily inspections of scaffolding by trained and certified Competent Scaffold Inspectors or Erectors.
- .4 Provide a scaffold tagging system as described in CSA Z797.
- .5 Ensure that all industry best practices for safe scaffold usage, including fall protection, proper loading, safe access, electrical hazards, exit door management and other concerns are strictly adhered to.

1.20 WORKING AT HEIGHTS

- .1 Ensure that fall restraint or fall arrest devices are used by all workers working at elevations greater than 3.05 meters above grade or floor level in accordance with CSA Z259, where alternate fall protection systems are not provided in accordance with Occupational Health and Safety Act and Regulations.
- .2 All workers performing work at height and who will be required to utilize a fall arrest system must be trained in a fall protection program certified by the WHSCC.
- .3 Prior to working at height workers shall be instructed in a Contractor SWP for working at height and associated rescue plan for working at height developed specific to the work, locations and risks.

1.21 PERSONAL PROTECTIVE EQUIPMENT

- .1 Ensure workers on the jobsite use personal protective equipment appropriate to the hazards identified in the Site Specific Health and Safety Plan and those workers are trained in the proper care, use, and maintenance of such equipment.
- .2 PPE selections shall be based on an evaluation of the performance characteristics of the PPE relative to the requirements and limitations of the site, task-specific conditions, duration and hazards and potential hazards identified on site.
- .3 Provide workers and visitors to the site with proper respiratory protection equipment.
 - .1 No work shall be performed in an area where an airborne contaminant exceeds recommendations of the ACGIH, do not meet the appropriate standards for the specific contaminants or are not in accordance with the OHS regulations..
 - .2 Respiratory protection shall be provided in accordance with the requirements of the Occupational Health and Safety Branch, Services NL and these specifications.
 - .3 Establish, implement and maintain a respirator inspection and maintenance program in accordance with the CSA standard identified in the OHS Regulations.
 - .4 Copies of all respirator owners' maintenance manuals, shall be kept at all times at the contractor's site office.
- .4 Provide and maintain a supply of dermal protection equipment to allow visitors and all workers proper dermal protection.
 - .1 Dermal protection shall be sufficient to act as a protective barrier between the skin and an airborne contaminant or hazardous material. Dermal protection shall also be provided for all physical hazards.
 - .2 Dermal protection equipment shall not be used after exceeding 75% of the break through time. The break through time shall be based on the contaminant which requires the least amount of time to break through the protective equipment
 - .3 Copies of all dermal protection user specifications, owners and maintenance manuals shall be kept at all times at the contractor's site office.

- .4 Establish, implement and maintain air inspection program to ensure proper dermal protection in accordance with CSA, NIOSH, U.S. EPA and manufacturer's requirements.
- .5 Provide all workers and up to five (5) visitors to the site with proper hearing protection. Workers and visitors shall not be exposed to noise levels greater than 85 dB (A) over an eight hour shift without proper hearing protection, in accordance with the Hearing Conservation Program.
- .6 Provide all workers and up to five (5) visitors to the site with CSA approved eye protection sufficient to act as a protective barrier between the eye and airborne contaminants, hazardous materials and physical hazard.
- .7 Provide workers and up to five (5) visitors to the site with CSA approved hard hats meeting the CSA Z94.1.
- .8 Provide high visibility apparel as defined in Occupational Health and Safety Regulations.
- .9 Provide CSA approved safety boots meeting CSA Z195.
- .10 Provide other personal protective equipment, as may be required by the owner, depending on duties being performed.

1.22 TRAFFIC CONTROL

- .1 Provide traffic control measures when working on, or adjacent to, roadways in accordance with the "Traffic Control Manual for Roadwork Operations", Department of Transportation and Works.

1.23 EXCAVATION SAFETY

- .1 Protect excavations more than 1.25 metres deep against cave-ins or wall collapse by side wall sloping to the appropriate angle of repose, an engineered shoring/sheathing system or an approved trench box.
 - .1 Provide a ladder which can extend from the bottom of the excavation to at least 0.91 metres above the top of the excavation.
- .2 Ensure that all excavations less than 1.25 metres deep are effectively protected when hazardous ground movement may be expected.
- .3 Design trench boxes, certified by a registered Professional Engineer, and fabricated by a reputable manufacturer. Provide the manufacturer's Depth Certificate Statement permanently affixed. Use trench boxes in strict accordance with manufacturer's instructions and depth certification data.
- .4 For excavations deeper than six (6) metres, provide a certificate from a registered Professional Engineer stating that the protection methods proposed have been properly designed in accordance with accepted engineering practice. The engineer's certificate

shall verify that the trench boxes, if used, are properly designed and constructed to suit the depth and soil conditions.

- .5 Ensure that the superintendent and every crew chief, foreperson and lead hand engaged in trenching operations or working in trenches have in his/her possession a copy of Occupational Health and Safety Regulations: Part XVII: Construction, Excavation and Demolition and Part XVIII: Excavation, Underground Work and Rock Crushing and where possible a copy of the Service NL's "Trench Excavation Safety Guide".

1.24 CONFINED SPACE WORK

- .1 Comply with the Newfoundland and Labrador Occupational health and Safety Regulations.
- .2 Ensure a hazard assessment has been conducted related to the confined space and the work to be performed within the space.
- .3 Provide approved air monitoring equipment where workers are working in confined spaces and ensure any test equipment to be used is calibrated, in good working order and used by trained persons.
- .4 Ensure all Required PPE is provided to the workers and workers are trained in its use, care and selection.
- .5 Develop a confined space entry (CSE) program specific to the nature of work performed and in accordance with OH&S Act and Regulations and ensure supervisors and workers are trained in the confined space entry program. This shall include training on the CSE permit system, rescue plan, testing, communication equipment and all equipment and safe work procedures conducted in and around the confined space.
 - .1 Ensure that personal protective equipment and emergency rescue equipment appropriate to the nature of the work being performed is provided and used.
- .6 Provide and maintain training of workers through a provider certified by the WHSCC.
- .7 Provide Owner's Representative with a copy of an "Entry Permit" for each entry into the confined space to ensure compliance Provincial Legislation.

1.25 HAZARDOUS MATERIALS

- .1 Should material resembling hazardous materials (e.g. asbestos/mould) not previously identified/documented be encountered during the execution of work and notify Owner's Representative. Do not proceed until written instructions have been received from Owner's Representative.
- .2 Unless otherwise noted the services of a recognized Environmental Consultant to provide all air monitoring and testing services required by regulatory requirements for hazardous materials abatement and repair.

1.26 HEAVY EQUIPMENT

- .1 Ensure mobile equipment used on jobsite is of the type specified in OH&S Act and Regulations fitted with a Roll Over Protective (ROP) Structure and Falling Object Protective (FOP) Structure.
- .2 Provide certificate of training in Power Line Hazards for operators of heavy equipment.
- .3 Obtain written clearance from the power utility where equipment is used in close proximity to (within 5.5 metres) overhead or underground power lines.
- .4 Equip cranes with:
 - .1 A mechanism which will effectively prevent the hook assembly from running into the top boom pulley.
 - .2 A legible load chart.
 - .3 A maintenance log book.

1.27 WORK STOPPAGE

- .1 Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations of Work.

PART 2 PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **FIRES**

- .1 Fires and burning of rubbish on site not permitted.

1.2 **DISPOSAL OF WASTES**

- .1 Do not bury rubbish and waste materials on site.
- .2 Do not dispose of waste or volatile materials, such as mineral spirits, oil or paint thinner into waterways, storm or sanitary sewers.

1.3 **DRAINAGE**

- .1 Provide temporary drainage and pumping as necessary to keep excavations and site free from water.
- .2 Do not pump water containing suspended materials into waterways, sewer or drainage systems.
- .3 Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authority requirements.

1.4 **POLLUTION CONTROL**

- .1 Maintain temporary erosion and pollution control features installed under this contract.
- .2 Control emissions from equipment and plant to local authorities emission requirements.
- .3 Prevent sandblasting and other extraneous materials from contaminating air beyond application area, by providing temporary enclosures.
- .4 Cover or wet down dry materials and rubbish to prevent blowing dust and debris. Provide dust control for temporary roads.

1.5 **NOTIFICATION**

- .1 Owner's Representative will notify Contractor in writing of observed non-compliance with Federal, Provincial or Municipal environmental laws or regulations, permits, and other elements of environmental protection. Contractor: after receipt of such notice, inform Owner's Representative of proposed corrective action and take such action as approved by Owner's Representative.
- .2 Owner's Representative may issue stop order of work until satisfactory corrective action has been taken.

- .3 No time extensions will be granted or equitable adjustments allowed to Contractor for such suspensions.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 GENERAL

1.1 REFERENCES AND CODES

- .1 Perform Work in accordance with National Building Code of Canada (NBC) including all amendments up to tender closing date and other codes of provincial or local application provided that in case of conflict or discrepancy, more stringent requirements apply.

- .2 Meet or exceed requirements of:
 - .1 Contract documents.
 - .2 Specified standards, codes and referenced documents.

1.2 HAZARDOUS MATERIAL DISCOVERY

- .1 Mould: stop work immediately should material resembling mould be encountered during the execution of work and notify Owner's Representative. Do not proceed until written instructions have been received from Owner's Representative.

1.3 BUILDING SMOKING ENVIRONMENT

- .1 Comply with smoking restrictions.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 GENERAL

1.1 SECTIONS INCLUDE

- .1 Inspection and testing, administrative and enforcement requirements.
- .2 Tests and mix designs.
- .3 Mill tests.

1.2 RELATED SECTIONS

- .1 Section 01 33 00 – Submittal Procedures
- .2 Section 01 78 00 – Closeout Submittals

1.3 INSPECTION

- .1 Allow Owner's Representative access to Work. If part of Work is in preparation at locations other than Place of Work, allow access to such Work whenever it is in progress.
- .2 Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Owner's Representative instructions.
- .3 If Contractor covers or permits to be covered Work that has been designated for special tests, inspections or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.
- .4 Owner's Representative may order any part of Work to be examined if Work is suspected to be not in accordance with Contract Documents. If, upon examination such work is found not in accordance with Contract Documents, correct such Work and pay cost of examination and correction. If such Work is found in accordance with Contract Documents, Owner's Representative shall pay cost of examination and replacement.

1.4 INDEPENDENT INSPECTION AGENCIES

- .1 Independent Inspection/Testing Agencies will be engaged by Owner's Representative for purpose of inspecting and/or testing portions of Work unless otherwise specified.
- .2 Allocated costs: to Section 01 29 83 – Payment Procedures: Testing Laboratory Services.
- .3 Provide equipment required for executing inspection and testing by appointed agencies.
- .4 Employment of inspection/testing agencies does not relax responsibility to perform Work in accordance with Contract Documents.

- .5 If defects are revealed during inspection and/or testing, appointed agency will request additional inspection and/or testing to ascertain full degree of defect. Correct defect and irregularities as advised by Owner's Representative at no cost to Owner's Representative. Pay costs for retesting and reinspection.

1.5 ACCESS TO WORK

- .1 Allow inspection/testing agencies access to Work, off site manufacturing and fabrication plants.
- .2 Co-operate to provide reasonable facilities for such access.

1.6 PROCEDURES

- .1 Notify appropriate agency and Owner's Representative in advance of requirement for tests, in order that attendance arrangements can be made.
- .2 Submit samples and/or materials required for testing, as specifically requested in specifications. Submit with reasonable promptness and in an orderly sequence so as not to cause delay in Work.
- .3 Provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.

1.7 REJECTED WORK

- .1 Remove defective Work, whether result of poor workmanship, use of defective products or damage and whether incorporated in Work or not, which has been rejected by Owner's Representative as failing to conform to Contract Documents. Replace or re-execute in accordance with Contract Documents.
- .2 Make good other Contractor's work damaged by such removals or replacements promptly.
- .3 If in opinion of Owner's Representative it is not expedient to correct defective Work or Work not performed in accordance with Contract Documents, Owner may deduct from Contract Price difference in value between Work performed and that called for by Contract Documents, amount of which shall be determined by Owner's Representative.

1.8 REPORTS

- .1 Submit 3 copies of inspection and test reports to Owner's Representative, plus electronic copies in PDF format.
- .2 Provide copy to Subcontractor of work being inspected or tested, manufacturer or fabricator of material being inspected or tested.
- .3 Include copy of all inspection and test reports in Commissioning Manuals.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 52 00 - Construction Facilities.
- .2 Section 01 56 00 - Temporary Barriers and Enclosures.

1.2 **INSTALLATION AND REMOVAL**

- .1 Provide temporary utilities controls in order to execute work expeditiously.
- .2 Remove from site all such work after use.

1.3 **DEWATERING**

- .1 Provide temporary drainage and pumping facilities to keep excavations and site free from standing water.

1.4 **WATER SUPPLY**

- .1 Arrange for connection with appropriate utility company and pay all costs for installation, maintenance and removal.

1.5 **TEMPORARY HEATING AND VENTILATION**

- .1 Pay for costs of temporary heat and ventilation used during construction, including costs of installation, fuel operation, maintenance and removal of equipment. Use of direct, fired heaters discharging waste products into work areas will not be permitted unless prior approval is given by Owner's Representative.
- .2 Construction heaters used inside building must be vented to outside or be non-flameless type. Solid fuel salamanders are not permitted.
- .3 Provide temporary heat and ventilation in enclosed areas as required to:
 - .1 Facilitate progress of Work.
 - .2 Protect Work and products against dampness and cold.
 - .3 Prevent moisture condensation on surfaces.
 - .4 Provide ambient temperatures and humidity levels for storage, installation and curing of materials.
 - .5 Provide adequate ventilation to meet health regulations for safe working environment.
- .4 Maintain temperatures of minimum 10°C and relative humidity less than 60% in areas where construction is in progress.

- .1 Maintain minimum temperature of 10°C or higher where specified as soon as finished work is commenced. Maintain until acceptance of structure by Owner's Representative.
- .2 Maintain ambient temperature and humidity levels as required for comfort of office personnel.
- .5 Ventilating:
 - .1 Prevent accumulations of dust, fumes, mists, vapours or gases in areas occupied during construction.
 - .2 Provide local exhaust ventilation to prevent harmful accumulation of hazardous substances into atmosphere of occupied areas.
 - .3 Dispose of exhaust materials in manner that will not result in harmful exposure to persons.
 - .4 Ventilate storage spaces containing hazardous or volatile materials.
 - .5 Ventilate temporary sanitary facilities.
 - .6 Continue operation of ventilation and exhaust system for time after cessation of work process to assure removal of harmful contaminants.
- .6 Maintain strict supervision of operation of temporary heating and ventilating equipment to:
 - .1 Conform with applicable codes and standards.
 - .2 Enforce safe practices.
 - .3 Prevent abuse of services.
 - .4 Prevent damage to finishes.
 - .5 Vent direct-fired combustion units to outside.
- .7 Be responsible for damage to Work due to failure in providing adequate heat, humidity and protection during construction.
- .8 Use of new or existing systems for temporary heating, ventilating or air conditioning will not be permitted.

1.6 TEMPORARY POWER AND LIGHT

- .1 Provide and pay for temporary power during construction for temporary lighting, heating, site construction trailers and operating of power tools in accordance with governing regulations and the Canadian Electrical Code, latest edition.
- .2 Arrange for connection with Utility company. Pay all costs for installation, maintenance and removal of cables, distribution and branch panel boards, poles, lighting, heating and general power receptacles as required.
- .3 Temporary power for electric cranes and other equipment requiring in excess of above is responsibility of Contractor.

- .4 Provide and maintain temporary lighting throughout project. Ensure level of illumination on all floors and stairs is not less than 162 lx. Temporary lighting to consist of wiring, pig tail sockets and 75 watt shatterproof incandescent lamps to provide a minimum light level of 162 lux.
- .5 Electrical power and lighting systems installed under this contract may be used for construction requirements only with prior approval of Owner's Representative provided that guarantees are not affected. Make good damage to electrical system caused by use under this contract. Replace lamps which have been used for more than 3 months.
- .6 General contractor responsible for payment of all electrical energy charges associated with temporary power up to date of substantial completion.

1.7 FIRE PROTECTION

- .1 Provide and maintain temporary fire protection equipment during performance of Work required by insurance companies having jurisdiction and governing codes, regulations and bylaws.
- .2 Burning rubbish and construction waste materials is not permitted on site.

1.8 SANITARY FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take precautions as required by local health authorities. Keep area and premises in sanitary condition.
- .3 When permanent water and drain connections are completed, provide temporary water closets and urinals complete with temporary enclosures, inside building. Permanent facilities may be used on approval of Owner's Representative.

1.9 TEMPORARY COMMUNICATION FACILITIES

- .1 Provide and pay for temporary telephone, fax, data hook up, lines and equipment necessary for own use and use of Owner's Representative.

1.10 REMOVAL OF TEMPORARY FACILITIES

- .1 Remove temporary facilities from site when directed by Owner's Representative.
- .2 When project is closed down at end of construction season keep temporary facilities operational until close down or removal is approved by Owner's Representative.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 51 00 – Temporary Utilities

Page 4 of 4

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 GENERAL

1.1 SECTION INCLUDES

- .1 Construction aids.
- .2 Office and sheds.
- .3 Parking.
- .4 Project identification.

1.2 RELATED SECTIONS

- .1 Section 01 35 29.06 – Health and Safety Requirements
- .2 Section 01 51 00 - Temporary Utilities.
- .3 Section 01 56 00 - Temporary Barriers and Enclosures.

1.3 INSTALLATION AND REMOVAL

- .1 Provide construction facilities in order to execute work expeditiously.
- .2 Remove from site all such work after use.

1.4 HOISTING

- .1 Provide, operate and maintain hoists cranes required for moving of workers, materials and equipment. Make financial arrangements with Subcontractors for use thereof.
- .2 Hoists cranes shall be operated by certified operator.

1.5 SITE STORAGE/LOADING

- .1 Confine work and operations of employees by Contract Documents. Do not unreasonably encumber premises with products.
- .2 Do not load or permit to load any part of Work with a weight or force that will endanger the Work.

1.6 CONSTRUCTION PARKING

- .1 Parking of private vehicles will not be permitted on site. Only vehicles required to carry out work will be permitted.
- .2 Provide and maintain adequate access to project site.

- .3 Build and maintain temporary roads where indicated or directed by Owner's Representative and provide snow removal during period of Work.
- .4 If authorized to use existing roads for access to project site, maintain such roads for duration of Contract and make good damage resulting from Contractor's use of roads.

1.7 CONTRACTOR'S SITE OFFICES

- .1 Provide office heated to 22 °C, lighted 750 lx and ventilated, of sufficient size to accommodate site meetings and furnished with drawing laydown table, fax machine, telephone, file cabinet and chair.
- .2 Provide a clearly marked and fully stocked first-aid case in a readily available location.
- .3 Subcontractors may provide their own offices as necessary. Direct location of these offices.

1.8 EQUIPMENT, TOOL AND MATERIALS STORAGE

- .1 Provide and maintain, in a clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
- .2 Locate materials not required to be stored in weatherproof sheds on site in a manner to cause least interference with work activities.

1.9 SANITARY FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take precautions as required by local health authorities. Keep area and premises in sanitary condition.

1.10 CLEAN-UP

- .1 Remove construction debris, waste materials, packaging material from work site daily.
- .2 Clean dirt or mud tracked onto paved or surfaced roadways.
- .3 Store materials resulting from demolition activities that are salvageable.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 52 00 – Construction Facilities

Page 3 of 3

PART 2 **PRODUCTS** (NOT APPLICABLE)

PART 3 **EXECUTION** (NOT APPLICABLE)

END OF SECTION

PART 1**GENERAL****1.1****SECTION INCLUDES**

- .1 Barriers.
- .2 Environmental Controls.
- .3 Traffic Controls.
- .4 Fire Routes.

1.2**RELATED SECTIONS**

- .1 Section 01 51 00 – Temporary Utilities.
- .2 Section 01 52 00 – Construction Facilities.

1.3**INSTALLATION AND REMOVAL**

- .1 Provide temporary controls in order to execute Work expeditiously.
- .2 Remove from site all such work after use.

1.4**HOARDING**

- .1 Provide safety orange PVC safety fencing around entire construction site area. Provide single entrance to site with secure gate for site security.
- .2 Provide barriers around trees and plants designated to remain. Protect from damage by equipment and construction procedures.

1.5**GUARD RAILS AND BARRICADES**

- .1 Provide secure, rigid guard rails and barricades around deep excavations, open shafts, open stair wells, open edges of floors and roofs.
- .2 Provide as required by governing authorities.

1.6**WEATHER ENCLOSURES**

- .1 Provide weather tight closures to unfinished concrete footings and walls.
- .2 Provide temporary heat for cold weather concrete work per applicable codes.
- .3 Erect enclosures to allow access for installation of materials and working inside enclosure.

- .4 Design enclosures to withstand wind pressure and snow loading.

1.7 ACCESS TO SITE

- .1 Provide and maintain access roads, sidewalk crossings, ramps and construction runways as may be required for access to Work.
- .2 Build and maintain temporary roads where indicated or directed and provide snow removal during period of work.
- .3 If authorized to use existing roads for access to project site, maintain such roads for duration of Contract and make good damage resulting from Contractor's use of roads.

1.8 PUBLIC TRAFFIC FLOW

- .1 Provide and maintain competent signal flag operators, traffic signals, barricades and flares, lights, or lanterns as required to perform Work and protect the public.

1.9 FIRE ROUTES

- .1 Maintain access to property including overhead clearances for use by emergency response vehicles.

1.10 PROTECTION FOR OFF-SITE AND PUBLIC PROPERTY

- .1 Protect surrounding private and public property from damage during performance of Work.
- .2 Be responsible for damage incurred.

1.11 PROTECTION OF BUILDING FINISHES

- .1 Provide protection for finished and partially finished building finishes and equipment during performance of Work.
- .2 Provide necessary screens, covers, and hoardings.
- .3 Confirm with Owner's Representative locations and installation schedule 3 days prior to installation.
- .4 Be responsible for damage incurred due to lack of or improper protection.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Requirements and limitations for cutting and patching the Work.

1.2 **RELATED SECTIONS**

- .1 Section 01 11 00 - Summary of Work.
- .2 Section 01 33 00 - Submittal Procedures.

1.3 **SUBMITTALS**

- .1 Submit written request in advance of cutting or alteration which affects:
 - .1 Structural integrity of any element of Project.
 - .2 Integrity of weather-exposed or moisture-resistant elements.
 - .3 Efficiency, maintenance, or safety of any operational element.
 - .4 Visual qualities of sight-exposed elements.
 - .5 Work of Owner or separate contractor.
- .2 Include in request:
 - .1 Identification of Project.
 - .2 Location and description of affected Work.
 - .3 Statement on necessity for cutting or alteration.
 - .4 Description of proposed Work, and products to be used.
 - .5 Alternatives to cutting and patching.
 - .6 Effect on Work of Owner or separate contractor.
 - .7 Written permission of affected separate contractor.
 - .8 Date and time work will be executed.

1.4 **PREPARATION**

- .1 Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
- .2 After uncovering, inspect conditions affecting performance of Work.
- .3 Beginning of cutting or patching means acceptance of existing conditions.
- .4 Provide supports to assure structural integrity of surroundings; provide devices and methods to protect other portions of project from damage.
- .5 Provide protection from elements for areas which may be exposed by uncovering work; maintain excavations free of water.

- .6 Obtain Owner's Representative's approval before cutting, boring or sleeving load-bearing members.

1.5 EXECUTION

- .1 Execute cutting, fitting, and patching including excavation and fill, to complete Work.
- .2 Fit several parts together, to integrate with other Work.
- .3 Uncover Work to install ill-timed Work.
- .4 Remove and replace defective and non-conforming Work.
- .5 Provide openings in non-structural elements of Work for penetrations of mechanical and electrical Work.
- .6 Execute Work by methods to avoid damage to other Work, and which will provide proper surfaces to receive patching and finishing.
- .7 Employ original installer to perform cutting and patching for weather-exposed and moisture-resistant elements, and sight-exposed surfaces.
- .8 Cut rigid materials using masonry saw or core drill. Pneumatic or impact tools not allowed on masonry work without prior approval.
- .9 Restore work with new products in accordance with requirements of Contract Documents.
- .10 Fit Work to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- .11 At penetration of fire rated wall, ceiling, or floor construction, completely seal voids with firestopping material in accordance with Section 07 84 00 - Firestopping, full thickness of the construction element.
- .12 Refinish surfaces to match adjacent finishes: For continuous surfaces refinish to nearest intersection; for an assembly, refinish entire unit.
- .13 Conceal pipes, ducts and wiring in floor, wall and ceiling construction of finished areas except where indicated otherwise.
- .14 Make cuts with clean, true, smooth edges.
- .15 Where new work connects with existing, and where existing work is altered, cut, patch and make good to match existing work.

1.6 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials in accordance with Section 01 74 21 – Construction/Demolition Waste Management and Disposal.

PART 2 **PRODUCTS** (NOT APPLICABLE)

PART 3 **EXECUTION** (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **GENERAL**

- .1 Conduct cleaning and disposal operations to comply with local ordinances and anti-pollution laws.
- .2 Store volatile waste in covered metal containers and remove from premises at end of each working day.
- .3 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.

1.2 **RELATED SECTION**

- .1 Section 01 77 00 - Closeout Procedures.

1.3 **PROJECT CLEANLINESS**

- .1 Maintain Work in tidy condition, free from accumulation of waste products and debris, other than that caused by Owner or other Contractors.
- .2 Remove waste materials and debris from site at the end of each working day. Do not burn waste materials on site.
- .3 Clear snow and ice from access to building.
- .4 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .5 Provide on-site containers for collection of waste materials and debris.
- .6 Clean interior areas prior to start of finish work, maintain areas free of dust and other contaminants during finishing operations.
- .7 Store volatile waste in covered metal containers, and remove from premises at end of each working day.
- .8 Provide adequate ventilation during use of volatile or noxious substances. Use of building ventilation systems is not permitted for this purpose.
- .9 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.
- .10 Schedule cleaning operations so that resulting dust, debris and other contaminants will not fall on wet, newly painted surfaces nor contaminate building systems.

1.4 FINAL CLEANING

- .1 Refer to General Conditions.
- .2 When Work is Substantially Performed, remove surplus products, tools, construction machinery and equipment not required for performance of remaining Work.
- .3 Remove waste products and debris other than that caused by others, and leave Work clean and suitable for occupancy.
- .4 When the Work is Totally Performed, remove surplus products, tools, construction machinery and equipment. Remove waste products and debris other than that caused by the Owner or other Contractors.
- .5 Remove waste materials from the site at regularly scheduled times or dispose of as directed by the Owner's Representative. Do not burn waste materials on site.
- .6 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .7 Remove dirt and other disfiguration from exterior surfaces.
- .8 Clean and sweep roofs.
- .9 Sweep and wash clean paved areas.
- .10 Remove snow and ice from access to building.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Text, schedules and procedures for systematic Waste Management Program for construction, deconstruction, demolition, and renovation projects, including:
 - .1 Diversion of Materials.
 - .2 Waste Audit (WA) - Schedule A.
 - .3 Waste Reduction Workplan (WRW) - Schedule B.
 - .4 Demolition Waste Audit (DWA) - Schedule C.
 - .5 Cost/Revenue Analysis Workplan (CRAW) - Schedule D.
 - .6 Materials Source Separation Program (MSSP).
 - .7 Canadian Governmental Responsibility for the Environment Resources - Schedule E.

1.2 **DEFINITIONS**

- .1 Demolition Waste Audit (DWA): Relates to actual waste generated from project.
- .2 Materials Source Separation Program (MSSP): Consists of series of ongoing activities to separate reusable and recyclable waste material into material categories from other types of waste at point of generation.
- .3 Recyclable: Ability of product or material to be recovered at end of its life cycle and re-manufactured into new product for reuse by others.
- .4 Recycle: Process by which waste and recyclable materials are transformed or collected for purpose of being transferred into new products.
- .5 Recycling: Process of sorting, cleansing, treating and reconstituting solid waste and other discarded materials for purpose of using in altered form. Recycling does not include burning, incinerating, or thermally destroying waste.
- .6 Reuse: Repeated use of product in same form but not necessarily for same purpose. Reuse includes:
 - .1 Salvaging reusable materials from re-modelling projects, before demolition stage, for resale, reuse on current project or for storage for use on future projects.
 - .2 Returning reusable items including pallets or unused products to vendors.
- .7 Salvage: Removal of structural and non-structural materials from deconstruction/disassembly projects for purpose of reuse or recycling.
- .8 Separate Condition: Refers to waste sorted into individual types.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

- .9 Source Separation: Acts of keeping different types of waste materials separate beginning from first time they became waste.

1.3 MATERIALS SOURCE SEPARATION PROGRAM (MSSP)

- .1 Prepare MSSP and have ready for use prior to project start-up.
- .2 Implement MSSP for waste generated on project in compliance with approved methods and as reviewed by authorities having jurisdiction.
- .3 Provide on-site facilities for collection, handling, and storage of anticipated quantities of reusable and recyclable materials.
- .4 Provide containers to deposit reusable and recyclable materials.
- .5 Locate containers in locations, to facilitate deposit of materials without hindering daily operations.
- .6 Locate separated materials in areas which minimize material damage.
- .7 Collect, handle, store on-site, and transport off-site, salvaged materials in separate condition.
 - .1 Transport to recycling facility.

1.4 STORAGE, HANDLING AND PROTECTION

- .1 Unless specified otherwise, materials for removal become Contractor's property.
- .2 Protect, stockpile, store and catalogue salvaged items.
- .3 Separate non-salvageable materials from salvaged items. Transport and deliver non-salvageable items to approved local facility.
- .4 Protect structural components not removed for demolition from movement or damage.
- .5 Support affected structures. If safety of building is endangered, cease operations and immediately notify Department having jurisdiction.
- .6 Protect surface drainage, mechanical and electrical from damage and blockage.
- .7 Separate and store materials produced during dismantling of structures in designated areas.
- .8 Prevent contamination of materials to be salvaged and recycled and handle materials in accordance with requirements for acceptance by designated facilities.
 - .1 On-site source separation is recommended.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016 Section 01 74 21 – Construction/Demolition Waste Management and Disposal Page 3 of 4

1.5 DISPOSAL OF WASTES

- .1 Do not bury rubbish or waste materials.
- .2 Do not dispose of any waste into waterways, storm, or sanitary sewers.
- .3 Remove materials from deconstruction as deconstruction/disassembly Work progresses.
- .4 Prepare project summary to verify destination and quantities on a material-by-material basis as identified in pre-demolition material audit.

1.6 USE OF SITE AND FACILITIES

- .1 Execute work with least possible interference or disturbance to normal use of premises.
- .2 Provide security measures approved by Owner's Representative.

1.7 SCHEDULING

- .1 Coordinate Work with other activities at site to ensure timely and orderly progress of Work.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION

3.1 APPLICATION

- .1 Handle waste materials not reused, salvaged, or recycled in accordance with appropriate regulations and codes.

3.2 CLEANING

- .1 Remove tools and waste materials on completion of Work, and leave work area in clean and orderly condition.
- .2 Clean-up work area as work progresses.
- .3 Source separate materials to be reused/recycled into specified sort areas.

3.3 DIVERSION OF MATERIALS

- .1 From following list, separate materials from general waste stream and stockpile in separate piles or containers, as reviewed by Owner's Representative and consistent with applicable fire regulations.
 - .1 Mark containers or stockpile areas.

Gros Morne National Park

Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016 Section 01 74 21 – Construction/Demolition Waste Management and Disposal Page 4 of 4

- .2 Provide instruction on disposal practices.
- .2 On-site sale or distribution of salvaged materials to third parties is not permitted.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 74 11 - Cleaning.
- .2 Section 01 78 00 - Closeout Submittals.

1.2 **FINAL INSPECTION AND DECLARATION PROCEDURES**

- .1 Contractor's Inspection: The Contractor and all Subcontractors shall conduct an inspection of Work, identify deficiencies and defects; repair as required. Notify the Owner's Representative in writing of satisfactory completion of the Contractor's Inspection and that corrections have been made. Request an Owner's Representative's Consultant's Inspection.
- .2 Owner's Representative's Inspection: Owner's Representative and the Contractor will perform an inspection of the Work to identify obvious defects or deficiencies. The contractor shall correct Work accordingly.
- .3 Completion: submit written certificate that the following have been performed:
 - .1 Work has been completed and inspected for compliance with Contract Documents.
 - .2 Defects have been corrected and deficiencies have been completed.
 - .3 Equipment and systems have been tested, adjusted and balanced and are fully operational.
 - .4 Certificates required by Fire Commissioner, Utility companies have been submitted.
 - .5 Operation of systems have been demonstrated to Owner's personnel.
 - .6 Work is complete and ready for Final Inspection.
- .4 Final Inspection: When items noted above are completed, request final inspection of Work by the Owner's Representative, representative of DMIA and the Contractor. If Work is deemed incomplete by the Owner's Representative, complete outstanding items and request a reinspection.
- .5 Declaration of Substantial Performance: When the Owner's Representative considers deficiencies and defects have been corrected and it appears requirements of Contract have been substantially performed, make application for Certificate of Substantial Performance. Refer to General Conditions for specifics to application.
- .6 Commencement of Lien and Warranty Periods: The date of DMIA acceptance of the submitted declaration of Substantial Performance shall be the date for commencement for the warranty period and commencement of the lien period.
- .7 Declaration of Total Performance: When the Owner's Representative considers final deficiencies and defects have been corrected and it appears requirements of the Contract

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016

Section 01 77 00 – Closeout Procedures

Page 2 of 2

have been totally performed, make application for certificate of Total Performance. Refer to General Conditions for specifics to application. If Work is deemed incomplete by the Consultant, complete the outstanding items and request a reinspection.

1.3 REINSPECTION

- .1 Should status of work require reinspection by Owner's Representative due to failure of work to comply with Contractor's claims for inspection, Owner will deduct amount of compensation for reinspection services from payment to Contractor.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 As-built, samples, and specifications.
- .2 Product data, materials and finishes, and related information.
- .3 Warranties and bonds.
- .4 Final site survey.

1.2 **RELATED SECTIONS**

- .1 Section 01 33 00 – Submittal Procedures.
- .2 Section 01 45 00- Quality Control.
- .3 Section 01 71 00 – Examination and Preparation.
- .4 Section 01 77 00 - Closeout Procedures.

1.3 **SUBMISSION**

- .1 Prepare instructions and data using personnel experienced in maintenance and operation of described products.
- .2 Submit one copy of completed volumes in final form 15 days prior to final inspection.
- .3 Copy will be returned after final inspection, with Owner's Representative's comments.
- .4 Revise content of documents as required prior to final submittal.
- .5 Two weeks prior to Substantial Performance of the Work, submit to the Owner's Representative, two final copies of operating and maintenance manuals.
- .6 Ensure spare parts, maintenance materials and special tools provided are new, undamaged or defective, and of same quality and manufacture as products provided in Work.
- .7 If requested, furnish evidence as to type, source and quality of products provided.
- .8 Defective products will be rejected, regardless of previous inspections. Replace products at own expense.
- .9 Pay costs of transportation.

1.4 FORMAT

- .1 Organize data in the form of an instructional manual.
- .2 Binders: vinyl, hard covered, 3 'D' ring, loose leaf 219 x 279 mm with spine and face pockets.
- .3 When multiple binders are used, correlate data into related consistent groupings. Identify contents of each binder on spine.
- .4 Cover: Identify each binder with type or printed title 'Project Record Documents'; list title of project and identify subject matter of contents.
- .5 Arrange content under Section numbers and sequence of Table of Contents.
- .6 Provide tabbed fly leaf for each separate product and system, with typed description of product and major component parts of equipment.
- .7 Text: Manufacturer's printed data, or typewritten data.
- .8 Drawings: provide with reinforced punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- .9 Provide CAD files in DWG format on CD. Also provide electronic files in PDF format.

1.5 CONTENTS - EACH VOLUME

- .1 Table of Contents: provide title of project; names, addresses, and telephone numbers of Consultant and Contractor with name of responsible parties; schedule of products and systems, indexed to content of volume.
- .2 For each product or system:
 - .1 List names, addresses and telephone numbers of subcontractors and suppliers, including local source of supplies and replacement parts.
- .3 Product Data: mark each sheet to clearly identify specific products and component parts, and data applicable to installation; delete inapplicable information.
- .4 Drawings: supplement product data to illustrate relations of component parts of equipment and systems, to show control and flow diagrams.
- .5 Typewritten Text: as required to supplement product data. Provide logical sequence of instructions for each procedure, incorporating manufacturer's instructions specified in Section 01 45 00 - Quality Control.
- .6 Training: Refer to Section 01 91 13 – General Commissioning (Cx) Requirements.

1.6 AS-BUILTS AND SAMPLES

- .1 In addition to requirements in General Conditions, maintain at the site for Owner's Representative one record copy of:

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 01 78 00 – Closeout Submittals

Page 3 of 4

- .1 Contract Drawings.
 - .2 Specifications.
 - .3 Addenda.
 - .4 Change Orders and other modifications to the Contract.
 - .5 Reviewed shop drawings, product data, and samples.
 - .6 Field test records.
 - .7 Inspection certificates.
 - .8 Manufacturer's certificates.
- .2 Store record documents and samples in field office apart from documents used for construction. Provide files, racks, and secure storage.
 - .3 Label record documents and file in accordance with Section number listings in List of Contents of this Project Manual. Label each document "PROJECT RECORD" in neat, large, printed letters.
 - .4 Maintain record documents in clean, dry and legible condition. Do not use record documents for construction purposes.
 - .5 Keep record documents and samples available for inspection by Owner's Representative.

1.7 RECORDING ACTUAL SITE CONDITIONS

- .1 Record information on set of blue line opaque drawings, provided by Owner's Representative.
- .2 Provide felt tip marking pens, maintaining red color pens for recording information.
- .3 Record information concurrently with construction progress. Do not conceal Work until required information is recorded.
- .4 Contract Drawings and shop drawings: legibly mark each item to record actual construction, including:
 - .1 Measured depths of elements of foundation in relation to finish first floor datum.
 - .2 Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
 - .3 Measured locations of internal utilities and appurtenances, referenced to visible and accessible features of construction.
 - .4 Field changes of dimension and detail.
 - .5 Changes made by change orders.
 - .6 Details not on original Contract Drawings.
 - .7 References to related shop drawings and modifications.
- .5 Specifications: legibly mark each item to record actual construction, including:
 - .1 Manufacturer, trade name, and catalogue number of each product actually installed, particularly optional items and substitute items.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016

Section 01 78 00 – Closeout Submittals

Page 4 of 4

- .2 Changes made by Addenda and change orders.
 - .6 Other Documents: submit manufacturer's certifications, inspection certifications, field test records, required by individual specifications sections.
 - .7 At completion of project provide all recorded information on print drawings or alternatively transfer to CAD files in DWG format. Submit DWG files, also with electronic files in PDF format as part of the Closeout Submittals..
- 1.8 FINAL SURVEY**
- .1 Submit final site survey certificate certifying that elevations and locations of completed Work are in conformance, or non-conformance with Contract Documents.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION (NOT APPLICABLE)

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTIONS INCLUDES**

- .1 Methods and procedures for demolishing, salvaging, recycling and removing sitework items designated to be removed in whole or in part, and for backfilling resulting trenches and excavations.

1.2 **RELATED SECTIONS**

- .1 Section 01 33 00 – Submittal Procedures
- .2 Section 01 35 29.06 - Health and Safety Requirements
- .3 Section 01 35 43 - Environmental Procedures
- .4 Section 01 45 00 - Quality Control
- .5 Section 01 74 19 – Construction/Demolition Waste Management and Disposal.
- .6 Section 31 23 33.01 – Excavating, Trenching and Backfilling.

1.3 **SUBMITTALS**

- .1 Submit plan indicating:
 - .1 Descriptions of and anticipated quantities of materials to be salvaged, reused, recycled and landfilled.
 - .2 Schedule of selective demolition.
 - .3 Number and location of dumpsters.
 - .4 Anticipated frequency of tippage.
- .2 Submit copies of certified weigh bills, bills of landing from authorized disposal sites and reuse and recycling facilities for material removed from upon request from Owner's Representative.

1.4 **QUALITY ASSURANCE**

- .1 Convene pre-installation meeting one week prior to beginning work of this section to:
 - .1 Verify project requirements.
 - .2 Review installation and substrate conditions.
 - .3 Co-ordination with building subtrades.
- .2 Arrange for site visit with Owner's Representative to examine existing site conditions adjacent to demolition work, prior to start of Work.
- .3 Hold project meetings every month.

- .1 Ensure key personnel, site supervisor, project manager, subcontractor representatives attend.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Protect existing items designated to remain and items designated for salvage. In event of damage to such items, immediately replace or make repairs to approval of Owner's Representative and at no cost to Owner's Representative.
- .2 Remove and store materials to be salvaged, in manner to prevent damage.
- .3 Store and protect in accordance with requirements for maximum preservation of material.

1.6 SITE CONDITIONS

- .1 In all circumstances ensure that demolition work does not adversely affect adjacent water courses groundwater and wildlife, or contribute to excess air and noise pollution.
- .2 Do not dispose, of waste or volatile materials such as mineral spirits, oil, petroleum based lubricants, or toxic cleaning solutions into watercourses, storm or sanitary sewers. Ensure proper disposal procedures are maintained throughout project.
- .3 Do not pump water containing suspended materials into watercourses, storm or sanitary sewers, or onto adjacent properties.
- .4 Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authorities.
- .5 Protect trees, plants and foliage on site and adjacent properties where indicated.

1.7 EXISTING CONDITIONS

- .1 Prior to start of any demolition work remove contaminated or hazardous materials as defined by authorities having jurisdiction from site and dispose of at designated disposal facilities

1.8 SCHEDULING

- .1 Employ necessary means to meet project time lines without compromising specified minimum rates of material diversion.
- .2 Notify Owner's Representative in writing when unforeseen delays occur.

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION**

3.1 **PREPARATION**

- .1 Inspect site with Owner's Representative and verify extent and location of items designated for removal, disposal, alternative disposal, recycling, salvage and items to remain.
- .2 Locate and protect utilities. Preserve active utilities traversing site in operating condition.
- .3 Notify and obtain approval of utility companies before starting demolition.

3.2 **REMOVAL OPERATIONS**

- .1 Remove items as indicated.
- .2 Do not disturb items designated to remain in place.
- .3 Removal of Pavements, Curbs and Gutters
 - .1 Square up adjacent surfaces to remain in place by saw cutting or other method approved by Owner's Representative.
 - .2 Protect adjacent joints and load transfer devices.
 - .3 Protect underlying and adjacent granular material.
- .4 When removing asphalt pavement for subsequent incorporation into hot mix asphalt concrete paving, prevent contamination with base course aggregates.
- .5 When removing pipes under existing or future pavement area, excavate at least 300mm below pipe invert.
- .6 Decommission water wells and monitoring wells in accordance with Provincial guidelines and regulations.
- .7 Removal from site
 - .1 Interim removal of stockpiled material will be required by Owner's Representative, if it is deemed to interfere with operations of Owner's Representative, Owner or other contractors.
- .8 Sealing
 - .1 Seal pipe ends and walls of manholes or catch basins as indicated. Securely plug to form watertight seal.
- .9 Backfill
 - .1 Backfill in areas as indicated

3.3 RESTORATION

- .1 Restore areas and existing works outside areas of demolition to match conditions of adjacent, undisturbed areas.
- .2 Use soil treatments and procedures which are not harmful to health, are not injurious to plants, and do not endanger wildlife, adjacent water courses or ground water.

3.4 CLEAN UP

- .1 Upon completion of work, remove debris, trim surfaces and leave work site clean.
- .2 Use cleaning solutions and procedures which are not harmful to health, are not injurious to plants, and do not endanger wildlife, adjacent water courses or ground water.

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Methods and procedures for demolition of structures, parts of structures, basements and foundation walls and includes abandonment and removal of septic tanks and tanks containing petroleum products.

1.2 **RELATED SECTIONS**

- .1 Section 01 11 00 – Summary of Work
- .2 Section 01 35 29.06 - Health and Safety Requirements
- .3 Section 01 35 43 - Environmental Procedures
- .4 Section 01 52 00 – Construction Facilities
- .5 Section 01 56 00 - Temporary Barriers and Enclosures
- .6 Section 01 74 21 – Construction/Demolition Waste Management and Disposal

1.3 **REFERENCES**

- .1 Canadian Standards Association (CSA).
 - .1 CSA S350, Code of Practice for Safety in Demolition of Structures

1.4 **QUALITY ASSURANCE**

- .1 Prior to start of Work arrange for site visit with Owner’s Representative to examine existing site conditions adjacent to demolition work
- .2 Hold project meetings every month.
- .3 Ensure key personnel, site supervisor, project manager, subcontractor representatives, attend.

1.5 **WASTE MANAGEMENT AND DISPOSAL**

- .1 Separate waste materials in accordance with Section 01 74 21 – Construction/Demolition Waste Management and Disposal.

1.6 **EXISTING CONDITIONS**

- .1 Should material resembling spray or trowel applied asbestos or any other designated substance be encountered in course of demolition, stop work, take preventative measures, and notify Owner’s Representative immediately. Do not proceed until written instructions have been received.

- .2 Structures to be demolished to be based on their condition on date that tender is accepted.
- .3 Salvage items as identified by Owner's Representative. Remove, protect and store salvaged items as directed by Owner's Representative. Deliver to Owner as directed.

1.7 DEMOLITION DRAWINGS

- .1 Where required by authorities having jurisdiction, submit for approval drawings, diagrams or details showing sequence of demolition work and supporting structures and underpinning.
- .2 Submit drawings stamped and signed by qualified professional engineer licensed in Province of Newfoundland and Labrador, Canada.

1.8 ENVIRONMENTAL PROTECTION

- .1 Ensure work is done in accordance with Section 01 35 43 – Environmental Procedures.
- .2 Prevent movement, settlement or damage of adjacent structures, services, walks, paving, trees, landscaping, adjacent grades parts of existing building to remain.
- .3 Support affected structures and, if safety of structure being demolished or adjacent structures or services appears to be endangered cease operations and notify Owner's Representative.
- .4 Prevent debris from blocking surface drainage system, elevators, mechanical and electrical systems which must remain in operation.
- .5 Ensure that demolition work does not adversely affect adjacent watercourses, groundwater and wildlife, or contribute to excess air and noise pollution.
- .6 Fires and burning of waste or materials is not permitted on site.
- .7 Do not bury waste or materials on site.
- .8 Do not dispose of waste or volatile materials such as mineral spirits, oil, petroleum based lubricants, or toxic cleaning solutions into watercourses, storm or sanitary sewers. Ensure proper disposal procedures are maintained throughout project.
- .9 Do not pump water containing suspended materials into watercourses, storm or sanitary sewers, or onto adjacent properties.
- .10 Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authorities' requirements.
- .11 Protect trees, plants and foliage on site and adjacent properties where indicated.

- .12 Prevent extraneous materials from contaminating air beyond application area, by providing temporary enclosures during demolition work.
- .13 Cover or wet down dry materials and waste to prevent blowing dust and debris. Control dust on all temporary roads.

1.9 SCHEDULING

- .1 Ensure project time lines are met without compromising specified minimum rates of material diversion. Notify Owner's Representative in writing of delays.

PART 2 PRODUCTS (NOT APPLICABLE)

PART 3 EXECUTION

3.1 PREPARATION

- .1 Do work in accordance with 01 35 29.06 – Health and Safety Requirements.
- .2 Disconnect electrical and telephone service lines entering buildings to be demolished. Post warning signs on electrical lines and equipment which must remain energized to serve other properties during period of demolition.
- .3 Disconnect and cap designated mechanical services.
 - .1 Sewer and water lines: remove to property line.
 - .2 Other underground services: remove and dispose of as directed by Owner's Representative.
- .4 Do not disrupt active or energized utilities designated to remain undisturbed.
- .5 Remove rodent and vermin as required by Owner's Representative.

3.2 SAFETY CODE

- .1 Do demolition work in accordance with Section 01 56 00 – Temporary Barriers and Enclosures.
- .2 Blasting operations not permitted during demolition.

3.3 DEMOLITION

- .1 Demolish foundation walls to minimum of 300mm below finished grade.
- .2 Demolish foundation walls and footings, and concrete floors below or on grade.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 02 41 16 - Structure Demolition

Page 4 of 6

- .3 Break 100mm holes per 10m² area in concrete slabs which are not to be removed, to prevent accumulation of water. Keep floor drains open if permanent drainage still connected.
- .4 Pieces of concrete and masonry not larger than 200 mm broken from demolition work may be used as backfill in open basements on excavations provided voids are filled. Keep demolition fill 300 mm below finished grade level. Do not backfill basement areas until inspected by Owner's Representative.
- .5 Remove existing equipment, services, and obstacles where required for refinishing or making good of existing surfaces, and replace as work progresses.
- .6 At end of each day's work, leave Work in safe and stable condition. Protect interiors of parts not to be demolished from exterior elements at all times.
- .7 Demolish to minimize dusting. Keep materials wetted as directed by Owner's Representative.
- .8 Remove structural framing.
- .9 Contain all fibrous materials (e.g. Insulation) to minimize release of airborne fiber while being transported to waste disposal site or alternative disposal location.
- .10 Only dispose of material specified by selected alternative disposal option as directed by Owner's Representative.
- .11 Ensure that these materials will not be disposed of in landfill or waste stream destined for landfill.
- .12 Remove and dispose of demolished materials except where noted otherwise and in accordance with authorities having jurisdiction.
- .13 Environmental:
 - .1 Remove contaminated or dangerous materials as defined by authorities having jurisdiction, relating to environmental protection, from site and dispose of in safe manner to minimized danger at site or during disposal.
 - .2 Septic Tanks:
 - .1 Pump out buried septic tanks, left in place. Fill with sand.
 - .2 Remove tanks within area of new construction or under paved areas and slabs.
- .14 Prior to the start of any demolition work remove contaminated or hazardous materials as defined by authorities having jurisdiction, from site and dispose of at designated disposal facilities.
- .15 Prior to the start of any demolition work remove underground storage tanks and piping as directed.

- .16 Use natural lighting to work by wherever possible. Shut off all lighting except those required for security purposes at the end of each day.

3.4 STOCKPILING

- .1 Stockpile materials in a location as directed by Owner's Representative.
- .2 Designate appropriate security resources/measures to prevent vandalism, damage and theft.
- .3 Separate from general waste stream each of the following materials. Stockpile materials in neat and orderly fashion in location and as directed by Owner's Representative for alternate disposal. Stockpile materials in accordance with applicable fire regulations.
 - .1 Glass fiber ceiling tiles.
 - .2 Wood fiber ceiling tiles.
 - .3 Power source poles deemed unfit for reuse by Owner's Representative.
 - .4 Wiring and conduit.
 - .5 Outlets/Switches
 - .6 Floor receptacles.
 - .7 Metal duct work, baffles, HVAC equipment.
 - .8 Demountable partitions.
 - .9 Drapes.
 - .10 Tracks and blinds.
 - .11 Insulation batts.
 - .12 Miscellaneous metals.
 - .13 Carpet.
- .4 Supply separate, clearly-marked disposal bins for all categories of waste material. Do not remove bins from site until inspected and approved by Owner's Representative.
- .5 Provide collection areas for collection of miscellaneous metals in the area of demolition.

3.5 REMOVAL FROM SITE

- .1 Notify Owner's Representative in writing of any materials identified as not suitable for alternate disposal. Provide reasons prior to approval for disposal.
- .2 Dispose of materials as directed by Owner's Representative.
- .3 Remove stockpiled material as directed by Owner's Representative when it interferes with operations of project construction.
- .4 Remove stockpiles of like materials by an alternate disposal option once collection of materials is complete.

- .5 Transport material designated for alternate disposal in accordance with applicable regulations.
- .6 Dispose of materials not designated for alternate disposal in accordance with applicable regulations.

3.6 REPORTING

- .1 Record off-site removal of debris and materials and provide following information regarding removed materials to Owner's Representative within 24 hours.
 - .1 Time and date of Removal
 - .2 Description of Material
 - .3 Weight and Quantity of Materials.
 - .4 Breakdown of reuse, recycling and landfill quantities.
 - .5 End Demolition of Materials.

3.7 COORDINATION

- .1 Coordinate alternative disposal activities with Owner's Representative's on site waste diversion representative.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 03 20 00 - Concrete Reinforcing.
- .2 Section 03 30 00 - Cast-in-place Concrete.

1.2 **REFERENCES**

- .1 Canadian Standards Association (CSA)
 - .1 CAN/CSA-A23.1/A23.2, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.
 - .2 CSA-O86S1, Supplement No. 1 to CAN/CSA-O86-01, Engineering Design in Wood.
 - .3 CSA O121, Douglas Fir Plywood.
 - .4 CSA O151, Canadian Softwood Plywood.
 - .5 CSA S269.1, Falsework for Construction Purposes.
 - .6 CAN/CSA-S269.3, Concrete Formwork.

1.3 **SUBMITTALS**

- .1 Indicate method and schedule of construction, shoring, stripping and re-shoring procedures, materials, arrangement of joints, special architectural exposed finishes, ties, liners, and locations of temporary embedded parts. Comply with CSA S269.1, for falsework drawings. Comply with CAN/CSA-S269.3, for formwork drawings.
- .2 Indicate formwork design data, such as permissible rate of concrete placement, and temperature of concrete, in forms.
- .3 Indicate sequence of erection and removal of formwork/falsework as directed by Owner's Representative.
- .4 Each shop drawing submission shall bear stamp and signature of qualified professional engineer licensed in Province of Newfoundland and Labrador, Canada.

PART 2 **PRODUCTS**

2.1 **MATERIALS**

- .1 Formwork materials:
 - .1 For concrete without special architectural features, use wood and wood product formwork materials to CSA-O121.

- .2 For concrete with special architectural features, use formwork materials to CSA-A23.1/A23.2.
- .2 Tubular column forms: round, spirally wound laminated fiber forms, internally treated with release material. Spiral pattern to show in hardened concrete.
- .3 Form ties:
 - .1 For concrete not designated 'Architectural', use removable or snap-off metal ties, fixed or adjustable length, free of devices leaving holes larger than 25 mm dia. in concrete surface.
 - .2 For Architectural concrete, use snap ties complete with plastic cones and light grey concrete plugs.
- .4 Form liner:
 - .1 Plywood: medium density overlay Douglas Fir to CSA O121, Canadian Softwood Plywood to CSA O151, T and G thickness as indicated.
- .5 Form release agent: chemically active release agents containing compounds that react with free lime in concrete resulting in water insoluble soaps, non-toxic, biodegradable.
- .6 Falsework materials: to CSA-S269.1.
- .7 Sealant: to Section 07 92 10 - Joint Sealing.
- .8 Form stripping agent: Colourless mineral oil, biodegradable, free of kerosene, with viscosity between 70 and 110s Saybolt Universal 15 to 24 mm²/s at 40 degrees C, flashpoint minimum 150 degrees C, open cup.

PART 3 **EXECUTION**

3.1 **FABRICATION AND ERECTION**

- .1 Verify lines, levels and centres before proceeding with formwork/falsework and ensure dimensions agree with drawings.
- .2 Obtain Owner's Representative's approval for use of earth forms framing openings not indicated on drawings.
- .3 Hand trim sides and bottoms and remove loose earth from earth forms before placing concrete.
- .4 Fabricate and erect falsework in accordance with CSA S269.1 and COFI Exterior Plywood for Concrete Formwork.
- .5 Refer to architectural drawings for concrete members requiring architectural exposed finishes.
- .6 Do not place shores and mud sills on frozen ground.

- .7 Provide site drainage to prevent washout of soil supporting mud sills and shores.
- .8 Fabricate and erect formwork in accordance with CAN/CSA-S269.3 to produce finished concrete conforming to shape, dimensions, locations and levels indicated within tolerances required by CAN/CSA-A23.1.
- .9 Align form joints and make watertight. Keep form joints to minimum.
- .10 Locate horizontal form joints for exposed columns 2400 mm above finished floor elevation.
- .11 Use 25 mm chamfer strips on external corners and/or 25 mm fillets at interior corners, joints, unless specified otherwise.
- .12 Form chases, slots, openings, drips, recesses, expansion and control joints as indicated.
- .13 Construct forms for architectural concrete, and place ties as indicated and/or as directed. Joint pattern not necessarily based on using standard size panels or maximum permissible spacing of ties.
- .14 Build in anchors, sleeves, and other inserts required to accommodate Work specified in other sections. Assure that anchors and inserts will not protrude beyond surfaces designated to receive applied finishes, including painting.
- .15 Line forms for following surfaces:
 - .1 Outer face of outside and vertical edge of bridge sidewalk slab.
 - .2 Soffit of girders and underside of bridge decks if exposed.
 - .3 Exposed faces of abutments, wingwalls, piers and pylons: Do not stagger joints of form lining material. Align joints to obtain uniform pattern.
- .16 Clean formwork in accordance with CAN/CSA-A23.1, before placing concrete.
- .17 If flying forms are used, submit details of equipment and procedures for Owner's Representative's approval.

3.2 REMOVAL AND RESHORING

- .1 Leave formwork in place for following minimum periods of time after placing concrete.
 - .1 3 days for walls and sides of beams.
 - .2 3 days for columns.
 - .3 7 days for beam soffits, slabs, decks and other structural members, or days when replaced immediately with adequate shoring to standard specified for falsework.
 - .4 5 days for footings and abutments.
- .2 Remove formwork when concrete has reached 80% of its design strength or minimum period noted above, whichever comes later, and replace immediately with adequate reshoring.

- .3 Provide necessary reshoring of members where early removal of forms may be required or where members may be subjected to additional loads during construction as required.
- .4 Space reshoring in each principal direction at not more than 3000 mm apart.
- .5 Re-use formwork and falsework subject to requirements of CAN/CSA-A23.1.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 03 10 00 – Concrete Forming and Accessories.
- .2 Section 03 30 00 - Cast-in-Place Concrete.

1.2 REFERENCES

- .1 American Concrete Institute (ACI)
 - .1 ACI 315R-80, Manual of Engineering and Placing Drawings for Reinforced Concrete Structure.
- .2 American National Standards Institute/American Concrete Institute (ANSI/ACI)
 - .1 ANSI/ACI 315-80, Details and Detailing of Concrete Reinforcement.
- .3 American Society for Testing and Materials (ASTM)
 - .1 ASTM A 775/A 775M-91c, Specification for Epoxy-Coated Reinforcing Steel Bars.
- .4 Canadian Standards Association (CSA)
 - .1 CAN/CSA-A23.1-94, Concrete Materials and Methods of Concrete Construction.
 - .2 CAN3-A23.3-94, Design of Concrete Structures for Buildings.
 - .3 CSA G30.3-M1983(R1991), Cold Drawn Steel Wire for Concrete Reinforcement.
 - .4 CSA G30.5-M1983(R1991), Welded Steel Wire Fabric for Concrete Reinforcement.
 - .5 CSA G30.14-M1983(R1991), Deformed Steel Wire for Concrete Reinforcement.
 - .6 CSA G30.15-M1983(R1991), Welded Deformed Steel Wire Fabric for Concrete Reinforcement.
 - .7 CAN/CSA-G30.18-M92, Billet-Steel Bars for Concrete Reinforcement.
 - .8 CAN/CSA-G40.21-M92, Structural Quality Steels.
 - .9 CAN/CSA-G164-M92, Hot Dip Galvanizing of Irregularly Shaped Articles.
 - .10 CSA W186-M1990, Welding of Reinforcing Bars in Reinforced Concrete Construction.

1.3 SHOP DRAWINGS

- .1 Submit shop drawings including placing of reinforcement in accordance with Section 01 33 00 – Submittal Procedures.

- .2 Indicate on shop drawings, bar bending details, lists, quantities of reinforcement, sizes, spacings, locations of reinforcement and mechanical splices if approved by Owner's Representative, with identifying code marks to permit correct placement without reference to structural drawings. Indicate sizes, spacings and locations of chairs, spacers and hangers. Prepare reinforcement drawings in accordance with Reinforcing Steel Manual of Standard Practice – by Reinforcing Steel Institute of Canada. ANSI/ACI 315 and ACI 315R, Manual of Engineering and Placing Drawings for Reinforced Concrete Structure.
- .3 Detail lap lengths and bar development lengths to CAN3-A23.3.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Substitute different size bars only if permitted in writing by Owner's Representative.
- .2 Reinforcing steel: billet steel, grade 400, deformed bars to CAN/CSA-G30.18, unless indicated otherwise.
- .3 Reinforcing steel: weldable low alloy steel deformed bars to CAN/CSA-G30.18.
- .4 Cold-drawn annealed steel wire ties: to CSA G30.3.
- .5 Deformed steel wire for concrete reinforcement: to CSA G30.14.
- .6 Welded steel wire fabric: to CSA G30.5. Provide in flat sheets only.
- .7 Welded deformed steel wire fabric: to CSA G30.15. Provide in flat sheets only.
- .8 Epoxy Coating of non-prestressed reinforcement: to ASTM A775/A 775M.
- .9 Chairs, bolsters, bar supports, spacers: to CAN/CSA-A23.1.
- .10 Mechanical splices: subject to approval of Owner's Representative.
- .11 Plain round bars: to CAN/CSA-G40.21.

2.2 FABRICATION

- .1 Fabricate reinforcing steel in accordance with CAN/CSA-A23.1, ANSI/ACI 315, and Reinforcing Steel Manual of Standard Practice by the Reinforcing Steel Institute of Canada. ACI 315R, Manual of Engineering and Placing Drawings for Reinforced Concrete Structures unless indicated otherwise.
- .2 Obtain Owner's Representative's approval for locations of reinforcement splices other than those shown on placing drawings.

- .3 Upon approval of Owner's Representative, weld reinforcement in accordance with CSA W186.
- .4 Ship bundles of bar reinforcement, clearly identified in accordance with bar bending details and lists.

2.3 SOURCE QUALITY CONTROL

- .1 Upon request, provide Owner's Representative with certified copy of mill test report of reinforcing steel, showing physical and chemical analysis, minimum 4 weeks prior to commencing reinforcing work.
- .2 Upon request inform Owner's Representative of proposed source of material to be supplied.

PART 3 EXECUTION

3.1 PREPARATION

- .1 Galvanizing to include chromate treatment.
 - .1 Duration of treatment to be 1 hour per 25 mm of bar diameter.
- .2 Conduct bending tests to verify galvanized bar fragility in accordance with ASTM A143/A143M.

3.2 FIELD BENDING

- .1 Do not field bend or field weld reinforcement except where indicated or authorized by Owner's Representative.
- .2 When field bending is authorized, bend without heat, applying slow and steady pressure.
- .3 Replace bars, which develop cracks or splits.

3.3 PLACING REINFORCEMENT

- .1 Place reinforcing steel as indicated on approved placing drawings and in accordance with CAN/CSA-A23.1.
- .2 Use plain round bars as slip dowels in concrete. Paint portion of dowel intended to move within hardened concrete with one coat of asphalt paint. When paint is dry, apply a thick even film of mineral lubricating grease.
- .3 Prior to placing concrete, obtain Owner's Representative's approval of reinforcing material and placement.
- .4 Ensure cover to reinforcement is maintained during concrete pour.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 03 20 00 – Concrete Reinforcing

Page 4 of 4

- .5 Protect epoxy and paint coated portions of bars with covering during transportation and handling.

3.4 FIELD TOUCH-UP

- .1 Touch up damaged and cut ends of epoxy coated or galvanized reinforcing steel with compatible finish to provide continuous coating.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 03 10 00 - Concrete Forming and Accessories.
- .2 Section 03 20 00 - Concrete Reinforcing.
- .3 Section 05 50 00 – Metal Fabrications.

1.2 **REFERENCES**

- .1 American Society for Testing and Materials (ASTM)
 - .1 ASTM C109/C109M-95, Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 2 in. or 50-mm Cube Specimens).
 - .2 ASTM C260-94, Specification for Air-Entraining Admixtures for Concrete.
 - .3 ASTM C309-94, Specification for Liquid Membrane-Forming Compounds for Curing Concrete.
 - .4 ASTM C332-87(1991), Specification for Lightweight Aggregates for Insulating Concrete.
 - .5 ASTM C494-92, Specification for Chemical Admixtures for Concrete.
 - .6 ASTM C827-95a, Test Method for Change in Height at Early Ages of Cylindrical Specimens from Cementitious Mixtures.
 - .7 ASTM C939-94a, Test Method for Flow of Grout for Preplaced-Aggregate Concrete.
 - .8 ASTM D412-92, Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers-Tension.
 - .9 ASTM D624-91, Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomer.
 - .10 ASTM D1751-83(1991), Specification for Preformed Expansion Joint Fillers for Concrete Paving and Structural Construction (Nonextruding and Resilient Bituminous Types).
 - .11 ASTM D1752-84(1992), Specification for Preformed Sponge Rubber and Cork Expansion Joint Fillers for Concrete Paving and Structural Construction.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-37.2-M88, Emulsified Asphalt, Mineral Colloid-Type, Unfilled, for Dampproofing and Waterproofing and for Roof Coatings.
 - .2 CAN/CGSB-51.34-M86, Vapour Barrier, Polyethylene Sheet for Use in Building Construction.
 - .3 CGSB 81-GP-1M-77, Flooring, Conductive and Spark Resistant.
- .3 Canadian Standards Association (CSA)

- .1 CAN/CSA-A5-93, Portland Cement.
- .2 CAN/CSA-A23.1-94, Concrete Materials and Methods of Concrete Construction.
- .3 CAN/CSA A23.2-94 Methods of Test for Concrete.
- .4 CAN/CSA-A23.5-M86(R1992), Supplementary Cementing Materials.
- .5 CAN/CSA A363-M88(R1996), Cementitious Hydraulic Slag.

1.3 ACRONYMS AND TYPES

- .1 Cement: hydraulic cement or blended hydraulic cement (XXb - where b denotes blended).
 - .1 Type GU or GUb - General use cement.
 - .2 Type MS or MSb - Moderate sulphate-resistant cement.
 - .3 Type MH or MHb - Moderate heat of hydration cement.
 - .4 Type HE or Heb - High early-strength cement.
 - .5 Type LH or LHb - Low heat of hydration cement.
 - .6 Type HS or HSb - High sulphate-resistant cement.
- .2 Fly ash:
 - .1 Type F - with CaO content less than 8%.
 - .2 Type CI - with CaO content ranging from 8 to 20%.
 - .3 Type CH - with CaO greater than 20%.
- .3 GGBFS - Ground, granulated blast-furnace slag.

1.4 SUBMITTALS

- .1 At least 4 weeks prior to commencing work, inform Owner's Representative of proposed source of aggregates and provide access for sampling.
- .2 Submit testing results and reports for review by Owner's Representative and do not proceed without written approval when deviations from mix design or parameters are found.
- .3 Certificates:
 - .1 Minimum 4 weeks prior to starting concrete work submit to Owner's Representative manufacturer's test data and certification by qualified independent inspection and testing laboratory that following materials will meet specified requirements:
 - .1 Portland cement.
 - .2 Blended hydraulic cement.
 - .3 Supplementary cementing materials.
 - .4 Grout.
 - .5 Admixtures.

- .6 Aggregates.
- .7 Water.
- .8 Waterstops.
- .9 Waterstop joints.
- .10 Joint filler.
- .2 Provide certification that mix proportions selected will produce concrete of quality, yield and strength as specified in concrete mixes, and will comply with CSA-A23.1/A23.2.
- .3 Provide certification that plant, equipment, and materials to be used in concrete comply with requirements of CSA-A23.1/A23.2.

1.5 SOURCE QUALITY CONTROL

- .1 Have all concrete produced and delivered by a ready-mix plant that is a member of the Atlantic Provinces Ready Mixed Concrete Association (APRMCA) and holds a current “Certificate of Ready Mixed Concrete Production Facilities” issued by the Association. Submit a copy of this certificate to the Owner’s Representative for approval.

1.6 QUALITY ASSURANCE

- .1 Minimum 4 weeks prior to starting concrete work, submit proposed quality control procedures in accordance with Section 01 45 00 - Quality Control for Owner’s Representative approval for following items:
 - .1 Falsework erection.
 - .2 Hot weather concrete.
 - .3 Cold weather concrete.
 - .4 Curing.
 - .5 Finishes.
 - .6 Formwork removal.
 - .7 Joints.

1.7 DELIVERY, STORAGE AND HANDLING

- .1 Concrete hauling time: maximum allowable time for concrete to be delivered to site of Work and discharged not to exceed 120 minutes after batching.
 - .1 Modifications to maximum time limit must be agreed to Owner’s Representative and concrete producer as described in CSA A23.1/A23.2.
 - .2 Deviations to be submitted for review by Owner’s Representative.
- .2 Concrete delivery: ensure continuous concrete delivery from plant meets CSA A23.1/A23.2.
- .3 Waste Management and Disposal:
 - .1 Divert unused concrete materials from landfill to local facility approved by Owner’s Representative.

- .2 Provide an appropriate area on the job site where concrete trucks can be safely washed.
- .3 Divert unused admixtures and additive materials (pigments, fibres) from landfill to official hazardous material collections site as approved by the Owner's Representative.
- .4 Unused admixtures and additive materials must not be disposed of into sewer systems, into lakes, streams, onto ground or in other location where it will pose health or environmental hazard.
- .5 Prevent admixtures and additive materials from entering drinking water supplies or streams. Using appropriate safety precautions, collect liquid or solidify liquid with inert, noncombustible material and remove for disposal. Dispose of waste in accordance with applicable local, Provincial and National regulations.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Portland cement with 40% fly ash replacement: to CAN/CSA-A5.
- .2 Supplementary cementing materials: to CAN/CSA-A363.
- .3 Cementitious hydraulic slag: to CAN/CSA-A363.
- .4 Water: to CAN/CSA-A23.1.
- .5 Aggregates: to CAN/CSA-A23.1. Coarse aggregates to be normal density.
- .6 Low density aggregate for insulating concrete: to CAN/CSA-A23.1 and ASTM C332 group I.
- .7 Air entraining admixture: to ASTM C260.
- .8 Chemical admixtures: to ASTM C494. Owner's Representative to approve accelerating or set retarding admixtures during cold and hot weather placing.
- .9 Concrete retarders: to ASTM C494 water based. Do not allow moisture of any kind to come in contact with the retarder film.
- .10 Shrinkage compensating grout: premixed compound consisting of non-metallic Portland cement, water reducing and plasticizing agents.
 - .1 Compressive strength: 25 MPa at 28 days.
 - .2 Consistency:
 - .1 Fluid: to ASTM C827. Time of efflux through flow cone (ASTM C939), under 30s.
 - .2 Flowable: to ASTM C827. Flow table, 5 drops in 3s, (ASTM C109, applicable portion) 125 to 145%.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 03 30 00 – Cast in Place Concrete

Page 5 of 10

- .3 Plastic: to ASTM C827. Flow table, 5 drops in 3 s, (ASTM C109, applicable portions) 100 to 125%.
- .4 Dry pack to manufacturer's requirements.
- .3 Net shrinkage at 28 days: maximum .5%.
- .11 Non premixed dry pack grout: composition of non metallic aggregate Portland cement with sufficient water for mixture to retain its shape when made into ball by hand and capable of developing compressive strength of 30 MPa at 28 days.
- .12 Post-Tensioning ducts: to CAN/CSA-A23.1.
- .13 Curing compound: to CAN/CSA-A23.1 white and to ASTM C309, Type 1-chlorinated rubber.
- .14 Cushion pads: tough, resilient, weather, moisture, and oil resistant material that will not corrode or cause corrosion, consisting of either layers of approved cotton duck saturated and bound together by approved rubber or synthetic compounds, or made from specially compounded synthetic materials.
- .15 Ribbed waterstops: extruded PVC of sizes indicated with shop welded corner and intersecting pieces with legs not less than 100 mm long:
 - .1 Tensile strength: to ASTM D412, method A, Die "C", minimum 12 MPa.
 - .2 Elongation: to ASTM D412, method A, Die "C", minimum 275%.
 - .3 Tear resistance: to ASTM D624.
- .16 Labyrinth waterstops: extruded PVC Arctic Grade of sizes indicated with prewelded corner and intersecting pieces with legs not less than 100 mm long:
 - .1 Tensile strength: to ASTM D412, method A, Die "C", minimum 12 MPa.
 - .2 Elongation: to ASTM D412, method A, Die "C", minimum 250%.
 - .3 Tear resistance: to ASTM D624, method A, Die "B", minimum 30 kN/m.
- .17 Premoulded joint fillers:
 - .1 Bituminous impregnated fiber board: to ASTM D1751.
 - .2 Sponge rubber: to ASTM D1752, Type I, flexible grade.
 - .3 Self-expanding cork: to ASTM D1752, Type II.
- .18 Weep hole tubes: galvanized steel.
- .19 Dovetail anchor slots: minimum 0.6 mm thick galvanized steel with insulation filled slots.
- .20 Dampproof membrane:
 - .1 Kraft/polyethylene membrane:
 - .1 Plain: .75 mm thick polyethylene film bonded to asphalt treated creped kraft.

- .2 Reinforced: two .75 mm thick polyethylene films bonded each side of asphalt treated creped kraft paper, reinforced with 13 x 13 mm fibreglass scrim.
- .3 Membrane adhesive: as recommended by membrane manufacturer.
- .21 Dampproofing:
 - .1 Emulsified asphalt, mineral colloid type, unfilled: to CAN/CGSB-37.2, and to Section 07 11 13 - Bituminous Dampproofing.
- .22 Polyethylene film: 15 mm thickness to CAN/CGSB-51.34.
- .23 Bonding adhesive: as approved by Owner's Representative.
- .24 Perimeter foundation wall insulation: Extruded polystyrene (XPS).
 - .1 Type: 4.
 - .2 Compressive strength: 275 KPa.
 - .3 Thickness: 51 mm.
 - .4 Size: 610 x 2438 mm.
 - .5 Edges: Shiplapped.
- .25 Fiber cement protection board.
 - .1 100% non-asbestos.
 - .2 Moisture and frost resistant.
 - .3 Thickness – 16 mm.
 - .4 Sheet size – 1220 x 2440.
 - .5 Fasteners – stainless steel or galvanized as per manufacturer's recommendations.
 - .6 Edges – square butt.

2.2 MIXES

- .1 Proportion normal density concrete in accordance with CSA-A23.1/A23.2, Alternative 1 to give following quality and yield for all concrete.
 - .1 Cement:
 - .1 Type GU Portland cement.
 - .2 Minimum compressive strength 35 MPa at 28 days.
 - .3 Minimum cement content: 300 kg/m³ of concrete.
 - .4 Class of exposure: N.
 - .5 Nominal size of coarse aggregate: 20 mm.
 - .6 Slump at time and point of discharge: 75 to 100 mm.
 - .7 Air content: 5 to 8 %.
 - .8 Chemical admixtures: admixtures in accordance with ASTM C494.

PART 3 **EXECUTION**

3.1 **PREPARATION**

- .1 Obtain Owner's Representative approval before placing concrete. Provide 24 h notice prior to placing of concrete.
- .2 Place concrete reinforcing in accordance with Section 03 20 00 - Concrete Reinforcing.
- .3 During concreting operations:
 - .1 Development of cold joints not allowed.
 - .2 Ensure concrete delivery and handling facilitates placing with minimum of re-handling, and without damage to existing structure or Work.
- .4 Pumping of concrete is permitted only after approval of equipment and mix.
- .5 Ensure reinforcement and inserts are not disturbed during concrete placement.
- .6 Prior to placing of concrete obtain Owner's Representative approval of proposed method for protection of concrete during placing and curing in adverse weather.
- .7 Protect previous Work from staining.
- .8 Clean and remove stains prior to application for concrete finishes.
- .9 Maintain accurate records of poured concrete items to indicate date, location of pour, quality, air temperature and test samples taken.
- .10 Do not place load upon new concrete until authorized by Owner's Representative.

3.2 **CONSTRUCTION**

- .1 Do cast-in-place concrete work in accordance with CSA-A23.1/A23.2.
- .2 Sleeves and inserts.
 - .1 No sleeves, ducts, pipes or other openings shall pass through joists, beams, column capitals or columns, except where indicated or approved by Owner's Representative.
 - .2 Where approved by Owner's Representative, set sleeves, ties, pipe hangers and other inserts and openings as indicated or specified elsewhere. Sleeves and openings greater than 100 x 100 mm not indicated, must be approved by Owner's Representative.
 - .3 Do not eliminate or displace reinforcement to accommodate hardware. If inserts cannot be located as specified, obtain approval of modifications from Owner's Representative before placing of concrete.
 - .4 Check locations and sizes of sleeves and openings shown on drawings.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 03 30 00 – Cast in Place Concrete

Page 8 of 10

- .5 Set special inserts for strength testing as indicated and as required by non-destructive method of testing concrete.
- .3 Anchor bolts.
 - .1 Set anchor bolts to templates under supervision of appropriate trade prior to placing concrete.
 - .2 With approval of Owner's Representative, grout anchor bolts in preformed holes or holes drilled after concrete has set. Formed holes to be minimum 100 mm diameter. Drilled holes to be manufacturers's recommendations.
 - .3 Protect anchor bolt holes from water accumulations, snow and ice build-ups.
 - .4 Set bolts and fill holes with shrinkage compensating grout.
 - .5 Locate anchor bolts used in connection with expansion shoes, rollers and rockers with due regard to ambient temperature at time of erection.
- .4 Grout under base plates using procedures in accordance with manufacturer's recommendations which result in 100 % contact over grouted area.
- .5 Finishing.
 - .1 Finish concrete in accordance with CSA-A23.1/A23.2.
 - .2 Use procedures acceptable to Owner's Representative or those noted in CSA-A23.1/A23.2, to remove excess bleed water. Ensure surface is not damaged.
 - .3 Wet cure using polyethylene sheets placed over sufficiently hardened concrete to prevent damage. Overlap adjacent edges 150 mm and tightly seal with sand on wood planks. Weigh sheets down to maintain close contact with concrete during the entire curing period.
 - .4 Where burlap is used for moist curing, place two prewetted layers on concrete surface and keep continuously wet during curing period.
 - .5 Finish concrete floor to meet requirements of CSA-A23.1/A23.2.
 - .6 Concrete floor to have finish hardness equal or greater than Mohs hardness in accordance with CSA-A23.1/A23.2.
 - .7 Provide swirl-trowelled finish for exterior walks, ramps, pads.
 - .8 Provide float finish for interior floor slabs.
 - .9 Rub exposed sharp edges of concrete with carborundum to produce 3 mm radius edges unless otherwise indicated.
- .6 Waterstops.
 - .1 Install waterstops to provide continuous water seal.
 - .2 Do not distort or pierce waterstop in such a way as to hamper performance.
 - .3 Do not displace reinforcement when installing waterstops.
 - .4 Use equipment to manufacturer's requirements to field splice waterstops.
 - .5 Tie waterstops rigidly in place.
 - .6 Use only straight heat sealed butt joints in field.

- .7 Use factory welded corners and intersections unless otherwise approved by Owner's Representative.
- .7 Joint fillers.
 - .1 Furnish filler for each joint in single piece for depth and width required for joint, unless otherwise authorized by Owner's Representative.
 - .2 When more than one piece is required for a joint, fasten abutting ends and hold securely to shape by stapling or other positive fastening.
 - .3 Locate and form, isolation, construction and expansion joints as indicated. Install joint filler.
 - .4 Use 12 mm thick joint filler to separate slabs-on-grade from vertical surfaces and extend joint filler from bottom of slab to within 12 mm of finished slab surface unless indicated otherwise.
- .8 Dampproof membrane.
 - .1 Install dampproof membrane under concrete slabs-on-grade inside building.
 - .2 Lap dampproof membrane minimum 150 mm at joints and seal.
 - .3 Seal punctures in dampproof membrane before placing concrete. Use patching material at least 150 mm larger than puncture and seal.
- .9 Drainage holes and weep holes:
 - .1 Form weep holes and drainage holes in accordance with Section 03 10 00 - Concrete Forming and Accessories. If wood forms are used, remove them after concrete has set.
 - .2 Install weep hole tubes and drains as indicated.

3.3 SITE TOLERANCE

- .1 Concrete slab tolerances in accordance with CSA-A23.1/A23.2, F-number Method, $F_F = 25$, $F_L = 20$.

3.4 FIELD QUALITY CONTROL

- .1 Inspection and testing of concrete and concrete materials will be carried out by a Testing Laboratory designated by Owner's Representative in accordance with CSA-A23.1/A23.2, and Section 01 45 00 - Quality Control.
- .2 Owner's Representative will pay for costs of tests as specified in Section 01 29 83 - Payment Procedures for Testing Laboratory Services. Costs of retesting due to deficient work will be paid for by contractor, by credit change order.
- .3 Owner's Representative will take additional test cylinders during cold weather concreting. Cure cylinders on job site under same conditions as concrete which they represent.
- .4 Non-destructive Methods for Testing Concrete shall be in accordance with CSA-A23.1/A23.2.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 03 30 00 – Cast in Place Concrete

Page 10 of 10

- .5 Provide Certificate of Field Quality Inspection and Testing to Owner's Representative for inclusion in Commissioning Manual.

- .6 Inspection or testing by Owner's Representative will not augment or replace Contractor quality control nor relieve the Contractor of his contractual responsibility.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .2 Section 03 30 00 - Cast-in-Place Concrete.

1.2 **REFERENCES**

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-25.20, Surface Sealer for Floors.
- .2 Canadian Standards Association (CSA)
 - .1 CSA-A23.1/A23.2, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.

1.3 **PERFORMANCE REQUIREMENTS**

- .1 Product quality and quality of work in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Submit written declaration that components used are compatible and will not adversely affect finished flooring products and their installation adhesives.

1.4 **PRODUCT DATA**

- .1 Submit WHMIS MSDS - Material Safety Data Sheets. WHMIS MSDS acceptable to Labour Canada and Health and Welfare Canada for concrete floor treatment materials. Indicate VOC content.
- .2 Include application instructions for concrete floor treatment.

1.5 **ENVIRONMENTAL REQUIREMENTS**

- .1 Temporary lighting:
 - .1 Minimum 1200 W light source, placed 2.5 m above floor surface, for each 40 sq m of floor being treated.
- .2 Electrical power:
 - .1 Provide sufficient electrical power to operate equipment normally used during construction.
- .3 Work area:
 - .1 Make the work area water tight protected against rain and detrimental weather conditions.

- .4 Temperature:
 - .1 Maintain ambient temperature of not less than 10°C from 7 days before installation to at least 48 hours after completion of work and maintain relative humidity not higher than 40% during same period.
- .5 Moisture:
 - .1 Ensure concrete substrate is within moisture limits prescribed by flooring manufacturer.
- .6 Safety:
 - .1 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials.
- .7 Ventilation:
 - .1 Ventilate area of work as directed by Owner's Representative by use of approved portable supply and exhaust fans.
 - .2 Ventilate enclosed spaces in accordance with Section 01 51 00 - Temporary Utilities.
 - .3 Provide continuous ventilation during and after coating application.

PART 2 PRODUCTS

2.1 CHEMICAL HARDENERS

- .1 Type 1- Sodium silicate.
- .2 Water: potable.

2.2 SEALING COMPOUNDS

- .1 Surface sealer: to CAN/CGSB-25.20, Type 2 - water based.
- .2 Surface sealers may not be manufactured or formulated with aromatic solvents formaldehyde halogenated solvents mercury lead cadmium hexavalent chromium and their compounds.

2.3 WET CURE

- .1 Clear polyethylene film to ASTM C171, minimum thickness 0.15 mm.

2.4 MIXES

- .1 Mixing, ratios and application in accordance with manufacturer's instructions.

2.5 JOINT SEALANT

- .1 Joint sealants to Section 07 92 00 – Joint Sealants.

PART 3 EXECUTION

3.1 EXAMINATION

- .1 Verify that slab surfaces are ready to receive work and elevations are as indicated on drawings by manufacturer.

3.2 PREPARATION OF EXISTING SLAB

- .1 Rub exposed sharp edges of concrete with carborundum to produce 3 mm radiused edges unless otherwise indicated.
- .2 Saw cut control joints to CSA-A23.1/A23.2, 24 hours maximum after placing of concrete.
- .3 Use mechanical stripping to remove chlorinated rubber or existing surface coatings.
- .4 Use protective clothing, eye protection, respiratory equipment during stripping of chlorinated rubber or existing surface coatings.

3.3 APPLICATION

- .1 After floor treatment is dry, seal control joints and joints at junction with vertical surfaces with sealant.
- .2 Apply floor treatment in accordance with Sealer manufacturer's written instructions.
- .3 Clean overspray. Clean sealant from adjacent surfaces.

3.4 PROTECTION

- .1 Protect finished installation in accordance with manufacturer's instructions.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.

1.2 **REFERENCES**

- .1 American Wood-Preservers' Association (AWPA)
 - .1 AWWA M2, Standard Inspection of Treated Wood Products.
 - .2 AWWA M4, Standard for the Care of Preservative-Treated Wood Products.
- .2 Canadian Standards Association (CSA)
 - .1 CSA O80 Series, Wood Preservation.
 - .2 CSA O80.20, Fire-Retardant Treatment of Lumbering Pressure Processes. This Standard applies to the fire-retardant treatment of lumber by pressure processes. Fire-Retardant Treatment of Lumber by Pressure Processes. This is not a stand alone specification.
 - .3 CSA O80.27, Fire-Retardant Treatment of Plywood by Pressure Processes. This Standard covers the fire-retardant treatment of Douglas Fir, hardwood, softwood, and Poplar plywood by pressure processes. Fire-Retardant Treatment of Plywood by Pressure Processes. This not a stand alone specification.
 - .4 CSA O80.201, Standard for Hydrocarbon Solvents for Preservatives. This Standard covers hydrocarbon solvents for preparing solutions of preservatives.- This is not stand alone specification
 - .5 CSA O322, Procedure for Certification of Pressure-Treated Wood Materials for Use in Preserved Wood Foundations.

1.3 **REGULATORY REQUIREMENTS**

- .1 Each board or bundle of fire-retardant treated material panel to bear ULC label indicating Flame Spread Classification (FSC), and smoke developed.

1.4 **CERTIFICATES**

- .1 For products treated with preservative, fire-retardant by pressure impregnation submit following information certified by authorized signing officer of treatment plant:
 - .1 Information listed in AWWA M2 and revisions specified in CSA O80 Series, Supplementary Requirement to AWWA M2 applicable to specified treatment.
 - .2 Moisture content after drying following treatment with water-borne preservative, fire-retardant.
 - .3 Acceptable types of paint, stain, and clear finishes that may be used over treated materials to be finished after treatment.

1.5 WASTE MANAGEMENT AND DISPOSAL

- .1 Do not dispose of preservative treated wood through incineration.
- .2 Do not dispose of preservative treated wood with other materials destined for recycling or reuse.
- .3 Dispose of treated wood, end pieces, wood scraps and sawdust at sanitary landfill approved by Owner's Representative.
- .4 Dispose of unused wood preservative material at official hazardous material collections site approved by Owner's Representative.
- .5 Do not dispose of unused preservative material into sewer system, into streams, lakes, onto ground or in other location where they will pose health or environmental hazard.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Preservative: to CAN/CSA-O80 Series, stained finish.
- .2 Fire-Retardant: to CAN/CSA O80.20.
- .3 Solvent: to CAN/CSA-O80.201.

PART 3 EXECUTION

3.1 APPLICATION: PRESERVATIVE

- .1 Treat lumber to CAN/CSA- O80 Series.
- .2 Following water-borne preservative treatment, dry material to maximum moisture content of 19%.

3.2 APPLICATION: FIRE-RETARDANT

- .1 Treat lumber by pressure impregnation with fire-retardant chemicals in accordance with CAN/CSA - O80.20.
- .2 Following treatment, kiln-dry material to maximum moisture content of 19%.

3.3 APPLICATION: FIELD TREATMENT

- .1 Comply with AWPA M4 and revisions specified in CAN/CSA-O80 Series, Supplementary Requirements to AWPA Standard M2.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 06 05 73 – Wood Treatment

Page 3 of 3

- .2 Treat all field cuts with two (2) coats of clear copper naphthenate or 5% pentachlorophenol solution, water repellent preservative.
- .3 Remove chemical deposits on treated wood to receive applied finish.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .2 Section 06 05 73 - Wood Treatment.
- .3 Section 07 52 00 - Modified Bituminous Membrane Roofing
- .4 Section 07 91 00 - Joint Sealants.

1.2 **REFERENCES**

- .1 American Society for Testing and Materials (ASTM)
 - .1 ASTM C36/C36M, Specification for Gypsum Wallboard.
 - .2 ASTM C578, Specification for Rigid, Cellular Polystyrene Thermal Insulation.
 - .3 ASTM D5055, Specification for Establishing and Monitoring Structural Capacities of Prefabricated Wood I-Joists.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.32, Sheathing, Membrane, Breather Type.
 - .2 CAN/CGSB-51.34, Vapour Barrier, Polyethylene Sheet for Use in Building Construction.
 - .3 CAN/CGSB-71.26, Adhesive for Field-Gluing Plywood to Lumber Framing for Floor Systems.
- .3 Canadian Standards Association (CSA)
 - .1 CSA A123.2, Asphalt Coated Roofing Sheets.
 - .2 CAN/CSA-A247, Insulating Fiberboard.
 - .3 CSA B111, Wire Nails, Spikes and Staples.
 - .4 CAN/CSA-G164, Hot Dip Galvanizing of Irregularly Shaped Articles.
 - .5 CSA O112 Series, CSA Standards for Wood Adhesives.
 - .6 CSA O121, Douglas Fir Plywood.
 - .7 CAN/CSA-O141, Softwood Lumber.
 - .8 CSA O151, Canadian Softwood Plywood.
 - .9 CAN/CSA-O325.0, Construction Sheathing.
- .4 National Lumber Grades Authority (NLGA)
 - .1 Standard Grading Rules for Canadian Lumber.

1.3 QUALITY ASSURANCE

- .1 Lumber identification: by grade stamp of an agency certified by Canadian Lumber Standards Accreditation Board.
- .2 Plywood, particleboard, OSB and wood based composite panels in accordance with CSA and ANSI standards.

1.4 SUBMITTALS

- .1 Submit proof of compatibility between Alkaline Copper Quaternary (ACQ) pressure treated lumber and fasteners to be utilized.

PART 2 PRODUCTS

2.1 FRAMING AND LUMBER MATERIALS

- .1 Lumber: unless specified otherwise, softwood, No. 1 or No. 2 grade, S4S, moisture content 19% (S-dry) or less in accordance with following standards:
 - .1 CAN/CSA-O141.
 - .2 NLGA Standard Grading Rules for Canadian Lumber.
- .2 Wood I-joists in accordance with Prefabricated Wood I-Joists ASTM D5055.
- .3 Framing and board lumber: in accordance with NBC.
- .4 Furring, blocking, nailing strips, grounds, rough bucks, fascia backing and sleepers:
 - .1 Board sizes: "Standard" or better grade.
 - .2 Dimension sizes: "Standard" light framing or better grade.
 - .3 Post and timbers sizes: "Standard" or better grade.
- .5 Pressure treated material to be Alkaline Copper Quaternary (ACQ).

2.2 ACCESSORIES

- .1 Polyethylene film: to Section 07 26 00 – Vapour Retarders.
- .2 Sealants: Section 07 91 00 – Joint Sealants.
- .3 General purpose adhesive: to CSA O112 Series.
- .4 Nails, spikes and staples: to CSA B111.
- .5 Bolts: 12.5 mm diameter unless indicated otherwise, complete with nuts and washers.
- .6 Proprietary fasteners: toggle bolts, expansion shields and lag bolts, screws and lead or inorganic fibre plugs, explosive actuated fastening devices, recommended for purpose by manufacturer.

2.3 FASTENER FINISHES

- .1 Galvanizing: to CAN/CSA-G164, use galvanized fasteners for exterior work, interior highly humid areas and fire-retardant treated lumber.

2.4 WOOD PRESERVATIVE

- .1 Surface-applied wood preservative: clear or copper naphthenate or 5% pentachlorophenol solution, water repellent preservative.

PART 3 EXECUTION

3.1 PREPARATION

- .1 Treat surfaces of material with wood preservative, before installation.
- .2 Apply preservative by dipping, or by brush to completely saturate and maintain wet film on surface for minimum 3 minute soak on lumber and one minute soak on plywood.
- .3 Re-treat surfaces exposed by cutting, trimming or boring with liberal brush application of preservative before installation.
- .4 Treat all material as indicated as follows:
 - .1 Wood fascia, backing, curbs, nailers.
 - .2 Wood furring for sheeting/siding on outside surface of exterior masonry concrete walls.
 - .3 Wood sleepers supporting wood subflooring over concrete slabs in contact with ground or fill.

3.2 INSTALLATION

- .1 Comply with requirements of NBC latest edition, Part 9 supplemented by following paragraphs.
- .2 Install members true to line, levels and elevations, square and plumb.
- .3 Construct continuous members from pieces of longest practical length.
- .4 Install spanning members with "crown-edge" up.
- .5 Select exposed framing for appearance. Install lumber and panel materials so that grade-marks and other defacing marks are concealed or are removed by sanding where materials are left exposed.
- .6 Install furring and blocking as required to space-out and support casework, cabinets, wall and ceiling finishes, facings, fascia, soffit, siding electrical equipment mounting boards, and other work as required.

- .7 Install furring to support siding applied vertically where there is no blocking and where sheathing is not suitable for direct nailing.
 - .1 Align and plumb faces of furring and blocking to tolerance of 1:600.
- .8 Install rough bucks, nailers and linings to rough openings as required to provide backing for frames and other work.
- .9 Install wood cants, fascia backing, nailers, and other wood supports as required and secure using galvanized steel fasteners.
- .10 Install sleepers as indicated.
- .11 Use dust collectors and high quality respirator masks when cutting or sanding wood panels.

3.3 ERECTION

- .1 Frame, anchor, fasten, tie and brace members to provide necessary strength and rigidity.
- .2 Countersink bolts where necessary to provide clearance for other work.
- .3 Use nailing disks for soft sheathing as recommended by sheathing manufacturer.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 61 00 - Common Product Requirements.
- .3 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .4 Section 06 40 00 - Architectural Woodwork.
- .5 Section 09 91 23 - Interior Painting.

1.2 **REFERENCES**

- .1 American National Standards Institute (ANSI)
 - .1 ANSI A208.1, Particleboard.
 - .2 ANSI A208.2, Medium Density Fibreboard (MDF).
 - .3 ANSI/HPVA HP-1, American National Standard for Hardwood and Decorative Plywood.
- .2 Architectural Woodwork Manufacturers Association of Canada (AWMAC) and Architectural Woodwork Institute (AWI)
 - .1 Architectural Woodwork Quality Standards, 1st edition.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-11.3, Hardboard.
- .4 Canadian Standards Association (CSA)
 - .1 CSA B111, Wire Nails, Spikes and Staples.
 - .2 CSA O121, Douglas Fir Plywood.
 - .3 CAN/CSA O141, Softwood Lumber.
 - .4 CSA O151, Canadian Softwood Plywood.
 - .5 CSA O153, Poplar Plywood.
- .5 National Lumber Grades Authority (NLGA)
 - .1 Standard Grading Rules for Canadian Lumber.

1.3 **QUALITY ASSURANCE**

- .1 Lumber by grade stamp of agency certified by Canadian Lumber Standards Accreditation Board (CLSAB).

- .2 Plywood, particleboard, OSB and wood based composite panels to CSA and ANSI standards.
- .3 Wood fire rated frames and panels: listed and labelled by an organization accredited by Standards Council of Canada to CAN4-S104 and CAN/ULC-S105.

1.4 SUBMITTALS

- .1 Indicate details of construction, profiles, jointing, fastening and other related details.
- .2 Indicate materials, thicknesses, finishes and hardware.

1.5 DELIVERY, STORAGE, AND HANDLING

- .1 Deliver, handle, store and protect materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Protect materials against dampness during and after delivery.
- .3 Store materials in ventilated areas, protected from extreme changes of temperature or humidity.

PART 2 PRODUCTS

2.1 LUMBER MATERIAL

- .1 Softwood lumber: unless specified otherwise, S4S, moisture content 19% or less in accordance with following standards:
 - .1 CAN/CSA-O141.
 - .2 NLGA Standard Grading Rules for Canadian Lumber.
 - .3 AWMAC custom premium grade, moisture content as specified.
- .2 Machine stress-rated lumber is acceptable.
- .3 Hardwood lumber: moisture content 10 % or less in accordance with following standards:
 - .1 National Hardwood Lumber Association (NHLA).
 - .2 AWMAC custom grade, moisture content as specified.

2.2 PANEL MATERIAL

- .1 Panel materials to be urea-formaldehyde free.
- .2 Douglas fir plywood (DFP): to CSA O121, standard construction.
- .3 Canadian softwood plywood (CSP): to CSA O151, standard construction.

- .4 Hardwood plywood: to ANSI/HPVA HP-1.
- .5 Poplar plywood (PP): to CSA O153, standard construction.
- .6 Hardboard: to CAN/CGSB-11.3.

2.3 ACCESSORIES

- .1 Nails and staples: to CSA B111; galvanized to CAN/CSA-G164 for exterior work, interior humid areas and for treated lumber; plain finish elsewhere.
- .2 Wood screws: plain, type and size to suit application.
- .3 Splines: wood
- .4 Adhesive: recommended by manufacturer.
- .5 Use least toxic sealants, adhesives, sealers, and finishes necessary to comply with requirements of this section.

PART 3 EXECUTION

3.1 INSTALLATION

- .1 Do finish carpentry to Quality Standards of the Architectural Woodwork Manufacturers Association of Canada (AWMAC), except where specified otherwise.
- .2 Scribe and cut as required, fit to abutting walls, and surfaces, fit properly into recesses and to accommodate piping, columns, fixtures, outlets, or other projecting, intersecting or penetrating objects.
- .3 Form joints to conceal shrinkage.

3.2 CONSTRUCTION

- .1 Fastening.
 - .1 Position items of finished carpentry work accurately, level, plumb, true and fasten or anchor securely.
 - .2 Design and select fasteners to suit size and nature of components being joined. Use proprietary devices as recommended by manufacturer.
 - .3 Set finishing nails to receive filler. Where screws are used to secure members, countersink screw in round cleanly cut hole and plug with wood plug to match material being secured.
 - .4 Replace items of finish carpentry with damage to wood surfaces including hammer and other bruises.
- .2 Standing and running trim.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135
Section 06 20 00 - Finish Carpentry

September 2016

Page 4 of 4

- .1 Butt and cope internal joints of baseboards to make snug, tight, joint. Cut right angle joints of casing and base with mitred joints.
- .2 Fit backs of baseboards and casing snugly to wall surfaces to eliminate cracks at junction of base and casing with walls.
- .3 Make joints in baseboard, where necessary using a 45° scarf type joint.
- .4 Install door and window trim in single lengths without splicing.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 45 00 - Quality Control.
- .3 Section 01 61 00 - Common Product Requirements.
- .4 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .5 Section 06 20 00 – Finish Carpentry.
- .6 Section 06 47 00 – Plastic Laminate Finishes.
- .7 Section 07 92 00 – Joint Sealants.
- .8 Section 08 70 05 – Cabinet and Miscellaneous Hardware.

1.2 **REFERENCES**

- .1 American National Standards Institute (ANSI)
 - .1 ANSI/NPA A208.1, Particle board.
 - .2 ANSI A208.2, Medium Density Fiberboard (MDF) for Interior Applications.
 - .3 ANSI/HPVA HP-1, Standard for Hardwood and Decorative Plywood.
 - .4 ANSI/NEMA LD-3, High-Pressure Decorative Laminates (HPDL).
- .2 Architectural Woodwork Manufacturers Association of Canada (AWMAC) and Architectural Woodwork Institute (AWI)
 - .1 Architectural Woodwork Quality Standards Illustrated.
- .3 American Society for Testing and Materials (ASTM)
 - .1 ASTM E1333, Standard Test Method for Determining Formaldehyde Concentrations in Air and Emission Rates From Wood Products Using a Large Chamber.
- .4 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-71.20, Adhesive, Contact, Brushable.
- .5 Canadian Standards Association (CSA)
 - .1 CSA B111, Wire Nails, Spikes and Staples.
 - .2 CSA O112.10, Evaluation of Adhesives for Structural Wood Products (Limited Moisture Exposure).
 - .3 CSA O121, Douglas Fir Plywood.

- .4 CSA O141, Softwood Lumber.
- .5 CSA O151, Canadian Softwood Plywood.
- .6 CSA O153, Poplar Plywood.
- .6 National Hardwood Lumber Association (NHLA)
 - .1 Rules for the Measurement and Inspection of Hardwood and Cypress.
- .7 National Lumber Grades Authority (NLGA)
 - .1 Standard Grading Rules for Canadian Lumber.

1.3 QUALITY ASSURANCE

- .1 Provide Certificate of Quality Compliance upon completion of Fabrication, in accordance with Architectural Woodwork Manufacturer's Association of Canada (AWMAC) quality standards.
- .2 Provide Certificate of Quality Compliance upon satisfactory completion of installation.

1.4 SUBMITTALS

- .1 Indicate details of construction, profiles, jointing, fastening and other related details.
Scales:
 - .1 profiles full size, details 1/2 full size.
- .2 Indicate all materials, thicknesses, finishes and hardware.
- .3 Indicate locations of service outlets in casework, typical and special installation conditions, and connections, attachments, anchorage and location of exposed fastenings.
- .4 Submit duplicate colour samples of laminated plastic for colour selection.
- .5 Submit duplicate samples of laminated plastic joints, edging, cutouts, and postformed profiles.

1.5 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, handle, store and protect materials of this section in accordance with Section 01 61 00 – Common Product Requirements.
- .2 Protect millwork against dampness and damage during and after delivery.
- .3 Store millwork in ventilated areas, protected from extreme changes of temperature or humidity.
- .4 Store materials off ground, in dry location and in accordance with manufacturer's recommendations in clean, dry, well-ventilated area.
- .5 Store and protect architectural woodwork from nicks, scratches, and blemishes.

- .6 Replace defective or damaged materials with new.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Softwood lumber: unless specified otherwise, S4S, moisture content 19 % or less in accordance with following standards:
 - .1 CAN/CSA-O141.
 - .2 NLGA Standard Grading Rules for Canadian Lumber.
 - .3 AWMAC premium grade, moisture content as specified.
- .2 Machine stress-rated lumber is acceptable for all purposes.
- .3 Hardwood lumber: moisture content 10% or less in accordance with following standards:
 - .1 National Hardwood Lumber Association (NHLA).
 - .2 AWMAC premium grade, moisture content as specified.
- .4 Douglas fir plywood (DFP): to CSA O121, standard construction.
 - .1 Urea-formaldehyde free.
- .5 Canadian softwood plywood (CSP): to CSA O151, standard construction.
 - .1 Urea-formaldehyde free.
- .6 Hardwood plywood: to ANSI/HPVA HP-1.
 - .1 Urea-formaldehyde free.
- .7 Poplar plywood (PP): to CSA O153, standard construction.
 - .1 Urea-formaldehyde free.
- .8 Maple plywood: to AWMAC Natural.
 - .1 Urea-formaldehyde free.
- .9 Hardboard: to CAN/CGSB – 11.3.
 - .1 Urea-formaldehyde free.
- .10 Medium density fibreboard (MDF): to ANSI A208.2, density 769 kg/m³.
 - .1 Urea-formaldehyde free.
 - .2 Must meet the performance requirements of ANSI A208.2
- .11 Nails and staples: to CSA B111.
- .12 Wood screws: steel plain, type and size to suit application.
- .13 Sealant: Section 07 92 00 – Joint Sealants.

2.2 WINDOW BOX, CASINGS

- .1 Window box, casings, maple species, NHLA premium grade, thickness as specified.

2.3 FABRICATION

- .1 Set nails and countersink screws apply stained wood filler to indentations, sand smooth and leave ready to receive finish.
- .2 Shop install cabinet hardware for doors, shelves and drawers. Recess shelf standards unless noted otherwise.
- .3 Shelving to cabinetwork to be adjustable unless otherwise noted.

2.4 FINISHING

- .1 Section 09 91 23 – Interior Painting

PART 3 EXECUTION

3.1 INSTALLATION

- .1 Do architectural woodwork to Quality Standards of the Architectural Woodwork Manufacturers Association of Canada (AWMAC), except where specified otherwise.
- .2 Install prefinished millwork at locations shown on drawings. Position accurately, level, plumb straight.

3.2 CLEANING

- .1 Clean window boxes and casings free from dust.
- .2 Remove excess sealant from surfaces.

3.3 PROTECTION

- .1 Repair damage to adjacent materials caused by architectural woodwork installation.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 06 10 00 – Rough Carpentry.
- .4 Section 07 26 00 - Vapour Retarders.

1.2 **REFERENCES**

- .1 American Society for Testing and Materials International, (ASTM).
 - .1 ASTM C1289, Standard Specification for Faced Rigid Cellular Polyisocyanurate Thermal Insulation Board.
- .2 Canadian Gas Association (CGA)
 - .1 CAN/CGA-B149.1, Natural Gas and Propane Installation Code Handbook.
 - .2 CAN/CGA-B149.2, Propane Storage and Handling Code.
- .3 Canadian General Standards Board (CGSB).
 - .1 CGSB 71-GP-24M, Adhesive, Flexible, for Bonding Cellular polystyrene Insulation.
- .4 Underwriters Laboratories of Canada (ULC).
 - .1 CAN/ULC-S701, Standard for Thermal Insulation, Polystyrene, Boards and Pipe Coverings.
 - .2 CAN/ULC-S702, Standard for Thermal Insulation, Mineral Fibre, for Buildings.
 - .3 CAN/ULC-S704, Standard for Thermal Insulation Polyurethane and Polyisocyanurate, Boards, Faced.

1.3 **SUBMITTALS**

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data.
 - .2 Submit two copies of WHMIS MSDS - Material Safety Data Sheets. Indicate VOC's insulation products and adhesives.
- .2 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.

1.4 QUALITY ASSURANCE

- .1 Provide certificate of quality compliance from insulation manufacturer.

PART 2 PRODUCTS

2.1 INSULATION

- .1 Board insulation shall be “Foamular C-200” extruded polystyrene by “Owens Corning” or approved equal, R.S.I. 0.87/25 mm.
- .2 Insulation types not indicated on drawings to be expanded polystyrene (EPS), Type 2 as a default, as per article 2.1.1.

2.2 ADHESIVE

- .1 Adhesive suitable for bonding polystyrene and mineral fibre insulation to substrates as indicated.

2.3 ACCESSORIES

- .1 Joint sealing tape: air resistant pressure sensitive adhesive tape as recommended by insulation manufacturer.

PART 3 EXECUTION

3.1 MANUFACTURER’S INSTRUCTIONS

- .1 Compliance: comply with manufacturer’s written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions and data sheets.

3.2 WORKMANSHIP

- .1 Install insulation after building substrate materials are dry.
- .2 Install insulation to maintain continuity of thermal protection to building elements and spaces.
- .3 Fit insulation tight around electrical boxes, plumbing and heating pipes and ducts, around exterior doors and windows and other protrusions.
- .4 Keep insulation minimum 75 mm from heat emitting devices such as recessed light fixtures, and CAN/CGA-B149.1 and CAN/CGA-B149.2 type B and L vents.
- .5 Cut and trim insulation neatly to fit spaces. Butt joints tightly, offset vertical joints. Use only insulation boards free from chipped or broken edges. Use largest possible dimensions to reduce number of joints.

- .6 Offset both vertical and horizontal joints in multiple layer applications.
- .7 Do not enclose insulation until it has been inspected and approved by Owner's Representative.

3.3 EXAMINATION

- .1 Examine substrates and immediately inform Owner's Representative in writing of defects.
- .2 Prior to commencement of work ensure:
 - .1 Substrates are firm, straight, smooth, dry, free of snow, ice or frost, and clean of dust and debris.

3.4 RIGID INSULATION INSTALLATION

- .1 Apply adhesive to insulation board in accordance with manufacturer's recommendations.
- .2 Mechanically fastened to plywood substrate, securing to structural insulation board members.

3.5 CLEANING

- .1 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 06 10 00 – Rough Carpentry.
- .4 Section 07 26 00 - Vapour Retarders.

1.2 REFERENCES

- .1 American Society for Testing and Materials, (ASTM).
 - .1 ASTM C553, Specification for Mineral Fibre Blanket Thermal Insulation for Commercial and Industrial Applications.
 - .2 ASTM C665, Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing.
 - .3 ASTM C1320, Standard Practice for Installation of Mineral Fiber Batt and Blanket Thermal Insulation for Light Frame Construction.
 - .4 ASTM E84, Test Method for Surface Burning Characteristics of Building Materials.
- .2 Canadian Standards Association (CSA International).
 - .1 CSA B111, Wire Nails, Spikes and Staples.
 - .2 CSA B149 PACKAGE, Consists of B149.1, Natural Gas and Propane Installation Code and B149.2, Propane Storage and Handling Code.
- .3 Underwriters Laboratories of Canada (ULC).
 - .1 CAN/ULC-S702, Standard for Mineral Fibre Insulation.

1.3 SUBMITTALS

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data sheet.
- .2 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.

PART 2 PRODUCTS

2.1 INSULATION

- .1 Thermal batt and blanket mineral fibre:

- .1 Unfaced glass fiber thermal insulation to ASTM C665 Type:I, thickness and RSI value as indicated on drawings for new or damaged materials.
- .2 Semi-rigid mineral wool batt insulation to CSA/ULC-S702, made from basalt rock and slag, thickness and RSI value as indicated on drawings.

PART 3 EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.

3.2 INSULATION INSTALLATION

- .1 Install insulation to maintain continuity of thermal protection to building elements and spaces and for sound attenuation as noted on drawings.
- .2 Fit insulation closely around electrical boxes, pipes, ducts, frames and other objects in or passing through insulation.
- .3 Do not compress insulation to fit into spaces.
- .4 Keep insulation minimum 75 mm from heat emitting devices such as recessed light fixtures, and minimum 50 mm from sidewalls and CSA B149.1 and CSA B149.2 Type B and L vents.
- .5 Do not enclose insulation until it has been inspected and approved by Owner's Representative.

3.3 CLEANING

- .1 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 – Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 03 30 00 - Cast-in-Place Concrete.
- .4 Section 06 10 00 – Rough Carpentry.

1.2 REFERENCES

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.34, Vapour Barrier, Polyethylene Sheet, for Use in Building Construction.
- .2 Underwriters Laboratories Canada (ULC)
 - .1 CAN/ULC S102, Method of Test for Surface Burning Characteristics of Building Materials and Assemblies.

1.3 SUBMITTALS

- .1 Submit manufacturer's printed product literature, specifications and datasheet and include:
 - .1 Product characteristics.
 - .2 Performance criteria.
 - .3 Limitations.
- .2 Submit two copies of Workplace Hazardous Materials Information System (WHMIS) Material Safety Data Sheets (MSDS).
- .3 Quality assurance submittals:
 - .1 Certificates: submit certificates certifying that materials comply with specified performance characteristics and physical properties.
 - .2 Instructions: submit manufacturer's installation instructions and comply with written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheet.

PART 2 **PRODUCTS**

2.1 **SHEET VAPOUR RETARDER EXTERIOR WALLS**

- .1 Polyethylene film: to CAN/CGSB-51.34, 0.15mm thick with a water vapour permeance of not greater than 45 ng/(P·s·m²), flame spread rating of less than 150 to CAN/ULC S102.

2.2 **ACCESSORIES**

- .1 Joint sealing tape: air resistant pressure sensitive adhesive tape, type recommended by vapour barrier manufacturer, 50 mm wide for lap joints and perimeter seals, 25 mm wide elsewhere.

PART 3 **EXECUTION**

3.1 **INSTALLATION**

- .1 Install Sheet Vapour retarder over rigid insulation with minimum lap of 300 mm.
- .2 Use sheets of largest practical size to minimize joints.
- .3 Inspect for continuity. Repair punctures and tears with sealing tape before work is concealed.

3.2 **CLEANING**

- .1 Upon completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Materials and installation methods providing primary air/vapour barrier materials and assemblies.
- .2 Air/vapour barrier materials to provide continuous seal between components of building envelope and building penetrations.

1.2 **RELATED SECTIONS**

- .1 Section 01 45 00 - Quality Control.
- .2 Section 01 51 00 - Temporary Utilities.
- .3 Section 01 61 00 - Common Product Requirements.
- .4 Section 07 92 00 - Joint Sealants.

1.3 **REFERENCES**

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-19.13M, Sealing Compound, One Component, Elastomeric Chemical Curing.
 - .2 CAN/CGSB-19.18M, Sealing Compound, One Component, Silicone Base Solvent Curing.
 - .3 CAN/CGSB-19.24M, Multi-Component, Chemical Curing Sealing Compound.
 - .4 CGSB 19-GP-14M, Sealing Compound, One Component, Butyl-Polyisobutylene Polymer Base, Solvent Curing.
- .2 National Building Code of Canada (NBCC)
 - .1 NBCC, Part 5 - Environmental Separation
- .3 Sealant and Waterproofer's Institute - Sealant and Caulking Guide Specification.

1.4 **SUBMITTALS**

- .1 Submit manufacturer's product data sheets.
- .2 Submit manufacturer's installation instructions.

1.5 **QUALITY ASSURANCE**

- .1 Perform Work in accordance with Sealant and Waterproofer's Institute - Sealant and Caulking Guide Specification requirements for materials and installation.

- .2 Perform Work in accordance with National Air Barrier Association - Professional Contractor Quality Assurance Program and requirements for materials and installation.
- .3 Manufacturer's Representative:
 - .1 Inspect substrate prior to commencement of work, twice during application of membrane and at commissioning to ascertain that air/vapour barrier system is installed according to membrane manufacturer's most current published specifications and details.
 - .2 Provide technical assistance to applicator and assist where required in correct installation of membrane.
 - .3 Provide certificate of quality compliance upon satisfactory completion of installation.
- .4 Maintain one copy of documents on site.

1.6 QUALIFICATIONS

- .1 Applicator: Company specializing in performing work of this section with minimum 5 years documented experience with installation of air/vapour barrier systems. Complete installation must be approved by the material manufacturer.
- .2 Applicator: Company who is currently licensed by certifying organization must maintain their license throughout the duration of the project.

1.7 PRE- INSTALLATION MEETINGS

- .1 Convene one week prior to commencing work of this section.

1.8 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Deliver, store and handle materials in accordance with manufacturer's written instructions. Deliver membrane materials in factory wrapped packaging indicating name of manufacturer and product.
- .3 Avoid spillage. Immediately notify Owner's Representative if spillage occurs and start clean up procedures.
- .4 Clean spills and leave area as it was prior to spill.
- .5 Store roll materials on end in original packaging.
- .6 Store primers at temperatures of 5°C and above to facilitate handling. Keep solvent away from open flame and excessive heat.

1.9 PROJECT ENVIRONMENTAL REQUIREMENTS

- .1 Do not install solvent curing sealants or vapour release adhesive materials in enclosed spaces without ventilation.
- .2 Ventilate enclosed spaces in accordance with Section 01 51 00 - Temporary Utilities.
- .3 Maintain temperature and humidity recommended by materials manufactures before, during and after installation.

1.10 WARRANTY

- .1 Provide a written warranty for work of this section from Manufacturer for failure due to defective materials and from contractor for failure due to defective installation workmanship for ten (10) years respectively from the date of Substantial Completion.
- .2 Include coverage of installed sealant and sheet materials which fail to achieve air tight and watertight seal, exhibit loss of adhesion or cohesion or do not cure.

PART 2 PRODUCTS

2.1 SHEET APPLIED, VAPOUR PERMEABLE AIR BARRIER MEMBRANE, ADHESIVE, PRIMER

- .1 Per Drawing A1.9.

2.2 SEALANTS

- .1 Sealants in accordance with Section 07 92 00 - Joint Sealants.
- .2 Primer: recommended by sealant manufacturer.

2.3 SCHEDULE

- .1 Type 1 Air Barrier: for installation on any solid surface.
- .2 Type 2 Air Barrier: for installation on masonry or concrete surfaces.
- .3 Type 3 Air Barrier: for installation on wood/gypsum board surfaces.
- .4 Type 4 Air Barrier: for installation on any solid surface approved by manufacturer.

PART 3 EXECUTION

3.1 EXAMINATION

- .1 Verify that surfaces and conditions are ready to accept the Work of this section.

- .2 Ensure all surfaces are clean, dry, sound, smooth, continuous and comply with air barrier manufacturer's requirements.
- .3 Report any unsatisfactory conditions to the Owner's Representative in writing.
- .4 Do not start work until deficiencies have been corrected.

3.2 PREPARATION

- .1 Remove loose or foreign matter which might impair adhesion of materials.
- .2 Ensure all substrates are clean of oil or excess dust; all masonry joints struck flush, and open joints filled; and all concrete surfaces free of large voids, spalled areas or sharp protrusions.
- .3 Ensure all substrates are free of surface moisture prior to application of membrane and primer.
- .4 Ensure metal closures are free of sharp edges and burrs.
- .5 Prime substrate surfaces to receive adhesive and sealants in accordance with manufacturer's instructions.

3.3 INSTALLATION (SHEET MEMBRANE)

- .1 Install materials in accordance with manufacturer's instructions.

3.4 PROTECTION OF WORK

- .1 Protect finished Work in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Do not permit adjacent work to damage work of this section.
- .3 Ensure finished Work is protected from climatic conditions.

3.5 INSPECTION

- .1 Carefully inspect for continuity of air barrier prior to placement of insulation.
- .2 Repair all deficient membrane areas.
- .3 Misaligned or inadequately lapped seams, punctures or other damage must be repaired with a patch of air barrier membrane extending 50mm in all directions from edge of damaged areas.
- .4 Cover membrane immediately after Owner's Representative's inspection to protect from damage by other trades.

3.6 TESTING

- .1 Air leakage testing as directed by Owner's Representative and paid for by contractor will be performed by professional testing agency for the locations selected at random for penetrations, laps, corners, etc.
- .2 Testing will be witnessed by Owner's Representative and test reports will be signed by tester, site representative and contractor.
- .3 Inform Owner's Representative 48 hours prior to required testing.

END OF SECTION

PART 1 **GENERAL**

1.1 **SECTION INCLUDES**

- .1 Materials, removal and installation of fiberglass-reinforced asphalt shingles and roll roofing.

1.2 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 45 00 - Quality Control.
- .3 Section 01 61 00 - Common Product Requirements.
- .4 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .5 Section 01 78 00 - Closeout Submittals.
- .6 Section 07 62 00 – Sheet Metal Flashing and Trim.

1.3 **REFERENCES**

- .1 Canadian General Standards Board (CGSB).
 - .1 CAN/CGSB-37.4, Fibrated, Cutback Asphalt, Lap Cement for Asphalt Roofing.
 - .2 CAN/CGSB-37.5, Cutback Asphalt Plastic Cement.
 - .3 CAN/CGSB-51.32, Sheathing, Membrane, Breather Type.
 - .4 CAN/CGSB-51.34, Vapour Barrier Polyethylene Sheet, for Use in Building Construction.
- .2 Canadian Roofing Contractors' Association (CRCA).
 - .1 CRCA Roofing Specification Manual.
- .3 Canadian Standards Association (CSA).
 - .1 CAN/CSA-A123.1/A123.5, Asphalt Shingles Made From Organic Felt and Surfaced With Mineral Granules/Asphalt Shingles Made From Glass Felt and Surfaced With Mineral Granules.
 - .2 CSA A123.2, Asphalt-Coated Roofing Sheets.
 - .3 CAN/CSA-A123.3, Asphalt Saturated Organic Roofing Felt.
 - .4 CAN3-A123.51, Asphalt Shingle Application on Roof Slopes 1:3 and Steeper.
 - .5 CAN3-A123.52, Asphalt Shingle Application on Roof Slopes 1:6 to Less Than 1:3.
 - .6 CSA B111, Wire Nails, Spikes and Staples.

- .4 National Research Council Canada (NRC)/Institute for Research in Construction (IRC) - Canadian Construction Materials Centre (CCMC).
 - .1 CCMC, Registry of Product Evaluations.

1.4 EXTRA MATERIALS

- .1 Provide maintenance materials in accordance with Section 01 78 00 - Closeout Submittals.
- .2 All unused shingles remain property of owner.

1.5 SUBMITTALS

- .1 Manufacturer's Instructions: Provide to indicate special handling criteria, installation sequence, cleaning procedures.
- .2 Submit product data sheets for asphalt shingles. Include:
 - .1 Product characteristics.
 - .2 Performance criteria.
 - .3 Installation instructions.
 - .4 Limitations.
 - .5 Colour and finish.
- .3 Submit duplicate samples of full size specified shingles.

1.6 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, handle, store and protect materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Provide and maintain dry, off-ground weatherproof storage.
- .3 Remove only in quantities required for same day use.

1.7 WASTE MANAGEMENT AND DISPOSAL

- .1 Place materials defined as hazardous or toxic in designated containers.
- .2 Ensure emptied containers are sealed and stored safely for disposal away from children.
- .3 Use the least toxic sealants, and adhesives necessary to comply with requirements of this section.
- .4 Close and seal tightly. Remove from site and dispose of all packaging materials at appropriate recycling facilities.
- .5 Place used hazardous sealant tubes and adhesive containers in areas designated for hazardous materials.

1.8 WARRANTY

- .1 Provide a written guarantee, signed and issued in the name of the owner, stating the fiberglass-reinforced asphalt shingles shall remain free from defects in materials and workmanship for a period of twenty five (25) years from the date of Substantial Completion.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Fiberglass-reinforced asphalt shingles: to CSA A123.1/A123.5.
 - .1 Type: per drawing A1.9.
- .2 Ice and water shield.
 - .1 Type: per drawing A1.9.
- .3 Continuous Ridge Vent:
 - .1 Type: per drawing A1.9.
- .4 Cement: Plastic cement: to CAN/CGSB-37.5.
- .5 Nails: to CSA B111, of galvanized steel, sufficient length to penetrate 19 mm into deck.

PART 3 EXECUTION

3.1 REMOVAL OF EXISTING ROOFING

- .1 Remove existing roofing, flashings and underlay, and expose sheathing or shingle lath of roof.
- .2 Withdraw existing shingle and flashing nails, set those which break off. Leave surfaces free from dirt and loose material.
- .3 Owner's Representative to inspect roof sheathing. Take up, cut out, portion of sheathing boards affected by fungal or insect attack as directed on site by Owner's Representative.
- .4 Replace cut out portions of sheathing or lath with sheathing of equal sectional dimensions, and specified grade. Seat each end of board on rafter/truss, with 25mm bearing, and secure to rafter/truss.

3.2 APPLICATION

- .1 Do fiberglass-reinforced asphalt shingle work in accordance with CAN3-A123.51/CAN3-A123.52, NBC/CRCA Specification, except where specified otherwise and to manufacturer's instructions.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016

Section 07 31 13.13 – Fiberglass-Reinforced Asphalt Shingles

Page 4 of 4

- .2 Install ice and water shield underlayment over the entire roof area.
- .3 Pre-finished metal fascia per detail.
- .4 Install bottom step flashing (soaker base flashing) interleaved between shingles at vertical junctions.
- .5 Install fiberglass-reinforced asphalt shingles on roof slopes 1:3 and steeper in accordance with CAN3-A123.51 supplemented as follows:
- .6 Install fiberglass-reinforced asphalt shingles on roof slopes 1:6 to less than 1:3 in accordance with CAN3-A123.52 supplemented as follows.

3.3 PROTECTION

- .1 Protect installed products and components from damage during construction.
- .2 Repair damage to adjacent materials caused by asphalt shingles installation.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .2 Section 06 10 00 – Rough Carpentry.
- .3 Section 07 62 00 – Sheet Metal Flashing and Trim.
- .4 Section 07 92 00 - Joint Sealants.
- .5 Section 07 27 00.01 – Air Barriers – Descriptive or Proprietary.
- .6 Section 07 21 13 – Board Insulation.

1.2 **REFERENCES**

- .1 American National Standards Institute (ANSI)
 - .1 ANSI A135.6, Hardboard Siding Standard.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-11.3, Hardboard.
 - .2 CAN/CGSB-11.5, Hardboard, Precoated, Factory Finished, for Exterior Cladding.
 - .3 CAN/CGSB-11.6, Installation of Exterior Hardboard Cladding.
 - .4 CAN/CGSB-51.32, Sheathing, Membrane, Breather Type.
- .3 Canadian Standards Association (CSA)
 - .1 CSA B111, Wire Nails, Spikes and Staples.
 - .2 CSA O121, Douglas Fir Plywood.
 - .3 CSA O151, Canadian Softwood Plywood.
- .4 National Lumber Grading Authority (NLGA)
 - .1 NLGA Standard Grading Rules for Canadian Lumber.

1.3 **SUBMITTALS**

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data sheet.
 - .2 Submit copies of WHMIS MSDS - Material Safety Data Sheets. Indicate VOC's for caulking materials during application and curing.
- .2 Submit duplicate 300 x 300 mm size profile specified.

- .3 Submit manufacturer's installation instructions.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver, handle, store and protect materials in accordance with Section 01 61 00 – Common Product Requirements.
- .2 Deliver siding suitable packaged to avoid damage to finished surface.
- .3 Store in an unheated structure or under cover until application. Siding may be temporarily stored outside if at least 4 inches off the ground and on a flat, well drained surface protected from moisture with a shed pack or waterproof cover.

1.5 QUALITY ASSURANCE

- .1 Provide Certificate of Quality Compliance from siding manufacturer upon completion of fabrication.
- .2 Provide Certificate of Quality Compliance upon satisfactory completion of installation.

1.6 WARRANTY

- .1 Warranty Period: 15 years against cracking, peeling, blistering, chalking, loss of coating adhesion, yellowing with age, and no damage caused by rinse cleaning surface dirt. Warranty to commence at date of Substantial Completion.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Engineering Wood Siding and Trims: Per Drawing A1.9.
- .2 Strapping: Softwood Lumber, kiln dried treated with brush applied wood preservative, size 38 x 89 spaced 400 mm o.c.
- .3 Nails: Mechanically galvanized, to securely and rigidly retain the work permanently in position, pre-finished baked on coating to match siding finish. Nails 64 mm long for siding and 83 mm for trims.
- .4 Exterior Sheathing Membrane: CAN/CGSB 51.32M, Spun bonded olefin sheeting, conforming to ASTM D3575, single ply laminated and coated.
- .5 Sealant: Thermoplastic type, color to exactly match siding.

- .6 Concealed Flashings: 0.4 mm thick galvanized steel.

2.2 FINISH

- .1 Pre-finish color: Thermoplastic acrylic latex emulsion, factory coated under controlled environment conditions by a modified vacuum coat method, one prime coat and one finish coat, applied to all board surfaces, minimum 0.15 mm dry film thickness.
 - .1 Standard color or custom color from manufacturers range of colors.
 - .2 Touch-Up Paint: Thermoplastic acrylic latex emulsion, same type and color as siding.

PART 3 EXECUTION

3.1 EXAMINATION

- .1 Verify that substrate surfaces and wall openings are ready to receive work.

3.2 PREPARATION

- .1 Install metal flashing continuous over window and other openings. Secure in position tight to wall sheathing.
- .2 Install 51 mm board insulation.
- .3 Install strapping at 400 mm o.c.
- .4 Install pre-fabricated starter strips, Cor-a-vent system per drawings.
- .5 Apply sealant around window, door and other opening frames.

3.3 INSTALLATION

- .1 Install siding and accessories to manufacturer's instructions.
- .2 Install Cor-a-vent system.
- .3 Install siding for natural watershed.
- .4 Install siding in straight aligned lengths, set level with plumb ends and corners.
- .5 Install hardboard to CGSB11-GP-6M and manufacturers' instructions.
- .6 Achieve siding joints no less than 800 mm apart in adjoining boards and distribute evenly over wall surface.
- .7 Install corner trims, battens, closures, etc.

- .8 Fasten siding securely to wood batten substrate. Ensure strapping is secured into the structural wood framing members a minimum of 64 mm of per siding manufacturer's specifications.
- .9 Face nail 25 mm from bottom of siding board directly into wood strapping, drive nail head just flush with siding surface; do not indent or penetrate painted coating.

3.4 INCIDENTAL SITE FINISHING

- .1 Carefully set exposed nails flush with siding coating.
- .2 Touch-up blemished siding materials to match siding color.

3.5 CLEANING

- .1 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 06 10 00 – Rough Carpentry.
- .4 Section 07 92 00 – Joint Sealants.
- .5 Section 07 31 13.13 – Fiberglass – Reinforced Asphalt Shingles.
- .6 Section 07 46 23 – Wood Siding Pre-finished.

1.2 **REFERENCES**

- .1 The Aluminum Association Inc. (AA)
 - .1 Aluminum Sheet Metal Work in Building Construction.
 - .2 AA DAF45, Designation System for Aluminum Finishes.
- .2 American Society for Testing and Materials (ASTM International)
 - .1 ASTM A653/A653M, Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - .2 ASTM A792/A792M, Standard Specification for Steel Sheet, 55% Aluminum-Zinc Alloy-Coated by the Hot-Dip Process.
 - .3 ASTM D523, Standard Test Method for Specular Gloss.
 - .4 ASTM D822, Standard Practice for Filtered Open-Flame Carbon-Arc Exposures of Paint and Related Coatings.
- .3 Canadian General Standards Board (CGBS)
 - .1 CAN/CGSB-37.5, Cutback Asphalt Plastic Cement.
- .4 Canadian Roofing Contractors Association (CRCA)
 - .1 Roofing Specifications Manual.
- .5 Canadian Standards Association (CSA International)
 - .1 CSA A123.3, Asphalt Saturated Organic Roofing Felt.
 - .2 CSA B111, Wire Nails, Spikes and Staples.

1.3 **SAMPLES**

- .1 Submit duplicate 50 x 50 mm samples of each type of sheet metal material, colour and finish.

PART 2 **PRODUCTS**

2.1 **SHEET METAL MATERIALS**

- .1 Aluminum-zinc alloy coated steel sheet: to ASTM A792/A792M, commercial quality, grade 33 with AZ150 coating, regular spangle surface, 0.60 mm base metal thickness. Pre-painted to CGSB –GP-71.

2.2 **PREFINISHED STEEL SHEET**

- .1 Prefinished sheet with factory applied polyvinylidene fluoride.
 - .1 Class F1S
 - .2 Colour as selected by Owner's Representative from manufacturer's standard range.
 - .3 Specular gloss: 30 units +/- 5 in accordance with ASTM D523.
 - .4 Coating thickness: not less than 22 micrometres.
 - .5 Resistance to accelerated weathering for caulk rating of 8, colour fade 5 units or less and erosion rate less than 20 % to ASTM D822 as follows:
 - .1 Outdoor exposure period 2500 hours.
 - .2 Humidity resistance exposure period 5000 hours.

2.3 **ACCESSORIES**

- .1 Isolation coating: alkali resistant bituminous paint.
- .2 Plastic cement: to CAN/CGSB 37.5.
- .3 Underlay for metal flashing: No. 15 perforated asphalt felt to CSA A123.3, or as noted.
- .4 Sealants: Section 07 92 00 – Joint Sealants.
- .5 Cleats: of same material, and temper as sheet metal, minimum 50 mm wide. Thickness same as sheet metal being secured.
- .6 Fasteners: of same material as sheet metal, to CSA B111, ring thread flat head roofing nails of length and thickness suitable for metal flashing application.
- .7 Washers: of same material as sheet metal, 1 mm thick with rubber packings.
- .8 Touch-up paint: as recommended by prefinished material manufacturer.

2.4 **FABRICATION**

- .1 Fabricate metal flashings and other sheet metal work in accordance with applicable CRCA 'FL' series details as indicated.
- .2 Fabricate aluminum flashings and other sheet aluminum work in accordance with Aluminum Association Aluminum Sheet Metal Work in Building Construction.

- .3 Form pieces in 2400 mm maximum lengths. Make allowance for expansion at joints.
- .4 Hem exposed edges on underside 12 mm. Mitre and seal corners with sealant.
- .5 Form sections square, true and accurate to size, free from distortion and other defects detrimental to appearance or performance.
- .6 Apply isolation coating to metal surfaces to be embedded in concrete or mortar.

2.5 METAL FLASHINGS

- .1 Form flashings, copings and fascias to profiles indicated of 0.60 mm thick prefinished steel. Form breaks as indicated.
- .2 Set all roof fascia, soffit flashings in full adhesive.

PART 3 EXECUTION

3.1 INSTALLATION

- .1 Install sheet metal work in accordance with CRCA FL series details and as detailed.
- .2 Use concealed fastenings except where approved before installation.
- .3 Provide underlay under sheet metal. Secure in place and lap joints 100 mm.
- .4 Counterflash bituminous flashings at intersections of roof with vertical surfaces and curbs. Flash joints using S-lock forming tight fit over hook strips, as detailed.
- .5 Lock end joints and caulk with sealant.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 07 92 00 - Joint Sealants.
- .4 Section 08 71 00 - Door Hardware.
- .5 Section 08 80 50 – Glazing.
- .6 Section 09 91 23 - Interior Painting.

1.2 REFERENCES

- .1 American Society for Testing and Materials (ASTM)
 - .1 ASTM A653/A653M, Specification for Steel Sheet Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvanized) by the Hot Dip Process.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-1.181, Ready-Mixed Organic Zinc-Rich Coating.
 - .2 CGSB 41-GP-19Ma, Rigid Vinyl Extrusions for Windows and Doors.
- .3 Canadian Standards Association (CSA)
 - .1 G40.20/G40.21, General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel.
 - .2 CSA W59, Welded Steel Construction (Metal Arc Welding).
- .4 Canadian Steel Door Manufacturers' Association, (CSDMA).
 - .1 CSDMA, Specifications for Commercial Steel Doors and Frames.
 - .2 CSDMA, Recommended Selection and Usage Guide for Commercial Steel Doors.
- .5 National Fire Protection Association (NFPA)
 - .1 NFPA 80, Standard for Fire Doors and Fire Windows.
 - .2 NFPA 252, Standard Methods of Fire Tests of Door Assemblies.
- .6 Underwriters' Laboratories of Canada (ULC)
 - .1 CAN4-S104M, Fire Tests of Door Assemblies.
 - .2 CAN4-S105M, Fire Door Frames Meeting the Performance Required by CAN4-S104.
 - .3 CAN/ULC-S701, Thermal Insulation, Polystyrene, Boards and Pipe Covering.

- .4 CAN/ULC-S702, Thermal Insulation, Mineral Fibre, for Buildings.
- .5 CAN/ULC-S704, Thermal Insulation, Polyurethane and Polyisocyanurate Boards, Faced.

1.3 DESIGN REQUIREMENTS

- .1 Design door assembly to withstand minimum 1,000,000 swing cycles in accordance with ANSI A151.1, with no failure of any design features of the door.
- .2 Design exterior frame assembly to accommodate to expansion and contraction when subjected to minimum and maximum surface temperature of -35°C to 35°C.
- .3 Maximum deflection for exterior steel entrance screens under wind load of 1.2 kPa not to exceed 1/175th of span.
- .4 Steel fire rated doors and frames: labelled and listed by an organization accredited by Standards Council of Canada in conformance with CAN4-S104 and NFPA 252 for ratings specified or indicated.
- .5 Provide fire labelled frames for openings requiring fire protection ratings. Test products in conformance with CAN4-S104 and NFPA 252 and listed by nationally recognized agency having factory inspection services and construct as detailed in Follow-Up Service Procedures/Factory Inspection Manuals issued by listing agency to individual manufacturers.

1.4 SUBMITTALS

- .1 Indicate each type frame material, core thickness, reinforcements, glazing stops, location of anchors and exposed fastenings and reinforcing firerating and finishes.
- .2 Include schedule identifying each unit, with door marks and numbers relating to numbering on drawings and door schedule.
- .3 Submit one 300 x 300 mm top corner sample of each type door.
- .4 Submit one 300 x 300 mm corner sample of each type of frame.
 - .1 Show butt cutout, glazing stops.

1.5 DELIVERY STORAGE AND HANDLING

- .1 Deliver, store, handle and protect frames in accordance with Section 01 61 00- Common Product Requirements.
- .2 Deliver, handle and store frames at the job site in such a manner as to prevent damage.
- .3 Store frames under cover in a vertical position on blocking, clear of floor and with blocking between frames to permit air circulation.

1.6 QUALITY ASSURANCE

- .1 Conform to requirements to ANSI A117.1
- .2 Company specializing in manufacturing products specified with a minimum of five (5) years documented experience.

1.7 WARRANTY

- .1 Provide a written warranty for work of this section from manufacturer for failure due to defective materials and from contractor for failure due to defective installation workmanship, for one (1) year respectively from the date of Substantial Completion.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Hot dipped galvanized steel sheet: to ASTM A653/A653M, ZF75, minimum base steel thickness in accordance with CSDMA Table 1 - Thickness for Component Parts.
- .2 Reinforcement channel: to CSA G40.20/G40.21, Type 44W, coating designation to ASTM A653/A653M, ZF75.

2.2 FRAMES FABRICATION GENERAL

- .1 Fabricate frames in accordance with CSDMA specifications.
- .2 Fabricate frames to profiles and maximum face sizes as indicated.
- .3 Exterior frames: 1.2 mm welded, thermally broken type construction.
- .4 Interior frames: 1.2 mm welded type construction.
- .5 Blank, reinforce, drill and tap frames for mortised, template hardware, and electronic hardware using templates provided by finish hardware supplier. Reinforce frames for surface mounted hardware.
- .6 Protect mortised cutouts with steel guard boxes.
- .7 Prepare frame for door silencers, 3 for single door, 2 at head for double door.
- .8 Manufacturer's nameplates on frames and screens are not permitted.
- .9 Conceal fastenings except where exposed fastenings are indicated.
- .10 Provide factory-applied touch up primer at areas where zinc coating has been removed during fabrication.
- .11 Insulate exterior frame components with polyurethane insulation.

2.3 FRAME ANCHORAGE

- .1 Shim and anchor new doors in accordance with CAN/CSA A440.4.
- .2 Provide appropriate anchorage to floor and wall construction.
- .3 Locate each wall anchor immediately above or below each hinge reinforcement on hinge jamb and directly opposite on strike jamb.
- .4 Provide 2 anchors for rebate opening heights up to 1520 mm and 1 additional anchor for each additional 760 mm of height or fraction thereof.
- .5 Locate anchors for frames in existing openings not more than 150 mm from top and bottom of each jambs and intermediate at 660 mm o.c. maximum.

2.4 FRAMES: WELDED TYPE

- .1 Welding in accordance with CSA W59.
- .2 Accurately mitre or mechanically joint frame product and securely weld on inside of profile.
- .3 Cope accurately and securely weld butt joints of mullions, transom bars, centre rails and sills.
- .4 Grind welded joints and corners to a flat plane, fill with metallic paste and sand to uniform smooth finish.
- .5 Securely attach floor anchors to inside of each jamb profile.
- .6 Weld in 2 temporary jamb spreaders per frame to maintain proper alignment during shipment.
- .7 Frames to be thermally broken per door schedule.

PART 3 EXECUTION

3.1 INSTALLATION GENERAL

- .1 Install frames to CSDMA Installation Guide.

3.2 FRAME INSTALLATION

- .1 Set frames plumb, square, level and at correct elevation.
- .2 Secure anchorages and connections to adjacent construction.
- .3 Brace frames rigidly in position while building-in. Install temporary horizontal wood spreader at third points of door opening to maintain frame width. Provide vertical

support at centre of head for openings over 1200 mm wide. Remove temporary spreaders after frames are built-in.

- .4 Make allowances for deflection of structure to ensure structural loads are not transmitted to frames.
- .5 Caulk perimeter of frames between frame and adjacent material.

3.3 DOOR INSTALLATION

- .1 Install doors and hardware in accordance with hardware templates and manufacturer's instructions and Section 08 71 00 - Door Hardware.
- .2 Provide even margins between doors and jambs and doors and finished floor as follows.
 - .1 Hinge side: 1.0 mm.
 - .2 Latch side and head: 1.5 mm.
 - .3 Finished floor: 13 mm.
- .3 Adjust operable parts for correct function.

3.4 FINISH REPAIRS

- .1 Touch up with primer finishes damaged during installation.
- .2 Fill exposed frame anchors and surfaces with imperfections with metallic paste filler and sand to a uniform smooth finish.

3.5 GLAZING

- .1 Install glazing for doors and frames in accordance with Section 08 80 50 - Glazing.

3.6 COMMISSIONING

- .1 Contractor to instruct maintenance personnel in operation and maintenance of doors and hardware.
- .2 Confirm operation and function for all doors and hardware.
- .3 Commissioning will be witnessed by Owner's Representative and Certificate will be signed by Contractor and Owner's Representative.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 01 78 00 - Closeout Submittals.
- .4 Section 07 26 00 –Vapour Retarders.
- .5 Section 07 92 00 - Joint Sealants.
- .6 Section 08 80 50 - Glazing

1.2 REFERENCES

- .1 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-79.1, Insect Screens.
- .2 Canadian Standards Association (CSA)
 - .1 CSA-A440-00/A440.1, A440, Windows / Special Publication A440.1, User Selection Guide to CSA Standard A440, Windows.
 - .2 CAN/CSA-Z91, Health and Safety Code for Suspended Equipment Operations.

1.3 SUBMITTALS

- .1 Indicate materials and details in scale full size for head, jamb and sill, profiles of components, interior and exterior trim. Junction between combination units, elevations of unit, anchorage details, location of isolation coating, description of related components and exposed finishes fasteners, and caulking. Indicate location of manufacturer's nameplates.
- .2 Shop drawings to include continuation of air barrier and vapour barrier between wall assembly and vinyl window.
- .3 Submit one complete full size window sample of each type window.
- .4 Include frame, sash, sill, glazing and weatherproofing method, insect screens, surface finish and hardware. Show location of manufacturer's nameplates.
- .5 Include 150 mm long samples of head, jamb, sill, meeting rail, mullions to indicate profile.

1.4 TEST REPORTS

- .1 Submit test reports from approved independent testing laboratories, certifying compliance with specifications, for:
 - .1 Windows classifications
 - .2 Air tightness
 - .3 Water tightness
 - .4 Wind load resistance
 - .5 Condensation resistance
 - .6 Forced entry resistance
 - .7 Insect screens
 - .8 Glazing
 - .9 Safety drop - vertical sliding windows only
 - .10 Ease of operation - windows with operable lights
 - .11 Sash pull-off - vinyl windows

1.5 WARRANTY

- .1 Provide a written warranty for work under this Section from Manufacturer for failure due to defective materials and from Contractor for failure due to defective installation, workmanship for ten (10) years respectively from the date of Substantial Completion.

1.6 CLOSEOUT SUBMITTALS

- .1 Provide operation and maintenance data for windows for incorporation into manual specified in Section 01 78 00 - Closeout Submittals.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Materials: to CSA-A440/A440.1 supplemented as follows:
- .2 All vinyl windows by same manufacturer. Acceptable product “Series 350” by Pella. See window schedule on drawing A1.8 for sizes and types.
- .3 Sash: vinyl.
- .4 Main frame: vinyl, thermally broken.
- .5 Glass: in accordance with Section 08 80 50 - Glazing.
- .6 Screens: to CAN/CGSB-79.1.
 - .1 Insect screening mesh: count 18 x 14
 - .2 Fasteners: tamper proof

- .3 Screen frames: aluminum, colour to match window frames
- .4 Mount screen frames for exterior replacement.
- .5 Provide full insect screens to cover entire window

2.2 WINDOW TYPE AND CLASSIFICATION

- .1 Types:
 - .1 Single hung, top vented, bottom position fixed, insulating glass.
 - .2 Single hung, bottom vented, top position fixed, insulating glass.
 - .3 Fixed: with insulating glass.
 - .4 Screens: screens as indicated.
- .2 Classification rating: to CSA-A440/A440.1 for various regions of Newfoundland and Labrador as follows:
 - .1 St. Anthony A3, B6, C4, I40, F1, S1
- .3 Energy ratings: windows to be Energy Star certified to Natural Resources Canada Climate Zones for various regions of Newfoundland and Labrador as follows:
 - .1 Northern part of Northern Peninsula and all of Labrador
 - .1 Zone 3 (\geq 6000 HDDs)

2.3 FABRICATION

- .1 Fabricate in accordance with CSA-A440/A440.1 supplemented as follows:
- .2 Fabricate units square and true with maximum tolerance of plus or minus 1.5 mm for units with a diagonal measurement of 1800 mm or less and plus or minus 3.0 mm for units with a diagonal measurement over 1800 mm.
- .3 Face dimensions detailed are maximum permissible sizes.
- .4 Brace frames to maintain squareness and rigidity during shipment and installation.

2.4 VINYL FINISHES

- .1 Vinyl finishes: in accordance with CSA-A440/A440.1, including appendices.

2.5 GLAZING

- .1 Glaze windows in accordance with CSA-A440/A440.1 and Drawing A1.8, window schedule.

2.6 HARDWARE

- .1 Hardware:
 - .1 stainless steel or white bronze trimline camlocks to provide security and permit easy operation of units.

- .2 Counter balance: stainless steel coil balance hardware.
- .2 Where windows latching devices are located in excess of 1600 mm above finished floor level:
 - .1 Equip vertical sliding units with ring pull at top sash. Provide operating pole of length required, complete with appropriate tip to suit ring pull. Provide one (1) pole for each room where vent sash occurs.

2.7 AIR BARRIER AND VAPOUR RETARDER

- .1 Provide low expanding, single component polyurethane foam sealant installed at head, jamb and sill perimeter of window for sealing to building air barrier, vapour retarder and window frame. Foam sealant width to be adequate to provide required air tightness and vapour diffusion control to building air barrier and vapour retarder foam interior.

PART 3 EXECUTION

3.1 WINDOW INSTALLATION

- .1 Install in accordance with CSA-A440.
- .2 Arrange components to prevent abrupt variation in colour.
- .3 Install shims between windows and building frame at each installation screw location. Shim and fasten windows in accordance with manufacturer's recommendations and CAN/CSA A440.4.

3.2 CAULKING

- .1 Seal joints between windows and window sills with sealant. Caulk between sill upstand and window-frame. Caulk butt joints in continuous sills.
- .2 Apply sealant in accordance with Section 07 92 00 - Joint Sealants. Conceal sealant within window units except where exposed use is permitted by Owner's Representative.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 61 00 - Common Product Requirements.
- .3 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .4 Section 01 78 00 - Closeout Submittals.
- .5 Section 08 11 14- Metal Doors & Frames.
- .6 Section 08 14 16 – Flush Wood Doors.

1.2 REFERENCES

- .1 American National Standards Institute (ANSI) / Builders Hardware Manufacturers Association (BHMA)
 - .1 ANSI/BHMA A156.1, American National Standard for Butts and Hinges.
 - .2 ANSI/BHMA A156.2, Bored and Preassembled Locks and Latches.
 - .3 ANSI/BHMA A156.3, Exit Devices.
 - .4 ANSI/BHMA A156.4, Door Controls - Closers.
 - .5 ANSI/BHMA A156.5, Auxiliary Locks and Associated Products.
 - .6 ANSI/BHMA A156.6, Architectural Door Trim.
 - .7 ANSI/BHMA A156.8, Door Controls - Overhead Stops and Holders.
 - .8 ANSI/BHMA A156.12, Interconnected Locks and Latches.
 - .9 ANSI/BHMA A156.13, Mortise Locks and Latches Series 1000.
 - .10 ANSI/BHMA A156.14, Sliding and Folding Door Hardware.
 - .11 ANSI/BHMA A156.15, Release Devices - Closer Holder, Electromagnetic and Electromechanical.
 - .12 ANSI/BHMA A156.16, Auxiliary Hardware.
 - .13 ANSI/BHMA A156.17, Self-closing Hinges and Pivots.
 - .14 ANSI/BHMA A156.18, Materials and Finishes.
 - .15 ANSI/BHMA A156.19, Power Assist and Low Energy Power - Operated Doors.
- .2 Canadian Steel Door and Frame Manufacturers' Association (CSDFMA)
 - .1 CSDFMA Recommended Dimensional Standards for Commercial Steel Doors and Frames.

1.3 SUBMITTALS

- .1 Product Data:

- .1 Submit manufacturer's printed product literature, specifications and data sheet.
- .2 Samples:
 - .1 Identify each sample by label indicating applicable specification paragraph number, brand name and number, finish and hardware package number.
 - .2 After approval samples will be returned for incorporation in the Work.
- .3 Hardware List:
 - .1 Submit contract hardware list.
 - .2 Indicate specified hardware, including make, model, material, function, size, finish and other pertinent information.
- .4 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.
- .5 Closeout Submittals
 - .1 Provide operation and maintenance data for door closers, locksets, door holders electrified hardware and fire exit hardware for incorporation into manual specified in Section 01 78 00 - Closeout Submittals.
- 1.4 MAINTENANCE MATERIALS**
 - .1 Provide maintenance materials in accordance with Section 01 78 00 - Closeout Submittals.
 - .2 Supply two sets of wrenches for door closers, locksets and fire exit hardware.
- 1.5 WARRANTY**
 - .1 Provide a written manufacturer's warranty for work of this Section for failure due to defective materials for ten (10) years, dated from substantial completion certificate.
 - .2 Provide a written Contractor's warranty for work of this Section for failure due to defective installation workmanship for one (1) year, dated from submittal completion certificate.
- 1.6 QUALITY ASSURANCE**
 - .1 Regulatory Requirements:
 - .1 Hardware for doors in fire separations and exit doors certified by a Canadian Certification Organization accredited by Standards Council of Canada.
 - .2 Only products meeting ANSI/BHMA standards are acceptable. Items that are equal in design, function and quality will be accepted upon approval of the Owner's Representative.
 - .3 Only recognized contract hardware distributors will be considered for the work of this section. The distributor shall have on staff a qualified Architectural Hardware Consultant

recognized by the Door and Hardware Institute or a person with equivalent qualifications to assist installers and direct detailing, processing and delivery of material, and certify installation acceptance.

1.7 DELIVERY, STORAGE, AND HANDLING

- .1 Deliver, store, handle and protect materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Store finishing hardware in locked, clean and dry area.
- .3 Package each item of hardware including fastenings, separately or in like groups of hardware, label each package as to item definition and location.

1.8 MAINTENANCE SERVICE

- .1 Provide maintenance service for one year during warranty period to maintain all barrier free entrance automatic operators as follows:
 - .1 Qualified service personal approved by manufacturer of operators.
 - .2 Site inspection every three months will all necessary adjustment made during this visit. Separate warranty service calls, if required, will only qualify as an inspection if time of call is close to the three month intervals.
 - .3 Make detailed reports of each visit and copy to Owner and Engineer.
 - .4 Cost of this service will be included as part of this Section and is not covered by any allowance amount.

PART 2 PRODUCTS

2.1 HARDWARE ITEMS

- .1 Only door locksets and latches listed on ANSI/BHMA Standards list are acceptable for use on this project.
- .2 Use one manufacturer's products only for similar items.

2.2 DOOR HARDWARE

- .1 Per hardware schedule listed on drawings.

2.3 FASTENINGS

- .1 Use only fasteners provided by manufacturer. Failure to comply may void warranties and applicable licensed labels.
- .2 Supply screws, bolts, expansion shields and other fastening devices required for satisfactory installation and operation of hardware.

- .3 Exposed fastening devices to match finish of hardware.
- .4 Where pull is scheduled on one side of door and push plate on other side, supply fastening devices, and install so pull can be secured through door from reverse side. Install push plate to cover fasteners.
- .5 Use fasteners compatible with material through which they pass.

2.4 KEYING

- .1 Door locks to be master keyed as directed. Prepare detailed keying schedule in conjunction with Owner's Representative and owner.
- .2 Provide keys in triplicate for every lock in this Contract.
- .3 Provide construction cores.
- .4 Provide all permanent cores and keys to Owner's Representative.

2.5 FINISHES

- .1 Following finishes are indicated in hardware groups.

BHMA	CAN MATERIAL	FINISH
626	C26D Brass/Bronze	Satin Chrome
628	C28 Aluminum	Satin Alum, Anodized
630	C32D Stainless Steel	Satin Stainless Steel
652	C26D Steel	Plated Satin Chrome
689	Al All	Painted Aluminum
	Alum Aluminum	Mill Finish
	TMDFF (to match door and frame finish).	

2.6 ABBREVIATIONS

ALD	Aluminum Door and Frame
ATMS STMS	Arm/strike To Template with Machine Screws
ASB	Arm Complete with Sex Bolts
BC	Back Check
C to C, C/L	Centerline to Centerline
Cyl	Cylinder (of a lock)
CMK	Construction Master Key
Deg.	Degree (of opening)
DEL	Delayed Action
FBB or BB	Ball bearing hinge

PART 3 **EXECUTION**

3.1 **MANUFACTURER'S INSTRUCTIONS**

- .1 Compliance: comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.
- .2 Furnish metal door and frame manufacturers with complete instructions and templates for preparation of their work to receive hardware.
- .3 Furnish manufacturers' instructions for proper installation of each hardware component.

3.2 **INSTALLATION**

- .1 Install hardware to standard hardware location dimensions in accordance with Canadian Metric Guide for Steel Doors and Frames (Modular Construction) prepared by Canadian Steel Door and Frame Manufacturers' Association.
- .2 Where door stop contacts door pulls, mount stop to strike bottom of pull.
- .3 Install key control cabinet.
- .4 Use of "quick" type fasteners, unless specifically supplied by manufacturer, is unacceptable.
- .5 Remove construction when directed by Owner's Representative; install permanent cores and check operation of locks.

3.3 **EXAMINATION**

- .1 Visit site prior to start of installation of hardware.
- .2 Visit will include examination of openings, site conditions and materials for conditions that prevent proper application of finish hardware.
- .3 Installation will imply conditions for installation acceptable hardware contractor to accept responsibility.

3.4 **FIELD QUALITY CONTROL**

- .1 Hardware contractor to have a qualified AHC representative from the manufacturer/supplier on site at Substantial Completion Inspection and at commissioning of the finished hardware. Cost of the visits to be included in contract.

3.5 **ADJUSTING**

- .1 Adjust door hardware, operators, closures and controls for optimum, smooth operating condition, safety and for weather tight closure.

- .2 Lubricate hardware, operating equipment and other moving parts.
- .3 Adjust door hardware to provide tight fit at contact points with frames.
- .4 Where hardware is found defective, repair or replace or correct as desired by inspection reports.

3.6 CLEANING

- .1 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .2 Clean hardware with damp rag and approved non-abrasive cleaner, and polish hardware in accordance with manufacture's instructions.
- .3 Remove protective material from hardware items where present.
- .4 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

3.7 PROTECTION

- .1 All hardware shall be protected against damage from paint, plaster or other defacing materials. Whenever possible manufacturers protective covering when applied, shall not be removed until final project cleaning takes place. Material not protected by manufacture shall be covered or removed from door during painting or any other adjustments that can cause damage to hardware.

3.8 HARDWARE GROUPS

- .1 Per door schedule on drawings.

3.9 COMMISSIONING

- .1 Site inspection or visit at Substantial Completion and training follow up and inspection at commissioning as directed by Owner's Representative.
- .2 Provide 10 month warranty service.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 45 00 - Quality Control.
- .3 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .4 Section 01 78 00 - Closeout Submittals.
- .5 Section 07 82 00 – Joint Sealants.
- .6 Section 08 11 14 – Metal Doors & Frames.
- .7 Section 08 53 13 – Vinyl Windows.

1.2 **REFERENCES**

- .1 American National Standards Institute (ANSI).
 - .1 ANSI/ASTM E330, Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference.
- .2 American Society for Testing and Materials (ASTM)
 - .1 ASTM C542, Specification for Lock-Strip Gaskets.
 - .2 ASTM D2240, Test Method for Rubber Property – Durometer Hardness.
- .3 Canadian General Standards Board (CGSB).
 - .1 CAN/CGSB-12.1, Tempered or Laminated Safety Glass.
 - .2 CAN/CGSB-12.3, Clear Float Glass
 - .3 CAN/CGSB-12.5, Mirrors, Silvered.
 - .4 CAN/CGSB-12.8, Insulating Glass Units.
 - .5 CAN/CGSB-12.11, Wired Safety Glass.
- .4 Canadian Standards Association (CSA).
 - .1 CSA A440.2, Energy Performance Evaluation of Windows and Sliding Glass Doors.
 - .2 CSA Certification Program for Windows and Doors.
- .5 Glass Association of North American (GANA)
 - .1 GANA Glazing Manual.
 - .2 GANA Laminated Glazing Reference Manual.

1.3 SYSTEM DESCRIPTION

- .1 Performance Requirements:
 - .1 Provide continuity of building enclosure vapour and air barrier using glass and glazing materials as follow:
 - .1 Utilize inner light of multiple light sealed units for continuity of air and vapour seal.
 - .2 Size glass to withstand wind loads, dead loads and positive and negative live loads as measured in accordance with ANSI/ASTM E330 and NBC latest edition.
 - .3 Limit glass deflection to 1/200 with full recovery of glazing materials.

1.4 SUBMITTALS

- .1 Product Data:
 - .1 Submit manufacturer's printed product literature, specifications and data sheet.
- .2 Manufacturer's Instructions:
 - .1 Submit manufacturer's installation instructions.
- .3 Closeout Submittals:
 - .1 Provide maintenance data including cleaning instructions for incorporation into manual specified in Section 01 78 00 - Closeout Submittals

1.5 QUALITY ASSURANCE

- .1 Perform work in accordance with GANA Glazing Manual and Laminated Glazing Reference Manual for glazing installation methods. Provide shop inspection and testing for glass.
- .3 Provide certificate of quality compliance from manufacturer.

1.6 WARRANTY

- .1 Provide ten (10) year warranty for glazing units from the date of Substantial Completion.

1.7 ENVIRONMENTAL REQUIREMENTS

- .1 Install glazing when ambient temperature is 10°C minimum. Maintain ventilated environment for 24 hours after application.
- .2 Maintain minimum ambient temperature before, during and 24 hours after installation of glazing compounds.

PART 2 **PRODUCTS**

2.1 **MATERIALS: SEALED INSULATING GLASS**

- .1 Insulating glass units: to CAN/CGSB-12.8, double unit, minimum 25 mm overall thickness (as per NBCC for window area and climatic conditions.)
 - .1 Glass: to CAN/CGSB-12.3
 - .2 Glass thickness: minimum 6 mm each light (as per NBCC calculations for window area and climatic conditions.)
 - .3 Inter-cavity space thickness: 13 mm.
 - .4 Glass coating: surface number 2 (inside surface of outer light), low “E”.
 - .5 Inert gas: argon.
 - .6 Light transmittance: minimum 0.70.

2.2 **MATERIALS**

- .1 Sealant: 07 92 00 – Joint Sealants.

2.3 **ACCESSORIES**

- .1 Setting blocks: Neoprene, 80-90 Shore A durometer hardness to ASTM D2240, minimum 100 mm x width of glazing rabbet space minus 1.5 mm x height.
- .2 Spacer shims: Neoprene, 50-60 Shore A durometer hardness to ASTM D2240, 75 mm long x one half height of glazing stop x thickness to suit application. Self adhesive on one face.
- .3 Glazing tape:
 - .1 Preformed butyl compound with integral resilient tube spacing device, 10-15 Shore A durometer hardness to ASTM D2240; coiled on release paper; black colour.
- .4 Glazing splines: resilient polyvinyl chloride, extruded shape to suit glazing channel retaining slot, colour as selected.
- .5 Glazing clips: manufacturer's standard type.
- .6 Lock-strip gaskets: to ASTM C542.

PART 3 **EXECUTION**

3.1 **MANUFACTURER’S INSTRUCTIONS**

- .1 Compliance: Comply with manufacturer's written data, including product technical bulletins, product catalogue installation instructions, product carton installation instructions, and data sheets.

3.2 EXAMINATION

- .1 Verify that openings for glazing are correctly sized and within tolerance.
- .2 Verify that surfaces of glazing channels or recesses are clean, free of obstructions, and ready to receive glazing.

3.3 PREPARATION

- .1 Clean contact surfaces with solvent and wipe dry.
- .2 Seal porous glazing channels or recesses with substrate compatible primer or sealer.
- .3 Prime surfaces scheduled to receive sealant.

3.4 INSTALLATION: EXTERIOR – WET/DRY METHOD (PREFORMED TAPE AND SEALANT)

- .1 Perform work in accordance with GANA Glazing Manual and GANA Laminated Glazing Reference Manual for glazing installation methods.
- .2 Cut glazing tape to length and set against permanent stops, 6 mm below sight line. Seal corners by butting tape and dabbing with sealant.
- .3 Apply heel bead of sealant along intersection of permanent stop with frame ensuring full perimeter seal between glass and frame to complete continuity of air and vapour seal.
- .4 Place setting blocks at 1/4 points, with edge block maximum 150 mm from corners.
- .5 Rest glazing on setting blocks and push against tape and heel of sealant with sufficient pressure to attain full contact at perimeter of light or glass unit.
- .6 Install removable stops with spacer strips inserted between glazing and applied stops 6 mm below sight line.
- .7 Fill gap between glazing and stop with sealant to depth equal to bite of frame on glazing, maximum 9 mm below sight line.
- .8 Apply cap head of sealant along void between stop and glazing, to uniform line, flush with sight line. Tool or wipe sealant surface smooth.

3.5 INSTALLATION: INTERIOR DRY METHOD (TAPE AND TAPE)

- .1 Perform work in accordance with GANA Glazing Manual and GANA Laminated Glazing Reference Manual for glazing installation methods.
- .2 Cut glazing tape to length and set against permanent stops, projecting 1.6 mm above sight line.
- .3 Place setting blocks at 1/4 with edge block maximum 150 mm from corners.

- .4 Rest glazing on setting blocks and push against tape with sufficient pressure to attain full contact at perimeter of light or glass unit.
- .5 Place glazing tape on free perimeter of glazing in same manner described in 3.4.3. Apply heel bead of sealant along intersection of permanent stop with frame ensuring full perimeter seal between glass and frame to complete continuity of air and vapour seal.
- .6 Install removable stop without displacement of tape. Exert pressure on tape for full continuous contact.
- .7 Knife trim protruding tape.

3.6 INSTALLATION: MIRRORS

- .1 Set mirrors with clips. Anchor rigidly to wall construction.
- .2 Set in frame.
- .3 Place plumb and level.

3.7 CLEANING

- .1 Perform cleaning after installation to remove construction and accumulated environmental dirt.
- .2 Remove traces of primer, caulking.
- .3 Remove glazing materials from finish surfaces.
- .4 Remove labels after work is complete.
- .5 Clean glass and mirrors using approved non-abrasive cleaner in accordance with manufacture's instructions.
- .6 Upon completion of installation, remove surplus materials, rubbish, tools and equipment barriers.

3.8 PROTECTION OF FINISHED WORK

- .1 After installation, mark light with an "X" by using removable plastic tape or paste. Do not mark heat absorbing or reflective glass units.
- .2 Repair damage to adjacent materials caused by glazing installation.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures
- .2 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .3 Section 06 10 00 - Rough Carpentry
- .4 Section 07 21 16 - Blanket Insulation
- .5 Section 07 84 00 – Firestopping.

1.2 REFERENCES

- .1 American Society for Testing and Materials, (ASTM)
 - .1 ASTM C475, Specification for Joint Compound and Joint Tape for Finishing Gypsum Board.
 - .2 ASTM C514, Specification for Nails for the Application of Gypsum Board.
 - .3 ASTM C840, Specification for Application and Finishing of Gypsum Board.
 - .4 ASTM C954, Specification for Steel Drill Screws for the Application of Gypsum Panel Products or Metal Plaster Bases to Steel Studs From 0.033 in. (0.84 mm) to 0.112 in. (2.84 mm) in Thickness.
 - .5 ASTM C1002, Specification for Steel Self-Piercing Tapping Screws for the Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs.
 - .6 ASTM C1047, Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base.
 - .7 ASTM C1280, Standard Specification for Application of Gypsum Sheathing.
 - .8 ASTM C1177/C1177M, Standard Specification for Glass Mat Gypsum Substrate for Use as Sheathing.
 - .9 ASTM C1178/C1178M, Standard Specification for Glass Mat Water-Resistant Gypsum Backing Board.
 - .10 ASTM C1396/C1396M, Standard Specification for Gypsum Wallboard.
- .2 Association of the Wall and Ceilings Industries International (AWCI)
 - .1 AWCI Levels of Gypsum Board Finish.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-51.34, Vapour Barrier, Polyethylene Sheet for Use in Building Construction.
- .4 Underwriters' Laboratories of Canada (ULC)

- .1 CAN/ULC-S102, Surface Burning Characteristics of Building Materials and Assemblies.

1.3 SUBMITTALS

- .1 Submit 300 mm size samples of corner and casing beads insulating strip.

1.4 DELIVERY, STORAGE AND HANDLING

- .1 Deliver materials in original packages, containers or bundles bearing manufacturers brand name and identification.
- .2 Store materials inside, level, under cover. Keep dry. Protect from weather, other elements and damage from construction operations and other causes.
- .3 Handle gypsum boards to prevent damage to edges, ends or surfaces. Protect metal accessories and trim from being bent or damaged.

1.5 SITE ENVIRONMENTAL REQUIREMENTS

- .1 Maintain temperature minimum 10° C, maximum 21° C for 48 hours prior to and during application of gypsum boards and joint treatment, and for at least 48 hours after completion of joint treatment.
- .2 Apply board and joint treatment to dry, frost free surfaces.
- .3 Ventilation: Ventilate building spaces as required to remove excess moisture that would prevent drying of joint treatment material immediately after its application.

1.6 QUALIFICATIONS

- .1 Dry wall installers: minimum 5 years proven experience.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Standard board: to ASTM C1396/C1396M regular and Type X, thicknesses as indicated on drawings, 1200 mm wide x maximum practical length, ends square cut, edges bevelled.
- .2 Interior panels: fiber-reinforced gypsum panels, moisture and mold resistant, square edge, thickness 16 mm, Aqua-tough by Fiberock or approved equal.
- .3 Metal furring runners, hangers, tie wires, inserts, anchors: to CSA A82.30 galvanized.
- .4 Drywall furring channels: 0.5 mm core thickness galvanized steel channels for screw attachment of gypsum board.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016

Section 09 21 16 – Gypsum Board Assemblies

Page 3 of 5

- .5 Resilient drywall furring: 0.5 mm base steel thickness galvanized steel for resilient attachment of gypsum board.
- .6 Nails: to ASTM C514.
- .7 Steel drill screws: to ASTM C1002.
- .8 Stud adhesive: to CAN/CGSB-71.25.
- .9 Laminating compound: as recommended by manufacturer, asbestos-free.
- .10 Casing beads, corner beads, control joints and edge trim: to ASTM C1047, metal, zinc-coated by hot-dip process 0.5 mm base thickness, perforated flanges, one piece length per location.
- .11 Sealants: in accordance with Section 07 92 00 - Joint Sealing.
- .12 Acoustic sealant: to CGSB 19-GP-21M.
- .13 Polyethylene: to CAN/CGSB-51.34, Type 2.
- .14 Insulating strip: rubberized, moisture resistant, 3 mm thick cork strip, 12 mm wide, with self sticking permanent adhesive on one face, lengths as required.
- .15 Joint compound: to ASTM C475, asbestos-free.

2.2 FINISHES

- .1 Texture finish: asbestos-free standard white texture coating and primer-sealer, recommended by gypsum board manufacturer.

PART 3 EXECUTION

3.1 ERECTION

- .1 Do application and finishing of gypsum board in accordance with ASTM C840 except where specified otherwise.
- .2 Do application of gypsum sheathing to ASTM C1280.
- .3 Erect hangers and runner channels for suspended gypsum board ceilings in accordance with ASTM C840 except where specified otherwise.
- .4 Support light fixtures by providing additional ceiling suspension hangers within 150 mm of each corner and at maximum 600 mm around perimeter of fixture.
- .5 Install work level to tolerance of 1:1200.
- .6 Frame with furring channels, perimeter of openings for access panels, light fixtures, diffusers, grilles, and other protrusions.

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 09 21 16 – Gypsum Board Assemblies

Page 4 of 5

- .7 Install 19 x 64 mm furring channels parallel to, and at exact locations of steel stud partition header track.
- .8 Furr for gypsum board faced vertical bulkheads within and at termination of ceilings.
- .9 Furr above suspended ceilings for gypsum board fire and sound stops and to form plenum areas as indicated.
- .10 Install wall furring for gypsum board wall finishes in accordance with ASTM C840, except where specified otherwise.
- .11 Furr openings and around built-in equipment, cabinets, access panels, on four sides. Extend furring into reveals. Check clearances with equipment suppliers.
- .12 Furr duct shafts, beams, columns, pipes and exposed services where indicated.

3.2 APPLICATION

- .1 Do not apply Aqua-tough board until bucks, anchors, blocking, sound attenuation, electrical and mechanical work are approved.
- .2 Apply single/double layer gypsum board to wood or metal furring or framing using screw fasteners. Maximum spacing of screws 300 mm oc.
 - .1 Single-Layer Application:
 - .1 Apply Aqua-tough board vertically or horizontally, providing sheet lengths that will minimize end joints.
 - .3 Apply 12 mm diameter bead of acoustic sealant continuously around periphery of each face of partitioning to seal Aqua-tough board/structure junction where partitions abut fixed building components. Seal full perimeter of cut-outs around electrical boxes, ducts, in partitions where perimeter sealed with acoustic sealant.
 - .4 Do not install damaged or damp boards.
 - .5 Locate edge or end joints over supports. Stagger vertical joints over different studs on opposite sides of wall.

3.3 INSTALLATION

- .1 Erect accessories straight, plumb or level, rigid and at proper plane. Use full length pieces where practical. Make joints tight, accurately aligned and rigidly secured. Mitre and fit corners accurately, free from rough edges. Secure at 150 mm oc using contact adhesive for full length.
- .2 Install casing beads around perimeter of suspended ceilings.
- .3 Install casing beads where Aqua-tough board butts against surfaces having no trim concealing junction and where indicated. Seal joints with sealant.
- .4 Aqua-tough Board Finish: finish board in accordance to manufacturers specifications:

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 09 21 16 – Gypsum Board Assemblies

Page 5 of 5

- .5 Finish corner beads, control joints and trim as required with two coats of joint compound and one coat of taping compound, feathered out onto panel faces.
- .6 Fill screw head depressions with joint and taping compounds to bring flush with adjacent surface of board so as to be invisible after surface finish is completed.
- .7 Sand lightly to remove burred edges and other imperfections. Avoid sanding adjacent surface of board.
- .8 Completed installation to be smooth, level or plumb, free from waves and other defects and ready for surface finish.
- .9 Apply one coat of white primer sealer over surface to be textured. When dry apply textured finish in accordance with manufacturer's instructions.
- .10 Mix joint compound slightly thinner than for joint taping.
- .11 Apply thin coat to entire surface using trowel or drywall broadknife to fill surface texture differences, variations or tool marks.
- .12 Allow skim coat to dry completely.
- .13 Remove ridges by light sanding or wiping with damp cloth.

3.4 SCHEDULES

- .1 Construct fire rated assemblies where indicated, seal penetrations, as per Section 07 84 00 – Firestopping.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 – Submittal Procedures.
- .2 Section 01 45 00 - Quality Control.
- .3 Section 01 61 00 - Common Product Requirements.
- .4 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .5 Section 01 78 00 – Closeout Submittals.
- .6 Section 32 17 23 - Pavement Marking.

1.2 **REFERENCES**

- .1 Environmental Protection Agency (EPA)
 - .1 EPA Test Method for Measuring Total Volatile Organic Compound Content of Consumer Products, Method 24 (for Surface Coatings).
- .2 Master Painters Institute (MPI)
 - .1 MPI Architectural Painting Specifications Manual
- .3 Society for Protective Coatings (SSPC).
 - .1 SSPC Painting Manual, Systems and Specifications Manual.
- .4 National Fire Code of Canada.

1.3 **QUALITY ASSURANCE**

- .1 Contractor shall have a minimum of five years proven satisfactory experience. When requested, provide a list of last three comparable jobs including, job name and location, specifying authority, and project manager.
- .2 Qualified journeyman shall be engaged in painting work. Apprentices may be employed provided they work under the direct supervision of a qualified journeyman in accordance with trade regulations.
- .3 Conform to latest MPI requirements for exterior painting work including preparation and priming.
- .4 Materials (primers, paints, coatings, varnishes, stains, lacquers, fillers, thinners, solvents, etc.) shall be in accordance with MPI Painting Specification Manual "Approved Products" listing and shall be from a single manufacturer for each system used.

- .5 Other paint materials such as linseed oil, shellac, turpentine, etc. shall be the highest quality product of an approved manufacturer listed in MPI Painting Specification Manual and shall be compatible with other coating materials as required.
- .6 Retain purchase orders, invoices and other documents to prove conformance with noted MPI requirements when requested by Owner's Representative.
- .7 Standard of Acceptance:
 - .1 Walls: No defects visible from a distance of 1000 mm at 90° to surface.
 - .2 Ceilings: No defects visible from floor at 45° to surface when viewed using final lighting source.
 - .3 Final coat to exhibit uniformity of colour and uniformity of sheen across full surface area.

1.4 ENVIRONMENTAL PERFORMANCE REQUIREMENTS

- .1 Provide paint products meeting MPI "Environmentally Friendly" E2 or E3 ratings based on VOC (EPA Method 24) content levels.

1.5 SCHEDULING OF WORK

- .1 Submit work schedule for various stages of painting to Owner's Representative for approval. Submit schedule minimum of two (2) working days in advance of proposed operations.
- .2 Obtain written authorization from Owner's Representative for changes in work schedule.
- .3 Schedule painting operations to prevent disruption of occupants in and about the building.

1.6 SUBMITTALS

- .1 Submit product data and manufacturer's installation/application instructions for paints and coating products to be used.
- .2 Submit WHMIS - MSDS - Material Safety Data Sheets.
- .3 Upon completion, submit records of products used, records to be included in Operation and Maintenance Manuals. List products in relation to finish system and include the following:
 - .1 Product name, type and use.
 - .2 Manufacturer's product number.
 - .3 Colour numbers.
 - .4 Manufacturer's Material Safety Data Sheets (MSDS).
 - .5 MPI Environmentally Friendly classification system rating.
- .4 Submit manufacturer's application instructions for each product specified.

- .5 Submit duplicate 200 x 300 mm sample panels of each paint, stain, clear coating, with specified paint or coating in colours, gloss/sheen and textures required to MPI Painting Specification Manual standards submitted on the following substrate materials:
 - .1 3 mm plate steel for finishes over metal surfaces.
 - .2 13 mm birch plywood for finishes over wood surfaces.
 - .3 50 mm concrete block for finishes over concrete or concrete masonry surfaces.
 - .4 13 mm gypsum board for finishes over gypsum board and other smooth surfaces.
- .6 When approved, samples shall become acceptable standard of quality for appropriate on-site surface with one of each sample retained on-site.
- .7 Submit full range of available colours where colour availability is restricted.

1.7 QUALITY CONTROL

- .1 Provide mock-up in accordance with Section 01 45 00 - Quality Control.
- .2 When requested by the Owner's Representative or Paint Inspection Agency, prepare and paint designated surface, area, room or item (in each colour scheme) to requirements specified herein, with specified paint or coating showing selected colours, gloss/sheen, textures and workmanship to MPI Painting Specification Manual standards for review and approval. When approved, surface, area, room and/or items shall become acceptable standard of finish quality and workmanship for similar on-site work.

1.8 EXTRA MATERIALS

- .1 Submit maintenance materials in accordance with Section 01 78 00 - Closeout Submittals.
- .2 Submit 1 - 4 litre can of each type and colour of finish coating. Identify colour and paint type in relation to established colour schedule and finish formula.
- .3 Deliver to Owner's Representative and store where directed.

1.9 DELIVERY, HANDLING AND STORAGE

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Deliver and store materials in original containers, sealed, with labels intact.
- .3 Labels shall clearly indicate:
 - .1 Manufacturer's name and address.
 - .2 Type of paint or coating.
 - .3 Compliance with applicable standard.
 - .4 Colour number in accordance with established colour schedule.

- .4 Remove damaged, opened and rejected materials from site.
- .5 Provide and maintain dry, temperature controlled, secure storage.
- .6 Observe manufacturer's recommendations for storage and handling.
- .7 Store materials and supplies away from heat generating devices.
- .8 Store materials and equipment in a well ventilated area with temperature range 7°C to 30°C.
- .9 Store temperature sensitive products above minimum temperature as recommended by manufacturer.
- .10 Keep areas used for storage, cleaning and preparation, clean and orderly to approval of Consultant. After completion of operations, return areas to clean condition to approval of Consultant.
- .11 Remove paint materials from storage only in quantities required for same day use.
- .12 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling storage, and disposal of hazardous materials.
- .13 Fire Safety Requirements:
 - .1 Provide one 9 kg Type ABC dry chemical fire extinguisher adjacent to storage area.
 - .2 Store oily rags, waste products, empty containers and materials subject to spontaneous combustion in ULC approved, sealed containers and remove from site on a daily basis.
 - .3 Handle, store, use and dispose of flammable and combustible materials in accordance with the National Fire Code of Canada.
- .14 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials.

1.10 SITE REQUIREMENTS

- .1 Heating, Ventilation and Lighting:
 - .1 Ventilate enclosed spaces.
 - .2 Perform no painting work unless adequate and continuous ventilation and sufficient heating facilities are in place to maintain ambient air and substrate temperatures above 10°C for 24 hours before, during and after paint application until paint has cured sufficiently.
 - .3 Where required, provide continuous ventilation for seven days after completion of application of paint.
 - .4 Provide temporary ventilating and heating equipment where permanent facilities are not available.

- .5 Perform no painting work unless a minimum lighting level of 323 Lux is provided on surfaces to be painted. Adequate lighting facilities shall be provided by General Contractor.
- .2 Temperature, Humidity and Substrate Moisture Content Levels:
 - .1 Unless specifically pre-approved by Owner's Representative and, applied product manufacturer, perform no painting work when:
 - .1 ambient air and substrate temperatures are below 10°C.
 - .2 substrate temperature is over 32°C unless paint is specifically formulated for application at high temperatures.
 - .3 substrate and ambient air temperatures are expected to fall outside MPI or paint manufacturer's prescribed limits.
 - .4 the relative humidity is above 85% or when dew point is less than 3°C variance between air/surface temperature.
 - .5 rain or snow are forecast to occur before paint has thoroughly cured or when it is foggy, misty, raining or snowing at site.
 - .2 Perform no painting work when maximum moisture content of substrate exceeds:
 - .1 12% for concrete and masonry (clay and concrete brick/block).
 - .2 15% for wood.
 - .3 12% for plaster and gypsum board.
 - .3 Conduct moisture tests using a properly calibrated electronic Moisture Meter, except test concrete floors for moisture using a simple "cover patch test".
 - .4 Test concrete, masonry and plaster surfaces for alkalinity as required.
- .3 Surface and Environmental Conditions:
 - .1 Apply paint finish only in areas where dust is no longer being generated by related construction operations or when wind or ventilation conditions are such that airborne particles will not affect quality of finished surface.
 - .2 Apply paint only to adequately prepared surfaces and to surfaces within moisture limits noted herein.
 - .3 Apply paint only when previous coat of paint is dry or adequately cured.
 - .4 Apply paint finishes only when conditions forecast for entire period of application fall within manufacturer's recommendations.
 - .5 Do not apply paint when:
 - .1 Temperature is expected to drop below 10°C before paint has thoroughly cured.
 - .2 Substrate and ambient air temperatures are expected to fall outside MPI or paint manufacturer's limits.
 - .3 Surface to be painted is wet, damp or frosted.
 - .6 Provide and maintain cover when paint must be applied in damp or cold weather. Heat substrates and surrounding air to comply with temperature and humidity conditions specified by manufacturer. Protect until paint is dry or until weather conditions are suitable.

- .7 Schedule painting operations such that surfaces exposed to direct, intense sunlight are scheduled for completion during early morning.
- .8 Remove paint from areas which have been exposed to freezing, excess humidity, rain, snow or condensation. Prepare surface again and repaint.
- .9 Paint occupied facilities in accordance with approved schedule only. Schedule operations to approval of the Owner's Representative such that painted surfaces will have dried and cured sufficiently before occupants are affected.

1.11 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.
- .3 Place materials defined as hazardous or toxic in designated containers.
- .4 Ensure emptied containers are sealed and stored safely.
- .5 Unused paint, coating materials must be disposed of at official hazardous material collections site as approved by Owner's Representative.
- .6 Paint, stain and wood preservative finishes and related materials (thinners, and solvents) are regarded as hazardous products and are subject to regulations for disposal.
- .7 Material which cannot be reused must be treated as hazardous waste and disposed of in an appropriate manner.
- .8 Place materials defined as hazardous or toxic waste, including used sealant and adhesive tubes and containers, in containers or areas designated for hazardous waste.
- .9 To reduce the amount of contaminants entering waterways, sanitary/storm drain systems or into ground follow these procedures:
 - .1 Retain cleaning water for water-based materials to allow sediments to be filtered out.
 - .2 Retain cleaners, thinners, solvents and excess paint and place in designated containers and ensure proper disposal.
 - .3 Return solvent and oil soaked rags used during painting operations for contaminant recovery, proper disposal, or appropriate cleaning and laundering.
 - .4 Dispose of contaminants in approved legal manner in accordance with hazardous waste regulations.
- .10 Empty paint cans are to be dry prior to disposal or recycling (where available).

PART 2 **PRODUCTS**

2.1 **MATERIALS**

- .1 Paint materials listed in the latest edition of the MPI Approved Products List (APL) are acceptable for use on this project.
- .2 Paint materials for each coating formula to be products of a single manufacturer.
- .3 Low odour products: whenever possible, select products exhibiting low odour characteristics. If two products are otherwise equivalent, select the product with the lowest odour. Only qualified products with E2 or E3 "Environmentally Friendly" rating are acceptable for use on this project.
- .4 Paints, coatings, adhesives, solvents, cleaners, lubricants, and other fluids, shall:
 - .1 be water-based, water soluble, water clean-up.
 - .2 be non-flammable
 - .3 be manufactured without compounds which contribute to ozone depletion in the upper atmosphere.
 - .4 be manufactured without compounds which contribute to smog in the lower atmosphere.
 - .5 do not contain methylene chloride, chlorinated hydrocarbons, toxic metal pigments.
- .5 Water-borne surface coatings must be manufactured and transported in a manner that steps of processes, including disposal of waste products arising therefrom, will meet requirements of applicable governmental acts, by-laws and regulations including, for facilities located in Canada, Fisheries Act and Canadian Environmental Protection Act (CEPA).
- .6 Water-borne surface coatings must not be formulated or manufactured with aromatic solvents, formaldehyde, halogenated solvents, mercury, lead, cadmium, hexavalent chromium or their compounds.
- .7 Water-borne surface coatings must have a flash point of 61.0°C or greater.
- .8 Both water-borne surface coatings and recycled water-borne surface coatings must be made by a process that does not release:
 - .1 Matter in undiluted production plant effluent generating a 'Biochemical Oxygen Demand' (BOD) in excess of 15 mg/L to a natural watercourse or a sewage treatment facility lacking secondary treatment.
 - .2 Total Suspended Solids (TSS) in undiluted production plant effluent in excess of 15 mg/L to a natural watercourse or a sewage treatment facility lacking secondary treatment.
- .9 Water-borne paints and stains, and water borne varnishes must meet a minimum "Environmentally Friendly" E2 rating.

2.2 COLOURS

- .1 Owner's Representative will provide Colour Schedule after Contract award.
- .2 Selection of colours will be from manufacturer's full range of colours.
- .3 Where specific products are available in a restricted range of colours, selection will be based on the limited range.
- .4 Second coat in a three coat system to be tinted slightly lighter colour than top coat to show visible difference between coats.

2.3 MIXING AND TINTING

- .1 Perform colour tinting operations prior to delivery of paint to site. On-site tinting of painting materials is allowed only with Owner's Representative written permission.
- .2 Paste, powder or catalyzed paint mixes shall be mixed in strict accordance with manufacturer's written instructions.
- .3 Where thinner is used, addition shall not exceed paint manufacturer's recommendations. Do not use kerosene or any such organic solvents to thin water-based paints.
- .4 Thin paint for spraying according in strict accordance with paint manufacturer's instructions. If directions are not on container, obtain instructions in writing from manufacturer and provide copy of instructions to Owner's Representative.
- .5 Re-mix paint in containers prior to and during application to ensure break-up of lumps, complete dispersion of settled pigment, and colour and gloss uniformity.

2.4 GLOSS/SHEEN RATINGS

- .1 Paint gloss shall be defined as the sheen rating of applied paint, in accordance with the following values:

Gloss Level /Category	Units @ 60E/	Units @ 85°
G1 - matte finish	0 to 5	max. 10
G2 - velvet finish	0 to 10	10 to 35
G3 - eggshell finish	10 to 25	10 to 35
G4 - satin finish	20 to 35	min. 35
G5 - semi-gloss finish	35 to 70	
G6 – gloss finish	70 to 85	
G7 - high gloss finish	> 85	

- .2 Gloss level ratings of painted surfaces shall be as specified herein.

2.5 EXTERIOR PAINTING SYSTEMS

- .1 The following paint formulas requires a three coat finish as indicated in the MPI Architectural Painting Specifications Manual.

- .2 Galvanized Metal: not chromate passivated
 - .1 EXT 5.3D - Pigmented polyurethane finish for use in high contact/high traffic areas.

PART 3 **EXECUTION**

3.1 **GENERAL**

- .1 Perform preparation and operations for exterior painting in accordance with MPI Painting Specifications Manual except where specified otherwise.
- .2 Apply all paint materials in accordance with paint manufacturer's written application instructions.

3.2 **EXISTING CONDITIONS**

- .1 Investigate existing substrates for problems related to proper and complete preparation of surfaces to be painted. Report to Owner's Representative damages, defects, unsatisfactory or unfavourable conditions before proceeding with work.
- .2 Conduct moisture testing of surfaces to be painted using a properly calibrated electronic moisture meter, except test concrete floors for moisture using a simple "cover patch test" and report findings to Owner's Representative. Do not proceed with work until conditions fall within acceptable range as recommended by manufacturer.
- .3 Maximum moisture content as follows:
 - .1 Concrete: 12%.
 - .2 Clay and Concrete Block/Brick: 12%.
 - .3 Wood: 15%.

3.3 **PROTECTION**

- .1 Protect existing building surfaces and adjacent structures from paint spatters, markings and other damage by suitable non-staining covers or masking. If damaged, clean and restore such surfaces as directed by Owner's Representative.
- .2 Cover or mask windows and other ornamental hardware adjacent to areas being painted to prevent damage and to protect from paint drops and splatters. Use non-staining coverings.
- .3 Protect items that are permanently attached such as Fire Labels on doors and frames.
- .4 Protect factory finished products and equipment.
- .5 Protect passing pedestrians, building occupants and general public in and about the building.

- .6 Remove electrical cover plates, light fixtures, surface hardware on doors, and all other surface mounted fittings, equipment and fastenings prior to undertaking any painting operations. Store for re-installation after painting is completed.
- .7 Cover or move exterior furniture and portable equipment around building as necessary to carry out painting operations. Replace as painting operations progress.
- .8 As painting operations progress, place "WET PAINT" signs in areas of work to approval of Owner's Representative.

3.4 CLEANING AND PREPARATION

- .1 Clean and prepare exterior surfaces in accordance with MPI Painting Specification Manual requirements. Refer to the MPI Manual in regard to specific requirements and as follows:
 - .1 Remove dust, dirt, and other surface debris by wiping with dry, clean cloths or compressed air.
 - .2 Wash surfaces with a biodegradable detergent and bleach where applicable and clean warm water using a stiff bristle brush to remove dirt, oil and other surface contaminants.
 - .3 Rinse scrubbed surfaces with clean water until foreign matter is flushed from surface.
 - .4 Allow surfaces to drain completely and allow to dry thoroughly.
 - .5 Prepare surfaces for water-based painting, water-based cleaners should be used in place of organic solvents.
 - .6 Use trigger operated spray nozzles for water hoses.
 - .7 Many water-based paints cannot be removed with water once dried. However, minimize the use of kerosene or any such organic solvents to clean up water-based paints.
- .2 Prevent contamination of cleaned surfaces before prime coat is applied and between applications of remaining coats. Apply primer, paint, or pretreatment as soon as possible after cleaning and before deterioration occurs.
- .3 Sand and dust between coats as required to provide adequate adhesion for next coat and to remove defects visible from a distance up to 1000 mm.
- .4 Clean metal surfaces to be painted by removing rust, loose mill scale, welding slag, dirt, oil, grease and other foreign substances in accordance with MPI requirements. Remove traces of blast products from surfaces, pockets and corners to be painted by brushing with clean brushes or blowing with clean dry compressed air.
- .5 Touch up of shop primers with primer as specified in applicable section. Major touch-up including cleaning and painting of field connections, welds, rivets, nuts, washers, bolts, and damaged or defective paint and rusted areas, shall be by supplier of fabricated material.

- .6 Do not apply paint until prepared surfaces have been accepted by Owner's Representative.

3.5 APPLICATION

- .1 Method of application to be as approved by Owner's Representative. Apply paint by brush roller, air sprayer, airless sprayer. Conform to manufacturer's application instructions unless specified otherwise.
- .2 Brush and Roller Application:
 - .1 Apply paint in a uniform layer using brush and/or roller of types suitable for application.
 - .2 Work paint into cracks, crevices and corners.
 - .3 Paint surfaces and corners not accessible to brush using spray, daubers and/or sheepskins. Paint surfaces and corners not accessible to roller using brush, daubers or sheepskins.
 - .4 Brush and/or roll out runs and sags, and over-lap marks. Rolled surfaces shall be free of roller tracking and heavy stipple.
 - .5 Remove runs, sags and brush marks from finished work and repaint.
- .3 Spray Application:
 - .1 Provide and maintain equipment that is suitable for intended purpose, capable of properly atomizing paint to be applied, and equipped with suitable pressure regulators and gauges.
 - .2 Keep paint ingredients properly mixed in containers during paint application either by continuous mechanical agitation or by intermittent agitation as frequently as necessary.
 - .3 Apply paint in a uniform layer, with overlapping at edges of spray pattern.
 - .4 Brush out immediately runs and sags.
 - .5 Use brushes to work paint into cracks, crevices and places which are not adequately painted by spray.
- .4 Use dipping, sheepskins or daubers only when no other method is practical in places of difficult access and only when specifically authorized by Owner's Representative.
- .5 Apply coats of paint as a continuous film of uniform thickness. Repaint thin spots or bare areas before next coat of paint is applied.
- .6 Allow surfaces to dry and properly cure after cleaning and between subsequent coats for minimum time period as recommended by manufacturer.
- .7 Sand and dust between coats to remove visible defects.
- .8 Finish surfaces both above and below sight lines as specified for surrounding surfaces, including such surfaces as projecting ledges.

- .9 Finish top, bottom, edges and cutouts of doors after fitting as specified for door surfaces.

3.6 MECHANICAL/ELECTRICAL EQUIPMENT

- .1 Unless otherwise specified, paint exterior exposed conduits, piping, hangers, ductwork and other mechanical and electrical equipment with colour and finish to match adjacent surfaces, except as noted otherwise.
- .2 Touch up scratches and marks on factory painted finishes and equipment with paint as supplied by manufacturer of equipment.
- .3 Paint fire protection piping red.
- .4 Do not paint over nameplates.
- .5 Paint steel electrical light standards. Do not paint outdoor transformers and substation equipment.

3.7 FIELD QUALITY CONTROL

- .1 Field inspection of exterior painting operations to be carried out by Owner's Representative.
- .2 Advise Owner's Representative when each applied coating is ready for inspection. Do not proceed with subsequent coats until previous coat has been approved.
- .3 Co-operate with Owner's Representative and provide access to areas of work.

3.8 RESTORATION

- .1 Clean and re-install all hardware items removed before undertaken painting operations.
- .2 Remove protective coverings and warning signs as soon as practical after operations cease.
- .3 Remove paint splashings on exposed surfaces that were not painted. Remove smears and spatter immediately as operations progress, using compatible solvent.
- .4 Protect surfaces from paint droppings and dust to approval of Owner's Representative. Avoid scuffing newly applied paint.
- .5 Restore areas used for storage, cleaning, mixing and handling of paint to clean condition as approved by Owner's Representative.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 45 00 - Quality Control.
- .3 Section 01 61 00 - Common Product Requirements.
- .4 Section 01 74 21 – Construction/Demolition Waste Management and Disposal.
- .5 Section 01 78 00 - Closeout Submittals.
- .6 Section 04 22 00 – Concrete Unit Masonry.
- .7 Section 06 20 00 – Finish Carpentry.
- .8 Section 06 40 00 - Architectural Woodwork.
- .9 Section 08 11 00 – Metal Doors & Frames.
- .10 Section 09 21 16 – Gypsum Board Assemblies.

1.2 **REFERENCES**

- .1 Environmental Protection Agency (EPA)
 - .1 EPA Test Method for Measuring Total Volatile Organic Compound Content of Consumer Products, Method 24 (for Surface Coatings).
- .2 Master Painters Institute (MPI)
 - .1 MPI Architectural Painting Specifications Manual.
- .3 Society for Protective Coatings (SSPC)
 - .1 SSPC Painting Manual, Volume Two, Systems and Specifications Manual.
- .4 National Fire Code of Canada.

1.3 **QUALITY ASSURANCE**

- .1 Contractor shall have a minimum of five years proven satisfactory experience. When requested, provide a list of last three comparable jobs including, job name and location, specifying authority, and project manager.
- .2 Qualified journeymen shall be engaged in painting work. Apprentices may be employed provided they work under the direct supervision of a qualified journeyman in accordance with trade regulations.

- .3 Conform to latest MPI requirements for interior painting work including preparation and priming.

1.4 ENVIRONMENTAL PERFORMANCE REQUIREMENTS

- .1 Provide paint products meeting MPI "Environmentally Friendly" E2 or E3 ratings based on VOC (EPA Method 24) content levels.
- .2 Where indoor air quality (odour) is a problem, use only MPI listed materials having a minimum E2 or E3 rating.

1.5 SCHEDULING

- .1 Submit work schedule for various stages of painting to Owner's Representative for approval. Submit schedule minimum of 48 hours in advance of proposed operations.
- .2 Obtain written authorization from Owner's Representative for any changes in work schedule.
- .3 Schedule painting operations to prevent disruption of occupants in and about the building.

1.6 SUBMITTALS

- .1 Submit product data and manufacturer's installation/application instructions for each paint and coating product to be
- .2 Submit product data for the use and application of paint thinner.
- .3 Submit WHMIS MSDS - Material Safety Data Sheets. Indicate VOCs during application and curing.
- .4 Upon completion, submit records of products used, records to be included in Operating and Maintenance Manuals. List products in relation to finish system and include the following:
 - .1 Product name, type and use
 - .2 Manufacturer's product number
 - .3 Colour numbers
 - .4 MPI Environmentally Friendly Classification System Rating
 - .5 Manufacturer's Material Safety Data Sheets (MSDS)
- .5 Submit full range colour sample chips to indicate where colour availability is restricted.

1.7 QUALITY CONTROL

- .1 Provide mock-up in accordance with Section 01 45 00 - Quality Control.

- .2 When requested by Owner's Representative, prepare and paint designated surface, area, room or item (in each colour scheme) to requirements specified herein, with specified paint or coating showing selected colours, gloss/sheen, textures and workmanship to MPI Painting Specification Manual standards for review and approval. When approved, surface, area, room and/or items shall become acceptable standard of finish quality and workmanship for similar on-site work.

1.8 EXTRA MATERIALS

- .1 Submit maintenance materials from same product run as products installed in accordance with Section 01 78 00 - Closeout Submittals. Package products with protective covering and identify with descriptive labels.
- .2 Submit one - four litre can of each type and colour of finish coating. Identify colour and paint type in relation to established colour schedule and finish formula.
- .3 Deliver to Owner's Representative and store where directed.
- .4 Provide certificate signed by staff that extra materials have been received in order.

1.9 DELIVERY, HANDLING AND STORAGE

- .1 Deliver, store and handle materials in accordance with Section 01 61 00 - Common Product Requirements.
- .2 Deliver and store materials in original containers, sealed, with labels intact.
- .3 Labels shall clearly indicate:
 - .1 Manufacturer's name and address.
 - .2 Type of paint or coating.
 - .3 Compliance with applicable standard.
 - .4 Colour number in accordance with established colour schedule.
- .4 Remove damaged, opened and rejected materials from site.
- .5 Provide and maintain dry, temperature controlled, secure storage.
- .6 Observe manufacturer's recommendations for storage and handling.
- .7 Store materials and supplies away from heat generating devices.
- .8 Store materials and equipment in a well ventilated area with temperature range 7° C to 30° C.
- .9 Store temperature sensitive products above minimum temperature as recommended by manufacturer.

- .10 Keep areas used for storage, cleaning and preparation, clean and orderly to approval of Owner's Representative. After completion of operations, return areas to clean condition to approval of Consultant.
- .11 Remove paint materials from storage only in quantities required for same day use.
- .12 Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling storage, and disposal of hazardous materials.
- .13 Fire Safety Requirements:
 - .1 Provide minimum one 9 kg Type ABC dry chemical fire extinguisher adjacent to storage area.
 - .2 Store oily rags, waste products, empty containers and materials subject to spontaneous combustion in ULC approved, sealed containers and remove from site on a daily basis.
 - .3 Handle, store, use and dispose of flammable and combustible materials in accordance with the National Fire Code of Canada.

1.10 WASTE MANAGEMENT AND DISPOSAL

- .1 Separate waste materials for reuse and recycling in accordance with Section 01 74 21 - Construction/Demolition Waste Management and Disposal.
- .2 Remove from site and dispose of packaging materials at appropriate recycling facilities.
- .3 Place materials defined as hazardous or toxic in designated containers.
- .4 Ensure emptied containers are sealed and stored safely.
- .5 Unused paint, coating materials must be disposed of at official hazardous material collections site as approved by Owner's Representative.
- .6 Paint, stain and wood preservative finishes and related materials (thinners, and solvents) are regarded as hazardous products and are subject to regulations for disposal.
- .7 Material which cannot be reused must be treated as hazardous waste and disposed of in an appropriate manner.
- .8 Place materials defined as hazardous or toxic waste, including used sealant and adhesive tubes and containers, in containers or areas designated for hazardous waste.
- .9 To reduce the amount of contaminants entering waterways, sanitary/storm drain systems or into ground follow these procedures:
 - .1 Retain cleaning water for water-based materials to allow sediments to be filtered out.
 - .2 Retain cleaners, thinners, solvents and excess paint and place in designated containers and ensure proper disposal.

- .3 Return solvent and oil soaked rags used during painting operations for contaminant recovery, proper disposal, or appropriate cleaning and laundering.
- .4 Dispose of contaminants in approved legal manner in accordance with hazardous waste regulations.
- .5 Empty paint cans are to be dry prior to disposal or recycling (where available).

1.11 SITE CONDITIONS

- .1 Heating, Ventilation and Lighting:
 - .1 Ventilate enclosed spaces.
 - .2 Perform no painting work unless adequate and continuous ventilation and sufficient heating facilities are in place to maintain ambient air and substrate temperatures above 10°C for 24 hours before, during and after paint application until paint has cured sufficiently.
 - .3 Where required, provide continuous ventilation for seven days after completion of application of paint.
 - .4 Perform no painting work unless a minimum lighting level of 323 Lux is provided on surfaces to be painted. Adequate lighting facilities shall be provided by General Contractor.
- .2 Temperature, Humidity and Substrate Moisture Content Levels:
 - .1 Unless specifically pre-approved by the specifying body, Paint Inspection Agency and the applied product manufacturer, perform no painting work when:
 - .1 Ambient air and substrate temperatures are below 10°C.
 - .2 Substrate temperature is over 32°C unless paint is specifically formulated for application at high temperatures.
 - .3 Substrate and ambient air temperatures are expected to fall outside MPI or paint manufacturer's prescribed limits.
 - .4 The relative humidity is above 60% or when the dew point is less than 3°C variance between the air/surface temperature.
 - .2 Perform no painting work when the maximum moisture content of the substrate exceeds:
 - .1 12% for concrete and masonry (clay and concrete brick/block).
 - .2 15% for wood.
 - .3 12% for plaster and gypsum board.
 - .3 Conduct moisture tests using a properly calibrated electronic Moisture Meter, except test concrete floors for moisture using a simple "cover patch test".
 - .4 Test concrete, masonry and plaster surfaces for alkalinity as required.
- .3 Surface and Environmental Conditions:
 - .1 Apply paint finish only in areas where dust is no longer being generated by related construction operations or when wind or ventilation conditions are such that airborne particles will not affect quality of finished surface.

- .2 Apply paint only to adequately prepared surfaces and to surfaces within moisture limits noted herein.
- .3 Apply paint only when previous coat of paint is dry or adequately cured.
- .4 Additional Interior Application Requirements:
 - .1 Apply paint finishes only when temperature at location of installation can be satisfactorily maintained within manufacturer's recommendations.
 - .2 Apply paint in occupied facilities during silent hours only. Schedule operations to approval of Owner's Representative such that painted surfaces will have dried and cured sufficiently before occupants are affected.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Paint materials listed in the MPI Approved Products List (APL) are acceptable for use on this project.
- .2 Paint materials for paint systems shall be products of a single manufacturer.
- .3 Low odor products. Whenever possible, select products exhibiting low odor characteristics. If two products are otherwise equivalent, select the product with the lowest odor. Only qualified products with E2 or E3 "Environmentally Friendly" rating are acceptable for use on this project.
- .4 Paints, coatings, adhesives, solvents, cleaners, lubricants, and other fluids, shall:
 - .1 be water-based, water soluble, water clean-up.
 - .2 be non-flammable.
 - .3 be manufactured without compounds which contribute to ozone depletion in the upper atmosphere.
 - .4 be manufactured without compounds which contribute to smog in the lower atmosphere.
 - .5 do not contain methylene chloride, chlorinated hydrocarbons, toxic metal pigments.
- .5 Water-borne surface coatings must be manufactured and transported in a manner that steps of process, including disposal of waste products arising therefrom, will meet requirements of applicable governmental acts, by-laws and regulations including, for facilities located in Canada, Fisheries Act and Canadian Environmental Protection Act (CEPA).
- .6 Water-borne surface coatings must not be formulated or manufactured with aromatic solvents, formaldehyde, halogenated solvents, mercury, lead, cadmium, hexavalent chromium or their compounds.
- .7 Water-borne surface coatings must have a flash point of 61.0°C or greater.

- .8 Both water-borne surface coatings and recycled water-borne surface coatings must be made by a process that does not release:
 - .1 Matter in undiluted production plant effluent generating a 'Biochemical Oxygen Demand' (BOD) in excess of 15 mg/L to a natural watercourse or a sewage treatment facility lacking secondary treatment.
 - .2 Total Suspended Solids (TSS) in undiluted production plant effluent in excess of 15 mg/L to a natural watercourse or a sewage treatment facility lacking secondary treatment.
- .9 Water-borne paints and stains, and water borne varnishes must meet a minimum "Environmentally Friendly" E2 rating.

2.2 COLOURS

- .1 Owner's Representative will provide Colour Schedule after contract award.
- .2 Selection of colours will be from manufacturers full range of colours.
- .3 Where specific products are available in a restricted range of colours, selection will be based on the limited range.
- .4 Second coat in a three coat system to be tinted slightly lighter colour than top coat to show visible difference between coats.

2.3 MIXING AND TINTING

- .1 Perform colour tinting operations prior to delivery of paint to site. On-site tinting of painting materials is allowed only with Owner's Representative written permission.
- .2 Paste, powder or catalyzed paint mixes shall be mixed in strict accordance with manufacturer's written instructions.
- .3 Where thinner is used, addition shall not exceed paint manufacturer's recommendations. Do not use kerosene or any such organic solvents to thin water-based paints.
- .4 Thin paint for spraying according in strict accordance with paint manufacturer's instructions. If directions are not on container, obtain instructions in writing from manufacturer and provide copy of instructions to Owner's Representative.
- .5 Re-mix paint in containers prior to and during application to ensure break-up of lumps, complete dispersion of settled pigment, and colour and gloss uniformity.

2.4 GLOSS/SHEEN RATINGS

- .1 Paint gloss shall be defined as the sheen rating of applied paint, in accordance with the following values:

Gloss Level Category	Units @ 60E	Units @ 85E
G1 - matte finish	max. 5	max. 10

Gloss Level Category	Units @ 60E	Units @ 85E
G2 - velvet finish	max. 10	10 to 35
G3 - eggshell finish	10 to 25	10 to 35
G4 - satin finish	20 to 35	min. 35
G5 - semi-gloss finish	35 to 70	
G6 - gloss finish	70 to 85	
G7 - high gloss finish	> 85	

- .2 Gloss level ratings of painted surfaces shall be as specified herein.

2.5 INTERIOR PAINTING SYSTEMS

- .1 The following paint formulas requires a three coat finish as indicated in the MPI Architectural Painting Specifications Manual.
- .2 Galvanized Metal: doors, frames, railings, misc. steel, pipes, overhead decking, ducts, etc.
- .1 INT 5.3A Latex G5 finish.
- .3 Dressed Lumber: including window box frames, casings, etc.
- .1 INT 6.5B Polyurethane varnish gloss finish (over stain).
- .4 Plaster and Gypsum Board: gypsum wallboard, drywall, “sheet rock type material”, etc and textured finishes:
- .1 INT 9.2A Latex G5 finish (over latex sealer) for walls.

PART 3 EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and data sheet.

3.2 GENERAL

- .1 Perform preparation and operations for interior painting in accordance with MPI Painting Specifications Manual except where specified otherwise.
- .2 Apply all paint materials in accordance with paint manufacturer's written application instructions.

3.3 PROTECTION

- .1 Protect existing building surfaces and adjacent structures from paint spatters, markings and other damage. If damaged, clean and restore such surfaces as directed by Owner's Representative.

- .2 Cover or mask floors, windows and other ornamental hardware adjacent to areas being painted to prevent damage and to protect from paint drops and splatters. Use non-staining coverings.
- .3 Protect items that are permanently attached such as Fire Labels on doors and frames.
- .4 Protect factory finished products and equipment.
- .5 Protect passing pedestrians, building occupants and general public in and about the building.
- .6 Remove electrical cover plates, light fixtures, surface hardware on doors, door stops, bath accessories and other surface mounted fittings and fastenings prior to undertaking any painting operations. Store for re-installation after painting is completed.
- .7 As painting operations progress place “WET PAINT” signs in occupied areas to approval of Owner’s Representative.

3.4 EXAMINATION

- .1 Investigate existing substrates for problems related to proper and complete preparation of surfaces to be painted. Report to Owner’s Representative all damage, defects, unsatisfactory or unfavourable conditions before proceeding with work.
- .2 Conduct moisture testing of surfaces to be painted using a properly calibrated electronic moisture meter, except test concrete floors for moisture using a simple “cover patch test” and report findings to Owner’s Representative. Do not proceed with work until conditions fall within acceptable range as recommended by manufacturer.
- .3 Maximum moisture content as follows:
 - .1 Plaster and wallboard: 12%
 - .2 Masonry/Concrete: 12%
 - .3 Concrete Block/Brick: 12%
 - .4 Wood: 15%

3.5 CLEANING AND PREPARATION

- .1 Clean and prepare surfaces in accordance with MPI Painting Specification Manual requirements. Refer to MPI Manual in regard to specific requirements and as follows:
 - .1 Remove dust, dirt, and other surface debris by vacuuming, wiping with dry, clean cloths or compressed air.
 - .2 Wash surfaces with a biodegradable detergent and bleach where applicable and clean warm water using a stiff bristle brush to remove dirt, oil and other surface contaminants.
 - .3 Rinse scrubbed surfaces with clean water until foreign matter is flushed from surface.
 - .4 Allow surfaces to drain completely and allow to dry thoroughly.

- .5 Prepare surfaces for water-based painting, water-based cleaners should be used in place of organic solvents.
- .6 Use trigger operated spray nozzles for water hoses.
- .7 Many water-based paints cannot be removed with water once dried. However, minimize the use of kerosene or any such organic solvents to clean up water-based paints.
- .2 Prevent contamination of cleaned surfaces by salts, acids, alkalis, other corrosive chemicals, grease, oil and solvents before prime coat is applied and between applications of remaining coats. Apply primer, paint, or pretreatment as soon as possible after cleaning and before deterioration occurs.
- .3 Sand existing surfaces with intact, smooth, high gloss coatings to provide adequate adhesion for new finishes.
- .4 Where possible, prime surfaces of new wood surfaces before installation. Use same primers as specified for exposed surfaces.
 - .1 Apply vinyl sealer to MPI #36 over knots, pitch, sap and resinous areas.
 - .2 Apply wood filler to nail holes and cracks.
 - .3 Tint filler to match stains for stained woodwork.
- .5 Sand and dust between coats as required to provide adequate adhesion for next coat and to remove defects visible from a distance up to 1000 mm.
- .6 Clean metal surfaces to be painted by removing rust, loose mill scale, welding slag, dirt, oil, grease and other foreign substances in accordance with MPI requirements. Remove traces of blast products from surfaces, pockets and corners to be painted by brushing with clean brushes blowing with clean dry compressed air, or vacuum cleaning.
- .7 Touch up of shop primers with primer as specified in applicable section. Major touch-up including cleaning and painting of field connections, welds, rivets, nuts, washers, bolts, and damaged or defective paint and rusted areas, shall be by supplier of fabricated material.
- .8 Do not apply paint until prepared surfaces have been accepted by Owner's Representative.

3.6 APPLICATION

- .1 Method of application to be as approved by Owner's Representative. Apply paint by brush, roller, air sprayer, airless sprayer. Conform to manufacturer's application instructions unless specified otherwise.
- .2 Brush and Roller Application:
 - .1 Apply paint in a uniform layer using brush and/or roller of types suitable for application.
 - .2 Work paint into cracks, crevices and corners.

- .3 Brush and/or roll out runs and sags, and over-lap marks. Rolled surfaces shall be free of roller tracking and heavy stipple.
- .4 Paint surfaces and corners not accessible to brush using spray, daubers and/or sheepskins. Paint surfaces and corners not accessible to roller using brush, daubers or sheepskins.
- .5 Remove runs, sags and brush marks from finished work and repaint.
- .3 Spray application:
 - .1 Provide and maintain equipment that is suitable for intended purpose, capable of properly atomizing paint to be applied, and equipped with suitable pressure regulators and gauges.
 - .2 Keep paint ingredients properly mixed in containers during paint application either by continuous mechanical agitation or by intermittent agitation as frequently as necessary.
 - .3 Apply paint in a uniform layer, with overlapping at edges of spray pattern.
 - .4 Brush out immediately all runs and sags.
 - .5 Use brushes to work paint into cracks, crevices and places which are not adequately painted by spray.
- .4 Use dipping, sheepskins or daubers only when no other method is practical in places of difficult access and only when specifically authorized by Owner's Representative.
- .5 Apply coats of paint as a continuous film of uniform thickness. Repaint thin spots or bare areas before next coat of paint is applied.
- .6 Allow surfaces to dry and properly cure after cleaning and between subsequent coats for minimum time period as recommended by manufacturer.
- .7 Sand and dust between coats to remove visible defects.
- .8 Finish tops of cupboards, cabinets and projecting ledges, both above and below sight lines as specified for surrounding surfaces.
- .9 Finish closets and alcoves as specified for adjoining rooms.
- .10 Finish top, bottom, edges and cutouts of doors after fitting as specified for door surfaces.

3.7

MECHANICAL/ELECTRICAL EQUIPMENT

- .1 In finished areas: paint exposed conduits, piping, hangers, ductwork and other mechanical and electrical equipment with colour and finish to match adjacent surfaces, except as noted otherwise.
- .2 In boiler room, mechanical and electrical rooms: paint exposed conduits, piping, hangers, ductwork and other mechanical and electrical equipment.
- .3 In other unfinished areas: leave exposed conduits, piping, hangers, ductwork and other mechanical and electrical equipment in original finish and touch up scratches and marks.

- .4 Touch up scratches and marks on factory painted finishes and equipment with paint as supplied by manufacturer of equipment.
- .5 Do not paint over nameplates.
- .6 Keep sprinkler heads free of paint.
- .7 Paint inside of ductwork where visible behind grilles, registers and diffusers with primer and one coat of matt black paint.
- .8 Paint disconnect switches for fire alarm system and exit light systems in red enamel.
- .9 Paint all fire protection piping red.
- .10 Paint both sides and edges of backboards for telephone and electrical equipment before installation. Leave equipment in original finish except for touch-up as required, and paint conduits, mounting accessories and other unfinished items.
- .11 Do not paint interior transformers and substation equipment.

3.8 FIRE SEPARATIONS

- .1 Contractor to stencil on both sides of fire rated partitions the fire rating for that assembly (i.e.: **1 HR FIRE SEPARATION**).
- .2 Stenciled fire ratings to be minimum 100 mm high **RED** letters, minimum 150 mm above finished ceilings, and minimum 2400 mm o.c. along partition.

3.9 FIELD QUALITY CONTROL

- .1 Field inspection of interior painting operations to be carried out by Owner's Representative.
- .2 Advise Owner's Representative when each applied coating is ready for inspection. Do not proceed with subsequent coats until previous coat has been approved.
- .3 Co-operate with Owner's Representative and provide access to all areas of the work.
- .4 Standard of Acceptance:
 - .1 Walls: no defects visible from a distance of 1000 mm at 90 degrees to surface.
 - .2 Ceilings: no defects visible from floor at 45 degrees to surface when viewed using final lighting source.
 - .3 Final coat to exhibit uniformity of colour and uniformity of sheen across full surface area.

3.10 RESTORATION

- .1 Clean and re-install all hardware items removed before undertaken painting operations.

**Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135**

September 2016

Section 09 91 23 – Interior Painting

Page 13 of 13

- .2 Remove protective coverings and warning signs as soon as practical after operations cease.
- .3 Remove paint splashings on exposed surfaces that were not painted. Remove smears and spatter immediately as operations progress, using compatible solvent.
- .4 Protect freshly completed surfaces from paint droppings and dust to approval of Owner's Representative. Avoid scuffing newly applied paint.
- .5 Restore areas used for storage, cleaning, mixing and handling of paint to clean condition as approved by Owner's Representative.

END OF SECTION

PART 1 **GENERAL**

1.1 **REFERENCES**

- .1 American Society for Testing and Materials International (ASTM)
 - .1 ASTM D 698, Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400ft-lbf/ft³) (600kN-m/m³).
- .2 Canadian Standards Association (CSA International)
 - .1 CSA-A23.1/A23.2, Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.
 - .2 CAN/CSA-A3000, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).
 - .3 CSA-A3001, Cementitious Materials for Use in Concrete.

1.2 **QUALITY ASSURANCE/REGULATORY REQUIREMENTS**

- .1 Shore and brace excavations, protect slopes and banks and perform all work in accordance with Provincial and Municipal regulations whichever is more stringent.
- .2 Comply with Explosives Act of Canada.
- .3 Perform blasting in accordance with Provincial and Municipal regulations. Repair damage to approval of Owner's Representative.
- .4 No blasting will be permitted within 3 m of any building and where damage would result.

1.3 **TESTS AND INSPECTIONS**

- .1 Testing of materials and compaction of backfill and fill will be carried out by testing laboratory designated by Owner's Representative.
- .2 Not later than one week before backfilling or filling, provide to designated testing agency, 23 kg sample of backfill for fill material proposed for use.
- .3 Do not begin backfilling or filling operations until material has been approved for use by Owner's Representative.
- .4 Not later than 48 hours before backfilling or filling with approved material, notify Owner's Representative so that compaction tests can be carried out by designated testing agency.
- .5 Before commencing work, conduct, with Owner's Representative, condition survey of existing structures, trees and other plants, lawns, fencing, service poles, wires, rail tracks and paving, survey bench marks and monuments which may be affected by work.

1.4 EXISTING CONDITIONS

- .1 Examine soil report available from Owner's Representative.
- .2 Before commencing work verify the location of all buried services on and adjacent to the site.
- .3 Arrange with appropriate authority for relocation of buried services that interfere with execution of work. Pay costs of relocating services.
- .4 Remove obsolete buried services within 2 m of foundations. Cap cut-offs.

1.5 PROTECTION

- .1 Protect excavations from freezing.
- .2 Keep excavations clean, free of standing water, and loose soil.
- .3 Where soil is subject to significant volume change due to change in moisture content, cover and protect to Owner's Representative's approval.
- .4 Protect natural and man-made features required to remain undisturbed. Unless otherwise indicated or located in an area to be occupied by new construction, protect existing trees from damage.
- .5 Protect buried services that are required to remain undisturbed.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Granular B-Type I, B-Type II, Select Subgrade to OPSS1010. Sand to OPSS1004.
- .2 Crushed Granular to CCDG14.02.
- .3 Unshrinkable fill: proportioned and mixed to provide:
 - .1 Maximum compressive strength of 0.4 MPa at 28 days.
 - .2 Maximum Portland cement content of 25 kg/m³.
 - .3 Minimum strength of 0.07 MPa at 24 h.
 - .4 Concrete aggregates: to CSA-A23.1/A23.2,
 - .5 Cement: to CAN/CSA-A3001, Type GU.
 - .6 Slump: 160 to 200 mm.

PART 3 **EXECUTION**

3.1 **SITE PREPARATION**

- .1 Remove obstructions, ice and snow, from surfaces to be excavated within limits indicated.
- .2 Cut pavement or sidewalk neatly along limits of proposed excavation in order that surface may break evenly and cleanly.

3.2 **CLEARING AND GRUBBING**

- .1 Remove trees, stumps, logs, brush, shrubs, bushes, vines, undergrowth, rotten wood, dead plant material, exposed boulders and debris within areas designated on drawings.
- .2 Remove stumps and tree roots below footings, slabs, and paving, and to 600 mm below finished grade elsewhere.
- .3 Dispose of cleared and grubbed material off site daily to disposal areas acceptable to authority having jurisdiction.

3.3 **EXCAVATION**

- .1 Strip topsoil over areas to be covered by new construction, over areas where grade changes are required, and so that excavated material may be stockpiled without covering topsoil.
 - .1 Stockpile topsoil on site for later use.
- .2 Excavate as required to carry out work, in all materials met.
 - .1 Do not disturb soil or rock below bearing surfaces.
 - .2 Notify Owner's Representative when excavations are complete.
 - .3 If bearings are unsatisfactory, additional excavation will be authorized in writing and paid for as additional work. Excavation taken below depths shown without Owner's Representative written authorization to be filled with concrete of same strength as for footings at Contractor's expense.
- .3 Excavate trenches to provide uniform continuous bearing and support for 150 mm thickness of pipe bedding material on solid and undisturbed ground.
 - .1 Trench widths below point 150 mm above pipe not to exceed diameter of pipe plus 600 mm.
- .4 Excavate for slabs and paving to subgrade levels.
 - .1 In addition, remove all topsoil, organic matter, debris and other loose and harmful matter encountered at subgrade level.

3.4 BACKFILLING

- .1 Inspection: do not commence backfilling until fill material and spaces to be filled have been inspected and approved by Owner's Representative.
- .2 Remove snow, ice, construction debris, organic soil and standing water from spaces to be filled.
- .3 Lateral support: maintain even levels of backfill around structures as work progresses, to equalize earth pressures.
- .4 Compaction of subgrade: compact existing subgrade under walks, paving, and slabs on grade, to same compaction as specified for fill.
 - .1 Fill excavated areas with selected subgrade material or gravel and sand compacted as specified for fill.
- .5 Placing:
 - .1 Place backfill, fill and basecourse material in 150 mm lifts. Add water as required to achieve specified density.
 - .2 Place unshrinkable fill in areas as indicated. Consolidate and level unshrinkable fill with internal vibrators.
- .6 Compaction: compact each layer of material to following densities for material to ASTM D698,
 - .1 To underside of basecourses: 95%.
 - .2 Basecourses: 100%.
 - .3 Elsewhere: 90%.
- .7 In trenches:
 - .1 Up to 300 mm above pipe or conduit: sand placed by hand.
 - .2 Over 300 mm above pipe or conduit: native material approved by Owner's Representative.
- .8 Under slabs:
 - .1 Use granular base courses, as indicated on drawings.
- .9 Under seeded and sodded areas: use site excavated material to bottom of topsoil except in trenches and within 600 mm of foundations.
- .10 Blown rock material, not capable of fine grading, is not acceptable, imported material must be placed on this type of material.
- .11 Against foundations (except as applicable to trenches and under slabs and paving): excavated material or imported material with no stones larger than 200 mm diameter within 600 mm of structures.

3.5 GRADING

- .1 Grade so that water will drain away from buildings, walls and paved areas, to catch basins and other disposal areas approved by the Owner's Representative.
- .1 Grade to be gradual between finished spot elevations shown on drawings.

3.6 SHORTAGE AND SURPLUS

- .1 Supply all necessary fill to meet backfilling and grading requirements and with minimum and maximum rough grade variance.
- .2 Dispose of surplus material off site.

3.7 CLEANING

- .1 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

PART 1 **GENERAL**

1.1 **SUMMARY**

- .1 This Section defines correction to maximum dry density to take into account aggregate particles larger than 4.75 mm.

1.2 **REFERENCES**

- .1 Codes and standards referenced in this section refer to the latest edition thereof.
- .2 American Society for Testing and Materials (ASTM)
 - .1 ASTM C127-88, Standard Test Method for Specific Gravity and Absorption of Coarse Aggregate.
 - .2 ASTM D698, Standard Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³) (600kN-m/m³).
 - .3 ASTM D1557, Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³).
 - .4 ASTM D4253, Standard Test Methods for Maximum Index Density and Unit Weight of Soils Using a Vibratory Table.

1.3 **DEFINITIONS**

- .1 Corrected maximum dry density is defined as:
 - .1 $D = (D1 \times D2) / (F1 \times D2 + (F2 \times D1))$
 - .2 Where: D = corrected maximum dry density kg/m³.
 - .1 F1 = fraction (decimal) of total field sample passing 4.75 mm sieve.
 - .2 F2 = fraction (decimal) of total field sample retained on 4.75 mm sieve (equal to 1.00 - F1)
 - .3 D1 = maximum dry density, kg/m³ of material passing 4.75 mm sieve determined in accordance with Method A C of ASTM D698.
 - .4 D2 = bulk density, kg/m³, of material retained on 4.75 mm sieve, equal to 1000G where G is bulk specific gravity (dry basis) of material when tested to ASTM C127.
 - .3 For free draining aggregates, determine D1 (maximum dry density) to ASTM D4253, dry method when directed by Owner's Representative.

Gros Morne National Park

Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 31 05 10 – Corrected Maximum Dry Density for Fill

Page 2 of 2

PART 2 **PRODUCTS (NOT APPLICABLE)**

PART 3 **EXECUTION (NOT APPLICABLE)**

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 03 30 00 – Cast-in-Place Concrete.
- .3 Section 31 23 33.01 – Excavating, Trenching and Backfilling.
- .4 Section 32 11 16.01 – Granular Sub Base.
- .5 Section 32 11 23 – Aggregate Base Courses.

1.2 **REFERENCES**

- .1 American Society for Testing and Materials (ASTM International).
 - .1 ASTM D4791, Standard Test Method for Flat Particles, Elongated Particles, or Flat and Elongated Particles in Coarse Aggregate.

1.3 **SOURCE QUALITY CONTROL**

- .1 Source of materials to be incorporated into work or stockpiles requires approval.
- .2 Inform Owner’s Representative of proposed source of aggregates and provide access for sampling at least 4 weeks prior to commencing production.
- .3 If, in opinion of Owner’s Representative, materials from proposed source do not meet, or cannot reasonably be processed to meet, specified requirements, locate an alternative source or demonstrate that material from source in question can be processed to meet specified requirements.
- .4 Should a change of material source be proposed, advise Owner’s Representative 4 weeks in advance of proposed change to allow sampling and testing.
- .5 Acceptance of material at source does not preclude future rejection if it is subsequently found to lack uniformity, or if its field performance is found to be satisfactory.

1.4 **SAMPLES**

- .1 Submit samples in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Allow continual sampling by Owner’s Representative during production.
- .3 Provide Owner’s Representative with access to source and processed material for sampling.

- .4 Install sampling facilities at discharge end of production conveyor, to allow Owner's Representative to obtain representative samples of items being produced. Stop conveyor belt when requested by Owner's Representative to permit full cross section sampling.
- .5 Pay cost of sampling and testing of aggregates which fail to meet specified requirements.
- .6 Provide water, electric power and propane to Owner's Representative laboratory trailer at production site.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Aggregate quality: sound, hard, durable material free from soft, thin, elongated or laminated particles, organic material, clay lumps or minerals, or other substances that would act in deleterious manner for use intended.
- .2 Flat and elongated particles of coarse aggregate: to ASTM D4791.
 - .1 Greatest dimension to exceed five times least dimension.
- .3 Fine aggregates satisfying requirements of applicable section to be one, or blend of following:
 - .1 Natural sand.
 - .2 Manufactured sand.
 - .3 Screenings produced in crushing of quarried rock, boulders, gravel or slag.
- .4 Coarse aggregates satisfying requirements of applicable section to be one of or blend of following:
 - .1 Crushed rock or slag.
 - .2 Gravel and crushed gravel composed of naturally formed particles of stone.
 - .3 Light weight aggregate, including slag and expanded shale.
- .5 Gradation Limits to be within specified limits when tested to ASTM C136 and ASTM C117 – Sieve sizes to CAN/CGSB-8.1, CSA A23.2:
 - .1 Fine aggregate for concrete:

Sieve Size	% Passing
10mm	100
5mm	95-100
2.5mm	80-100
1.25mm	50-90
0.630mm	25-65
0.315mm	10-35
0.160mm	2-10

- .2 Coarse aggregate for concrete:

Sieve Size	% Passing
28mm	100
20mm	90-100
10mm	25-60
5mm	0-10
2-5mm	0-5

- .3 Granular Base Material (Class "A")

Sieve Size	% Passing
19mm	100
9.51mm	55-80
4.76mm	35-60
1.20mm	17-35
0.300mm	7-20
0.075mm	3-8

- .4 Granular Sub-Base Material (Class "B")

	% Passing
50.8mm	75-100
15.9mm	45-80
4.76mm	25-55
1.20mm	12-35
0.300mm	7-20
0.075mm	3-8

- .5 Base Type 1: See section 31 23 33.01.
.6 Base Type 2: See Section 32 23 33.01.

PART 3 **EXECUTION**

3.1 **TOPSOIL STRIPPING**

- .1 Do not handle topsoil while in wet or frozen condition or in any manner in which soil structure is adversely affected.

- .2 Commence topsoil stripping of areas as indicated after area has been cleared and removed from site.
- .3 Strip topsoil to depths as indicated. Avoid mixing topsoil with subsoil.
- .4 Stockpile in locations as directed by Owner's Representative. Stockpile height not to exceed 2.0 m.
- .5 Dispose of topsoil to location as directed by Owner's Representative off site.

3.2 AGGREGATE SOURCE PREPARATION

- .1 Prior to excavating materials for aggregate production, clear and grub area to be worked, and strip unsuitable surface materials. Dispose of cleared, grubbed and unsuitable materials as directed by Owner's Representative approved by authority having jurisdiction.
- .2 Where clearing is required, leave screen of trees between cleared area and roadways as directed.
- .3 Clear, grub and strip area ahead of quarrying or excavating operation sufficient to prevent contamination of aggregate by deleterious materials.
- .4 When excavation is completed dress sides of excavation to nominal [1.5:1] slope, and provide drains or ditches as required to prevent surface standing water.
- .5 Trim off and dress slopes of waste material piles and leave site in neat condition.

3.3 PROCESSING

- .1 Process aggregate uniformly using methods that prevent contamination, segregation and degradation.
- .2 Blend aggregates, if required, to obtain gradation requirements, percentage of crushed particles, or particle shapes, as specified. Use methods and equipment approved by Owner's Representative.
- .3 Wash aggregates, if required to meet specifications. Use only equipment approved by Engineer /Architect.
- .4 When operating in stratified deposits use excavation equipment and methods that produce uniform, homogeneous aggregate.

3.4 HANDLING

- .1 Handle and transport aggregates to avoid segregation, contamination and degradation.

3.5 STOCKPILING

- .1 Stockpile aggregates on site in locations as indicated unless directed otherwise by Owner's Representative. Do not stockpile on completed pavement surfaces.

- .2 Stockpile aggregates in sufficient quantities to meet Project schedules.
- .3 Stockpiling sites to be level, well drained, and of adequate bearing capacity and stability to support stockpiled materials and handling equipment.
- .4 Except where stockpiled on acceptably stabilized areas, provide compacted sand base not less than 300 mm in depth to prevent contamination of aggregate. Stockpile aggregates on ground but do not incorporate bottom 300 mm of pile into work.
- .5 Separate different aggregates by strong, full depth bulkheads, or stockpile far enough apart to prevent intermixing.
- .6 Do not use intermixed or contaminated materials. Remove and dispose of rejected materials as directed by Owner's Representative within 48 h of rejection.
- .7 Stockpile materials in uniform layers of thickness as follows:
 - .1 Max 1.0 m for coarse aggregate and base course materials.
 - .2 Max 2.0 m for fine aggregate and sub-base materials.
 - .3 Max 1.5 m for other materials.
- .8 Complete each layer over entire stockpile area before beginning next layer.
- .9 Uniformly spot-dump aggregates delivered to stockpile in trucks and build up stockpile as specified.
- .10 Do not cone piles or spill material over edges of piles.
- .11 Do not use conveying stackers.
- .12 During winter operations, prevent ice and snow from becoming mixed into stockpile or in material being removed from stockpile.

3.6 CLEANING

- .1 Leave aggregate stockpile site in tidy, well drained condition, free of standing surface water.
- .2 Leave any unused aggregates in neat compact stockpiles as directed by Owner's Representative.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 31 23 33.01 - Excavation, Trenching and Backfilling.

1.2 **REFERENCES**

- .1 Codes and standards referenced in this section refer to the latest edition thereof.
- .2 American Society for Testing and Materials (ASTM)
 - .1 ASTM D698, Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (600kN-m/m³)

1.3 **EXISTING CONDITIONS**

- .1 Examine subsurface investigation report which is available for inspection from Owner's Representative.
- .2 Known underground and surface utility lines and buried objects are as indicated on site plan.
- .3 Refer to dewatering in Section 31 23 33.01 - Excavating Trenching and Backfilling.

1.4 **PROTECTION**

- .1 Protect and/or transplant existing fencing trees, landscaping, natural features, bench marks, buildings, pavement, surface or underground utility lines which are to remain as directed by Owner's Representative. If damaged, restore to original or better condition unless directed otherwise.
- .2 Maintain access roads to prevent accumulation of construction related debris on roads.

PART 2 **PRODUCTS**

2.1 **MATERIALS**

- .1 Fill material: Type 3 in accordance with of Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .2 Excavated or graded material existing on site may be suitable to use as fill for grading work if approved by Owner's Representative.

PART 3 **EXECUTION**

3.1 **STRIPPING OF TOPSOIL**

- .1 Do not handle topsoil while in wet or frozen condition or in any manner in which soil structure is adversely affected as determined by Owner's Representative.
- .2 Commence topsoil stripping of areas as indicated after area has been cleared of brush, weeds and grasses and removed from site.
- .3 Strip topsoil to depths as indicated. Avoid mixing topsoil with subsoil.
- .4 Stockpile in locations as directed by Owner's Representative. Stockpile height not to exceed 2 m.
- .5 Dispose of unused topsoil as directed by Owner's Representative.

3.2 **GRADING**

- .1 Rough grade to levels, profiles, and contours allowing for surface treatment as indicated.
- .2 Rough grade to following depths below finish grades:
 - .1 250mm for concrete slabs and walks precast paving units.
- .3 Slope rough grade away from building 1:50 minimum.
- .4 Grade ditches to depth as indicated.
- .5 Prior to placing fill over existing ground, scarify surface to depth of 150 mm. Maintain fill and existing surface at approximately same moisture content to facilitate bonding.
- .6 Compact filled and disturbed areas to corrected maximum dry density to ASTM D698, as follows:
 - .1 85% under landscaped areas.
 - .2 95% under paved and walk areas.
- .7 Do not disturb soil within branch spread of trees or shrubs to remain.

3.3 **TESTING**

- .1 Inspection and testing of soil compaction will be carried out by testing laboratory designated by Owner's Representative. Refer to Sections 01 29 83 - Payment Procedures for Testing Laboratory Services and 01 45 00 – Quality Control.
- .2 Submit testing procedure, frequency of tests, to Owner's Representative for approval.

3.4 SURPLUS MATERIAL

- .1 Remove surplus material and material unsuitable for fill, grading or landscaping as directed by Owner's Representative.

END OF SECTION

PART 1 **GENERAL**

1.1 **RELATED SECTIONS**

- .1 Section 01 33 00 – Submittal Procedures.
- .2 Section 01 35 43 - Environmental Procedures.
- .3 Section 31 05 16 – Aggregate Materials.
- .4 Section 31 22 13 – Rough Grading.

1.2 **REFERENCES**

- .1 Codes and Standards referenced in this section refer to the latest edition thereof.
- .2 American Society for Testing and Materials (ASTM).
 - .1 ASTM C117, Standard Test Method for Material Finer Than 0.075 mm (No. 200) Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C136, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .3 ASTM D422, Standard Test Method for Particle-Size Analysis of Soils.
 - .4 ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³) (600 kN-m/m³).
 - .5 ASTM D1557, Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³) (2,700 kN-m/m³).
 - .6 ASTM D4318, Standard Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.
- .3 Canadian General Standards Board (CGSB).
 - .1 CAN/CGSB-8.1, Sieves, Testing, Woven Wire, Inch Series.
 - .2 CA/CGSB-8.2, Sieves, Testing, Woven Wire, Metric
- .4 Canadian Standards Association (CSA)
 - .1 CAN/CSA-A3000, Cementitious Materials Compendium (Consists of A3001, A3002, A3003, A3004 and A3005).
 - .1 CSA-A3001, Cementitious Materials for Use in Concrete.
 - .2 CSA-A23.1/A23.2, Concrete Materials and Methods of Concrete Construction/ Methods of Test and Standard Practices for Concrete.

1.3 **DEFINITIONS**

- .1 Excavation classes: two classes of excavation will be recognized; common excavation and rock excavation.

- .1 Rock excavation: excavation of material from solid masses of igneous, sedimentary or metamorphic rock which, prior to its removal, was integral with its parent mass, and boulders or rock fragments having individual volume in excess of 1 m³. Frozen material not classified as rock.
- .2 Common excavation: excavation of materials of whatever nature, which are not included under definitions of rock excavation.
- .2 Unclassified excavation: excavation of deposits of whatever character encountered in work.
- .3 Topsoil: material capable of supporting good vegetative growth and suitable for use in top dressing, landscaping and seeding.
- .4 Waste material: excavated material unsuitable for use in work or surplus to requirements.
- .5 Borrow material: material obtained from locations outside area to be graded, and required for construction of fill areas or for other portions of work.
- .6 Unsuitable materials:
 - .1 Weak and compressible materials under excavated areas.
 - .2 Frost susceptible materials under excavated areas.
 - .3 Frost susceptible materials:
 - .1 Fine grained soils with plasticity index less than 10 when tested to ASTM D4318, and gradation within limits specified when tested to ASTM D422 and ASTM C136: Sieve sizes to CAN/CGSB-8.1.

<u>Sieve Designation</u>	<u>%Passing</u>
2.00 mm	100
0.10 mm	45-100
0.02 mm	10-80
<u>0.005 mm</u>	<u>0-45</u>

- .2 Coarse grained soils containing more than 20% by mass passing 0.075 mm sieve.

1.4 QUALITY ASSURANCE

- .1 Submit design and supporting data at least 2 weeks prior to commencing work.
- .2 Design and supporting data submitted to bear stamp and signature of qualified professional engineer registered or licensed in the province of Newfoundland and Labrador.
- .3 Keep design and supporting data on site.
- .4 Engage services of qualified professional engineer who is registered or licensed in Province of Newfoundland and Labrador to design and inspect cofferdams, shoring, bracing and underpinning required for work.

- .5 Do not use soil material until written report of soil test results are reviewed and approved by Owner's Representative.

1.5 **EXISTING CONDITIONS**

- .1 Buried services:
 - .1 Before commencing work verify location of buried services on and adjacent to site.
 - .2 Arrange with appropriate authority for relocation of buried services that interfere with execution of work: pay costs of relocating services.
 - .3 Remove obsolete buried services within 2 m of foundations: cap cut-offs.
 - .4 Size, depth and location of existing utilities and structures as indicated are for guidance only. Completeness and accuracy are not guaranteed.
 - .5 Prior to commencing excavation work, notify applicable Owner or authorities having jurisdiction, establish location and state of use of buried utilities and structures. Owners or authorities having jurisdiction to clearly mark such locations to prevent disturbance during work.
 - .6 Confirm locations of buried utilities by careful test excavations.
 - .7 Maintain and protect from damage, water, sewer, gas, electric, telephone and other utilities and structures encountered as indicated.
 - .8 Where utility lines or structures exist in area of excavation, obtain direction of Owner's Representative before removing or re-routing.
 - .9 Record location of maintained, re-routed and abandoned underground lines.
 - .10 Confirm locations of recent excavations adjacent to area of excavation.
- .2 Existing buildings and surface features:
 - .1 Conduct, with Owner's Representative condition survey of existing buildings, trees and other plants, lawns, fencing, service poles, wires, rail tracks, pavement, survey bench marks and monuments which may be affected by work.
 - .2 Protect existing buildings and surface features from damage while work is in progress. In event of damage, immediately make repair to approval of Owner's Representative.
 - .3 Where required for excavation, cut roots or branches as approved by Owner's Representative.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Backfill Type 1 and Type 2 fill: properties to Section 31 05 16 - Aggregate Materials and the following requirements:
 - .1 Crushed, pit run or screened stone, gravel or sand.
 - .2 Gradations to be within limits specified when tested to ASTM C136 and ASTM C117. Sieve sizes to CAN/CGSB-8.1.

Sieve Designation	% Passing	
	Type 1	Type 2
75mm	-	100
50mm	-	-
37.5mm	-	-
25mm	100	-
19mm	75-100	-
12.5mm	-	-
9.5mm	50-100	-
4.75mm	30-70	22-85
2.00mm	20-45	-
0.425mm	10-25	5-30
0.180mm	-	-
0.075mm	3-8	0-10

- .2 Type 3 fill: selected material from excavation or other sources, approved by Engineer for use intended, unfrozen and free from rocks larger than 75 mm, cinders, ashes, sods, refuse or other deleterious materials.
- .3 Rock Fill: Rock fill material from the excavation or other sources approved by Engineer to meet the following requirements.
 - .1 Quarry rock consisting of well graded hard durable particles free from clay lumps, frozen material and other deleterious materials, and free from splits, seams or defects likely to impair its soundness during handling or under action of water.
 - .2 Relative density (formally specific gravity): to ASTM C12, not less than 2.56.
 - .3 Gradations to be within limits specified when tested to: ASTM C136 and ASTM C117. Sieve sizes: to CAN/CGSB-8.1 – 88, rather than ASTM E11-87.

Sieve Designation	% Passing
150mm	100
100mm	90-100
75mm	55-85
50mm	35-65
38mm	25-40
25mm	15-25
19mm	7-15
12mm	3-8
10mm	3

- .4 Quarried rock: to be free from splits, seams or defects likely to impair its soundness during handling to approval of Engineer.
- .5 Rock, cubical and angular in shape with ratio of maximum to minimum dimensions of less than 3.

PART 3 EXECUTION

3.1 SITE PREPARATION

- .1 Remove obstructions, ice and snow, from surfaces to be excavated within limits indicated.

3.2 PREPARATION/PROTECTION

- .1 Protect existing features in accordance with Section 01 56 00 - Temporary Barriers and Enclosures and applicable local regulations.
- .2 Keep excavations clean, free of standing water, and loose soil.
- .3 Where soil is subject to significant volume change due to change in moisture content, cover and protect to Owner’s Representative’s approval.
- .4 Protect natural and man-made features required to remain undisturbed. Unless otherwise indicated or located in an area to be occupied by new construction, protect existing trees from damage. Protect buried services that are required to remain undisturbed.

3.3 STOCKPILING

- .1 Stockpile fill materials in areas designated by Owner's Representative. Stockpile granular materials in manner to prevent segregation.
- .2 Protect fill materials from contamination.

3.4 COFFERDAMS, SHORING, BRACING AND UNDERPINNING

- .1 Maintain sides and slopes of excavations in safe condition by appropriate methods and in accordance with Section 01 35 30 - Health and Safety Requirements and Occupational Health and Safety Act for the Province of Newfoundland and Labrador.
- .2 Obtain permit from authority having jurisdiction for temporary diversion of water course.
- .3 Construct temporary works to depths, heights and locations as indicated or approved by Owner's Representative.
- .4 During backfill operation:
 - .1 Unless otherwise as indicated or as directed by Owner's Representative remove sheeting and shoring from excavations.
 - .2 Do not remove bracing until backfilling has reached respective levels of such bracing.
 - .3 Pull sheeting in increments that will ensure compacted backfill is maintained at an elevation at least 500 mm above toe of sheeting.
- .5 When sheeting is required to remain in place, cut off tops at elevations as indicated.
- .6 Upon completion of substructure construction:
 - .1 Remove cofferdams, shoring and bracing.
 - .2 Remove excess materials from site and restore water courses as indicated and as directed by Owner's Representative.

3.5 DEWATERING AND HEAVE PREVENTION

- .1 Keep excavations free of water while work is in progress.
- .2 Submit for Owner's Representative's review details of proposed dewatering or heave prevention methods, such as dikes, well points, and sheet pile cut-offs.
- .3 Avoid excavation below groundwater table if quick condition or heave is likely to occur. Prevent piping or bottom heave of excavations by groundwater lowering, sheet pile cut-offs, or other means.
- .4 Protect open excavations against flooding and damage due to surface run-off.
- .5 Provide flocculation tanks, settling basins, or other treatment facilities to remove suspended solids or other materials before discharging to storm sewers, water courses or drainage areas.

3.6 EXCAVATION

- .1 Excavate to lines, grades, elevations and dimensions as indicated by Owner's Representative.
- .2 Remove concrete, masonry, paving, walks, demolished foundations and rubble and other obstructions encountered during excavation in accordance with Section 02 41 13 - Selective Site Demolition.
- .3 Excavation must not interfere with bearing capacity of adjacent foundations.
- .4 Do not disturb soil within branch spread of trees or shrubs that are to remain. If excavating through roots, excavate by hand and cut roots with sharp axe or saw.
- .5 For trench excavation, unless otherwise authorized by Owner's Representative in writing, do not excavate more than 30 m of trench in advance of installation operations and do not leave open more than 15 m at end of day's operation.
- .6 Keep excavated and stockpiled materials a safe distance away from edge of trench as directed by Owner's Representative.
- .7 Restrict vehicle operations directly adjacent to open trenches.
- .8 Dispose of surplus and unsuitable excavated material off site.
- .9 Do not obstruct flow of surface drainage or natural watercourses.
- .10 Earth bottoms of excavations to be undisturbed soil, level, free from loose, soft or organic matter.
- .11 Notify Owner's Representative when bottom of excavation is reached.
- .12 Obtain Owner's Representative approval of completed excavation.
- .13 Remove unsuitable material from trench bottom to extent and depth as directed by Owner's Representative.
- .14 Correct unauthorized over-excavation as follows:
 - .1 Fill under bearing surfaces and footings with concrete specified for footings.
 - .2 Fill under other areas with Type 2 fill compacted to not less than 95% of corrected maximum dry density.
- .15 Hand trim, make firm and remove loose material and debris from excavations. Where material at bottom of excavation is disturbed, compact foundation soil to density at least equal to undisturbed soil. Clean out rock seams and fill with concrete mortar or grout to approval of Owner's Representative.

3.7 FILL TYPES AND COMPACTION

- .1 Use fill of types as indicated or specified below. Compaction densities are percentages of maximum densities obtained from ASTM D698 corrected maximum dry density.
 - .1 Exterior side of perimeter walls: use Type 3 fill to subgrade level. Compact to 95%.
 - .2 Within building area: use Type 2 to underside of base course for floor slabs. Compact to 98%.
 - .3 Under concrete slabs: provide 150 mm compacted thickness base course of Type 1 fill to underside of slab. Compact base course to 100%.
 - .4 Retaining walls: use Type 2 fill to subgrade level on high side for minimum 500 mm from wall and compact to 95%. For remaining portion, use Type 3 fill compacted to 95%.
 - .5 To correct over excavation in trenches: use Type 2 fill to underside of sand bedding compacted to 95%.

3.8 BEDDING AND SURROUND OF UNDERGROUND SERVICES

- .1 Place and compact granular material for bedding and surround of underground services as indicated.
- .2 Place bedding and surround material in unfrozen condition.

3.9 BACKFILLING

- .1 Vibratory compaction equipment: approved by Owner's Representative.
- .2 Do not proceed with backfilling operations until Owner's Representative has inspected and approved installations.
- .3 Areas to be backfilled to be free from debris, snow, ice, water and frozen ground.
- .4 Do not use backfill material which is frozen or contains ice, snow or debris.
- .5 Place backfill material in uniform layers not exceeding 150 mm compacted thickness up to grades indicated. Compact each layer before placing succeeding layer.
- .6 Backfill around installations.
 - .1 Place bedding and surround material as specified elsewhere.
 - .2 Do not backfill around or over cast-in-place concrete within 24 hours after placing of concrete.
 - .3 Place layers simultaneously on both sides of installed work to equalize loading. Difference not to exceed 600 mm.
 - .4 Where temporary unbalanced earth pressures are liable to develop on walls or other structures.

- .1 Permit concrete to cure for minimum 14 days or until it has sufficient strength to withstand earth and compaction pressure, and approval obtained from Owner's Representative, or
- .2 If approved by Owner's Representative, erect bracing or shoring to counteract unbalance, and leave in place until removal is approved by Owner's Representative.

3.10 RESTORATION

- .1 Upon completion of work, remove waste materials and debris, trim slopes, and correct defects as directed by Owner's Representative.
- .2 Replace topsoil as indicated by Owner's Representative.
- .3 Reinstate lawns to elevation which existed before excavation.
- .4 Reinstate pavement and sidewalks distributed by excavation to thickness, structure, and elevation which existed before excavation.
- .5 Clean and reinstate areas affected by work as directed by Owner's Representative.
- .6 Use temporary plating to support traffic loads over unshrinkable fill for initial 24 h.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 31 05 16 - Aggregate Materials.
- .2 Section 31 23 33.01 - Excavating, Trenching and Backfilling.
- .3 Section 32 11 23 - Aggregate Base Courses.

1.2 REFERENCES

- .1 American Society for Testing and Materials (ASTM).
 - .1 ASTM C117, Standard Test Method for Material Finer Than 0.075 mm Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C136, Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates.
 - .3 ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³) (600 kN-m/m³).
 - .4 ASTM D1557, Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³) (2,700 kN-m/m³).
 - .5 ASTM D4318, Standard Test Methods for Liquid Unit, Plastic Unit and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB).
 - .1 CAN/CGSB-8.1, Sieves, Testing, Woven Wire, Inch series.
 - .2 CAN/CGSB-8.2, Sieves, Testing, Woven Wire, Metric.
 - .3 Codes and standards referenced in this section refer to the latest edition thereof.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Granular sub-base material to Section 31 05 16 - Aggregate Materials and following requirements:
 - .1 Crushed pit run or screened stone, gravel or sand.
 - .2 Granulations to be within limits specified when tested to ASTM C136 and ASTM C117 - sieve sizes to CAN/CGSB-8.1.
 - .1 Granulation to:

<u>Sieve Designation</u>	<u>% Passing (Base Type 2)</u>
100 mm	-
75 mm	-
50 mm	100
37.5 mm	-

Gros Morne National Park
Port au Choix Visitor Centre Upgrades, PN: 1135

September 2016

Section 32 11 16.01 – Granular Sub-Base

Page 2 of 3

25	mm	60-100
19	mm	-
12.5	mm	38-70
9.5	mm	-
4.75	mm	25-55
2.00	mm	13-42
0.425	mm	5-28
0.180	mm	-
0.075	mm	2-10

- .3 Other properties as follows:
 - .1 Liquid limit: to ASTM D4318, maximum 25
 - .2 Plasticity index: to ASTM D4318, maximum 6

PART 3 **EXECUTION**

3.1 **PLACING**

- .1 Place granular sub-base after subgrade is inspected and approved by Owner's Representative.
- .2 Construct granular sub-base to depth and grade in areas indicated.
- .3 Ensure no frozen material is placed.
- .4 Place material only on clean unfrozen surface, free from snow or ice.
- .5 Place granular sub-base materials using methods which do not lead to segregation or degradation.
- .6 Place material to full width in uniform layers not exceeding 150 mm compacted thickness. Owner's Representative may authorize thicker lifts (layers) if specified compaction can be achieved.
- .7 Shape each layer to smooth contour and compact to specified density before succeeding layer is placed.
- .8 Remove and replace portion of layer in which material has become segregated during spreading.

3.2 **COMPACTION**

- .1 Compaction equipment to be capable of obtaining required material densities.
- .2 Compact to density of not less than 98% corrected maximum dry density ASTM D698.
- .3 Shape and roll alternately to obtain smooth, even and uniformly compacted sub-base.

- .4 Apply water as necessary during compaction to obtain specified density.
- .5 In areas not accessible to rolling equipment, compact to specified density with mechanical tampers approved by Owner's Representative.
- .6 Correct surface irregularities by loosening and adding or removing material until surface is within specified tolerance.

3.3 SITE TOLERANCES

- .1 Finished sub-base surface to be within 10 mm of elevation as indicated but not uniformly high or low.

3.4 PROTECTION

- .1 Maintain finished sub-base in condition conforming to this section until succeeding base is constructed, or until granular sub-base is accepted by Owner's Representative.

END OF SECTION

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 31 05 16 - Aggregate Materials.
- .2 Section 32 11 16.01 - Granular Sub Base.

1.2 REFERENCES

- .1 American Society for Testing and Materials (ASTM).
 - .1 ASTM C117, Standard Test Method for Material Finer Than 0.075 mm Sieve in Mineral Aggregates by Washing.
 - .2 ASTM C136, Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine.
 - .3 ASTM D136, Standard Test Method for Sieve Analysis of Fine and Course Aggregated.
 - .4 ASTM D698, Stand Test Methods for Laboratory Compaction Characteristics of Soil Using standard Effort (12,400 ft-lbf/ft³)(600 N m/m³).
 - .5 ASTM D1557, Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³) (2,700 kN-m/m³).
 - .6 ASTTM D 1883, Standard Test Method of CBR (California Bearing Ratio) of Laboratory Compacted Soil.
 - .7 ASTM D4318, Standard Test Methods for Liquid Unit, Plastic Unit and Plasticity Index of Soils.
- .2 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB-8.1, Sieves, Testing, Woven-Wire, Inch Series.
 - .2 CAN/CGSB-8.2-, Sieves, Testing, Woven Wire, Metric.
 - .3 Codes and standards referenced in this section refer to the latest edition thereof.

1.3 DELIVERY, STORAGE, AND HANDLING

- .1 Deliver and stockpile aggregates in accordance with Section 31 05 16 – Aggregate Materials. Stockpile minimum 50% of total aggregate required prior to commencing operation.
- .2 Store cement in weathertight bins or silos that provide protection from dampness and easy access for inspection and identification of each shipment.

PART 2 PRODUCTS

2.1 MATERIALS

.1 Granular base: material to Section 31 05 16- Aggregate Materials and the following requirements:

- .1 Crushed stone or gravel.
- .2 Granulations to be within limits specified when tested to ASTM C136 and ASTM C117. Sieve sizes to CAN/CGSB - 8.1.

.1 Granulation to:

Sieve Designation	% Passing (Base Type 1)
100 mm	-
75 mm	-
50 mm	-
37.5 mm	-
25 mm	-
19 mm	100
12.5 mm	70-100
9.5 mm	-
4.75 mm	40-70
2.00 mm	23-50
0.425	7-25
0.180 mm	-
0.075 mm	3-8

- .3 .Liquid limit: to ASTM D4318, maximum 25
- .4 Plasticity index: to ASTM D4318 maximum 6
- .5 Los Angeles degranulation: to ASTM C131. Maximum % loss by weight 45.
- .6 Crushed particles: at least 60% of particles by mass within each of following sieve designation ranges to have at least 1 (one) freshly fractured face. Materials to be divided into ranges using methods of ASTM C136.

Passing Retained on

50 mm	to	25 mm
25 mm	to	19 mm
19 mm	to	4.75 mm

- .7 Soaked CBR to ASTM D1833, min 100 when compacted to 100% of ASTM D1557.

PART 3 EXECUTION

3.1 SEQUENCE OF OPERATION

.1 Place granular base after granular sub base surface is inspected and approved by Owner's Representative.

- .1 Construct granular base to depth and grade in areas indicated.
- .2 Ensure no frozen material is placed.

- .3 Place material only on clean unfrozen surface, free from snow and ice.
- .4 Place material using methods which do not lead to segregation or degradation of aggregate.
- .5 Place material to full width in uniform layers not exceeding 150 mm compacted thickness. Owner's Representative may authorize thicker lifts (layers) if specified compaction can be achieved.
- .6 Shape each layer to smooth contour and compact to specified density before succeeding layer is placed.
- .7 Remove and replace that portion of layer in which material becomes segregated during spreading.
- .2 Compaction Equipment
 - .1 Compaction equipment to be capable of obtaining required material densities.
- .3 Compacting
 - .1 Compact to density not less than 100% corrected maximum dry density ASTM D698
 - .2 Shape and roll alternately to obtain smooth, even and uniformly compacted base.
 - .3 Apply water as necessary during compacting to obtain specified density.
 - .4 In areas not accessible to rolling equipment, compact to specified density with mechanical tampers approved by Owner's Representative.
 - .5 Correct surface irregularities by loosening and adding or removing material until surface is within specified tolerance.

3.2 SITE TOLERANCES

- .1 Finished base surface to be within plus or minus 10 mm of established grade and cross section but not uniformly high or low.

3.3 PROTECTION

- .1 Maintain finished base in condition conforming to this section until succeeding material is applied or until acceptance by Owner's Representative.

END OF SECTION