



RETURN BIDS TO:
RETOURNER LES SOUMISSIONS À:
Bid Receiving Public Works and Government
Services Canada/Réception des soumissions
Travaux publics et Services gouvernementaux
Canada
1713 Bedford Row
Halifax, N.S./Halifax, (N.É.)
B3J 1T3
Nova Scotia
Bid Fax: (902) 496-5016

SOLICITATION AMENDMENT

MODIFICATION DE L'INVITATION

The referenced document is hereby revised; unless otherwise indicated, all other terms and conditions of the Solicitation remain the same.

Ce document est par la présente révisé; sauf indication contraire, les modalités de l'invitation demeurent les mêmes.

Comments - Commentaires

Vendor/Firm Name and Address
Raison sociale et adresse du
fournisseur/de l'entrepreneur

Issuing Office - Bureau de distribution
Atlantic Region Acquisitions/Région de l'Atlantique
Acquisitions
1713 Bedford Row
Halifax, N.S./Halifax, (N.É.)
B3J 3C9
Nova Scot

| | |
|---|--|
| Title - Sujet 1-Ton Dump Truck | |
| Solicitation No. - N° de l'invitation 5P119-160091/A | Amendment No. - N° modif. 001 |
| Client Reference No. - N° de référence du client 5P119-16-0091 | Date 2016-09-28 |
| GETS Reference No. - N° de référence de SEAG PW-\$HAL-405-9937 | |
| File No. - N° de dossier HAL-6-77025 (405) | CCC No./N° CCC - FMS No./N° VME |
| Solicitation Closes - L'invitation prend fin at - à 02:00 PM on - le 2016-11-07 | |
| Time Zone Fuseau horaire Atlantic Daylight Saving Time ADT | |
| F.O.B. - F.A.B. Plant-Usine: <input type="checkbox"/> Destination: <input checked="" type="checkbox"/> Other-Autre: <input type="checkbox"/> | |
| Address Enquiries to: - Adresser toutes questions à: MacDonald, Ashley | Buyer Id - Id de l'acheteur hal405 |
| Telephone No. - N° de téléphone (902) 496-5291 () | FAX No. - N° de FAX (902) 496-5016 |
| Destination - of Goods, Services, and Construction: Destination - des biens, services et construction: | |

Instructions: See Herein

Instructions: Voir aux présentes

| | |
|--|--|
| Delivery Required - Livraison exigée | Delivery Offered - Livraison proposée |
| Vendor/Firm Name and Address Raison sociale et adresse du fournisseur/de l'entrepreneur | |
| Telephone No. - N° de téléphone Facsimile No. - N° de télécopieur | |
| Name and title of person authorized to sign on behalf of Vendor/Firm (type or print) Nom et titre de la personne autorisée à signer au nom du fournisseur/ de l'entrepreneur (taper ou écrire en caractères d'imprimerie) | |
| Signature | Date |

Solicitation No. - N° de l'invitation
5P119-160091/A
Client Ref. No. - N° de réf. du client
5P119-160091

Amd. No. - N° de la modif.
001
File No. - N° du dossier
HAL-6-77025

Buyer ID - Id de l'acheteur
HAL405
CCC No./N° CCC - FMS No./N° VME

Amendment 001

Amendment 001 is being issued to answer the following question:

Question 1: Can 17 inch wheels be accepted as a minimum?

Answer 1: Yes. Please see amended Annex A and Annex C (attached) to reflect these changes.

Wheels and Tires: Item 2.

All other terms and conditions remain the same

Solicitation No. - N° de l'invitation
5P119-160091/A
Client Ref. No. - N° de réf. du client
5P119-160091
ANNEX "A"

Amd. No. - N° de la modif.
001
File No. - N° du dossier
HAL-6-77025

Buyer ID - Id de l'acheteur
HAL405
CCC No./N° CCC - FMS No./N° VME

MANDATORY REQUIREMENT

Truck Chassis Specifications

- 1) Gross Vehicle Weight (GVW): Class III - 10001–14000 lb (4536–6350 kg)
- 2) Wheelbase: Must accommodate a 11' to 12' Landscape Dump Box
- 3) Overall Length: Overall Length: Must accommodate a 11' to 12' Landscape Dump Box
- 4) Cab to Axle: Must accommodate a 11' to 12' Landscape Dump Box
- 5) Limited Slip Differential
- 6) Configuration: 4X2

Engine Specifications

- 1) Engine Type: Gasoline V8 or V10 – Water cooled - Minimum
- 2) Combustion System: Direct injection
- 3) Engine: 300 HP- Minimum
- 4) Transmission: Automatic

Wheels and Tires

- 1) Wheels: Dual Rear Wheels- Minimum
- 2) Wheels and Tires: 17 inch-Minimum

Breaks

- 1) Service Brake: Hydraulic, Front and Rear Disc with Auto adjust
- 2) Control: Hydraulic dual circuit with Antilock Brake System

Steering

- 1) Type: Tilt Steering Column
- 2) Steering: Power Assist

Cab Equipment

- 1) Construction: Steel or Aluminium
- 2) Seating: Three- Driver Seat Adjustable
- 3) Seat Belts: 3- Point type
- 4) Mirrors: Power mirror – Telescopic or Camper Style
- 5) Air Conditioning: Air Conditioning
- 6) Windshield Wipers: Variable speed Electric Window Wipers
- 7) Windows: Electric Power
- 8) Cruise Control: Yes
- 9) Power Outlet: 12V
- 10) Door Locks: Power Door Locks
- 11) Exterior Color: White
- 12) Fuel Tank: 100L Capacity- Minimum
- 13) Conventional Cab: Must accommodate 3 Persons- Minimum
- 14) Radio: AM/FM- Minimum
- 15) Floor Covering: Vinyl

Solicitation No. - N° de l'invitation
5P119-160091/A
Client Ref. No. - N° de réf. du client
5P119-160091

Amd. No. - N° de la modif.
001
File No. - N° du dossier
HAL-6-77025

Buyer ID - Id de l'acheteur
HAL405
CCC No./N° CCC - FMS No./N° VME

Electrical Equipment

- 1) Batteries: 2 Parallel Connection – 12V each
- 2) Alarm: Back up
- 3) Safety Lighting: Amber Flashing safety light
- 4) Exterior Wiring: All exterior wiring shall be enclosed in body components or conduit

Landscape Dump Box

- 1) Construction: Steel
- 2) Nominal Width: 7' Minimum, 8' Maximum
- 3) Nominal Length: 11' Minimum, 12' Maximum
- 4) Dump: Hydraulic Dump lift allowing rear end dumping - 8 ton. - Minimum
- 5) Sides:
 - Sides must be mounted on hinges allowing operation while in the upright or down position when driving.
 - The drop sides must be minimum 15" high and equipped with anchoring brackets located on the top in order to house wood panels (2x6" or 2x8") allowing to raise the protected height temporarily
 - When closed, the drop sides must be sealed sufficiently to allow the transport of fine materials such as sand.
- 6) Bed: Bed is to be steal. Constructed from flat stock only, no ribs, checker plate etc.
- 7) Tailgate: 20" Minimum height, dual hinged to allow tailgate to lay flat, or to hinge at the top to allow for dumping of construction materials
- 8) Box Front:
 - The protective guard for the rear of the cab must accommodate the height of the cab and must be equipped with a metal screen window
 - The protective guard (cab shield) for the top of the cab must cover at least 20% of the top section of the cab.
 - The protective guards must not compromise the access and the efficiency of the cab equipment and components such as lights
- 9) Accessories:
 - Provide anchoring devices for securing straps on both sides
 - Trailer hitch receiver for class 3 hitch or greater
 - Brake Module - Towing Package

Documentation

The Contractor **must** provide the following documentation:

- Owner's Manual. The technical evaluation will assess whether all mandatory requirements are met using information provided with a bid. Canada reserves the right, but is under no obligation to clarify any information or compliance with a mandatory requirement with a bidder.

Delivery:

All deliverables **must** be received on or before **March 31, 2017** to
40 Dalvay Crescent
Dalvay, PE C1A 1P0

Annex D

Specifications: Medium Truck with landscape dump box

BIDDERS MUST INDICATE THEIR CONFORMANCE TO THE SPECIFICATIONS

| | | | | | Mandatory (M) | Yes | No |
|-------------------------------------|-----------------------------|--|---|---------|---------------|-----|----|
| Truck Chassis Specifications | | | | | | | |
| 1 | Gross Vehicle Weight (GVW): | | Class III - 10001–14000 lb (4536–6350 kg) | | M | | |
| 2 | Wheelbase: | | Must accommodate a 11' to 12' Landscape Dump Box | | M | | |
| 3 | Overall Length: | | Must accommodate a 11' to 12' Landscape Dump Box | | M | | |
| 4 | Cab to Axle: | | Must accommodate a 11' to 12' Landscape Dump Box | | M | | |
| 5 | Limited Slip Differential: | | | | M | | |
| 6 | Configuration: | | 4X2 | | M | | |
| Engine Specifications | | | | | | | |
| 1 | Engine Type: | | Gasoline V8 or V10 - Water cooled | Minimum | M | | |
| 2 | Combustion System: | | Direct injection | | M | | |
| 3 | Engine: | | 300HP | Minimum | M | | |
| 4 | Transmission: | | Automatic | | M | | |
| Wheels and Tires | | | | | | | |
| 1 | Wheels: | | Dual Rear Wheels | Minimum | M | | |
| 2 | Wheels and Tires: | | 17 inch | Minimum | M | | |
| Brakes | | | | | | | |
| 1 | Service Brake: | | Hydraulic, Front and Rear Disc with Auto adjust. | | M | | |
| 2 | Control: | | Hydraulic dual circuit with Antilock Brake System | | M | | |
| Steering | | | | | | | |
| 1 | Type: | | Tilt steering column | | M | | |
| 2 | Steering: | | Power Assist | | M | | |
| Cab Equipment | | | | | | | |
| 1 | Construction: | | Steel or Aluminium | | M | | |
| 2 | Seating: | | Three - Driver Seat adjustable | | M | | |
| 3 | Seat Belts: | | 3 - point type | | M | | |
| 4 | Mirrors: | | Power mirrors - Telescopic or Camper Style | | M | | |
| 5 | Air Conditioning: | | Air Conditioning: | | M | | |
| 6 | Windshield Wipers: | | Variable speed Electric Window Wipers | | M | | |
| 9 | Windows: | | Electric Power | | M | | |
| 10 | Cruise Control: | | Yes | | M | | |
| 11 | Power Outlet | | 12V | | M | | |
| 12 | Door Locks: | | Power Door locks | | M | | |
| 13 | Exterior Color: | | White | | M | | |
| 14 | Fuel Tank: | | 100L Capacity | Minimum | M | | |
| 15 | Conventional Cab: | | Must accommodate 3 Persons | Minimum | M | | |
| 16 | Radio | | AM/FM | Minimum | M | | |
| 17 | Floor Covering | | Vinyl | | M | | |
| Electrical Equipment | | | | | | | |
| 1 | Batteries: | | 2 parallel connection - 12V each | | M | | |
| 2 | Alarm: | | Back up | | M | | |
| 3 | Safety Lighting | | Amber flashing safety light | | M | | |
| 4 | Exterior wiring | | All exterior wiring shall be enclosed in body components or conduit. | | M | | |
| Landscape Dump Box | | | | | | | |
| 1 | Construction | | Steel | | M | | |
| 2 | Nominal width | | 7' Minimum, 8' Maximum | | M | | |
| 3 | Nominal Length | | 11' Minimum, 12' Maximum | | M | | |
| 4 | Dump | | Hydraulic Dump lift allowing rear end dumping - 8 ton. | Minimum | M | | |
| 5 | Sides | | Sides must be mounted on hinges allowing operation while in the upright or down position when driving. | | M | | |
| 6 | Sides | | The drop sides must be minimum 15" high and equipped with anchoring brackets located on the top in order to house wood panels (2x6" or 2x8") allowing to raise the protected height temporarily | | M | | |
| 7 | Sides | | When closed, the drop sides must be sealed sufficiently to allow the transport of fine materials such as sand. | | M | | |
| 8 | Bed | | Bed is to be steel. Constructed from flat stock only, no ribs, checkerplate etc. | | M | | |
| 9 | Tailgate | | 20" Minimum height, dual hinged to allow tailgate to lay flat, or to hinge at the top to allow for dumping of construction materials | | M | | |
| 10 | Box Front | | The protective guard for the rear of the cab must accommodate the height of the cab and must be equipped with a metal screen window | | M | | |
| 11 | Box Front | | The protective guard (cab shield) for the top of the cab must cover at least 20% of the top section of the cab. | | M | | |
| 12 | Box Front | | The protective guards must not compromise the access and the efficiency of the cab equipment and components such as lights | | M | | |
| 12 | Accessories | | Provide anchoring devices for securing straps on both sides | | M | | |
| 13 | Accessories | | Trailer hitch receiver for class 3 hitch or greater | | M | | |
| 14 | Accessories | | Brake Module - Towing Package | | M | | |