



Fisheries and Oceans  
Canada

Pêches et Océans  
Canada

Canada

## **Small Craft Harbours Branch**

### **SPECIFICATIONS**

**WHARF 404 RECONSTRUCTION**

**UNDER BUILDINGS 1007 & 1008**

**STEVESTON GULF SMALL CRAFT HARBOUR**

**RICHMOND, BRITISH COLUMBIA**

**AUGUST 2016**

**SUMMARY OF WORK**

<b>SECTION</b>	<b>TITLE</b>
01 11 00	Summary of Work
01 15 00	Owner Supplied Materials

**GENERAL REQUIREMENTS**

<b>SECTION</b>	<b>TITLE</b>
01 13 00	General Requirements

**TECHNICAL SPECIFICATIONS**

<b>SECTION</b>	<b>TITLE</b>
00 20 60	Demolition
00 51 00	Steel
00 99 00	Timber
01 35 43	Environmental Procedures

**HEALTH AND SAFETY REQUIREMENTS**

<b>SECTION</b>	<b>TITLE</b>
01 35 29 06	Health and Safety Requirements

**DRAWINGS**

<b>NUMBER</b>	<b>DESCRIPTION</b>
S-WR-001	General Arrangement of Wharf 404 Reconstruction Under Building 1008
S-WR-002	General Arrangement of Wharf 404 Reconstruction Under Building 1007
S-WR-003	Concrete Jacket & Bracket Details
STG-1	Steveston Gulf Site Map

**END OF SECTION**

## 1 SITE LOCATION

- .1 The project is located in Steveston Gulf, which is on the north shore of the south arm of the Fraser River in Richmond, BC. Wharf reconstruction will be under Building No. 1007 and 1008. These buildings are located on Wharf 404, situated directly west of the Gulf of Georgia Cannery heritage building and they provide net storage and repair facilities for Canfisco operations. Refer to Drawing STG-1 for the location of these buildings (Building 1008 is labelled as BLDG 8 and Building 1007 is labelled as BLDG 7).

## 2 DEFINITIONS

- .1 Throughout contract documents, the words “Owner,” “Harbour Authority”, “Engineer,” or “Department,” shall be defined as follows:
  - .1 Owner  
Small Craft Harbours Program of the Department of Fisheries and Oceans Canada, 200-401 Burrard Street Vancouver BC V6C 3S4
  - .2 Harbour Authority (HA)  
For the most part, Harbour Authorities are incorporated, not-for-profit organizations. They have a board of directors and members, who are representative of local interest groups and harbour users. Each Harbour Authority is a unique and independent business responsible for managing, operating and maintaining one or more public fishing harbours, through a lease agreement with Small Craft Harbours.
  - .3 Engineer  
An employee of the Owner or Consultant assigned by the Owner as the Engineer for this project, or the Engineer’s representative assigned by the Engineer as his representative for the project.
  - .4 Contractor  
The party accepted by the Owner with whom a formal contract is entered to complete the work of this project.
  - .5 Department  
The Department of Fisheries and Oceans Canada.
  - .6 The Site  
Steveston Small Craft Harbour: 12740 Trites Road, Richmond, BC V7E 3R8.

## 3 WORK INCLUDED

- .1 In general, the nature of work consists of light to heavy wharf repairs under Building 1007 and 1008. This work is to be completed with a minimum 3-person carpentry ground crew for 180 man-days. For example, a 3-person crew would be  $180/3 = 60$  working days. The Contractor’s ground crew shall be self-supervising and efficient in daily work activities and will have periodic inspection and direction by the Engineer or Owner representative.
- .2 Wharf repairs consists of, but are not limited to, replacing timber decking, stringers, caps, corbels, subcaps and replacing bearing piles with stubs and concrete jackets. This work includes field cutting and treating as per Section 00 99 00. The Contractor’s ground crew

shall conduct work where shown on drawings S-WR-001 & S-WR-002. Bearing pile replacement and concrete jacket work shall be done in accordance to S-WR-003.

- .3 The Contractor is required to supply materials shown below in Section 01 11 00, 3.5.1.2 (timber), 3.5.1.3 (hardware) and 3.5.1.4 (misc. materials). All other materials required for the work will be supplied by the Owner. A list of Owner supplied materials is provided in Section 01 15 00. Owner supplied materials will be accessible at an Owner specified laydown area on Site (to be determined after Contract Award).
- .4 All work and materials shall conform to Technical Specifications in Sections 00 20 60, 00 51 00, 00 99 00 and 01 35 43.

**.5 Description of Items**

With reference to items listed in the **Construction Tender Form: 13.0 Combined Price Schedule**, work consists of, but is not limited to, the following items:

**.1 Lump Sum Items**

**.1 Mobilization / Demobilization**

The lump sum cost of mobilization/demobilization includes the following:

- .1 Moving all crew and equipment on and off the Site.
- .2 Site clean-up after completion of the work.
- .3 Supply equipment for temporary support of the wharf for replacement of bearing piles and wharf timbers (based on all the repairs identified on S-WR-001 & S-WR-002).
- .4 Dispose all replaced items (based on all the repairs identified on S-WR-001 & S-WR-002), cut-offs and waste material in accordance to Section 01 13 00, 23.

**.2 Supply Timber**

The lump sum cost to supply timber includes the following:

- .1 All timber shall conform to Section 00 99 00.
- .2 Supply all labour and equipment required for ordering, inspection, certification that timber meets specifications and delivery (including loading and unloading) of timber to Site.
- .3 Supply the following timber quantities, sizes, surfacing and treatment:
- .1 200 pieces of 26' long 3"x12" S1S2E (2.75"x11.5") untreated douglas fir decking.

- .2 200 pieces of 20' long 3"x12" S1S2E (2.75"x11.5") untreated douglas fir decking.
- .3 300 pieces of 16' long 3"x12" S1S2E (2.75"x11.5") untreated douglas fir decking.

### **.3 Supply Hardware**

The lump sum cost to supply hardware includes the following:

- .1 All hardware shall conform to Section 00 51 00.
- .2 This item includes all labour, equipment and materials required for ordering, verifying quantities and dimensions and delivering (including loading and unloading) hardware to Site.
- .3 Supply the following hardware:
  - .1 70 units of 3/4" diameter x 20" long galvanized drift pins.
  - .2 45 units of 1" diameter x 20" long galvanized drift pins.
  - .3 17 boxes (50lbs each) of 6" Lg. Galv. Ardox Nails

### **.4 Supply Misc. Materials**

The lump sum cost to supply misc. materials includes the following:

- .1 All brackets shall conform to Section 00 51 00.
- .2 This item includes all labour, equipment and materials required for ordering, verifying quantities and dimensions and delivering (including loading and unloading) misc. materials to Site.
- .3 Supply the following misc. materials (UHMW for shimming):
  - .1 64 units (2 – 4'x8' sheets) of 12" wide x12" length x 1/16" thick UHMW.
  - .2 64 units (2 – 4'x8' sheets) of 12" wide x12" length x 1/8" thick UHMW.
  - .3 64 units (2 – 4'x8' sheets) of 12" wide x12" length x 3/8" thick UHMW.
  - .4 64 units (2 – 4'x8' sheets) of 12" wide x12" length x 1/2" thick UHMW.
  - .5 50 units of 9.5 x 102 x 102 x 500 custom galvanized L-brackets as per S-WR-003, Detail 1.
  - .6 50 units of 9.5 x 102 x 102 x 850 custom galvanized L-brackets as per S-WR-003, Detail 2.

- .7 Supply field treatment for ACZA and Creosote cut ends in accordance to Section 00 99 00.

## **.2 Unit Price Items**

### **.1 Minimum 3 Man Labour Crew**

The unit cost per man-day for a minimum 3 man labour crew includes the following:

- .1 Supply a minimum 3 man labour crew. The crew shall include a foreman for the coordination and safety of the crew.
- .2 Supply all necessary equipment and tools required to execute light to heavy wharf construction repairs shown on Drawings: S-WR-001 and S-WR-002. Concrete work requires, but is not limited to, cement mixers, power supply (cords/generators), shovels and wheel barrows.
- .3 Include all daily live-out expenses for the work crew.
- .4 The crew shall be professional, self-sufficient and carryout work shown on Drawings: S-WR-001, S-WR-002 & S-WR-003, in accordance to Technical Specifications: Sections 00 20 60, 00 51 00, 00 99 00 and 01 35 43, without the direct supervision of the Owner. For clarity, this is a labour and equipment based item. If all the man-days of this item are used up, the Contractor will not be responsible for completing unfinished work. Alternatively, if all the work is complete on Drawings: S-WR-001 and S-WR-002 and the man-days are not used up, additional work of the same nature will be assigned.
- .5 One (1) "man-day" is defined as eight (8) hours worked by one (1) crew member in a weekday (Monday – Friday). For example, a 3 man crew that worked 8 hours in a weekday would use 3 man-days of this item.
- .6 The crew is expected to work standard hours: 8 hours per day, Monday – Friday.
- .7 Demolition for replacement of timbers shall be done in accordance to Section 00 20 60.
- .8 Field cutting and treating shall be done in accordance to Section 00 99 00.

**END OF SECTION**

---

**1 OWNER SUPPLIED MATERIALS**

Owner supplied materials will be provided at an Owner specified laydown area on Site (to be determined after Contract Award). The following materials shall be supplied by the Owner:

**.1 Timber**

- .1 15 units of 34' long x 6" width x 12" length S4S creosote treated
- .2 10 units of 34' long x 12" width x 12" length S4S creosote treated
- .3 10 units of 22' long x 8" width x 12" length S4S creosote treated
- .4 30' long creosote treated piles (to be cut into stubs by the Contractor)

**.2 Hardware**

- .1 8 boxes (50lbs each) of 6" Lg. Galv. Ardox Nails
- .2 Various lengths of 3/4" Hex Bolts, Washers and Nuts for Brackets

**.3 Concrete & Rebar**

- .1 Bags of concrete mix
- .2 Pre-assembled rebar cages

**END OF SECTION**

## 1 COMMENCEMENT AND COMPLETION

- .1 Work shall commence upon **Contract Award**.
- .2 Site work shall commence no later than **October 15, 2016**.
- .3 All work including site clean-up and demobilization must be completed by **January 15, 2017**.

## 2 INSPECTION OF SITE

- .1 It is the responsibility of each bidder to obtain all necessary information pertaining to local site conditions and existing works, beyond the information provided in this Specification and accompanying drawing(s).

## 3 PERMITS, CERTIFICATES, LAWS AND ORDINANCES

- .1 The Contractor must, at his own expense, procure all permits, certificates and licenses required of him by law for the execution of his work under this contract. He shall comply with all Federal, Provincial or Municipal laws, ordinances or rules and regulations relating to the performance of his work and in force during the duration of this contract.
- .2 The Contractor is required to give all required notices, comply with all local, municipal, provincial, and federal laws, ordinances, codes, by-laws, rules and regulations relating to the work.
- .3 All work to be done in accordance with Work Safe BC regulations.
- .4 The Contractor shall comply with Federal and Provincial laws, orders and regulations concerning the control and abatement of water and air pollution.
- .5 The Contractor shall comply with the requirements of any local or other Noise By-Laws.

## 4 MINIMUM STANDARDS

- .1 In the absence of other standards specified in the Contract Documents, all work is to conform to, or exceed, the minimum standards of the Canadian Government Specifications Boards, the Canadian Standards Association, the American Society for Testing of Materials, or the National Building Code of Canada, whichever is applicable.
- .2 All work to be done in accordance with Work Safe BC regulations.

## 5 INTERFERENCE WITH OPERATION

- .1 The Contractor shall obey all navigation regulations and conduct operations so as to interfere as little as possible with the use of berthing spaces, fairways and passages. Install and maintain any and all protection to navigation as may be required by any properly constituted authority or by the Owner. During the course of construction and clean-up, do not dispose of surplus, waste or demolished materials in navigable waters.
- .2 The Contractor shall upon instruction of the Owner or Engineer, promptly remove any of the Contractor's equipment located outside the specified work area and obstructing any harbour operation.



**6 COMPLIANCE WITH STANDARD SPECIFICATIONS CODES AND REGULATIONS**

- .1 Unless expressly stated to the contrary, all materials, equipment and articles furnished by the Contractor shall comply with the applicable provisions of the standards of the Canadian Standards Association (CSA) or the Canadian Government Specification Board (CGSB) with the applicable provisions of the American Society for Testing Materials (ASTM), National Dredging Association (NFPA), American Concrete Institute (ACI) and the American Water Works Association (AWWA).
- .2 The Contractor shall follow all regulations in accordance with the Fisheries Act. Care shall be taken not to release any deleterious materials to fish habitat, into the water.
- .3 All work to be done in accordance with Work Safe BC regulations.

**7 CONTRACTOR'S PERSONNEL**

- .1 The Contractor's representative on Site shall be completely familiar with the method of work to be employed. Such personnel shall remain on Site for the duration of the work.

**8 RESPONSIBILITY TO PERSONNEL**

- .1 The Contractor shall have full responsibility for the board, lodging and transportation of his personnel and subcontractors. The cost for this shall be incorporated into his unit prices. He shall comply with all labor requirements, and Worker's Compensation regulations.

**9 BARRIERS, LIGHTS AND WATCHING**

- .1 The Contractor shall provide all requisite barriers, fences, warning signs, lights and watching for the protection of persons and property on or adjacent to the Site.

**10 SITE ACCESS**

- .1 The Contractor shall provide access to the work for the Owner's inspectors and surveyors as required.
- .2 General Site access shall be coordinated with the Owner.
- .3 The Contractor shall maintain routes of travel, with the Owner being the sole judge as to what may be deemed reasonable.
- .4 The Contractor shall erect and maintain barriers, fences, lights, warning devices, and other protective devices as may be required for prevention of theft or damage of goods and protection of the public and workmen, or if so ordered by the Owner.

**11 CONSTRUCTION AREA**

- .1 The Contractor shall regulate construction traffic on public areas and comply with all local ordinances in connection therewith, including load limitation and removal of debris.
- .2 The Contractor shall confine his operations on the Site to those areas actually required for the work including routes and regulations approved by the Owner for haulage of materials.

**12 NIGHT WORK**

- .1 The Contractor shall keep proper lights each night between the hours of sunset and sunrise upon all floating plants, false-work and other obstructions where necessary, and upon all buoys of such size and in such locations as required by a governing authority. When work is done at night, maintain from sunset to sunrise such lights on or about the work and plant as necessary for the proper observation of the work and the efficient prosecution thereof.

**13 CLEAN-UP**

- .1 At all times the Contractor shall keep the Site free from accumulation of waste material and debris and leave the Site clean and tidy on completion.

**14 TEMPORARY SERVICES**

- .1 On Site the Contractor shall make his own arrangements for supply of water and electricity.
- .2 The Contractor shall supply for his own use; sanitary, first aid, and all other temporary services and facilities required for the work.

**15 PROGRESS REPORT**

- .1 The Contractor shall keep a daily record of progress of the work available for inspection by the Engineer.
- .2 The daily record shall include particulars of weather conditions, number of men working, plant and equipment working and work performed.

**16 ENGINEER'S ACCESS**

- .1 The Contractor shall provide access to the work for the Engineer's inspectors and surveyors as required.

**17 PERMITS AND ROYALTIES**

- .1 Permits and licenses required for the Contractors work are the responsibility of the Contractor and shall be for the Contractor's account. The Contractor shall have the appropriate business license.

**18 PROTECTION OF EXISTING STRUCTURES**

- .1 Existing structures, adjacent marine facilities, roads, services, piping or equipment within the work area which are not to be replaced shall be properly protected from any injury or damage, direct or indirect. Any damage that is caused as a result of the operations of the Contractor shall be repaired and made good at the Contractor's expense to the satisfaction of the Engineer.

**19 WEATHER**

- .1 Time lost by the Contractor due to stoppage on account of adverse weather conditions may be allowed the Contractor, at the discretion of the Engineer, as an extension of time for the completion of the work over and above the date of completion specified in the contract agreement.

**20 SOIL DATA AND EXISTING TOPOGRAPHY**

- .1 The Contractor shall notify the Engineer of any subsurface conditions at the place of the work that may differ materially from those indicated in the Contract Documents.

**21 UTILITIES AND SERVICES**

- .1 The Contractor shall be responsible for any damage to overhead, underwater and/or underground utilities and/or services caused by the Contractor's operations and shall repair and make good the repairs at the Contractor's own expense.
- .2 The Contractor shall be responsible, unless otherwise agreed to by the Engineer, for all temporary or construction services and utilities, and first aid facilities.

**22 CARE OF FINISHED WORK**

- .1 The Contractor shall protect all finished work from injury, defacement, unauthorized entry, or trespass until such time as the work described in the Contract Documents is substantially complete.

**23 DISPOSAL**

- .1 All material designated to be replaced or removed will become the property of the Contractor and will be disposed of in an environmentally acceptable manner so that they neither become a menace to marine navigation nor a nuisance to the public on adjacent or any other property.
- .2 All replaced items, cut-offs and waste material shall be disposed by the Contractor in strict accordance with provincial, local, and municipal regulations and Part 8 of the National Building Code and with the Canadian Construction Safety Code.
- .3 Conduct clean-up and disposal operations to comply with local ordinances and antipollution laws.

**24 MATERIAL HANDLING AND STORAGE**

- .1 Any materials damaged by the Contractor during handling, transportation and storage shall be replaced at the Contractor's expense.

**25 CONSTRUCTION WORK SCHEDULE**

- .1 The Contractor shall work whatever shifts required in order to ensure the work meets regulatory windows and is completed by the completion date of the contract.
- .2 The Contractor shall normally perform all work within the hours of daylight except in instances where the Contractor has requested and received approval for shift changes from the Owner.
- .3 Within 7 days of award the Contractor is to supply a week by week schedule of proposed activities related to the contract.
- .4 The Contractor must notify the Owner immediately whenever a variation from the construction schedule is expected to occur or when the submission of the submittals will be delayed.

**26 SETTING OUT OF WORK**

- .1 The Contractor is expected to familiarize themselves with the Site, facilities and amenities within.
- .2 The Contractor shall not enter on nor occupy with men, tools, equipment or material, any ground outside the property of the Harbour Authority without the written consent of the party owning such ground. Other Contractors or employees or representatives of the Department may, for all necessary purposes, enter upon the work and premises used by the Contractor, and the Contractor shall conduct his work so as not to impede unnecessarily any work being done by others nor adjacent to the Site.

**27 AS-BUILT DRAWINGS**

- .1 The Contractor shall mark up one set of plans with any changes or amendments implemented during the Contract. These plans shall be submitted to the engineer before the Final Certificate of completion is issued.

**28 SITE SECURITY**

- .1 The Contractor is responsible for all materials and equipment either supplied by the Contractor, the Client Department, or the Owner. The Contractor is responsible for the repair and replacement of stolen or damaged items.

**29 SITEWORK**

- .1 All work shall be completed as per direction of on-site Owner or representative.
- .2 All heavy construction equipment shall be free of leaks and cleaned prior to construction.
- .3 The Contractor shall have absorbent pads on site in case of any oil leaks or contaminants entering the water.

**30 CO-OPERATION WITH HARBOUR AUTHORITY**

- .1 The Contractor shall give the Harbour Authority **minimum 1 week notice** for start of work.
- .2 The Contractor shall give the Harbour Authority **minimum 48 hours notice** for work that may interrupt harbour operations including access to floats.
- .3 The site shall be left in a safe condition at the completion of each work day.

**31 CONDITION OF STRUCTURE**

- .1 Existing structures, adjacent marine facilities, roads, and all other structures, services, piping or equipment within the work area shall be properly protected from any injury or damage, direct or indirect. Any damage that is caused as a result of the operations of the Contractor shall be repaired and made good at the Contractors expense to the satisfaction of the Owner.

**32 INSPECTION OF STRUCTURE**

- .1 The Owner or inspector, shall inspect the completed works. The Contractor shall be responsible for the costs of any re-inspections that may be required due to errors or omissions of the Contractor.

**END OF SECTION**

## **1 GENERAL**

This section refers to demolition specifications required as part of this Contract.

- .1 Where existing works are to be removed, they shall be removed and salvaged or disposed of to the satisfaction of the Engineer.
- .3 Demolition and disposal shall be carried out in strict accordance with provincial, local, and municipal regulations and Part 8 of the National Building Code and with the Canadian Construction Safety Code.

## **2 EQUIPMENT**

- .1 The Contractor shall furnish all labour, materials, tools, plant and services required incidental to the completion to the full extent of the drawings and specifications for execution of all demolition salvage and protection work specified herein.
- .2 Demonstrate that tools and machinery are being used in manner which allows for salvage of materials in best condition possible or reinstatement of temporarily relocated structures.

## **3 REMOVAL OF DEMOLISHED MATERIAL**

- .1 All materials, which are not to be salvaged for the Owner, shall become the Contractor's property and the Contractor must remove it from the work site.
- .2 If not specifically identified, the Engineer shall decide as to which material shall be salvaged and which materials shall be disposed of.

## **4 SALVAGED MATERIAL**

- .1 Material to be salvaged for the Owner shall be stored as directed by the Engineer.
- .2 Remove items to be reused, stockpile and re-install as directed by Engineer.
- .3 Designate appropriate security resources/measures to prevent vandalism, damage and theft of salvaged items.
- .4 Contractor is responsible for lost, stolen or damaged materials.

## **5 PROTECTION OF STRUCTURES TO REMAIN**

- .1 Protect remaining structural elements, services and equipment against damage from demolition works.
- .2 Contractor is liable for any damage caused to structures not specified for removal as a result of completing work.

## **6 SERVICES**

- .1 All services that must be removed from existing structures in order to perform work must be removed so as not to damage them.

- 
- .2 All service materials including miscellaneous hangers, fasteners and supplies required to reinstall the services shall be supplied by the Contractor and will be of equivalent quality to the new conditions of such materials being replaced.
  - .3 All materials that are not reusable shall be disposed of by the Contractor.
  - .4 The Contractor shall be responsible for the handling and storage of services lines, lamps standards and other equipment during construction. All materials damaged by the Contractor shall be replaced at the Contractor's expense.

## **7 CLEANING AND RESTORATION**

- .1 Keep site clean and organized throughout demolition procedure.
- .2 Upon completion of project or as appropriate, reinstate gangway, floats, walkways, light standards, electrical and water services and other items affected by Work to condition which existed prior to beginning of Work.

**END OF SECTION**

## 1 GENERAL

This section refers to steel specifications required as part of this Contract.

### .1 Reference Standards

Unless specified otherwise, all steel shall be new and conform to the current edition of the following standards:

- .1 CSA B-111-M: Wire nails, spikes and staples
- .2 CSA-G164-M: Hot dip galvanizing of irregularly shaped articles
- .3 CSA-G40.21-M81: Drift bolts, machine bolts, washers, and miscellaneous iron
- .4 ASTM A307: Specification of carbon steel bolts and studs
- .5 ASTM A153: Hot dipped galvanizing
- .6 CSA B34: Lag screws

## 2 PRODUCTS

### .1 Steel Hardware

- .1 Bolts, nuts, and washers through timber shall conform to ASTM A307.
- .2 Drift pins shall conform to CSA G40.21-M81 Grade 260W.
- .3 All spikes, nails, and staples to conform to CSA B-111-M.
- .4 All lag screws to conform to CSA B34.
- .5 Hot-dip galvanize all miscellaneous metal and fasteners in accordance with CSA G164-M, unless noted otherwise.
- .6 Unless noted otherwise, use plate washers under heads and nuts of all bolts bearing on timber; plate washers against piles shall be curved to match the rounded surface.
- .7 All bolts shall be National Course Thread, unless shown otherwise.
- .8 Unless noted otherwise, all bolts shall have minimum 152mm (6") of thread.
- .9 All hardware including, but not limited to, bolts, drift bolts, spikes, carriage bolts, lag bolts, nuts and washers shall be hot dipped galvanized in accordance with the ASTM A153. Galvanize to 610gm/m<sup>3</sup> (2oz/ft<sup>2</sup>).

### .2 Fabrication Steel

- .1 Items manufactured or fabricated from scrap steel of unknown chemical or physical properties are not acceptable.
- .2 All fabrication steel such as brackets shall be galvanized in accordance to CSA G164-M.



### 3 EXECUTION

#### .1 Assembly

- .1 All bolts shall be tightened to 100 newton meters (80 lbs feet).
- .2 Care shall be taken not to damage the treated wood finish. All treatment damaged by the Contractor shall be repaired at his own expense.
- .3 Predrill all timbers that require bolting (hex or lag) and end timbers that require nails prior to installation to prevent splitting.
- .4 Holes for machine bolts shall be bored to provide a driving fit.
- .5 All field drilled holes shall be treated with preservative as specified prior to bolting.

#### .2 Decking

- .1 Lay boards heart side down, spaced 6mm to 10mm apart.
- .2 Secure each contact point with 2 – 152mm galvanized RDOX nails.
- .3 Pre-drill deck boards for nails nearest to both board ends.

#### .3 Stub Piles

- .1 Stub Piles shall be secured in accordance to S-WR-003.

#### .4 Stringers

- .1 Stringers shall be secured using 3/4" dia. x 20" long galv. drift pins.

#### .5 Caps/Subcaps/Corbels

- .1 Caps/subcaps/corbels shall be secured using 1" dia. x 20" long galv. drift pins.

**END OF SECTION**

## 1 GENERAL

This section refers to timber specifications required as part of this Contract.

### .1 Reference Standards

Unless specified otherwise, timber shall conform to the following standards:

- .1 American Wood Preservers' Association (AWPA)
  - .1 AWPA M2, Standard for Inspection of Wood Products Treated with Preservatives.
  - .2 AWPA M4, Standard for the Care of Preservative Treated Wood Products.
- .2 ASTM International
  - .1 ASTM A153M-09, Standard Specification for Zinc Coating (Hot Dip) on Iron and Steel Hardware.
  - .2 ASTM A307-14, Standard Specification for Carbon Steel Bolts, Studs and Threaded Rod, 60,000 PSI Tensile Strength.
  - .3 ASTM D256-10, Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics
  - .4 ASTM D638-10, Standard Test Method for Tensile Properties of Plastics
  - .5 ASTM D790-10, Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials
- .3 CSA International
  - .1 CSA B111-03, Wire Nails, Spikes and Staples. (Note: This standard is actually discontinued but there is no equivalent replacement – consequently have chosen to make reference to the old version.)
  - .2 CSA O80 Series-12, Wood Preservation.
  - .3 CSA O86-09 Consolidated – Engineering Design in Wood
  - .4 CAN/CSA Z809-13, Sustainable Forest Management.
  - .5 CAN/CSA G164-03, Hot Dip Galvanizing of Irregularly Shaped Articles.
- .4 Health Canada / Workplace Hazardous Materials Information System (WHMIS)
  - .1 Material Safety Data Sheets (MSDS).
- .5 National Lumber Grades Authority (NLGA)
  - .1 Standard Grading Rules for Canadian Lumber 2014.

**.2 Protection**

- .1 Deliver, store and handle materials in a manner that protects products from damage. Replace damaged or defective materials with new products conforming to the requirements of this section.

**2 PRODUCTS****.1 General**

- .1 Except as otherwise noted, only new materials will be used in, and remain an integral part of the structures.
- .2 The Engineer may inspect materials and products at his discretion at all stages of their manufacture, and transportation to the Site. Satisfactory inspection at any stage does not preclude future rejection if the materials or products are subsequently found to lack uniformity or fail to conform to the requirements specified. Acceptance will not be made until the materials or products are satisfactorily installed in the completed structures as specified.
3. Salvaged materials deemed to be reusable shall remain property of the Owner, unless specified otherwise.

**.2 Timber**

- .1 All timber shall be suitable for the purpose intended and shall conform to the Standard Grading Rules for Canadian Lumber, (NLGA), of the Canadian Lumber Standards Administration Board, and shall be No. 1 Structural Grade Coast Douglas Fir unless otherwise specified.
- .2 The Contractor shall supply to the Engineer documentation indicating the grade class and species of all timber delivered to the site.
- .3 Timber for stringers, risers and tie rails, fascia and rub boards shall be provided surfaced four sides (S4S). Timber for decking shall be provided surfaced one face (S1F).
- .4 The Engineer shall be the sole judge as to the acceptability of timber incorporated into the work. Timber not accepted by the Engineer shall be removed from the site.

**.3 Treatment of Material****.1 General**

- .1 All timber shall be pressure preservative treated in accordance with CSA-O80-M 'Wood Preservation', its applicable subsections and amendments. The use category to which timber elements will be exposed is UC5A (Marine (salt water) applications).
- .2 The contractor shall provide certification that the specified treatment retention has been achieved.
- .3 Preservative treatment of timber shall be undertaken in compliance with the latest revision of the 'Best Management Practices (BMP's) for the Use of Treated Wood in Aquatic Environments', as published by The

Canadian Institute of Treated Wood and the Western Wood Preservers Institute. The Contractor shall provide assurance to the Engineer that preservative treatment has been undertaken in accordance with these BMP's.

**.2 Creosote-treated Materials:**

- .1 All joists, stringers, lower stringer splice blocks, crossties, well blocking, flanges, flange splice blocks (upper and lower), caps, subcaps and corbels shall be creosote treated.
- .2 All creosote treated materials will have a minimum retention of 225kg per cubic meter (14lb. per cubic foot).

**.3 Salt-treated Materials:**

- .1 All decking, guards, bull rails, risers, rub boards and upper stringer splice blocks shall be treated ACZA treated.
- .2 All timber specified to be treated with water-home salts will be treated in accordance with CSA-080-M, "Wood Preservation", and its applicable subsections and amendments, for materials in contact with ground or water. Only non-leachable ACA salts will be accepted.
- .3 All salt-treated timber will have a minimum retention of 6.4 kg/m<sup>3</sup> (0.40 lb. per cubic foot) and a depth of penetration of 10mm as specified in CSA 080.14.

**3 EXECUTION**

**.1 Field Treating**

- .1 Creosote treated timber members that have fresh cut surfaces exposed in the structure shall be treated with two coats of hot creosote oil. All cuts or breaks in the surfaces of creosote treated timber shall be treated with two separate coats of hot creosote oil. Where bolt holes must be bored through creosote treated piles, the holes shall be filled with hot creosote oil and the bolts shall be dipped in hot creosote oil before the bolts are placed. Other alternative field wood treatment should be approved by the Engineer before application. Ensure the creosote or other preservatives are properly stored and protected in case of spillage (ie: place in tray).
- .2 For pile completion, treat all end cut offs and field drilled holes with creosote preservative. Apply two coats of hot creosote to top of dry pile, allowing as much creosote to soak in as possible. Apply a coat of coal tar pitch or mastic after creosote application.
- .3 All salt treated members that are modified (cut or drilled) shall be field treated with two coats of Copper Naphthenate or pentachlorophenol. When field treating by brushing, spraying, dipping or soaking do so in such a manner that the preservative does not drip into the water or onto the ground. Ensure the creosote or other preservatives are properly stored and protected in case of spillage. (ie: place in tray)

**.2 Handling of Materials**

- .1 Treated material will not be accepted if damaged in any manner in handling. This includes damage from strapping and slings.
- .2 The Contractor shall be responsible to repair or replace all materials damaged by his handling, storage and installation of materials.

**.3 Shimming**

- .1 Contractor will submit a proposed construction method to the Engineer prior to construction.
- .2 All shims shall be UHMW and properly sized to create even bearing loading.

**.4 Existing Structures**

- .1 Any structures damaged by the Contractor during the works shall be repaired and made good at the Contractor's expense to the satisfaction of the Engineer.

**.5 Services**

- .1 All services that must be removed from existing structures in order to perform work must be removed so as not to damage them.
- .2 All service materials misc. hangers, fasteners and supplies required to reinstall the services shall be supplied by the Contractor.
- .3 All materials that are not reusable shall be disposed of by the Contractor.
- .4 The Contractor shall be responsible for the handling and storage of the service lines, lamp standards and other equipment during construction. All materials damaged by the Contractor shall be replaced at the Contractor's expense.

**.6 Patching and Repairs**

- .1 All unused bolt holes or damaged areas of creosote treatment shall be patched with creosote treated dowels, mastic, ships felt and copper patches as specified.

**.7 Painting**

- .1 Timber specified to be painted will receive one brushed undercoat. After 48 hours, two brushed finish coats of 2-part urethane paint will be applied with a minimum of 48 hours between finish coats. Paint will be applied to clean, dry surfaces only.
- .2 Provide paint specifications to Owner to be approved before construction.
- .3 Paint colours will match the following:
  - .1 "Signal Red"
  - .2 "Safety Yellow"

**END OF SECTION**

## 1 GENERAL

### .1 Related Requirements

.1 Not used.

### .2 References

.1 Definitions:

.1 Environmental Pollution and Damage: presence of chemical, physical, biological elements or agents which adversely affect human health and welfare; unfavourably alter ecological balances of importance to human life; affect other species of importance to humans; or degrade environment aesthetically, culturally and/or historically.

.2 Environmental Protection: prevention/control of pollution and habitat or environment disruption during construction.

### .3 In Water Works

.1 Construction equipment to be operated on land or from floating barge equipment.

.2 Waterways to be kept free of excavated fill, waste material and debris.

### .4 Notification

.1 Engineer will notify Contractor in writing of observed noncompliance with Federal, Provincial or Municipal environmental laws or regulations, permits, and other elements of Contractor's Environmental Protection plan.

.2 Contractor: after receipt of such notice, Engineer of proposed corrective action and take such action for approval by Engineer.

.1 Take action only after receipt of written approval by Engineer.

.3 Engineer will issue stop order of work until satisfactory corrective action has been taken.

.4 No time extensions granted or equitable adjustments allowed to Contractor for such suspensions.

## 2 PRODUCTS

### .1 Not Used

.1 Not Used.

---

**3 EXECUTION****.1 Cleaning**

- .1 Leave work area clean at end of each day.
- .2 Ensure public waterways, storm and sanitary sewers remain free of waste and volatile materials.
- .3 Final Cleaning: upon completion remove surplus materials, rubbish, tools and equipment to the approval of the Owner.

**END OF SECTION**

## 1 GENERAL

Health and safety requirements are mandatory to ensure that Small Craft Harbours shows due diligence towards health and safety on construction sites.

## 2 REFERENCES

Unless specified otherwise, Health and Safety Requirements shall conform to the current edition of the following standards:

- .1 Government of Canada  
Canada Labour Code, Part II  
Canada Occupational Health and Safety Regulations.
- .2 National Building Code of Canada (NBC):  
Part 8, Safety Measures at Construction and Demolition Sites.
- .3 Canadian Standards Association (CSA):  
CSA S269, Falsework for Construction Purposes.  
CSA S269.2, Access Scaffolding for Construction Purposes.  
CSA-S350, Code of Practice for Safety in Demolition of Structures.
- .4 Fire Protection Engineering Services, HRSDC:  
FCC No. 301, Standard for Construction Operations.  
FCC No. 302, Standard for Welding and Cutting.  
HRSDC website:  
[http://www.hrsdc.gc.ca/eng/labour/fire\\_protection/policies\\_standards/commissioner/index.shtml](http://www.hrsdc.gc.ca/eng/labour/fire_protection/policies_standards/commissioner/index.shtml)
- .5 American National Standards Institute (ANSI):  
ANSI A10.3, Operations – Safety Requirements for Powder-Actuated Fastening Systems.
- .6 Province of British Columbia:  
Workers Compensation Act. Part 3 Occupational Health and Safety.  
Occupational Health and Safety Regulation
- .7 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
  - .1 Material Safety Data Sheets (MSDS).

## 3 GENERAL CONDITIONS

- .1 Provide safety barricades around work site as required to provide a safe working environment for workers and protection for pedestrian traffic.
- .2 Ensure that non-authorized persons are not allowed to circulate in designated construction areas of the work site.
- .3 Provide appropriate means by use of barricades, fences, and warning signs as required.
- .4 Secure site at night time as deemed necessary to protect site against entry.
- .5 Mark floating equipment with lights in accordance with International Rules of Road and maintain radio watch on board.
- .6 Place and maintain buoys, markers and lights required to define work and disposal areas.



---

#### **4 RESPONSIBILITY**

- .1 Assume responsibility as the Prime Contractor under this Contract.
- .2 Be responsible for health and safety of persons on site, safety of property on site and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
- .3 Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial and local statutes, regulations, and ordinances, and with site-specific Health and Safety Plan.

#### **5 GENERAL REQUIREMENTS**

- .1 Comply with specified codes, acts, bylaws, standards and regulations to ensure safe operations at site.
- .2 In event of conflict between any provision of the above authorities, the most stringent provision will apply. Should a dispute arise in determining the most stringent requirement, the Departmental Representative will advise on the course of action to be followed.
- .3 Mark floating equipment with lights in accordance with requirements and directives of Queen's Harbour Master.
- .4 Develop written site-specific Health and Safety Plan based on hazard assessment prior to beginning site Work and continue to implement, maintain, and enforce plan until final demobilization from site. Health and Safety Plan must address project specifications.
- .5 Departmental Representative may respond in writing, where deficiencies or concerns are noted and may request re-submission with correction of deficiencies or concerns

#### **6 COMPLIANCE REQUIREMENTS**

- .1 Comply with Workers Compensation Act, B.C.
- .2 Comply with Occupational Health and Safety Regulations.
- .3 Comply with Canada Labour Code, Canada Occupational Safety and Health Regulations.
- .4 Small Craft Harbours may terminate the Contract without liability to Small Craft Harbours where the Contractor, in the opinion of Small Craft Harbours, refuses to comply with a requirement of the Workers' Compensation Act or the Occupational Health and Safety Regulations.
- .5 It is the Contractor's responsibility to ensure that all workers are qualified, competent and certified to perform the work as required by the Workers' Compensation Act or the Occupational Health and Safety Regulations.

#### **7 WORKER'S COMPENSATION BOARD COVERAGE**

- .1 Comply fully with the Workers' Compensation Act, regulations and orders made pursuant thereto, and any amendments up to the completion of the work.
- .2 Maintain Workers' Compensation Board coverage during the term of the Contract, until and including the date that the Certificate of Final Completion is issued.

---

**8 SUBMITTALS**

- .1 Submit site-specific Health and Safety Plan: Within 7 days after date of Notice to Proceed and prior to commencement of Work. Health and Safety Plan must include:
  - .1 Results of site specific safety hazard assessment.
  - .2 Results of safety and health risk or hazard analysis for site tasks and operation found in work plan.
  - .3 Risk Management and Safety Procedure for possible events including but not limited to storm, fire, and fall.
- .2 Submit one copy of Contractor's authorized representative's work site health and safety inspection reports to Departmental Representative weekly.
- .3 Submit copies of reports or directions issued by Federal, Provincial and Territorial health and safety inspectors.
- .4 Submit copies of incident and accident reports.
- .5 Submit WHMIS MSDS - Material Safety Data Sheets if requested.
- .6 Departmental Representative may review Contractor's site-specific Health and Safety Plan and provide comments to Contractor within 5 days after receipt of plan. Revise plan as appropriate and resubmit plan to Departmental Representative within 5 days after receipt of comments from Departmental Representative.
- .7 Departmental Representative review of Contractor's final Health and Safety plan should not be construed as approval and does not reduce the Contractor's overall responsibility for construction Health and Safety.
- .8 Medical Surveillance: where prescribed by legislation, regulation or safety program, submit certification of medical surveillance for site personnel prior to commencement of Work, and submit additional certifications for any new site personnel to Departmental Representative.
- .9 On-site Contingency and Emergency Response Plan: address standard operating procedures to be implemented during emergency situations.

**9 FILING OF NOTICE**

- .1 File Notice of Project with Provincial authorities prior to beginning of Work.

**10 SAFETY ASSESSMENT**

- .1 Perform site specific safety hazard assessment related to project.

**11 MEETINGS**

- .1 Schedule and administer Health and Safety meeting prior to commencement of Work.

**12 PROJECT/SITE CONDITIONS**

- .1 Work at site will involve contact with:

- .2 Harbour Manager.
- .3 Departmental Representative.

### **13 UNFORSEEN HAZARDS**

- .1 When unforeseen or peculiar safety-related factor, hazard, or condition occur during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction and advise Departmental Representative verbally and in writing.

### **14 HEALTH AND SAFETY CO-ORDINATOR**

- .1 Employ and assign to Work, competent and authorized representative as Health and Safety Co-ordinator. Health and Safety Co-ordinator must:
  - .1 Have site-related working experience specific to activities associated with the repairs.
  - .2 Have working knowledge of occupational safety and health regulations.
  - .3 Be responsible for completing Contractor's Health and Safety Training Sessions and ensuring that personnel not successfully completing required training are not permitted to enter site to perform Work.
  - .4 Be responsible for implementing, enforcing daily and monitoring site-specific Contractor's Health and Safety Plan.
  - .5 Be on site during execution of Work.

### **15 POSTING OF DOCUMENTS**

- .1 Ensure applicable items, articles, notices and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province having jurisdiction, and in consultation with Departmental Representative.

### **16 CORRECTION OF NON-COMPLIANCE**

- .1 Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Departmental Representative.
- .2 Provide Departmental Representative with written report of action taken to correct non-compliance of health and safety issues identified.
- .3 Departmental Representative may stop Work if non-compliance of health and safety regulations is not corrected.

### **17 WORK STOPPAGE**

- .1 Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations for Work.

**END OF SECTION**