

Cape Spear Lightstation
Remediation/Risk Management
Cape Spear, NL

2016-08-20

PART 1 GENERAL

1.1 RELATED SECTIONS

- .1 Section 01 33 00 - Submittal Procedures.

1.2 REFERENCES

- .1 American Wood-Preservers' Association (AWPA)
- .1 AWPA M2, Standard Inspection of Treated Wood Products.
- .2 AWPA M4, Standard for the Care of Preservative-Treated Wood Products.
- .2 Canadian Standards Association (CSA)
- .1 CSA O80 Series, Wood Preservation.

1.3 CERTIFICATES

- .1 For products treated with preservative, fire-retardant by pressure impregnation submit following information certified by authorized signing officer of treatment plant:
- .1 Information listed in AWPA M2 and revisions specified in CSA O80 Series, Supplementary Requirement to AWPA M2 applicable to specified treatment.
- .2 Moisture content after drying following treatment with water-borne preservative, fire-retardant.
- .3 Acceptable types of paint, stain, and clear finishes that may be used over treated materials to be finished after treatment.

1.4 WASTE MANAGEMENT AND DISPOSAL

- .1 Do not dispose of preservative treated wood through incineration.
- .2 Do not dispose of preservative treated wood with other materials destined for recycling or reuse.
- .3 Dispose of treated wood, end pieces, wood scraps and sawdust at sanitary landfill approved by Owner's Representative.
- .4 Dispose of unused wood preservative material at official hazardous material collections site approved by Owner's Representative.

Cape Spear Lightstation
Remediation/Risk Management
Cape Spear, NL

2016-08-20

- .5 Do not dispose of unused preservative material into sewer system, into streams, lakes, onto ground or in other location where they will pose health or environmental hazard.

PART 2 PRODUCTS

2.1 MATERIALS

- .1 Preservative: to CAN/CSA-080 Series, stained finish.

PART 3 EXECUTION

3.1 APPLICATION: PRESERVATIVE

- .1 Treat lumber to CAN/CSA- 080 Series.
- .2 Following water-borne preservative treatment, dry material to maximum moisture content of 19%.

3.2 APPLICATION: FIELD TREATMENT

- .1 Comply with AWPA M4 and revisions specified in CAN/CSA-080 Series, Supplementary Requirements to AWPA Standard M2.
- .2 Treat all field cuts with two (2) coats of clear copper naphthenate or 5% pentachlorophenol solution, water repellent preservative.
- .3 Remove chemical deposits on treated wood to receive applied finish.