



- NOTES:
- 1- WIRE COLOUR - RED - NEGATIVE, YELLOW - POSITIVE
 - 2- TWO MAGNETIC PICK-UPS WITH 3 WIRES ARE REQUIRED ON ENGINES FOR BURRARD YARROW. FOR ALL OTHER ENG'S INSTALL ON MAGNETIC PICK-UP-2 WIRES
 - 3- CONNECTION TO EGB-ACTUATOR.
WIRE 214 - PLUG - J - CABLE - BROWN - SHUT DOWN SOLENOID
WIRE 215 - PLUG - I - CABLE - YELLOW - SHUT DOWN SOLENOID
WIRE 216 - PLUG - A - CABLE - PINK - TRANSDUCER
WIRE 217 - PLUG - B - CABLE - VIOLET - TRANSDUCER
 - 4- USE #20 WIRE FOR EXHAUST CYLINDER THERMOCOUPLES.
USE #12 WIRE FOR PRE-LUBE PUMP
USE #14 HI-TEMP (TYPE TFE) FOR JACKET WATER HEATERS
USE #14 WIRE (900-133009-998) FOR ALL REMAINING DEVICES, EXCEPT THOSE DEVICES SHOWN WIRED WITH MULTI-CONDUCTOR CABLE ON THE CONDUIT ROUTING ARRET.

Rev	Drawn	Description	Rev	Drawn	Description	Rev	Drawn	Description	Rev	Drawn	Description	Rev	Drawn	Description	Rev	Drawn	Description
1			1			1			1			1			1		
2			2			2			2			2			2		
3			3			3			3			3			3		
4			4			4			4			4			4		
5			5			5			5			5			5		
6			6			6			6			6			6		
7			7			7			7			7			7		
8			8			8			8			8			8		

PROJECTION

TO DECCA ISIS

TO TEMP. INDICATORS ON ENGINE CONTROL PNL.

7-5616

100 NAVAIDS VESSELS

C34-037316