



<b>T1</b>	Plastic Laminate Pattern: Wood grain Colour: Brown Oak
<b>L2</b>	Plastic Laminate Pattern: Small textured circle pattern Colour: Green/Beige
<b>L3</b>	Plastic Laminate Colour: Satin Brushed Aluminium
<b>L4</b>	Plastic Laminate Colour: Sculpted White
<b>L5</b>	Plastic Laminate Colour: Beige Granite
<b>F1</b>	Window Film (Magic Leaf pattern) Departmental Representative to provide EPS file for film design. Refer to 24/10/10 for design.
<b>F2</b>	Window Film (Safety) None Scratchy film to be fastened to window frame

P1	Paint - General (White) Colour: White Finish: Gloss level 3
P2	Paint - Accent (Light Gray) Colour: Gray Finish: Gloss level 3
P3	Paint - Accent (Blue) Colour: Blue Finish: Gloss level 3
P4	Paint - Doors (Dark Gray) Colour: Dark Gray Finish: Gloss level 6
P5	Paint - Ceiling (White) Colour: White Finish: Gloss level 1
P6	Paint - Corridor (Gray) Colour: Purple/Gray Finish: Gloss level 3
G1	Back Painted Glass (Corridor) Finish: 12mm, low iron, tempered Colour: Back painted white

1. Contractor to ensure all surfaces under countertop/worksurface are sand smooth to prevent harm to cabinet.
2. Refer to Partition Plan on D404 for plywood block location within partition cavity.
3. Countertops to be 16mm plywood, finished with plastic laminate, unless otherwise noted.
4. Cabinets to be 16mm high density particle board, finished with plastic laminate, unless otherwise noted.
5. Shelves to be 16mm high density particle board.
6. Interior surfaces of closed cabinets, drawers and adjustable shelves to be finished with standard white melamine.
7. It is the Contractor's responsibility to provide hardware connection to all equipment supplied/installed by Others, including any electrical and/or plumbing.
8. Refer to Mechanical Drawings for connection of plumbing fixtures and equipment.
9. Refer to Plan Details and Elevations for countertop material joint/beam locations.
10. Contractor to finish edge of tiles with brushed stainless steel square edge trim.  
Notes:
  - Thickness of trim to suit application
11. Open shelving to be finished with plastic laminate all exposed faces.
12. Additional blocking to be provided in partition cavity as required to support milkwork.
13. Supply of equipment including: Refrigerators, Microwave Ovens, Coffee Machines, Photocopiers, Fax Machines, Cash Registers and Printers, is by Departmental Representative.

1. Cabinet hinges to be concealed and self-closing.
2. Drawers to be installed on full extension heavy duty gliders c/w built in stoppers.
3. Adjustable shelves to be installed on stainless steel pilaster c/w support clips recessed within gable and cut to suit interior cabinet height.
4. Supply and install ladder door pulls:  
Length: 208mm  
Finish: Stainless steel

- 1 Supply and install new water closet. Refer to Mechanical Drawings.
- 2 Supply and install new lever faucet. Refer to Mechanical Drawings.
- 3 Supply and install new wall hung sink. Refer to Mechanical Drawings.
- 4 Supply and install new wall mounted toilet. Refer to Mechanical Drawings.
  - Supply and install new floor mounted toilet partition.
  - Ambulatory stall door requirements as follows:
    - Capable of being latched from the inside with a mechanism that is operable using a closed fist.
    - When the door is in an open position have a clear opening of at least 810mm for the ambulatory stall.
    - Provided with a spring type or gravity hinge in order for the door to close automatically.
    - Provided with a door pull on both sides of the door, near the latch side of the door, located at a height not less than 900 mm and not more than 1100 mm A.F.F.
    - Custom: Ambulatory door material, grab bar reinforced panels
  - Size dimension required.
- 5 Supply and install new stainless steel L-shaped grab bar.
  - Length: 760mm long horizontal and vertical components
  - Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition.
  - Finish: Slip resistant metal surface
  - Provide reinforced partition to stall. Resistance load of at least 1.3KN applied vertically or horizontally.
- 7 Supply and install new stainless steel 600mm long grab bar.
  - Length: 600mm
  - Specification: Grab bar to be 35mm Min. - 40mm Max. dia. and have a fascia of 40mm clearance from partition.
  - Finish: Slip resistant metal surface
  - Provide reinforced partition to stall. Resistance load of at least 1.3KN applied vertically or horizontally.
- 8 Supply and install new toilet tissue dispenser. Mounting height: 600mm - 800mm A.F.F.
- 9 Supply and install new paper towel dispenser. Mounting height: 1100mm A.F.F.
- 10 Supply and install new surface mounted paper towel dispenser. Mounting height: 1200mm A.F.F.
- 11 Supply and install new surface mounted garbage disposal. Mounting height: 900mm A.F.F.
- 12 Supply and install surface mounted sanitary napkin disposal. Mounting height: 900mm A.F.F.
- 13 Supply and install new wall mount coat hook.
  - Color Brushed metal
  - Mounting height: Mounted not more than 1200mm A.F.F. on a side partition and projecting not more than 40mm from partition fascia.
- 14 Supply and install new mirror. Mounting height: 1000mm A.F.F.
- 15 Supply and install wall mounted shelf.
  - Size: 200mm x 400mm
  - Shelf to be located not more than 200mm above the top of the lavatory and not more than 1100mm A.F.F. and mounted not more than 200mm from the wall.

